

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
19 February 2004 (19.02.2004)

PCT

(10) International Publication Number
WO 2004/014209 A1

(51) International Patent Classification⁷: **A47L 5/28**,
9/22, 9/12, 9/30, 9/00

Stephen, Benjamin [GB/GB]; 20 Kensington Place, Bath,
Bath and South East Somerset BA1 6AP (GB).

(21) International Application Number:
PCT/GB2003/003132

(74) Agents: **HUCKER, Nerys** et al.; Intellectual Property De-
partment, Dyson Limited, Tetbury Hill, Malmesbury, Wilt-
shire SN16 0RP (GB).

(22) International Filing Date: 18 July 2003 (18.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0218426.5 9 August 2002 (09.08.2002) GB

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(71) Applicant (*for all designated States except US*): **DYSON
LTD** [GB/GB]; Tetbury Hill, Malmesbury, Wiltshire SN16
0RP (GB).


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): **COURTNEY,**

[Continued on next page]

(54) Title: SURFACE TREATING APPLIANCE



(57) Abstract: A surface treating appliance (200), such as a vac-
uum cleaner, comprises a main body (210), a surface treating
head (230) and a support assembly (220). The support assembly
is rollably mounted to the main body (210) for allowing the main
body (210) to be rolled along a surface. The support assembly
(220) also houses a component of the appliance, such as a motor
for driving a surface-agitating device. Alternatively, or addition-
ally, the support assembly may accommodate a fluid inlet (531)
for receiving fluid flow, a fluid outlet (535) for exhausting fluid
and means for acting on the fluid flow received by the inlet, such
as a filter or suction apparatus.

WO 2004/014209 A1



SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*