

TITLE: IMPROVED DISINFECTION

TECHNICAL FIELD

The invention relates to the field of disinfection.

BACKGROUND

5 The disinfection of surfaces, for example of skin, non-autoclavable medical instruments, hospital wards, operating theatres, walls, hand rails, air conditioning ducts and the like remains one of the most problematic areas of infection control.

 The majority of disinfection methods rely on direct contact of the surface to be disinfected with a liquid disinfectant. These methods require considerable quantities of liquid disinfectants to ensure that all areas of the treated surface are covered with the disinfectant. Usually the disinfectant is applied either as a liquid or a spray. Commonly the amount of disinfectant used is 100-100,000 times more than required to kill the microorganisms present on the surface. For example, 10^{-5} (0.00001)g of iodine is sufficient to kill all bacteria on a surface area of 1 m^2 with a contamination level of 10^5 cfu/cm² in 10 minutes (Block, S.S., Disinfection, Sterilisation and Preservation, 3rd Edition, p.183) whilst the recommended amount of disinfectant would contain 0.1-0.2 g (10,000 times the level) of iodine. Such a high usage creates a series of problems with respect to cost, occupational safety and environmental impact.

 Another problem associated with the traditional methods of contacting surfaces with liquid disinfectants is that of human toxicity. The use of disinfecting fluids which can be safely and conveniently handled by humans requires that the active disinfecting agents are typically present at low concentrations, resulting in unacceptably long contact times to achieve the required levels of disinfection.

- 2 -

For example, a commonly used aqueous disinfecting solution, containing 2% glutaraldehyde, requires soaking times of around 6 to 10 hours to achieve total kill.

Further problems may also be encountered when liquid disinfectants are applied to common surfaces, like walls, hand rails, air conditioning ducts and some bulky medical instruments. Apart from the stated practical difficulties in covering such surfaces with an even layer of the disinfectant, the surfaces usually contain minute cracks, crevices, and pores which can harbour bacteria. As the surface tension of most liquid disinfectants is relatively high, such areas are not penetrated and remain contaminated even after prolonged disinfection cycles.

One solution to the problem is the use of disinfectants in the gaseous phase which addresses the problem of access to cracks, crevices and pores. The small particle size of gaseous disinfectants creates another problem; the concentrations of the active biocidal chemicals need to be very high or the chemicals required are toxic and dangerous to handle. Several methods employing disinfectants in the gaseous phase have been developed. The most common utilise either ethylene oxide and its analogues, or formaldehyde. Both compounds are extremely toxic, and have been identified as primary carcinogens. In addition, sterilising with the above gases requires a thorough control of pressure and humidity in the chamber, which necessitates the use of complex and expensive equipment. Thus, their use is limited to hospitals and critical medical instruments and requires careful supervision.

Another approach is used in a variety of plasma disinfecting methods. In these methods disinfection under essentially dry conditions is achieved using various active radicals and ions as the biocide. These can be formed from conventional disinfectants (as precursors) under plasma forming conditions. In addition to the cost and complexity of

- 3 -

plasma equipment, these methods tend to result in degradation of many construction materials such as are used in endoscopes and other instruments. Obviously, plasma methods can not be used for bulky equipment and large surfaces.

An area of particular difficulty is in the field of dentistry and dental prosthetics.

5 The invention will be described herein with particular reference to its use in that field but it will be understood not to be limited to that use.

Dental personnel are exposed to a wide variety of pathogens in the blood and saliva of patients. These pathogens can cause infections such as the common cold, pneumonia, tuberculosis, herpes, viral hepatitis and HIV.

10 A particular problem occurs when contaminated dental impressions taken from patients' mouths are used to make dental casts. In these circumstances, microorganisms from the impression material are transferred to the cast. This infected cast can, in turn, contaminate the pumice pans and polishing wheels which are used in shaping the casts for manufacturing prosthetic devices. This shaping procedure, in turn, produces an
15 atmosphere of infectious dust which is potentially harmful. The polishing of dentures with a common pumice pan and polishing wheel can lead to cross-contamination between patients.

Disinfection of the impressions and casts has been recommended as a method of preventing the transfer of infection in the field of dental prosthetics. The most commonly
20 used impression materials are alginate-based. Alginates tend to swell on soaking in aqueous solutions, thus reducing the accuracy of the subsequently derived casting and ultimately, resulting in an unsuitable prosthetic device.

To overcome the immersion of alginates into bulk liquids, a number of researchers recommend using spray atomised disinfectants generated by manual spray pumps.

When spray atomised disinfectants are used, a considerably smaller amount of liquid is brought into contact with the impression than is the case with immersion and thus the potential liquid absorption is reduced. However the shape of the dental impression is complex and it requires spraying from different angles to achieve even coverage. Thus the amount of disinfectant delivered into the contact with alginate is sufficient to distort the alginate by additional swelling while being insufficient to ensure even coverage of the surface.

A number of studies have shown that the efficacy of registered disinfectants when used as a spray to coat a very uneven surface is low. For example (Efficacy of Various Spray Disinfectants on Irreversible Hydrocolloid Impressions; Westerholm, Bradley, Schwartz – Int J Prosthodont 1992;5:47–54), 5.25% sodium hypochlorite and 2% glutaraldehyde achieve only a log 3 to log 4 reduction in a bacterial population of *Staphylococcus aureus* and *M. phlei* when sprayed on to the alginate impressions. These liquids, which are expected to be highly efficacious, achieve only a log 2 reduction in the number of microbial pathogens when they were sprayed on impressions inoculated with vegetative *Bacillus subtilis*. A severe disadvantage of the various spray methods is the probability of severe irritation to eyes and mucous membranes by the atomised liquid disinfectants.

The methods of atomising liquids using ultrasonic irradiation have been cited in previous art for atomising liquid medicine, disinfectants and for moisturising human tissues. For example, US Patent 4,679,551 discloses the use of a low frequency ultrasonic sprayer for moisturising the oral cavity of terminal patients. Igusa et al US 5,449,502 describes the use of an ultrasonic transducer vibrating at 30–80 kHz to atomise a disinfecting solution and deliver a sufficient amount of the solution for the disinfection of



hands. WO 97/17933 discloses a method of spraying liquids onto human tissue using sprays produced by low frequency (20 to 200 kHz) ultrasonic irradiation utilising a spray gun described in US Patent 5, 076,266. However, the atomisation at low frequency produces, in large part, particles with diameters in the range of 5 to 10 micrometers. This is of the same order or larger than that obtained by the application of mechanical spraying techniques. As a result, the amount of liquid accumulating on the treated surface is significant. This amount of liquid is sufficient to cause unacceptable dimensional distortion of moisture sensitive materials such as dental alginate impressions.

In WO 97/17933 it is claimed that any liquid including distilled water exhibits and maintains antibacterial properties after sonication, whilst solutions containing antibiotics improve their bactericidal products by virtue of sonication. Low frequency ultrasonic irradiation has been recognised as a means of quantitatively transferring bacteria from solid surfaces (eg AOAC Method of Analysis No. 991.47).


It is an object of the present invention to overcome or ameliorate one or more of the disadvantages of the prior art, or at least to provide a useful alternative.

SUMMARY OF THE INVENTION

According to a first aspect, the invention consists in a method of disinfection comprising the step of applying ultrasonic energy at a frequency selected to be above 1.5 MHz to a liquid disinfectant in a nebulising chamber to produce a nebulised disinfectant product. For preference the selected frequency is above 2 MHz

Preferably the frequency of the ultrasonic energy and the liquid disinfectant formulation are selected such that 90% of microdroplets are between 0.8 and 2.0 micrometres in diameter.

This Sheet Has Been Replaced



The applicant has found that when a mist of disinfectant atomised by ultrasonic nebulisers with frequencies over 1.5 MHz contacts a surface it can provide significantly improved disinfection in comparison with immersion or with sprays of the same or similar disinfectants, including sprays nebulised at lower frequencies. Without wishing to be
5 bound by theory, it is believed that the improvement is due to activation of the disinfectant by ultrasonic irradiation at the selected frequency and not merely to smaller particle size.

The droplets of the atomised disinfectant containing the activated biocidal compound are desirably delivered onto the surface to be disinfected as a cold (preferably below 40° C) mist of microdroplets.

10 The amount of disinfectant delivered, the concentration of the disinfectant mist and condensation conditions are regulated by varying the size of the droplets, air flow conditions and the period of disinfectant contact with the surface to be disinfected.

Preferably, the nebulising time and ultrasonic frequency are selected in combination having regard to the disinfectant composition to provide a predetermined level
15 of disinfection of an object exposed to the nebulised product.

The surfaces to be disinfected may be for example skin, medical instruments, hospital wards, operation theatres, walls, hand rails, air conditioning ducts, dental and medical prosthesis, skin, and open wounds but are not limited to such surfaces.

The present invention also relates to the disinfection of a volume contained within
20 an enclosed space.

According to second aspect the invention consists in the addition to disinfectant of a surfactant or surfactant system. The size of microdroplets and their susceptibility to activation is modified by the addition of a surfactant or surfactant system.





Preferably the disinfectants selected for use in the present invention are compounds which can be activated by high frequency ultrasound. Disinfectants useful in the present invention include, but are not limited to, those which improve their performance when exposed to high frequency ultrasonic irradiation, for example those based on the peroxy compounds (e.g. hydrogen peroxide, peracetic acid, persulphates and percarbonates), halogen solutions, halogen compounds and solutions of halogen compounds (e.g. sodium hypochlorite and povidone iodine), phenolic compounds and halogenated phenolic compounds in solution (e.g. Triclosan) have been found to benefit from ultrasonic irradiation.

10 According to a third aspect the invention consists in performing the disinfection within an enclosed disinfection chamber, such that nebulisation occurs in an ultrasonic chamber which resides in or communicates with the enclosed disinfection chamber.

According to a fourth aspect, the invention consists in a method according to the first or second aspects further comprising the step of atomising neutralising agents, for example peroxidase enzymes for peroxy-compounds or sodium thiosulfate for halogen based disinfectants, after the completion of a sterilisation cycle to decompose all active biocides.

According to a fifth aspect, the invention consists in selecting a combination of nebulising time and ultrasonic frequency having regard to the disinfectant composition so as to ensure adequate disinfection of a predetermined object. Preferably the nebulising time and ultrasonic frequency are selected such that disinfection occurs with a minimum of liquid and such that the disinfected object is quickly and easily dried. This can be achieved by air drying, blow drying or vacuum or by a combination of these, whereby a given level of sterilisation and drying of an object may be achieved in a minimum time at ambient

- 8 -

temperature.

According to a sixth aspect, the invention consists in a disinfected volume in a nebulising chamber prepared according to one of the methods of the invention.

The invention also consist in a method of disinfection comprising the step of
5 applying ultrasonic energy at a frequency selected to be above 1.5 MHz to a nebulised
disinfectant.

The invention also consist in a method of disinfection comprising the step of
nebulising a liquid disinfectant to form microdroplets, allowing the microdroplets to
contact a surface and applying ultrasonic energy to at least one of the surface and the
10 microdroplets.

The invention further consists in a composition for use in accordance with the
methods of the invention.

Unless the context clearly requires otherwise, throughout the description and the
claims, the words 'comprise', 'comprising', and the like are to be construed in an inclusive
15 as opposed to an exclusive or exhaustive sense; that is to say, in the sense of "including,
but not limited to".

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 shows an embodiment of a disinfection apparatus in accordance with one
aspect of the present invention.

20 Figure 2 shows a preferred configuration of an embodiment of a disinfection
apparatus in accordance with one aspect of the present invention.

Figure 3 shows another preferred configuration of an embodiment of a disinfection
apparatus in accordance with one aspect of the present invention.

This Sheet Has Been Replaced





BEST MODE FOR CARRYING OUT THE INVENTION.

The invention will now be described by way of example only with reference to preferred embodiments.

Ultrasonic and acoustic vibrations are known to produce aerosols. The mechanism
5 of atomising liquids with ultrasound consists of the microeruption of cavitation bubbles close to the liquid/air interface: breaking bubbles scatter the liquid. Using air flows generated either by pumping air or by the Bernoulli effect, the mist of droplets can be separated from the bulk of the liquid and directed onto an object.

The invention will be described with particular reference to its use with hydrogen
10 peroxide based disinfectants but it will be understood not to be limited to these disinfectants.

It is believed that the mode of biocidal action of commonly used disinfectants is not due to the molecule itself, but to the production of more powerful derivatives, for example, the hydroxyl radical in the case of peroxy compounds or hypochlorous acid in the case of
15 hypochlorite-based disinfectants. These radicals normally form as a result of irradiation with ultraviolet or infra-red radiation or the catalytic action of metal ions.

Hydrogen peroxide vapour sterilisers have been used in the past. These sterilisers have a series of drawbacks, amongst which is the need for a high temperature to generate vapour. The increased temperatures are required for vaporisation and the production of
20 active biocidal particles. As the concentration of hydroxyl radicals is directly proportional to the concentration of hydrogen peroxide in the formulation and the temperature, the highest practical temperature and concentration are used.

In the present invention the high frequency ultrasonic energy is utilised for both the atomisation of disinfectant solutions and the production of biocidally active hydroxyl



radicals. This in-situ formation of hydroxyl radicals allows the achievement of the required concentrations of biocidal actives without increasing the temperature or the concentration of biocide in the bulk liquid.

The combination of atomisation and activation by ultrasound overcomes the major
5 drawbacks of the previous art. The amount of antiseptic vapour delivered on the object to be disinfected is very much less than required for bulk liquid and spray disinfection methods. The particle size of 0.8 - 2.0 micrometres of the atomised mist is of the same order as the size of the smallest cracks and pores which can potentially harbour microorganisms.

10 The layer of the condensed antiseptic which forms in the course of, and subsequent to, sonication contains a sufficient amount of active biocide to destroy all susceptible microorganisms.

The low concentration of disinfectant, in the case of hydrogen peroxide, left on the disinfected object rapidly decomposes forming harmless water and oxygen. If the
15 remaining peroxide needs to be decomposed after treatment, a small amount of peroxidase enzymes or any other suitable neutraliser can be atomised on the object.

In the case of other disinfectants the small amounts remaining on the surface can be left, neutralised or rinsed off as required.

When subjected to ultrasound at 1.2 MHz water produces particles with the mass
20 median aerodynamic diameter (MMAD) of 4 - 5 micrometres (The Ultrasonic Generation of Droplets for the production of Submicron Size Particles, Charuau, Tierce, Birocheau; J Aerosol Sci. V. 25, Suppl.1, ppS233-S234, 1994). At lower frequencies the particles are larger and at higher frequencies the MMAD is reduced. At 2.5 MHz, MMAD is 1.9 micrometres. Further increase in frequency results in the increase of energy density and

hence an increase in the temperature of the nebulised liquid. A further reduction in aerosol particle size to 0.8 - 1.0 micrometres can be achieved by decreasing the surface tension by the addition of a small amount of an appropriate surfactant without significant increase in temperature.

5 A mixture of water soluble surfactants with the addition of non-water soluble surfactants to suppress foam is found to be effective in one of the embodiments of the current invention.

Suitable surfactants can include a mixture of ethoxylated alcohols (eg Teric 12A3) together with dodecylbenzenesulfonic acid salts, or ethoxylated alcohols alone or block copolymers of ethylene oxide and propylene oxide with alcohol either alone
10 or as part of a mixture with the above surfactants. A skilled addressee would understand that the above surfactants are included only as non-limiting examples of species which can be applied as part of the invention.

The amount of liquid condensed on a surface after a 2 minute exposure to nebulised
15 droplets in a sealed system was found to be in the order of 30 g/m^2 for low frequency ultrasound. When ultrasound in the high frequency range which is the subject of this invention is used, the condensate level was found to be reduced to 3 g/m^2 in the same sealed system

A substantial advantage of the invention is associated with the small amount of
20 condensate formed on surfaces. Inclusion in the disinfectant of substances with high vapour pressure is advantageous to reduce drying time. For example alcohols with high vapour pressure relative to water, ethers with high vapour pressure relative to water, hydrocarbons with high vapour pressure relative to water, esters with high vapour pressure relative to water and other organic substances with high vapour pressure relative to water



- 12 -

or mixtures of such substances with high vapour pressure may substantially reduce the time required for drying.

Even when the disinfectant utilised in the process has a relatively high vapour pressure (eg aqueous hydrogen peroxide solution), this material can be easily removed by
5 air drying. At a relative humidity of 50 to 60% and a temperature of 22°C the air drying of an object with a surface area of 100 to 150 cm² is achieved in 10 to 15 minutes. However if a warm, dry source of air is blown across the surface of the object the drying time is reduced to 0.5 to 3 minutes. Therefore a high speed, cold disinfection cycle which begins with a microbially contaminated instrument and results in a dry, disinfected
10 instrument can be achieved quickly, simply and cheaply.

The application of such equipment is potentially very broad and includes hospitals, medical clinics, dental clinics, veterinary clinics, food processors, fast food outlets, beauty salons, hairdressers, tattoo parlours, etc.

With reference to the drawings, figure 1 shows an embodiment of a disinfection
15 apparatus suitable for use in the present invention. An article to be disinfected is placed in enclosed chamber 2. The lid of the chamber 1 is removable for this purpose. The disinfectant is placed in ultrasonic nebulising chamber 3, and nebulised by ultrasonic transducer 4. The air intake 5 provides the necessary air from outside the chamber.

Figure 2 shows a preferred embodiment of a disinfection apparatus suitable for use
20 in the present invention. An article to be disinfected is placed in enclosed chamber 2 by means of a removable lid 1. The disinfectant is placed in ultrasonic nebulising chamber 3 and nebulised by ultrasonic transducer 4. The air intake 5 provides the necessary air from inside the chamber.

This Sheet Has Been Replaced



Figure 3 shows an adaptation of the apparatus according to Figure 2. While ultrasonic transducer 4 is located outside the chamber, air intake 5 still provides the necessary air from within the enclosed chamber 2.

The advantage of configurations shown in Figures 2 and 3, and similar configurations is that they provide a completely sealed system. The disinfectant both prior to, and after, nebulisation is contained within the sealed system, providing significant advantages over unsealed systems where the disinfectant has implications with respect to human health and safety.

Embodiments of the invention will now be exemplified.

10 Example 1

Efficacy data was obtained with the following disinfectants:

- A. 6% w/w hydrogen peroxide (pH=3), 94% w/w water.
- B. 6% w/w hydrogen peroxide + 15% w/w n-propanol + 0.3% w/w Irgasan 3000 + 0.02% w/w PVP K15 + 0.5% w/w STPP (pH=7) + 2% w/w LAS + 2% w/w Teric12A3
- 15 C. 5% w/w peroxyacetic acid, diluted 1:50 with distilled water
- D. 2% w/w chlorhexidine gluconate + 15% w/w n-propanol in distilled water

Test Procedures:

Equipment.

The principle of operation of nebulisers is described elsewhere, (for example by K. Sollner in Trans. Faraday Soc. v.32, p1532, 1936). The main elements of an ultrasonic nebuliser are: a high-frequency generator, a piezoceramic transducer and a reservoir for the solution to be nebulised. The production of a fine aerosol involves forcing the transducer to vibrate mechanically by applying resonance frequency. These high frequency vibrations are focussed in the near-surface part of the solution, and create an "ultrasonic fountain".

This Sheet Has Been Replaced



- 14 -

Once the energy exceeds a certain threshold, droplets break off and are forced by air streams out of the reservoir.

A Mousson 1 ultrasonic nebuliser (currently discontinued, similar nebulisers are manufactured by Otto Schill GmbH & Co., K. Medizintechnik, Germany) with a concave glass covered transducer was used to atomise the various disinfectants under study. The nebuliser operates at 2.64 MHz. The nebulising rate was approximately 1mL/min. The nebulised liquid disinfectant was pumped into a 1.5L hermetically sealed vessel (Figure 1) for 2 minutes. Normally the disinfectant vapour pressure in the vessel reaches the same value as in the nebulising chamber of the nebuliser within 30-40 seconds. As the nebulising rate depends on the pressure differential, the vapour delivery rate reduced significantly after 30-40 seconds, and was just sufficient to compensate for the condensed vapour. Total amount of nebulised disinfectant during the cycle was under 1mL.

The inoculated carriers were placed in the close vicinity of the nebulising horn.

Inoculum:

The inoculum of vegetative *Pseudomonas aeruginosa* (ATCC15442), *Mycobacterium terrae* (ATCC 15755), *E.coli* (ATCC 8739), and *S.aureus* (ATCC 6538), were prepared from an overnight culture and contained approximately $10^8 - 10^9$ cfu/mL.

The inoculum of dry, non vegetative *Clostridium sporogenes* (ATCC 3584), and *B.subtilis* (ATCC 19659) spores was prepared as per the method described in AOAC 966.04.

Each carrier was inoculated with approximately 0.02 mL of the inoculum to provide for contamination levels of $10^6 - 10^7$ cfu per carrier.

Carriers:

This Sheet Has Been Replaced



- 15 -

20 microlitres of an inoculum was placed on sterile (3 hours at 180°C oven)
10x20mm glass plates, and dried for 40 minutes in the incubator at 36°C

Sterile (3 hrs at 180°C) glass penicylinders were soaked in the inoculum for 10 minutes
and then for 40 minutes in the incubator at 36°C

5 Alginate slices were prepared from Fast Set Alginate powder (Palgat Plus Quick,
ESPE) sterilised for 1 hr at 120°C. The alginate was hand mixed for 30 seconds using
manufacturer recommended water/powder ratio and loaded onto dry sterile trays. After
settling for 3 minutes alginate has been cut with a flame-sterilised scalpel into a 20x10x1
mm slices. The slices were aseptically placed on a sterile Petri dish and contaminated by
10 pressing the scalpel soaked in inoculum onto the slices. Extreme care was taken to avoid
inoculation of the slides and the surface of Petri dish.

Sterile silicone slices were prepared from Hydrophilic Vinyl Polysiloxane
Impression Material (Heavy Body, Normal Setting, ADA Spec. 19, Elite H-D by
Zhermack) using mixing procedure recommended by the manufacturer and loaded onto a
15 sterile tray. After setting for five minutes, the impression material was cut into a 20x10x1
mm slices with the sterile scalpel. The slices were sterilised by soaking in a 1%
peroxyacetic acid for three minutes, then rinsed with the sterile water and dried under UV
light for five minutes. The slices were aseptically placed on a sterile Petri dish and
contaminated by pressing the scalpel soaked in inoculum onto the slices.

20 A Petri dish with inoculated carriers was placed into the disinfecting vessel. The
vessel was then covered tightly with a lid to ensure that nebulised liquid could not escape
from the vessel. The disinfection cycle consisted of 2 minutes nebulising, and then left for
four minutes to allow the vapour to condense.

- 16 -

Immediately after opening the lid, each carrier was aseptically placed in the test tube with sterile nutrient broth containing disinfectant deactivator (Tween 80). Bacto Lethen broth was used for *P. aeruginosa*, *S. aureus* and *E. coli*, a Bacto Middlebrook 7H9 both for *M. terrae* and a Bacto Fluid Thioglycolate Media for the spores. As a control, 5 inoculated carriers were treated with nebulised, sterile distilled water in place of disinfectant

Essentially, this experiment is modelled on the AOAC's sterilant testing methods. No growth in the test tube indicates that 100% kill of a test organism has been achieved. This is a significantly more severe requirement than the log 5 reduction in the bacteria 10 population required by the ADA. This method has been chosen as the surest method for demonstrating the efficacy of disinfecting techniques.

Results:

"nt" - not tested

"passes" - complete kill of the tested organism has been achieved on at least

15 10 out of 10 replicas, with no survivals

"growth" number of carriers which carried viable test organisms

- 17 -

TABLE 1

Mycobacterium terrae:Inoculum: 10^8 cfu/mL in tryptone soya broth

Carrier/ /disinfectant	A	B	C	D
Glass slides	passes	passes	passes	passes
Glass penicylinders	nt	passes	passes	nt
Silicone	nt	passes	passes	nt
Alginate slices	passes	passes	passes	growth 8 out of 8

5 TABLE 2

*Pseudomonas aeruginosa*Inoculum: 10^8 cfu/mL in tryptone soya broth

Carrier/ /disinfectant	A	B	C	D
Glass slides	passes	passes	passes	passes
Glass penicylinders	5 out of 9	passes	passes	growth 6 out of 10
Silicone	nt	passes	passes	growth 10 out of 10
Alginate slices	growth 8 out of 10	passes	passes	growth 9 out of 10

TABLE 3

E.coli:

Inoculum: 10^8 cfu/mL in tryptone soya broth

Carrier/ disinfectant	A	B	C	D
Glass slides	passes	passes	passes	passes
Glass penicylinders	nt	passes	passes	nt
Silicone	nt	passes	passes	nt
Alginate slices	nt	passes	passes	nt

5 TABLE 4

S.aureus:

Inoculum: 10^8 cfu/mL in tryptone soya broth

Carrier/ disinfectant	A	B	C	D
Glass slides	passes	passes	passes	passes
Glass penicylinders	growth 3 out of 10	passes	passes	nt
Silicone	nt	passes	passes	nt
Alginate slices	nt	passes	passes	nt

TABLE 5

Clostridium sporogenes dried spores:

Inoculum: 10^8 cfu/mL in tryptone soya broth

This Sheet Has Been Replaced



Carrier/ disinfectant	A	B	C	D
Glass slides	passes	growth 4 out of 10	passes	passes
Glass penicylinders	nt	growth 5 out of 10	passes	passes
Silicone	nt	nt	nt	nt
Alginate slices	nt	nt	nt	nt

- 5 "nt" not tested
 "passes" complete kill of the tested organism has been achieved on at least 10 out of 10 replicas, no survivals
 "growth" number of carriers which carried viable test organisms

10 Example 2

Assessing the efficacy of the disinfectants on alginate dental impressions using a sealed system (Figure 2).

The testing procedure has been adapted from that described in US Patent No. 5,624,636. Sterile models of a patient's maxillary and mandible teeth and soft tissues were
 15 contaminated with the bacterial suspensions containing 10^8 to 10^9 cfu/mL. Fast set alginate dental impressions (Palgat Plus Quick, ESPE) were hand mixed for 30 seconds using the water/powder ratio the manufacturer recommended, and loaded onto sterilised plastic trays.

The impressions were made of contaminated models, and these were allowed to bench set for 3 minutes. after which time the models were removed. To transfer viable
 20 bacteria the parts of the impressions containing the 12th and 13th teeth (UL4 and UL5) for

- 20 -

maxillary jaws and 30th and 29th (LL4 and LL5) teeth for the mandible jaws were cut out with a sterile scalpel and placed into 10 mL of sterile tryptone soya broth, sonicated in a 40KHz ultrasonic bath for 2 minutes, plated onto tryptone soya agar and incubated aerobically for 48 hours. After disinfection, the parts of the impressions containing 4th and 5th (UR4 and UR5) teeth for maxillary jaws or 28th and 28th (LR4 and LR5) teeth for the mandible jaws were cut out and viable bacteria were transferred in the tryptone soya broth as described above. Both maxillary and mandible impressions were processed in the same cycle. The tabulated results of bacterial survivals are an average between the bacterial populations of the two impressions.

10 TABLE 6

Alginate impressions

Inoculum: *Pseudomonas aeruginosa* 10^8 cfu/mL in tryptone soya broth

	A	B	C	D
Before treatment, cfu per impression	3×10^7	3×10^7	3×10^7	3×10^7
After treatment, cfu per impression	1.2×10^4	85	47	6.4×10^5

TABLE 7

Alginate impressions

Inoculum: *Pseudomonas aeruginosa* 10^8 cfu/mL in tryptone soya water

	A	B	C	D
Before treatment, cfu/mL	4.5×10^7	4.5×10^7	4.5×10^7	4.5×10^7
After treatment, cfu/mL	7.2×10^3	0	0	4.3×10^3

5 TABLE 8

Alginate impressions

Inoculum: *E. coli* 10^8 cfu/mL in tryptone soya broth

	A	B	C	D
Before treatment , cfu/mL	8×10^6	8×10^6	8×10^6	8×10^6
After treatment, cfu/mL	5.5×10^2	0	0	3×10^4

TABLE 9

Alginate impressions

Inoculum: *Pseudomonas aeruginosa* 10^8 cfu/mL in tryptone soya broth, rinsed after inoculation with 250 mL sterile tap water as per the ADA protocol

	A	B	C	D
Before treatment , cfu/mL	9×10^4	9×10^4	9×10^4	9×10^4
After treatment, cfu/mL	0	0	0	60

5 Example 3

To compare the biocidal efficacy of sonicated and non-sonicated solutions of hydrogen peroxide the following experiment was conducted. 0.1 mL inocula of *P.aeruginosa* (10^9 cfu/mL) and vegetative *Bacillus subtilis* were spread evenly over 20 x 15 mm areas of glass plates, dried for 40 min and then treated with 0.05 mL of 4% hydrogen peroxide for 2 minutes. The surviving microorganisms were transferred, as described in example 1, into tryptone soya broth and then plated. The same contaminated plates were treated for 15 seconds with the nebulised mist of the same 4% hydrogen peroxide solution, and then left for 1 minute and 45 seconds. The total amount of hydrogen peroxide condensed on each plate was below 0.01 mL (or at least 10 times less than in the reference experiment). The results were as follows: In the experiment with the bulk solution the observed survival level was 4×10^3 cfu/mL; the nebulised hydrogen peroxide killed all bacteria and no survivors were detected either on Petri dishes, or in the test tubes with tryptone soya broth.

15 Example 4.

- 23 -

A 1% hypochlorite disinfecting solution has been used to disinfect mandible dental impressions made of the same model as described in Example 2. Three different modes of disinfectant delivery were compared:

1. Atomised with a fine spray hand pump (AC Colmack Ltd). The disinfectant was
5 sprayed on the impressions and left for 10 minutes.
2. Atomised with a 40KHz Micromist ultrasonic atomiser (Misonix Inc) for 3 minutes, then left for another 8 minutes. Total contact time is 10 minutes.
3. Atomised with a 2.64 MHz Mousson ultrasonic nebuliser for three minutes and then left in the nebulising chamber (sealed system) for seven minutes. Total contact time is
10 10 minutes.

The results are as follows:

TABLE 10

Delivery Mode	Amount of Disinfectant Delivered	Contamination levels, cfu per impression	
		Before disinfection	After disinfection
Hand Sprayed	0.41 g	8.7×10^7	3.9×10^2
40 kHz nebuliser	0.28 g	1.2×10^7	2.4×10^2
2.6 MHz nebuliser	0.06 g	5.3×10^7	0

- 24 -

It can be seen that greater kill levels are achieved when the mixture is nebulised at 2.6 MHz than by the other methods. The quantity of disinfectant used is also significantly lower

Although the invention has been described with reference to specific examples, it
5 will be appreciated by those skilled in the art from the reading hereof that the invention may be embodied in other forms without departing from the scope of the concept herein disclosed.

This Sheet Has Been Replaced





THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. A method of disinfection comprising the step of applying ultrasonic energy at a frequency selected to be above 1.5 MHz to a liquid disinfectant in a nebulising chamber to produce a nebulised disinfectant product.
2. A method according to claim 1 wherein the nebulising time and ultrasonic frequency are selected in combination to provide a predetermined level of disinfection of an object exposed to the nebulised disinfectant product.
3. A method according to claim 1 or claim 2 wherein the frequency is above 2 MHz.
4. A method according to any one of the preceding claims wherein the frequency of the ultrasonic energy and the liquid disinfectant formulation are selected such that 90% of microdroplets are between 0.8 and 2.0 micrometers in diameter.
5. A method according to any one of the preceding claims wherein the disinfection occurs below 40°C.
6. A method according to any one of the preceding claims wherein the liquid disinfectant is formulated together with a surfactant and/or surfactant system.
7. A method according to claim 6 wherein the surfactant modifies the size of the microdroplets.
8. A method according to claim 6 or claim 7 wherein the surfactant modifies the susceptibility to activation of the microdroplets.
9. A method according to any one of the preceding claims wherein the disinfectant is activated by high frequency ultrasound.
10. A method according to any one of the preceding claims wherein the disinfectant is selected from the group consisting of peroxy compounds, halogenated compounds, phenolic compounds, and halogenated phenolic compounds.

This Sheet Has Been Replaced



- 26 -

11. A method according to claim 10 wherein a peroxy compound is selected from the group consisting of hydrogen peroxide, peracetic acid, persulfates, and percarbonates.
12. A method according to claim 10 wherein a halogenated compound is selected from sodium hydrochloride and povidone iodine.
13. A method according to claim 10 wherein a halogenated phenolic compound is Triclosan.
14. A method of performing disinfection within an enclosed disinfection chamber such that nebulisation occurs in an ultrasonic chamber which resides in or communicates with the enclosed disinfection chamber.
15. A method of disinfection according to any one of the preceding claims wherein the time and frequency are selected to ensure a predetermined level of disinfection.
16. A method according to any one of the preceding claims wherein the nebulisation time and ultrasonic frequency are selected such that a disinfected object is quickly dried.
17. A method of performing disinfection according to claim 16 wherein the disinfected article is blow dried.
18. A method of performing disinfection according to any one of the preceding claims wherein the disinfectant substance includes at least one substance with high vapour pressure relative to water.
19. A method according to claim 18 wherein the at least one substance or substances are selected to reduce drying time.
20. A method according to any one of claims 18 to 19 wherein the at least one substance or substances with higher vapour pressure is selected from the group consisting of alcohols, ethers, hydrocarbons, and esters.



- 27 -

21. A method according to any one of the preceding claims further including the step of neutralising the disinfectant with a neutralising agent subsequent to the disinfection step.
22. A method according to claim 21 wherein the neutralising agent is applied in
5 nebulised form.
23. A method according to claim 21 or 22 wherein the neutralising agent is selected from the group consisting of peroxidase enzymes or sodium thiosulfate.
24. A disinfected volume in a nebulising chamber prepared by a method according to any one of the proceeding claims.
- 10 25. A composition for use in a disinfection method according to any one of the preceding claims comprising a disinfectant.
26. A composition according to claim 25 wherein the disinfectant is selected from the group consisting of peroxy compounds, halo compounds, phenolic compounds, and halogenated phenolic compounds.
- 15 27. A composition according to claim 26 wherein the peroxy compound is selected from the group consisting of hydrogen peroxide, peracetic acid, persulfates, and percarbonates.
28. A composition according to claim 26 wherein the halogenated compound is selected from sodium hydrochloride and povidone iodine.
- 20 29. A composition according to claim 26 wherein the halogenated phenolic compound is Triclosan.
30. A composition according to any one of claims 25 to 29 further comprising a surfactant.

This Sheet Has Been Replaced





31. A composition according to claim 30 wherein the surfactant is one or more compounds selected from the group consisting of ethoxylated alcohols, dodecylbenzene sulfonic acid salts, block copolymers of ethylene oxide and propylene oxide and alcohol
- 5 32. A composition according to claim 31 wherein the surfactant is Teric 12A3.
33. A composition according to any one of claims 24 to 32 further comprising a substance with a higher vapour pressure than water.
34. A composition according to claim 33 wherein the substance and/or mixture of substances with higher vapour pressure is selected from the group consisting of
- 10 alcohols, ethers, hydrocarbons, and esters.
35. A mist comprising droplets of a composition containing a disinfectant and having a 90% of the droplets between 0.8 and 2.0 micrometres in diameter.
36. A mist according to claim 35 when formed by the method of any one of claims 1 to 23.
- 15 37. A mist according to claim 35 when formed from the nebulisation of a composition of any one of claims 25 to 34.
38. A disinfected article when disinfected according to a method of any one of claims 1 to 23, or by exposure to a mist according to any one of claims 35 to 37.
39. A disinfected article according to claim 38 in the form of a dental impression.
- 20 40. A method of disinfection comprising the step of applying ultrasonic energy at a frequency selected to be above 1.5 MHz to a nebulised disinfectant.
41. A method of disinfection comprising the step of nebulising a liquid disinfectant to form microdroplets, allowing the microdroplets to contact a surface and applying ultrasonic energy to at least one of the surface and the microdroplets.





42. A method of disinfection substantially as herein described with reference to any one of the examples.
43. A composition for disinfection substantially as herein described with reference to any one of the examples.
- 5 44. A mist substantially as herein described with reference to any one of the examples.

This Sheet Has Been Replaced

