

- 1 -

ELECTRICAL CONNECTOR HOLD-DOWN

Field of the Invention

The invention relates to a hold-down for electrical connectors, and more particularly to a multi sided hold-down
5 for interconnecting an electrical connector to a printed circuit board ("PCB").

Background of the Invention

Hold-downs are generally used to interconnect electrical connectors to other electrical connectors or PCBs.
10 The type of hold-down used depends on the type of electrical connection being formed between the components. For example, if the electrical connection is a solderless form of connection, the hold-down used may be a rivet or nut and bolt combination. These form of hold-downs are necessary when the
15 interconnection needs to minimize lateral (X & Y plane) movement relative to the interconnection.

Hold-downs may also need to resist unwanted vertical (Z plane) movement such as from mating and unmating forces. Although, rivets and nut and bolt combinations may be adequate,
20 a hold-down at a lower manufacturing cost which provides adequate resistance to X, Y and Z plane movement is needed. In addition, a hold-down is needed that does not require any tools when used to form an interconnection between an electrical connector and a PCB.

- 2 -

Summary of the Invention

The object of the invention is to provide a hold-down which resists movement in the X, Y and Z plane, which has a lower manufacturing cost than conventional hold-downs, and
5 which does not require tools for its insertion into an electrical connector and a PCB when forming an interconnection of the electrical connector and the PCB.

To this end, a hold-down of the present invention for interconnecting a structure via a circular bore within the
10 structure includes a body having a base portion, a first side portion, and a second side portion. The portions forming the body where the diameter of the smallest circle which encompasses the body is greater than the diameter of the circular bore within the structure.

15 In addition, the body has a gap formed between the ends of the first side portion and second side portion so that the diameter of the smallest circle which encompasses the body may be made smaller than the diameter of the circular bore within the structure so that the body of the hold-down may be
20 inserted into the circular bore within the structure.

As a consequence, the body of the hold-down provides a plurality of points of contact against the side walls of the circular bore within the structure when the body is inserted in the bore because the diameter of the smallest circle that
25 encompasses the body is greater than the diameter of the bore.

This embodiment of the invention may further include a second body connected to the body of the hold-down for interconnecting a second structure via a circular bore within the second structure to the structure interconnected by the
30 body of the hold-down. The second body having a base portion, a first side portion, and a second side portion forming the second body where the diameter of the smallest circle which encompasses the second body is greater than the diameter of the circular bore within the second structure.

35 The second body also having a gap formed between the ends of the first side portion and second side portion so that the diameter of the smallest circle which encompasses the

- 3 -

second body may be made smaller than the diameter of the circular bore within the second structure so that the second body of the hold-down may be inserted into the circular bore within the second structure,

5 As a consequence, the second body of the hold-down provides a plurality of points of contact against the side walls of the circular bore within the second structure when the second body of the hold-down is inserted in the bore of the second structure because the diameter of the smallest circle
10 which encompasses the second body is greater than the diameter of the bore of the second structure so that the structure and the second structure are interconnected by the body and the second body of the hold-down.

 According to another embodiment of the invention, a
15 hold-down of the present invention for interconnecting a structure via a circular bore within the structure includes a body having a plurality of portions. The portions forming the body where the diameter of the smallest circle which encompasses the body is greater than the diameter of the
20 circular bore within the structure.

 In addition, the body has a gap formed between ends of portions of the body so that the diameter of the smallest circle which encompasses the body may be made smaller than the diameter of the circular bore within the structure so that the
25 body of the hold-down may be inserted into the circular bore within the structure.

 As a consequence, the body of the hold-down provides a plurality of points of contact against the side walls of the circular bore within the structure when the body is inserted in
30 the bore because the diameter of the smallest circle that encompasses the body is greater than the diameter of the bore.

 This embodiment of the invention may further include a second body connected to the body of the hold-down for interconnecting a second structure via a circular bore within
35 the second structure to the structure interconnected by the body of the hold-down. The second body having a plurality of portions forming the second body where the diameter of the

- 4 -

smallest circle which encompasses the second body is greater than the diameter of the circular bore within the second structure.

5 The second body also having a gap formed between the ends of portions of the body so that the diameter of the smallest circle which encompasses the second body may be made smaller than the diameter of the circular bore within the second structure so that the second body of the hold-down may be inserted into the circular bore within the second structure,

10 As a consequence, the second body of the hold-down provides a plurality of points of contact against the side walls of the circular bore within the second structure when the second body of the hold-down is inserted in the bore of the second structure because the diameter of the smallest circle
15 which encompasses the second body is greater than the diameter of the bore of the second structure so that the structure and the second structure are interconnected by the body and the second body of the hold-down.

According to another embodiment of the invention, a
20 hold-down for interconnecting a first structure to a second structure via a circular bore within the first structure and a circular bore within the second structure includes a first body having a plurality of portions forming the first body where the diameter of the smallest circle which encompasses the first
25 body is greater than the diameter of the circular bore within the first structure.

The first body having a gap formed between the ends of portions of the first body so that the diameter of the smallest circle which encompasses the first body may be made
30 smaller than the diameter of the circular bore within the first structure so that the first body of the hold-down may be inserted into the circular bore within the first structure.

The embodiment also includes a second body having a plurality of portions forming the second body where the
35 diameter of the smallest circle which encompasses the second body is greater than the diameter of the circular bore within the second structure.

- 5 -

The second body having a gap formed between the ends of portions of the second body so that the diameter of the smallest circle which encompasses the second body may be made smaller than the diameter of the circular bore within the second structure so that the second body of the hold-down may be inserted into the circular bore within the second structure where the diameter of the smallest circle which encompasses the first body is smaller than the diameter of the smallest circle which encompasses the second body.

Finally, the embodiment includes a shoulder connecting the first body to the second body where the shoulder is offset so that the first body and the second body are aligned along a common centerline.

Brief Description of the Drawings

The invention will be described below in more detail with reference to the figures.

Figure 1a shows a side view of a first preferred embodiment of a hold-down according to the invention.

Figure 1b shows a side view of the hold-down shown in Figure 1a rotated 90 degrees.

Figure 1c shows a bottom view of the hold-down shown in Figure 1a.

Figure 1d shows a top view of the hold-down shown in Figure 1a.

Figure 2a shows a side view in partial Cross-Section of the first preferred embodiment of a hold-down interconnecting two structures according to the invention.

Figure 2b shows a bottom view in partial Cross-Section of the hold-down shown in Figure 2a.

Figure 2c shows a bottom view in partial Cross-Section of the hold-down shown in Figure 2a.

Figure 3a shows another side view in partial Cross-Section of the first preferred embodiment of a hold-down interconnecting two structures according to the invention.

Figure 3b shows a bottom view in partial Cross-Section of the hold-down shown in Figure 3a.

- 6 -

Figure 3c shows a bottom view in partial Cross-Section of the hold-down shown in Figure 3a.

Figure 4 shows a top view in partial Cross-Section of the first preferred embodiment of a hold-down of the present invention.

Figure 5a shows the first preferred embodiment of a hold-down of the present invention in a stage of manufacturing.

Figure 5b shows a side view of the hold-down shown in Fig. 5a.

Figure 6a shows two hold-downs according to the invention in the process of being inserting into a circuit board via an insertion tool to form an interconnection between an electrical connector and the printed circuit board.

Figure 6b shows a top view of the hold-downs and electrical connector as shown in Fig. 6a.

Figure 7 shows a hold-down according to the invention in the process of being inserting into a circuit board via an insertion tool to form an interconnection between an electrical connector and the printed circuit board and is a side view of Fig. 6a.

Figure 8a shows a side view of a second preferred embodiment of a hold-down according to the invention.

Figure 8b shows a side view of the hold-down shown in Figure 8a rotated 90 degrees.

Figure 8c shows a bottom view of the hold-down shown in Figure 8a.

Figure 8d shows a top view of the hold-down shown in Figure 8a.

Figure 9a shows two side views in partial Cross-Section of the first preferred embodiment of a hold-down according to the invention additionally having retentive bumps.

Figure 9b shows two side views in partial Cross-Section of the first preferred embodiment according to the invention of a hold-down additionally having stamped barbs.

Figure 9c shows two side views in partial Cross-Section of the first preferred embodiment according to the

- 7 -

invention of a hold-down additionally having interlocking stamped barbs.

Figure 10a shows a side view in partial Cross-Section of a third preferred embodiment of a hold-down interconnecting
5 two structures according to the invention.

Figure 10b shows a bottom view in partial Cross-Section of the hold-down shown in Figure 10a.

Figure 11a shows a side view in partial Cross-Section of a fourth preferred embodiment of a hold-down interconnecting
10 two structures according to the invention.

Figure 11b shows a bottom view in partial Cross-Section of the hold-down shown in Figure 11a.

Figure 12 shows a side view in partial Cross-Section of a fifth preferred embodiment of a right angle hold-down
15 interconnecting two structures at right angles according to the invention.

Detailed Description of Preferred Embodiments

Figures 1a to 1d show a first preferred embodiment of a hold-down 10 of the present invention for interconnecting two
20 structures. The hold-down 10 as shown in Figures 1a to 1d has two bodies 20 and 30 which are connected by a shoulder 40 which offsets the two bodies so that they are aligned along a common centerline as shown in Figure 1b. If the bodies have the same diameter, however, the shoulder 40 need not be offset to align
25 the bodies along a common centerline.

As shown in Figures 1c and 1d, in the first preferred embodiment of the invention, the bodies 20 and 30 have a substantially triangular shape when viewed from a horizontal perspective of the hold-down. Each body 20 and 30, includes a
30 base portion 26 and 36, a first side wall portion 27 and 37, and a second side wall portion 28 and 38.

Referring to the first body 20 in detail, the base portion of the body 26 connects to the first side wall portion 27 and the second side wall portion 28 at the ends of the base
35 portion. The first side wall portion 27 is attached to an end

- 8 -

of the base portion 26 and extends at an acute angle from the base portion. The first side wall portion 27 extends to a centerline formed by bisecting the base portion 26 of the body 20.

5 The second side wall portion 28 extends at an acute angle from the other end of the base portion 26 of the body 20 towards a centerline formed by bisecting the base portion 26 of the body 20. The first side wall portion 27 and the second side wall portion 28 do not meet at the centerline but form a
10 gap 29. The base portion 26, first side wall portion 27, and second side wall portion 28 form a substantially triangular shaped body having a first diameter where the body 20 extends in a vertical direction. Similarly, the body 30 has a base
15 portion 36, first side wall portion 37, and second side wall portion 38 that form a substantially triangular shaped body having a second diameter where the body 30 also extends in a vertical direction.

In the preferred embodiment of the invention, the base portion 26 and 36 of the each body 20 and 30 of the hold-down
20 10 also includes a barb 24 and 34. The barb extends out vertically from top portion of each body toward to the bottom portion of the body. In the preferred embodiment of the invention, each body 20 and 30 of the hold-down 10 also has a beveled edge 22 and 32. The beveled edge 22 and 32 is formed
25 on the base portion 26 and 36, first side wall portion 27 and 37, and second side wall portion 28 and 38. The interaction of the various components of the bodies 20 and 30 of the hold-down 10 is explained with reference to Figures 2a to 2c, 3a to 3c, and 4 below.

30 Figures 2a to 2c and 3a to 3c, show the hold-down shown in Figures 1a to 1d inserted into two structures 50 and 60 to form an interconnection of the structures. As shown in Figures 2a to 2c and 3a to 3c, the first body 20 is inserted in a first structure 50 and the second body 30 is inserted in a
35 second structure 60. In the preferred embodiment of the invention, the first structure 50 is a printed circuit board,

- 9 -

PCB and the second structure 60 is an electrical connector which is to be electrically coupled to the PCB.

The PCB 50 has a circular bore 52 having a first diameter and the electrical connector 60 also has a circular bore 62 having a second diameter where the circular bores are used to maintain engagement of the PCB 50 to the connector 60 via a hold-down. In the exemplary embodiment of the invention, the diameter of the circular bore 52 of the PCB 50 is larger than the circular bore 62 of the connector 60.

10 In particular, the diameter of bores of electrical connectors is commonly .100 inches and the diameter of bores of PCBs is commonly .120 inches. These sizes were selected in practice to accommodate prior art hold-downs such as rivets and nuts and bolts. As a consequence, different, in particular
15 smaller, bore diameters may be used for the hold-downs of the present invention.

As will be discussed further below, the diameters of the smallest circles that would encompass the bodies 20 and 30 of the hold-down 10 of the present invention are larger than
20 the corresponding diameters of the circular bores that the bodies are to be inserted into to provide engagement therewith. In particular, the diameter of the smallest circle that would encompass the first body 20 (which is inserted in the circular bore 52 of the PCB 50) is larger than the diameter of the
25 circular bore 52 of the PCB 50. As a consequence, the base portion 26, first side wall portion 27 and the second side wall portion 28 exert lateral forces against the side walls of the circular bore 52 of the PCB 50 when the body 20 is inserted in the bore 52.

30 Similarly, the diameter of the smallest circle that would encompass the second body 30 which is inserted in the circular bore 62 of the electrical connector 60 is larger than the diameter of the circular bore 62 of the connector 60. As a consequence, the base portion 36, the first side wall portion
35 37 and the second side wall portion 38 exert lateral forces against the side walls of the circular bore 62 of the connector 60 when the body 30 is inserted in the bore 62.

- 10 -

In addition, in the preferred embodiment of the invention, the diameter of the second body 30 (which is inserted in the connector 60) is smaller than the diameter of the first body 20 (which is inserted in the PCB 50) due to the fact that in the preferred embodiment of the invention, the diameter of the circular bore 62 of the electrical connector 60 is smaller than the diameter of the circular bore 52 of the PCB 50. As noted above, as a consequence of the different sizes of the bodies in the preferred embodiment of the invention, the shoulder 40 offsets the bodies so that the bodies are aligned along a common centerline.

As a consequence, the shoulder 40 extends at angle between the first and second bodies 20 and 30 as shown in Figures 1b and 2a due to the fact that the diameter of the second body 30 is smaller than the diameter of the first body 20 of hold-down 10, in the preferred embodiment of the invention. In this configuration, the shoulder 40 helps align the two bodies 20 and 30 of the hold-down 10 in the respective bores 52 and 62 of the PCB 50 and the connector 60.

The offset shoulder 40 of the preferred embodiment of the invention enables an individual to insert the hold-down of the present invention into an electrical connector and PCB to form an interconnection therebetween without the need of tools.

In the preferred embodiment of the invention, an individual follows a simple two step process to interconnect an electrical connector and PCB using a hold-down of the present invention due to the offset of the shoulder 40. In particular, the individual first inserts the smaller body 30 of the hold-down 10 into the bore 62 of an electrical connector 60 until the shoulder 40 engages the edge of the bore 62. Due to the fact that shoulder 40 is offset, the shoulder 40 forms a circle having a diameter greater than the diameter of the bore 62 and thus the shoulder 40 will engage the edge of the bore 62 of the connector 60 when inserted.

To complete the interconnection process, the individual then inserts the other body 20 into a corresponding bore 52 of a PCB 50 to be interconnected with the electrical

- 11 -

connector 60 by aligning the body 20 over the bore 52 and pressing down on the electrical connector 60 towards the PCB 50. Due to the fact that the shoulder 40 is offset, as note above, the body 20 will be engage the bore 52 of the PCB 50 and not travel into any portion of the bore 62 of the electrical connector 60 as the electrical connector 60 is being pressed toward the PCB 50 to interconnect them via the hold-down of the present invention. As a consequence, an individual can interconnect an electrical connector to a PCB with a hold-down of the present invention without the aid of tools.

In the preferred first embodiment of the invention, the bodies 20 and 30 of the hold-down 10 also have barbs 24 and 34 extending from the base portions 26 and 36. The barb 24 extends horizontally to a distance greater than or equal to the diameter formed by the smallest circle which encompasses the body 20. Likewise, the barb 34 also extends horizontally to a distance greater than or equal to the diameter formed by the smallest circle which encompasses the body 30. As a consequence, when the body 20 is inserted in the circular bore 52 of PCB 50, the barb 24 provides lateral force against the side wall of the circular bore 52 of the PCB 50.

In particular, due to the fact that the barb extends out vertically from the top of the body 20, the lateral force exerted by the barb 24 is increased by any vertical force in a direction towards the top of the body 20, i.e., away from the mating connection with the electrical connector 60.

Similarly, when the body 30 is inserted in the circular bore 62 of the electrical connector 60, the barb 34 provides lateral force against the side wall of the circular bore 62 of the electrical connector 60. In particular, due to the fact that the barb extends out vertically from the top of the body 30, the lateral force exerted by the barb 34 is also increased by any vertical force in a direction towards the top of the body 30, i.e., away from the mating connection with the PCB 50. As a consequence, the barbs 24 and 34 work together to limit any vertical movement of the electrical connector 60 and the PCB 50 away from each other.

- 12 -

As noted above, in the preferred embodiment of the invention, each body 20 and 30 of the hold-down 10 has a beveled edge 22 and 32 at its top. The beveled edge 22 and 32 is provided to facilitate the insertion of the body 20 or 30 into a structure by an individual without the aid of tools. As also noted above, the bodies are inserted into a circular bore of a structure having a diameter smaller than the diameter formed by the body 20 or 30. As a consequence, the body must be compressed prior or while being inserted into the circular bore of the structure.

The beveled edge 22 or 32 allows the body to be inserted partially into the circular bore of the structure without compression and then the necessary compression forces are generated by the walls of the circular bore of the structure when the body 20 or 30 is inserted further into the circular bore of the structure. As a consequence, an individual inserting the hold-down of the present invention into an electrical connector or PCB does not need to use a tool to compress the hold-down.

As also noted above, the first side wall portion 27 and 37 and second side wall portion 28 and 38 of a body 20 and 30 form a gap 29 and 39. The gap 29 and 39 enables the body to be compressed to a body having smaller diameter (the diameter formed by the smallest circle when encompasses the compressed body) during the insertion process into a circular bore of a structure having a diameter smaller than the uncompressed diameter formed by the smallest circle which encompasses a body 20 and 30.

The gap 29 and 39 also permits the exact diameter of the circular bore of the structure to be variable, i.e., not subject to strict tolerance, since, depending on the size of the gap 29 and 39, the diameter formed by the body 20 and 30 may be compressed to a range of sizes. As a consequence, the manufacturing costs of a electrical connector or PCB may be reduced since the precision required to generate the bores used to interconnect the devices need not be as great using a hold-down of the present invention.

- 13 -

Figure 4 shows lines of contact made between the body 20 when inserted into the circular bore 52 of the PCB 50, for example. As noted above, the diameter of the circular bore 52 of the PCB 50 is smaller than the uncompressed diameter formed by the smallest circle which encompasses the body 20 of the hold-down 10. As a consequence, portions of the body 20 exert a force against the side walls of the circular bore 52 of the PCB 50.

In particular, the end of the base portion 26 which is connected to the first side wall portion 27, forms a line of contact 72 with the side wall of the circular bore 52. As shown by the planar diagram, this line of contact exerts forces in the X-Y plane. The other end of the base portion 26 which is connected with the second side wall portion 28, also forms a line of contact 74 with the side wall of the circular bore 52. This line of contact also exerts forces in the X-Y plane.

The ends of the first side wall portion 27 and second side wall portion 28 also form lines of contact 76 and 78. These lines of contact 76 and 78 also exert forces in the X-Y plane. Similarly, the body 30 of the hold-down 10 exerts forces against the side walls of the circular bore 62 of the electrical connector 60 when inserted. As a consequence, the bodies 20 and 30 of the present invention are effective at limiting lateral movement of the PCB 50 relative to the interconnection of an electrical connector 60 to a PCB 50. The limitation of lateral movement is critical for certain forms of electrical connections including solderless electrical connections.

Figures 5a and 5b show a preferred method of manufacturing the first preferred embodiment of the hold-down 10 as shown in Figures 1-4. In particular, as shown in Figure 5a, the hold-down 10 is first stamped from metal, such as sheet metal, phosphor bronze, brass, stainless steel, or brilliant copper, into a flat piece of metal as shown in Figure 5a. The metal is flat except for the protrusion of the barbs as shown in Figure 5b.

- 14 -

To complete the manufacture of the hold-down 10 of the present invention, the bodies 20 and 30 of the hold-down are bent at the ends of the base portions 26 and 36 of the bodies 20 and 30 so that the first side wall portions 27 and 37 and the second side wall portions 28 and 38 extend at an acute angle relative to the base portion 26 and 36 towards a centerline formed by bisecting the base portion 26 and 36 and form a gap 29 and 39. Finally, the bodies are aligned along a common centerline (such as shown in Figure 1b) by offsetting the shoulder 40.

Thus, the hold-down 10 of the present invention may be easily formed by stamping out the pattern shown in Figures 5a and 5b and by folding side wall portions of the bodies 20 and 30 of the hold-down about the base portions 26 and 36 of the bodies 20 and 30 and aligning the bodies along a common centerline by offsetting the shoulder 40.

As noted above, an individual may insert the hold-down of the present invention into an electrical connector and a PCB with the aid of tools. In some particular applications, the alignment of the electrical connector to the PCB is critical, i.e., there is little tolerance. For example, if the electrical connector has a high density of pins, it may be necessary to use an alignment tool to aid in the interconnection of the electrical connector to the PCB to avoid possibly bending the pins or damaging the PCB.

Figures 6a, 6b, and 7 show a method of inserting the body 20 of the hold-down 10 into the circular bore 52 of a PCB 50 using an alignment tool 80 for special applications. As shown in these Figures, the alignment tool 80 is a spring loaded insertion tool 80 which is used to guide the insertion of the body 20 of the hold-down 10 into the circular bore 52 of the PCB 50 after the body 30 of the hold-down 10 has already been inserted into the electrical connector 60.

In particular, the insertion tool 80 is first inserted into the bore 52 so that the insertion pin 82 extends through the circular bore 52. The body 20 of the hold-down 10 is placed over the insertion pin 82 where the pin 82 fits within

- 15 -

the gap formed by the base portion 26, the first side wall portion 27, and the second side wall portion 28.

Downward pressure towards the PCB 50 is then applied against the electrical connector 60. When the pressure applied, the insertion pin 82 then guides the first body 20 of the hold-down 10 into the circular bore 52 of the PCB 50. As a consequence, the pins of the electrical connector 60 will be precisely aligned during the insertion process into the PCB 50 thus avoiding the possibility of bending pins or damaging the PCB 50.

Figure 6b is a top view of the process which shows the insertion pin 82 in the gap formed by the base portion 26, the first side wall portion 27, and the second side wall portion 28. Figure 7 is a side view of the insertion process shown in Figure 6a.

Figures Fig. 8a to 8d show a second preferred embodiment of the invention. In this embodiment of the invention, the hold-down 110 has barbs 124 and 134 extending from the base portions 26 and 36 that are triangular in shape. Similar to the barbs shown in Figures 1a to 1d, barbs 124 and 134 extend horizontally to a distance greater than or equal to the diameter formed by the smallest circle which encompasses the bodies of the hold-down 110. Additional modifications that may be to hold-down of the present invention to increase the lateral and vertical stability of the hold-down are shown in Figures 9a to 9c.

In particular, as shown in Figure 9a, one or more retentive bumps 224 may be added to one or more sides 27, 28, 37, and 38 of the hold-down 220. These bumps 224 increase the number of the points of contact between the hold-down of the present invention and the electrical connector 60 and the PCB 50. In addition, as shown in Figures 9b and 9c, respectively, stamped barbs 248 or interlocking barbs 268 may be formed on the edges of the sides 27, 28, 37, and 38 where the gap 29 or 39 is formed in the bodies 20 or 30 of a hold-down 240 or 260. These barbs 248 or 268 increase the number of the points of

- 16 -

contact between the hold-down of the present invention and the electrical connector 60 and the PCB 50.

Although, in the first preferred embodiment of the invention, the hold-down forms a substantially triangular shape when viewed from a horizontal perspective, hold-downs of other preferred embodiments of the invention may form other shapes when viewed from a horizontal perspective as shown in Figures 10a, 10b, 11a, and 11b. In particular, in Figures 10a and 10b, a third preferred embodiment of a hold-down 410 is shown which is rectangular in shape when viewed from a horizontal perspective.

As shown in Figure 10b, in the third preferred embodiment of the invention, the bodies have a substantially rectangular shape when viewed from a horizontal perspective of the hold-down. Each body includes a base portion 426, a first multiple side wall portion 427 and a second multiple side wall portion 438. The base portion 426 connects to the first multiple side wall portion 427 and the second multiple side wall portion 428 at the ends of the base portion.

The multiple side wall portions 427 and 428 are attached to the ends of the base portion 426 and form an L-shape from the base portion. The multiple side wall portions 427 and 428 extend toward a centerline formed by bisecting the base portion 426. Similar to the first preferred embodiment of the invention, the first multiple side wall portion 427 and second multiple side wall portion 428 form a gap 429.

The gap 429 enables the body to be compressed to a body having a smaller diameter (the diameter formed by the smallest circle when encompasses the compressed body) during the insertion process into a circular bore of a structure having a diameter smaller than the uncompressed diameter formed by the smallest circle which encompasses a body of the hold-down 410.

The gap 429 also permits the exact diameter of the circular bore of the structure to be variable, i.e., not subject to strict tolerance, since, depending on the size of the gap 429, the diameter formed by the body may be compressed

- 17 -

to a range of sizes. Another preferred of the invention is shown in Figures 11a and 11b.

Figures 11a and 11b show a fourth preferred embodiment of a hold-down 410 which is V shaped when viewed from a horizontal perspective. As shown in Figure 11b, in the third preferred embodiment of the invention, the bodies have a substantially V shape when viewed from a horizontal perspective of the hold-down. As for the other preferred embodiments of the invention, each body includes a base portion 526, a first side wall portion 527 and a second side wall portion 538. The base portion 526 connects to the first side wall portion 527 and the second side wall portion 528 at the ends of the base portion, thus the base portion 526 may only be the intersection of the side wall portions 527 and 528 so that, in effect, the bodies of the hold-down 510 are formed from only two sides.

The side wall portions 527 and 528 are attached to the ends of the base portion 526 and at an obtuse angle from the base portion. The side wall portions 527 and 528 extend away from a centerline formed by bisecting the base portion 526. Similar to the other preferred embodiments of the invention, the first side wall portion 527 and second side wall portion 528 form a gap 529.

The gap 529 also enables the body to be compressed to a body having smaller diameter (the diameter formed by the smallest circle when encompasses the compressed body) during the insertion process into a circular bore of a structure having a diameter smaller than the uncompressed diameter formed by the smallest circle which encompasses a body of the hold-down 510.

The gap 529 also permits the exact diameter of the circular bore of the structure to be variable, i.e., not subject to strict tolerance, since, depending on the size of the gap 529, the diameter formed by the body may be compressed to a range of sizes.

Although not shown in Figures 10a, 10b, 11a and 11b, these embodiments of the invention may also have barbs as

- 18 -

illustrated in Figures 1a to 1d or 8a to 8d or retentive bumps or stamped barbs as shown in Figures 9a to 9c.

It will be evident that other embodiments of the hold-down are possible without departing from the scope of the invention. For example, a hold-down capable of interconnecting a right angle electrical connector to a PCB may be formed by extending the length of the shoulder 340 of the hold-down 310 of the present invention and bending the shoulder to form a right angle as shown in Figure 12. The bodies 330 and 320 of the hold-down 310 as shown in Figure 12 extend at right angles from the shoulder portion 340. In addition, the hold-down may have a conventional hold-down such as a rivet or bolt attached to a body 20 or 30 of the present invention. In addition, an electrical connector may have a body 20 or 30 extending from a portion to engage another connector or printed circuit board and thus have a single body hold-down.



- 19 -

What is claimed is:

THIS SHEET HAS BEEN REPLACED

1. A hold-down for interconnecting a structure via a circular bore within the structure, said hold-down comprising:

5 a body having a base portion, a first side portion, and a second side portion forming the body where the diameter of the smallest circle which encompasses the body is greater than the diameter of the circular bore within the structure and the body having a gap formed between the ends of the first side
10 portion and second side portion so that the diameter of the smallest circle which encompasses the body may be made smaller than the diameter of the circular bore within the structure so that the body of the hold-down may be inserted into the circular bore within the structure,

15 thereby, the body of the hold-down provides a plurality of points of contact against side walls of the circular bore within the structure when the body of the hold-down is inserted in the bore because the diameter of the smallest circle that encompasses the body of the hold-down is
20 greater than the diameter of the bore.

2. The hold-down according to claim 1, wherein the body has a beveled edge for easing the insertion of the body of the hold-down into the circular bore of the structure.

3. The hold-down according to claim 1, wherein the base portion has a barb extending vertically from the end to be inserted in the circular bore of the structure and projecting outwardly from the body as it extends vertically so that the
5 barb prevents vertical movement of the hold-down once inserted into the circular bore of the structure.

4. The hold-down according to claim 2, wherein the base portion has a barb extending vertically from the end to be inserted in the circular bore of the structure and projecting outwardly from the body as it extends vertically so that the





THIS SHEET HAS BEEN
REPLACED

barb prevents vertical movement of the hold-down once inserted into the circular bore of the structure.

5. The hold-down according to claim 4, wherein the structure is an electrical connector.

6. The hold-down according to claim 4, wherein the structure is a circuit board.

7. The hold-down according to claim 1, wherein the hold-down has a second body connected to the body of the hold-down for interconnecting a second structure via a circular bore within the second structure to the structure interconnected by
5 the body of the hold-down,

the second body having a base portion, a first side portion, and a second side portion forming the second body where the diameter of the smallest circle which encompasses the second body is greater than the diameter of the circular bore
10 within the second structure and the second body having a gap formed between the ends of the first side portion and second side portion so that the diameter of the smallest circle which encompasses the second body may be made smaller than the diameter of the circular bore within the second structure so
15 that the second body of the hold-down may be inserted into the circular bore within the second structure,

thereby, the second body of the hold-down provides a plurality of points of contact against side walls of the circular bore within the second structure when the second body
20 of the hold-down is inserted in the bore of the second structure because the diameter of the smallest circle which encompasses the second body is greater than the diameter of the bore of the second structure so that the structure and the second structure are interconnected by the body and the second
25 body of the hold-down.

This Sheet Has Been Replaced





THIS SHEET HAS BEEN
REPLACED

- 21 -

8. The hold-down according to claim 7, wherein the body has a beveled edge for easing the insertion of the body of the hold-down into the circular bore of the structure.

9. The hold-down according to claim 8, wherein the second body has a beveled edge for easing the insertion of the second body of the hold-down into the circular bore of the second structure.

10. The hold-down according to claim 7, wherein the base portion of the body has a barb extending vertically from the end to be inserted in the circular bore of the structure and projecting outwardly from the body as it extends vertically so that the barb prevents vertical movement of the body of the hold-down once inserted into the circular bore of the structure.

11. The hold-down according to claim 10, wherein the base portion of the second body has a barb extending vertically from the end to be inserted in the circular bore of the second structure and projecting outwardly from the second body as it extends vertically so that the barb prevents vertical movement of the second body of the hold-down once inserted into the circular bore of the second structure.

12. The hold-down according to claim 11, wherein a portion of the body has a retentive bump extending from the portion so that the bump prevents vertical movement of the body of the hold-down once inserted into the circular bore of the structure.

13. The hold-down according to claim 12, wherein a portion of the second body has a retentive bump extending from the portion so that the bump prevents vertical movement of the second body of the hold-down once inserted into the circular bore of the second structure.

This Sheet Has Been Replaced





THIS SHEET HAS BEEN
REPLACED

14. The hold-down according to claim 11, wherein the first and second side portions of the body have stamped barbs extending from the portions so that the barbs prevent vertical and lateral movement of the body of the hold-down once inserted
5 into the circular bore of the structure.

15. The hold-down according to claim 14, wherein the first and the second side portions of the second body have stamped barbs extending from the portions so that the barbs prevent vertical and lateral movement of the second body of the
5 hold-down once inserted into the circular bore of the second structure.

16. The hold-down according to claim 13, wherein the structure is an electrical connector and the second structure is a circuit board.

17. The hold-down according to claim 4, wherein the diameter of the smallest circle which encompasses the body is smaller than the diameter of the smallest circle which encompasses the second body.

18. The hold-down according to claim 17, wherein the body is connected to the second body by a shoulder which is offset so that the body and second body are aligned along a common centerline.

19. The hold-down according to claim 1, wherein the body is substantially triangular in shape when viewed from a horizontal perspective.

20. The hold-down according to claim 1, wherein the body is substantially rectangular in shape when viewed from a horizontal perspective.

This Sheet Has Been Replaced





THIS SHEET HAS BEEN
REPLACED

21. The hold-down according to claim 1, wherein the body is substantially V-shaped when viewed from a horizontal perspective.

22. A hold-down for interconnecting a structure via a circular bore within the structure, said hold-down comprising:

a body having a plurality of portions forming the body
5 where the diameter of the smallest circle which encompasses the body is greater than the diameter of the circular bore within the structure and the body having a gap formed between the ends of portions of the body so that the diameter of the smallest circle which encompasses the body may be made smaller than the
10 diameter of the circular bore within the structure so that the body of the hold-down may be inserted into the circular bore within the structure,

thereby, the body of the hold-down provides a plurality of points of contact against side walls of the
15 circular bore within the structure when the body of the hold-down is inserted in the bore because the diameter of the smallest circle that encompasses the body of the hold-down is greater than the diameter of the bore.

23. The hold-down according to claim 22, wherein the body has a beveled edge for easing the insertion of the body of the hold-down into the circular bore of the structure.

24. The hold-down according to claim 22, wherein a portion has a barb extending vertically from the end to be inserted in the circular bore of the structure and projecting outwardly from the body as it extends vertically so that the
5 barb prevents vertical movement of the hold-down once inserted into the circular bore of the structure.

25. The hold-down according to claim 23, wherein the base portion has a barb extending vertically from the end to be inserted in the circular bore of the structure and projecting





THIS SHEET HAS BEEN
REPLACED

- 24

outwardly from the body as it extends vertically so that the barb prevents vertical movement of the hold-down once inserted into the circular bore of the structure.

26. The hold-down according to claim 25, wherein the structure is an electrical connector.

27. The hold-down according to claim 25, wherein the structure is a circuit board.

28. The hold-down according to claim 22, wherein the hold-down has a second body connected to the body of the hold-down for interconnecting a second structure via a circular bore within the second structure to the structure interconnected by
5 the body of the hold-down,

the second body having a plurality of portions forming the second body where the diameter of the smallest circle which encompasses the second body is greater than the diameter of the circular bore within the second structure and the second body
10 having a gap formed between the ends of portions of the second body so that the diameter of the smallest circle which encompasses the second body may be made smaller than the diameter of the circular bore within the second structure so that the second body of the hold-down may be inserted into the
15 circular bore within the second structure,

thereby, the second body of the hold-down provides a plurality of points of contact against side walls of the circular bore within the second structure when the second body of the hold-down is inserted in the bore of the second
20 structure because the diameter of the smallest circle which encompasses the second structure of the hold-down is greater than the diameter of the bore of the second structure so that the structure and the second structure are interconnected by the body and the second body of the hold-down.

This Sheet Has Been Replaced





THIS SHEET HAS BEEN
REPLACED

29. The hold-down according to claim 28, wherein the body has a beveled edge for easing the insertion of the body of the hold-down into the circular bore of the structure.

30. The hold-down according to claim 29, wherein the second body has a beveled edge for easing the insertion of the second body of the hold-down into the circular bore of the second structure.

31. The hold-down according to claim 28, wherein a portion of the body has a barb extending vertically from the end to be inserted in the circular bore of the structure and projecting outwardly from the body as it extends vertically so
5 that the barb prevents vertical movement of the body of the hold-down once inserted into the circular bore of the structure.

32. The hold-down according to claim 31, wherein a portion of the second body has a barb extending vertically from the end to be inserted in the circular bore of the second structure and projecting outwardly from the second body as it
5 extends vertically so that the barb prevents vertical movement of the second body of the hold-down once inserted into the circular bore of the second structure.

33. The hold-down according to claim 32, wherein a portion of the body has a retentive bump extending from the portion so that the bump prevents vertical movement of the body of the hold-down once inserted into the circular bore of the
5 structure.

34. The hold-down according to claim 33, wherein a portion of the second body has a retentive bump extending from the portion so that the bump prevents vertical movement of the second body of the hold-down once inserted into the circular
5 bore of the second structure.

This Sheet Has Been Replaced





THIS SHEET HAS BEEN
REPLACED

35. The hold-down according to claim 32, wherein portions of the body which form the gap have stamped barbs extending from the portions so that the barbs prevent vertical and lateral movement of the body of the hold-down once inserted
5 into the circular bore of the structure.

36. The hold-down according to claim 35, wherein portions of the second body which form the gap have stamped barbs extending from the portions so that the barbs prevent vertical and lateral movement of the second body of the hold-
5 down once inserted into the circular bore of the second structure.

37. The hold-down according to claim 32, wherein the structure is an electrical connector and the second structure is a circuit board.

38. The hold-down according to claim 25, wherein the diameter of the smallest circle which encompasses the body is smaller than the diameter of the smallest circle which encompasses the second body.

39. The hold-down according to claim 38, wherein the body is connected to the second body by a shoulder which is offset so that the body and second body are aligned along a common centerline.

40. The hold-down according to claim 22, wherein the body is substantially triangular in shape when viewed from a horizontal perspective.

41. The hold-down according to claim 22, wherein the body is substantially rectangular in shape when viewed from a horizontal perspective.





THIS SHEET HAS BEEN
REPLACED

42. The hold-down according to claim 22, wherein the body is substantially V-shaped when viewed from a horizontal perspective.

43. A hold-down for interconnecting a first structure to a second structure via a circular bore within the first structure and a circular bore within the second structure, said hold-down comprising:

5 a first body having a plurality of portions forming the first body where the diameter of the smallest circle which encompasses the first body is greater than the diameter of the circular bore within the first structure and the first body having a gap formed between the ends of portions of the first
10 body so that the diameter of the smallest circle which encompasses the first body may be made smaller than the diameter of the circular bore within the first structure so that the first body of the hold-down may be inserted into the circular bore within the first structure;

15 a second body having a plurality of portions forming the second body where the diameter of the smallest circle which encompasses the second body is greater than the diameter of the circular bore within the second structure and the second body having a gap formed between the ends of portions of the second
20 body so that the diameter of the smallest circle which encompasses the second body may be made smaller than the diameter of the circular bore within the second structure so that the second body of the hold-down may be inserted into the circular bore within the second structure where the diameter of
25 the smallest circle which encompasses the first body is smaller than the diameter of the smallest circle which encompasses the second body; and

 a shoulder connecting the first body to the second body where the shoulder is offset so that the first body and
30 the second body are aligned along a common centerline.

This Sheet Has Been Replaced





THIS SHEET HAS BEEN
REPLACED

- 28 -

44. The hold-down according to claim 43, wherein the first structure is an electrical connector and the second structure is a circuit board.

45. The hold-down according to claim 44, wherein the first body has a beveled edge for easing the insertion of the first body of the hold-down into the circular bore of the first structure and the second body has a beveled edge for easing the
5 insertion of the second body of the hold-down into the circular bore of the second structure.

46. The hold-down according to claim 45, wherein a portion of the first body has a barb extending vertically from the end to be inserted in the circular bore of the first structure and projecting outwardly from the body as it extends
5 vertically so that the barb prevents vertical movement of the first body of the hold-down once inserted into the circular bore of the first structure and a portion of the second body has a barb extending vertically from the end to be inserted in the circular bore of the second structure and projecting
10 outwardly from the second body as it extends vertically so that the barb prevents vertical movement of the second body of the hold-down once inserted into the circular bore of the second structure.

47. The hold-down according to claim 46, wherein the body and the second body are substantially triangular in shape when viewed from a horizontal perspective.

48. The hold-down according to claim 47, wherein the body and the second body are substantially rectangular in shape when viewed from a horizontal perspective.

49. The hold-down according to claim 48, wherein the body and the second body are substantially V-shaped when viewed from a horizontal perspective.

This Sheet Has Been Replaced





AMENDED CLAIMS

[received by the International Bureau on 8 November 1995 (08.11.95);
original claims 1, 7, 17-22, 28 and 38-43 amended;
remaining claims unchanged (10 pages)]

THIS SHEET HAS BEEN
REPLACED

1. A hold-down for interconnecting a structure via a circular bore within the structure, said hold-down comprising:

5 a body having a base portion, a first side portion, and a second side portion forming the body wherein the body is substantially triangular in shape when viewed from a horizontal perspective, the diameter of the smallest circle which encompasses the body when viewed from a horizontal perspective
10 is greater than the diameter of the circular bore within the structure and the body having a gap formed between the ends of the first side portion and second side portion so that the diameter of the smallest circle which encompasses the body may be made smaller than the diameter of the circular bore within
15 the structure so that the body of the hold-down may be inserted into the circular bore within the structure, and the body of the hold-down provides a plurality of points of contact against side walls of the circular bore within the structure when the body of the hold-down is inserted in the bore because the
20 diameter of the smallest circle that encompasses the body of the hold-down is greater than the diameter of the bore prior to insertion into the bore.

2. The hold-down according to claim 1, wherein the body has a beveled edge for easing the insertion of the body of the hold-down into the circular bore of the structure.

3. The hold-down according to claim 1, wherein the base portion has a barb extending vertically from the end to be inserted in the circular bore of the structure and projecting outwardly from the body as it extends vertically so that the
5 barb prevents vertical movement of the hold-down once inserted into the circular bore of the structure.

4. The hold-down according to claim 2, wherein the base portion has a barb extending vertically from the end to be

This Sheet Has Been Replaced



AMENDED SHEET (ARTICLE 19)



THIS SHEET HAS BEEN
REPLACED

inserted in the circular bore of the structure and projecting outwardly from the body as it extends vertically so that the

This Sheet Has Been Replaced





THIS SHEET HAS BEEN
REPLACED

barb prevents vertical movement of the hold-down once inserted into the circular bore of the structure.

5. The hold-down according to claim 4, wherein the structure is an electrical connector.

6. The hold-down according to claim 4, wherein the structure is a circuit board.

7. The hold-down according to claim 1, wherein the hold-down has a second body connected to the body of the hold-down for interconnecting a second structure via a circular bore within the second structure to the structure interconnected by
5 the body of the hold-down,

the second body having a base portion, a first side portion, and a second side portion forming the second body wherein the diameter of the smallest circle which encompasses the second body when viewed from a horizontal perspective is
10 greater than the diameter of the circular bore within the second structure and the second body having a gap formed between the ends of the first side portion and second side portion so that the diameter of the smallest circle which encompasses the second body may be made smaller than the
15 diameter of the circular bore within the second structure so that the second body of the hold-down may be inserted into the circular bore within the second structure and the second body of the hold-down provides a plurality of points of contact against side walls of the circular bore within the second
20 structure when the second body of the hold-down is inserted in the bore of the second structure because the diameter of the smallest circle which encompasses the second body is greater than the diameter of the bore of the second structure prior to insertion into the bore of the second structure so that the
25 structure and the second structure are interconnected by the body and the second body of the hold-down.

This Sheet Has Been Replaced





-32-

THIS SHEET HAS BEEN
REPLACED

14. The hold-down according to claim 11, wherein the first and second side portions of the body have stamped barbs extending from the portions so that the barbs prevent vertical and lateral movement of the body of the hold-down once inserted
5 into the circular bore of the structure.

15. The hold-down according to claim 14, wherein the first and the second side portions of the second body have stamped barbs extending from the portions so that the barbs prevent vertical and lateral movement of the second body of the
5 hold-down once inserted into the circular bore of the second structure.

16. The hold-down according to claim 13, wherein the structure is an electrical connector and the second structure is a circuit board.

17. The hold-down according to claim 7, wherein the diameter of the smallest circle which encompasses the body is smaller than the diameter of the smallest circle which encompasses the second body.

5 18. The hold-down according to claim 17, wherein the body is connected to the second body by a shoulder which is offset relative to the longitudinal axis of the body and the longitudinal axis of the second axis so that the body and second body are aligned along a common centerline.

10 19. The hold-down according to claim 7, wherein the second body is substantially triangular in shape when viewed from a horizontal perspective.

20. The hold-down according to claim 7, wherein the second body is substantially rectangular in shape when viewed
15 from a horizontal perspective.

This Sheet Has Been Replaced





THIS SHEET HAS BEEN
REPLACED

-33-

21. The hold-down according to claim 7, wherein the second body is substantially V-shaped when viewed from a horizontal perspective.

22. A hold-down for interconnecting a structure via
5 a circular bore within the structure, said hold-down comprising:

a body having a plurality of portions forming the body wherein the body is substantially triangular in shape when viewed from a horizontal perspective, the diameter of the
10 smallest circle which encompasses the body when viewed from a horizontal perspective is greater than the diameter of the circular bore within the structure and the body having a gap formed between the ends of portions of the body so that the diameter of the smallest circle which encompasses the body may
15 be made smaller than the diameter of the circular bore within the structure so that the body of the hold-down may be inserted into the circular bore within the structure and the body of the hold-down provides a plurality of points of contact against side walls of the circular bore within the structure when the
20 body of the hold-down is inserted in the bore because the diameter of the smallest circle that encompasses the body of the hold-down is greater than the diameter of the bore prior to insertion into the bore.

23. The hold-down according to claim 22, wherein the body has a beveled edge for easing the insertion of the body of the hold-down into the circular bore of the structure.

24. The hold-down according to claim 22, wherein a portion has a barb extending vertically from the end to be inserted in the circular bore of the structure and projecting outwardly from the body as it extends vertically so that the
5 barb prevents vertical movement of the hold-down once inserted into the circular bore of the structure.

This Sheet Has Been Replaced



AMENDED SHEET (ARTICLE 19)



-34-

THIS SHEET HAS BEEN
REPLACED

25. The hold-down according to claim 23, wherein the base portion has a barb extending vertically from the end to be inserted in the circular bore of the structure and projecting outwardly from the body as it extends vertically so that the
5 barb prevents vertical movement of the hold-down once inserted into the circular bore of the structure.

26. The hold-down according to claim 25, wherein the structure is an electrical connector.

27. The hold-down according to claim 25, wherein the structure is a circuit board.

28. The hold-down according to claim 22, wherein the hold-down has a second body connected to the body of the hold-down for interconnecting a second structure via a circular bore within the second structure to the structure interconnected by
5 the body of the hold-down,

the second body having a plurality of portions forming the second body wherein the diameter of the smallest circle which encompasses the second body when viewed from a horizontal perspective is greater than the diameter of the circular bore
10 within the second structure and the second body having a gap formed between the ends of the first side portion and second side portion so that the diameter of the smallest circle which encompasses the second body may be made smaller than the diameter of the circular bore within the second structure so
15 that the second body of the hold-down may be inserted into the circular bore within the second structure and the second body of the hold-down provides a plurality of points of contact against side walls of the circular bore within the second structure when the second body of the hold-down is inserted in
20 the bore of the second structure because the diameter of the smallest circle which encompasses the second body is greater than the diameter of the bore of the second structure prior to insertion into the bore of the second structure so that the

This Sheet Has Been Replaced



AMENDED SHEET (ARTICLE 19)



THIS SHEET HAS BEEN
REPLACED

structure and the second structure are interconnected by the
body and the second body of the hold-down.

This Sheet Has Been Replaced





-36-

THIS SHEET HAS BEEN
REPLACED

35. The hold-down according to claim 32, wherein portions of the body which form the gap have stamped barbs extending from the portions so that the barbs prevent vertical and lateral movement of the body of the hold-down once inserted
5 into the circular bore of the structure.

36. The hold-down according to claim 35, wherein portions of the second body which form the gap have stamped barbs extending from the portions so that the barbs prevent vertical and lateral movement of the second body of the hold-
5 down once inserted into the circular bore of the second structure.

37. The hold-down according to claim 32, wherein the structure is an electrical connector and the second structure is a circuit board.

38. The hold-down according to claim 28, wherein the diameter of the smallest circle which encompasses the body is smaller than the diameter of the smallest circle which encompasses the second body.

5 39. The hold-down according to claim 38, wherein the body is connected to the second body by a shoulder which is offset relative to the longitudinal axis of the body and the longitudinal axis of the second axis so that the body and second body are aligned along a common centerline.

10 40. The hold-down according to claim 28, wherein the second body is substantially triangular in shape when viewed from a horizontal perspective.

41. The hold-down according to claim 28, wherein the second body is substantially rectangular in shape when viewed
15 from a horizontal perspective.

This Sheet Has Been Replaced





THIS SHEET HAS BEEN
REPLACED

-37-

42. The hold-down according to claim 28, wherein the second body is substantially V-shaped when viewed from a horizontal perspective.

43. A hold-down for interconnecting a first structure
5 to a second structure via a circular bore within the first structure and a circular bore within the second structure, said hold-down comprising:

a first body having a plurality of portions forming the first body wherein the diameter of the smallest circle
10 which encompasses the first body when viewed from a horizontal perspective is greater than the diameter of the circular bore within the first structure and the first body having a gap formed between the ends of portions of the first body so that the diameter of the smallest circle which encompasses the first
15 body may be made smaller than the diameter of the circular bore within the first structure so that the first body of the hold-down may be inserted into the circular bore within the first structure prior to insertion into the bore;

a second body having a plurality of portions forming
20 the second body wherein the diameter of the smallest circle which encompasses the second body when viewed from a horizontal perspective is greater than the diameter of the circular bore within the second structure and the second body having a gap formed between the ends of portions of the second body so that
25 the diameter of the smallest circle which encompasses the second body may be made smaller than the diameter of the circular bore within the second structure prior to insertion into the bore so that the second body of the hold-down may be inserted into the circular bore within the second structure and
30 the diameter of the smallest circle which encompasses the first body is smaller than the diameter of the smallest circle which encompasses the second body; and

a shoulder connecting the first body to the second body wherein the shoulder is offset relative to the
35 longitudinal axis of the body and the longitudinal axis of the

This Sheet Has Been Replaced





THIS SHEET HAS BEEN
REPLACED

-38-

second axis so that the first body and the second body are aligned along a common centerline.

This Sheet Has Been Replaced



STATEMENT UNDER ARTICLE 19

Replacement pages 19, 19/1, 20, 22, 23, 24, 24/1, 26, 27, and 27/1 submitted herewith contain amended claims 1, 7, 17-22, 28 and 38-43. These claims have been amended to correspond to amendments entered in the U.S. priority application. No new matter has been added. Claims 2-6, 8-16, 23-27, 29-37 and 44-49 have not been amended. Entry of the replacement pages is respectfully requested.

1/12




FIG. 1d




FIG. 1a




FIG. 1c




FIG. 1b




FIG. 2c

FIG. 2a

FIG. 2b

3/12




FIG. 3c




FIG. 3a




FIG. 3b

4/12





FIG. 4

5/12




FIG. 5a






FIG. 5b

6/12

*FIG. 6a**FIG. 6b*

7/12




FIG. 7

8/12




FIG. 8d




FIG. 8a




FIG. 8b




FIG. 8c

9/12

220




FIG. 9a

240




FIG. 9b

260






FIG. 9c

10/12

410*FIG. 10a*410*FIG. 10b*

11/12

510




FIG. 11a

510





FIG. 11b

12/12

**FIG. 12**



- 19 -

REPLACEMENT SHEET

Date : 20 JAN 1998

What is claimed is:

1. A hold-down for interconnecting a first structure to a second structure via a circular bore within the first structure and a circular bore within the second structure, said hold-down comprising:

a first body having a base portion, a first side portion, and a second side portion forming the first body wherein the diameter of the smallest circle which encompasses the first body is greater than the diameter of the circular bore within the first structure, and the first body having a gap formed between ends of the first side portion and second side portion so that the diameter of the smallest circle which encompasses the first body may be made smaller than the diameter of the circular bore within the first structure so that the first body of the hold-down may be inserted into the circular bore within the first structure,

a second body having a base portion, a first side portion, and a second side portion forming the second body wherein the diameter of the smallest circle which encompasses the second body is greater than the diameter of the circular bore within the second structure, and the second body having a gap formed between ends of the first side portion and second side portion so that the diameter of the smallest circle which encompasses the second body may be made smaller than the diameter of the circular bore within the second structure so that the second body of the hold-down may be inserted into the circular bore within the second structure,


said first and second structures are interconnected by the first and second bodies of the hold down wherein each body of the hold-down provides a plurality of points of contact against side walls of the circular bore within the structures when the body of the hold-down is inserted in the bore because the diameter of the smallest circle that encompasses the body of the hold-down is greater than the diameter of the bore prior to insertion into the bore.

2. The hold-down according to claim 1, wherein the first body has a beveled edge for easing the insertion of the first body of the hold-down into the circular bore of the structure.

REPLACEMENT SHEET



- 20 -



3. The hold-down according to claim 2, wherein the second body has a beveled edge for easing the insertion of the second body of the hold-down into the circular bore of the second structure.

4. The hold-down according to claim 1, wherein the base portion of the first body has a barb extending vertically from the end to be inserted in the circular bore of the first structure and projecting outwardly from the first body as it extends vertically so that the barb prevents vertical movement of the first body of hold-down once inserted into the circular bore of the first structure.

5. The hold-down according to claim 4, wherein the base portion of the second body has a barb extending vertically from the end to be inserted in the circular bore of the second structure and projecting outwardly from the second body as it extends vertically so that the barb prevents vertical movement of the second body of the hold-down once inserted into the circular bore of the second structure.

6. The hold-down according to claim 5, wherein a portion of the first body has a retentive bump extending from the portion so that the bump prevents vertical movement of the first body of the hold-down once inserted into the circular bore of the first structure.

7. The hold-down according to claim 6, wherein a portion of the second body has a retentive bump extending from the portion so that the bump prevents vertical movement of the second body of the hold-down once inserted into the circular bore of the second structure.

8. The hold-down according to claim 5, wherein the first and second side portions of the first body have stamped barbs extending from the portions so that the barbs prevent vertical and lateral movement of the first body of the hold-down once inserted into the circular bore of the structure.



REPLACEMENT SHEET

REPLACEMENT SHEET
20 JAN 1998
Date

- 21 -

9. The hold-down according to claim 8, wherein the first and the second side portions of the second body have stamped barbs extending from the portions so that the barbs prevent vertical and lateral movement of the second body of the hold-down once inserted into the circular bore of the second structure.

10. The hold-down according to claim 7, wherein the first structure is an electrical connector and the second structure is a circuit board.

11. The hold-down according to claim 1, wherein the diameter of the smallest circle which encompasses the first body is smaller than the diameter of the smallest circle which encompasses the second body.

12. The hold-down according to claim 11, wherein the first body is connected to the second body by a shoulder which aligns the first body and the second body along a common centerline.

13. The hold-down according to claim 1, wherein at least one of the bodies is substantially triangular in shape when viewed from a horizontal perspective.

14. A hold-down for interconnecting a first structure to a second structure via a circular bore within the first structure and a circular bore within the second structure, said hold-down comprising:

a first body having a plurality of portions forming the first body wherein the diameter of the smallest circle which encompasses the first body is greater than the diameter of the circular bore within the first structure, and the first body having a gap formed between the ends of portions of the first body so that the diameter of the smallest circle which encompasses the first body may be made smaller than the diameter of the circular bore within the first structure so that the first body of the hold-down may be inserted into the circular bore within the first structure,



- 22 -

REPLACEMENT SHEET

Date 20 JAN 1998

a second body having a plurality of portions forming the second body wherein the diameter of the smallest circle which encompasses the second body is greater than the diameter of the circular bore within the second structure, and the second body having a gap formed between ends of portions of the second body so that the diameter of the smallest circle which encompasses the second body may be made smaller than the diameter of the circular bore within the second structure so that the body of the hold-down may be inserted into the circular bore within the second structure,

said first and second structures are interconnected by the first and second bodies of the hold down wherein each body of the hold-down provides a plurality of points of contact against side walls of the circular bore within the structures when the body of the hold-down is inserted in the bore because the diameter of the smallest circle that encompasses the body of the hold-down is greater than the diameter of the bore prior to insertion into the bore.

15. The hold-down according to claim 14, wherein the first body has a beveled edge for easing the insertion of the first body of the hold-down into the circular bore of the structure.

16. The hold-down according to claim 15, wherein the second body has a beveled edge for easing the insertion of the second body of the hold-down into the circular bore of the second structure.

17. The hold-down according to claim 14, wherein the base portion of the first body has a barb extending vertically from the end to be inserted in the circular bore of the first structure and projecting outwardly from the first body as it extends vertically so that the barb prevents vertical movement of the first body of the hold-down once inserted into the circular bore of the first structure.



Date : 20 JAN 1998

18. The hold-down according to claim 17, wherein a portion of the second body has a barb extending vertically from the end to be inserted in the circular bore of the second structure and projecting outwardly from the second body as it extends vertically so that the barb prevents vertical movement of the second body of the hold-down once inserted into the circular bore of the second structure.

19. The hold-down according to claim 18, wherein a portion of the first body has a retentive bump extending from the portion so that the bump prevents vertical movement of the first body of the hold-down once inserted into the circular bore of the structure.

20. The hold-down according to claim 19, wherein a portion of the second body has a retentive bump extending from the portion so that the bump prevents vertical movement of the second body of the hold-down once inserted into the circular bore of the second structure.

21. The hold-down according to claim 18, wherein portions of the first body which form the gap have stamped barbs extending from the portions so that the barbs prevent vertical and lateral movement of the first body of the hold-down once inserted into the circular bore of the first structure.

22. The hold-down according to claim 21, wherein portions of the second body which form the gap have stamped barbs extending from the portions so that the barbs prevent vertical and lateral movement of the second body of the hold-down once inserted into the circular bore of the second structure.

23. The hold-down according to claim 18, wherein the first structure is an electrical connector and the second structure is a circuit board.

24. The hold-down according to claim 14, wherein at least one of the bodies is substantially triangular in shape when viewed from a horizontal perspective.



REPLACEMENT SHEET

- 24 -

REPLACEMENT SHEET

Date 20 JAN 1998

25. The hold-down according to claim 14, wherein at least one of the bodies is substantially rectangular in shape when viewed from a horizontal perspective.

26. The hold-down according to claim 14, wherein at least one of the bodies is substantially V-shaped when viewed from a horizontal perspective.

27. A hold-down for interconnecting a first structure to a second structure via a circular bore within the first structure and a circular bore within the second structure, said hold-down comprising:

a first body having a plurality of portions forming the first body wherein the diameter of the smallest circle which encompasses the first body when viewed from a horizontal perspective is greater than the diameter of the circular bore within the first structure and the first body having a gap formed between the ends of portions of the first body so that the diameter of the smallest circle which encompasses the first body may be made smaller than the diameter of the circular bore within the first structure so that the first body of the hold-down may be inserted into the circular bore within the first structure prior to insertion into the bore;

a second body having a plurality of portions forming the second body wherein the diameter of the smallest circle which encompasses the second body when viewed from a horizontal perspective is greater than the diameter of the circular bore within the second structure and the second body having a gap formed between the ends of portions of the second body so that the diameter of the smallest circle which encompasses the second body may be made smaller than the diameter of the circular bore within the second structure prior to insertion into the bore so that the second body of the hold-down may be inserted into the circular bore within the second structure and the diameter of the smallest circle which encompasses the first body is smaller than the diameter of the smallest circle which encompasses the second body; and

a shoulder connecting the first body to the second body wherein the shoulder is offset relative to the longitudinal axis of the body and the longitudinal axis of the second axis so that the first body and the second body are aligned along a common centerline.



REPLACEMENT SHEET

- 25 -

REPLACEMENT SHEET
20 JAN 1998
Date :

28. The hold-down according to claim 27, wherein the first structure is an electrical connector and the second structure is a circuit board.

29. The hold-down according to claim 28, wherein the first body has a beveled edge for easing the insertion of the first body of the hold-down into the circular bore of the first structure and the second body has a beveled edge for easing the insertion of the second body of the hold-down into the circular bore of the second structure.

30. The hold-down according to claim 29, wherein a portion of the first body has a barb extending vertically from the end to be inserted in the circular bore of the first structure and projecting outwardly from the body as it extends vertically so that the barb prevents vertical movement of the first body of the hold-down once inserted into the circular bore of the first structure and a portion of the second body has a barb extending vertically from the end to be inserted in the circular bore of the second structure and projecting outwardly from the second body as it extends vertically so that the barb prevents vertical movement of the second body of the hold-down once inserted into the circular bore of the second structure.

31. The hold-down according to claim 30, wherein the first body and the second body are substantially triangular in shape when viewed from a horizontal perspective.

32. The hold-down according to claim 30, wherein the first body and the second body are substantially rectangular in shape when viewed from a horizontal perspective.

33. The hold-down according to claim 31, wherein the first body and the second body are substantially V-shaped when viewed from a horizontal perspective.

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H01R 13/73	A1	(11) International Publication Number: WO 96/02963 (43) International Publication Date: 1 February 1996 (01.02.96)
(21) International Application Number: PCT/US95/09125 (22) International Filing Date: 19 July 1995 (19.07.95) (30) Priority Data: 08/277,989 20 July 1994 (20.07.94) US (71) Applicant: BERG TECHNOLOGY, INC. [US/US] ; One East First Street, Reno, NV 89501 (US). (72) Inventor: HORCHLER, David, C. ; 423 Berrysburg Road, Millersburg, PA 17061 (US). (74) Agents: DONOHUE, John, P., Jr. et al. ; Woodcock Washburn Kurtz Mackiewicz & Norris, 46th floor, One Liberty Place, Philadelphia, PA 19103 (US).	(81) Designated States: JP, KR, SG, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report. With amended claims and statement.	

(54) Title: ELECTRICAL CONNECTOR HOLD-DOWN

(57) Abstract

A hold-down (10) for interconnecting an electrical connector (60) and a printed circuit board (50) where the hold-down has two bodies (20, 30) which have multiple sides. When the bodies of the hold-down are inserted into the circular bores (62, 52) of the electrical connector and printed circuit board, the bodies form several points of contact which resist lateral and vertical movement of the interconnection between the electrical connector and PCB.

