

DESCRIPTION

TRAIN INFORMATION MANAGEMENT DEVICE

5 TECHNICAL FIELD

[0001] The present invention relates to a train
information management device that performs high-order
priority processing of brake command information output
from a train safety control device and the like, and
10 selects a brake command to output the command.

BACKGROUND ART

[0002] An automatic train control (ATC) system has
conventionally been known in which an on-train device makes
15 a deceleration pattern based on information on distance
from a preceding train to a next train detected by a ground
device, and that controls braking of the train according to
this deceleration pattern.

[0003] An ATC system described in Patent Document 1 has
20 three processing units each of which performs the same
processing in parallel and outputs a brake notch, and a
common unit that compares the brake notches output from
these three processing units to determine a brake notch.
The brake notch includes three types of brakes, normal
25 braking, emergency braking, and brake ease, and stepwise
notch numbers for normal braking. The common unit is
configured to first make a selection from among the brake
types output from the three processing units based on
majority rule, and then, to select the largest notch number
30 (that is, high-order priority) when normal braking is
selected, and select emergency braking when a brake type
cannot be selected. Regarding selection based on majority
rule, when at least two out of three brake types created by

the respective processing units match, the brake type is selected to be output, and when there is no match, it is determined that a brake type cannot be selected.

[0004] Patent Document 1 Japanese Patent Laid-open
5 Publication No. 2001-157316

DISCLOSURE OF INVENTION

PROBLEM TO BE SOLVED BY THE INVENTION

[0005] However, the above conventional technique has
10 problems described below.

[0006] In the ATC system described in Patent Document 1, when the common unit goes out of order, a brake command cannot be output to a braking device, resulting in a system failure. Therefore, the redundancy is degraded and the
15 reliability is deteriorated.

[0007] Moreover, although in the common unit, the output is determined by making a selection from among inputs from the three processing units based on majority rule, when the distance from a preceding train is short and the train is
20 rapidly decelerated, for example, inputs from the respective processing units cannot be synchronized, and the outputs of the respective processing units can be inconsistent. In such a case, emergency braking is activated to stop the train even though no system failure
25 has occurred, and the reliability is deteriorated.

[0008] Furthermore, because the processing units are limited to the triple system, inputs to the common unit are also limited to three, and other inputs are not supported.

[0009] Moreover, in addition to the ATC system, when
30 other devices (for example, an automatic train stop, a manual braking device, and the like) that output a brake command are to be added, an upper-stage common unit to perform comparison processing on outputs from the

respective devices is further required. Therefore, the number of common units increases, and need for maintenance increases to lead to high cost. In addition, the train weight increases and a larger braking force is to be required.

[0010] Furthermore, conventionally, there has been a case where a relay is used for high-order priority processing in the common unit. In this case, it takes time for comparison processing, and maintenance of the relay itself is to be required.

[0011] Recently, a train information management device that monitors an on-board device to collect car information and that controls and manages operation of the train comprehensively is used, and as a higher level system of ATC system and the like, management of a brake command and the like is also performed.

[0012] The present invention is achieved in view of the above problems, and it is an object of the present invention to provide a train information management device that performs high-order priority processing of brake commands without using a relay, that has a simple configuration, that has improved redundancy, that can perform high-speed processing, and that achieves high reliability.

[0013] In order to solve the above problem, and in order to attain the above object, in a train information management device that is equipped on each car of a train, that monitors on-board devices, and that collects car information to control and manage operation of the train, and that selects a brake notch to be output to a brake control device from among a plurality of brake notches output from a plurality of brake-notch creating devices each of which includes a first and a second processing

units that are independent of each other, the train information management device of the present invention includes a first comparison processing unit to which brake notches created by the first and the second processing

5 units in each of the brake-notch creating devices, that performs comparison processing on all of the input brake notches based on software processing, and that determines and outputs a brake notch producing a largest brake force; a second comparison processing unit to which brake notches

10 created by the first and the second processing units in each of the brake-notch creating devices, that performs comparison processing on all of the input brake notches based on software processing independently of the first comparison processing unit, and that determines a brake

15 notch producing a largest brake force; the second comparison processing unit determines whether an output from the first comparison processing unit is available, and outputs the determined brake notch to the brake control device only when an output from the first comparison

20 processing unit is not available, and a selection switching unit that performs such processing of selecting the brake notch output from the first comparison processing unit by a switching control of the second comparison processing unit to output to the brake control device when an output from

25 the first comparison processing unit is available, and of selecting the brake notch from the second comparison processing unit by a switching control of the second comparison processing unit to output to the brake control device when no output from the first comparison processing

30 unit is available, based on software processing. The second comparison processing unit monitors an output from the selection switching unit to the brake control device, and only when there is no output thereto, outputs a control

signal to an emergency braking unit to output an emergency brake command from the emergency braking unit to the brake control device.

5 EFFECT OF THE INVENTION

[0014] According to the present invention, because the train information management device is configured in a double system having system I and system II, when there is no output from one, output from the other can be used, and
10 the redundancy is improved, and the reliability is high. Moreover, the number of the comparison processing units is two, and the configuration is simplified compared to the conventional technique.

[0015] Moreover, in the present invention, the
15 comparison processing is achieved by software processing, and hardware such as a relay is not necessary to be used as the conventional technique. Therefore, parts for maintenance are not required and costs are reduced. In addition, a failure rate is low and the reliability is
20 improved.

[0016] Furthermore, because hardware such as a relay is not required to be used, the weight of railcar is reduced, and a required brake force is less.

[0017] Moreover, in the present invention, because the
25 comparison processing is executed by software logic, the comparison processing is simplified and high-speed processing is possible.

BRIEF DESCRIPTION OF DRAWINGS

30 [0018] FIG. 1 is a control block diagram including a train information management device according to an embodiment.

FIG. 2 is a flowchart showing brake-notch selection

processing in the train information management device.

FIG. 3 is a control block diagram of an on-train device of the ATC system described in Patent Document 1.

FIG. 4 is a control block diagram when the ATC device,
 5 an automatic train stop, and a manual braking device are arranged in parallel and a brake notch to be output to a brake control device is determined.

EXPLANATIONS OF LETTERS OR NUMERALS

10	[0019]	1, 100	Power receiver
		2, 101	On-train unit
		3, 102	Speed
		4, 103	ATC system
		5, 8, 11, 104	Processing unit I
15		6, 9, 12, 105	Processing unit II
		7, 110	Automatic train stop
		10	Manual braking device
		13, 118	Brake handle
		14	Train information management device
20		17	System I-system II selecting unit
		18, 108	Brake control device
		19	Emergency braking unit
		106	Processing unit III
		107	Common unit (comparison processing)
25		114	Manual braking device

BEST MODE(S) FOR CARRYING OUT THE INVENTION

[0020] Embodiments of a train information management device according to the present invention are explained in
 30 detail below with reference to the accompanying drawings. The present invention is not limited by the embodiments.

[0021] In the following description, first, referring to FIG. 3 and FIG. 4, conventional techniques are explained

and the problems therein are specifically explained, thereby clarifying the effects of the present embodiment.

[0022] FIG. 3 is a control block diagram of the on-train device of the ATC system described in Patent Document 1.

5 As shown in FIG. 3, this ATC system 103 has a triple system configuration having three processing units to create brake notches in parallel. Specifically, the ATC system 103 has a processing unit I 104, a processing unit II 105, and a processing unit III 106. To each processing unit,
10 distance-related information is input from a power receiver 100, correction information of a current position of the train is input from the on-train unit 101, and current speed 102 of the train is input from a speed detector (not shown).

15 [0023] In each of the processing unit I 104, the processing unit II 105, and the processing unit III 106, a brake notch is created. All of these created notches are input to a common unit 107 that performs comparison processing. In the common unit 107, when types of at least
20 two brake notches out of the three brake notches created by the processing unit I 104, the processing unit II 105, and the processing unit III 106 match with each other, the matching brake notch is selected, and if the type is normal braking, a brake notch to be output is determined by high-
25 order priority. The brake notch output by the common unit 107 is input to a brake control device 108, and thus, speed control of the train is performed.

[0024] In the conventional ATC system 103 as described, when a failure occurs in the common unit 107, a brake notch
30 cannot be output to the brake control device 108, and the system goes down. In other words, because the common unit 107 is a "single system", the redundancy is low and the reliability is degraded.

[0025] FIG. 4 is a control block diagram when the ATC device, an automatic train stop, and a manual braking device are arranged in parallel and a brake notch to be output to the brake control device is determined. That is, FIG. 4 illustrates a configuration in which, in addition to the ATC system shown in FIG. 3, an automatic train stop 110 and a manual braking device 114 that are the other devices that output a brake notch are added.

[0026] As shown in FIG. 4, the configuration of the ATC system 103 is the same as that shown in FIG. 3, and the ATC system 103 includes the processing unit I 104, the processing unit II 105, the processing unit III 106, and a common unit 107 that performs comparison processing. Moreover, to each processing unit of the ATC system 103, distance-related information is input from the power receiver 100, correction information of a current position of the train is input from the on-train unit 101, and the current speed 102 of the train is input from the speed detector (not shown).

[0027] Similarly to the case shown in FIG. 3, all brake notches created by the processing unit I 104, the processing unit II 105, and the processing unit III 106 are input to the common unit 107, and a brake notch is determined in the common unit 107. The brake notch determined by the common unit 107 is output to a common unit 119 that performs higher level comparison processing.

[0028] The automatic train stop 110 includes a processing unit I 111, a processing unit II 112, and a common unit 113 that performs comparison processing. Furthermore, to each processing unit of the automatic train stop 110, correction information of a current position of the train is input from the on-train unit 101, and the current speed 102 is input from the speed detector (not

shown).

[0029] In each of the processing unit I 111 and the processing unit II 112, a brake notch is created. These created brake notches are all input to the common unit 113.

5 In the common unit 113, a brake notch to be output is determined out of the two brake notches created by the processing unit I 111 and the processing unit II 112 by high-order priority. The brake notch determined by the common unit 113 is further output to the common unit 119.

10 [0030] The manual braking device 114 includes a processing unit I 115, a processing unit II 116, and a common unit 117 that performs comparison processing. To each processing unit of the manual braking device 114, a manual brake command is input from a brake handle.

15 [0031] In each of the processing unit I 115 and the processing unit II 116, a brake notch is created. These created brake notches are all input to the common unit 117, and in the common unit 117, a brake notch to be output is determined out of the two brake notches created by the processing unit I 115 and the processing unit II 116 by high-order priority. The brake notch determined by the common unit 117 is further input to the common unit 119.

[0032] The common unit 119 performs comparison processing on the brake notches that are output from the ATC system 103, the automatic train stop 110, and the manual braking device 114, respectively, to determine a brake notch to be output by high-order priority. The brake notch output by the common unit 119 is input to the brake control device 108, to conduct speed control of the train.

25 [0033] As described, in the configuration shown in FIG. 4, comparison processing at higher level than the three devices is required, and therefore, the upper-stage common unit 119 is required. Because the upper-stage common unit

119 is a single system, the redundancy is low and the reliability is degraded. In addition, because four common units are provided, the number of the common units is increased, and accordingly, there are problems that the failure rate of the common units increases and parts for maintenance increase, and the like.

[0034] Embodiment

FIG. 1 is a control block diagram including a train information management device according to the present embodiment. As shown in FIG. 1, for example, three units of devices, that is, an ATC system 4, an automatic train stop 7, and a manual braking device 10, each of which creates and outputs a brake notch are provided, and the brake notches created by these three devices are input to a train information management device 14. The train information management device 14 is a system that is equipped in each car of the train, that monitors on-board devices, and that collects car information to control and manage the operation of the train comprehensively, and the present embodiment relates to brake control thereof.

[0035] The ATC system 4 includes a processing unit I 5 and a processing unit II 6, and has a processing unit of a double system. To each of the processing unit I 5 and the processing unit II 6, distance-related information is input from a power receiver 1, correction information of a current position of the train is input from an on-train unit 2, and current speed 3 of the train is input from a speed detector (not shown). The processing unit I 5 performs calculation based on the input from the power receiver 1, the input from the on-train unit 2, and the speed 3, and creates and outputs a brake notch. Similarly, the processing unit II 6 performs calculation based on the input from the power receiver 1, the input from the on-

train unit 2, and the speed 3, and creates and outputs a brake notch. For the ATC system 4, the brake notch has, for example, 1- to 8-segment brakes.

[0036] The automatic train stop 7 includes a processing unit I 8 and a processing unit II 9, and has a processing unit of a double system. To each of the processing unit I 8 and the processing unit I 9, correction information of a current position of the train is input from the on-train unit 2, and current speed 3 of the train is input from the speed detector (not shown). The processing unit I 8 performs calculation based on the input from the on-train unit 2 and the speed 3, and creates and outputs a brake notch. Similarly, the processing unit II 9 performs calculation based on the input from the on-train unit 2 and the speed 3, and creates and outputs a brake notch. For the automatic train stop 7, the brake notch has, for example, 1- to 32-segment brakes.

[0037] The manual braking device 10 includes a processing unit I 11 and a processing unit II 12, and has a processing unit of a double system. To each of the processing unit I 11 and the processing unit II 12, a manual brake command is input from a brake handle 13. The processing unit I 11 performs calculation based on the input from the brake handle 13, and creates and outputs a brake notch. The processing unit II 12 performs calculation based on the input from the brake handle 13, and creates and outputs a brake notch. For the manual braking device 10, the brake notch has, for example, 1- to 8-segment brakes.

[0038] The train information management device 14 includes a comparison processing unit 15 of system I, a comparison processing unit 16 of system II, and a system I-system II selecting unit 17, and forms a double system for

comparison processing.

[0039] To the comparison processing unit 15, the brake notches that are created by the processing unit I 5 and the processing unit II 6 of the ATC system 4 are input, the
5 brake notches that are created by the processing unit I 8 and the processing unit II 9 of the automatic train stop 7 are input, and further, the brake notches that are created by the processing unit I 11 and the processing unit II 12 of the manual braking device 10 are input. That is, all of
10 the outputs from the processing unit I and the processing unit II of the respective devices that create a brake notch are input. To the comparison processing unit 16 also, similarly to the comparison processing unit 15, all of the outputs from the processing unit I and the processing unit
15 II of the respective devices that create a brake notch are input.

[0040] In the comparison processing unit 15, values of the input six brake notches are compared, and a largest brake notch is selected. That is, the high-order priority
20 processing is performed. If the segment number of the brake notches differ among those of the ATC system 4, the automatic train stop 7, and the manual braking device 10, translation of the brake notches, by changing the scale from one to another or the like, is performed to execute
25 the comparison processing. Moreover, the high-order priority processing is executed by software logic by a CPU of the train information management device 14. As described, the comparison processing unit 15 is implemented by the processing of the CPU based on software. The
30 comparison processing unit 16 also performs the comparison processing similarly to the comparison processing unit 15, independently of the comparison processing unit 15.

[0041] The output from the comparison processing unit 15

and the output from the comparison processing unit 16 are both input to the system I-system II selecting unit 17. In the present embodiment, system I is the main system and system II is the subordinate system, and as shown in FIG. 1, as long as an output from system I is available, the system I-system II selecting unit 17 always selects the output of the comparison processing unit 15, and outputs the selected one to the brake control device 18. That is, the comparison processing unit 16 of system II is configured such that an output thereof is selected by the system I-system II selecting unit 17 to be output to the brake control device 18 only when an output from the comparison processing unit 15 of system I is not available.

[0042] The brake control device 18 performs brake control according to the brake notch output by the train information management device 14. When there is no output from the train information management device 14 due to failure of the device and the like, an emergency braking unit 19 detects this, and issues an emergency brake command to the brake control device 18. In the present embodiment, system II switches the system I-system II selecting unit 17. Furthermore, system II monitors an output to the brake control device 18, and when there is no output thereto, outputs a control signal to the emergency braking unit 19 through another route.

[0043] Next, referring to FIG. 2, brake-notch selection processing performed by the train information management device 14 is explained in detail. FIG. 2 is a flowchart showing the brake-notch selection processing performed by the train information management device 14.

[0044] As shown in FIG. 2, first, in either one of the comparison processing unit 15 or the comparison processing unit 16 that is selected by the system I-system II selecting

unit 17, translation of a brake notch is performed on the brake notch input from device A to compare with brake notches input from other devices (step S1). Subsequently, translation of a brake notch is performed on the brake notch input from device B to compare with brake notches input from other devices (step S2). Furthermore, translation of a brake notch is performed on the brake notch input from device C to compare with brake notches input from other devices (step S3). The devices A, B, and C indicate the ATC system 4, the automatic train stop 7, and the manual braking device 10 in no particular order.

[0045] Next, based on the results of translation of the brake notches at steps S1 to S3, comparison of six brake notches is performed (step S4). Subsequently, by software logic, a high level brake notch producing the largest brake force is determined, and is selected to be output (step S5).

[0046] As a result of determination whether an own device is system I or system II made at step S6, if it is system I, the output thereof is output to the brake control device 18 (step S7).

[0047] As a result of the determination whether the own device is system I or system II made at step S6, if it is system II, it is determined whether an output from system I is available (step S8). When an output from system I is available, selection of the system I-system II selecting unit 17 is switched from system II to system I (step S10). When an output from system I is not available, selection of the system I-system II selecting unit 17 is switched from system I to system II (step S9). When it is switched to system II, it is determined whether there is an output to the brake control device 18 (step S11), and when there is no output thereto, the emergency braking unit 19 is driven (step S12).

[0048] According to the present embodiment, because the train information management device 14 is configured in a double system having system I and system II, when there is no output from one, an output from the other can be used, and compared to the configuration based on a single system "common unit" as shown in FIG. 3 and FIG. 4, the redundancy is improved and the reliability is high.

[0049] Moreover, while four common units that perform comparison processing are required in the configuration shown in FIG. 4 in which brake notches output from the ATC system 4, the automatic train stop 7, and the manual braking device 10 are processed similarly to FIG. 1, in the present embodiment, only the comparison processing units 15 and 16 are required and the configuration is simplified.

[0050] Furthermore, in the present embodiment, the comparison processing units 15 and 16 are implemented by software processing, and a common unit that is implemented by a relay and the like as the conventional technique is not required. Therefore, parts for maintenance are not required and costs are reduced. Further, because the common unit is not required, failure rate becomes low, and the reliability is improved.

[0051] Moreover, because a common unit that is implemented by a relay and the like is not required, the weight of a railcar is reduced, and a required brake force is less.

[0052] Furthermore, in the present embodiment, because the comparison processing is executed by software logic, the comparison processing is simplified, and high-speed processing is possible. The processing time is about 10 msec.

[0053] Although in the present embodiment, it is configured such that calculation is performed on brake

notches output from three devices, the ATC system 4, the automatic train stop 7, and the manual braking device 10, by the train information management device 14, "brake-notch creating devices" that output brake notches to the train
5 information management device 14 can be arranged in arbitrary number.

INDUSTRIAL APPLICABILITY

[0054] The present invention is useful as a train
10 information management device that performs high-order priority processing of brake command information output from a train security control device and the like, and that selects and outputs a brake command.

CLAIMS

1. A train information management device (14) that is equipped on each car of a train, that monitors on-board devices, and that collects car information to control and manage operation of the train, and that selects a brake notch to be output to a brake control device (18) from among a plurality of brake notches output from a plurality of brake-notch creating devices each of which includes a first and a second processing units that are independent of each other, the train information management device (14) comprising:

a first comparison processing unit (15) to which brake notches created by the first and the second processing units in each of the brake-notch creating devices, that performs comparison processing on all of the input brake notches based on software processing, and that determines and outputs a brake notch producing a largest brake force;

a second comparison processing unit (16) to which brake notches created by the first and the second processing units in each of the brake-notch creating devices, that performs comparison processing on all of the input brake notches based on software processing independently of the first comparison processing unit (15), and that determines a brake notch producing a largest brake force;

the second comparison processing unit (16) determines whether an output from the first comparison processing unit (15) is available, and outputs the determined brake notch to the brake control device (18) only when an output from the first comparison processing unit (15) is not available, and

a selection switching unit (17) that performs such processing of selecting the brake notch output from the

first comparison processing (15) unit by a switching
control of the second comparison processing unit (16) to
output to the brake control device (18) when an output from
the first comparison processing unit (15) is available, and
5 of selecting the brake notch from the second comparison
processing unit (16) by a switching control of the second
comparison processing unit (16) to output to the brake
control device (18) when no output from the first
comparison processing unit (15) is available, based on
10 software processing,

wherein the second comparison processing unit (16)
monitors an output from the selection switching unit (17)
to the brake control device (18), and only when there is no
output thereto, outputs a control signal to an emergency
15 braking unit (19) to output an emergency brake command from
the emergency braking unit (19) to the brake control
device (18).

20 2. The train information management device (14) according
to claim 1, wherein the brake-notch creating devices are an
automatic train control system (4,13), an automatic train
stop (7,110), and a manual braking device.