

METHOD FOR MANUFACTURING A THERMAL MODIFICATION KILN

Technical field

The application relates generally to a method for manufacturing a thermal modification kiln.

5 Background

The production of kilns intended for the thermal modification of wood has been traditionally carried out with machine shop methods by ordering steel plates of a given size made in stainless steel and by press-bending the same one at a time in keeping with CAD drawings for the kiln. These plates have then been
10 assembled in the machine shop into a complete thermal modification kiln by means of a beam system, whereby the kiln can be provided with a required strength and pressure resistance, followed by shipping the kiln as a complete unit to the customer.

Due to a large size of the kiln, the transport costs in export deliveries make up
15 a significant part of the investment costs in the case of a long distance transport. Also, many potential export countries have a lot of impediments on the road, such as bridges, traffic signs, and trees, making it difficult, if not even impossible, to transport a large complete kiln.

Because of difficulties in transport, attempts have been made to render the
20 kilns structurally lighter or alternatively to assemble the same from components at a final destination of the kiln. Welding kiln segments together has resulted in the warping of stainless steel with a propensity of distorting structural dimensions and shapes.

Accordingly, it has been found the best practice to complete the kiln structure
25 at a machine shop in such a way that the kiln components are first fastened together - so-called tacked - with short intermittent welds, thereby managing to assemble the entire kiln to its form. The welding together of kiln joints is not started until at this point, whereby the entire kiln is better to retain its shape and the transportation of such a constructed complete kiln is inconvenient and
30 expensive.

Summary

Embodiments of the invention reduce problems related to the production and transport processes of currently available thermal timber modification kilns.

According to a first aspect of the present invention, there is provided a method for manufacturing a thermal timber modification kiln, the method comprises making plate modules from steel plates, the modules comprise a panel section and edges, the edges comprise end and side sections, first flaps between the panel and the sections, and overlays, and, the first flaps between the panel and the sections are formed such that the sections are folded inwards in such a way that the folded sections present the first flaps at some angle with the panel, method further comprises forming second flaps between the sections and the overlays such that the overlays are folded outwards in such a way that the folded overlays are substantially parallel to the panel and present the second flaps at some angle with the sections, and the first and second flaps enable adjacent modules to be interconnected for constructing a kiln frame.

According to a second aspect of the present invention, there is provided a plate module for manufacturing a thermal timber modification kiln, said module is made by the above method and comprises a panel section and edges, the edges comprise end and side sections, first flaps between the panel and the sections, and overlays, the sections are folded inwards in such a way that the folded sections present the first flaps at some angle with the panel, and the overlays are folded outwards in such a way that the folded overlays are substantially parallel to the panel and present second flaps at some angle with the sections, and the first and second flaps enable adjacent modules to be interconnected for constructing a kiln frame.

According to a third aspect of the present invention, there is provided a thermal timber modification kiln, which has its frame consisting of plate modules and which is manufactured by a method the above method, each modules comprising a panel section and edges, the edges comprise end and side sections, first flaps between the panel and the sections, and overlays, the sections are folded inwards in such a way that the folded sections present the first flaps at some angle with the panel, and the overlays are folded outwards in such a way that the folded overlays are substantially

parallel to the panel and present second flaps at some angle with the sections, and the first and second flaps enable adjacent modules to be interconnected for constructing a kiln frame.

A method according to one embodiment, which is intended for manufacturing a thermal timber modification kiln, comprises constructing plate modules from steel plates by forming the plate edges with flaps that enable adjacent modules to be interconnected for a kiln frame.

In a plate module according to one embodiment, which is intended for manufacturing a thermal timber modification kiln, the edges of a module constructed from a steel plate are formed with flaps that enable adjacent modules to be interconnected for a kiln frame.

In a thermal timber modification kiln according to one embodiment, the kiln frame is manufactured of plate modules, which are constructed from steel plates by forming the plate edges with flaps that enable adjacent modules to be interconnected.

Brief description of the figures

The detailed description of the figures will deal with exemplary embodiments of the invention more precisely with reference to the accompanying figures, in which

- fig. 1 shows a flowchart for a method of manufacturing a thermal timber modification plant,
- figs. 2a-2f show from various perspectives a steel plate cut for folding a plate module, as well as a complete module with folded flaps, and
- figs. 3a-3b show from a side and obliquely from the front a thermal modification plant constructed from plate modules.

Detailed description of the figures

Fig. 1 shows a method 100 for manufacturing a thermal timber modification kiln 300 depicted in figs. 3a-3b. A beam frame 350 of the kiln 300 is assembled from plate or installation modules 202, 302 as presented in figs. 2a-2f.

5 In a starting step 102, a message is received from an orderer of the kiln 300 about which size kiln 300 is to be supplied for the orderer's disposal. The ordered kiln 300 can be either of a predetermined standard size, for example 8, 18, 28, 44, 60, 120 or 240 m³ in volume, or it can be customized for the orderer.

10 The dimensional data obtained in step 110 is used as a basis for modeling the kiln 300 as well as the plate modules 202, 302 employed for its fabrication. The modules 202, 302 have an unvarying shape regardless of the size of the kiln 300, it being only the surface area, i.e. the length and/or width, of the modules 202, 302 and/or angles α , β for the folded end edges of the module 202, 302 which are variable, depending on a size of the kiln 300 to be manu-
15 factured and on a location of the module 202, 302 in the frame 350.

Making use of 3D modeling, as well as computational fluid dynamics and optimization, makes it possible to manufacture a kiln structure 300, which is to be constructed from structurally unvarying modules 202, 302 and which is economically attractive to manufacture, possible to transport in parts with just one
20 shipping container, thus reducing the required transport space, and possible not to be assembled until on site in the customer's building, enabling the assembly work to be carried out cost-effectively and to a high standard.

Step 120 comprises automated manufacturing of the module 202, 302 for example from a stainless steel plate 200 with a machine according to design. Alternatively, the plate 200 can be for example a coated sheet of steel or aluminum or a duplex plate. Fig. 2a shows a plan view of the plate 200, which has
25 been cut to a desired size and shape.

In the method 100, the modules 202, 302 can be manufactured in a cost-effective and dimensionally precise manner by making use of modern automated machines, for example sheet metal and laser workstations. The utilization of machine automation in manufacturing lowers manufacturing costs significantly and, above all, the dimensionally precise parts enable the assembly
30 to be carried out on installation site.

The die-cut stainless steel plate 200 comprises a panel section 204, end edges 210, 230, and side edges 220, 240. The plate 200 has its edges 210, 220, 230, 240 formed, as denoted by dashed lines in fig. 2a, with flaps 211, 213, 215, 221, 223, 225, 231, 233, 235, 241, 243, 245 fitting together with those
5 211, 213, 215, 221, 223, 225, 231, 233, 235, 241, 243, 245 of other modules 202, 302 and enabling the adjacent modules 202, 302 to be interconnected for constructing the frame 350.

The flaps 211, 213, 215, 221, 223, 225, 231, 233, 235, 241, 243, 245 are formed at either one or more edges 210, 220, 230, 240 at a time, such that first
10 folded inwards along the dashed lines 211, 221, 231, 241 is an end/side section 212, 222, 232, 242 in such a way that the side section 222, 242 presents the flaps 221, 241 for example at a substantially 90° angle with the panel section 204. Respectively, the end sections 212, 232 are folded inwards at the flaps 211, 231 in such a way that the sections 212, 232 are for example con-
15 sistent with angles α , β established by the sections 222, 242, and the angle of the flaps 211, 231 is α , β . The angles α , β can be equal or unequal, depending on a location of the to-be-manufactured module 202, 302 in the frame 350. Likewise, the angles α , β have their size depending on the size of the kiln.

Next folded inwards along the dashed lines 213, 223 are overlays 214, 224 for
20 the sections 212, 222 so as to lie for example substantially parallel to the panel 204 and, respectively, overlays 234, 244 outwards along the dashed lines 233, 243 for the sections 232, 242, such that at least one or both of the overlays 234, 244 can be for example substantially parallel to the panel 204, i.e. substantially perpendicular to the edge 230, 240, or at least one or both of them
25 can be at some angle relative to the edge 230, 240 as required by the frame structure.

Finally folded inwards along the dashed lines 215, 225 are lips 216, 226, such that the lips 216, 226 are for example substantially perpendicular to the panel 204 as well as to the overlay 214, 224 and, respectively, lips 236, 246 out-
30 wards along the dashed lines 235, 245, such that the lips 236, 246 are for example substantially perpendicular, i.e. at a substantially 90° angle, to the overlay 234, 244 or in such a way that the lips 236, 246 are parallel to the sections 232, 242.

It is also possible that the flaps 211, 213, 215, 221, 223, 225, 231, 233, 235, 241, 243, 245 be formed in an order other than described above, for example in reverse order.

Alternatively, in the process of manufacturing for example corner modules 202, 302 for the kiln 300, it is possible that one or more of the edges 210, 220, 230, 240 of the module 202, 302 not be folded at all.

Alternatively, if it is desirable to strengthen the edges 210, 220, 230, 240, the flap fold 211, 213, 215, 221, 223, 225, 231, 233, 235, 241, 243, 245 is made as a single unit in such a way that for example the lip 246 visible in fig. 2c is folded with two additional flaps perpendicularly against a bottom surface of the overlay 244. Alternatively, more strength is obtained by widening the size (surface area) of the overlays 214, 224, 234, 244 and the lips 216, 226, 236, 246.

The manufacturing process of the module 202, 302 further comprises providing the edges 210, 220, 230, 240 of the module 202, 302 with at least one penetration 228, 248 intended for fasteners that are used for locking the modules 202, 302 to each other prior to a final unification by welding. Moreover, in case a particular module 202, 302 is intended to include other penetrations 228, 248, a penetration shall be provided for at least one of the following devices of the kiln 300: at least one fan, at least one temperature sensor, at least one sensor measuring the temperature of timber to be dried, at least one moisture sensor, at least one heating radiator, at least one steam pipe, at least one water pipe, and at least one ventilation pipe.

Fig. 2b shows in a plan view a complete module 202, 302 with folded flaps, which is used for constructing a thermal modification kiln 300 for timber. The module 202, 302 made from a steel plate 200 has its edges 210, 220, 230, 240 formed with flaps 211, 213, 215, 221, 223, 225, 231, 233, 235, 241, 243, 245 that enable the adjacent modules 202, 302 to be interconnected for constructing a beam frame 350 for the kiln 300. The beam systems made up by the edges 210, 220, 230, 240 constitute a load-bearing structure for the kiln 300 together with the panel section 204 of the modules 202, 302. Clearly visible in the figure are the inwardly folded overlays 214, 224 of the edges 210, 220 and the outwardly folded overlays 234, 244 of the edges 230, 240.

In a module 202, 302 according to one embodiment, the folded edges 210, 220, 230, 240, for example the sections 222, 242, are provided with penetra-

tions 228, 248 intended for fasteners. In addition, at least one penetration 228, 248 can be provided, as opposed to fig. 2a, also in the end edges 210, 230 and/or in the panel 204.

5 In a kiln 300 according to one embodiment, which has been constructed from modules 202, 302, the modules 202, 302 have the edges 210, 220, 230, 240 thereof provided with penetrations 228, 248 intended for fasteners.

The completed module 202, 302 with folded flaps is further shown in fig. 2c from a direction of the edge 210, in fig. 2d from a direction of the edge 220, in fig. 2e from a direction of the edge 230, and in fig. 2f from a direction of the
10 edge 240.

If, in step 122, there are still modules 202, 302 to be made, the method 100 returns back to the fabrication step 120.

On the other hand, if all modules 202, 302 for the kiln 300 are ready to use, the modules 202, 302 are transported in step 130 to an assembly site of the kiln
15 300.

An advantage of the method 100 is to enable a transport of the kiln 300 in parts to its final destination and not having to make a final assembly of the kiln 300 until on a working site at the orderer's. Hence, the modules 202, 302 can be installed by using local labor, and the working steps of the method 100 can
20 be carried out each time wherever most prudent.

In step 140, the modules 202, 302 are interconnected at the assembly site in such a way that the flaps 211, 213, 215, 221, 223, 225, 231, 233, 235, 241, 243, 245 at the edges 210, 220, 230, 240 of adjacent modules 202, 302 are fitted to each other and the penetrations 228, 248 present in the folded edges
25 220, 240 of the interconnected adjacent modules 202, 302 are set in alignment with each other.

In the process of connecting the modules 202, 302 to each other, there is a possibility of using bracing pieces, for example a flexed bracing plate conforming to the folded edges 210, 220, 230, 240 and being fitted between the flaps
30 of the modules 202, 302. The bracing plate can be made from the same material as the modules 202, 302, for example from stainless steel, a coated sheet of steel or aluminum, or a duplex plate. Optionally, the bracing piece may

comprise a pipe beam, which is placed in an inner flap 211, 213, 215, 221, 223, 225, 231, 233, 235, 241, 243, 245 at the edges 210, 220, 230, 240 of that particular module 202, 302 whose flaps 211, 213, 215, 221, 223, 225, 231, 233, 235, 241, 243, 245 are left in the lowermost position as the modules 202, 302 are connected. The bracing pieces make it possible to increase the strength and durability of the frame 350.

In a module 202, 302 according to one embodiment, the die-cut edges 210, 220, 230, 240 of a plate 200 are folded in such a way that the flaps 211, 213, 215, 221, 223, 225, 231, 233, 235, 241, 243, 245 fit in those 211, 213, 215, 221, 223, 225, 231, 233, 235, 241, 243, 245 of other modules 202, 302 in a manner that the edge 230 is capable of being laid on top of the edge 210 and the edge 240 respectively on top of the edge 220.

In a kiln 300 according to one embodiment, which has been constructed from modules 202, 302, the modules 202, 302 have the edges 210, 220, 230, 240 thereof die-cut and folded in such a way that the flaps 211, 213, 215, 221, 223, 225, 231, 233, 235, 241, 243, 245 fit in those 211, 213, 215, 221, 223, 225, 231, 233, 235, 241, 243, 245 of other modules 202, 302.

In a kiln 300 according to one embodiment, which has been constructed from modules 202, 302, the modules 202, 302 are interconnected in such a way that the flaps 211, 213, 215, 221, 223, 225, 231, 233, 235, 241, 243, 245 at the edges 210, 220, 230, 240 of adjacent modules 202, 302 are fitted in each other and the penetrations present in the folded edges 210, 220, 230, 240 of the interconnected adjacent modules 202, 302 are set in alignment with each other.

If, in step 142, more modules 202, 302 still need to be interconnected and/or fitted to each other, the method 100 returns back to step 140.

On the other hand, if the modules 202, 302 have been interconnected in a desired manner, the interconnected adjacent modules 202, 302 are attached in step 150 with fasteners capable of being fitted in the penetrations 228, 248. The modules 202, 302, which have been initially attached with fasteners, remain fixed in position without welding, whereby the frame 350 can be assembled completely by means of the fasteners prior to a final attachment of the modules 202, 302 to each other by welding.

Alternatively, the modules 202, 302 can be attached in such a way that adjacent modules 202, 302 are interconnected by means of the flaps 211, 213, 215, 221, 223, 225, 231, 233, 235, 241, 243, 245 and are one by one attached with fasteners to each other prior to connecting the next modules 202, 302.

- 5 The useful fasteners may include at least one of the following fastener types: a pop rivet (blind rivet), a traditional T rivet, a rivet nut, a rivet bolt, a screw/nut combination, and an anchor bolt.

Alternatively, the initial attachment of modules 202, 302 in step 150 can be implemented with welding tongs or the like fasteners, which do not require penetrations 228, 248, or by spot or seam welding.

10

In a kiln 300 according to one embodiment, which has been constructed from modules 202, 302, the interconnected modules 202, 302 are attached with fasteners capable of being fitted in the penetrations 228, 248.

Step 160 comprises welding firmly to each other the edges 210, 220, 230, 240 of modules 202, 302, initially attached with fasteners, for constructing an air-tight beam frame 350. The long welding joints, which are needed for providing a tight internal surface for the kiln 300, are made for example on the corners established by the flaps 211, 221, 231, 241 and the panel section 204 of the modules 202, 302. Hence, those surfaces, being for example at 90° degree angles with each other, i.e. the panel sections 204 as well as the edges 210, 220, 230, 240, preclude dimensional changes of the modules 202, 302 even though the modules 202, 302 are attached to each other with long welding joints. The modules 202, 302 retain unchanged outer dimensions as opposed to traditional manufacturing, in which the outermost edges of metal sheets are distorted as a result of residual welding stresses.

15

20

25

The welding sequence for the modules 202, 302 and/or the edges 210, 220, 230, 240 does not matter by virtue of the initial fastening and the welding process being performed on the corner of the flap 211, 221, 231, 241. The kiln structure 300, assembled from dimensionally precise modules 202, 302, turns out to become sufficiently tight to withstand the pressure generated by fans and filters of the kiln 300.

30

In addition, it is possible to produce a welding joint on a corner 219, 239 made up by sections 212, 222, 232, 242 of the edges 210, 220, 230, 240 of modules

202, 302 and/or to weld at least one set of overlays 214, 224, 234, 244 of the interconnected modules 202, 302 firmly to each other from outside the frame 350.

5 When the edges 210, 220, 230, 240 of modules 202, 302 are welded, for example at the flaps 211, 221, 231, 241 and at the corners 219, 239, firmly to each other, the modules 202, 302 retain unchanged outer dimensions and straight surfaces for connecting to the next modules 202, 302 - i.e. the modules 202, 302 do not undergo deformations - and the assembly of the kiln 300 is facilitated.

10 In addition, the sections 212, 222, 232, 242 constitute a "root backing" for weld joints, thus enabling the use of a thinner plate 200 in manufacturing the kiln 300 and reducing the manufacturing costs of the kiln 300 for this reason as well.

15 In a kiln according to one embodiment, which has been constructed from modules 202, 302, the edges 210, 220, 230, 240 of the adjacent fastener-attached modules 202, 302 have been welded firmly to each other for producing an airtight beam frame 350.

20 By virtue of the modules 202, 302, the kiln 300 does not require the use of an expensive beam structure, because in a preferred construction made up by modules 202, 302, the edges 210, 220, 230, 240 in and of themselves constitute a robust "beam support structure" for the kiln 300.

25 Putting together a modular beam frame 350 for the kiln 300 takes time on average about one minute per module 202, 302, the initial fastening of the frame 350 being therefore achievable in about 24 hours. The final fastening of the frame 350 by welding takes about one week, whereby the time gained over current assembly modes is at least in the order of two months, which represents not only time saving but also saving in costs since putting together the frame 350 only requires workforce for just over a week at the assembly site.

In step 162, the method 100 comes to an end.

30 Figs. 3a-3b illustrates a kiln 300, its beam frame 350, consisting of modules 202, 302, comprising a doorway 354, which is equipped with a door 352 and whereby timber stacks 260 to be thermally modified are passed into and out of

the kiln 300 by means of a transfer line 356. Clearly visible in fig. 3b is the shape of the kiln 300 with the frame 350 being narrower at its lower part than at its upper part. This particular shape of the frame 350 is possible to implement by virtue of the modules.

- 5 The above presentation only shows a few exemplary embodiments of the invention. The principle according to the invention can naturally be varied within the scope of protection defined by the claims, regarding for example implementation details and fields of use.

Claims

1. A method (100) for manufacturing a thermal timber modification kiln (300),
characterized in that the method comprises
 - 5 making (120) plate modules (202) from steel plates (200) by forming edges (210, 220, 230, 240) with flaps (211, 213, 215, 221, 223, 225, 231, 233, 235, 241, 243, 245), which enable adjacent modules to be interconnected for constructing a kiln frame (350).
2. A method according to claim 1, wherein the making of modules comprises cutting the plates to a desired shape and forming the die-cut edges of the
10 plates with flaps which fit in flaps at the edges of other modules.
3. A method according to either of the preceding claims, wherein the making of modules further comprises forming the folded edges with penetrations (228, 248) intended for fasteners.
- 15 4. A method according to any of the preceding claims, which further comprises interconnecting (140) the modules in such a way that the folded edges of adjacent modules are fitted in each other and the penetrations present in the edges of the interconnected adjacent modules are set in alignment with each other.
- 20 5. A method according to any of the preceding claims, which further comprises fastening (150) the interconnected modules with fasteners capable of being fitted in the penetrations.
6. A method according to any of the preceding claims, which further comprises welding (160) the edges of adjacent fastener-secured modules firmly to
25 each other for constructing an airtight kiln frame.
7. A plate module (202, 302) for manufacturing a thermal timber modification kiln (300), said module having been made with a method according to any of claims 1-3.
8. A thermal timber modification kiln (300), which has its frame (350) consisting of plate modules (202, 302) and which has been manufactured with a
30 method according to any of claims 1-6.