WHAT IS CLAIMED IS:

1. A computer-implemented method comprising:

receiving, by a first server from a second server, first sensitive information relating to a user having an account with the second server;

receiving, by the first server from a user device, second sensitive information via a data entry page hosted by the first server, wherein the data entry page is configured to receive second sensitive data associated with the user and the second sensitive information is different to the first sensitive information; and

associating, by the first server, the first sensitive information with the second sensitive information;

wherein the first server and the second server communicate via a first communication channel and the first server and the user device communicate via a second, different communication channel.

2. The computer-implemented method of claim 1, further comprising, in response to receiving the first sensitive information:

transmitting, by the first server to the second server, a session identifier, wherein the second server forwards the session identifier to the user device so that the user device can access the data entry page.

3. The computer-implemented method of claim 1, further comprising, in response to receiving the first sensitive data:

transmitting, by the first server to the second server, a first token with the session identifier.

4. The computer-implemented method of claim 3, further comprising:

providing, by the first server to the user device, a second token and the data entry page, wherein the second token is used to provide the second sensitive information to the first server.

5. The computer-implemented method of claim 4, wherein the first and second tokens are different tokens.

6. The computer-implemented method of claim 1, further comprising:

receiving, by the first server from the second server, a re-direct URL; and

providing, by the first server to the user device, the re-direct URL, such that a browser of the user device automatically accesses a resource associated with the second server using the re-direct URL after the second sensitive information has been inputted to the data entry page.

7. The computer-implemented method of claim 1, further comprising:

accessing, by the second server, the account of the user; and

obtaining the first sensitive information.

8. The computer-implemented method of claim 1, further comprising:

receiving, by the second server, an identifier of the user, wherein the identifier is associated with the account of the user.

9. A computer readable medium comprising instructions executable by a processor to cause the processor to perform the computer-implemented method of claim 1.

10. A server computer comprising:

a processor; and

a computer readable medium configured to store executable instructions,

wherein the server computer is configured to communicate with a user device and a second server computer, and the processor is configured to execute the stored executable instructions to:

receive, from the second server computer via a first communication channel, first sensitive information relating to a user having an account with the second server;

receive, from the user device, second sensitive data associated with the user, wherein the second sensitive information is different to the first sensitive information;

receive, from the user device via a second, different communication channel, second sensitive information via the data entry page; and

associate the first sensitive information with the second sensitive information.

11. The server computer of claim 10, configured to:

host a data entry page accessible by the user device and configured to receive the second sensitive data.

12. The server computer of claim 11, wherein the processor is configured to execute the stored executable instructions to:

transmit, to the second server computer via the first communication channel, a session identifier, wherein the second server computer forwards the session identifier to the user device so that the user device can access the data entry page.

13. The server computer of claim 10, wherein the processor is configured to execute the stored executable instructions to:

transmit, to the second server computer via the first communication channel, a first token with the session identifier.

14. The server computer of claim 13, wherein the processor is configured to execute the stored executable instructions to:

provide, to the user device via the second communication channel, a second token and the data entry page, wherein the second token is used to provide the second sensitive information to the server computer.

15. The server computer of claim 14, wherein the first and second tokens are different tokens.

16. The server computer of claim 12, wherein the processor is configured to execute the stored executable instructions to:

receive, from the second server computer via the first communication channel, a re-direct URL; and

provide, to the user device via the second communication channel, the re-direct URL, such that a browser of the user device automatically accesses a resource associated with the second server computer using the re-direct URL after the second sensitive information has been inputted to the data entry page.

17. A system comprising a client computer, a first server and a second server,
wherein the first server is configured to:

interact with the second server and the client computer via respective data transfer channels;

receive, from the second server via the respective data transfer channel, first sensitive information relating to a user having an account with the second server and associated with the client computer;

provide a data entry page accessible by the client computer;

receive, from the client computer via the respective data transfer channel, second sensitive information associated with the user via the data entry page, wherein the second sensitive information is different to the first sensitive information; and

link the first sensitive information with the second sensitive information;
wherein the client computer is configured to:

access the data entry page to allow the user to input the second sensitive information into the data entry page; and

provide the second sensitive information to the first server via the respective data transfer channel;
wherein the second server is configured to:

identify the account of the user;

retrieve the first sensitive information relating to the user using the identified account; and

send the first sensitive information to the first server via the respective data transfer channel.

18. The system of claim 17, wherein:

the first server is configured to:

send a session identifier to the second server via the respective data transfer channel; and

the second server is configured to:

forward the session identifier to the client computer; and

the client computer is configured to:

access the data entry page using the session identifier.

19. The system of claim 18, wherein:

the first server is configured to, in response to receiving the first sensitive data:

send a first token with the session identifier to the second server via the respective data transfer channel.

20. The system of claim 19, wherein:

the first server is configured to:

provide a second token to the client computer; and

the client computer is configured to:

use the second token to provide the second sensitive information to the first server.