

CLAIMS:

1. A computer-implemented method for providing visual feedback to a user of a rotary shaver, the method comprising:
 - (i) receiving movement measurements representing movement of the rotary shaver during a shaving operation;
 - 5 (ii) processing the received movement measurements to determine a representation of a trajectory of movement of the rotary shaver during the shaving operation;
 - (iii) processing the determined representation to project the representation onto a two-dimensional plane;
 - (iv) generating a graphical user interface, GUI, the GUI including the
 - 10 projected representation and a graphical template comprising an annular target zone for a correct circular motion of the rotary shaver during the shaving operation; and
 - (v) displaying the generated GUI using a display unit.
2. A method as claimed in claim 1, the method further comprising repeating steps
- 15 (ii)-(iv) for further received movement measurements to generate an updated GUI, and displaying the generated updated GUI using the display unit.
3. A method as claimed in claim 1 or 2, the method further comprises the step of:
 - 20 comparing the projected representation to one or more boundaries represented by the annular target zone; and
 - wherein the step of generating the GUI further comprises generating the GUI to further include a visual element based on a result of the comparison.
4. A method as claimed in claim 1, 2 or 3, wherein the step of generating the
- 25 GUI comprises:
 - determining an alignment of the projected representation with the graphical template; and
 - generating the GUI with the projected representation overlaid on the graphical template according to the determined alignment.

5. A method as claimed in any of claims 1-4, wherein the step of processing the received movement measurements to determine a representation of the trajectory of movement comprises filtering to remove high frequency components in the movement measurements.
- 5
6. A method as claimed in any of claims 1-5, wherein the step of processing the determined representation to project the representation onto a two-dimensional plane comprises:
- 10 for a plurality of movement measurement samples in the received movement measurements, computing an orientation of an instant tangent plane based on a previous plurality of measurement samples;
- projecting the movement measurement samples on to the instant tangent plane;
- aligning the projected movement measurement samples with previously-projected movement measurement samples; and
- 15 applying de-trending to the aligned projected movement measurement samples.
7. A method as claimed in any of claims 1-6, wherein the method further comprises the step of:
- 20 processing the projected representation to determine values for one or more characteristics of the movement of the rotary shaver; and
- wherein the step of generating the GUI further comprises generating the GUI to further include the determined value or determined values.
- 25 8. A computer program product comprising a computer readable medium having computer readable code embodied therein, the computer readable code being configured such that, on execution by a suitable computer or processor, the computer or processor is caused to perform the method of any of claims 1-7.
- 30 9. An apparatus for providing visual feedback to a user of a rotary shaver, the apparatus comprising:
- a display unit; and
- a processing unit that is configured to:
- receive movement measurements representing movement of the rotary shaver

during a shaving operation;

process the received movement measurements to determine a representation of a trajectory of movement of the rotary shaver during the shaving operation;

5 process the determined representation to project the representation onto a two-dimensional plane;

generate a graphical user interface, GUI, the GUI including the projected representation and a graphical template comprising an annular target zone for a correct circular motion of the rotary shaver during the shaving operation; and

display the generated GUI using the display unit.

10

10. An apparatus as claimed in claim 9, the processing unit is further configured to:

compare the projected representation to one or more boundaries represented by the annular target zone; and

15

wherein the processing unit is configured to generate the GUI to further include a visual element based on a result of the comparison.

11. An apparatus as claimed in claim 9 or 10, wherein the processing unit is configured to generate the GUI by:

20

determining an alignment of the projected representation with the graphical template; and

generating the GUI with the projected representation overlaid on the graphical template according to the determined alignment.

25

12. An apparatus as claimed in any of claims 9-11, wherein the processing unit is configured to process the received movement measurements to determine a representation of the trajectory of movement by filtering to remove high frequency components in the movement measurements.

30

13. An apparatus as claimed in any of claims 9-12, wherein the processing unit is configured to process the determined representation to project the representation onto a two-dimensional plane by:

for a plurality of movement measurement samples in the received movement measurements, computing an orientation of an instant tangent plane based on a previous

plurality of measurement samples;

projecting the movement measurement samples on to the instant tangent plane;

aligning the projected movement measurement samples with previously-

projected movement measurement samples; and

- 5 applying de-trending to the aligned projected movement measurement samples.

14. An apparatus as claimed in any of claims 9-13, wherein the processing unit is further configured to:

- 10 process the projected representation to determine values for one or more characteristics of the movement of the rotary shaver; and

wherein the processing unit is configured to generate the GUI to further include the determined value or determined values.

- 15 15. A system, comprising:
a rotary shaver; and
an apparatus for providing visual feedback to a user of the rotary shaver as claimed in any of claims 9-14.