

This Sheet Has Been Replaced



VEHICLE TRACK FOR CONSTRUCTION TOY SYSTEM

Related Cases

The application is related to the subject matter of the Glickman U.S. Patents No. 5,061,219, granted October 29, 1991, No. 5,199,919, granted April 6, 1993, and No. 5,137,486, granted August 11, 1992.

Background and Summary of the Invention

This invention is based upon a novel construction toy system as described and claimed in the above mentioned applications and patents, all owned by Connector Set Limited Partnership, Hatfield, PA, United States of America. In general, the basic construction toy system is comprised of a novel strut and connector system in which connectors are provided with open-sided sockets for the lateral reception and substantially rigid retention of end portions of rod-like strut elements. The sockets of the connector elements are defined by spaced-apart gripping arms formed with axially extending grooves which engage and grip opposite sides of a strut adjacent its end to align and firmly hold the strut along a predefined axis. One or more locking elements project from the gripping arms partially into the socket area, and these are received in grooves formed on the ends of the struts, such that the struts, when engaged by the gripping arms, are locked against axial motion by cooperation between the projections and grooves. Desirably, the struts are provided with longitudinally extending opposed grooves designed for cooperation with the locking projections formed on the gripping arms of the connector elements. This arrangement enables the struts to be pressed crosswise into the gripping sockets, until the locking projections are snapped into the opposed longitudinal grooves, thus firmly locking the strut in a crosswise orientation in the connecting

-2-

This Sheet Has Been Replaced



element.

The above described construction toy system enables large and complex three-dimensional structures to be assembled in virtually limitless variety. The present invention enables the incorporation, in a structure assembled using the described construction toy system, of a simplified track structure for the guided movement of a vehicle. To this end, the system incorporates specially modified connector elements which, in addition to forming part of an underlying structure, also mount and support guide rails forming a vehicle guide track. The new system enables guide tracks to be designed with portions arranged in a straight line manner, and with other portions formed with horizontal curves and vertical contours. By way of example, a representative structure specifically illustrated herein is in the form of roller coaster, which easily illustrates the manner in which the invention can be employed.

To particular advantage, the track system of the invention utilizes, for the rail elements of the track structure, generally continuous lengths of modified flexible plastic tubing, which is slotted lengthwise. Special connector elements, provided for mounting and supporting the rail elements, are formed with integral mounting lugs, each including an upwardly projecting stem portion and an enlarged head portion. The rail elements can be assembled to their supports by applying the slotted side of the tubing over the mounting lugs, so that the interior of the tubular rail section is supported by the head portions of the mounting lugs, and the rail section is spaced above the connector element by the stem portion, which passes through the slotted sidewall of the rail. In a typical track structure, rail-supporting connector

This Sheet Has Been Replaced



-3-

elements are spaced apart longitudinally, and the rail sections are self-supporting in the spaces between longitudinally adjacent connector elements.


One form of the rail-supporting connector is a modification of an otherwise standard connector element for the construction toy system, which is incorporated in the basic underlying structure and forms part of the structure. For purposes of this description, such a connector will sometimes be referred to as a structural connector. In addition, the system of the invention includes separate clip-like support devices, which attach to the basic underlying structure, but do not form part of the structural framework. The rail-supporting clips may be installed anywhere along the length of a strut element underlying the rail path, to support a section of rail which is adjacent thereto. The support clips may be slidably adjusted longitudinally along the rod-like strut elements so that the location of the support may be empirically optimized. In addition, the rod-like strut elements are, in most cases, rotationally adjustable in the structural framework, which facilitates shaping of the rail in horizontal and vertical curved areas.

For a more complete understanding of the above and other features and advantages of the invention, reference should be made to the following detailed description of a preferred embodiment of the invention and to the accompanying drawings.

Description of the Drawings

Fig. 1 is a schematic perspective illustration of a simple roller coaster structure constructed in accordance with the invention.

This Sheet Has Been Replaced



-4- -

Fig. 2 is an enlarged, fragmentary view showing a section of the structure of Fig. 1.

Fig. 3 is a top plan view of the structural segment of Fig. 2.

5 Fig. 4 is a perspective illustration of one preferred form of rail-mounting connector element according to the invention.

10 Fig. 5 is a perspective view of a preferred form of strut element employed in the construction of a track system, for maintaining uniform track spacing.

Fig. 6 is a perspective view of a section of rail utilized in the structure of the invention.

Fig. 7 is an enlarged fragmentary cross sectional view as taken generally on line 7-7 of Fig. 2.

15 Fig. 8 is an enlarged fragmentary cross sectional view as taken generally on line 8-8 of Fig. 7.

Fig. 9 is an enlarged fragmentary cross sectional view as taken generally on line 9-9 of Fig. 2.

20 Fig. 10 is a fragmentary cross sectional view as taken generally on line 10-10 of Fig. 10.

25 Fig. 11 is a fragmentary view, with parts broken away, of a section of structure and track, illustrating the use of a clip-like intermediate rail support element, which attaches to the underlying structure but does not form part of the structural framework.

-5-

This Sheet Has Been Replaced



Fig. 12 is a cross sectional view as taken generally on line 12-12 of Fig. 11.

Description of Preferred Embodiments

Referring now to the drawing, the reference numeral 5 10 (Fig. 1) represents generally a typical structure employing the features of the invention. In the illustrated instance, the structure 10 is a roller coaster comprised of spaced-apart rails 11, 12 mounted on a skeletal structure 13 comprised of rod-like struts and 10 connector elements, preferably according to the principles and disclosures of the before mentioned Glickman United States patents. The rails 11, 12 are spaced-apart uniformly over their entire length, forming a two-rail guide track for one or more wheeled vehicles 14. In a 15 structure such as shown in Fig. 1, a motorized or manual lift device (not shown) desirably is provided for carrying the vehicle 14 up an inclined portion 15 of the structure. When the vehicle reaches the top of the incline, it is released and returns by gravity to the bottom of the 20 incline.

With reference to Figs. 2 and 3, a rail-supporting structure of suitable configuration may be assembled utilizing a plurality of struts 16-19 and transversely disposed spacing struts 20, joined with connector elements 25 21-23. Pursuant to principles of my before mentioned patents, the connector elements are preferably formed of molded plastic and are provided with a plurality of strut-engaging sockets 24 (Fig. 10). The sockets 24 are comprised of spaced-apart gripping arms 25 formed with 30 axially extending grooves 26. The sockets 24 are open at one end and closed at the other by an end wall 27. Locking projections 28, integral with the gripping arms 25, project slightly into the socket space forming a constriction.

This Sheet Has Been Replaced



-6- -

As shown in Fig. 9, the several strut elements are provided at each end with a configuration complementary to the sockets 24. In particular, in a preferred form the strut end includes a cylindrical section 29, an annular grooved portion 30, and an end flange 31. The end flanges 31 are adapted to be closely received in an end chamber 32 in the connector socket, formed between the end wall 27 and the locking projections 28. The projections 28 are designed to closely conform to the annular groove 30 in the strut, and the cylindrical portions 29 of the struts are adapted to be received in and gripped by the axially grooved portions 26 of the gripping arms 25. Normal attachment of a strut to a connecting element involves a lateral snap-in assembly in which the strut end is forced laterally into an open side of the socket 24, with the gripping arms 25 temporarily flexing outward sufficiently to enable the cylindrical portions 29 of the strut to enter into the grooved portions 26. The strut is then firmly gripped and positioned in the socket.

As shown in Fig. 10, a strut can also be inserted into the socket in a crosswise orientation. To this end, central portions of the strut elements are formed with opposed grooves 33, running lengthwise along the struts. The positioning of the locking projections 28, in relation to the end wall 27 of the sockets, is such that, when a crosswise oriented strut is pressed into the open end of a socket 24, it can be pressed deep enough into the socket that the locking projections 28 snap into the longitudinal grooves 33, locking the strut firmly in its crosswise orientation.

As is reflected in the above mentioned patents, the connector elements can be provided in a variety of

This Sheet Has Been Replaced



-7- -

configurations, with multiple strut-receiving sockets radiating in a single plane, or in multiple planes, to accommodate a wide variety of structural possibilities.

In the specific structure shown in the drawings, which is illustrative and not in any way limiting of the multitude of possibilities, a structural base is formed by a plurality of flat-sided base connectors 23 joined by horizontal, longitudinally extending struts 17. In general, it is desired that the connector elements 23 be arranged in transversely opposed pairs, as shown in Fig. 3, and these may be joined by transverse spacing struts 20 received crosswise in the connector elements. In the illustrated arrangement, an elevated structure is formed using vertical struts 18, which extend from the base connectors 23 to intermediate connector elements 22. Longitudinally adjacent ones of the intermediate connectors 22 are joined by horizontal struts 17 of the same length as directly below.

In the arrangement illustrated in Fig. 2, short struts 16 join the intermediate connector 22 with upper, rail-supporting connectors. The connectors 21 are, in general, similar to the flat-sided base connectors 23. However, as shown in Figs. 4 and 7, a rail-mounting lug 35 projects upward from the flat sidewall 34 of the connector. The lug 35 desirably is integral with the molded connector element 21 and is comprised of an upwardly projecting relatively flat, thin stem portion 36 and an enlarged head portion 37, which typically will be of cylindrical cross section. The rail-mounting lug 35 preferably is of relatively short length (measured horizontally in Fig. 4) in comparison with the overall length of the flat sidewall 34.

This Sheet Has Been Replaced



-8-

Cooperating with the rail-mounting lugs 35 are special rail elements 38, shown in Fig. 6 (and constituting the rail elements 11, 12 of Fig. 1). To particular advantage, the rail element 38 is an elongated section of
5 extruded (or possibly molded) plastic tubing, which is formed with an open side 39 and continuous, divergent guide flanges 39a extending from its opposite edges. The tubing preferably is formed by extrusion of a flexible plastic material and, in one advantageous embodiment of the
10 invention, has a hollow interior of approximately 3.18 mm (1/8 inch) diameter and side walls 40 of approximately 0.79 mm (1/32 inch) in thickness. A suitable throat width for the slot-like opening 39 is approximately 1.52 mm (0.06 inch).

15 In the illustrated structure, the rail-mounting lugs 35 are sized and shaped to be complementary with the rail sections 38. To this end, the cylindrical head portions 37 of the mounting lugs of approximately 3.18 mm (1/8 inch) diameter, to be received snugly within the 3.18 mm (1/8
20 inch) internal opening of the tubing. The stem portions 37 may have a thickness of, for example, 1.60 mm (0.063 inch), barely larger than the nominal width of the slot opening 39.

A complete track structure is made of a series of
25 longitudinally joined connector elements 21, providing spaced-apart rail-mounting lugs 35. The rail sections 38 ideally are provided in more or less continuous lengths to provide for an uninterrupted rail over the entire length of the assembled structure. However, sections of rail can be
30 joined in any suitable manner, or a single rail section may be joined end to end to form a closed loop. In many cases, it is sufficient merely to apply adjacent ends of a rail section to a common support lug 35. Alternatively, a thin

This Sheet Has Been Replaced



-9-

rod-like connector plug (not shown) may be inserted into the abutted ends of adjacent rail sections in order to provide a smooth connection and transition.

A preferred material for the tubular rail sections 38 is polypropylene, but other materials may be employed. The stiffness/flexibility of the rail sections is not critical. For some structures, relatively straight, relatively rigid rail sections may be preferred. In others, relatively flexible sections may be preferred, and some structures may desirably employ a mixture of both relatively rigid and relatively flexible sections, depending upon contours of the structure.

In a typical rail-supporting structure, there may be both vertical and horizontal contours. Horizontal curves may be provided by joining adjacent rail-supporting connectors 21 at opposite sides of the structure using struts of different lengths. For example, in Fig. 3, longitudinally adjacent connectors 21 at the bottom of the figure are joined by a strut 17 of one size, whereas the corresponding connectors 21 at the opposite side (top of the figure) are joined by a strut 17' of greater length. This causes the track structure to be curved slightly toward the bottom of the figure. A succession of such connections will cause the track structure to change directions significantly, as will be understood. Vertical contours may be imparted by employing vertical connecting struts of different size between the intermediate connectors 22 and the rail-supporting connectors 21. In the illustration of Fig. 2, for example, the rail-supporting connectors 21 are joined to the structure by struts 16 of minimum length. Over a succession of adjacent segments, the length of the connecting struts 16 may be progressively increased, to cause the track structure to be

This Sheet Has Been Replaced



-10-

diverted upwardly. As is evident in Fig. 1, a structure of complex, compound contours may be easily assembled using struts of appropriate lengths to connect adjacent segments of the structure. By using relatively flexible rail sections 38, the contours of the tracks are smooth, with gradual transitions in changing from one direction to another.

In any structure in which two or more parallel rails 10, 11 are employed to support a vehicle 14 having spaced-apart wheels 41, uniform horizontal spacing of the rails throughout is desirable. To this end, it is particularly advantageous to configure the transverse spacing struts 20 with spacing flanges 42 adjacent to but spaced from cylindrical end portions 29 of the spacing struts (see Fig. 5). The longitudinal grooves 33, which normally extend continuously from one end portion 29 to the other, are interrupted by the spacing flanges 42 to define locating sections 43. The length of the locating sections is approximately equal to, or slightly greater than the thickness of the connector elements 21, such that an opposed pair of gripping elements 25 can receive the strut 20 in a crosswise orientation within the limits of the spacing section 43. When the spacing strut 20 is thus joined with the connectors 21, the latter are accurately and uniformly spaced apart, so that the respective rails 11, 12 are maintained in relatively uniform horizontal spacing throughout the full extent of the track structure. The spacing struts 20 may of course be utilized in conjunction with any of the connector elements 22 or 23, at intermediate levels or at the base of the structure, as well as the rail-supporting elements at the top of the structure.

The new track structure can be utilized with any

This Sheet Has Been Replaced



-11-

wheeled vehicle having appropriately flanged wheels 41, as shown particularly in Fig. 3. In a typical assembly, pairs of the flanged wheels 41 are rotatably mounted on horizontal axle struts 44, using single socket connectors 5 45 at each end to retain the wheels on the struts. In the disclosed vehicle structure, which is merely illustrative, a vehicle body is made up of longitudinal struts 46 and transverse struts 47, joined at the corners by right angle connectors 48. Double-ended connectors 49 grip the 10 longitudinal struts 46 and extend downward to engage longitudinal struts 50. Additional right angle connectors 51 are attached to the longitudinal struts 50 and to the axle struts 44 (see Fig. 3) to provide a rudimentary vehicle capable of rolling along the track structure.

15 As will be readily appreciated, the system of the invention enables a complex, contoured track structure to be assembled. The illustrated structure employs a two-rail track structure for supporting a vehicle having two or more wheels. Monorail and multiple rail structures are also 20 possible with the system of the invention. A feature of particular advantage is the utilization of strut and connector assemblies, providing for lateral snap-in assembly of the struts and connectors to enable complex skeletal structures to be assembled, and wherein selected 25 connector elements are provided with projecting mounting lugs for receiving and mounting, at spaced intervals, a tubular plastic (typically flexible) track element. Assembly of the basic structure proceeds in accordance with principles of the several Glickman U.S. patents mentioned 30 above, utilizing at the appropriate locations special connectors having projecting rail-mounting lugs. Upon completion of the basic structure, the individual rails 11,12 are quickly and easily applied by either snapping the flexible rail element over the exposed ends of the rail-

This Sheet Has Been Replaced



-12- -

mounting lugs 35, or by "threading" the rail element onto the lugs in a linear fashion, advancing the end of the rail-forming tube individually over successive mounting lugs. Application of the rails over the mounting lugs 5 is facilitated by the divergent guide flanges 39a, which initially help to position the rail elements properly with respect to the mounting lugs and then to wedge open the throat sufficiently to allow the throat to pass over the enlarged head portions 37 of the mounting lugs.

10 The new structure, which can employ to advantage substantially continuous, flexible rail elements, enables an endless variety of railed structures to be assembled. Utilizing a kit of multiple loose parts, provided in a variety of strut lengths and connector types, a virtually 15 endless variety of structures may be assembled for the support and guidance of wheeled vehicles along a smoothly contoured guide track arrangement. Both monorail and parallel rail structures are possible using the system of the invention.

20 With reference to Figs. 11 and 12, another preferred embodiment of the invention is illustrated. In the modified form of the invention, clip-like intermediate track supports can be attached to the structural framework at any of a wide variety of locations, as needed or 25 desired, and readily adjusted to provide optimum support and contouring of the track. Thus, in the partial structure shown in Figs. 11 and 12, a longitudinal strut element 60 is attached at each end to rail-supporting connector elements 61. The connector 61, together with the 30 strut 60, form part of the structural framework supporting a rail 62, which may be an elongated section of plastic tubing of the type shown in Fig. 6.

This Sheet Has Been Replaced



-13-


Each of the structural connectors 61 is provided with a rail-supporting lug 63 comprising a thin, upwardly extending stem 64 and an enlarged, generally cylindrical head 65. The connector elements 61 illustrated in Fig. 11 correspond generally to the connector shown in Fig. 4 except that the head portions 65 of the rail-supporting lugs are of somewhat greater length to, among other things, facilitate the joining of rail sections end to end with a portion of the head 65 projecting into each of two butted-together rail sections.

To provide intermediate support for the rail section 62, between structural connectors 61, a clip-like support element 66 (see Fig. 12) can be used to great advantage. The support element 66 includes a body portion 67 comprising a pair of spaced-apart gripping arms 68, 69 which can be generally of the same type and configuration as the pairs of gripping arms incorporated in the structural connectors 21 and 61. In particular, each of the gripping arms 68, 69 is formed with a transverse locking projection 70 spaced a predetermined distance from the closed base end 71 of the clip body. The opposite end of the clip body is open and is adapted for the crosswise reception of the strut element 60.

As previously described, the strut elements incorporated into the structural framework, including the strut 60, are formed with longitudinal grooves 72 arranged such that, when the strut 60 is forced crosswise into the body of the clip-like support 66, the grooves 72 are lockingly engaged by the projections 70, in the manner shown in Fig. 12.

The clip-like support 66 is provided with a mounting lug 73 extending upwardly from the clip body 77,

This Sheet Has Been Replaced



-14-

substantially in the same manner as the mounting lugs for the structural connectors 61. The lug 73 includes a flat upwardly projecting stem 74 integrally mounting a horizontally disposed cylindrical head portion 75.

5 In a typical structural framework for a vehicle track incorporated in the invention, adjacent structural connectors 61 are joined by a strut-like connector of predetermined length. If a section of rail 62, supported by mounting lugs 63 at spaced points, needs additional
10 support or guidance, either because of the distance between mounting lugs 63 or because of the weight of the article to be supported on the rail, a clip-like support 66 can be installed on the strut 60, in the manner shown in Fig. 11, providing intermediate support for the rail element 62.

15 To particular advantage, when the clip-like support 66 is installed on the strut 60, the gripping arms 68, 69 engage the strut with sufficient force that the support 66 is retained in its installed position by friction of the gripping action of the arms 68, 69, so that the support
20 will remain in the position in which it is installed. That position may be manually adjusted, of course, by simply manually sliding the clip longitudinally along the strut 60, to locate the clip-like support in the most desirable location. In addition, the support 60, which is engaged by
25 the spaced-apart structural connector 61, is rotatable with respect thereto, although frictionally gripped by gripping sockets of the connectors. This enables the intermediate support to be adjusted slightly in a rotational manner, about the axis of the strut 60, so that the clip-like
30 support 66 can automatically assume an appropriate position, even where the rail 62 has a horizontally curved configuration.

This Sheet Has Been Replaced



-15-

As will be readily appreciated, the system of the invention enables a complex, contoured track structure to be assembled. The illustrated structure employs a two-rail track structure for supporting a vehicle having two or more wheels. Monorail and multiple rail structures are also possible with the system of the invention. A feature of particular advantage is the utilization of strut and connector assemblies, providing for lateral snap-in assembly of the struts and connectors to enable complex skeletal structures to be assembled, and wherein selected connector elements are provided with projecting mounting lugs for receiving and mounting, at spaced intervals, a tubular plastic (typically flexible) track element. Assembly of the basic structure proceeds in accordance with principles of the several Glickman U.S. patents mentioned above, utilizing at the appropriate locations special connectors having projecting rail-mounting lugs. Upon completion of the basic structure, the individual rails 11,12 are quickly and easily applied by either snapping the flexible rail element over the exposed ends of the rail-mounting lugs 35, or by "threading" the rail element onto the lugs in a linear fashion, advancing the end of the rail-forming tube individually over successive mounting lugs. Application of the rails over the mounting lugs 35 is facilitated by the divergent guide flanges 39a, which initially help to position the rail elements properly with respect to the mounting lugs and then to wedge open the throat sufficiently to allow the throat to pass over the enlarged head portions 37 of the mounting lugs.

Particularly where the span between structural connectors is fairly long and/or where the vehicle to be supported is heavier than normal, intermediate support of the flexible rail elements can be provided by means of clip-like supports, which can be snapped over elements of

This Sheet Has Been Replaced



-16-

the structural framework and adjusted longitudinally therealong to any appropriate position. This can be particularly useful where the track framework is structured for a horizontal curve, for example, because the normal span between structural connectors on the outside of the curve can be substantially greater than on the inside of the curve in such areas.


The structure of the invention, which can employ to advantage substantially continuous, flexible rail elements, enables an endless variety of railed structures to be assembled. Utilizing a kit of multiple loose parts, provided in a variety of strut lengths and connector types, a virtually endless variety of structures may be assembled for the support and guidance of wheeled vehicles along a smoothly contoured guide track arrangement. Both monorail and parallel rail structures are possible using the system of the invention.

It should be understood, of course, that the specific forms of the invention herein illustrated and described are intended to be representative only, as certain changes may be made therein without departing from the clear teachings of the disclosure. Accordingly, reference should be made to the following appended claims in determining the full scope of the invention.

-17-

This Sheet Has Been Replaced

Claims:



1 1. A track construction for a toy construction system
2 which comprises
3 (a) at least one section of tubing (11) forming an
4 individual rail element,
5 (b) said section of tubing (38) having a diameter and a
6 length which is a large multiple of such diameter,
7 (c) said section of tubing having outer walls (40) and a
8 hollow interior and having at least longitudinally spaced
9 portions of its outer walls cut radially to provide access
10 opening means (39) to said hollow interior at least at
11 longitudinally spaced points along the length of said
12 section,
13 (c) a plurality of rail-mounting elements (21),
14 (d) longitudinal spacing elements (17) for securing a
15 plurality of said rail mounting elements in longitudinally
16 spaced relation,
17 (e) said rail mounting elements each including one or
18 more projecting lugs (35), each said lug including a
19 projecting portion (36,37) insertable into said access
20 opening means and thereby into the hollow interior of a
21 section of tubing (38) for securing said section of tubing
22 along a predetermined path formed by said rail mounting
23 elements.

1 2. A track construction according to claim 1, wherein
2 (a) a pair of said rail elements (11,12) are arranged in
3 spaced-apart, parallel relation,
4 (b) said rail-mounting elements (21) being arranged
5 generally in spaced-apart pairs, and
6 (c) spacing struts (20) extending between and connecting
7 spaced-apart pairs of said rail-mounting elements.



-18-

This Sheet Has Been Replaced




1 3. A track construction according to claim 2, wherein
2 (a) said longitudinal spacing elements (17) connecting
3 selected rail-mounting elements of an opposed pair thereof
4 being of different length to impart horizontal curvature to
5 a track (11,12) formed of said rail elements (38).

6 4. A track construction according to claim 1, wherein
7 (a) said rail-mounting elements (21) comprise connector
8 elements of molded plastic construction and formed with at
9 least one pair of spaced-apart gripping arms (25) defining
10 a socket-forming recess (24),
11 (b) said gripping arms having outer portions formed with
12 axial grooves (26) facing into said recess,
13 (c) rod-like strut elements (17) are provided, having
14 generally cylindrical end regions (29) adapted to be
15 received in and gripped in axial alignment by said gripping
16 arms,
17 (d) said gripping arms (25) having intermediate portions
18 formed with locking projections (28) extending into and
19 forming a restriction in said socket,
20 (e) said strut elements having an annular groove (30)
21 adjacent an end thereof adapted for locking engagement with
22 said locking projections.

1 5. A track construction according to claim 4, wherein
2 (a) said rail mounting elements (21) are formed with a
3 plurality of radially disposed pairs of gripping elements
4 (25), each said pair forming a socket recess (24) adapted
5 for the reception and gripping of an axially oriented strut
6 element (17,18,19,20),
7 (b) at least selected ones (20) of said strut elements
8 are of generally cylindrical outline and formed with at
9 least one pair of longitudinally extending grooves (33),
10 (c) said selected ones of said strut elements (20) being
11 adapted for crosswise reception in a socket recess (24) of

This Sheet Has Been Replaced



-19-


12 a rail-mounting element, with said locking projections (28)
13 being received in and lockingly engaged with said
14 longitudinally extending grooves (33).

1 6. A track construction according to claim 5, wherein
2 (a) said longitudinally extending grooves are terminated
3 at each end by generally cylindrical end portions (29) of
4 said strut elements, and
5 (b) generally cylindrical abutment stops (42) are formed
6 in said strut elements, spaced a predetermined distance
7 from said generally cylindrical end portions, to form
8 short, confined sections of said longitudinally extending
9 grooves,
10 (c) said strut elements (20) being received crosswise in
11 a socket of a rail-mounting element, with gripping arms
12 (25) of said rail-mounting element engaging said strut
13 element in said confined sections of said longitudinally
14 extending grooves.

1 7. A track construction according to claim 1, wherein
2 (a) said tubing (38) is formed of a flexible plastic
3 material of hollow form and having a continuous opening
4 (39) along one side, and
5 (b) integral, divergently related guide flanges (39a)
6 extend outward from opposite sides of said opening.

1 8. A track construction according to claim 1, wherein
2 (a) said rail mounting elements comprise molded plastic
3 connector elements (21),
4 (b) a plurality of rod-like strut elements (17-20),
5 (c) each said connector element (21) having a plurality
6 of sockets (24) for the snap-on reception and retention of
7 said strut elements,
8 (d) said track construction comprising an assembly of
9 such struts and connector elements,

This Sheet Has Been Replaced




-20-



10 (e) said connector elements have upper and lower
11 portions,
12 (f) said lower portions including a plurality of sockets
13 (25) arranged in an angularly spaced array for engagement
14 with one or more strut elements (17-20),
15 (g) the upper portions of said connector elements
16 including one or more upwardly projecting integral rail
17 mounting lugs (35), each having an upwardly projecting stem
18 portion (36) and an enlarged head portion (37),
19 (h) there being at least two of said connector elements
20 (21),
21 (i) at least one strut element (20) extending between and
22 joining said at least two connector elements (21), to
23 maintain said connector elements in a predetermined spaced-
24 apart relation,
25 (j) said track structure further including at least two
26 rail elements (11,12),
27 (k) each of said rail elements being secured to a
28 separate one of said spaced-apart connector elements by
29 means of said rail mounting lugs (35), with the enlarged
30 head portions (37) of said lugs being received within the
31 hollow interior of a rail element and the stem (36)
32 portions of said lugs passing through said access opening
33 means (39).

1 9. A track construction according to claim 8, wherein
2 (a) said strut element includes end portions (29) and
3 intermediate portions extending between said end portions,
4 (b) said sockets (24) each comprising a pair of spaced-
5 apart gripping arms (25) adapted to grippingly engage a
6 strut element (20) disposed at right angles to said
7 gripping arms,
8 (c) said strut end portions (29) forming first abutment
9 stops for limiting movement of said gripping arms toward
10 the ends of said strut element,

This Sheet Has Been Replaced



-21-



11 (d) second abutment stops (42) on said strut element,
12 spaced from said first abutment stops a distance not
13 substantially greater than the width of said gripping arms,
14 (e) said first and second abutment stops serving to
15 position a pair of connector elements (21) in a
16 predetermined spaced-apart relation on said strut element
17 (20).

1 10. A track construction according to claim 9, wherein
2 (a) said strut element (20) has a generally cylindrical
3 envelope,
4 (b) said end portions (29) are of generally cylindrically
5 form and provided adjacent each end extremity with an
6 annular groove (30),
7 (c) said intermediate portions are formed with
8 longitudinal grooves (33) extending generally between said
9 end portions,
10 (d) said first abutment stops are formed by said
11 generally cylindrical end portions (29), and
12 (e) said second abutment stops are formed by generally
13 cylindrical flanges (42) formed on said strut elements and
14 spaced from said first abutment stops.

1 11. A track construction according to claim 10, wherein
2 (a) said gripping arms (25) have outer portions formed
3 with opposed, radially extending grooves (26) adapted for
4 the reception of a cylindrical end portion (29) of a
5 radially aligned strut (17-19) element,
6 (b) said gripping arms (25) are further provided,
7 adjacent said radially extending grooves and positioned
8 radially inward thereof, with opposed locking projections
9 (28) disposed at right angles to said grooves (26) and
10 projecting into a radially oriented socket space (24)
11 formed by said spaced-apart gripping arms (25) and being
12 lockingly engageable with the annular groove (30) of a

This Sheet Has Been Replaced



-22-

13 radially aligned strut element (17-19),
14 (c) said locking projections (28) being adapted to be
15 grippingly received in longitudinally extending grooves
16 (33) in a strut element (20) for locking engagement with a
17 strut element oriented at right angles to a radially
18 oriented socket space.

1 12. A track construction according to claim 8, wherein
2 (a) said rail elements (38) are formed of flexible
3 plastic material and are formed with a continuous opening
4 (39) on one side, and
5 (b) integral guide flanges (39a) extend divergently
6 outward from opposite sides of said continuous opening.

1 13. A track construction according to claim 1, wherein
2 (a) one or more clip-like rail supports (66) is removably
3 attachable to said spacing elements (60) and provided with
4 projecting lugs (75) insertable into said access opening
5 means for supporting said tubing (62) at one or more
6 locations intermediate said rail mounting elements (61).

1 14. A track construction according to claim 13, wherein
2 (a) said rail mounting elements (60) and said
3 longitudinally disposed spacing elements (60) comprise part
4 of the structural framework of a track structure, and
5 said clip-like rail supports (66) are carried by said
6 structural framework.

1 15. A track construction according to claim 13, wherein
2 (a) said longitudinally disposed spacing elements (60)
3 comprise elongated rod-like strut elements having opposed
4 pairs of longitudinally extending grooves (72),
5 (b) said clip-like rail supports (66) each includes a
6 body portion comprised of a pair of spaced-apart opposed
7 gripping arms (68,69) joined at one end to form an open

This Sheet Has Been Replaced



-23-



8 ended gripping socket,
9 (c) each of said gripping arms having an inwardly
10 extending locking projection (70) located generally
11 directly opposite to a locking projection on the opposed
12 gripping arm, and
13 (d) said gripping arms (68,69) being resiliently forcible
14 into assembled relation with a cross-wise disposed strut
15 element (60), into a position in which said locking
16 projections (70) are received in longitudinally extending
17 grooves (72) of said strut element.

1 16. A track construction according to claim 15, wherein
2 (a) said clip-like support (66) being longitudinally
3 adjustable along said strut element while gripped thereon.

1 17. A track construction according to claim 13, wherein
2 (a) said longitudinally disposed spacing elements (60)
3 comprising rod-like struts formed with generally
4 cylindrical end portions and with annular grooves in said
5 generally cylindrical end portions adjacent end extremities
6 of said struts to form flanged ends thereof,
7 (b) said rail-mounting elements (61) comprise structural
8 connectors, each having one or more open ended sockets for
9 the lateral snap-in reception of said struts,
10 (c) said sockets being formed by pairs of spaced apart
11 gripping arms provided with axially grooved portions for
12 receiving said generally cylindrical end portions and
13 locking projections for reception in said annular grooves,
14 whereby said struts (60) are locked in position in said
15 sockets while being rotatable therein about central axes of
16 said struts against the friction of said gripping arms, and
17 (d) said clip-like rail supports (66) each having a pair
18 of gripping arms adapted for snap-fit attachment about a
19 strut.



-24- -

- 1 18. A track construction according to claim 17, wherein
2 (a) said struts (60) having longitudinally extending
3 grooves (72) therein engageable with portions (70) of the
4 gripping arms of said clip-like rail supports (66).

This Sheet Has Been Replaced