

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : F16L 9/12, 11/08, 41/12		A1	(11) International Publication Number: WO 99/11960
			(43) International Publication Date: 11 March 1999 (11.03.99)
(21) International Application Number: PCT/SE98/01529		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 28 August 1998 (28.08.98)			
(30) Priority Data: ① 9703109-0 ✓ 29 August 1997 (29.08.97) ✓ SE ✓			
(71) Applicant (for all designated States except US): TRELLEBORG VIKING AS [NO/NO]; P.O. Box A, N-3051 Mjødalen (NO). ✓			
(72) Inventor; and (75) Inventor/Applicant (for US only): SJÖTUN, Kyrre [NO/NO]; Veungsdalsveien 15, N-3600 Kongberg (NO). ✓			
(74) Agent: LUNDIN, Björn-Eric; Trelleborg AB, Patents and Trademarks, P.O. Box 21024, S-100 31 Stockholm (SE).			
		Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments. In English translation (filed in Swedish). 1 PD. 1 appⁿ (Look for Symbol) 1 Inv. (Look for Symbol)	
(54) Title: CORROSION- AND FIRE-RESISTANT PIPE SYSTEM ✓ 4 PAS. IPC: F16L 9/12 F16L 11/02 F16L 41/12.			
Exam. Rep. pt. 28/4/99			
(57) Abstract			
A corrosion-resistant and fire-resistant pipe system suitable for sprinkler systems and the like in the offshore industry and also on military and civilian seagoing vessels, and generally as sprinkler systems in official buildings and in industrial buildings. The pipe system is characterised in that the pipe system includes rigid and cold-formable pipe sections (10) that have one or more tubular rubber layers (11, 13, 15) and reinforcement layers (12, 14) that surround or embrace one or more of said tubular rubber layers (11, 13, 15). The reinforcement layers are comprised of wires or ribbons that have been wound, braided, knitted or formed in some other way so as to cross each other, wherein each of said wires or ribbons defines with the longitudinal axis of the pipe section a winding or spiralling angle that imparts the greatest possible strength to said reinforced, tubular rubber layers (11, 13, 15). In the present case, the system also includes branch connections (18) for connecting a pipe section (10) to another pipe section in a multi-path coupling.			