

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



9802144-7

1805

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶: D21H 27/32 // 17:26, 17:28, 17:36, 17:39, 17:55, 17:72	A1	(11) International Publication Number: WO 97/11226 (43) International Publication Date: 27 March 1997 (27.03.97)
(21) International Application Number: PCT/US96/13982 (22) International Filing Date: 30 August 1996 (30.08.96) (30) Priority Data: 08/524,316 6 September 1995 (06.09.95) US (71) Applicant: THE PROCTER & GAMBLE COMPANY [US/US]; One Procter & Gamble Plaza, Cincinnati, OH 45202 (US). (72) Inventors: NEAL, Charles, William; 1826 Forester Drive, Cincinnati, OH 45240 (US). WEGELE, George, Vincent; 5638 Macey Avenue, Cincinnati, OH 45227 (US). LORENZ, Timothy, Jude; 5846 Valleyway Court, Cincinnati, OH 45247 (US). (74) Agents: REED, T., David et al.; The Procter & Gamble Company, 5299 Spring Grove Avenue, Cincinnati, OH 45217 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(54) Title: PAPER PRODUCT COMPRISING ADHESIVELY JOINED PLIES		
(57) Abstract A multi-ply paper product wherein the plies are adhesively joined together is disclosed. One or both of the plies may have embossments protruding towards and contacting the other ply. The plies are adhesively joined, preferably at such embossments. The adhesive is selected from a composition that advantageously provides a minimum wet ply bond strength and a dry ply bond strength which falls within a particularly desired range.		