
**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G10L 3/00		A1	(11) International Publication Number: WO 96/25733
		(43) International Publication Date:	22 August 1996 (22.08.96)
(21) International Application Number: PCT/GB96/00344		(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AZ, BY, KG, KZ, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 15 February 1996 (15.02.96)			
(30) Priority Data: 95300975.0 15 February 1995 (15.02.95) EP (34) Countries for which the regional or international application was filed: GB et al.			
(71) Applicant (for all designated States except US): BRITISH TELECOMMUNICATIONS PUBLIC LIMITED COMPANY [GB/GB]; 81 Newgate Street, London EC1A 7AJ (GB).		Published With international search report.	
(72) Inventor; and (75) Inventor/Applicant (for US only): BRIDGES, James, Anthony [GB/GB]; 88 Suffolk Road, Ipswich, Suffolk IP4 2EL (GB).			
(74) Agent: HIBBERT, Juliet, Jane, Grace; BT Group Legal Services, Intellectual Property Dept., 8th floor - Holborn Centre, 120 Holborn, London EC1N 2TE (GB).			

(54) Title: VOICE ACTIVITY DETECTION



(57) Abstract

A voice activity detector (26) comprising an input for receiving an outgoing speech signal transmitted from a speech system (2) to a user and an input for receiving an incoming signal from the user. Both the outgoing and incoming signals are divided into time limited frames. Means (263) are provided for calculating a feature from each frame of the incoming signal and for forming a function of the calculated feature and a threshold. Based on the function, it is determined whether or not the incoming signal includes speech. Means are provided to determine the echo return loss during an outgoing speech signal from the interactive speech system and to control the threshold in dependence on the echo return loss measured.