

Description

The present invention is concerned with the transfer of confidential information to a subscriber by means of a portable ticket. More specifically this invention relates to games of chance in which outcomes
 5 are indicated to a player by means of confidential information printed on a blank ticket in such a manner as to conceal the information from sight until the player selectively exposes it.

As is known, games of chance such as instant lotteries are played by patrons who purchase lottery tickets, each of which has the outcome of a patron's lottery play printed on it. Such tickets and processes
 10 for manufacturing them are disclosed in, for example, U.S. Patent Nos. 3956049 and 4191376. Typically, the play result is imprinted in some visible form on a predetermined area of the ticket that is thereafter covered by an overlay to conceal the play result. In the prior art such tickets are produced by a continuous printing process that imprints the result of a respective play on each ticket and then covers the printed result by the opaque covering.

The tickets with their pre-printed, concealed play results are then bundled and distributed through the
 15 lottery organization to agents who sell the tickets to the lottery patrons. Typically, extreme security measures must be implemented for the printing, distribution and servicing of the lottery tickets. Because the tickets are premarked, they have a determinable value that can be ascertained if the printed results are known. In the normal course, each ticket is assigned a unique serial number so that a winning ticket can be spotted and identified prior to its sale. In order to prevent unscrupulous persons who might have access to
 20 information associating ticket serial numbers with gaming outcomes from wrongfully manipulating the results of the lottery, the aforementioned security measures are maintained throughout the whole line of ticket distribution to the lottery patrons.

Because the line of distribution is so long and involves so many people including persons responsible for printing, administering, warehousing, and distributing the tickets to agents, the security measures are
 25 extreme and expensive. Ultimately, the profit earned by a lottery is reduced by the cost of the security measures involved.

Because lotteries are often used to raise revenue for public or quasi-public purposes, it is necessary to control the costs of promoting the games in order to maximize the benefits the public derives from the games. Therefore, a system that could efficiently distribute confidential lottery result information to patrons
 30 in an efficient, secure, yet inexpensive manner would enhance the public benefit derived from the game.

It is therefore the principal object of the present invention to permit secure placement of confidential information on a generally-circulated blank ticket.

It is a further object of the present invention to provide a system having the ability to securely place the confidential information on the blank ticket after it is circulated.

SUMMARY OF THE INVENTION

These objects are realized by the provision of tickets that can be generally circulated in blank form to subscribers who wish to obtain confidential information by means of a ticket. Each ticket is provided with
 40 the ability to receive the information in visible form and, during and after receipt of the information, to conceal it from the ticket holder. Once the information is placed on the ticket, it is returned to the patron who then implements a procedure for exposing the concealed confidential information.

In the instant invention a ticket is circulated or transferred to a lottery patron. When the patron initially obtains the ticket it is devoid of any information indicating an outcome or result. However, the ticket has a
 45 predetermined area upon which lottery outcome information can be printed in visible form. An overlay conceals the predetermined area from the view of the patron until after the patron removes it.

When the patron purchases a chance in the lottery, the ticket is entered into a printer employing a printing process that places visible characters indicating the outcome of the lottery attempt through the overlay onto the predetermined area in such a manner that the printed information is hidden and not
 50 indicated by the overlay. The ticket is also imprinted with a serial number associated with the respective outcome. Then, the ticket is returned to the patron who can discover the outcome by removing the opaque overlay.

The above, and other objects, features and advantages of this invention will be apparent in the following detailed description of an illustrative embodiment thereof, when the description is read in connection with
 55 the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 illustrates the imprinting of a generally-circulated blank ticket with concealed information.

Figure 2 illustrates how the printed information on the ticket is exposed to the view of the ticket holder.

Figure 3 is an enlarged cross sectional view of a ticket constructed to receive visible information from a printer through an opaque overlay which conceals the printed information until removed by a holder.

Figure 4 is a mechanical schematic diagram illustrating how a ticket is imprinted with secure information through the opaque overlay.

Figure 5 is a block diagram illustrating how the ticket of Figure 3 and the printing terminal of Figure 4 can be employed in an instant lottery system.

Figure 6 is a flow diagram illustrating a routine implemented by the system of Figure 5 to provide in a secure manner the outcome of a lottery chance on the ticket of Figure 3 and to validate a chance outcome on the ticket.

DESCRIPTION OF THE PREFERRED EMBODIMENT

With reference now to Figure 1 there is illustrated a ticket, indicated by 10, that is one of many generally circulated to patrons of a system which distributes confidential information. The reference numeral 10a indicates the upper surface of the ticket, which includes an area 12 on which a visible indication of the confidential information to be obtained by the holder of the ticket 10 is to be printed. The reference numeral 10b indicates the obverse surface of the ticket on which a conventional bar code 13 is printed that indicates a category to which the ticket belongs.

The ticket 10 can comprise, for example, an instant lottery ticket of the type wherein the holder purchases the ticket and with it a chance in the lottery. As is known, a presently-available instant lottery ticket, when purchased by a lottery player would have the outcome of the player's purchased chance already printed on the ticket. As is known, the outcome on such a ticket would be printed at the time that the ticket was manufactured and covered during the process of printing the result by an opaque covering that the patron would remove after purchasing the ticket.

Such a covering can comprise, for example, a scratch-off ink that a patron can remove by rubbing or scraping. When the scratch-off ink is removed, the underlying printed information is revealed.

However, the ticket 10 differs from the conventional instant lottery ticket in that the area 12 where the lottery result is to be printed is blank when the ticket is obtained by a lottery player. Further, in the preferred embodiment, the area 12 is covered by an opaque overlay when the ticket is distributed. The overlay which conceals the area 12 therefore conceals nothing from the ticket holder when he initially obtains the ticket 10.

In contrast with the conventional type of instant lottery ticket, the lottery result purchased by the holder of the ticket 10 is printed in the area 12 through the opaque overlay only after the holder of the card exchanges cash for his lottery chance. Then, the ticket has the outcome of the purchased chance printed through the opaque overlay into the area 12. After this printing, the upper surface of the ticket 10 is indicated by 10c.

The surface 10a of the ticket still has the opaque overlay covering the area 12. However, a result has been printed through the opaque overlay into the area 12 in such a manner as to conceal the result by means of the overlay until the patron voluntarily removes it.

At the same time when the result is printed through the overlay, a unique serial number 14 associated with the respective information printed in the area 12 is printed in visible form at one end of the ticket surface 10c. The serial number is also represented by a visible bar code 16 printed at the other end of the ticket.

After the patron has obtained the ticket 10 and purchased a chance in a lottery game, he surrenders the ticket 10 to a lottery agent who inserts the ticket 10 into a printer terminal 18 through an input slot 20. The printer terminal 18, in a manner described hereinbelow, prints the lottery chance result through the opaque covering into the area 12 in such a manner that the opaque covering conceals the printed outcome when the process is complete. The printer also prints the serial number 14 and bar code 16 on the ticket and returns the ticket 10 through a customer output slot 22 at the top of the printer terminal 18.

The slot 20 is used by the lottery agent to enter a ticket imprinted with a serial number and a result for validation as explained hereinbelow. The validated ticket is returned to the agent through the slot 24. The printer terminal 18 includes a programmable processor, not shown, to initiate the process of issuing a lottery result by printing it onto a ticket or validating a lottery result printed on a ticket. The printer terminal 18 also includes a CRT having a screen 30 for indicating various pieces of control information to the lottery agent who operates the terminal.

As explained in further detail below, the printer terminal 18 obtains the information to be printed on the

ticket 10a from a lottery information source 32, which provides lottery outcome and serial number information to the terminal 18 in the form of signals which the terminal translates to the information printed on, for example, the ticket surface 10c.

As illustrated in Figure 2, once the ticket 10 has been completely printed by the printer terminal 18 and returned to the patron, the patron can remove the opaque overlay to expose the result indicated by the information printed in the area 12. For example, in Figure 2 the legend WIN \$5.00 is exposed to the ticket holder's view when the opaque overlay is removed.

In Figure 3 an enlarged half section of the ticket 10 includes a ticket blank portion 34 consisting of a piece of conventional seven millimeter card stock having a thermally-sensitive surface finish. A release coat 36, consisting of a thin layer of thermo-setting varnish, is applied over the thermally-coated surface. On top of the release coat 36, and over the area where information is to be printed on the ticket 10, an opaque overlay 38 consisting of a coat of scratch-off ink is placed to overlie and cover the area 12 of the card 10 where lottery result information is to be printed. A second opaque overlay 40 consisting of a camouflage coat of white flexographic ink is applied by a printing plate having an irregular surface in order to make the composite opaque overlay diffusely reflective. A diffusely reflective overlay surface is useful to camouflage any secondary effects of the printing process that might leave an outline or other indication of the information printed into the area 12 through the overlay that might be detectable on a specularly reflective or mirror-like surface. Finally, an overlying coat of varnish 42 is applied over the upper face of the ticket 10 that includes the composite overlay consisting of the ink layers 38 and 40.

This particular structure permits the area of the thermally-coated ticket stock underlying the opaque covering to be imprinted by a conventional thermal printing process that acts through the overlay after it is in place. When the thermal printing is completed, the imprinted information can be observed by scratching or rubbing off the overlay.

The ticket 10 may be produced on a flexographic press with multiple work stations. Using the flexographic press, a ticket blank consisting of a seven millimeter thermally-coated card stock is fed on a first pass through the press during which a varnish is applied on the upper surface of the card and cured into a glossy finish at an ultraviolet curing station forming a part of the press. The thickness of the release coat varnish layer is left to the needs of the designer; however, the inventors have successfully used tickets having a varnish layer 36 of less than one millimeter thickness. During a second pass of the varnished ticket blank on the flexographic press, markings such as the bar code 13 on the ticket 10b are applied at a first press station to the non-coated side of the ticket using regular flexographic ink. At a second station, after the marking on the non-treated side of the ticket, one coat of opaque scratch-off ink is applied. Preferably, the ink has an optical density that is sufficient to conceal a portion of the ticket surface underlying it. At a third work station, another layer of scratch-off opaque ink is applied on top of the first ink layer. At a fourth press work station, after application of the opaque ink layers, graphics are applied to the coated side of the ticket 10. At a fifth work station, after application of the graphics, a camouflage coat 40 of white flexographic ink is applied in a manner to maximize the optical diffusion of the opaque overlay. Next, at the sixth work station during the second pass of the card 10 through the press, the overlying varnish coat 42 is applied over the whole top surface of the card 10. Then, the finally-coated ticket is passed through a set of knurling rollers which rough the surface, again to make it optically diffusive, and the card is cured at the ultraviolet station.

Although a plurality of materials are available to use in constructing the ticket 10, it is preferred to provide a ticket with the following material selection:

Reference

<u>Numeral</u>	<u>Product No.</u>	<u>Manufacturer or Distributor</u>
34	Ticket Stock Type 2700	3M, St. Paul, MN
36, 42	UKJ1019-A Varnish	Inmont Corp., Hawthorne NJ
38	WC-190NHP Scratch-Off Ink	Elektromek, Carlstadt NJ
40	White Flexographic Ink	Inmont Corp., Hawthorne NJ

With reference now to Figure 4, the printing method and mechanism employed by the printer terminal

18 to print the information on the surface of the card 10 in the area 12 beneath the opaque overlay without disturbing or leaving any indication in the overlay is illustrated in Figure 4. Preferably, the printer terminal 18 comprises one of the Datamark DM family of printing terminals available from International Totalizator Systems, Inc.,

5 While a general organization and operation of the printer terminal 18 can be understood with reference to an available Datamark maintenance manual, a reader/printer mechanism embodied in the terminal is illustrated in detail in Figure 4. The reader/printer accepts tickets through the input slot 20. When the ticket enters the slot 20 the light path of a photosensor 44 is interrupted. The photosensor 44 is connected to a controller 46, comprising a programmable processor, that starts and selectively and incrementally operates
10 a stepper motor 48 when the photosensor light path is interrupted. The motor 48 is conventionally coupled to drive a feed pulley 50 and a pair of rollers 52 and 58. When activated, the pulley 50 grasps the ticket and propels it on an input ticket path past an upper roller 52 which presses the back of the ticket against a conventional bar code reader 54 connected to the controller 46. The reader 54 reads the ticket category code on the ticket surface corresponding to ticket surface 10b of Figure 1. The code is indicated to the
15 controller 46 by the reader 54. When a lottery ticket category code is detected, the processor 46 awaits an input from a sensor including optical elements 56a and 56b.

When the ticket has been propelled by the roller 52 between the optical elements 56a and 56b, a light beam passing between the elements is interrupted, which causes an interruption signal to be provided to the controller 46. Upon receiving the indication that the ticket has passed between the elements 56a and
20 56b, the controller 46 activates another bar code reader 57 and an optical sensor 60, to both of which it is connected. The lower roller 58 propels the ticket past the reader 57 which reads the face of the ticket corresponding to the ticket face 10a of Figure 1 and indicates to the controller the presence and content of any bar codes on the face.

Assuming that no bar code has been read by the reader 57, the controller 46 prepares to issue a lottery
25 chance by having a serial number, a serial number bar code, and a lottery result thermally printed on the ticket in a location corresponding to the location for identical printings illustrated in Figure 2. Under these circumstances, when the lower roller 58 has propelled the forward edge of a ticket past the sensor 60, the sensor 60 sends a print location signal to the controller 46. At this, the controller 46 enters a conventional printing routine, passing data to a conventional thermal printer 62, energizing the print solenoid 64, and pulsing the motor 48 each time a row of dots, which make up characters, is to be printed on a ticket.
30 Preferably, the thermal printer 62 prints by a dot-matrix format and prints the serial number, the lottery chance result, and the bar code representing the serial number at the appropriate locations on the card.

The inventors have selected a thermal printing process to print on a card because the process is effective to print through the opaque overlay constructed according to the description provided hereinabove
35 onto the concealed area 12 of the ticket, which includes a portion of the thermally-coated ticket surface which is responsive to thermal printing.

In printing into the concealed area 12, the thermal printing process leaves no easily-discernible mark or other indication in the opaque overlay. However, the ticket stock is responsive to thermal printing and responds in a typical fashion to the thermal printer by producing visible printed characters at locations on
40 the prepared surface of a ticket corresponding to the location on surface 10c in Figure 1.

Thus it is possible to print confidential information into the concealed area and to conceal, by means of the opaque overlay, the printed information during and after the printing process so that the ticket can be provided to the patron with the confidential information still concealed by the opaque overlay.

As the printing operation progresses, a post-print bar code reader 66 reads the bar-coded serial number
45 of the ticket, providing an indication of the read bar code to the controller 46.

If the bar code read by the reader 66 is correct, the controller 46 causes the solenoid 68 to remain idle, keeping the diverter gate 70 off of the upper roller 52 so that the ticket is passed through the output slot 22 to the patron.

If the bar code is incorrect, the solenoid 68 is energized to move the diverter gate 70 onto the upper
50 roller 52 and to divert the ticket to the agent output port 24, where the agent can retrieve it and take the appropriate action.

The terminal printing mechanism controller 46 also controls the mechanism to process tickets imprinted with serial number bar codes. Thus, when a patron has discovered that he has a winning outcome printed on his ticket, he will present the ticket to the agent who will enter it into the terminal for validation.

55 During the validation procedure, a ticket is inserted through the slot 20 by the agent, passes the reader 54 and the sensors 56a and 56b and is guided by the lower roller 58 past the bar code reader 57 which reads the serial number bar code and passes the information to the controller 46.

If the controller 46 finds that a serial number has been entered on the ticket, it checks also to discover

if the ticket has been validated. If not, the terminal obtains confirmation of the outcome and passes the ticket under the printer 64 to have a validation mark printed on the ticket's upper surface. If a ticket has been previously validated, nothing more is printed on it.

When the validated ticket is propelled by the lower roller 58 past the sensor 60, the sensor 60 provides a presence signal to the controller 46 which activates the solenoid 68. Activation of the solenoid 68 places the diverter gate 70 on the upper roller 52 and diverts the ticket out through the agent's output slot 24.

Figure 5 illustrates a system for implementing a lottery game in which tickets constructed according to Figure 3 are distributed in blank to game players. It should be evident that because the tickets are distributed in blank, security requirements to protect them during printing, storage, and distribution are attenuated. Furthermore, since the tickets are blank when they are distributed and circulated among the population desiring to participate in the lottery, they have a minimal initial value, which reduces the likelihood of their being counterfeited.

In the system of Figure 5, a plurality of printer terminals (T), one indicated by reference numeral 70, are placed at various lottery agency locations throughout the geographical area in which a lottery game is to be played. Each of the terminals corresponds to the terminal 18 of Figure 1 and includes the printer/reader mechanism of Figure 4. In addition, each of the terminals includes conventional communication circuitry which enables its controller to communicate through a communications system 72 with a central computer system 74. The communications system 72 can include, for example, telecommunications links such as telephone lines. As is known, printer terminals such as the above-referenced Datamark family include the ability of communicating via standard telecommunications links with a central computer system. Further, central computer systems including master processors are available to control gaming operations of remote printer terminals such as 70. For example, the Datamark terminal family is used in a conventional configuration controlled by a central computer to conduct pari-mutual and lottery betting operations.

Algorithms and techniques are known which can be implemented in the central computer system 74 to randomly produce lottery results. Further, algorithms are known which can randomly associate such results with a predetermined list of serial numbers for lottery tickets. Such techniques are employed, for example, when pre-printed instant lottery tickets are printed and processed for distribution. In the system of Figure 5, instead of providing the lottery chance results with the associated ticket serial numbers for printing on individual pre-printed tickets, the results and their associated serial numbers are stored in a game data storage device 76. The game data storage device 76 can comprise any conventionally-available storage medium such as hard discs. An exemplary data entry in the storage device 76 is represented by the data format 78. The data format for each individual lottery chance result stored in the storage device, 76 includes a ticket serial number, the lottery chance result or outcome, and information indicating whether or not the serial number and outcome have been distributed (D) to a lottery patron. Finally, an information storage sector is used to store information indicating that the lottery ticket on which the serial number and outcome have been printed has been returned to a lottery agent for validation (V).

The general sequence of operations of the system of Figure 5 can be understood with reference to Figure 6. At the beginning of a game, for example, an instant lottery game, the central computer system 74 will randomly generate the game outcomes and randomly associate respective ones of a plurality of ticket serial numbers with the outcomes. All of the outcomes and their associated serial numbers will be stored in an appropriate format in the game data storage device 76. Then, a quantity of tickets equivalent to the ticket 10 are distributed to agents and sold for a nominal sum, or possibly even distributed for free to potential game patrons. When a potential patron decides to purchase a chance in the lottery game, the patron pays the lottery agent for the chance and surrenders his blank ticket to the agent. The agent then operates his printer terminal to obtain a ticket serial number and lottery game outcome from the central system 74. The general sequence of operations followed by the system of Figure 5 in issuing and validating lottery chances is illustrated in Figure 6.

When the patron purchases a lottery chance and surrenders his card to the agent, the agent places the blank ticket in the slot 20 of his terminal. As described above, the terminal controller will read the card category type in program step 80 to confirm that the ticket is a lottery ticket. Next, the serial number reader (reference numeral 57 in Figure 4) will be activated to determine whether a serial number bar code has been placed on the ticket. This is represented by decision block 82. Of course a blank ticket, that is one which has not had a lottery result printed on it, will have no serial number. In this event, the negative exit will be followed from block 82 and in step 84, the terminal controller will establish communication with the central computer system to obtain a ticket serial number and chance outcome to be printed on the blank ticket. At the same time the system will enter information into the distribution (D) sector of the data storage location whence the serial number and outcome were obtained to indicate that they have been distributed. Once the distribution information is entered into this storage sector, that serial number and outcome will not

be used again for the remainder of the lottery game. Then the central system 74 provides the information to the printer terminal and, in program step 86, the serial number is visibly printed in numeric and bar code form on the ticket and, the lottery result is printed through the opaque overlay of the ticket. Then the printer terminal controller passes the ticket through the patron output slot to the patron.

5 Returning to Figure 6, in the event that the printer terminal controller detects a serial number on a ticket during an issue routine prior to the obtaining and printing steps, it will take a positive exit from program step 82, providing a visual indication to the lottery agent on the screen of the terminal.

Thus, after a patron has purchased a chance, had his ticket printed, and removed the ticket's opaque overlay to discover a winning outcome such as is indicated in Figure 2, he can present the winning ticket to
10 a lottery agent for payment. In the validation routine of Figure 6, a printed ticket presented for payment is entered into the input slot of a printer terminal, the printed serial number bar code is detected and the terminal controller follows the positive exit from block 83 while imposing a sequence of operations resulting in the reading of the bar-coded result thermally printed onto the ticket in the result printing area. Once the result is read and interpreted by the terminal controller, the controller establishes communication with the
15 central system 74 to indicate that a ticket bearing the detected serial number has been presented for payment. This is accomplished between program steps 82 and 90.

As indicated by the decision in step 90, the central system 74 consults the record entry in the data storage device 76 associated with the read serial number. If the card has not previously been validated, then no entry will have been made in the validation (V) sector of the information field and the system 74 will
20 send a message to the terminal indicating that the terminal should validate the ticket for payment (step 92). Once this message is transmitted by the central system 74 an entry is made into the V segment of the serial number record to indicate that the printed ticket has been presented for payment and validated. In order to prevent a subsequent presentation of the same ticket for a payment upon a claim that the computer system 74 has malfunctioned, the terminal, in validating the ticket, will cause a validation mark to
25 be printed on the ticket during the validation step 92.

Should a previously-validated ticket be later presented to claim a payment, both the controller 46 and the system 74 will detect respective validation indications and take the positive exit from decision block 90. In this case, a message indicating prior validation and payment will be presented on the terminal screen for the lottery agent's information and the ticket will be retained by the Agent.

30 Although the system of Figure 5 has been presented in terms of distribution of lottery chances, it can be used to securely distribute any kind of confidential information to an information subscriber holding a blank ticket identical to that described above.

Claims

- 35 1. A ticket (10) for use in a lottery system in which predetermined lottery results are given to patrons in printed form on tickets, the ticket comprising:
 - a ticket body for receiving imprinted lottery information on a ticket body portion (12) thereof, which is characterised by
 - 40 masking means (38, 40) on the ticket body overlying the ticket body portion (12) through which the lottery information may be imprinted on the ticket body portion, the masking means (38, 40) for, during and after the imprinting of the lottery information onto the ticket body portion, concealing the lottery information on the ticket body portion and for, after the imprinting of lottery information onto the ticket body portion, being operated to reveal the lottery information.
- 45 2. A ticket according to claim 1, wherein the ticket body portion (12) includes print responsive means for receiving the lottery information in printed form.
3. A ticket according to claim 2, wherein the printed responsive means includes means for receiving
50 thermally printed information.
4. A ticket according to claim 2, wherein the print responsive means includes a ticket stock material responsive to a process that produces visible printing on the material.
- 55 5. A ticket according to claim 4, wherein the ticket stock material is responsive to a thermal printing process.
6. A ticket according to claim 2, wherein the masking means (38, 40) includes an opaque overlay (38, 40)

be used again for the remainder of the lottery game. Then the central system 74 provides the information to the printer terminal and, in program step 86, the serial number is visibly printed in numeric and bar code form on the ticket and, the lottery result is printed through the opaque overlay of the ticket. Then the printer terminal controller passes the ticket through the patron output slot to the patron.

Returning to Figure 6, in the event that the printer terminal controller detects a serial number on a ticket during an issue routine prior to the obtaining and printing steps, it will take a positive exit from program step 82, providing a visual indication to the lottery agent on the screen of the terminal.

Thus, after a patron has purchased a chance, had his ticket printed, and removed the ticket's opaque overlay to discover a winning outcome such as is indicated in Figure 2, he can present the winning ticket to a lottery agent for payment. In the validation routine of Figure 6, a printed ticket presented for payment is entered into the input slot of a printer terminal, the printed serial number bar code is detected and the terminal controller follows the positive exit from block 83 while imposing a sequence of operations resulting in the reading of the bar-coded result thermally printed onto the ticket in the result printing area. Once the result is read and interpreted by the terminal controller, the controller establishes communication with the central system 74 to indicate that a ticket bearing the detected serial number has been presented for payment. This is accomplished between program steps 82 and 90.

As indicated by the decision in step 90, the central system 74 consults the record entry in the data storage device 76 associated with the read serial number. If the card has not previously been validated, then no entry will have been made in the validation (V) sector of the information field and the system 74 will send a message to the terminal indicating that the terminal should validate the ticket for payment (step 92). Once this message is transmitted by the central system 74 an entry is made into the V segment of the serial number record to indicate that the printed ticket has been presented for payment and validated. In order to prevent a subsequent presentation of the same ticket for a payment upon a claim that the computer system 74 has malfunctioned, the terminal, in validating the ticket, will cause a validation mark to be printed on the ticket during the validation step 92.

Should a previously-validated ticket be later presented to claim a payment, both the controller 46 and the system 74 will detect respective validation indications and take the positive exit from decision block 90. In this case, a message indicating prior validation and payment will be presented on the terminal screen for the lottery agent's information and the ticket will be retained by the Agent.

Although the system of Figure 5 has been presented in terms of distribution of lottery chances, it can be used to securely distribute any kind of confidential information to an information subscriber holding a blank ticket identical to that described above.

Claims

1. A ticket (10) for use in a lottery system in which predetermined lottery results are given to patrons in printed form on tickets, the ticket comprising:
 - a ticket body for receiving imprinted lottery information on a ticket body portion (12) thereof, which is characterised by
 - masking means (38, 40) on the ticket body overlying the ticket body portion (12) through which the lottery information may be imprinted on the ticket body portion, the masking means (38, 40) for, during and after the imprinting of the lottery information onto the ticket body portion, concealing the lottery information on the ticket body portion and for, after the imprinting of lottery information onto the ticket body portion, being operated to reveal the lottery information.
2. A ticket according to claim 1, wherein the ticket body portion (12) includes print responsive means for receiving the lottery information in printed form.
3. A ticket according to claim 2, wherein the printed responsive means includes means for receiving thermally printed information.
4. A ticket according to claim 2, wherein the print responsive means includes a ticket stock material responsive to a process that produces visible printing on the material.
5. A ticket according to claim 4, wherein the ticket stock material is responsive to a thermal printing process.
6. A ticket according to claim 2, wherein the masking means (38, 40) includes an opaque overlay (38, 40)



disposed over said print responsive means.

7. A ticket according to claim 6, wherein the opaque overlay (38, 40) is a removable opaque overlay.
8. A ticket according to claim 6, wherein the opaque overlay (38, 40) includes a removable layer of ink.
9. A ticket according to claim 8, wherein the opaque overlay (38, 40) includes a removable layer (40) of material having a diffusely reflective surface.
10. A ticket according to claim 6, wherein the opaque overlay (38, 40) includes a layer (40) constructed to conceal an outline of the printed information formed when the ticket is imprinted with said information.
11. A ticket according to claim 1, wherein the masking means (38, 40) includes a material layer that can be removed by scratching.
12. A ticket according to claim 1, wherein the masking means (38, 40) includes a material layer that can be removed from the ticket body to reveal the lottery information after the lottery information is imprinted.
13. A method of distributing lottery results in a system in which the lottery results are preselected at random and printed onto individual tickets (10), characterised by the steps of:
 distributing one or more blank tickets (10), each of the tickets having print responsive means for being imprinted with information and masking means (38, 40) covering the print responsive means for concealing information imprinted onto the print responsive means during and after the imprinting of the information on the print response means and for being operated after the receipt to reveal the information;
 after the distribution step, imprinting a printed form lottery result onto the print responsive means through the masking means while the masking means conceals the lottery information; and
 operating the masking means to reveal the imprinted lottery result.
14. A method according to claim 13, wherein the print responsive means includes means for receiving thermally printed information.
15. A method according to claim 13, wherein the print responsive means includes a ticket stock material responsive to a printing process that produces visible printing on the material.
16. A method according to claim 15, wherein the ticket stock material is responsive to a thermal printing process.
17. A method according to claim 13, wherein the masking means (38, 40) includes an opaque overlay disposed over the print responsive means.
18. A method according to claim 17, wherein the opaque overlay (38, 40) is a removable opaque overlay.

Revendications

1. Ticket (10) destiné à être utilisé dans un système de loterie dans lequel des résultats de loterie prédéterminés sont donnés aux clients sous la forme imprimée sur des tickets, le ticket comprenant :
 un corps de ticket destiné à recevoir une information de loterie imprimée sur une partie (12) du corps du ticket, qui est caractérisé par :
 des moyens de masquage (38, 40) prévus sur le corps du ticket, qui recouvrent la partie (12) du corps du ticket, à travers lesquels l'information de loterie peut être imprimée sur la partie du corps du ticket, les moyens de masquage (38, 40) servant à dissimuler l'information de loterie sur la partie du corps du ticket pendant et après l'impression de l'information de loterie sur la partie du corps du ticket, et étant destinés à être soumis à une action, après l'impression de l'information de loterie sur la partie du corps du ticket, pour révéler l'information de loterie.
2. Ticket selon la revendication 1, dans lequel la partie (12) du corps du ticket comprend des moyens sensibles à l'impression pour recevoir l'information de loterie sous une forme imprimée.



3. Ticket selon la revendication 2, dans lequel les moyens sensibles à l'impression comprennent des moyens destinés à recevoir une information imprimée par effet thermique.
- 5 4. Ticket selon la revendication 2, dans lequel les moyens sensibles à l'impression comprennent une matière de base du ticket qui est sensible à un procédé qui produit une impression visible sur la matière.
- 10 5. Ticket selon la revendication 4, dans lequel la matière de base du ticket est sensible à un procédé d'impression thermique.
- 6 6. Ticket selon la revendication 2, dans lequel les moyens de masquage (38, 40) comprennent un recouvrement opaque (38, 40) disposé par dessus lesdits moyens sensibles à l'impression.
- 15 7. Ticket selon la revendication 6, dans lequel le recouvrement opaque (38, 40) est un recouvrement opaque amovible.
- 8 8. Ticket selon la revendication 6, dans lequel le recouvrement opaque (38, 40) comprend une couche d'encre amovible.
- 20 9. Ticket selon la revendication 8, dans lequel le recouvrement opaque (38, 40) comprend une couche amovible (40) de matière possédant une surface à réflexion diffuse.
- 25 10. Ticket selon la revendication 6, dans lequel le recouvrement opaque (38, 40) comprend une couche (40) construite pour dissimuler un contour de l'impression imprimée formée lorsque le ticket est imprimé avec cette information.
- 30 11. Ticket selon la revendication 1, dans lequel les moyens de masquage (38, 40) comprennent une couche de matière qui peut être enlevée par grattage.
- 35 12. Ticket selon la revendication 1, dans lequel les moyens de masquage (38, 40) comprennent une couche de matière qui peut être enlevée du corps du ticket pour révéler l'information de loterie après que l'information de loterie a été imprimée.
- 40 13. Procédé de distribution des résultats d'une loterie dans un système dans lequel les résultats de la loterie sont pré-sélectionnés dans un mode aléatoire et imprimés sur des tickets individuels (10), caractérisé par les phases consistant à :
distribuer un ou plusieurs tickets vierges (10), chacun des tickets possédant des moyens sensibles à l'impression destinés à recevoir une information sous une forme imprimée, et des moyens de masquage (38, 40) qui recouvrent les moyens sensibles à l'impression et destinés à dissimuler l'information imprimée sur les moyens sensibles à l'impression pendant et après l'impression de l'information sur les moyens sensibles à l'impression, et destinés à être soumis à une action après la réception pour révéler l'information ;
après la phase de distribution, imprimer un résultat de loterie sous une forme imprimée sur les moyens sensibles à l'impression à travers les moyens de masquage pendant que les moyens de masquage dissimulent l'information de loterie ; et
45 soumettre les moyens de masquage à une action pour révéler le résultat de loterie imprimé.
- 50 14. Procédé selon la revendication 13, dans lequel les moyens sensibles à l'impression comprennent des moyens destinés à recevoir une impression imprimée par effet thermique.
- 55 15. Procédé selon la revendication 13, dans lequel les moyens sensibles à l'impression comprennent une matière de base du ticket qui est sensible à un procédé d'impression qui produit une impression visible sur la matière.
16. Procédé selon la revendication 15, dans lequel la matière de base du ticket est sensible à un procédé d'impression thermique.
17. Procédé selon la revendication 13, dans lequel les moyens de masquage (38, 40) comprennent un



recouvrement opaque disposé par dessus les moyens sensibles à l'impression.

18. Procédé selon la revendication 17, dans lequel le recouvrement opaque (38, 40) est un recouvrement opaque amovible.

5

Patentansprüche

1. Karte (10) zur Verwendung in einem Lotteriesystem, bei dem vorbestimmte Lotterieergebnisse an Spieler in gedruckter Form auf Karten ausgegeben werden, wobei die Karten einen Kartenkörper zur Aufnahme gedruckter Lotteriejnformation auf einen Kartenkörperabschnitt (12) enthalten, gekennzeichnet durch auf dem Kartenkörper vorgesehene, über den Kartenkörperabschnitt (12) gelagerte Verdeckmittel (38, 40), durch welche die Lotteriejnformation hindurch auf den Kartenkörperabschnitt aufdruckbar ist, wobei die Verdeckmittel (38, 40) während und nach dem Drucken der Lotteriejnformation auf den Kartenkörperabschnitt die Lotteriejnformation auf dem Kartenkörperabschnitt verdecken und nach dem Drucken der Lotteriejnformation auf den Kartenkörperabschnitt zur Enthüllung der Lotteriejnformation handhabbar sind.
2. Karte nach Anspruch 1, dadurch gekennzeichnet, daß der Kartenkörperabschnitt (12) bedruckungsempfindliche Mittel zur Aufnahme der Lotteriejnformation in gedruckter Form aufweist.
3. Karte nach Anspruch 2, dadurch gekennzeichnet, daß die bedruckungsempfindlichen Mittel Mittel zur Aufnahme thermogedruckter Information aufweisen.
4. Karte nach Anspruch 2, dadurch gekennzeichnet, daß die bedruckungsempfindlichen Mittel ein Kartenmaterial aufweisen, welches auf ein Verfahren zur Erzeugung einer sichtbaren Bedruckung auf das Material anspricht.
5. Karte nach Anspruch 4, dadurch gekennzeichnet, daß das Kartenmaterial auf ein Thermodruckverfahren anspricht.
6. Karte nach Anspruch 2, dadurch gekennzeichnet, daß die Verdeckmittel (38, 40) einen undurchsichtigen Überzug (38, 40) aufweisen, der über die bedruckungsempfindlichen Mittel gelegt ist.
7. Karte nach Anspruch 6, dadurch gekennzeichnet, daß der undurchsichtige Überzug (38, 40) ein entfernbarer undurchsichtiger Überzug ist.
8. Karte nach Anspruch 6, dadurch gekennzeichnet, daß der undurchsichtige Überzug (38, 40) eine entfernbare Farbschicht aufweist.
9. Karte nach Anspruch 8, dadurch gekennzeichnet, daß der undurchsichtige Überzug (38, 40) eine entfernbare Schicht (40) aus einem eine diffus reflektierende Oberfläche aufweisenden Material aufweist.
10. Karte nach Anspruch 8, dadurch gekennzeichnet, daß der undurchsichtige Überzug (38, 40) eine Schicht (40) aufweist, die derart aufgebaut ist, daß sie eine Umrißlinie einer gedruckten Information verbirgt, die dadurch gebildet wird, daß die Karte mit der Information bedruckt wird.
11. Karte nach Anspruch 1, dadurch gekennzeichnet, daß die Verdeckmittel (38, 40) eine Materialschicht aufweisen, die durch Kratzen entfernbar ist.
12. Karte nach Anspruch 1, dadurch gekennzeichnet, daß die Verdeckmittel (38, 40) eine Materialschicht aufweisen, die vom Kartenkörper zur Enthüllung der Lotteriejnformation entfernbar ist, nachdem die Lotteriejnformation aufgedruckt worden ist.
13. Verfahren zur Verteilung von Lotterieergebnissen in einem System, bei dem die Lotterieergebnisse nach dem Zufallsprinzip ausgewählt und auf individuelle Karten (10) aufgedruckt werden, gekennzeichnet durch die Schritte:
 - Verteilen einer oder mehrerer Blankokarten (10), wobei jede der Karten bedruckungsempfindliche



Mittel zum Bedrucken mit Information und die bedruckungsempfindlichen Mittel abdeckende Verdeckmittel (38, 40) zum Verdecken der auf die bedruckungsempfindlichen Mittel aufgedruckten Information, sowohl während als auch nach dem Drucken der Information auf die bedruckungsempfindlichen Mittel, und die nach dem Erhalt zur Enthüllung der Information gehandhabt werden, aufweist;

- nach dem Verteilschritt, Aufdrucken einer Druckform eines Lotteriergebnisses durch die Verdeckmittel hindurch auf die bedruckungsempfindlichen Mittel während die Verdeckmittel die Lotterinformation verdecken; und
- Handhaben der Verdeckmittel zum Enthüllen des aufgedruckten Lotteriergebnisses.

14. Verfahren nach Anspruch 13, dadurch gekennzeichnet, daß die bedruckungsempfindlichen Mittel Mittel zur Aufnahme thermogedruckter Information aufweisen.

15. Verfahren nach Anspruch 13, dadurch gekennzeichnet, daß die bedruckungsempfindlichen Mittel ein Kartenmaterial aufweisen, welches auf ein Druckverfahren zur Erzeugung einer sichtbaren Bedruckung auf das Material anspricht.

16. Verfahren nach Anspruch 15, dadurch gekennzeichnet, daß das Kartenmaterial auf ein Thermodruckverfahren anspricht.

17. Verfahren nach Anspruch 13, dadurch gekennzeichnet, daß die Verdeckmittel (38, 40) einen undurchsichtigen Überzug (38, 49) aufweisen, der über die bedruckungsempfindlichen Mittel gelegt ist.

18. Verfahren nach Anspruch 17, dadurch gekennzeichnet, daß der undurchsichtige Überzug (38, 40) ein entfernbare undurchsichtiger Überzug ist.

