

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
27 November 2003 (27.11.2003)

PCT

(10) International Publication Number
WO 03/097364 A1

(51) International Patent Classification⁷: **B41J 2/045**,
2/055, 2/175, B05B 17/04, F04B 43/04, 9/00

[JP/JP]; 11-3-301, Kitayamata 3-chome, Tsuzuki-ku,
Yokohama-shi, Kanagawa 224-0021 (JP).

(21) International Application Number: PCT/JP03/06082

(74) Agent: **ITO, TADAHIKO**; 32nd Floor, Yebisu Garden
Place Tower, 20-3, Ebisu 4-chome, Shibuya-ku, Tokyo
150-6032 (JP).

(22) International Filing Date: 15 May 2003 (15.05.2003)

(25) Filing Language: English

(81) Designated States (*national*): CN, KR, SG, US.

(26) Publication Language: English

(30) Priority Data:
2002-145300 20 May 2002 (20.05.2002) JP
2002-259573 5 September 2002 (05.09.2002) JP

(84) Designated States (*regional*): European patent (AT, BE,
BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU,
IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).


(71) Applicant (*for all designated States except US*): **RICOH
COMPANY, LTD.** [JP/JP]; 3-6, Nakamagome 1-chome,
Ohta-ku, Tokyo 143-8555 (JP).

Published:
— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(72) Inventor; and
(75) Inventor/Applicant (*for US only*): **TANAKA, Shinji**

(54) Title: ELECTROSTATIC ACTUATOR AND LIQUID DROPLET EJECTING HEAD HAVING STABLE OPERATION CHARACTERISTICS AGAINST ENVIRONMENTAL CHANGES



(57) Abstract: A liquid droplet ejecting head includes: one or more nozzle holes ejecting liquid droplets; one or more pressure liquid chambers communicating with the nozzle holes and containing liquid to be ejected; a common liquid chamber communicating with the pressure liquid chambers; one or more diaphragms each forming a wall face of the corresponding pressure liquid chamber; one or more vibration chambers containing air gaps provided in contact with the diaphragms on the opposite side from the pressure liquid chambers; and one or more electrodes provided to oppose the diaphragms through the air gaps. The liquid droplet ejecting head further includes: a deformable plate whose deformation is greater than the total deformation of the diaphragms, the deformable plate forming a wall face of the common liquid chamber; and a pressure correcting chamber provided across the deformable plate from the common liquid chamber so as to communicate with the vibration chambers.



WO 03/097364 A1