

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶: G11B 20/00, G06F 1/00	A1	(11) International Publication Number: WO 98/54713 (43) International Publication Date: 3 December 1998 (03.12.98)
(21) International Application Number: PCT/IB98/00800 (22) International Filing Date: 25 May 1998 (25.05.98) (30) Priority Data: 97303706.2 30 May 1997 (30.05.97) EP (34) Countries for which the regional or international application was filed: GB et al. (71) Applicant: C-DILLA LIMITED [GB/GB]; Woodley House, Crockhamwell Road, Woodlex, Reading, Berkshire RG5 3JP (GB). (72) Inventor: NEWMAN, Peter, A.; Woodley House, Crockhamwell Road, Woodley RG5 3JP (GB). (74) Agent: FAESSEN, Louis, M.; H.; Internationaal Octrooibureau B.V., P.O. Box 220, NL-5600 AE Eindhoven (NL).		(81) Designated States: AL, AM, AU, AZ, BA, BB, BG, BR, BY, CA, CN, CU, CZ, EE, GB, GE, GH, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, RO, RU, SD, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(54) Title: METHOD FOR COPY PROTECTING A RECORD CARRIER, COPY PROTECTED RECORD CARRIER AND MEANS FOR DETECTING ACCESS CONTROL INFORMATION		
(57) Abstract A method for copy protecting a record carrier is disclosed, in which method the copy protected record carriers are provided with a pattern of logical errors which cannot be corrected by the error correcting rules predefined for said record carrier. The pattern of logical errors represents access control information. The logical errors are generated during decoding the bit sequence read from the record carrier. Bit errors may be positioned in the bit sequence so as to counteract de-interleaving which is part of an error decoding process in a reading device and accumulate in error words which are uncorrectable. Also a method for detecting access control information and a retrieval arrangement are disclosed, which retrieval arrangement serves to detect the access control information by selecting at least one error location, but not all error locations on the record carrier, and verifying the presence of an error by reading the selected error location via the reading means.		