

CARRYING DEVICE

The present invention relates to a carrying device.

An existing type of carrying device is described in, for example, WO 2005/025383 A2. It comprises a receiving body with an upper edge, a lower edge and two opposite side edges. In addition, the carrying device has a carrying harness system with a hip strap, two shoulder straps and a chest strap. The hip strap is suitable for surrounding the wearer's hips. It has an upper edge which is connected to the lower edge of the receiving body in such a manner that the receiving body is centered substantially centrally above the hip strap. An upper end of each shoulder strap is connected to an upper corner of the receiving body, and a lower end of each shoulder strap is connected to the receiving body below the upper end of the shoulder strap in such a manner that each shoulder strap forms a loop. The chest strap is connected slidably at each of the ends thereof to the shoulder straps. Furthermore, the carrying device has a head part which comprises an upper edge, a lower edge and two opposite side edges, the lower edge of the head part being fastened to the upper edge of the receiving body in such a manner that the head part is centered substantially above the receiving body. In addition, fastening elements designed in the manner of loops are fastened to each upper corner of the head part, the fastening elements being held on the chest strap with the aid of releasable connecting elements.

Such a construction creates a carrying device in which a baby or a small child can be held between the receiving body and either the wearer's back or chest, wherein the contact pressure force required for this purpose is produced by the shoulder straps, the hip

strap and the chest strap being closed and appropriately adjusted. However, a substantial disadvantage of this carrying device is that it cannot be adapted to the height of the baby or child to be received in the carrying device. For example, newborn babies may sink or sag in the receiving body while the back area of larger small children is already no longer sufficiently supported.

An embodiment of the present invention seeks to overcome, or at least ameliorate, this and/or other disadvantages of the prior art. In an embodiment of the present invention, there is provided a carrying device of the type mentioned at the beginning which is suitable for receiving small children from birth up to the age of small children, wherein an orthopedically correct manner of support both for the small child and for the wearer is to be ensured. The carrying device is furthermore to be constructed in a simple and cost-effective manner and to be simple to handle. Furthermore, increased safety both for the child to be received and for the male or female wearer of the device is sought.

According to an aspect of the present invention, there is provided a carrying device with a receiving body for receiving a baby or small child, wherein the receiving body is designed in such a manner that at least one area of the rear side of the baby or small child can be received and/or can be supported therein, and with a holding harness system for fastening the receiving body to a person, wherein the receiving body is furthermore designed in such a manner that the height thereof can be changed due to the carrying device has at least one extension element which can be positioned on the receiving body in such a manner that the receiving body is extended in the vertical direction by the extension element, whereat the receiving body consists of a main section and an above arranged end section and the extension element can be arranged between the main section and the end section.

This height adjustability enables the receiving body always to be optimally adapted to the height of the baby or small child to be received in the carrying device such that babies even from birth up to the age of small children, i.e. up to, for example, approximately 20 kg, can be carried in the carrying device.

At least sections of the receiving body, preferably involve a receiving body which is in the manner of a cloth or pad and is suitable for adapting to the body shape of that area of the rear side of the baby or of the small child which is received in the receiving body and which is supported by the latter.

In order to realize the height adjustability of the receiving body, the carrying device preferably has at least one extension element which can be positioned on the receiving body in such a manner that the receiving body is extended in the vertical direction by the extension element. The extension element is advantageously likewise designed in the manner of a cloth and/or pad in order even in the case of said extension element to ensure adaptability to the body of the small child.

According to an embodiment of the present invention, the extension element can be fastened releasably to the receiving body. If a taller small child is to be carried in the carrying device, the extension element is positioned on the receiving body in order to extend the latter. If, by contrast, the small child is still very small, consequently if therefore a baby, the extension element is simply not used or is pulled in or folded up.

According to an alternative embodiment of the present invention, the extension element is designed as a single part with the receiving body, wherein said extension element can be adjusted between at least two positions, specifically a first position, in which the height of the receiving body is not increased by said extension element, and a second position, in which the height of the receiving body is increased by the extension element. In this case, the extension element can preferably be folded from the first position into the second position, and vice versa. As an alternative, the extension element can be rolled up or unrolled from the first position into the second position, or vice versa.

A fastening device is advantageously provided in order to fix the extension element in the first position thereof. The fastening device can have, for example, a zipper and/or snap fasteners and/or touch and close fasteners. In the case of touch and close fasteners which comprise barb surfaces and loop surfaces, the carrying device preferably has covering means with which touch and close fastener regions, in particular the barb surfaces, can be covered. The covering means prevent contact of the child with annoying touch and close fastener regions, thus making it more comfortable for the child to sit in the receiving body.

In order to be able to adapt the shape of the receiving body of the carrying device even better to the height of the baby or small child to be received in the carrying device and in order to increase both the safety and the carrying comfort, the carrying device advantageously comprises a seat reduction device. The latter can preferably be positioned on the receiving body in such a manner that a baby or a small child is

received higher and therefore in an elevated position in the receiving body.

In a similar manner to the receiving body and the extension element, at least sections of the seat reduction device are also designed in the manner of a cloth and/or pad such that said seat reduction device can be flexibly adapted to the body shape of the area of the small child to be received by it.

According to an embodiment of the present invention, the seat reduction device can be fastened releasably to the receiving body and can be positioned on the receiving body or not used, depending on requirements.

According to another embodiment of the present invention, the seat reduction device is designed as a single part with the receiving body, wherein it can be adjusted between at least two positions, specifically a first position, in which it reduces the height of the seat of the small child in the receiving body, and a second position, in which it does not reduce the height of the seat of the small child in the receiving body. In the latter case, the seat reduction device is preferably designed such that it can be folded in such a manner that it can be stowed in the second position thereof such that it does not impair the operation of the carrying device. In order to fold the seat reduction device, the latter preferably has predetermined folding lines, for example in the form of color-contrasted seams or the like which assist a person in the folding of said seat reduction device. In order to stow the seat reduction device, the receiving body advantageously has a pocket which preferably comprises closure elements for closing of same.

The carrying harness system of the carrying device according to an embodiment of the present invention preferably has a shoulder strap device with shoulder straps. The shoulder strap device advantageously comprises at least one adjustment device for changing the shoulder strap length such that the shoulder strap device can be adapted to the body build and the height of the wearer. In order to pad the shoulders, the shoulder strap device furthermore preferably has shoulder pad sections, wherein the shoulder strap device advantageously has at least one adjustment device for changing the effective position of the shoulder pad sections, thus permitting comfortable wearing of the carrying device for the wearer.

The shoulder straps preferably have closure elements for opening and closing the shoulder straps, wherein the closure elements are advantageously secured by a securing device preventing immediate release of the shoulder straps after the opening of a closure element. It can thereby be ensured that, after the release of the closure elements on the shoulder straps, a child held in the carrying device will not immediately drop out of the carrying device. The securing device can be designed, for example, in the manner of a loop, specifically such that, after the release of the closure elements of the shoulder straps, said closure elements remain attached to the securing device which is designed in the manner of a loop. Although the shoulder straps are then already released from the lateral clips on the receiving body, the child held by the carrying device can still not drop out.

Furthermore, the carrying harness system of the carrying device according to an embodiment of the present invention preferably comprises a hip strap device with a hip strap. The hip strap device advantageously comprises at least one

closure element for opening and closing of same, wherein the at least one closure element is likewise advantageously secured by a securing device of the type described previously, which prevents immediate release or opening of the hip strap after the opening of the closure element.

In addition, the carrying harness system of the carrying device according to an embodiment of the present invention advantageously comprises a chest strap device with a chest strap which is preferably fastened to the shoulder device.

By means of a carrying harness system with a shoulder strap device, a hip strap device and a chest strap device, both the safety and wearing comfort of the carrying device according to an embodiment of the present invention are optimized.

Furthermore, the carrying device according to an embodiment of the present invention preferably comprises a head part which supports the head and/or back of the neck of the child received in the carrying device and/or serves as a sunshade. The head part is also preferably designed in the manner of a cloth and/or pad and is connected releasably or fixedly to the receiving body. The head part advantageously has fastening elements which can be positioned on the carrying harness system in order to position the head part in a predetermined manner, wherein the fastening elements are preferably designed in such a manner that they can tension or tighten up the head part. This can be realized, for example, by elastic bands or the like being used as the fastening elements. In addition, receiving elements for receiving the fastening elements are advantageously arranged on the carrying harness system, in particular on the shoulder straps.

Said receiving elements are preferably formed and positioned movably on the shoulder straps in order to be able to arrange and, if appropriate, tension the head part in different positions, wherein the receiving elements are designed in such a manner that they can optionally be fixed at a selected position on the carrying harness system or on the shoulder strap such that they cannot be moved further. Accordingly, the head element can be fixed in different positions to meet requirements.

Further features, details and advantages of the invention emerge from the wording of the claims and from the description below of exemplary embodiments with reference to the drawings, in which:

Fig. 1 shows a rear view of a first embodiment of the carrying device according to the invention, in which an extension element is in the position in which it extends the receiving body of the carrying device in the vertical direction;

Fig. 2 shows a front view of the carrying device illustrated in figure 1;

Fig. 3 shows a rear view of the carrying device illustrated in figures 1 and 2, wherein the extension element is in the position in which it does not extend the receiving body in the vertical direction;

Fig. 4 shows a front view of the carrying device illustrated in figure 3;

Fig. 5 shows a front view of the carrying device illustrated in figures 1 to 4, with the seat reduction device unfolded;

Fig. 6 shows a rear view of the carrying device illustrated in figure 5, the rear view showing a subregion of said carrying device;

Fig. 7 shows a rear view of a further embodiment of a carrying device according to the invention, and Fig. 8 shows a rear view of another embodiment of a carrying device according to the invention.

5

The same reference numbers refer below to components which are identical or are of the same kind.

10 Figure 1 is a rear view of a first embodiment of a carrying device according to the invention which is referred to in general by the reference number 10. The carrying device 10 comprises a receiving system with a receiving body 12 in which at least one area of the rear side of a small child can be received.

15

The receiving body 12 is produced from a stable, one or two layer fabric or fabric-like, moldable and slightly elastic material and substantially has a rectangular or trapezoidal shape with an upper edge 14, a lower edge 16 and two mutually opposite side edges 18 and 20. In the present embodiment, said receiving body comprises three sections formed as a single piece with one another and arranged one above another, namely a main section 22, an extension section 24 arranged above the main section 22, and an end section 26 arranged thereabove.

Respective zipper strips 28, 30 which are provided with teeth are arranged on the linear transition regions between the main section 22 and the extension section 24 and between the extension section 24 and the end section 26, wherein the zipper strips 28 and 30 can be positioned next to each other and can be fastened to each other by interaction with a zipper slide 32, as shown in figure 3. However, in the state illustrated in figure 1 of the carrying device 10, the zipper strips 28 and 30 are spaced apart from each other such that

the extension section 24 increases the overall height of the receiving body 12 by the height h of the extension section 24. A plurality of tucks 34 are provided in the upper region of the central section 22, which substantially serves to receive the small child's bottom area, the tucks providing the main section 22 with a slight hollow shape such that the child sits anatomically correctly as in a preshaped pocket and the thighs are easily drawn up to his body. In order to increase the comfort, the receiving body 12 can additionally be padded in regions 23, in particular so that the child's thighs do not receive any pressure points.

An elongate, underpadded clip 36, to which the closure elements 68 of the shoulder straps 62 are fastened, protrudes on each side of the receiving body 12. A pocket (not illustrated in figure 1) which is accessible from the upper edge 14 of the receiving body 12 is incorporated into the end section of the receiving body 12. Said pocket serves for the stowing of a head part 110 which is illustrated in figure 7.

A hip strap device 40 is fastened substantially centrally to the lower edge 16 of the receiving body 12. The hip strap device 40 comprises a base body 42 which is produced from an elongate, rectangular fabric material and is padded at points with foam, neoprene or a similarly stabilizing material, thus ensuring a good dissipation of weight to the wearer's hips and high wearing comfort.

In order to ensure the mobility of the base body 42, the latter is divided by vertical tucks 44 into a plurality of parts. Two wing-like cutouts 46 on the lower border of the base body 42 improve the anatomical fitting shape and, when the device is being worn in

front of the stomach, form corresponding bulges for the wearer's thighs if the wearer wants to kneel or sit down.

5 Furthermore, the hip strap device 40 comprises a hip strap 48 which extends along the base body 42 and is held thereon. The hip strap 48 can be fastened releasably to a person's hips with the aid of a closure element 50. The closure element 50 comprises two
10 closure members 52 and 54 which are fastened to the free ends of the hip strap 48 and can be brought into engagement with each other in the manner of a plug-in connection. In order to prevent immediate release of the hip strap 48 after the opening of the closure
15 element 50, the hip strap device 40 comprises a safety device 56 in the form of a loop through which the closure member 54 is guided during the closure of the closure element 50 before said closure member is brought into engagement with the closure member 52. If
20 the closure members 52 and 54 are subsequently separated from each other, the closure member 54 remains attached to the safety device 56, which is designed in the manner of a loop, such that the fastening, which is realized by the hip strap device
25 40, to the wearer's hips is not immediately released. This is to prevent the small child received in the receiving body 12 of the carrying device 10 from being able to drop out when the hip strap device 40 is opened.

30
Irrespective of all of this, the hip strap device 40 has an adjustment device 58 which, in the present case, is designed as a single piece with the closure member 52 of the closure element 50. With the aid of the
35 adjustment device, the length of the hip strap 48 can be changed in a known manner in order to adapt said length to the body build and the height of the wearer.

The carrying device 10 furthermore comprises a shoulder strap device 60 with shoulder straps 62 which are fastened laterally to the upper edge 14 of the end section 26 of the receiving body 12. Furthermore, two shoulder pad sections 65 are fastened laterally to the upper edge 14, said shoulder pad sections extending under the shoulder straps 62 and ensuring a comfortable fit of the carrying device 10 on the wearer's shoulders.

As can readily be seen in particular in figure 3, closure members 66 are arranged at the end of each shoulder strap 62. These closure members 66 can be brought releasably into engagement with corresponding closure members 68 which are fastened to clips 36 protruding outward laterally from the main section 22 of the receiving body 12. If the closure members 66 and 68 are brought into engagement with each other, the shoulder straps 62 each form the shape of a loop which can be pulled over an arm and can be arranged resting on the wearer's shoulder.

Like the hip strap 48, the shoulder strap device 60 is also provided with safety devices 69 in order to prevent immediate opening of the loops after the opening of the closure elements 66, 68. Each safety device 69 is in the form of a loop through which the closure member 66 has to be guided during the closing of the closure before said closure member is brought into engagement with the closure member 68. If the closure members 66 and 68 are subsequently separated from each other, the closure member 66 remains attached to the safety device 69, which is designed in the manner of a loop, and therefore the shoulder strap loops cannot open immediately. This prevents the baby

or the small child from being able to inadvertently drop out when the carrying device 12 is removed.

5 A first adjustment device 70, with the aid of which the length of each shoulder strap 62 can be individually changed, is designed as a single part with each closure member 66. A further adjustment device 72 is provided at the other end of each shoulder strap 62. Said adjustment device 72 not only brings about an
10 adjustment of the shoulder strap length 62; it also tightens together the preferably unpadded strap section 64 located therebelow when, with the aid of said adjustment device, the length of the shoulder strap 62 is shortened, as indicated on the left side in figure
15 1. Not only is the strap length thereby adapted to the wearer's body build, but also the position of the padded section 65 will always be optimally selected.

Furthermore, a respective D-shaped ring 74, to which,
20 for example, a pacifier chain or the like can be fastened, is held on the shoulder straps 62. Finally, a receiving element 46 is provided on each shoulder strap 62, the receiving element being arranged movably along the direction of extent of the shoulder strap and being
25 optionally fixable at different positions on the respective shoulder strap 62. The receiving elements 76 serve to receive fastening elements of a head part, which will be explained in more detail with reference to figures 7 and 8.

30 The previously described construction of the shoulder strap device 60 permits a small child to be carried in various positions. The following variants are possible here:

35

- i. The receiving body 12 is arranged on the wearer's stomach, the shoulder straps 62 crossing over on the back;
- ii. The receiving body 12 is arranged on the wearer's stomach, the shoulder straps 62 being shaped to form loops and not crossing over;
- iii. The receiving body 12 is arranged on the wearer's back, the shoulder straps 62 being shaped to form loops and not crossing over;
- iv. The receiving body 12 is arranged on the wearer's back, the shoulder straps 62 crossing over on the chest; and
- v. The receiving body 12 is arranged laterally on the wearer's hips, one shoulder strap 62 being closed obliquely over the shoulder and the other shoulder strap 62 being closed vertically on the back.

Figure 2 shows a front view of the carrying device 10 which is illustrated in figure 1. The surface formed in this view by the main section 22, the extension section 24 and the end section 26 of the receiving body 12 forms the receiving surface for an area of the rear side of the small child. The receiving body 12 comprises two touch and close fasteners, wherein, in the present case, the barb surfaces 78 of the touch and close fasteners are provided in the upper region of the main section 22 and the loop surfaces 80 of the touch and close fasteners are provided in the lower region of the extension section 24. If the zipper strips 28 and 30 which are illustrated in figure 1 are brought into engagement with each other by actuation of the zipper slide 32, the extension section 24 can be folded up downward in such a manner that the barb surfaces 78 are brought into engagement with the corresponding loop surfaces 80 such that the extension section 24 is held, folded in the downward direction, on the inner side of the main section 22, as illustrated in figure 4. The

extension section 24 of the receiving body 12 can thereby be stowed in the position in which the extension section does not increase the height of the receiving body 12. By folding the extension section 24
5 in the downward direction, dirt is prevented from accumulating in the fold of the extension section 24.

In order, in the unfolded state of the extension section 24 of the receiving body 12, which is
10 illustrated in figure 2, to cover the barb surfaces 78 of the touch and close fasteners, which barb surfaces are unpleasant for the small child, strip-shaped covering elements 82 are provided which, as shown on the left in figure 2, can be arranged over the barb
15 surfaces 78 of the touch and close fasteners. When the extension section 24 is folded up, the covering elements 82 can be folded to the side, as indicated on the right in figure 2, and therefore the barb surfaces 78 can be brought into engagement with the loop
20 surfaces 80.

Figures 3 and 4 show the carrying device 10 illustrated in figures 1 and 2 in the state in which the extension section 24 is folded up. In this state, the zipper
25 strips 28 and 30 are in engagement with each other, as shown in figure 3, and the extension section 24 is folded inward in the downward direction forming a loop, wherein the barb surfaces 78 and the loop surfaces 80 of the touch and close fasteners are in engagement with
30 one another, as can be seen in figure 4.

Figure 5 shows a front view of the carrying device 10 illustrated in figures 1 to 4 in a state in which a seat reduction device 90, which in the previous
35 illustrations was accommodated folded up in a pocket 94 provided with a strip-shaped touch and close fastener 92, a zipper or the like, is unfolded. The seat

reduction device 90 is produced from a fabric material and has a substantially trapezoidal cut with an upper edge 96, a lower edge 98 and two curved side edges 100 and 102. The lower edge 98 is fastened fixedly to the main section 22 of the receiving body 12 by means of a seam, and therefore the seat reduction device 90 is designed as a single part with the receiving body 12. The seat reduction device 90 is pulled up between the legs of the small child until it covers the stomach and lower body of the child. It is subsequently folded at the upper, free corners thereof laterally around the receiving body 12 and fixed to the rear side of same. For this purpose, a respective snap fastener member 104 is provided at the upper, free corners of the seat reduction device 90, which snap fastener member can be brought into engagement with one of the snap fastener members 106 or 108 which are correspondingly arranged on the rear side of the extension section 24 and of the end section 26 of the receiving body 12, as can be seen in the detailed rear view according to figure 6. The snap fastener members 104 are brought into engagement with the snap fastener members 106 when the extension section 24 is in the position in which the effective height of the receiving body 12 is increased by said extension section by the height h thereof, and the snap fastener members 104 are brought into engagement with the snap fastener members 108 when the extension section 24 is in the folded up state thereof, as illustrated in figures 3, 4 and 5.

Alternatively, the baby may, of course, also be inserted into the seat reduction device 90 which is already fastened to the rear side of the receiving body 12.

In the seat reduction device 90, a baby which is still relatively small is in particular held higher in the

receiving body 12, with the baby's legs being optimally spread. They may protrude laterally out of the receiving body.

5 The variants mentioned below can be realized with the aid of the seat reduction device 90 and the extension section 24 of the receiving body 12:

- 10 i. Zipper strips 30 and 32 in engagement and seat reduction device 90 in use (for very small children and babies);
- ii. Zipper strips 30 and 32 not in engagement and seat reduction device 90 in use (for very small, but long small children);
- 15 iii. Zipper strips 30 and 32 in engagement and seat reduction device 90 not in use (for small children with long thighs or babies from 3 months) and
- iv. Zipper strips 30 and 32 not in engagement and seat reduction device 90 not in use (for tall small
20 children of up to, for example, approximately 20 kg).

Figure 7 shows a front view of the carrying device 10 in a state in which a head part 110 is in an unfolded
25 position. The head part 110 is produced from a cloth-like material and has a substantially rectangular shape with an upper edge 112, a lower edge 114 and two mutually opposite side edges 116 and 118. The lower edge 114 of the head part 110 is connected fixedly to
30 the upper edge 14 of the receiving body 12 with the aid of a seam. Fastening elements 120 in the form of elastic cords are sewn into the side edges 116 and 118 of the head part 110, the ends of which fastening elements protrude in each case over the upper edge 112
35 and form a loop. The loops are placed around T-shaped projections of the receiving elements 76 which are positioned on the shoulder straps 62. If the receiving

elements 76 are moved together with the fastening elements 120, which are arranged thereon, of the head part 110 in the direction of the arrows 122, the head part 110 is correspondingly tensioned. By contrast, if
5 the receiving elements 76 are moved in the direction of the arrows 124, the head part 110 is relaxed.

Figure 8 shows a front view of a further embodiment of a carrying device 140, the construction of which
10 substantially corresponds to parts of the carrying device 10 illustrated in figures 1 to 7. In contrast to the carrying device 10, the carrying device 140 additionally comprises a chest strap device 142 with a chest strap 144 which is fastened at the free ends
15 thereof at a corresponding height to the shoulder straps 62, the chest strap 144 being displaceable in the direction of extent of the shoulder straps 62, which is indicated by the arrows 146 in figure 8.

20 For the releasable fastening of the chest strap 144, the latter comprises a closure element 148 with closure members 150 and 152 which can be plugged separately one into the other. An adjustment device 154 is designed as a single part with the closure member 152 and can be
25 used to adjust the chest strap 144 in respect of the length thereof in a known manner.

Furthermore, the carrying device 140 comprises the head part 110 of the embodiment, illustrated in figures 1 to
30 7, of the carrying device 10 according to the invention, only said head part is shown in the tightened together state. In order to tighten together the head part 110, the receiving elements are moved downward in the direction of the arrows 124, and the
35 elastic cords, which form the fastening elements 120, are pulled downward, as shown by the arrow 156.

The head part 110 which is illustrated in figures 7 and 8 serves in the tightened together state primarily as a headrest for sleeping children, the neck muscles of whom are relaxed in this state such that the head tends
5 to tilt away to the rear. By contrast, in the tensioned state, the head part 110 serves as a sunshield.

The head part 110 can be rolled up or folded and stowed in a pocket 158 which is formed in the end section 26
10 of the receiving body 12.

Furthermore, the head part 110 can also be designed in the manner of a hood, but this is not illustrated in the figures.

15 The carrying device according to the invention ensures an orthopedically correct manner of support which is adapted both to the needs of the small child and also to those of the wearer. By means of the different
20 adjustment variants which are made possible by the extension element for extending the receiving body and the seat reduction device, small children of very different heights, in particular even small children immediately after birth, can be received in the
25 carrying device according to the invention. The carrying device has a very low weight and can be folded up compactly.

The invention is not restricted to one of the above-described embodiments, but rather can be modified in
30 diverse ways.

All of the features and advantages emerging from the claims, the description and the drawing, including
35 structural details, three-dimensional arrangements and method steps, may be essential to the invention both on their own and in a great variety of combinations.

List of reference numbers

	10	Carrying device
	12	Receiving body
5	14	Upper edge
	16	Lower edge
	18	Side edge
	20	Side edge
	22	Main section
10	24	Extension section
	26	End section
	28	Zipper strip
	30	Zipper strip
	32	Zipper slide
15	34	Tuck
	36	Clip
	40	Hip strap device
	42	Base body
	44	Tuck
20	46	Cutouts
	48	Hip strap
	50	Closure element
	52	Closure member
	54	Closure member
25	56	Safety device
	58	Adjustment device
	60	Shoulder strap device.
	62	Shoulder straps
	64	Strap section
30	65	Padded section
	66	Closure member
	68	Closure member
	69	Safety device
	70	Adjustment device
35	72	Adjustment device
	74	Ring
	76	Receiving elements

	78	Barb surfaces
	80	Loop surfaces
	82	Covering elements
	90	Seat reduction device
5	92	Touch and close fastener
	94	Pocket
	96	Upper edge
	98	Lower edge
	100	Side edge
10	102	Side edge
	104	Snap fastener members
	106	Snap fastener members
	108	Snap fastener members
	110	Head part
15	112	Upper edge
	114	Lower edge
	116	Side edge
	118	Side edge
	120	Fastening elements
20	122	Arrows
	124	Arrows
	140	Carrying device
	142	Chest strap device
	144	Chest strap
25	146	Arrows
	148	Closure element
	150	Closure member
	152	Closure member
	154	Adjustment device
30	156	Arrow
	158	Pocket

Patent Claims

1. A carrying device with a receiving body for
5 receiving a baby or small child, wherein the receiving
body is designed in such a manner that at least one
area of the rear side of the baby or small child can be
received and/or can be supported therein, and with a
holding harness system for fastening the receiving body
10 to a person, wherein the receiving body is furthermore
designed in such a manner that the height thereof can
be changed due to the carrying device has at least one
extension element which can be positioned on the
receiving body in such a manner that the receiving body
15 is extended in the vertical direction by the extension
element, whereat the receiving body consists of a main
section and an above arranged end section and the
extension element can be arranged between the main
section and the end section.

2. The carrying device as claimed in claim 1, characterized in that the extension element is fastened releasably to the receiving body.

5 3. The carrying device as claimed in claim 1, characterized in that the extension element is designed as a single part with the receiving body.

10 4. The carrying device as claimed in claim 1, characterized in that the extension element can be adjusted between at least two positions, specifically a first position, in which the height of the receiving body is not increased, and a second position, in which the height of the receiving body is increased.

15 5. The carrying device as claimed in claim 4, characterized in that the extension element can be folded from the first position into the second position, and vice versa.

20 6. The carrying device as claimed in claim 4, characterized in that the extension element can be rolled up and unrolled from the first position into the second position.

25 7. The carrying device as claimed in one of claims 4 to 6, characterized in that a fastening device is provided in order to fix the extension element in the first position thereof.

30 8. The carrying device as claimed in claim 7, characterized in that the fastening device has a zipper and/or snap fasteners and/or touch and close fasteners.

35 9. The carrying device as claimed in claim 8, characterized in that if the fastening device has touch and close fasteners, covering means with which

touch and close fastener regions can be covered in the second position of the extension element are provided.

- 5 10. The carrying device as claimed in any one of the preceding claims, characterized in that said carrying device has a seat reduction device.

- 10 11. The carrying device as claimed in claim 10, characterized in that the seat reduction device can be positioned on the receiving body in such a manner that a baby or a small child is received in an elevated position in the receiving body.

- 15 12. The carrying device as claimed in one of claims 10 or 11, characterized in that the seat reduction device can be fastened releasably to the receiving body.

- 20 13. The carrying device as claimed in any one of claims 10 or 11, characterized in that the seat reduction device is designed as a single part with the receiving body.

- 25 14. The carrying device as claimed in any one of claims 10 to 13, characterized in that the seat reduction device can be adjusted between at least two positions, specifically a first position, in which it reduces the height of the seat of the child in the receiving body, and a second position, in which it does
30 not reduce the height of the seat of the child in the receiving body.

15. The carrying device as claimed in any one of the preceding claims, characterized in that said carrying device has a head part.

5 16. The carrying device as claimed in claim 15, characterized in that the head part is connected releasably to the receiving body.

10 17. The carrying device as claimed in claim 15, characterized in that the head part is connected fixedly to the receiving body.

15 18. The carrying device as claimed in any one of claims 15 to 17, characterized in that the head part has fastening elements which can be positioned on the carrying harness system.

20 19. The carrying device as claimed in claim 18, characterized in that the fastening elements are designed in such a manner that they can tension or tighten up the head part.

25 20. The carrying device as claimed in claim 18 or 19, characterized in that receiving elements for receiving the fastening elements are arranged on the carrying harness system.

30 21. The carrying device as claimed in claim 20, characterized in that the receiving elements are arranged movably on the carrying harness system, said receiving elements being designed in such a manner that they can optionally be fixed at different positions on the carrying harness system.