

CLAIMS

5 1. A method for beamforming information interaction, comprising:

receiving, by a first network device, first beamforming information sent by a second network device, the first network device being a network device corresponding to a present serving cell for a terminal, the second network device being a neighbouring network device of the first network device, wherein the first
10 beamforming information comprises first measurement configuration information which comprises at least one of a measurement frequency, a measurement cycle, a measurement duration, a measurement mode or a beamforming resource allocation parameter; and

15 configuring, by the first network device, the terminal according to the first beamforming information.

2. The method of claim 1, wherein configuring, by the first network device, the terminal according to the first beamforming information comprises:

20 configuring, by the first network device, the terminal for beam measurement according to the first measurement configuration information.

3. The method of claim 2, further comprising:

25 sending, by the first network device, parameter request information to the second network device, the parameter request information being configured to request the second network device for the first measurement configuration information.

4. The method of claim 2 or 3, wherein the first measurement configuration information further comprises at least one of a beam index, an identifier of a beam group to which the beam belongs, a cell identifier corresponding to the beam, an
30 identifier of an Access Point (AP) corresponding to the beam, an identifier of a base station corresponding to the beam, or information of a reference signal corresponding to the beam.

5. The method of any one of claims 2-4, wherein the first measurement configuration

information is carried in network device configuration signaling or handover configuration signaling, and the network device configuration signaling comprises establishing signaling of a network device interface or updating signaling of a network device configuration.

5

6. The method of claim 1, wherein the first beamforming information further comprises a first measurement result, and configuring, by the first network device, the terminal according to the first beamforming information comprises:

10 performing, by the first network device, a cell handover for the terminal according to the first measurement result.

7. The method of claim 6, further comprising:

15 sending, by the first network device, second measurement configuration information to the terminal, the second measurement configuration information being configured to instruct the terminal to send an uplink signal on the beam according to the second measurement configuration information; and

performing, by the first network device, beam measurement to obtain a second measurement result based on the uplink signal, wherein

20 performing, by the first network device, the cell handover for the terminal according to the first measurement result comprises:

performing, by the first network device, the cell handover for the terminal according to the first measurement result and the second measurement result.

8. The method of claim 6, further comprising:

25 sending, by the first network device, measurement configuration coordination information to the second network device, the measurement configuration coordination information being configured to coordinate with the second network device about measurement configuration information used for measurement of an uplink signal on the beam; and

30 receiving, by the first network device, feedback information of the measurement configuration coordination information from the second network device.

9. The method of any one of claims 6-8, wherein the first measurement result is

carried in handover configuration signaling, and the handover configuration signaling comprises handover request signaling or handover confirmation signaling.

10. A network device, the network device being a first network device and
5 comprising:

a receiving module, configured to receive first beamforming information sent by a second network device, the first network device being a network device corresponding to a present serving cell for a terminal, the second network device being a neighbouring network device of the first network device, wherein the first
10 beamforming information comprises first measurement configuration information which comprises at least one of a measurement frequency, a measurement cycle, a measurement duration, a measurement mode or a beamforming resource allocation parameter; and

a processing module, configured to configure the terminal according to the
15 first beamforming information received by the receiving module.

11. The network device of claim 10, wherein the processing module is specifically configured to:

configure the terminal for beam measurement according to the first
20 measurement configuration information.

12. The network device of claim 11, further comprising a sending module, configured to send parameter request information to the second network device, the parameter request information being configured to request the second network device for the
25 first measurement configuration information.

13. The network device of claim 11 or 12, wherein the first measurement configuration information further comprises at least one of a beam index, an identifier of a beam group to which the beam belongs, a cell identifier corresponding to the beam, an identifier of an Access Point (AP) corresponding to the beam, an identifier
30 of a base station corresponding to the beam or information of a reference signal corresponding to the beam.

14. The network device of claim 10, wherein the first beamforming information further comprises a first measurement result, and the processing module is specifically configured to:

5 perform a cell handover for the terminal according to the first measurement result.

15. The network device of claim 14, further comprising a sending module, configured to send second measurement configuration information to the terminal, the second measurement configuration information being configured to instruct the terminal to
10 send an uplink signal on the beam according to the second measurement configuration information, wherein

 the processing module is further configured to perform beam measurement to obtain a second measurement result based on the uplink signal; and

 the operation that the processing module performs the cell handover for the
15 terminal according to the first measurement result comprises:

 performing the cell handover for the terminal according to the first measurement result and the second measurement result.

16. The network device of claim 14, further comprising a sending module, configured
20 to send measurement configuration coordination information to the second network device, the measurement configuration coordination information being configured to coordinate with the second network device about measurement configuration information used for measurement of an uplink signal on the beam, wherein

 the receiving module is further configured to receive feedback information of
25 the measurement configuration coordination information from the second network device.