

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 390 268 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
17.01.1996 Bulletin 1996/03

(51) Int Cl.⁶: **G11B 27/28**, G11B 7/013
// G11B20/18, G11B11/10

(21) Application number: **90200687.3**

(22) Date of filing: **23.03.1990**

(54) **Method of and device for recording data signals on a record carrier of an inscribable type**

Verfahren und Anordnung zum Aufzeichnen von Datensignalen auf einem Aufzeichnungsträger
einer beschreibbaren Art

Procédé et dispositif d'enregistrement de signaux de données sur un support d'information de type
enregistrable

(84) Designated Contracting States:
AT BE CH DE ES FR GB IT LI NL SE

(30) Priority: **29.03.1989 NL 8900766**
28.11.1989 NL 8902931

(43) Date of publication of application:
03.10.1990 Bulletin 1990/40

(73) Proprietor: **Philips Electronics N.V.**
NL-5621 BA Eindhoven (NL)

(72) Inventors:
• **Roth, Rudolf**
NL-5656 AA Eindhoven (NL)
• **Van der Zande, Paulus Cristianus Maria**
NL-5656 AA Eindhoven (NL)

(74) Representative:
Groenendaal, Antonius Wilhelmus Maria et al
NL-5656 AA Eindhoven (NL)

(56) References cited:
EP-A- 0 119 657 **EP-A- 0 164 131**
EP-A- 0 215 133 **EP-A- 0 275 972**
EP-A- 0 281 415 **EP-A- 0 288 571**
EP-A- 0 292 917 **EP-A- 0 325 330**
GB-A- 2 187 008

- **PATENT ABSTRACTS OF JAPAN** vol. 12, no. 136 (P-694)(2983) 26 April 1988, & JP-A- 62 256289 (TOSHIBA CORP.) 07 November 1987
- **PATENT ABSTRACTS OF JAPAN** vol. 12, no. 123 (P-690)(2970) 16 April 1988, & JP-A- 62 246193 (NEC CORP.) 27 October 1987
- **PATENT ABSTRACTS OF JAPAN** vol. 13, no. 524 (P-964)(3872) 22 November 1989, & JP-A-01 213883 (FUJITSU GENERAL, LTD.) 28 August 1989

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 0 390 268 B1

Description

The invention relates to a method of recording a series of data signals on a record carrier of an inscribable type, a definitive table of contents in the form of a definitive address information signal being recorded on the record carrier after the last data signal of the series has been recorded, which table of contents specifies addresses of the positions on the record carrier where the data signals have been recorded, the table of contents being of a type which cannot be extended without adaptation of the data included in the table prior to extension.

The invention further relates to a device for recording a series of data signals, which device comprises means for generating a definitive table of contents after the last data signal of the series has been recorded, which definitive table of contents specifies the addresses of the positions on the record carrier where the data signals have been recorded, the definitive table of contents being of a type which cannot be extended without adaptation of the data included in the table prior to extension, the device further comprising means for causing the definitive table of contents to be recorded on the record carrier in the form of a definitive address information signal.

Such a method and such devices are known from EP-A-0,215,133. The method and the device described therein are suitable for recording data signals in the form of standard CD-signals on record carriers of a write-once type.

A problem encountered when the table of contents, which is the "Table of Contents" prescribed by the CD standard, is recorded is that the "Table of Contents" cannot be recorded until the last data signal of the series has been recorded.

However, it is desirable that also in the process of recording the data signals information is available about the positions of the data signals already recorded. Therefore, in the known device a list is kept of the addresses of the data signals already recorded. This list is updated each time that a new data signal is recorded.

When a partly inscribed record carrier is reinserted the problem occurs that no list is available of the addresses of the data signals recorded on the record carrier. During a suitable search process such a list is then derived from address information obtained by reading parts of the data signals already recorded. Such a search process is very complex and also time-consuming.

It is an object of the invention to provide a method and a device which mitigate the above drawbacks.

According to the invention the method is characterized in that a temporary table of contents in the form of a temporary address information signal is recorded, the temporary table of contents being of a type which can be extended without adaptation of the data already included in the table prior to extension, the definitive table of contents being generated on the basis of the data in the temporary table of contents. The recording device in accordance with the invention is characterized in that the device

comprises means for causing a temporary table of contents in the form of a temporary address information signal to be recorded on the record carrier, the temporary table of contents being of a type which can be extended without adaptation of the data already included in the table prior to extension, means for adapting the recorded temporary table of contents after one or more data signals of the series has been recorded, the means for generating the definitive table of contents being adapted to generate said table of contents on the basis of the recorded temporary table of contents.

Such a temporary table of contents enables the recorded address information signal to be updated, so that when a partly inscribed record carrier is reinserted the address information can be obtained simply by reading the temporary table of contents.

An embodiment of the method is characterized in that the temporary table of contents, in the form of a temporary address information signal, is recorded on the record carrier outside the area intended for recording the data signals and the definitive address information signal. When standard CD-signals are recorded this embodiment enables the temporary table of contents to be recorded outside the area intended for the storage of signals in conformity with the CD-Audio or CD-ROM standard. Since the CD-Audio and CD-ROM playing equipment which is already commercially available does not read the information outside this area, the process of reading a record carrier on which a CD-signal is recorded in conformity with the above method will not be influenced by the presence of the temporary table of contents on the record carrier. This means that inscribed record carriers thus obtained can be read by means of equipment for reading Compact Discs of the read-only type already in use at the consumers'. Moreover, the temporary table of contents is always available on the record carrier, which means that the data signals can readily be recorded by different recording devices. When standard CD-signals are recorded on a disc-shaped record carrier the temporary table of contents can be recorded, for example, before the lead-in track at the inner side of the record carrier or after the lead-out track at the outer side of the record carrier. Recording the temporary table of contents after the lead-out track may give rise to problems. On account of variations in track pitch the variation in the overall playing time of a record carrier is approximately 15%, which makes it difficult to define a location for recording the temporary table of contents after the lead-out track. Moreover, reading information situated very close to the edge is less reliable owing to height variations caused by the position of the disc.

Another embodiment of the method which mitigates said drawbacks is characterized in that the temporary table of contents is recorded on the record carrier as a temporary address information signal, the relationship between the temporary address information signal and the information represented thereby deviating from the relationship between said other recorded signals and the in-

formation represented by said other signals. If a record carrier inscribed in conformity with this embodiment of the method is read, the temporary address information signal thus read cannot be processed and will therefore be ignored.

A further embodiment of the method is characterized in that the data signals and the definitive address information signal comprise first error-detection signals which exhibit a first relationship with the signals in which they are comprised, the temporary address information signal comprising second error-detection signals which exhibit a second relationship with the signal in which they are comprised, the first and the second relationship being different. This embodiment has the advantage that the manner in which addresses are encoded in the temporary address information signal can be the same as the manner in which the addresses in the definitive address information signal are assigned, except for the error-detection signals. This has the advantage that conversion of the temporary address information signal can be very simple.

The method in accordance with the invention is very suitable for recording data signals and a definitive address information signal in the form of a "Table of Contents" as specified by one of the CD-standards (CD-Audio and CD-ROM) on an inscribable record carrier. However, the invention is not limited to such a use and can also be applied to other recording systems in which updating of previously recorded contents information presents problems.

The scope of the invention is not limited to its use in conjunction with write-once record carriers. In the case of re-inscribable record carriers the method and device in accordance with the invention preclude unnecessary loss of time required to re-record the entire table of contents each time that the recorded table of contents is to be updated.

In the event that information signals corresponding to the said CD-standards are recorded an embodiment of the method may be further characterized in that the temporary address information signal is recorded as a sequence of groups of subcode frames, each group representing the address information for one recorded information signal, and each group comprises a sequence of a predetermined number of subsequent subcode frames with the same address information, the individual subcode frames of each group comprising a sequence code indicating the sequence number of that frame in the group.

The use of the sequence code enables that the end of the temporary address information signal already recorded can be determined with high accuracy. So a good linking between subsequently recorded parts can be quaranteed.

Such linking may be obtained for an embodiment of the method characterized in that before the start of the recording of an extension of the temporary address information signal sequence codes of the subcode frames

forming the temporary address information signal is read out, the recording of the extension being started in response to the read out of the sequence code indicating the last frame of the last group of subcode frames forming the temporary address information signal

The read device in accordance with the invention is characterized in that the device comprises a second error detector for detecting a second predetermined relationship between the error-correction bits and the other bits of the subcodes being read. In this way it is achieved that both the temporary and the definitive table of contents can be read reliably.

Further embodiments and the advantages thereof will now be described in more detail, by way of example, with reference to Figures 1 to 9, in which

Figure 1 is a plan view of a standard CD-Audio or CD-ROM disc,

Figure 2 illustrates the format of a subcode Q-frame as recorded in the lead-in track in conformity with the CD-standard.

Figure 3 shows an example of a table of contents in a format prescribed by the CD-Audio or CD-ROM standard.

Figure 4 gives an example of a temporary table of contents,

Figure 5 gives an example of a method in which the addresses of the temporary table of contents can be inserted in the subcode Q-frame,

Figure 6 shows an embodiment of a device in accordance with the invention,

Figure 7 shows diagrammatically the lay-out of the servo track of an inscribable record carrier,

Figures 8 and 11 show a flow chart of a program for use in the device in accordance with the invention, Figure 9 shows diagrammatically the lay-out of a record carrier inscribed in accordance with the invention, and

Figure 10 shows an embodiment of the read device in accordance with the invention.

The invention will be clarified by a description of embodiments of methods and devices for recording CD-signals on an inscribable record carrier, such that the recorded CD-signals can be read without any problems by a read device which is constructed to read record carriers of the read-only type such as for example a CD-Audio disc or CD-ROM disc. However, first of all a number of aspects of the CD-Audio and the CD-ROM standard which are essential for a correct understanding of the invention will be described briefly.

Figure 1 is a plan view of a standard CD-Audio or CD-ROM disc 1. Such a disc is provided with a spiral information track (not shown), in which a CD-signal is recorded. The disc 1 is divided into a plurality of areas, namely:

1) The program area, which is situated between the

radii r2 and r3. In this area a plurality of data signals are recorded.

2) The lead-in area, which is situated between the radii r1 and r2. This area comprises a lead-in track, in which the addresses of the data signals are recorded in a "Table of Contents" which is included in the Subcode Q-channel.

3) The lead-out area, which is situated between the radii r3 and r4. This area comprises a lead-out track, which directly adjoins the last data signal and which indicates the end of the program area.

Figure 2 illustrates the format of the subcode Q-channel frames in the lead-in track. A frame comprises a section SO, S1 intended for synchronizing purposes and a data section comprising 96 bits (DB). The data section is divided into a number of groups. The data section comprises a group of sixteen error-detection bits CRC, which are derived from the other 80 bits of the data section. The error-detection bits CRC are selected in such a way that when the binary number formed by the data bits DB is divided by a predetermined polynomial the remainder is zero. The polynomial for error detection in the subcode Q-channel in accordance with the CD-standard is equal to $P(x) = X^{16} + X^{12} + X^5 + 1$. For a detailed description of such an error detection reference is made to J. Watkinson, "The art of digital audio", FOCAL PRESS (ISBN 0-240-51270-7), pp. 201-247.

Figure 3 shows an example of a "Table of Contents" for a standard Compact Disc 1, in which a series of 6 data signals is recorded. The left-hand column gives the frame numbers of the subcode Q-channel frames. The other two columns specify the contents of the relevant frame. The code 01-06 (hexadecimal) in the second column (POINT) indicates the sequence numbers of the recorded data signals. Column 3 gives the start address for these data signals by means of an absolute time code. The code AO indicates that the relevant frame specifies the sequence number of the first data signal (in the PMIN-column). The code A1 indicates that the relevant frame specifies the sequence number of the last data signal. The code A2 indicates that the relevant frame specifies the start address of the lead-out track. Every row of the table is recorded three times in the "Table of Contents". Moreover, the "Table of Contents" thus obtained is recorded several times in the lead-in track.

It will be apparent from the above that a "Table of Contents" once it has been composed and recorded cannot be updated with an address of a subsequently added data signal without re-recording the "Table of Contents". If a number of the data signals and a "Table of Contents" should be recorded on a write-once record carrier in such a way that the record carrier thus obtained complies with the above-mentioned specifications for the "Table of Contents" as laid down in the CD-ROM or CD-Audio standard, the fact that this "Table of Contents" cannot be extended poses a problem.

Hereinafter a number of embodiments of the method

and recording devices in accordance with the invention will be described, which solve the above problem.

Figure 4a shows a temporary table of contents, which specifies the start address and the stop address for the consecutive data signals by means of an absolute time code. The column NO gives the sequence number of the data signal. The column CONTROL indicates whether the data signal concerns audio or other data and whether copying is permitted. For this purpose a similar 4-bit code may be employed as the code laid down in the CD-ROM or CD-Audio standard. Each row of this temporary table of contents may be inserted, for example, in a subcode Q-frame, as is illustrated in Figure 5. This temporary table of contents can readily be extended with new address information. Data signals can now be recorded on an inscribable record carrier in the following manner. The first of a series of data signals to be recorded is recorded at the beginning of the program area defined by the radii r2 and r3. This beginning can be found, for example, by the method described in NL-A-8800152 (PHN 12.399), which is herewith incorporated by reference. Said application describes a record carrier with a servo track intended for recording data signals and in which positional information is recorded in a track by means of a preformed track modulation. By reading the pre-recorded information it is simple to locate any desired position in the track.

After the first data signal has been recorded the start and the stop address are included in the temporary table of contents. For every subsequent data signal to be recorded the beginning of the still non-inscribed track is determined by means of the temporary table of contents and subsequently the data signal is recorded in the track contiguously with the data signals already recorded and the temporary table of contents is updated with the address information of this data signal. At the instant that it is decided that no further data signals are to be recorded, for example because the record carrier is full, the definitive "Table of Contents" can be drawn up by means of the temporary table of contents, and the "Table of Contents" thus obtained can be recorded in the lead-in track.

In principle, the temporary table of contents can be stored, for example, in a semiconductor memory which forms part of the recording device. However, suitably the temporary table of contents is recorded on the record carrier itself, at the instant at which the record carrier leaves the recording device. In that case the consecutive data signal can be recorded by means of different recording devices. Figure 4b shows a suitable format for recording the temporary table of contents. In this table the stop and start address is repeated several times for every data signal. This repeated recording has the advantage that the stop and start addresses can be read very reliably. In practice, it is found that repeating every stop and start address ten times results in a very reliable read-out. In the temporary table of contents shown in Figure 4 both the start and the stop address are given. However, in principle it would be adequate to store only the

start addresses because the "Table of Contents" also specifies only the start addresses.

In the temporary table of contents shown in Fig. 4b to each frame a sequence code indicating the sequence number of each frame of a group of frames with the same address information is included in the frame, e.g. in the bitgroup "ZERO" of the frame.

This has the advantage that in reading the sequence codes the end of the temporary table of contents already recorded, and herewith the starting point of the recording of an extension of the recorded temporary table of contents, can be determined with high accuracy. So a good linking of subsequently recorded parts of the temporary table of contents can be guaranteed.

A flow diagram of program for the control of the recording of an extension of the temporary table of contents is shown in Figure 11. In step S110 of this program the last information signal for which address information is recorded in the table of contents is determined. This can simply be done on basis of the read out of temporary table of contents, which is normally made after a record carrier is reinserted in the recording apparatus.

In step S111 a search to the area PMA, in which the temporary table of contents is recorded, is performed. After this area has been reached the read out of the temporary table of contents is started in step S112. In step S113 it is tested whether the number indicated by the bitgroup "POINT" corresponds to the number of the last information signal with address information included in the temporary table of contents. In the event that this part of the temporary table of contents is reached the program proceeds with step S114, otherwise step S113 is executed again. In step S114 it is tested whether the sequence code read out indicates the last frame of a sequence of frames with the same address information. In the event of a positive result of the test in step S115 the recording of the extension of the temporary table of contents is started directly after the read out of the last bitgroup (CRC) of the frame, otherwise the program proceeds with the execution of step S113.

When the temporary table of contents is recorded on the record carrier and such a record carrier is read by means of a read device which is intended exclusively for CD-ROM or CD-Audio discs steps must be taken to ensure that the read process is not disturbed to an undesirable extent by the presence of the recorded temporary table of contents. In an embodiment of the method in accordance with the invention this can be realized simply by recording the temporary table of contents within the area indicated by the radius r1 or outside the area indicated by the radius r4. (This means before the lead-in track or after the lead-out track.). The recording before the radius r1 is to be preferred. In that case the temporary table of contents cannot be read out by CD-players for the read out of "Compact Discs" of the read only type, because in this player the read out of the area before radius r1 is prevented. Recording in the area outside the radius r4 may also present problems because the end of

the lead-out track cannot readily be detected on account of variations in track pitch, as a result of which the overall playing time may exhibit a variation of the order of magnitude of 15%.

In another embodiment of the method in accordance with the invention the temporary table of contents can be recorded in such a way that the recorded signal does not comply with the requirements imposed by the CD-standard on the relationship between the recorded signals and the information represented thereby. In that case a read error will be detected when the temporary table of contents is read by the CD-ROM or CD-Audio player, so that the signal being read will be ignored. Such a deviating relationship can be obtained very simply for the format illustrated in Figure 5 by selecting another relationship between the data bits DB and the error-detection bits CRC. This is possible by selecting the error-detection bits in such a way that upon division of the binary number defined by the data bits by another polynomial, for example $P(X) = X^{16} + X^{15} + X^2 + 1$, the remainder of this division becomes zero. This has the advantage that the subcode Q-frame thus obtained differs from a format prescribed by the CD-Audio or CD-ROM standard to such a small extent that the contents of the sub-Q-frame can be determined but is regarded as being read erroneously. Preferably, such a temporary address information signal, which exhibits a deviating error code, is recorded in the lead-in track, preferably at the beginning of the lead-in track. However, the signal may also be recorded elsewhere, for example at the beginning of the program area defined by the radii r3 and r2. As described hereinbefore, it is preferred to record the temporary table of contents on the record carrier itself. However, it may be advantage to postpone the recording of additions to the temporary table of contents until the instant at which the user wishes to remove the record carrier from the recording device. In the meantime, the additions to the temporary table of contents may be stored in a memory, for example a solid-state memory, of the recording device.

Figure 6 shows an embodiment of a recording device in accordance with the invention. The recording device shown in this Figure is an optical read/write device 60 for optically recording and reading EFM-modulated signals on a record carrier 61 of a write-once type. Such a record carrier 61 may comprise an information layer 62 in the form of, for example, a metal layer or a dye layer, in which optically detectable changes can be obtained with the aid of a radiation beam of sufficiently high intensity. The recording layer 62 comprises a spiral servo track (not shown), which is provided for the purpose for tracking and in which the data signal can be recorded. The positional information, for example in the form of absolute time codes, is recorded in the track by means of a preformed track modulation. Such a record carrier is described in detail in the afore-mentioned Patent Application NL-A-8800152 (PHN 12.399). The record carrier is rotated in the customary manner about an axis 64 by means of a motor 63. An optical read/write head 65 is

arranged opposite the rotating record carrier 61 to record and/or read the information in the servo track by means of a radiation beam 66. The read/write head 65 is movable in a radial direction by means of a radial positioning device, comprising for example a motor 67 and a spindle 68. The read/write head 65 comprises a system of radiation-sensitive detectors, which convert the beam reflected from the information layer 62 into detection signals, which are applied to an EFM demodulation circuit 69, which converts the EFM modulated signal being read into a subcode Q-signal and a main data signal Vo in a customary manner. The detection signals are also applied to a detection signal processing circuit 70, which derives an address signal ATIP from the signal components in the detection signals which are caused by the preformed track modulation.

An example of the circuit 70 is described in detail in PHN 12.399. The address signal ATIP is applied to a control unit 71, which comprises for example a microprocessor 61 of a customary type. The subcode Q-signal on the output of the circuit 69 is also applied to the microprocessor 71 via an error-detection circuit 72. The error-detection circuit 72 comprises two error detectors 73 and 74, which on the basis of the error-detection bits CRC in the subcode Q-frames determine whether read-out of the subcode Q-frame is effected correctly. The binary number defined by the subcode Q-bits of a subcode Q-frame are then divided by a predetermined polynomial and it is tested whether the remainder of the division is zero. The polynomials used for the two error detectors are different. For example, the error detector 73 employs the polynomial $P(x) = X^{16} + X^{12} + X^5 + 1$ prescribed by the CD-standard and the error detector 74 employs the polynomial $p^*(x) = X^{16} + X^{15} + X^5 + 1$ which deviates therefrom. The error detectors may comprise, in a customary manner, shift registers and exclusive OR-gates, as is described in detail in, for example, the afore-mentioned book "The art of Digital Audio". The microprocessor 71 can select one of the error detectors 73 or 74 via a signal line 75. The selected error detector applies the data bits of the subcode Q-frame to the microprocessor 71 together with a signal which indicates whether the received signal is correct. The read/write head 65 can be set to the read mode or to a write mode via a signal line 76. In the read mode the intensity of the radiation beam 66 is inadequate to produce an optically detectable change in the recording layer 62. In the write mode a radiation beam of an intensity which is high enough to produce the optically detectable change is modulated in conformity with a write signal Vs supplied by an EFM-modulation circuit 77. The EFM-modulation circuit 77 is of a customary type, in which an applied data signal Vi and an applied subcode Q-channel component are converted into a signal which is EFM-modulated in conformity with the CD-standard, which signal is subsequently converted into the write signal Vs. The data bits of the subcode Q-frames, with the exclusion of the error-detection bits, are applied to the EFM modulation cir-

cuit 77 via an error-detection-bit generator circuit 78. The circuit 78 derives and inserts the error-detection bits CRC. The circuit 78 comprises two error-detection-bit generators 79 and 80, which in a customary manner derive the error-detection bits by division by a predetermined polynomial. Such a circuit may comprise shift registers and exclusive-OR gates, as described comprehensively in the aforementioned book "The art of Digital Audio". The polynomials used in the error-detection generators 79 and 80 are different, the polynomial used in the generator 79 being for example $p^*(x) = X^{16} + X^{15} + X^2 + 1$ and the polynomial used in the generator 80 being $P(x) = X^{16} + X^{12} + X^5 + 1$, which is the polynomial as specified by the CD-standard. The microprocessor 71 can select one of the two generators 79 and 80 via a signal line 81. The lay-out of a non-inscribed record carrier will be described in more detail with reference to Figure 7, before a detailed description of the operation of the read/write device 60 is given.

Figure 7 shows the spiral servo track diagrammatically as an elongate straight track bearing the reference numeral 82. The record carrier has a centre of rotation ro. The track section LI constitutes the lead-in track. The radii defining the boundaries of the lead-in track are r1 and r2. The values of r1 and r2 are selected in such a way that they are in conformity with the CD-Audio and CD-ROM standard, i.e. the distance from r0 to r1 is 23 mm and the distance from r0 to r2 is 25 mm. The track section following the lead-in track is intended for recording data signals. PMA indicates a section of the lead-in track between r1 and r1'. The section PMA is intended for recording the temporary table of contents. It is to be noted that the length of the temporary table of contents depends on the number of data signals recorded, so that the position of r1' is not fixed. The maximum number of data signals permissible in conformity with the CD-standard is 99. This means that the maximum difference between r1 and r1' is approximately 0.2 mm, which is only 10% of the total length of the lead-in track. Figure 7 also shows the address signal ATIP represented by the preformed track modulation. The signal ATIP indicates the track position expressed in playing time. The value of ATIP is zero at the boundary between the lead-in track section and the track section intended for recording data signals. In the lead-in track the value of ATIP decreases from the maximum time of 99 minutes, 59 seconds, 74 frames and in the section intended for recording the data signals the value of ATIP increases starting from 00:00:00. The operation of the read/write device shown in Figure 6 will now be explained with reference to Figure 8.

Figure 8 shows a flow chart of a control program which is stored in the microprocessor 71 and which is fetched when a data signal is to be recorded. In step S1 of the program the read/write head 75 is brought to the position indicated by the radius r1 under control of the microprocessor 77. By means of the signal ATIP being read, it is possible to determine whether this position is

reached. Once this position is reached the section PMA opposite the read head is read in step S2, in which section the temporary table of contents is recorded in the subcode Q-channel. For the purpose of error detection the error detector 79 is selected, which employs the polynomial $P^*(X)$.

Moreover, by means of the temporary table of contents thus read the start address is determined where recording the new data signal should start. In step S3 the read head is moved to this start address. By means of the signal ATIP being read it is again ascertained whether the starting address is reached. Subsequently, step S4 is carried out, in which the read/write head 65 is set to the write mode. Moreover, the error-bit generator 80 employing the polynomial $P(x)$ is selected. During recording the values of the various data-bit groups are determined in conformity with CD-standard, the value of the bit group ATIME (see Figure 5) being derived from the address signal ATIP being read. Once recording of the data signal to be recorded has been terminated, the read/write head 65 is moved to the track section PMA in step S5, in which section the temporary table of contents is stored, and subsequently the stop and the start address are recorded in the temporary table of contents. This lastmentioned operation is performed during step S6. The start and the stop address are then inserted in a subcode Q-frame in a manner as illustrated in Figure 5. Moreover, the error-detection-bit generator 79 is selected to insert the error-detection bits, which are then determined in accordance with the polynomial $P(x)^*$, which deviates from the CD-standard.

Subsequently, it is ascertained in step S7 whether the recorded data signal is the last of the series of data signals to be recorded. If this is not the case, the program is terminated. If it is the last signal, step S8 is carried out, in which the definitive "Table of Contents" in conformity with the CD-standard is derived from the temporary table of contents and is subsequently recorded after the temporary table of contents in the lead-in track 83. Moreover, the lead-out track is recorded in a manner as laid down in the CD-standard. It is to be noted that the program represented by the flow chart in Figure 8 can be modified in various ways. For example, it is possible to adapt the program in such a way that the adaptations of the temporary table of contents are stored temporarily in the memory of the microprocessor 71 until the instant at which the record carrier 6 is to be removed from the recording device, in which case all additions to the temporary table of contents can be recorded on the record carrier in one recording cycle briefly before removal of the record carrier.

Figure 9 shows the lay-out of the track 82 for a record carrier obtained by means of the device in accordance with the invention, the Figure also indicating the values of the various bit groups in the subcode Q-frames. In Figure 9 the lead-out track is referenced LO and the sections in which three different data signals are recorded are referenced DS1, DS2 and DS3 respectively. As will be ap-

parent from Figure 9, the recording obtained by means of the device in accordance with the invention deviates only slightly from a standard CD-Audio or CD-ROM recording. Only the beginning of the lead-in track differs. However, when this beginning is read by a read device for reading CD-ROM or CD-Audio discs the subcode Q-frames in which the temporary table of contents has been inserted will be regarded as erroneously read subcode Q-frames on account of the deviating error-detection-bit group CRC. This means that this information will be ignored completely.

As will be apparent from the above, the Compact Disc thus obtained can be played without any problems on CD-players which are already on the market. However, for this purpose it is necessary that the definitive "Table of Contents" has been recorded. Since a partly un-inscribed record carrier does not yet comprise a "Table of Contents" such a record carrier can be read only by CD-players already on the market after the record carrier has been "filled" completely and has been provided with a "Table of Contents".

Figure 10 shows an adapted read device 103 which mitigates this drawback. Elements in the read device 103 which correspond to elements already described bear the same reference numerals. In the read device shown in Figure 10 the outputs of both error detectors 73 and 74 are connected to a control unit 100. The control unit 100 is further connected to a memory 101 and a control panel 102. The control unit 100 may comprise a conventional microcomputer loaded with a suitable program. Under control of this program, upon insertion of a new record carrier 61, the read head 65 is positioned opposite the area of the record carrier in which the "Table of Contents" is recorded in the case of a standard read-only Compact Disc. Subsequently, the process of reading the area opposite the read head 65 is started under control of the program.

If the record carrier which has been loaded is a read-only Compact Disc the error detector 73 will supply a signal to the control unit 100 via one of its outputs to indicate that the information being read satisfies the relationship, defined by the polynomial $P(x)$, between the error-detection bits and the other bits of the subcode being read. In that case the subcode information representing the "Table of Contents" and received by the control unit via the error detector 73 is loaded into the memory 101, for example by deriving for every track in the CD signal the sequence number, the start address and the stop address from the "Table of Contents", the information thus derived being subsequently stored in the memory 101. Subsequently, the information recorded on the record carrier is read in the sequence indicated by the user via the control panel 102. To locate the areas of the record carrier where the desired information has been recorded the information stored in the memory 101 is utilised in customary manner. If a record carrier is inserted on which a temporary table of contents has been recorded but which does not yet contain a definitive "Table of

Contents" the error detector 74 will apply a signal to the control unit via one of its outputs to indicate that for the subcodes being read the relationship, defined by the polynomial $P^*(x)$, between the error-detection bit and the other bits of the subcode is satisfied, while during reading of the area intended for the "Table of Contents" the error detector 73 detects errors. Under control of the control unit it is then possible to load information about the temporary table of contents into the memory. This is possible, for example, by deriving the sequence number, the start address and the stop address from the temporary table of contents for every track of the CD signal and by storing the information thus derived in the memory 101.

Subsequently, the information recorded on the record carrier can be read in the sequence specified by the user via the control panel 102. To locate the record-carrier areas to be read the information stored in the memory 101 is used.

It is to be noted that the scope of the invention, in relation to the read device, is not limited to the device illustrated in Figure 10. For example, controlling the read device on the basis of the subcodes being read can be effected in numerous different manners. However, it is essential that the read device is constructed to detect two different relationships between the error-detection bits and the other bits of the subcode, so that it is possible to read both the definitive "Table of Contents" and the temporary table of contents in a reliable manner.

In the embodiment of the recording device described hereinbefore the temporary table of contents is recorded at the beginning of the lead-in track. However, it is alternatively possible to record the temporary table of contents at different locations in the track, for example immediately after the lead-out track or immediately before the lead-in track. In the lastmentioned case a deviating error-detection code is not needed because a commercial available CD-player of the play-back of CD-read only discs is not able to read out the area before the lead-in track. So the play-back of a disc on which a temporary table of contents is recorded at that location cannot be disturbed by the presence of that temporary table. Moreover, it is possible to store the temporary table of contents in a solid-state memory of the recording device. Moreover, it is possible to ensure that during reading of the temporary table of contents this table is ignored by the read device in another manner than by means of a deviating error-detection code, for example by selecting another data format, which differs from the CD-standard, during recording of the temporary table of contents.

Furthermore, it is to be noted that the use of the invention is not limited to the recording of CD-signals. The invention may equally be employed in other recording systems in which the recording format of the table of contents does not allow subsequent extension of the table of contents. For example, it is possible to insert a bit combination in the bit groups ADR and TNO the subcode Q-frame, which combination is not permissible in conformity with the CD-standard. Neither is it necessary to

insert the temporary table of contents in the subcode Q-channel. Alternatively, this temporary table of contents may be inserted in the main channel or in other subcode channels, for example in one or more subcode R-W-channels.

Finally, it is to be noted that the use of the invention is not limited to the recording of data signals on write-once record carriers. The invention may also be utilized for recording on re-inscribable record carriers, because in such cases the repeated formatting and recording of the table of contents may be time-consuming in comparison with the time needed for recording and generating the definitive table of contents in accordance with the invention.

Claims

1. A method of recording a series of data signals on a record carrier of an inscribable type, a definitive table of contents in the form of a definitive address information signal being recorded on the record carrier after the last data signal of the series has been recorded, which table of contents specifies addresses of the positions on the record carrier where the data signals have been recorded, the table of contents being of a type which cannot be extended without adaptation of the data included in the table prior to extension, characterized in that a temporary table of contents in the form of a temporary address information signal is recorded, the temporary table of contents being of a type which can be extended without adaptation of the data already included in the table prior to extension, the definitive table of contents being generated on the basis of the data in the temporary table of contents.
2. A method as claimed in Claim 1, characterized in that the temporary table of contents, in the form of a temporary address information signal, is recorded on the record carrier outside the area intended for recording the data signals and the definitive address information signal.
3. A method as claimed in Claim 1 or 2, characterized in that the temporary table of contents is recorded on the record carrier as a temporary address information signal, the relationship between the temporary address information signal and the information represented thereby deviating from the relationship between said other recorded signals and the information represented by said other signals.
4. A method as claimed in Claim 3, characterized in that the data signals and the definitive address information signal comprise first error-detection signals which exhibit a first relationship with the signals in which they are comprised, the temporary address

Contents" the error detector 74 will apply a signal to the control unit via one of its outputs to indicate that for the subcodes being read the relationship, defined by the polynomial $P^*(x)$, between the error-detection bit and the other bits of the subcode is satisfied, while during reading of the area intended for the "Table of Contents" the error detector 73 detects errors. Under control of the control unit it is then possible to load information about the temporary table of contents into the memory. This is possible, for example, by deriving the sequence number, the start address and the stop address from the temporary table of contents for every track of the CD signal and by storing the information thus derived in the memory 101.

Subsequently, the information recorded on the record carrier can be read in the sequence specified by the user via the control panel 102. To locate the record-carrier areas to be read the information stored in the memory 101 is used.

It is to be noted that the scope of the invention, in relation to the read device, is not limited to the device illustrated in Figure 10. For example, controlling the read device on the basis of the subcodes being read can be effected in numerous different manners. However, it is essential that the read device is constructed to detect two different relationships between the error-detection bits and the other bits of the subcode, so that it is possible to read both the definitive "Table of Contents" and the temporary table of contents in a reliable manner.

In the embodiment of the recording device described hereinbefore the temporary table of contents is recorded at the beginning of the lead-in track. However, it is alternatively possible to record the temporary table of contents at different locations in the track, for example immediately after the lead-out track or immediately before the lead-in track. In the lastmentioned case a deviating error-detection code is not needed because a commercial available CD-player of the play-back of CD-read only discs is not able to read out the area before the lead-in track. So the play-back of a disc on which a temporary table of contents is recorded at that location cannot be disturbed by the presence of that temporary table. Moreover, it is possible to store the temporary table of contents in a solid-state memory of the recording device. Moreover, it is possible to ensure that during reading of the temporary table of contents this table is ignored by the read device in another manner than by means of a deviating error-detection code, for example by selecting another data format, which differs from the CD-standard, during recording of the temporary table of contents.

Furthermore, it is to be noted that the use of the invention is not limited to the recording of CD-signals. The invention may equally be employed in other recording systems in which the recording format of the table of contents does not allow subsequent extension of the table of contents. For example, it is possible to insert a bit combination in the bit groups ADR and TNO the subcode Q-frame, which combination is not permissible in conformity with the CD-standard. Neither is it necessary to

insert the temporary table of contents in the subcode Q-channel. Alternatively, this temporary table of contents may be inserted in the main channel or in other subcode channels, for example in one or more subcode R-W-channels.

Finally, it is to be noted that the use of the invention is not limited to the recording of data signals on write-once record carriers. The invention may also be utilized for recording on re-inscribable record carriers, because in such cases the repeated formatting and recording of the table of contents may be time-consuming in comparison with the time needed for recording and generating the definitive table of contents in accordance with the invention.

Claims

1. A method of recording a series of data signals on a record carrier of an inscribable type, a definitive table of contents in the form of a definitive address information signal being recorded on the record carrier after the last data signal of the series has been recorded, which table of contents specifies addresses of the positions on the record carrier where the data signals have been recorded, the table of contents being of a type which cannot be extended without adaptation of the data included in the table prior to extension, characterized in that a temporary table of contents in the form of a temporary address information signal is recorded, the temporary table of contents being of a type which can be extended without adaptation of the data already included in the table prior to extension, the definitive table of contents being generated on the basis of the data in the temporary table of contents.
2. A method as claimed in Claim 1, characterized in that the temporary table of contents, in the form of a temporary address information signal, is recorded on the record carrier outside the area intended for recording the data signals and the definitive address information signal.
3. A method as claimed in Claim 1 or 2, characterized in that the temporary table of contents is recorded on the record carrier as a temporary address information signal, the relationship between the temporary address information signal and the information represented thereby deviating from the relationship between said other recorded signals and the information represented by said other signals.
4. A method as claimed in Claim 3, characterized in that the data signals and the definitive address information signal comprise first error-detection signals which exhibit a first relationship with the signals in which they are comprised, the temporary address



information signal comprising second error-detection signals which exhibit a second relationship with the signal in which they are comprised, the first and the second relationship being different.

5. A method as claimed in Claim 1 or 2, characterized in that the data signals and the definitive address information signal are recorded in conformity with a CD-standard for read-only record carriers.
6. A method as claimed in Claim 5, characterized in that the temporary address information signal is recorded before the beginning of the lead-in track defined by CD-standard.
7. A method as claimed in Claim 5 or 6, characterized in that the temporary address information signal is recorded as a sequence of groups of subcode frames, each group representing the address information for one recorded information signal, and each group comprises a sequence of a predetermined number of subsequent subcode frames with the same address information, the individual subcode frames of each group comprising a sequence code indicating the sequence number of that frame in the group.
8. A method as claimed in Claim 7, characterized in that before the start of the recording of an extension of the temporary address information signal sequence codes of the subcode frames forming the temporary address information signal are read out, the recording of the extension being started in response to the read out of the sequence code indicating the last frame of the last group of subcode frames forming the temporary address information signal.
9. A device for recording a series of data signals, which device comprises means for generating a definitive table of contents after the last data signal of the series has been recorded, which definitive table of contents specifies the addresses of the positions on the record carrier where the data signals have been recorded, the definitive table of contents being of a type which cannot be extended without adaptation of the data included in the table prior to extension, the device further comprising means for causing the definitive table of contents to be recorded on the record carrier in the form of a definitive address information signal, characterized in that the device comprises means for causing a temporary table of contents in the form of a temporary address information signal to be recorded on the record carrier, the temporary table of contents being of a type which can be extended without adaptation of the data already included in the table prior to extension, means for adapting the recorded temporary table of contents

after one or more data signals of the series has been recorded, the means for generating the definitive table of contents being adapted to generate said table of contents on the basis of the recorded temporary table of contents.

10. A device as claimed in Claim 9, characterized in that the storage means are adapted to record the temporary table of contents as a temporary address information signal in an area on the record carrier which is situated outside the area intended for recording data signals and the definitive address information signal.
11. A device as claimed in Claim 9 or 10, characterized in that the storage means are adapted to record the temporary table of contents on the record carrier as a temporary address information signal in such a way that the relationship between the temporary address information and the information represented thereby deviates from the relationship between said other recorded signals and the information represented by said other signals.
12. A device as claimed in Claim 11, characterized in that the device comprises means for adding first error-detection signals to the data signals and the definitive address-information signal, and means for adding second error-detection signals to the temporary address information signal, the relationship between the first error-detection signals and the signals to which these first error-detection signals have been added deviates from the relationship between the second error-detection signals and the signals to which said second error-detection signals have been added.
13. A device as claimed in Claim 9 or 10, characterized in that the storage means are adapted to record the definitive address information signal in conformity with a CD-standard for read-only record carriers.
14. A device as claimed in Claim 13, characterized in that the storage means are adapted to record the temporary address information signal before the beginning of the lead-in track of the record carrier as defined by the CD-standard.
15. A device as claimed in Claim 13 or 14, characterized in that the means for causing the recording of the temporary address information signal are adapted to record a sequence of a predetermined number of subsequent subcode frames for recorded information signals, each group representing the address information for the corresponding recorded information signal, each subcode frame of the group comprising the same address information, the individual subcode frames of each group comprising a



sequence code indicating the sequence number of that frame within the group.

16. A device as claimed in Claim 15, characterized by means for reading the sequence codes of the subcode frames forming the temporary address information signal before starting the recording of an extension of the temporary address information signal, and means for starting the recording of the extension in response to the read out of the sequence code indicating the last frame of the last group of the subcode frames of the temporary address signal already recorded.

Patentansprüche

1. Verfahren zum Aufzeichnen einer Reihe von Datensignalen auf einem Aufzeichnungsträger einer beschreibbaren Art, wobei nach der Aufzeichnung des letzten Datensignals aus der Reihe ein endgültiges Inhaltsverzeichnis in Form eines endgültigen Adresseninformationssignals auf dem Aufzeichnungsträger aufgezeichnet wird, wobei dieses Inhaltsverzeichnis Adressen der Positionen auf dem Aufzeichnungsträger angibt, bei denen die Datensignale aufgezeichnet worden sind, und wobei das Inhaltsverzeichnis von einer Art ist, die ohne Anpassung der Daten, die vor der Erweiterung bereits in das Verzeichnis aufgenommen worden sind, nicht erweitert werden kann, dadurch gekennzeichnet, daß ein vorläufiges Inhaltsverzeichnis in Form eines vorläufigen Adresseninformationssignals aufgezeichnet wird, wobei das vorläufige Inhaltsverzeichnis von einer Art ist, die ohne Anpassung der vor der Erweiterung bereits in das Verzeichnis aufgenommenen Daten erweitert werden kann, und wobei das endgültige Inhaltsverzeichnis auf Basis der Daten in dem vorläufigen Inhaltsverzeichnis generiert wird.
2. Verfahren nach Anspruch 1, dadurch gekennzeichnet, daß das vorläufige Inhaltsverzeichnis in Form eines vorläufigen Adresseninformationssignals außerhalb des zum Aufzeichnen der Datensignale und des endgültigen Adresseninformationssignals bestimmten Gebiets auf dem Aufzeichnungsträger aufgezeichnet wird.
3. Verfahren nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß das vorläufige Inhaltsverzeichnis als ein vorläufiges Adresseninformationssignal auf dem Aufzeichnungsträger aufgezeichnet wird, wobei die Beziehung zwischen dem vorläufigen Adresseninformationssignal und der durch dieses repräsentierten Information von der Beziehung zwischen den genannten anderen aufgezeichneten Signalen und der durch diese anderen Signale repräsentierten Information abweicht.
4. Verfahren nach Anspruch 3, dadurch gekennzeichnet, daß die Datensignale und das endgültige Adresseninformationssignal erste Fehlerdetektionssignale umfassen, die eine erste Beziehung zu denjenigen Signalen aufweisen, in denen sie enthalten sind, wobei das vorläufige Adresseninformationssignal zweite Fehlerdetektionssignale umfaßt, die eine zweite Beziehung zu demjenigen Signal aufweisen, in dem sie enthalten sind, wobei die erste und die zweite Beziehung unterschiedlich sind.
5. Verfahren nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß die Datensignale und das endgültige Adresseninformationssignal entsprechend einem CD-Standard für ausschließlich auslesbare Aufzeichnungsträger aufgezeichnet werden.
6. Verfahren nach Anspruch 5, dadurch gekennzeichnet, daß das vorläufige Adresseninformationssignal vor dem Anfang der durch den CD-Standard festgelegten Anlaufspur aufgezeichnet wird.
7. Verfahren nach Anspruch 5 oder 6, dadurch gekennzeichnet, daß das vorläufige Adresseninformationssignal als Folge von Gruppen von Subcodierahmen aufgezeichnet wird, wobei jede Gruppe die Adresseninformation für ein einziges aufgezeichnetes Informationssignal repräsentiert, und jede Gruppe eine Folge aus einer vorgegebenen Anzahl nachfolgender Subcodierahmen mit der gleichen Adresseninformation umfaßt, wobei die einzelnen Subcodierahmen jeder Gruppe einen laufenden Code umfassen, der die laufende Nummer dieses Rahmens in der Gruppe angibt.
8. Verfahren nach Anspruch 7, dadurch gekennzeichnet, daß vor dem Beginn des Aufzeichnens einer Erweiterung des vorläufigen Adresseninformationssignals laufende Codes der Subcodierahmen, die das vorläufige Adresseninformationssignal bilden, ausgelesen werden, wobei das Aufzeichnen der Erweiterung in Reaktion auf das Auslesen des laufenden Codes, der den letzten Rahmen der letzten Gruppe von das vorläufige Adresseninformationssignal bildenden Subcodierahmen angibt, gestartet wird.
9. Einrichtung zum Aufzeichnen einer Reihe von Datensignalen, wobei die Einrichtung Mittel umfaßt zum Generieren eines endgültigen Inhaltsverzeichnisses nach der Aufzeichnung des letzten Datensignals aus dieser Reihe, wobei dieses endgültige Inhaltsverzeichnis die Adressen der Positionen auf dem Aufzeichnungsträger angibt, bei denen die Datensignale aufgezeichnet worden sind, und wobei das endgültige Inhaltsverzeichnis von einer Art ist, die ohne Anpassung der Daten, die vor der



Erweiterung bereits in das Verzeichnis aufgenommen worden sind, nicht erweitert werden kann, wobei diese Einrichtung ferner Mittel umfaßt zum Bewirken einer Aufzeichnung des endgültigen Inhaltsverzeichnisses auf dem Aufzeichnungsträger in Form eines endgültigen Adresseninformationssignals, dadurch gekennzeichnet, daß die Einrichtung Mittel zum Bewirken der Aufzeichnung eines vorläufigen Inhaltsverzeichnisses in Form eines vorläufigen Adresseninformationssignals auf dem Aufzeichnungsträger umfaßt, wobei das vorläufige Inhaltsverzeichnis von einer Art ist, die ohne Anpassung der bereits in dem Verzeichnis vor der Erweiterung vorhandenen Daten erweitert werden kann, sowie Mittel zum Anpassen des aufgezeichneten vorläufigen Inhaltsverzeichnisses nach Aufzeichnung eines oder mehrerer Datensignale aus der Reihe, wobei die Mittel zum Generieren des endgültigen Inhaltsverzeichnisses eingerichtet sind, dieses Inhaltsverzeichnis auf Basis des aufgezeichneten vorläufigen Inhaltsverzeichnisses zu generieren.

10. Einrichtung nach Anspruch 9, dadurch gekennzeichnet, daß die Speichermittel eingerichtet sind zum Aufzeichnen des vorläufigen Inhaltsverzeichnisses in Form eines vorläufigen Adresseninformationssignals in einem Gebiet auf dem Aufzeichnungsträger, das außerhalb des Gebiets liegt, das zum Aufzeichnen von Datensignalen und des endgültigen Adresseninformationssignals bestimmt ist.

11. Einrichtung nach Anspruch 9 oder 10, dadurch gekennzeichnet, daß die Speichermittel eingerichtet sind, das vorläufige Inhaltsverzeichnis auf dem Aufzeichnungsträger in Form eines vorläufigen Adresseninformationssignals so aufzuzeichnen, daß die Beziehung zwischen der vorläufigen Adresseninformation und der durch diese repräsentierten Information von der Beziehung zwischen den genannten anderen aufgezeichneten Signalen und der durch diese anderen Signale repräsentierten Information abweicht.

12. Einrichtung nach Anspruch 11, dadurch gekennzeichnet, daß die Einrichtung Mittel zum Hinzufügen erster Fehlerdetektionssignale zu den Datensignalen und dem endgültigen Adresseninformationssignal umfaßt sowie Mittel zum Hinzufügen zweiter Fehlerdetektionssignale zu dem vorläufigen Adresseninformationssignal, wobei die Beziehung zwischen den ersten Fehlerdetektionssignalen und den Signalen, denen diese ersten Fehlerdetektionssignale zugefügt worden sind, von der Beziehung zwischen den zweiten Fehlerdetektionssignalen und den Signalen, denen diese zweiten Fehlerdetektionssignale zugefügt worden sind, abweicht.

13. Einrichtung nach Anspruch 9 oder 10, dadurch

gekennzeichnet, daß die Speichermittel zum Aufzeichnen des endgültigen Adresseninformationssignals entsprechend einem CD-Standard für ausschließlich auslesbare Aufzeichnungsträger eingerichtet sind.

14. Einrichtung nach Anspruch 13, dadurch gekennzeichnet, daß die Speichermittel zum Aufzeichnen des vorläufigen Adresseninformationssignals vor dem Anfang der durch den CD-Standard festgelegten Anlaufspur des Aufzeichnungsträgers eingerichtet sind.

15. Einrichtung nach Anspruch 13 oder 14, dadurch gekennzeichnet, daß die Mittel zum Bewirken des Aufzeichnens des vorläufigen Adresseninformationssignals eingerichtet sind, eine Folge einer vorbestimmten Anzahl aufeinanderfolgender Subcodierahmen für aufgezeichnete Informationssignale aufzuzeichnen, wobei jede Gruppe die Adresseninformation für das entsprechende aufgezeichnete Informationssignal repräsentiert, jeder Subcodierahmen der Gruppe die gleiche Adresseninformation umfaßt, und die einzelnen Subcodierahmen jeder Gruppe einen laufenden Code umfassen, der die laufende Nummer dieses Rahmens innerhalb der Gruppe angibt.

16. Einrichtung nach Anspruch 15, gekennzeichnet durch Mittel zum Lesen der laufenden Codes der das vorläufige Adresseninformationssignal bildenden Subcodierahmen vor dem Beginn des Aufzeichnens einer Erweiterung des vorläufigen Adresseninformationssignals und Mittel zum Starten des Aufzeichnens einer Erweiterung in Reaktion auf das Auslesen des laufenden Codes, der den letzten Rahmen der letzten Gruppe des Subcodierahmen des bereits aufgezeichneten Adresseninformationssignals angibt.

Revendications

1. Procédé d'enregistrement d'une série de données sur un support d'enregistrement de type enregistrable, une table des matières définitive ayant la forme d'un signal d'information d'adresse définitif enregistré sur le support d'enregistrement après que le dernier signal de données de la série a été enregistré, ladite table des matières spécifiant les adresses des positions sur le support d'enregistrement où les signaux de données ont été enregistrés, la table des matières étant d'un type qui ne peut pas être étendu sans adaptation des données incluses dans la table avant extension, caractérisé en ce qu'on enregistre une table des matières temporaire sous la forme d'un signal d'information d'adresse temporaire, la table des matières temporaire étant d'un type qui



peut être étendu sans adaptation des données déjà comprises dans la table avant l'extension, la table des matières définitive étant générée sur la base des données de la table des matières temporaire.

2. Procédé selon la revendication 1, caractérisé en ce que la table des matières temporaire est enregistrée sous la forme d'un signal d'information d'adresse temporaire sur le support d'enregistrement à l'extérieur de la zone destinée à l'enregistrement des signaux de données et du signal d'information d'adresse définitif.
3. Procédé selon la revendication 1 ou 2, caractérisé en ce que la table des matières temporaire est enregistrée sur le support d'enregistrement sous la forme d'un signal d'information d'adresse temporaire, la relation entre le signal d'information d'adresse temporaire et les informations représentées par celui-ci s'écartant de la relation entre lesdits autres signaux enregistrés et les informations représentées par lesdits autres signaux.
4. Procédé selon la revendication 3, caractérisé en ce que les signaux de données et le signal d'information d'adresse définitif comprennent des premiers signaux de détection d'erreurs qui présentent une première relation avec les signaux dans lesquels ils sont compris, le signal d'information d'adresse temporaire comprenant des deuxième signaux de détection d'erreurs qui présentent une deuxième relation avec le signal dans lequel ils sont compris, la première et la deuxième relations étant différentes.
5. Procédé selon la revendication 1 ou 2, caractérisé en ce que les signaux de données et le signal d'information d'adresse définitif sont enregistrés en conformité avec un standard CD pour des supports d'enregistrement à lecture seulement.
6. Procédé selon la revendication 5, caractérisé en ce que le signal d'information d'adresse temporaire est enregistré avant le début de la piste initiale définie par le standard CD.
7. Procédé selon la revendication 5 ou 6, caractérisé en ce que le signal d'information d'adresse temporaire est enregistré sous la forme d'une séquence de groupes de trames de sous-codes, chaque groupe représentant les informations d'adresse pour un signal d'information enregistré, et chaque groupe comprend une séquence d'un nombre prédéterminé de trames de sous-codes ultérieures avec les mêmes informations d'adresse, les trames de sous-codes individuelles de chaque groupe comprenant un code de séquence indiquant le numéro de séquence de cette trame dans le groupe.

8. Procédé selon la revendication 7, caractérisé en ce que, avant le début de l'enregistrement d'une extension du signal d'information d'adresse temporaire, des codes de séquence des trames de sous-codes formant le signal d'information d'adresse temporaire sont extraits par lecture, l'enregistrement de l'extension étant amorcé en réaction à l'extraction du code de séquence indiquant la dernière trame du dernier groupe des trames de sous-codes formant le signal d'information d'adresse temporaire.
9. Dispositif pour enregistrer une série de signaux de données, ledit dispositif comprenant des moyens pour générer une table des matières définitive après que le dernier signal de données de la série a été enregistré, ladite table des matières définitive spécifiant les adresses des positions sur le support d'enregistrement où les signaux de données ont été enregistrés, la table des matières définitive étant d'un type qui ne peut être étendu sans adaptation des données comprises dans la table avant extension, le dispositif comprenant, en outre, des moyens pour amener la table des matières définitive à être enregistrée sur le support d'enregistrement sous la forme d'un signal d'information d'adresse définitif, caractérisé en ce que le dispositif comprend des moyens pour provoquer l'enregistrement d'une table des matières temporaire sous la forme d'un signal d'information d'adresse temporaire sur le support d'enregistrement, la table des matières temporaire étant d'un type qui peut être étendu sans adaptation des données déjà comprises dans la table avant l'extension, des moyens pour adapter la table des matières temporaire enregistrée après qu'un ou plusieurs des signaux de données de la série ont été enregistrés, les moyens destinés à générer la table des matières définitive étant à même de générer ladite table des matières sur la base de la table des matières temporaire enregistrée.
10. Dispositif selon la revendication 9, caractérisé en ce que les moyens de stockage sont à même d'enregistrer la table des matières temporaire sous la forme d'un signal d'information d'adresse temporaire dans une zone du support d'enregistrement qui est située à l'extérieur de la zone destinée à l'enregistrement des signaux de données et du signal d'information d'adresse définitif.
11. Dispositif selon la revendication 9 ou 10, caractérisé en ce que les moyens de stockage sont à même d'enregistrer la table des matières temporaire sur le support d'enregistrement sous la forme d'un signal d'information d'adresse temporaire de telle manière que la relation entre le signal d'information d'adresse temporaire et les informations représentées par celui-ci s'écartent de la relation entre lesdits autres signaux enregistrés et les informations repré-



sentées par lesdits autres signaux.

12. Dispositif selon la revendication 11, caractérisé en ce que le dispositif comprend des moyens pour ajouter des premiers signaux de détection d'erreurs aux signaux de données et au signal d'information d'adresse définitif, et des moyens pour ajouter des deuxièmes signaux de détection d'erreurs au signal d'information d'adresse temporaire, la relation entre les deux signaux de détection d'erreurs et les signaux auxquels ces premiers signaux de détection d'erreurs ont été ajoutés s'écartant de la relation entre lesdits signaux de détection d'erreurs et les signaux auxquels lesdits deuxièmes signaux de détection d'erreurs ont été ajoutés. 5 10 15
13. Dispositif selon la revendication 9 ou 10, caractérisé en ce que les moyens de stockage sont à même d'enregistrer le signal d'information d'adresse définitif en conformité avec un standard CD pour des supports d'enregistrement à lecture seulement. 20
14. Dispositif selon la revendication 13, caractérisé en ce que les moyens de stockage sont à même d'enregistrer le signal d'information d'adresse temporaire avant le début de la piste initiale du support d'enregistrement tel que défini par le standard CD. 25
15. Dispositif selon la revendication 13 ou 14, caractérisé en ce que les moyens permettant de provoquer l'enregistrement du signal d'information d'adresse temporaire sont à même d'enregistrer une séquence d'un nombre prédéterminé de trames de sous-codes ultérieures pour des signaux d'information enregistrés, chaque groupe représentant les informations d'adresse pour le signal d'information enregistré correspondant, chaque trame de sous-code du groupe comprenant les mêmes informations d'adresse, les trames de sous-codes individuelles de chaque groupe comprenant un code de séquence indiquant le numéro de séquence de cette trame dans le groupe. 30 35 40
16. Dispositif selon la revendication 15, caractérisé par des moyens pour lire les codes de séquence des trames de sous-codes formant le signal d'information d'adresse temporaire avant d'amorcer l'enregistrement d'une extension du signal d'information d'adresse temporaire, et des moyens pour amorcer l'enregistrement de l'extension en réaction à la lecture du code de séquence indiquant la dernière trame du dernier groupe des trames de sous-codes du signal d'adresse temporaire déjà enregistré. 45 50

55

