

5

SPECIFICATION



166166

VISCOUS MATERIAL APPLICATION APPARATUS

TECHNICAL FIELD

10 The present invention relates to a viscous material application apparatus for applying a viscous material such as an adhesive, cream solder or a conductive paste to an application target such as a circuit board.

15 BACKGROUND ART

 The basic configuration of a conventional viscous material application apparatus is described with reference to the schematic illustrations of Fig.29A and Fig.29B. As shown in Fig.29A, this viscous material application
20 apparatus comprises a material supply section 1 for holding a viscous material 5 such as an adhesive or cream solder, and a pressure regulating section 22 for regulating and supplying compressed air to the material supply section 1, and the viscous material 5 is pressurized by the compressed
25 air, and discharged from a discharge port 4a of a discharge section 4.

 Furthermore as shown in Fig.29B, in some cases a valve 16 for starting and stopping the supply of compressed air may also be provided between the material supply section 1



G00002

5 and the discharge section 4. In this apparatus, in the case where a predetermined quantity of the viscous material 5 is required to be discharged, the viscous material 5 is pressurized from above by compressed air supplied from the pressure regulating section 22 and forced downward, and the 10 valve 16 is then opened and the viscous material 5 discharged from the discharge port 4a. Then, when application onto the circuit board has been completed, the valve 16 is closed.

However, in a viscous material application apparatus 15 of the conventional configuration described above, because the compressed air supplied from the pressure regulating section 22 is applied on top of the viscous material 5 contained in the material supply section 1, then depending on the characteristics of the viscous material 5, the 20 pressure of the compressed air may be affected by the viscosity resistance of the viscous material 5 and find it difficult to reach the vicinity of the distant discharge port 4a of the discharge section 4. Consequently, variations developed in the pressure transmission, and it 25 was difficult to obtain highly accurate discharge quantities and discharge pressures.

Furthermore as shown in Fig.30, the response time from the point where a signal is output to start discharge at a predetermined pressure, to the point where discharge at

5 that pressure is actually started, also lengthens for the same reasons, and so a waiting period develops from transmission of a discharge start signal to the actual start of discharge. In addition, after stopping pressurization residual pressure remains, and so other
10 problems arise such as the viscous material 5 hanging down from the discharge port 4a being forced out near the discharge port 4a and adhering to the circuit board, creating a bridge, when the viscous material application apparatus is next positioned on the circuit board.

15 Furthermore in the aforementioned conventional apparatus, in those cases where a device called a multiple nozzle 4c with a plurality of discharge ports 4d, such as that shown in Fig.31A and Fig.31B, was used for performing a two dimensional bulk supply of the viscous material, the
20 following problems also arose. In highly viscous materials, the pressure transmission through to the viscous material 5 does not occur uniformly, and when a conductive paste 31 was applied to a circuit board 32, then as shown in Fig.32A and Fig.32B, because the transmitted pressure
25 from the compressed air differed depending on the position of the discharge port 4d, a variation developed in the discharge quantity depending on the discharge position.

The present invention aims to resolve the above problems, with an object of providing a viscous material

5 application apparatus capable of improving discharge accuracy and increasing efficiency by carrying out the pressure transmission for discharging the viscous material efficiently, and improving the responsiveness.

10 DISCLOSURE OF THE INVENTION

In order to achieve the above object, a viscous material application apparatus of the present invention comprises: a main body having a pressurized chamber which connects through to a discharge port and stores a viscous
15 material; and a viscous material supply device for transferring the viscous material under pressure to the pressurized chamber, wherein a discharge pressure regulating device for regulating the discharge pressure of the viscous material by increasing or decreasing the
20 capacity of the pressurized chamber when the viscous material inside the pressurized chamber is pressurized and discharged is provided either inside the pressurized chamber or facing the pressurized chamber.

According to the present invention, because the
25 viscous material stored in the pressurized chamber is discharged with a discharge pressure regulated by the discharge pressure regulating device provided either inside the pressurized chamber or facing the pressurized chamber, the air pressure is transmitted efficiently and uniformly

5 to the viscous material, and so the responsiveness from the
start of pressurization to the start of discharge improves,
and a suitable discharge quantity of the viscous material
is discharged almost instantaneously. Then, following
completion of the discharge, because no residual pressure
10 remains within the pressurized chamber, the problem seen in
conventional apparatus, where the viscous material hangs
down from the discharge port and then adheres to the
application target during the next application, is
prevented. Because the effects of viscosity resistance are
15 minimal even with highly viscous materials, improved
discharge accuracy and increased efficiency are achieved
across all types of viscous material application, enabling
for example, a uniform discharge even in the case of screen
printing where a printing paste is applied along a straight
20 line.

The discharge pressure regulating device may suitably
comprise a pouch positioned inside the pressurized chamber
for increasing or decreasing internal capacity thereof
through the intake or exhausting of gas, and an air supply
25 section for regulating the pressure inside the pouch by
either supplying gas to, or discharging gas from the pouch,
and as the shape of the pouch transforms with the intake or
exhausting of gas from the air supply section and the
pressurized chamber, the capacity of the pressurized

5 chamber is increased or decreased, enabling the discharge
pressure to be easily adjusted. In this case, the closer
the air pouch is positioned to the discharge port inside
the pressurized chamber, the smaller the difference will be
between the air pressure used for discharge and the actual
10 discharge pressure, and the more the responsiveness is
improved.

The discharge pressure regulating device may also be
constructed from an actuator such as an air cylinder and a
voice coil motor, and a diaphragm which transforms under
15 the influence of the actuator and increases or decreases
the capacity inside the pressurized chamber.

Furthermore, it is desirable to employ a configuration
in which a pressurized chamber, a discharge pressure
regulating device and a discharge port are shared across a
20 plurality of linearly aligned viscous material supply
devices, with the discharge pressure of the viscous
material at discharge positions along the alignment
direction of the viscous material supply devices being
regulated in a single batch. According to this
25 configuration, in screen printing such as that described
above, the discharge of a highly viscous printing paste is
carried out uniformly and with a high degree of accuracy,
regardless of the discharge position.

5 Another suitable configuration uses a plurality of discharge pressure regulating devices, with the discharge pressure of the viscous material at a discharge position being regulated as desired, and this configuration enables localized pressure regulation to be performed with ease.

10 Furthermore, by attaching a pair of inclined plates which approach one another in a downward direction to both sides of the lower section of the pressurized chamber, and using the opening between the bottom edges of these plates as a discharge port, these inclined plates function as a
15 substitute for a squeegee in the aforementioned screen printing, and enable the filling of a screen opening with printing paste to be appropriately performed by discharge pressure regulation, and so highly accurate printing is possible, and an improvement in printing quality is
20 achieved.

 According to a configuration not restricted to supply by pressure transfer using the viscous material supply device used for transferring the viscous material under pressure in the aforementioned configuration, by forming
25 the main body to allow for easy exchange, and enabling a cartridge filled with a viscous material to be accommodated within the main body, the viscous material is stored in the pressurized chamber, the pressurizing device for supplying

5 the viscous material becomes unnecessary, and supply of the viscous material is simplified.

Furthermore in another suitable configuration, a soft elastic material is inserted between the aforementioned inclined plates and the lower side surfaces of the
10 pressurized chamber. In such a configuration, when the inclined plates are pressed onto the screen, the inclined plates flex causing an improvement in the adhesion with the screen. Accordingly, the problem of the viscous material seeping out between the inclined plates and the screen when
15 the viscous material is supplied into the pressurized chamber or when the viscous material inside the pressurized chamber is pressurized is prevented. However, in order to further improve the adhesion, the inclined plates need to be lengthened to increase their flexion. Such lengthening
20 causes the capacity of the pressurized chamber to increase and the amount of supplied viscous material to increase, which leads to an increase in the supply time and an increase in the weight of the application unit. By inserting a soft elastic material between the inclined
25 plates and the lower side surfaces of the pressurized chamber, the capacity of the pressurized chamber is kept small while still ensuring flexion of the inclined plates, and the volume of the viscous material is kept to a minimum. The soft elastic material could also be

5 constructed along the inclined plates, and may be connected
at the edges of the two plates, or alternatively separate
pieces of soft elastic material are also inserted at the
edges of the inclined plates. When large amounts of
viscous material are permissible, the soft elastic material
10 need not be formed along the inclined plates, and a soft
material could be inserted only at the tips of the inclined
plates.

In another suitable configuration, in the case where
following the filling of the pressurized chamber with a
15 viscous material using the aforementioned viscous material
supply device the supply pressure of the viscous material
supply device is cut, but even though the supply pressure
has been cut the viscous material within the pressurized
chamber still retains a degree of pressure, a pouch which
20 functions as a discharge pressure regulating device absorbs
this residual supply pressure remaining in the pressurized
chamber, causing a reduction in the pressure inside the
pressurized chamber. Accordingly, the residual pressure
within the pressurized chamber is removed, and the
25 discharge pressure is controlled using the aforementioned
pouch.

Furthermore, in another suitable configuration, by
providing a pressure detecting member at an internal edge
of the pressurized chamber or between the pressure chamber

5 and the viscous material supply device, then as the viscous material is supplied to the pressurized chamber by the viscous material supply device, the pressure detecting member detects when the pressurized chamber is full of the viscous material.

10 Furthermore in another suitable configuration, in those cases where during pressurization of the pressurized chamber by the discharge pressure regulating device, the detected pressure at pressure detecting member does not reach a predetermined pressure, a judgment is made that the
15 amount of viscous material is insufficient, and the viscous material supply device is used to supply the viscous material to replenish the viscous material within the pressurized chamber.

In another suitable configuration, the pressurized
20 chamber is moved while pressurized by the discharge pressure regulating device, and the pressure of the discharge pressure regulating device is regulated based on a pressure of the pressurized chamber detected with the pressure detecting member.

25 Furthermore in another suitable configuration, a rotatable shaft is provided in the pressurized chamber, and the viscous material is mobilized by rotating the shaft.

Furthermore in another suitable configuration, the viscous material is recovered into the pressurized chamber

5 by setting the pressure of the pressurized chamber to a negative pressure by the discharge pressure regulating device following completion of discharge, and lifting the pressurized chamber while moving the chamber in a horizontal direction.

10 Moreover in another suitable configuration, the temperature of the viscous material is stabilized by exchanging the air inside an air pouch.

BRIEF DESCRIPTION OF THE DRAWINGS

15 Fig.1 is a longitudinal cross-sectional view showing a viscous material application apparatus according to a first embodiment of the present invention;

Fig.2A and Fig.2B show experimental data according to the same embodiment, where Fig.2A is a graph showing the
20 responsiveness of the discharge pressure, and Fig.2B is a graph showing the efficiency of the discharge pressure through a comparison with a conventional apparatus;

Fig.3 is a longitudinal cross-sectional view showing a second embodiment of the present invention;

25 Fig.4 is a longitudinal cross-sectional view showing a third embodiment of the present invention;

Fig.5A and Fig.5B show a fourth embodiment of the present invention, where Fig.5A is a front view, and Fig.5B is a side view;

5 Fig.6A to Fig.6E are reference diagrams for the same embodiment, describing a process for applying a printing paste (viscous material) by screen printing in a sequence from Fig.6A to Fig.6E;

10 Fig.7A and Fig.7B show experimental data comparing variations in discharge pressure with a conventional example, where Fig.7A is a graph showing data according to the same embodiment, and Fig.7B is a graph showing data according to a conventional example;

15 Fig.8A and Fig.8B show experimental data comparing the responsiveness of the discharge pressure with a conventional example, where Fig.8A is a graph showing data according to the same embodiment, and Fig.8B is a graph showing data according to a conventional example;

20 Fig.9 is a longitudinal cross-sectional view showing a modified example of the same embodiment;

 Fig.10A and Fig.10B show a fifth embodiment of the present invention, where Fig.10A is a longitudinal cross-sectional view, and Fig.10B is a graph showing a discharge pressure distribution for the same embodiment;

25 Fig.11A and Fig.11B show a sixth embodiment of the present invention, where Fig.11A is a schematic perspective view showing the essential elements, and Fig.11B is a graph showing a discharge pressure distribution for the same embodiment;

5 Fig.12A and Fig.12B are diagrams showing the action of
the present invention using the fourth and the fifth
embodiments, where Fig.12A is a longitudinal cross-
sectional view showing the state immediately following the
completion of discharge of a viscous material, and Fig.12B
10 is a longitudinal cross-sectional view showing the state
where the discharge pressure has been regulated following
completion of discharge;

Fig.13 is a longitudinal cross-sectional view
describing the essential elements of a seventh embodiment
15 of the present invention;

Fig.14A and Fig.14B show an eighth embodiment of the
present invention, where Fig.14A is a longitudinal cross-
sectional view, and Fig.14B is a transverse cross-sectional
view;

20 Fig.15A is a perspective view showing an integrated
type soft elastic material, and Fig.15B is a perspective
view showing a divided type soft elastic material;

Fig.16A and Fig.16B are graphs showing the removal of
residual pressure from inside a pressurized chamber by an
25 air pouch;

Fig.17A, Fig.17B, Fig.17C and Fig.17D are cross-
sectional views showing various states of an air pouch;

Fig.18 is an explanatory diagram showing a slit for
removing air;

5 Fig.19 is an explanatory diagram showing pressure detecting member inside a pressurized chamber;

 Fig.20 is a graph showing the pressure inside a pressurized chamber when an initial supply and an additional supply are carried out;

10 Fig.21 is a graph showing the pressure inside a pressurized chamber during printing;

 Fig.22 is an explanatory diagram showing pressure detecting member inside a pressurized chamber;

 Fig.23A and Fig.23B are diagrams showing the flow of a
15 viscous material;

 Fig.24A and Fig.24B show an example in which a shaft is positioned inside a pressurized chamber, where Fig.24A is a longitudinal cross-sectional view, and Fig.24B is a left side view;

20 Fig.25 is a graph showing viscosity variation of a viscous material;

 Fig.26A and Fig.26B are diagrams showing flow velocity distributions for a viscous material;

 Fig.27A to Fig.27E are diagrams showing an operation
25 for recovering a viscous material from on top of a screen;

 Fig.28A to Fig.28C are diagrams describing a method of rapidly returning a viscous material to room temperature, where Fig.28A is a longitudinal cross-sectional view, and Fig.28B and Fig.28C are graphs;

5 Fig.29A and Fig.29B are schematic perspective views showing two types of conventional viscous material application apparatus;

 Fig.30 is a graph showing data for the responsiveness of the discharge pressure for the same conventional
10 example;

 Fig.31A and Fig.31B are schematic perspective views showing two types of multiple nozzles of other conventional examples;

 Fig.32A and Fig.32B are graphs showing data for the
15 discharge pressure from the multiple nozzles of the same conventional examples, corresponding with the measurement points of Fig.31A and Fig.31B respectively; and

 Fig.33 is a diagram of a modified embodiment of the present invention, showing an example where joints are
20 positioned at the left and right sides of an application unit.

BEST MODE FOR CARRYING OUT THE INVENTION

 As follows is a description of a viscous material
25 application apparatus according to an embodiment of the present invention, with reference to Fig.1 through Fig.28, and Fig.33.

 A viscous material application apparatus according to a first embodiment shown in Fig.1 comprises a material

5 supply section 1, an air supply section 2, and an application unit 3 which forms a main body of the apparatus. The material supply section 1 contains a viscous material 5 such as an adhesive and cream solder stored inside a cylinder shaped storage tank 1b, and under
10 the effect of compressed air used for material supply, a plunger 1a operates and pressurizes the viscous material 5, and transfers the viscous material under pressure so that the inside of a chamber (pressurized chamber) 3c of the application unit 3 is always full.

15 The application unit 3 and the material supply section 1 are connected by a joint 6, and by positioning a through aperture 6a provided in the joint 6 so that the through aperture 6a interconnects with a viscous material supply passage 3d provided horizontally in the side of the
20 aforementioned chamber 3c, the viscous material 5 is supplied to the inside of the application unit 3.

A discharge nozzle 4b extends from a discharge section 4 at the bottom of the application unit 3. In contrast, the air supply section 2 is positioned at the top of the
25 application unit 3, and compressed air from this air supply section 2, which has been adjusted to a predetermined pressure for use in material supply, is transferred into an air pouch 3b occupying the entire upper portion of the inside of the chamber 3c. In the first embodiment, this

5 air pouch 3b and the aforementioned air supply section 2 make up the discharge pressure regulating device. Although compressed air was used in this embodiment, an inert gas such as nitrogen gas could also be used as the gas phase.

The air pouch 3b is formed from a pouch shaped vessel
10 made of rubber or a resin material such as a urethane elastomer, polyethylene or nylon or the like, with a thickness of 0.03mm to 1mm for example. Furthermore, on consideration of the composition of the viscous material 5, the use of a solvent resistant material for the air pouch
15 is also desirable. Preferred thickness for the air pouch is in the range of 0.3mm to 0.5mm. If the thickness of the air pouch 3b is overly thin, then there is a danger of the pouch rupturing. In particular, the air pouch 3b needs to be pressurized when the viscous material 5 is supplied into
20 the chamber 3c, in order to absorb residual supply pressure remaining in the chamber 3c, and there is a possibility of the air pouch 3b rupturing at this time. Furthermore, if the thickness of the air pouch 3b is overly thick then there is a danger of deterioration in the responsiveness of
25 the expansion and contraction of the pouch.

Furthermore as the air pouch 3b expands or contracts accompanying the inflow of compressed air from the air supply section 2 or the outflow of compressed air to the air supply section 2, the capacity of the chamber 3c inside

5 the application unit 3 either decreases or increases.
Accordingly, the viscous material 5 inside the chamber 3c
is pushed out or sucked up under a predetermined pressure.
Furthermore, by shortening the distance from the air pouch
3b to the discharge port 4a to approximately 10mm for
10 example, the responsiveness is improved.

In other words, as shown in the graph of Fig.2A, there
is no waiting period from the point discharge is turned on
until actual pressurization occurs, and there is no
residual pressure at the completion of discharge.
15 Experiments revealed that the discharge pressure reached
the predetermined pressure transferred from the air supply
section 2 within 0.3 to 0.5 seconds. Furthermore in the
same manner, when the discharge is turned off, the pressure
inside the chamber 3c following completion of the
20 pressurization falls almost instantaneously to a value
close to zero, enabling the discharge to be stopped. In
addition, in the first embodiment, because the distance
between the air pouch 3b and the discharge port 4a at the
tip of the discharge nozzle 4b is small, the air pressure
25 of the compressed air supplied to the air pouch 3b from the
air supply section 2, and the discharge pressure of the
viscous material discharged from the discharge port 4a are
approximately equal, and this fact is confirmed by
comparative experiments conducted with a conventional

5 apparatus, as shown in the graph of Fig.2B. In this manner, in the first embodiment, the efficiency of pressure transmission is improved by a discharge pressure regulating function which utilizes the expansion and contraction action of the air pouch 3b associated with the supply and
10 exhaust actions of the air supply section 2, and the effects on the flow characteristics of the viscous material 5 stored in the chamber 3c are reduced. The exhaust action of the air supply section 2 is realized by either releasing the air inside the air pouch 3b into the atmosphere, or by
15 suctioning the air out.

According to a second embodiment shown in Fig.3, an air cylinder 7 which is connected to the air supply section 2 and a diaphragm 7b which is described below are used instead of the aforementioned discharge pressure regulating
20 air pouch 3b. A piston 7a is provided in the air cylinder 7, and compressed air from the air supply section 2 which has been adjusted to a predetermined air pressure is supplied from an air port 3a, and accordingly the piston 7a moves up and down causing a deformation of the diaphragm 7b
25 attached to the bottom end of the piston. This deformation of the diaphragm 7b causes an increase or a decrease in the capacity inside the chamber 3c, thereby applying pressure to, or releasing pressure from the viscous material 5. In

5 addition to the device shown in the Figure, the diaphragm
7b may also utilize a bellows or the like.

According to a third embodiment shown in Fig.4, an
electric motor 8 known as a voice coil motor (VCM) is used
for driving the aforementioned piston 7a to achieve
10 regulation of the discharge pressure. In the third
embodiment, the mechanism wherein the deformation of the
diaphragm 7b is used for increasing or decreasing the
capacity inside the chamber 3c is the same as that of the
second embodiment, although by using an electric drive,
15 even faster responses is realized. The operating distance
(the stroke) of the voice coil motor 8 is either controlled
by attaching a pressure sensor 19 to the chamber 3c or near
the tip of the piston 7a and then comparing the detected
value with a set value, or alternatively the resistance
20 value (the resistive force) generated during operation is
read from the driver of the voice coil motor 8 and
converted to a pressure, and this pressure value then used
for control. In either case, in order to ensure efficient,
immediate and precise transmission of the pressure, the
25 distance between the drive source and the diaphragm 7b of
the discharge pressure regulating device and the discharge
port 4a needs to be reduced as far as possible.

A fourth embodiment shown in Figs.5A and 5B is an
apparatus which regulates the discharge pressure using a

5 discharge pressure regulating device similar to the air
pouch shown in the first embodiment, although a feature of
this embodiment is that by providing a plurality of
material supply sections 1, and sharing a chamber 11a and a
tube shaped air pouch 11b, the discharge pressure within a
10 predetermined capacity is regulated in a single batch by
the single discharge pressure regulating device.

Specifically, as shown in Fig.6A-Fig.6E, in order to
mount an electrical component, in a printing apparatus such
as a planograph and mimeograph system (screen system) for
15 printing a viscous material (printing paste) 31 onto a land
pattern 33 of a circuit board 32, a squeegee 37 is used for
filling an opening 35 in a screen 34 positioned on the
circuit board 32 with the viscous material 31, but in the
present embodiment, instead of the squeegee 37, a thin
20 blade (inclined plate) 12 described below is used under the
operation of the aforementioned discharge pressure
regulating device. In other words, a viscous material
application apparatus according to the fourth embodiment is
used as the print head of a screen printing machine.

25 According to the fourth embodiment, in the printing
step where the viscous material 31 is used to fill the
opening 35 in the screen 34, by increasing or decreasing
the capacity of the chamber 11a by utilizing the gas intake
and exhausting actions associated with the air pouch 11b

5 positioned along the alignment direction of the material
supply sections 1 and the discharge pressure regulating
device (air supply section) 2 positioned in a single
location at one end of the apparatus, highly accurate
discharge pressure adjustments are performed for
10 maintaining the filling pressure of the viscous material 31
entering the opening 35 at a suitable value, enabling an
improvement in the printing quality. One example of this
viscous material application apparatus has a length of
270mm, and the viscous material 31 is stored in material
15 supply sections 1, with one positioned centrally and the
others positioned with a 85mm separation to the left and
the right, respectively. The viscous material 31 is
transferred under pressure from a through aperture 9a with
diameter of approximately 6mm inside a joint 9 connected to
20 the material supply section 1, into the chamber 11a inside
the application unit 11. The chamber 11a is provided with
an air port 11d for supplying compressed air from the air
supply section 2, a joint 11e, and the air pouch 11b.

A shaft 11g and a pipe 11f with air holes for the
25 intake or exhausting of air are mounted inside the air
pouch 11b. Because the length of the discharge port 14, at
270mm, is quite long, the shaft 11g is provided to enable
air to be transferred evenly and instantaneously into the
air pouch 11b, thereby preventing the air pouch 11b, which

5 is made of nylon tube of 0.05mm in thickness, from
deforming and protruding outside the chamber 11a. The
joint 11e is connected to the pipe 11f. The air pouch 11b
has a diameter of approximately 10mm and a length of
approximately 220mm, and is connected to the joint 11e
10 using an O-ring or the like to prevent air leaks.

Two thin blades 12 made of thin copper blades of 0.3mm
in thickness are attached at both sides at the bottom of
the chamber 11a, and are held in position by blade weights
10 so as to approach one another in a downward direction
15 leaving a spacing of approximately 10mm, and in screen
printing this arrangement replaces the conventional
squeegee. In the fourth embodiment, the opening between
the two thin blades 12, 12 forms the discharge port 14, and
the viscous material 31 is discharged through this
20 discharge port 14. Side plates 13 are fixed to the chamber
11a with side stoppers 15 of urethane rubber or the like
disposed therebetween, to prevent the viscous material 31
from leaking out of the chamber 11a.

For viscous material application apparatus formed with
25 three material supply sections 1 such as the apparatus
described above, data results from comparative experiments
comparing an apparatus utilizing discharge pressure
regulating devices (an air supply section 2 and an air
pouch 11b) similar to that of the fourth embodiment, and a

5 conventional apparatus in which the viscous material 5 is discharged using only the compressed air for supplying material from the material supply section 1 are shown in Figs.7A to 8A.

First, in terms of a comparison of the pressure
10 variation between the three measurement positions, at the central section and at the left and right sections along the length of the apparatus, then in the case where the air pressure was set to 0.2kgf/cm^2 , the variation in the fourth embodiment was approximately 0.01kgf/cm^2 , as shown in
15 Fig.7A, and can effectively be ignored. However, in the conventional apparatus the variation was approximately 0.1kgf/cm^2 , as shown in Fig.7B.

Next, is a comparison of the responsiveness of the discharge pressure, based on Fig.8A and Fig.8B. The
20 filling pressure rise time was approximately 0.3 seconds for the fourth embodiment, as shown in Fig.8A, whereas for the conventional apparatus the rise time was approximately 10 seconds. In a similar manner, following completion of the pressurization, whereas in the conventional apparatus a
25 residual pressure of approximately 0.3kgf/cm^2 remained in the chamber and moreover a period of approximately 30 seconds was required from stopping of the discharge until this residual pressure was reached, in the fourth embodiment the pressure inside the chamber 11a drops almost

5 instantaneously. The reason for this immediate drop in pressure is that following completion of the pressurization, the air pouch 11b contracts and exhausts air to the air supply section 2 thereby removing the residual pressure within the chamber 11a.

10 Furthermore as shown in Fig.9, a design wherein a plate 11h is fixed to the top face of the viscous material 31 being pressurized by the air pouch 11b inside the chamber of the fourth embodiment, so that the viscous material 31 inside the chamber 11a spreads out uniformly,
15 is also possible.

In a viscous material application apparatus according to the fourth embodiment described above, the viscous material 31 is pressurized inside the chamber 11a uniformly, and with a high degree of accuracy, and the
20 viscous material 31 discharged from the discharge port 14 is applied uniformly along the length of the discharge port 14. However in a fifth embodiment shown in Fig.10A, the discharge pressure is varied at each of the application positions.

25 According to the fifth embodiment, material supply sections 1 are provided in two locations as shown in Fig.10A, and air pouches 3f, 3e, 3g are provided in three locations in the central section and at the left and right sections, and are arranged with separate air ports 3a which

5 interconnect with air supply sections 2. If the discharged
viscous material has a high viscosity of approximately
200Pa·s, such as a printing paste, then by setting the air
pressure for the compressed air from the left hand and
right hand air supply sections 2 to 0.5kgf/cm² and setting
10 the value for the central section to 0.3kgf/cm², the
discharge pressure from the chamber 3c is subjected to
localized pressure regulation at the left section, the
right section and the central section, as shown in Fig.10B.
In order to improve the accuracy of the localized pressure
15 regulation even further, the chamber 3c could also be
partitioned in accordance with the air supply sections 2.

Furthermore, the plurality of air pouches 3e, 3f, 3g
need not necessarily be positioned in a straight line as in
the apparatus described above, and in a sixth embodiment
20 shown in Fig.11A, by arranging a plurality of air pouches
3b in parallel, the discharge pressure is varied within a
single application unit 3, and a desired pressure
distribution is created. Fig.11B is a graph showing that
pressure distribution.

25 Fig.12A and Fig.12B are diagrams showing the suction
action on the viscous material 31 when the discharge port
14 is moved away from the application target 32 following
discharge of the viscous material 31 from the viscous
material application apparatus and application of that

5 viscous material onto the application target 32, for the
apparatus of the embodiment 4 and the embodiment 5. In
this case, the viscous material 31 near the discharge port
14 is pulled apart between the application target 32 and
the discharge port 14, and a portion of the viscous
10 material 31b is applied to the application target 32, and
the remaining viscous material 31a is left hanging down
from the discharge port 14. However as shown in Fig.12B,
by suctioning air from the air pouch 11b via the pipe 11f
with air holes, the air pouch 11b contracts and the viscous
15 material 31a hanging down is returned to the inside of the
chamber 11a.

In other words, when the viscous material application
apparatus is repositioned on top of the application target
32, then if done so in the state shown in Fig.12A, the
20 viscous material 31 adheres to the area surrounding the
discharge port 14 (the surfaces of the opening to the
chamber 11a). However if, as shown in Fig.12B, the
dangling viscous material 31a is suctioned inside the
chamber 11a using air suction such as that described above,
25 then even if the discharge port 14 is repositioned on top
of the application target 32 for reprinting, the viscous
material 31 does not protrude out, and the surface of the
application target 32 is kept in a clean state. The
pressure required for performing this suction is supplied

5 by the air supply section 2, and the pressure for the suction action need only be sufficient to contract the air pouch 11b, with values of -0.2kgf/cm^2 to -0.3kgf/cm^2 being suitable.

Fig.13 shows a seventh embodiment. In the above
10 embodiments supply of the viscous material 5 to the chamber 3c formed inside the application unit 3 was carried out using compressed air, but the supply device is not restricted to this configuration. For example in the seventh embodiment, the application unit 3 is formed so as
15 to be detachable from the air pouch 3b, and supply of the viscous material 5 is carried out by exchanging this application unit 3 with a new application unit 3 filled with the viscous material 5. Supply of the viscous material 5 may also be carried out by exchanging a
20 cartridge 3h formed such as to be accommodated within the chamber 3c. In such a case, the internal space of the cartridge 3h forms the chamber (pressurized chamber) inside the application unit 3. The material of the cartridge 3h may be any material capable of being accommodated in the
25 chamber 3c such as nylon, a fluorine based system, a metal system, or a non-metal system.

An eighth embodiment shown in Fig.14A and Fig.14B is an apparatus in which the discharge pressure is regulated using a discharge pressure regulating device similar to the

5 air pouch 11b shown in the fourth embodiment, wherein a plurality of aligned material supply sections 1 share a chamber 11a and an air pouch 11b, the discharge pressure within a predetermined capacity is regulated in a single batch using the single discharge pressure regulating
10 device, and a soft elastic material 38 is inserted between the lower side surfaces of the chamber 11a and the thin blades (inclined plates) 12.

Even without the soft elastic material 38, when the viscous material 31 is supplied to the chamber 11a or when
15 the viscous material 31 inside the chamber 11a is pressurized, by pressing the application unit 11 down onto the screen and causing the thin blades 12 to flex, the adhesion to the screen can be improved, and any leakage of the viscous material 31 from between the thin blades 12 and
20 the screen can be prevented. However, in order to improve the adhesion even further, and enable any waviness or the like within the screen to be followed, the thin blades 12 need to be lengthened and the flexion of the thin blades 12 increased. However, such lengthening causes the capacity
25 of the chamber 11a to increase and the amount of supplied viscous material 31 to increase, which invites an increase in the supply time and an increase in the weight of the application unit 11.

5 By inserting the soft elastic material 38 between the
thin blades 12 and the lower side surfaces of the chamber
11a, the capacity of the chamber 11a is kept small while
still ensuring flexion of the thin blades 12, and the
volume of the viscous material 31 is kept to a minimum.

10 The soft elastic material 38 is constructed along the thin
blades 12, and may be connected at the edges of the two
thin blades 12 forming a single integrated unit, as shown
in numeral 38a of Fig.15A, or alternatively may be divided
into a pair of left and right soft elastic materials 38b

15 formed along the thin blades 12 and another pair of soft
elastic materials 38c formed at the two edges of the thin
blades 12, as shown in Fig.15B. In cases where large
amounts of the viscous material are permissible, the soft
elastic material 38 need not be formed along the thin

20 blades 12, and the soft material 38 is inserted only at the
two edges of the thin blades 12. Furthermore, the soft
elastic material 38 may be fixed to the chamber 11a, or may
also be simply inserted between the chamber 11a and the
thin blades 12 or a separate plate from the edges of the

25 thin blades 12. Furthermore, the flexion of the thin
blades 12 could also be ensured by reducing the thickness
of the thin blades 12 or by using a resin based material.

As described above, when a viscous material
application apparatus of this embodiment is used as a print

5 head in a screen printing machine, by allowing a large degree of flexion for the thin blades 12, any waviness or the like within the screen is followed, and the viscous material 31 is scraped with the thin blades 12 even if there is no circuit board beneath the screen.

10 Furthermore during printing, the application unit 11 is often configured to enable free movement up and down to enable the screen to be followed, although restricting the up and down movement of the application unit 11 in order to effectively utilize the flexion of the thin blades 12 is
15 preferable in that it enables the thin blades 12 to move up and down and the viscous material 31 to be scraped.

Moreover the soft elastic material 38, in addition to being soft, should preferably be solvent resistant, and suitable materials include a soft polyethylene or urethane
20 rubber for example, although if the material is to be exchanged periodically, then silicon rubber and more particularly foam based silicon rubber, which is a soft material, is also suitable. In addition, if a material with a high degree of hardness such as fluorine based
25 material is joined to, or coated onto the surface of the soft elastic material 38 facing the screen, then the slipperiness is improved and the life of the soft elastic material 38 is extended.

5 Next is a comparison of pressure levels within the
chamber 11a using Fig.16A and Fig.16B. When the supply
pressure to the material supply section 1 is cut following
the filling of the chamber 11a with the viscous material 31
from the material supply section 1, then as shown in
10 Fig.16A, the viscous material 31 inside the chamber 11a
retains a certain amount of pressure (hereafter referred to
as the residual pressure) even though the supply pressure
has been cut, and this residual pressure does not decrease
significantly even after several minutes have passed. The
15 discharge pressure is generated by the air pouch 11b, and
although the discharge pressure can be controlled by the
air pouch 11b in those cases where the residual pressure is
smaller than the discharge pressure, control of the
discharge pressure becomes difficult in those cases where
20 the residual pressure is larger than the discharge
pressure.

Accordingly, if the air pouch 11b is inflated when
supply pressure is applied to the material supply section
1, or during the supply process, and then when the supply
25 pressure is cut at the point the inside of the chamber 11a
becomes filled with the viscous material 31, if the air for
the air pouch 11b is also cut, the deflation of the air
pouch 11b enables the residual pressure within the chamber
11a to be absorbed, and as shown in Fig.16B, the residual

5 pressure inside the chamber 11a is reduced within a period of no more than 1 second. Consequently, the pressure within the chamber 11a disappears, and the discharge pressure is controlled by the air pouch 11b.

At this time, as shown in Fig.17A, the air pouch 11b
10 may be provided in a separate chamber 11m from the chamber 11a so as not to inhibit the movement of the viscous material 31 within the chamber 11a (in such a case, the pressurized chamber of the present invention includes both 11a and 11m), or alternatively similar effects are achieved
15 by providing the air pouch 11b in the upper portion of the chamber 11a. The air pouches 11b described up until this point have had a circular cross section (Fig.17A), although the same effects are obtained using an air pouch 39a which collects air in a sheet like shape such as that shown in
20 Fig.17B, or an air pouch 39b which collects air in a bag type arrangement such as that shown in Fig.17C. Applying these possibilities, the same effects are also obtained by forming the pressurized chamber (chamber) 11a in a pouch shape, and using an elastic material pouch (air pouch) 39c
25 so that the region the air enters becomes a chamber, as shown in Fig.17D. In this embodiment, the description outlined an apparatus in which the thin blades were made of copper with a thickness of 0.3mm, but copper, stainless steel or resin (polyimide or combination of polyamide and

5 polyimide or the like) plates with an approximate thickness of 0.1mm to 0.5mm may also be used.

Furthermore in the present embodiment, the left and right joints 9 between the material supply sections 1 and the application unit 11 were positioned in the upper
10 portion of the application unit 11 as shown in Fig.5, but these joints may also be positioned on the left and right side surfaces of the application unit 11, as shown in Fig.33, with the viscous material 31 from the material supply sections 1 being supplied from the side surface of
15 the chamber 11a. So doing enables the supply of the viscous material 31 to the chamber 11a to be carried out smoothly.

Next, as shown in Fig. 18, when the viscous material 31 is supplied into the chamber 11a, there are occasions
20 when an air pocket 40a remains in the chamber 11a even when the chamber 11a is full. Because the inside of the chamber 11a is subjected to a uniform pressure by the air pouch 11b, the same pressure will be applied to the air pocket 40a, and no significant problems arise accordingly, but if
25 an air vent 40 such as a minute hole or a slit is provided to allow even more accurate pressure control, then the air within the air pocket 40a is vented. At this time, because the hole or slit is minute, the resistance to the viscous

5 material 31 seeping out is very high, and so the viscous material 31 will not seep out through the air vent 40.

Next is a description of the detection of when a chamber 11a is filled with the viscous material 31. When a supply pressure is applied to the material supply section 1
10 and the viscous material 31 is supplied to the chamber 11a, the supply pressure may be applied for a predetermined length of time, although by providing at least one pressure detecting member 41 either on an inside edge of the chamber 11a or between the chamber 11a and the material supply
15 section 1, the state where the chamber 11a is filled with the viscous material 31 is detected using the pressure detecting member 41.

As follows is a description of a method of supplying the viscous material 31 during printing, based on Fig.20.
20 The method for the initial supply of the viscous material 31 into the chamber 11a is the same as that described above, and when the inside of the chamber 11a is full, the air pouches 11b, 39a, 39b, 39c (hereafter recorded as simply 11b) are inflated and printing is started. As the
25 printing occurs, the amount of the viscous material 31 gradually decreases, but as long as the air pouch 11b is inflated, a predetermined pressure is generated inside the chamber 11a and printing is continued.

5 When the air pouch 11b becomes fully inflated and no longer fills the capacity generated by the reduced viscous material 31, the pressure inside the chamber 11a falls, and reaches a preset lower limit pressure necessary for printing. By detecting the lower limit pressure inside the
10 chamber 11a with the pressure detecting member 41, the reduction in the amount of the viscous material 31 is detected, and by then carrying out the same operations as those used during the initial supply to re-supply the inside of the chamber 11a with the viscous material 31, the
15 air pouch 11b can once again be inflated, enabling a discharge pressure to be generated and the printing to be continued.

 At this time, if residual pressure within the chamber 11a is not a problem then only the material supply section
20 1 need be operated, but in cases where residual pressure is a problem, it may be necessary to remove the residual pressure using the air pouch 11b.

 Furthermore, in those cases where the supply timing of the viscous material 31 is known beforehand, then the
25 viscous material 31 may be supplied in accordance with a set timing such as the number of printings, without detecting the lower limit pressure, and in cases where the viscosity of the viscous material 31 is low, a normal low

5 supply pressure may be applied, and the viscous material 31 supplied a little at a time.

Next, the pressure inside the chamber 11a during printing is described with reference to Fig.21. By inflating the air pouch 11b, the pressure inside the chamber 11a is raised instantaneously, and printing is then carried out by moving the application unit 11. During this time, because the movement of the application unit 11 causes the viscous material 31 to move inside the chamber 11a, the pressure detected by the pressure detecting member 41 will be lower than that detected when the application unit 11 is stopped.

If the screen opening is such that this difference in pressure does not cause any problems, then the air pouch 11b can be left inflated at a predetermined pressure, but if problems arise, then the pressure during actual printing should also be detected, and the difference in the pressure inside the chamber 11a between the case when the application unit 11 is stopped and the case when it is moving is used in considering the movement state of the viscous material 31. Particularly in the case where the pressure difference inside the chamber 11a is large, often this indicates the viscous material 31 is easily moved, in other words the case where the viscosity has fallen, and so

5 the pressure of the air pouch 11b needs to be reset in accordance with the degree of this fall in pressure.

This resetting of the pressure is a way of correcting the relationship with the viscosity of the viscous material 31, and so if the relationship between the viscosity, the
10 detected pressure and the set pressure has already been determined in advance, then this resetting can be performed automatically even during printing. Furthermore even if the viscosity of the viscous material 31 varies with a variation in temperature or with extended usage or the
15 like, by resetting the pressure of the air pouch 11b by conducting a comparison with the pressure measured during the previous printing, stable printing is achieved.

Furthermore by applying pressure to the air pouch 11b prior to the start of printing, and moving the application
20 unit 11 at a position with no screen opening, then the pressure of the air pouch 11b is reset even without actually conducting any printing.

Furthermore, by providing a plurality of pressure detecting members 41 around the perimeter of the inside of
25 the chamber 11a, as shown in Fig.22, the pressure state of the viscous material 31 is detected with greater accuracy, and detection of movement of the viscous material 31 inside the chamber 11a also becomes possible. If the pressure difference between the pressure detecting members 41 is

5 large, then the movement of the viscous material 31 is poor, in other words the viscosity is high, and so the pressure of the air pouch 11b (39a) is set to a large value, whereas if the pressure difference between the pressure detecting members 41 is small, then the movement
10 of the viscous material 31 is good, in other words the viscosity is low, and so the pressure of the air pouch 11b is set to a small value.

Next is a description of a method of promoting the flow of the viscous material, based on Fig.23A and Fig.23B.
15 If the viscous material 31 which fills the inside of the chamber 11a is moved across the top of a screen 34 with a discharge pressure applied, as shown in Fig.23A, then a circulating flow develops in the same direction as the direction of movement. In the case where a discharge
20 pressure is not applied, this flow does not occur, and because the viscous material 31 slides over the screen 34 it is unlikely to enter the opening in the screen 34 and so printing cannot be conducted. In other words, the flow of the viscous material 31 enables the viscous material 31 to
25 enter the opening in the screen 34, thereby enabling printing to be carried out.

As shown in Fig.23B, this phenomenon is the same as the case where a squeegee 37 is used for printing, and when

5 the squeegee 37 is moved the viscous material 31 undergoes a circulating flow in the same direction.

Furthermore, in the case of this squeegee system, in order to promote the mobility of the viscous material 31, the viscous material 31 is stirred frequently inside the
10 vessel, before being supplied to the squeegee 37.

In cases such as the present invention where the viscous material 31 is inside a chamber 11a, the viscous material 31 is unable to be stirred prior to supplying, but considering that the viscous material 31 inside the chamber
15 11a flows during the printing operation, it is clear that the viscous material 31 is stirred prior to the commencement of printing by moving the application unit 11 back and forth across the top of the screen 34 with a discharge pressure applied, and performing this type of
20 operation prior to printing is a suitable technique for stabilizing the printing.

In addition, in those cases where there is a need to stir the viscous material 31, then as shown in Fig.24A and Fig.24B, a shaft 42 is provided inside the chamber 11a so
25 that the viscous material 31 is stirred by rotating this shaft. The shaft 42 sits inside the chamber 11a and is supported at both ends, and O-rings 43 prevent the viscous material 31 from leaking out. A pulley 44 is fixed to at least one end of the shaft 42, and the pulley 44 is

5 connected to a motor 46 via a belt 45. In other words, by rotating the motor 46, the shaft 42 rotates and the viscous material 31 is forcibly stirred.

As shown in Fig.25, if the viscous material 31 is viewed in terms of viscosity, then during each printing
10 operation the viscous material 31 is flowing and so the viscosity decreases, albeit gradually. By moving the application unit (print head) 11 back and forth, the viscosity of the viscous material 31 is lowered by a certain amount in advance, although by using the shaft 42,
15 the viscosity is lowered even further and the degree of viscosity variation in the viscous material 31 during subsequent printing is reduced. Needless to say, rotating the shaft 42 while moving the print head 11 back and forth is even more effective.

20 As follows is a description of the flow velocity of the viscous material 31 inside the chamber 11a, based on Fig.26A and Fig.26B. The flow velocity of the viscous material 31 during printing, as shown by the arrows of Fig.26A, is largest at the location of the discharge port
25 14 and decreases with movement up and away from the discharge port. In cases where the viscosity of the viscous material 31 is high, because the material is less inclined to flow, the flow velocity is smaller, and accordingly the flow velocity at the location of the

5 discharge port 14 falls and no longer matches the velocity
of the print head 11, which causes slipping between the
screen 34 and the viscous material 31, making printing
difficult. Furthermore, in cases where the printing speed
is high, the flow velocity at the location of the discharge
10 port 14 attempts to speed up, but the viscosity of the
viscous material 31 inside the chamber 11a acts as
resistance and prevents the flow velocity at the discharge
port 14 from increasing, and accordingly slipping develops
between the screen 34 and the viscous material 31, and
15 printing becomes difficult.

As shown in Fig.26B, by also rotating the shaft 42
provided inside the chamber 11a during printing, the flow
of the viscous material 31 inside the chamber 11a is
promoted, and so in those cases where the viscosity of the
20 viscous material 31 is high or in cases where the printing
speed is high, the flow velocity at the location of the
discharge port 14 is increased, and accordingly printing is
carried out without slipping occurring between the screen
34 and the viscous material 31.

25 Of course the shaft 42 may also be freed and allowed
to rotate in accordance with the flow of the viscous
material 31, and furthermore a strain gauge or the like
could also be attached to the end axis of the shaft 42 to

5 enable the viscosity to be measured, but forcibly rotating the shaft 42 is more effective.

Next is a description of a method of retracting the print head (application unit) 11 from a screen 34 without leaving any viscous material 31 on the surface of the
10 screen, with reference to Fig.27A-Fig.27E. As shown in Fig.27A, there is the viscous material 31 inside a chamber 11a of the print head 11, and the viscous material 31 contacts the screen 34 at the discharge port 14. As shown in Fig.27B, if the print head 11 is simply lifted in this
15 state, then a large amount of the viscous material 31 is left on the screen 34. Furthermore, as shown in Fig.27C, even if the print head 11 is lifted after deflating the air pouch 11b, using the same technique used to prevent the viscous material 31 hanging down from the discharge port
20 14, then some viscous material 31 is still left on the screen 34. Reusing this remaining viscous material 31 requires considerable effort, and so all of the viscous material 31 on the screen 34 must be recovered by the print head 11.

25 According to the present invention, by deflating the air pouch 11b inside the chamber 11a the capacity of the space available for storing the viscous material is increased, and by moving the viscous material 31 inside the chamber 11a away from the screen 34, recovery of the

5 viscous material 31 is carried out with ease. By moving
the viscous material 31 inside the chamber 11a in this
manner (moving the viscous material away from the screen
34), the present invention enables the recovery of the
viscous material 31 to be carried out with ease. In this
10 embodiment, the viscous material 31 was moved by deflating
the air pouch 11b, as described below, but the method for
increasing the capacity of the space available for storing
the viscous material inside the chamber 11a is not
restricted to this method.

15 In this embodiment, as shown in Fig.27C, the air pouch
11b is deflated to increase the capacity of the space
available for storing the viscous material inside the
chamber 11a, and so as shown in Fig.27D, by moving the
print head 11 horizontally and scraping up the viscous
20 material 31 on the screen 34 with the thin blades 12, and
then lifting the print head 11 up while the horizontal
movement is continued as shown in Fig.27E, the print head
11 is separated from the screen 34 without leaving any
viscous material 31 on the surface of the screen 34.

25 As follows is a description of a method of rapidly
returning the application unit 11 to room temperature,
based on Fig.28A to Fig.28C. When production is halted
during use, a lid or the like is usually placed on the
application unit 11 and the viscous material 31 is stored

5 in a refrigerator or the like. When production is
restarted, the temperature of the viscous material 31 needs
to be returned to room temperature, and as shown in
Fig.28B, this normally requires the viscous material 31 to
be removed from the refrigerator at least 30 minutes prior
10 to the start of production. If exchange of the viscous
material 31 occurs frequently, then considerable time and
effort is expended on returning the viscous material 31 to
room temperature.

In the present invention, by replacing the air inside
15 the air pouch 11b as shown in Fig.28A, the temperature of
the viscous material 31 is rapidly returned to room
temperature as shown in Fig.28C, and so production is
started earlier and excessive amounts of time and effort
are eliminated.

20

INDUSTRIAL APPLICABILITY

As described above, according to the present
invention, discharge pressure regulating device positioned
near the discharge port enables efficient pressure
25 transmission to occur when a viscous material stored inside
a pressurized chamber is discharged, and enables an
instantaneous discharge to be carried out at an appropriate
and uniform discharge pressure with good efficiency and a
high degree of accuracy, and moreover by utilizing the

5 invention in screen printing, the increase in precision of
the filling pressure at an opening of the screen enables
leakage or bridge generation by the viscous material to be
prevented, and so the invention is useful in improving the
printing quality.

10

CLAIMS

1. A viscous material application apparatus comprising:

5 a main body (3) having a pressurized chamber (3c) for storing a viscous material (5), the pressurized chamber connecting through to a discharge port (4a);

a viscous material supply device (1) for transferring said viscous material (5) under pressure to
10 said pressurized chamber (3c); and

a discharge pressure regulating device (2, 3b) for regulating a discharge pressure of said viscous material (5) by increasing and decreasing a capacity of said pressurized chamber (3c) when said viscous material (5)
15 inside said pressurized chamber (3c) is pressurized and discharged,

wherein the discharge pressure regulating device includes a pouch (3b) which is positioned inside the pressurized chamber (3c) and which increases and
20 decreases in internal capacity through intake and exhausting of gas, and an air supply section (2) for regulating pressure inside said pouch (3b) by either one of supplying gas to, and discharging gas from said pouch (3b).

25

2. A viscous material application apparatus comprising:

a main body (3) having a pressurized chamber (3c) for storing a viscous material (5), the pressurized
30 chamber connecting through to a discharge port (4a);

a viscous material supply device (1) for transferring said viscous material (5) under pressure to said pressurized chamber (3c); and

a discharge pressure regulating device (7, 8, 7b) for regulating a discharge pressure of said viscous material (5) by increasing and decreasing a capacity of said pressurized chamber (3c) when said viscous material (5) inside said pressurized chamber (3c) is pressurized and discharged,

wherein the discharge pressure regulating device includes an actuator such as an air cylinder (7) and a voice coil motor (8), and a diaphragm (7b) which transforms under influence of said actuator and increases and decreases capacity inside said pressurized chamber (3c).

3. A viscous material application apparatus comprising:

a main body having a single pressurized chamber (11a) for storing a viscous material (31), the pressurized chamber connecting through to a single discharge port (14);

a plurality of viscous material supply devices (1) for transferring said viscous material (31) under pressure to said pressurized chamber (11a); and

a single discharge pressure regulating device (2, 11b) for regulating a discharge pressure of said viscous material (31) by increasing and decreasing a capacity of said pressurized chamber (11a) when said viscous material (31) inside said pressurized chamber (11a) is pressurized and discharged, the discharge pressure regulating device being provided either inside said pressurized chamber (11a) or facing said pressurized chamber (11a),

wherein the pressurized chamber (11a), the discharge pressure regulating device (2, 11b) and the discharge port (14) are shared across the plurality of linearly

aligned viscous material supply devices (1), and a discharge pressure of said viscous material (31) at discharge positions along an alignment direction of said viscous material supply devices (1) is regulated in a single batch.

4. A viscous material application apparatus comprising:

a main body (3) having a pressurized chamber (3c) for storing a viscous material (5), the pressurized chamber connecting through to a discharge port (4a);

a viscous material supply device (1) for transferring said viscous material (5) under pressure to said pressurized chamber (3c); and

a plurality of discharge pressure regulating devices (2, 3e, 3f, 3g) for regulating a discharge pressure of said viscous material (5) at a discharge position by increasing and decreasing a capacity of said pressurized chamber (3c) when said viscous material (5) inside said pressurized chamber (3c) is pressurized and discharged, the discharge pressure regulating devices being provided either inside said pressurized chamber (3c) or facing said pressurized chamber (3c).

5. The viscous material application apparatus according to claim 4, wherein a pair of inclined plates (12, 12) are attached to both sides of a lower section of said pressurized chamber (11a) so as to approach one another in a downward direction, and an opening between bottom edges of said plates (12, 12) is used as a discharge port (14).

6. The viscous material application apparatus

according to claim 6, wherein a soft elastic material (38) is inserted between each of said inclined plates (12, 12) and a lower side surface of said pressurized chamber (11a).

5

7. The viscous material application apparatus according to claim 2, wherein following filling of said pressurized chamber (3c) with said viscous material (5) using said viscous material supply device (1), residual
10 supply pressure remaining inside said pressurized chamber (3c) is absorbed by said pouch (3b).

8. The viscous material application apparatus according to claim 4, wherein a pressure detecting member
15 (41) is provided at either one of an inside edge of said pressurized chamber (11a) and a position between the pressurized chamber and said viscous material supply device (1), and said pressure detecting member (41) detects when said pressurized chamber (11a) is filled
20 with said viscous material (31).

9. The viscous material application apparatus according to claim 10, wherein when said pressurized chamber (11a) is pressurized by said discharge pressure
25 regulating device (2, 11b), in cases where a detected pressure at said pressure detecting member (41) does not reach a predetermined pressure, an amount of viscous material (31) is judged to be insufficient, and said viscous material (31) is supplied by said viscous
30 material supply device (1).

10. The viscous material application apparatus according to claim 10, wherein said pressurized chamber

(11a) is moved while pressurized by said discharge pressure regulating device (2, 11b), and a pressure of said discharge pressure regulating device (2, 11b) is regulated based on a pressure of said pressurized chamber (11a) detected with said pressure detecting member (41).

11. The viscous material application apparatus according to claim 4, wherein a rotatable shaft (42) is provided in said pressurized chamber (11a), and said viscous material (31) is mobilized by rotating said shaft (42).

12. The viscous material application apparatus according to claim 4, wherein said viscous material (31) is recovered into said pressurized chamber (11a) by setting a pressure of said pressurized chamber (11a) to a negative pressure by said discharge pressure regulating device (2, 11b), and lifting said pressurized chamber (11a) while moving said chamber (11a) horizontally.

13. The viscous material application apparatus according to claim 2, wherein a temperature of said viscous material (31) is stabilized by exchanging gas inside said pouch (11b).

14. A screen printing machine comprising the viscous material application apparatus according to claim 6 as a print head (11).

15. A viscous material application method wherein a single pressurized chamber (11a), discharge pressure regulating device (2, 11b) and discharge port (14) are shared across a plurality of linearly aligned viscous

material supply devices (1), a discharge pressure of a viscous material (31) is regulated in a single batch by increasing and decreasing a capacity of said pressurized chamber (11a) when said viscous material (31) inside said pressurized chamber (11a) is pressurized and discharged, and said viscous material (31) is moved inside said chamber (11a) and recovered into said chamber (11a).

16. A viscous material application method wherein a single pressurized chamber (11a), discharge pressure regulating device (2, 11b) and discharge port (14) are shared across a plurality of linearly aligned viscous material supply devices (1), a discharge pressure of a viscous material (31) is regulated in a single batch by increasing and decreasing a capacity of said pressurized chamber (11a) when said viscous material (31) inside said pressurized chamber (11a) is pressurized and discharged, and said viscous material (31) is recovered into said pressurized chamber (11a) by setting a pressure of said pressurized chamber (11a) to a negative pressure by said discharge pressure regulating device (2, 11b), and lifting said pressurized chamber (11a).

17. A viscous material application method wherein a single pressurized chamber (11a), discharge pressure regulating device (2, 11b) and discharge port (14) are shared across a plurality of linearly aligned viscous material supply devices (1), a discharge pressure of a viscous material (31) is regulated in a single batch by increasing and decreasing a capacity of said pressurized chamber (11a) when said viscous material (31) inside said pressurized chamber (11a) is pressurized and discharged, and said viscous material (31) is recovered into said

pressurized chamber (11a) by setting a pressure of said
pressurized chamber (11a) to a negative pressure by said
discharge pressure regulating device (2, 11b), and
lifting said pressurized chamber (11a) while moving said
5 chamber (11a) horizontally.