CLAIMS

[Claim 1]

An aerobic biofilm treatment method comprising supplying raw water to an aeration tank, aerating the aeration tank using an aeration device, and subjecting a substance to be removed in the raw water to an aerobic biological treatment using a biofilm retaining carrier ~~or granule-packed~~ in the aeration tank, wherein

a relationship between an oxygen consumption rate per carrier ~~or granule~~, and a corresponding DO target value and/or a corresponding aeration intensity set value is set in advance,

the DO target value and/or the aeration intensity set value is adjusted based on the relationship according to a fluctuation of a measured value of the oxygen consumption rate per carrier ~~or granule~~, and

the aeration device is controlled such that the DO becomes the target value or the aeration intensity becomes the set value~~.~~, and

wherein the oxygen consumption rate per carrier is any of an oxygen consumption rate per packing volume of the carrier, and an oxygen consumption rate per total surface area of a carrier group.

[Claim 2]

The aerobic biofilm treatment method according to claim 1, wherein the oxygen consumption rate per carrier ~~or granule is any of an oxygen consumption rate per packing volume of the carrier, an oxygen consumption rate per total surface area of a carrier group, an oxygen consumption rate per packing volume of the granule, and an oxygen consumption rate per total surface area of a granule group.~~

~~[Claim 3]~~

~~The aerobic biofilm treatment method according to claim 1 or 2, wherein~~

~~the oxygen consumption rate per carrier or granule~~ is calculated from

a measured value of an aeration air volume,

a measured value of a concentration of oxygen in a gas phase released from the aeration tank, or a measured value of the DO of the aeration tank and an experimental value or a calculated value of an oxygen dissolution efficiency of the aeration tank, and

a measured value or a calculated value of a packing volume or a surface area of the carrier.

[Claim ~~4~~3]

The aerobic biofilm treatment method according to ~~any one of claims~~claim 1 ~~to 3~~or 2, wherein the aeration intensity is controlled by controlling an aeration air volume, an aeration stop time, or an aeration suppression time.

[Claim ~~5~~4]

The aerobic biofilm treatment method according to any one of claims 1 to 4~~3~~, wherein the relationship is set using any of an experimental result, an operation result of an actual machine, and a mechanism model considering diffusivity of oxygen in the biofilm.

[Claim ~~6~~5]

An aerobic biofilm treatment device comprising an aeration tank to which raw water is supplied, an aeration device that aerates the aeration tank, a biofilm-attached carrier ~~or granule packed~~ in the aeration tank, and a controller that controls the aeration device,

wherein the device further comprises:

a setting unit that sets in advance a relationship between an

oxygen consumption rate per carrier ~~or granule~~, and a corresponding DO target value and/or a corresponding aeration intensity set value; and

an adjusting unit that adjusts the DO target value and/or the aeration intensity set value based on the relationship according to a fluctuation of a measured value of the oxygen consumption rate per carrier ~~or granule~~, and

wherein the controller controls the aeration device such that the DO becomes the target value or the aeration intensity becomes the set value~~.~~, and

wherein the oxygen consumption rate per carrier is any of an oxygen consumption rate per packing volume of the carrier, and an oxygen consumption rate per total surface area of a carrier group.