

Electro-hydraulic device for moving a jib

The invention relates to an electro-hydraulic device
for moving a jib and to a tower crane having a luffing
5 jib with a device of this type.

In tower cranes having a luffing jib, the movement of
the jib in the vertical direction can take place via a
hydraulic cylinder which is retracted or extended in
10 order to achieve the desired spacing between the crane
axis and the rope axis. Here, a hydraulic assembly,
comprising an oil pump, provides the oil quantity which
is required for force transmission at the required
pressure.

15

When the jib has reached the desired angle, that is to
say further retraction or extension is first of all no
longer required, changing oil quantity or changing oil
pressure is not required any more at the hydraulic
20 cylinder. After the movement has stopped, the hydraulic
assembly continues to deliver only as much oil as is
required to maintain the pressure. In this operating
state, the electric motor which drives the hydraulic
assembly is running virtually at idling speed.

25

In a tower crane with a hydraulically movable luffing jib, the motor which drives the hydraulic assembly is usually a three-phase asynchronous motor.

5 However, a three-phase asynchronous motor which is running at idling speed has a very poor performance factor and degree of efficiency. During the idling phase, the three-phase asynchronous motor continues to consume energy. A large part of said energy
10 consumption, approximately about 60%, is unnecessary; the energy is consumed merely in order to deliver the oil in an empty manner in the circuit, but not for the work of the hydraulic cylinder. A reduction in the energy consumption is desirable for cost and
15 environmental reasons.

In addition, the noise caused by the hydraulic assembly at idling speed is only negligibly lower than in the normal operating state.

20

It was therefore an object to provide an electro-hydraulic device for moving a jib for a tower crane, in which electro-hydraulic device the energy consumption for the jib movement and the development of noise are
25 reduced.

This object is achieved by way of an electro-hydraulic device for moving a jib as claimed in claim 1.

Furthermore, the object is achieved by way of a luffing
5 jib tower crane as claimed in claim 4.

Further embodiments are the subject matter of the subclaims or are described in the following text.

10 The electro-hydraulic device according to the invention for moving a jib brings about time-delayed switching off of the motor if no changing oil pressure is required at the hydraulic cylinder for a predefined time period (= delay time). If, in contrast, only a
15 very short interruption of the movement sequence takes place, for example when a load is being positioned, the motor is usually not switched off.

Switching on the motor again and running it up always
20 likewise require a certain time, with the result that consideration has to be taken of whether the interruption is long enough to give preference to the saving of energy over the delay in movement which is disruptive for the crane driver. The delay time is set
25 in a corresponding manner.

It is particularly advantageous if the time which switching on again and running up of the motor takes is kept low by way of an optimized electric or electronic starting circuit. The delay time can then be selected
5 to be all the shorter; the energy saving is also improved in this way. In particular, the motor can also start by way of an electronic soft starting unit.

The delay time can preferably be set as desired in the
10 case of an electro-hydraulic jib movement according to the invention.

If the position of the jib is to be changed again, the motor is switched on again upon actuation of the
15 operating elements for the jib.

The working time of a crane per year can be estimated at 260 days times 10 hours which equals 2600 hours. The interval times of a luffing gear should be on average
20 approximately 60%, that is to say 1560 hours. If it is assumed, for example, that the idling losses are 1.1 kW in the case of a nominal power of 22 kW, the energy saving in this example is 1700 kWh per year.

25 The system can be provided in such a way that restarting of the motor is brought about not only by

way of an initiated change in the jib angle, but rather also by way of any other desired crane movements, for example of the lifting gear or the slewing gear.

Patent Claims

1. An electro-hydraulic device for moving a jib for a tower crane, characterized in that the motor of the hydraulic assembly is switched off if the position of the jib is not changed for a predefined time period.
2. The electro-hydraulic device for moving a jib as claimed in claim 1, characterized in that the motor is switched on again if the operating elements for changing the vertical position of the jib, the lifting gear or the slewing gear are actuated.
3. The electro-hydraulic device for moving a jib as claimed in claim 1 or 2, characterized in that the motor is a three-phase asynchronous motor.
4. A luffing jib tower crane, comprising an electro-hydraulic device for moving a jib as claimed in one of the preceding claims.