

PUNCH UNIT

Field of the Invention

5 The invention relates to a punch unit, comprising a punch driver connected with a punch which punch driver has a base at its back end, safeguarding members, which keep the punch and the punch driver free of relative rotation during the stroke of the punch, and a pre-loaded compression spring which, during the
10 stroke of the punch, can be compressed between the base and a guide bushing receiving the punch so that it cannot be rotated, but is axially displaceable.

Background of the Invention

15 A punch unit of this type is known from U.S. Patent No. 5,131,303. In this structure the back end of the punch, which is provided with an exterior thread, is screwed into a threaded bore at the front end of the punch driver. The threaded section
20 at the back end of the punch is provided with four axial, longitudinal grooves, and an open spring washer, whose one end is radially bent inward and projects through a radial hole into one of the axial grooves of the punch, is seated on the exterior circumference of the front end of the punch driver. In the
25 assembled state the guide bushing is frictionally connected via an O-ring with a washer seated on the punch driver underneath the compression spring and prevents the spring washer from being able to yield radially outward. In this way the punch and the punch driver are directly connected with each other by the spring
30 washer without being able to rotate.

 When the punch is to be reground, the punch driver can be pulled away from the guide bushing toward the rear, in the course of which the frictional connection at the O-ring is released. After the spring washer has left the guide bushing, the threaded
35 connection between the punch and the punch driver can be released by relative rotation. Because the radially inward bent end of the open spring washer has a point and the lateral walls of the grooves are inclined, the free end of the spring washer is pushed out of the groove in which it had been engaged when the punch is

rotated in relation to the punch driver and, with continued relative rotation, then engages the next groove. Knowing the thread pitch, it is also known which change in the total length of the punch and punch driver corresponds to the rotational angle between two grooves. Because of this it is possible in a very simple way to reset the total length of the punch and punch driver following the regrinding of the punch. As soon as the guide bushing has subsequently again been pushed over the open spring washer and has been frictionally connected with the punch driver via the O-ring, the screw connection between the punch and the punch driver is again dependably blocked against relative rotation because the guide bushing does not permit the open spring washer to widen radially, so that therefore its radially inwardly bent end no longer can leave the radial groove with which it is in engagement at that time.

Although the known punch unit assures a simple setting of the total length of the punch and punch driver, it suffers from the essential disadvantage that the grooves intended for safeguarding against relative rotation weaken the thread through which the large punching forces are transmitted to the punch. This is of particular disadvantage in connection with punches having a relatively small cross section, as finer adjustment is required with decreasing cross section, because it is then necessary to have correspondingly more grooves at the circumference. Furthermore, the assembly and the installation or removal of the punch, for example for regrinding, are comparatively difficult and involved because the compression spring is seated under pre-load on the punch driver, which makes itself felt in a disruptive way during every manipulation.

Summary of the Invention

It is therefore the primary object of the invention to provide a punch unit of the initially mentioned type with a limited return stroke of the punch, which permits a simpler and more rapid installation and removal of the punch.

The above object is attained in accordance with the invention in that the pressure spring is held in a pre-loaded manner in the guide bushing, which is embodied in one or several pieces, and the punch driver in the position where it is inserted into the guide bushing is kept by a releasable catch supported on the guide bushing from a movement toward the back.

The proposed punch unit has the advantage that even in the completely assembled state there is only one unit comprised of the punch and the punch driver which, after releasing the catch, can be easily pushed out of the guide bushing toward the back or upward and pulled out without a need for a tool. In a corresponding manner it is sufficient at the end of the assembly operation and following regrinding, as well as during a replacement of the punch, to let the punch together with the punch driver slide into the guide bushing from behind or above.

To be able to compensate for the loss of length because of the regrinding of the punch, there is customarily a threaded connection between the punch and the punch driver which permits the adjustment of the length. In this case it is also necessary to see to it that the punch and the punch driver are connected with each other during operation in such a way that they cannot rotate in relation to each other. The punch unit in accordance with the invention permits the embodiment of the safeguard elements in the way described in U.S. Patent No. 5,131,303. However, a simpler design is preferred, wherein the safeguard elements are constituted by a connection between the punch driver and the guide bushing which is interlocking in the circumferential direction. Since in the process the punch, on the one hand, and the punch driver, on the other, are guided in the guide bushing so they cannot rotate, they are also maintained secure against relative rotation in respect to each other.

The interlocking connection between the punch driver and the guide bushing is preferably provided on the back end of the latter, i.e. back of the back spring bearing. In a particularly simple embodiment, the base of the punch driver is embodied with a plurality of axial grooves distributed over the circumference,

which is engaged by at least one radially inward pointing protrusion of the guide bushing.

The novel punch unit can be realized in the form that the threaded connection, by means of which the length compensation is performed following grinding, is located at the back end of the punch and the front end of the punch driver. However, alternatively the shaft of the punch driver can also be embodied as one piece with the punch. In this case a threaded connection between the back end of the shaft and the base of the punch driver is provided.

With the novel punch unit, the front part of the guide bushing performs the function of guiding the punch, while the back part receives the pre-loaded spring and maintains the punch driver secure against relative rotation. Because of the different functions, it is recommended to manufacture the front and back parts of the guide bushing in the form of two separate parts and to connect them, secure against relative rotation, preferably by means of an axial plug connection. In the process the front spring bearing is suitably formed by a shoulder at the guide bushing and the back spring bearing by a ring insert, which can be screwed into the back end of the guide bushing or can be fastened in another way, by means of which the pre-load of the compression spring can be set. Simultaneously the ring insert, which can be fixed in place in the desired rotational angle position in the guide bushing, can have the mentioned radial protrusion, which engages an axial groove in the base of the punch driver and in this way prevents its rotation. To change the length of the unit comprised of the punch and the punch driver, it is sufficient to release the catch and to push the base of the punch driver out of the ring insert or the guide bushing toward the back and to turn it by one or several groove pitches. The selected length setting is preserved after the punch driver base has again been inserted into the back end of the guide bushing.

The invention will be explained in detail below by means of an exemplary embodiment illustrated in the drawings.

Brief Description of the Drawings

There follows a detailed description of the preferred embodiments of the present invention which are to be taken together with the accompanying drawings, wherein:

Fig. 1 is a lateral view, partially in section, of a punch unit in the completely assembled state;

Fig. 2 is a view corresponding to Fig. 1 in a position of the parts wherein they are sufficiently pulled apart axially so that a respective relative rotation of the upper part in respect to the lower part is possible; and

Fig. 3 is a partial section of the upper area of a variant embodiment of the punch unit on an enlarged scale and in a sectional plane turned by 135° in relation to Figs. 1 and 2.

Detailed Description of the Preferred Embodiments

Referring now to the figures, like elements are represented by like numerals throughout the several views.

The punch unit represented in Figs. 1 and 2 consists in a known manner of a punch 10 guided linearly displaceable in a guide bushing 12. A rotation of the punch 10 in relation to the guide bushing 12 is prevented by a pin 14, fixedly seated in a radial bore in the punch 10, which protrudes radially and engages an interior longitudinal groove 16 in the guide bushing 12. This axial groove 16 is also radially outwardly open over a portion of its length, so that a pin, not shown, or other securing member can engage the groove 16 from the outside and can maintain the guide groove 12 non-rotatingly on the machine frame, not shown. In this respect, as well as in relation to the disposition of a stripper ring 20 fastened on the lower end of the guide bushing 12 by a safety washer 18, the disclosed punch unit corresponds to conventional designs.

In further agreement with known punching tools, the back or upper end of the punch 10 is screwed together with a punch driver 22. In the exemplary embodiment represented, the back end of the punch 10 is provided with a threaded bore for this

purpose, into which the front end 24, which is provided with an exterior thread, of the shaft of the punch driver 22 is screwed. The total length of the punch 10 and the punch driver 22 is set by screwing the front end 24 of the punch driver 22 into the threaded bore of the punch 10 more or less deeply. The base seated at the back end of the punch driver 22 is identified by 26.

An unusual feature of the disclosed punch unit resides in that the guide bushing 12 is extended at the back by a slip-on bushing 28. It has a tapered shoulder at the front end which fits into a widened end section of the bore of the guide bushing 12, in which an O-ring 30 is seated which alternatively can also be placed on the exterior circumference of the tapered section of the slip-on bushing 28. In the area of the tapered front section the interior diameter of the slip-on bushing 28 is also greater than the exterior diameter of the punch 10, so that during the stroke of the punch the latter is freely axially displaceable and can be inserted from above or the back into the guide bushing 12 through the slip-on bushing 28. Otherwise the punch 10 can also be guided through the tapered front section of the slip-on bushing 28.

To connect the slip-on bushing 28 secure against relative rotation with the guide bushing 12, the latter is provided with one or a plurality of axial bores 32 at its back end, which are engaged by a pin 34 seated in the axial stepped surface of the tapered section of the slip-on bushing 28. Thus, in the assembled state the two bushings 12 and 28 are connected frictionally engaged via the O-ring 30 and secure against relative rotation to form a sealed unit, in other words a guide bushing put together from a front and a back part 12 and 28, which could also be manufactured as one piece.

In the embodiment of Figs. 1 and 2, the slip-on bushing 28 is provided with an interior thread at the rear end, into which a set collar 36 is screwed as a ring insert. It constitutes a back stop surface, or a back spring bearing, for a compression spring 38 received in the slip-on bushing 28, which is supported at the front by a front stop surface, i.e., the

shoulder formed by the taper. The desired pre-load of the compression spring 38 can be set by screwing the set collar 36 more or less deeply into the interior thread of the slip-on bushing 28. The selected setting is then fixed in place by means of a securing screw 40, for example, which is screwed in from the inside into a radial threaded bore of the set collar 36 until it engages the interior thread of the slip-on bushing 28. The securing screw 40 can be a set screw whose back end projects radially inward from the set collar 36. Alternatively it is possible to embody one or a plurality of radial protrusions at the radial interior circumference of the set collar 36, for example in one piece construction, or in the form of pressed-in pins. In the assembled state as shown in Fig. 1, the set screw 40 or a corresponding other radial protrusion engages one of four axial longitudinal grooves 42, which are evenly distributed over the circumference of the exterior circumferential surface of the base 26, so that in this way the punch driver 22 is held fixed against relative rotation in respect to the bushings 28 and 12 and therefore also in respect to the punch 10. Since the longitudinal grooves 42 in the base 26 are continuous, i.e. open at both their axial ends, the punch 10 and the punch driver 22 can be easily assembled axially from the back, perform punching strokes in the assembled state shown in Fig. 1 and lifted out again toward the back or the top. It is only necessary to assure that in the course of their connection the radial protrusion 40 is aligned with one of the longitudinal grooves 42.

To improve the contact of the upper end of the compression spring 38, an intermediate ring 44 has been inserted between it and the set collar 36, by means of which the spring is supported on the set collar 36. The interior diameter of the intermediate ring 44 has been selected to be such that the punch 10 and the shaft of the punch driver 22 can be guided through it. However, the base 26 has a larger exterior diameter, so that in the assembled state shown in Fig. 1 it rests on the back or upper front face of the intermediate ring 44. In the course of the stroke of the punch, the intermediate ring 44 therefore follows

the axial movement of the base 26 against whose underside it is pressed by the compression spring 38.

The punch unit illustrated has the particular advantage that changes in the total length of the punch 10 and the punch driver 22 can be made very rapidly and simply. Starting with the position shown in Fig. 1, it is only necessary to lift the unit comprised of the punch 10 and the punch driver 22 in relation to the guide bushing 12 sufficiently far so that the radial protrusion 40 can move downward out of the groove which receives it and which is open at the ends. This retracted position of the punch driver 22 is illustrated in Fig. 2. If in this position or in a position which is even further lifted or retracted the punch driver 22 is turned in one or the other direction, while the punch 10, together with the guide bushing 12, is held, fixed against relative rotation, by the engagement of the pin 14 with the groove 16, the engagement length with which the front end 24 of the punch driver 22 which is provided with the exterior thread enters the threaded bore in the back end of the punch 10 is changed. Since the pitch of this thread is known, it is also known by what amount the total length of the punch 10 and the punch driver 22 is changed when the latter is rotated by the amount of the pitch angle between two grooves 42. It is understood that with an increase of the number of the grooves 42 distributed over the circumference the adjustment accuracy is increased. In the course of this, for example, there is also the option to embody the grooves 42 in the form of a toothing and the interior circumference of the set collar 36 in the form of a matching interior toothing.

To make the setting of the total length of the punch 10 and the punch driver 22 easier, it is possible to apply visible markers to the existing grooves 42 at the exterior circumference of the slip-on bushing 28.

After setting the desired total length, it is only required to lower the punch driver 22 back into the operational position shown in Fig. 1 in which the radial protrusion 40 is again in engagement with one of the grooves 42.

Differing from the embodiment represented, the shaft of the punch driver 22 can be made in one piece with the punch 10. In this case the base 26 is screwed on the back of this unit, and the total length of the punch 10 and the punch driver 22, 26 is
5 adjusted in that the base 26 is screwed down to a greater or lesser extent and can then be fixed in place in the desired position, for example by means of a securing screw to be screwed into a radial threaded bore. Simultaneously this securing screw can radially project away outward from the base 26, analogously
10 to the set screw 40, and can be brought into engagement with one or a plurality of longitudinal grooves distributed over the circumference of the set collar 36, unless the disposition represented in the drawings is preferred.

Based on the above description and the drawings it must
15 be stated that the securing members which safeguard the rotational angle position of the punch driver 22 or at least of its base 26 in respect to the punch 10 are of a simple nature in regard to their structure and manufacturing techniques. A change of the total length of the punch 10 and the punch driver 22 can
20 be performed more rapidly and simpler than before. As shown in a comparison between Figs. 1 and 2, following the change in length it can be readily seen whether the punch driver is again correctly seated in the push-on bushing 28. If the radial protrusion 40 has not been brought into correct engagement with
25 one of the grooves 42 in the base 26, the latter extends radially toward the back out of the slip-on bushing 28.

Finally, there is the further advantage over the initially mentioned prior art, that the longitudinal grooves 42 required for a safeguard against relative rotation do not weaken the
30 thread required for adjusting the length through which the pushing force is transmitted during punching. Since the longitudinal grooves 42 are located on the exterior circumference of the base 26 it is possible to cut several longitudinal grooves 42 without difficulty, even if the punch 10 only has a
35 comparatively small circular or otherwise shaped cross section.

It is understood that further variants and designs of the above described details are possible, particularly regarding the

connection between the slip-on bushing 28 and the guide bushing 12 and the shape of the slip-on bushing 28 as well as its connection with the set collar 36. Because the punch 10 can be easily pulled out toward the back from the two bushings 12, 28, which are connected with each other, the bushings 12, 28 can also be connected with each other by means of, for example, a threaded connection which can be fixed in place, a bayonet connection or in another suitable manner, wherein the setting of the pre-load of the compression spring 38 can also be provided there, as in the case of a threaded connection. In addition, this as well as the embodiment illustrated in Figs. 1 and 2 offers the option to perform a finer adjustment of the total length of the punch 10 and the punch driver 22, even with only a few longitudinal grooves 42 provided on the circumference, by either rotating the slip-on bushing 28 as a whole or the set collar 36 in respect to the guide bushing 12 and then fixing the threaded connection in place again. The small change in the pre-load of the compression spring 38 taking place in this case is normally of no importance.

When in the embodiment represented in Figs. 1 and 2 no limitation of the reverse stroke of the unit consisting of the punch 10 and the punch driver 22, 26 is provided, the latter with its base can jump toward the rear out of the guide bushing 12, 28 to a larger or smaller extent because of the strong and rapid action of the spring 38. This undesirably long reverse stroke can be braked by a brake ring, for example an O-ring, inserted into the set collar 36, for example. However, this also includes the disadvantage that the base 26 of the punch driver can no longer be easily removed through the back of the guide bushing 12, 28. In order to be able, on the one hand, to pull the unit consisting of the punch and the punch driver very easily and simply either partially or completely out of the guide bushing 12, 28 toward the rear but, on the other hand, to effectively prevent the undesirable jumping out of the punch driver base 28 during operation of the punch device, a catch 46, illustrated in Fig. 3, is pivotably seated at the rear end of the guide bushing, 12, 28, preferably at the ring insert 36. It has the form of a

two-armed lever. A pin 48, used as a pivot shaft, has been inserted in the position illustrated horizontally and tangentially to the ring insert, which in Fig. 3 is identified by 36'. In this way the catch 46 is radially pivotable to a limited extent in a slit in the ring insert 36', which essentially extends axially and radially and is not completely cut through. A spring wire 50, pressing against the catch 46 radially from the outside in the front or lower area, has the tendency to continuously pivot the catch 46 into the locking position shown in Fig. 3, wherein the catch 46 blocks a rearward movement of the punch driver base 26 out of the guide bushing 12, 28 toward the back or the top. In this position, the catch 46 engages an axially extending groove 52 in the circumferential surface of the punch driver base 26 which, in contrast to the continuous grooves 42 open at both ends, is closed at the front or lower end by an end wall forming a shoulder 54. In the exemplary embodiment, four grooves 52 evenly distributed over the circumference of the punch driver base 26 are provided, which are respectively located in the middle between two continuous grooves 42, and the catch 46 is arranged on the circumference, offset by 135° in relation to the radial protrusion 40.

Since in the locking position normally set by the spring wire 50 in accordance with Fig. 3 the catch 46 has a slight, resiliently maintained oblique position, in which its front or lower end points radially inward, it can escape radially outward from the front edge of the punch driver base 26 in the course of the insertion of the unit consisting of the punch 10 and the punch driver 22, 26. However, as soon as the end wall of the groove 52 forming the shoulder 54 has passed the catch 46 and the punch driver base is supported on the intermediate ring 44, the front or lower end of the catch 46 snaps with an audible click into the groove 52 behind the shoulder 54 and in this way blocks the rearward movement of the punch driver 22 and the punch 10.

To unlock the punch driver, an actuating button 56 seated in a fitting bore in the rear end of the guide bushing 12, 28 is manually depressed and in turn pushes radially from the exterior against the upper end of the catch 46 and because of this pivots

it in a clockwise position and against the force of the spring 50 into a released or unlocked position, in which it no longer engages the groove 52, so that the punch driver 22, 26 and the punch 10 can be pulled out of the guide bushing 12, 28 toward the back or top.

The actuation button 56 at its radially inner end has a head of an increased diameter, so that the actuating button 56 cannot fall toward the outside out of the hole receiving it.

In the course of assembly, the ring insert 36' is inserted axially from above or the rear into the guide bushing 12, 28. At the place at the circumference where the actuating button 50 is located, the ring insert 36' has an axial groove 58 in its exterior circumferential surface, which is axially open at the front, but closed at the rear end. The groove 58 is sufficiently wide and deep to receive the head of the actuating button 56. The actuating button 56 is therefore captively maintained following the assembly of the ring insert 36'. Since it rests against the upper end of the catch 46 with its widened head, it is normally held in its radially outward position by the spring 50.

As can be furthermore seen from Fig. 3, an annular groove has been cut into the interior circumferential surface of the guide bushing 12, 28 at a defined distance from the rear end, and at approximately the same distance from the rear end the ring insert 36' is also provided with an annular groove in its exterior circumferential surface. In the assembled state the two annular grooves are located directly opposite each other and delimit an annular hollow space 60, into which a flexible wire 62, whose diameter is larger than the depth, measured in the radial direction, of each of the two oppositely located annular grooves, can be inserted from the outside via an approximately tangential bore, not shown, through the wall of the guide bushing 12, 28. Following insertion of the wire 62 the ring insert 36' is axially fixed in place.

Although the invention has been described in considerable detail with respect to preferred embodiments thereof, variations and modifications will be apparent to those skilled in the art

without departing from the spirit and scope of the invention as set forth in the claims.

Claims

What is claimed is:

1. A punch unit comprising:

a punch driver having front and back ends,

a base positioned on said back end;

a punch having a back end connected to said front end of said punch driver;

a guide bushing receiving said punch and said punch driver and for guiding axial displacement of said punch, means for preventing rotation of said punch relative to said guide bushing during a stroke of said punch, said guide bushing including a front stop surface and a rear stop surface, the rear stop surface being closer to the base than the front stop surface;

a compression spring maintained under pre-load between said stop surfaces, the base positioned to compress the compression spring against the front stop surface during its forward movement; and

safeguarding members for preventing relative rotation of said punch and said punch driver during a stroke of said punch.

2. The punch unit according to claim 1 further comprising front and back spring bearings disposed on said guide bushing, said compression spring being clamped between said spring bearings.

3. The punch unit according to claim 2 wherein said guide bushing comprises a front part for guiding said punch attached to a back part in which said compression spring is seated under pre-load, said front part and back part including securing means for preventing relative rotation.

4. The punch unit according to claim 3 wherein said front and back parts of said guide bushing are attached by means of a sliding connection.

5. The punch unit according to claim 4 wherein said sliding connection is formed by insertion of a front section of said back part of said guide bushing into a back section of said front part of said guide bushing, and said securing means comprises at least



one axial bore in said back section which engages a pin seated in said front section.

5 6. The punch unit according to claim 3 wherein said front spring bearing comprises a shoulder on said guide bushing and said back spring bearing comprises a set collar connected with an inner circumferential wall of said back part of said guide bushing.

10 7. The punch unit according to claim 6 wherein said set collar is connected to said inner circumferential wall of said back part of said guide bushing by means of a threaded connection, whereby distance between said spring bearings is adjustable.

15 8. The punch unit according to claim 2 wherein said safeguarding members comprise interlocking contacts which interlock in a circumferential direction between said punch driver and said guide bushing.

20 9. The punch unit according to claim 8 wherein said interlocking contacts are positioned in a radial direction between said base of said punch driver and said back spring bearing.

10. The punch unit according to claim 9 wherein said interlocking contacts comprise at least one axial groove on a circumference of said base and a radial protrusion on said back spring bearing for engaging said axial groove.

25 11. The punch unit according to claim 2 further comprising an intermediate ring inserted between said compression spring and said back spring bearing, said intermediate ring having an exterior diameter which exceeds an interior diameter of said back spring bearing and having an interior diameter which is smaller than an exterior diameter of said base of said punch driver, said intermediate ring being axially displaceably guided in said back part of said guide bushing.

30 12. The punch unit according to claim 2 wherein said punch is approximately equal in length to a portion of said guide bushing located between said front spring bearing and said second end of said guide bushing.



13. The punch unit according to claim 1 wherein said punch and said punch driver are attached by means of a threaded connection.

5 14. The punch unit according to claim 1 wherein said punch driver and said punch comprise a single piece attached to said base by means of a threaded connection which is axially adjustable.

10 15. The punch unit according to claim 1 wherein said means for preventing rotation comprises a radially protruding pin seated in a radial bore in said punch which engages an interior longitudinal groove in said guide bushing.

16. A punch unit comprising;

a punch driver having front and back ends,

a base positioned on said back end;

15 a punch having a back end connected to said front end of said punch driver;

a guide bushing receiving said punch and said punch driver and for guiding axial displacement of said punch, means for preventing rotation of said punch relative to said guide bushing during a stroke of said punch, said guide bushing including front and rear stop surfaces;

a compression spring pre-loaded between said stop surfaces; and

25 means for connecting and disconnecting the base to the guide bushing, rearward of said rear stop surface, to respectively operatively interconnect the punch driver to the punch or operatively release the punch driver from the punch for axial adjustment of the punch relative to the punch driver.

30 17. A punch unit according to claim 16 wherein said means for connecting and disconnecting comprises a radial protrusion in said guide bushing, said protrusion being engageable with at least one axial longitudinal groove in said base.

35 18. A punch unit according to claim 17 wherein said base includes at least four longitudinal grooves which are evenly distributed over an exterior circumference of the base.

19. A punch unit comprising;

a punch driver having front and back ends,



a base positioned on said back end;

a punch having a back end connected to said front end of said punch driver;

a guide bushing receiving said punch and said punch driver and for guiding axial displacement of said punch, means for preventing rotation of said punch relative to said guide bushing during a stroke of said punch, said guide bushing including a front stop surface and a rear stop surface, the rear stop surface being closer to the base than the front stop surface;

a compression spring maintained under pre-load between said stop surfaces, the base positioned to compress the compression spring against the front stop surface during its forward movement; and

a releasable catch supported on said guide bushing for preventing movement of said punch driver out of said guide bushing.

20. The punch unit according to claim 19 wherein said releasable catch is supported on said back spring bearing.

21. The punch unit according to claim 20 wherein said base includes an outer shoulder and said releasable catch comprises a two-armed lever having forward and rearward ends and seated in such a manner as to be pivotable to a limited extent, said forward end of said lever being movable radially inward by a spring into a locking position in which said lever cooperates with said outer shoulder to form a stop and movable radially outward into a released position by pressure means for providing a radially inwardly directed pressure on a rearward end of said lever.

22. The punch unit according to claim 21 wherein said lever is pivotable about a pin positioned horizontally and tangentially to said back spring bearing.

23. The punch unit according to claim 21 wherein said base includes at least one axial groove formed in a circumference thereof, said axial groove being closed by an end wall at an end furthest from an open end of said guide bushing, said end wall forming said outer shoulder.



24. The punch unit according to claim 21 wherein said spring comprises a leaf spring or a spring wire for pre-loading said lever in a direction of said locking position.

25. The punch unit according to claim 21 wherein said pressure means comprises an actuating button seated in a radial bore near an open end of said guide bushing for engaging a recess in an exterior circumferential surface of said back spring bearing.

26. The punch unit according to claim 25 wherein said actuating button includes a head having a larger diameter than said radial bore.

27. The punch unit according to claim 21 further comprising a spring wire insertable through a radially outwardly open hole in a back part of said guide bushing into oppositely located annular grooves in an interior circumferential surface and in an exterior circumferential surface of said back spring bearing for axially fixing said back spring bearing in place in said guide bore.

28. A punch unit comprising:
a punch driver having front and back ends,
a base positioned on said back end;
a punch having a back end connected to said front end of said punch driver;
a guide bushing receiving said punch and said punch driver and for guiding axial displacement of said punch, means for preventing rotation of said punch relative to said guide bushing during a stroke of said punch, said guide bushing including a front stop surface and a rear stop surface, the rear stop surface being closer to the base than the front stop surface;

a compression spring maintained under pre-load between said stop surfaces, the base positioned to compress the compression spring against the front stop surface during its forward movement; and
connecting means interconnecting the guide bushing, rearward of the rear stop surface and the base.

29. A punch unit according to claim 28 wherein said connecting means includes a releasable catch for selectively



securing the punch driver in or allowing the punch driver to move rearward out of the guide bushing.

5 30. A punch unit according to claim 28 wherein said connecting means comprises safeguarding members for either preventing relative rotation of the punch and punch driver, for normal operation, or allowing relative rotation of the punch and punch driver to allow axial adjustment of the punch relative to the punch driver.

10 31. A punch unit according to claim 28 wherein said connecting means includes a releasable catch for selectively securing the punch driver in or allowing the punch driver to move rearward out of the guide bushing and safeguarding members for either preventing relative rotation of the punch and punch driver, for normal operation, or allowing relative rotation of
15 the punch and punch driver to allow axial adjustment of the punch relative to the punch driver.




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B26F 1/14	A1	(11) International Publication Number: WO 96/05030 (43) International Publication Date: 22 February 1996 (22.02.96)
(21) International Application Number: PCT/US95/09330 (22) International Filing Date: 26 July 1995 (26.07.95) (30) Priority Data: P 44 28 286.9 10 August 1994 (10.08.94) DE 195 08 091.2 8 March 1995 (08.03.95) DE (71) Applicant: MATE PUNCH AND DIE CO. [US/US]; P.O. Box 728, 6400 Industry Avenue, N.W., Anoka, MN 55303 (US). (72) Inventors: SCHNEIDER, Albrecht; Im Heidegraben 10, D-61440 Oberursel (DE). JOHNSON, Gary, E.; 15147 Ramsey Boulevard, Ramsey, MN 55303 (US). SIMON, Gerd; Michaelstrasse 46, D-06116 Chemnitz (DE). (74) Agent: PETRY, Marvin; Larson and Taylor, 727 23rd Street, South, Arlington, VA 22202 (US).	(81) Designated States: AT, AU, BR, CH, CN, CZ, DK, ES, FI, JP, KR, MX, NZ, SE, SG, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report.	

(54) Title: PUNCH UNIT

(57) Abstract

The punch unit comprises a punch driver (22) connected with a punch (10) which on its back end has a base. Furthermore, safeguarding members which keep the punch and the punch driver free of relative rotation during the stroke of the punch, and a pre-loaded compression spring (38) which during the stroke of the punch can be compressed between the base and a guide bushing (28) receiving the punch so that it cannot be rotated, but is axially displaceable, are part of it. To obtain a simpler and quicker assembly and disassembly of the punch it is provided that the pressure spring is maintained under pre-load in the guide bushing which is embodied as one or several pieces. A catch (46) releasably supported on the rear end of the guide bushing and releasably engaging a recess, open toward the back, in the circumferential surface of the punch driver head prevents the punch driver head from jumping toward the back out of the guide bushing.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

9608588-1

1/2

Fig. 1




Fig. 2

