9802068-8
IPOS's copy

PCT WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : H04N 1/00 — A1

(11) International Publication Number: **WO 97/50243**

(43) International Publication Date: 31 December 1997 (31.12.97)

(21) International Application Number: PCT/JP97/02148

(22) International Filing Date: 23 June 1997 (23.06.97)

(30) Priority Data:

8/164487	25 June 1996 (25.06.96)	JP
8/260022	30 September 1996 (30.09.96)	JP
8/260023	30 September 1996 (30.09.96)	JP
8/280229	30 September 1996 (30.09.96)	JP

(81) Designated States: AU, CA, CN, KR, NO, PL, SG, US, European patent (AT, BE, CH, DE, ES, FI, FR, GB, IT, NL, SE).

Published
With international search report.

(71) Applicant *(for all designated States except US)*: CASIO COMPUTER CO., LTD. [JP/JP]; 6-1, Nishi-Shinjuku 2-chome, Shinjuku-ku, Tokyo 163-02 (JP).

(72) Inventors; and
(75) Inventors/Applicants *(for US only)*: SASAKI, Koh [JP/JP]; 3-1-168, Somechi, Chofu-shi, Tokyo 182 (JP). ISHIKAWA, Tomohisa [JP/JP]; 23-9, Higashi-Tamachi, Kawagoe-shi, Saitama 350 (JP).

(74) Agent: KOMIZO, Satoshi; Kanda-Sakata Building, 6th floor, 2-5-1, Kandanishiki-cho, Chiyoda-ku, Tokyo 101 (JP).

(54) Title: PRINTING APPARATUS AND PRINTING SYSTEM

(57) Abstract

When an "ON" key (22) of a printer (20) is operated in the state wherein a digital camera (10) and the printer (20) can communicate with each other, menu data and a menu display command signal are transferred to the digital camera (10), and a print menu is displayed on a liquid crystal display section (13). When a "SET" key (24) is operated, an image readout command signal is transferred to the digital camera (10), and stored image data representing a recorded image is displayed on the liquid crystal display section (13). When a "+" key (23a) or a "-" key (23b) is depressed under the condition wherein the image is being displayed on the liquid crystal display section (13), an image switching command signal is transferred to the digital camera (10), and the image which is being displayed is switched to another recorded image. When a "PRINT" key (27) is operated under the condition wherein the desired image is being displayed on the liquid crystal display section (13), a print command signal is sent from the printer (20) to the digital camera (10), and image data corresponding to the image which is being displayed on the liquid crystal display section (13) is transferred to the digital camera (10) or the printer (20). The printer (20) prints the image corresponding to the transferred image data, in accordance with a print mode determined.

