

LIQUID EJECTING HEAD AND
LIQUID EJECTING APPARATUS USABLE THEREWITH

5 FIELD OF THE INVENTION AND RELATED ART:

The present invention relates to a liquid
ejecting head for ejecting liquid such as ink and a
liquid ejecting apparatus using the same. The liquid
ejecting apparatus is applicable to an ordinary
10 printer which effects recording by ejecting ink, a
copying machine, a facsimile having a communication
system, a multi-function recording device having such
functions in combination, or the like, and in addition
to an apparatus for drawing a figure or a pattern by
15 ejecting liquid other than ink.

It has been proposed that ink jet recording
head which is a typical one of liquid ejecting heads
is provided on an ink jet recording substrate with a
ROM (Read Only Memory) to store data such as
20 individual information for the particular head such as
its ID (Identity) code, a driving particularly
property of its ink ejecting mechanism. For example,
Japanese Laid-open Patent Application Hei 3 - 126560
discloses an ink jet recording head having an EEPROM
25 (Electrically Erasable Programmable ROM).

It is known that heat generating resistors for
generating energy for ink ejection is constituted in a

plurality of lamination film layers on a base portion of an ink jet recording substrate of the ink jet recording head, and a resistance indicative of information peculiar to the head (or individual
5 information) is formed. This is useful when the amount of the information to be store is relatively small. The peculiar information of the peculiar is acquired by the ink jet recording apparatus on which the ink jet recording head is mounted reading the value of the
10 resistance of the resistor formed on the base substrate, on the basis of which the ink jet recording apparatus side can effect optimum drive controls for the liquid ejection from the ink jet recording head.

Japanese Laid-open Patent Application Hei
15 6 - 91877 discloses that when the lamination film layers constituting the ink ejection portion are formed on the base substrate for manufacturing the ink jet recording, a fuse (ROM) is simultaneously formed. By selectively melting the fuse by controlling a logic
20 circuit formed simultaneously, binary data can be written and stored on the basis of the state of the fuse.

With the ink jet head using such an ink jet recording substrate, the peculiar information of the
25 head is stored, and still, the structure is simplified, and the production property and cost saving is good.

In the case of such an ink jet recording head

as is capable of recording the information, a measure should be taken against static electricity.

Particularly, in the case of an ink jet recording head detachably mountable to a main assembly of the ink jet recording apparatus, the ink jet recording head is necessarily touched by the user's hand or fingers upon the mounting thereof to the main assembly of the apparatus. For example, when the head and the ink container are integral, an ink jet recording head is mounted each time the ink in the ink container is used up, and the head is touched by the user's hand or fingers each time the mounting. When an ink jet recording apparatus is selectively usable as a normal image quality recording machine or as a photographic (high image quality) recording machine by replacing the recording head with that of another kind, the ink jet recording head is touched by the user each time of replacement. In such operations, it is desirable to protect the ink jet recording head from static electricity attack. For such a purpose, Japanese Laid-open Patent Application Hei 07 - 06095 3 discloses provision of an electrical discharge circuit around contact pads for electrical connection with the main assembly of the ink jet recording apparatus.

However, the conventional ink jet recording head capable of storing the information involves the following problems.

The ink jet recording head having the storing element such as ROM or EEPROM disclosed in Japanese Laid-open Patent Application Hei 3 - 126560 or Japanese Laid-open Patent Application Hei 6 - 9187 7, 5 unavoidably has a complicated structure, and therefore, various improvements for a high production property or for reduction in size and weight are desired. Fundamentally, a ROM chip is advantageous when the amount of recording data is large, but it is 10 disadvantageous when the amount is small.

In addition, the problem of the static electricity is not taken into account. When the size of the storing element for storing the peculiar information on the head substrate, the contact for 15 outputting the peculiar information of the head is relative weaker against the static electricity attack, and therefore, the there is a liability that storing element is broken, or the content of the stored information is changed when the head is touched by the 20 user. In view of this, measurement against the static electricity attack is important.

In the ink jet recording head disclosed in Japanese Laid-open Patent Application Hei 07 - 06095 33, the influence of the static electricity can be 25 avoided, but it is required to provide a discharge circuit on the substrate separately. For this reason, improvements in the space efficiency, downsizing

and/or cost reduction are desired.

SUMMARY OF THE INVENTION:

5 Accordingly, it is a principal object of the present invention to provide a liquid ejecting head and a liquid ejecting apparatus usable therewith wherein the influence of the static electricity is suppressed with a simple structure.

10 It is another object of the present invention to provide a liquid ejecting head and a liquid ejecting apparatus wherein the discharge during handling of the liquid ejecting head more easily occurs to a voltage source contact pad or a grounding
15 contact pad than to an information output contact pad, by which the problem of the breakdown of unintentional overwriting or rewriting of the information in the storing element due to the electric discharge is minimized.

20 According to an aspect of the present invention, there is provided a liquid ejecting head for ejection liquid, comprising electric wiring member including a plurality of contact pads which are electrically contactable to a liquid ejecting apparatus; a storing
25 element for storing individual information; a liquid ejection member, provided with an ejection outlet for ejecting the liquid, for ejecting the liquid using

electric energy supplied through a part of said plurality of contact pads, wherein said contact pads include an information contact pad electrically connected with said storing element, a voltage source
5 contact pad for supply the electric energy and a grounding contact pad, and said voltage source contact pad or said grounding contact pad is disposed at each of both sides of said information output contact pad, with no individual information contact pad which is
10 electrically contactable to the liquid ejecting apparatus, therebetween.

These and other objects, features and advantages of the present invention will become more apparent upon a consideration of the following
15 description of the preferred embodiments of the present invention taken in conjunction with the accompanying drawings.

20 BRIEF DESCRIPTION OF THE DRAWINGS:

Figure 1 is a schematic view of a wiring substrate of an ink jet recording head according to a first embodiment of the present invention.

Figure 2 is a schematic view of a wiring
25 substrate of an ink jet recording head according to a second embodiment of the present invention.

Figure 3 is a schematic view of a wiring

substrate of an ink jet recording head according to a third embodiment of the present invention.

Figure 4 is a schematic view of a wiring substrate of an ink jet recording head according to a fourth embodiment of the present invention.

Figure 5 is a perspective view illustrating a first ink jet recording head using the wiring substrate shown in Figure 2.

Figure 6 is an exploded perspective view of an ink jet recording head shown in Figure 5.

Figure 7 is a partly broken perspective view of a first recording element substrate constituting the ink jet recording head shown in Figure 5.

Figure 8 is a perspective view illustrating the second ink jet recording head using a wiring substrate for the ink jet recording head of Figure 1.

Figure 9 is an exploded perspective view of an ink jet recording head shown in Figure 8.

Figure 10 is a partly broken perspective view of a second recording element substrate constituting the ink jet recording head shown in Figure 8.

Figure 11 is a schematic view of a Si substrate including a fuse for storing peculiar information of the head and peripheral circuits therefor, according to the present invention.

Figure 12 is a schematic top plan view of an inside of an example of a recording device usable with

the ink jet recording head according to the present invention.

Figure 13 is a schematic view illustrating an ESD experiment.

5

DESCRIPTION OF THE PREFERRED EMBODIMENTS:

The description will be made as to the embodiments of the present invention in conjunction
10 with the accompanying drawings.

Figure 5 to Figure 12 illustrate an ink jet recording head or an ink jet recording apparatus which is a liquid ejecting head or a liquid ejecting apparatus according to the present invention. The
15 respective constituent-elements will be described.

The recording head of this embodiment is of a type integral with an ink container, and may be a first recording head H1000 filled with black ink, as shown in (a) and (b) of Figure 5, and may be a second
20 recording head H1001 filled with color inks (cyan ink, magenta ink and yellow ink), as shown in (a) and (b) of Figure 8. The recording head H1000 or H1001 is securely supported on a carriage 102 of a main assembly of the ink jet recording apparatus by
25 positioning means and electrical contacts, and is detachably mountable to the carriage 102. When the ink is used up, the recording head can be replaced.

The description will be made as to the structures of the recording heads H1000 and H1001 in detail.

(Recording head)

5 The first recording head H1000 and the second recording head H1001 are both of a type using an electrothermal transducer for generating thermal energy for creating film boiling in the ink in response to an electric signal, and the electrothermal
10 transducer functions as a recording element and is disposed opposed to an ink ejection outlet. In this embodiment, the recording head integrally comprises a recording element substrate for ejecting the ink (in this embodiment, the liquid ejection member is
15 provided with ejection outlets for ejecting the liquid, and the liquid is ejected using the supplied electric power), and an ink container for retaining and storing the ink to be supplied to the recording element substrate. However, the present invention is
20 applicable also to a recording head not having the ink container integrally.

(1) first recording head H1000:

Figure 6 is an exploded perspective view of the first recording head H1000. The first recording head
25 H1000 comprises a first recording element substrate H1100, an electric wiring member (electric wiring sheet) H1300, and an ink retention member H1500.

Figure 7 is a partly broken perspective view of the first recording element substrate H1100.

The first recording element substrate H1100 is constituted by a Si substrate H1110 having a thickness of 0.5 mm-1 mm, in which ink supply port H1102 in the form of an elongated through-opening (ink flow path) is formed. The ink supply port 1102 of the first recording element substrate H1100 is in fluid communication with the ink supply port H1200 of the ink retention member H1500 by bonding and fixing the first recording element substrate H1100 to the ink retention member H1500 with high precision.

The Si substrate H1110 is provided with an array of electrothermal transducer elements H1103 at each lateral side of the ink supply port H1102, so that arrays interpose the ink supply port H1102, and there are further provided unshown electric wiring of Al and the like for supplying electric power to the electrothermal transducer elements H1103.

The Si substrate H1110 is provided along edge portions adjacent opposite ends of the arrays of the electrothermal transducer elements H1103 with electrode portions H1104 for supplying the electric power to the electric wiring and for supplying the electric signals for driving the electrothermal transducer elements H1103, and bumps H1105 of Au are formed at the tops of the electrode portions H1104.

The Si substrate H1110 is further provided with a fuse and a peripheral circuit therefor formed thereon, the fuse being effective to store the peculiar information of the head. Figure 11 show the
5 fuse and the peripheral circuit.

In Figure 11 the fuse is indicated by a reference H1117. In this example, four fuses H1117 of polysilicon resistor are disposed adjacent a short side of the ink supply port H1102. Each of the fuses
10 H1117 is connected with a second driving element H1118 for melting the fuse and reading the information corresponding to the melting or non-melting of the fuse. The second driving element H1118 is disposed adjacent to the first driving element H1116 for
15 driving the electrothermal transducer element H1103.

A signal for selecting the first driving element H1116 for driving the electrothermal transducer element H1103 is used as the signal for selecting the second driving element H1118 for driving
20 the fuse H1117 as it is. Therefore, the circuit portion for selecting the second driving element H1118 can be formed with the structure similar to the circuit portion for selecting the first driving element H1116. More particularly, the portion from the
25 signal line to which the signal is inputted outside the ink jet recording substrate to the signal line connected to the second driving element H1118 through

a shift register, a latching circuit and a decoder, may be common circuit structure with the circuit for selecting the first driving element H1116. The selection circuit H1112 for finally selecting the
5 second driving element H1118 on the basis of the output from the shift register or the like, has a structure similar to the selection circuit for the first driving element H1116.

A VH pad H1104c for supplying a voltage from a
10 VH voltage source is connected with the electrothermal transducer element H1103 through the VH wiring lead H1114. A GNDH pad H1104d for connection with the GNDH voltage source is commonly connected to the second driving element H1118 connected with the fuse H1117
15 and the first driving element H1116 connection to the electrothermal transducer element H1103 through the GNDH wiring lead H1113. Namely, the GNDH wiring lead H1113 is common for the first driving element H1116 and the second driving element H1118.

20 When the fuse H1117 is to be melted, the ID pad H1104a functions as a fuse cutting voltage source contact for applying a melting voltage, and when the information indicated by the fuse is to be read out, it functions as a signal output contact. More
25 particularly, when the fuse H1117 is to be melted, a voltage (a driving voltage 24V for the electrothermal transducer element, for example) is applied to the ID

pad H1104a to instantaneously disconnect the corresponding fuse H1117 by actuating the second driving element H1118 selected by the selection circuit. At this time, the electrical conduction
5 between the ID voltage source pad H1104b for reading the information of the fuse out and the outer circuit such as the voltage source for reading the fuse information, is disconnected.

On the other hand, when the information is to
10 be read out, the ID voltage source pad H1104b is supplied with a voltage (power source voltage 3.3V of a logic circuit, for example), so that when the fuse H1117 is disconnected, the potential of the ID voltage source pad H1104b and that of the ID pad H1104a are
15 equal to each other, and therefore, a Hi level voltage is outputted from the ID pad H1104a. When the fuse H1117 is not melted, a Lo level voltage is outputted from the ID pad H1104a since the fuse H1111 has a resistance value which is far larger than the
20 resistance value of the fuse H1117.

In another example, the fuse H1117 is replaced with a simple wiring on the Si substrate H1110, and the presence or absence of such wiring may indicate information to be stored and read out. In such a case,
25 the peculiar information of the head is written during film formation for the wiring lead on the Si substrate H1110. The reading of the information is exactly the

same as the foregoing example, but it is not possible to write information after the formation.

In a further example, a resistance element representing information peculiar to the head is formed on the Si substrate H1110, and one end of the resistance element is connected to the ID pad H1104a, and the other end is connected to the GNDH pad H1104d. In such a case, the main assembly of the ink jet recording apparatus reads a resistance value between the ID pad H1104a and the GNDH pad H1104d to acquire the peculiar information of the head corresponding to the resistance value.

In any of such examples, structure of resin material having an ink flow path is formed, for each of the electrothermal transducer elements H1103, on such a side of the Si substrate H1110 as is provided with the fuses, the wiring pattern or the resistance element through a photolithography. The structure has an ink flow passage wall H1106 for defining each of the ink flow paths and a ceiling portion covering the top part thereof, and in the ceiling portion, ejection outlets H1107 are formed. The ejection outlets 1107 are provided opposed to the respective ones of the electrothermal transducer elements H1103, thus constituting a group of ejection outlets H1108.

In the first recording element H1100 thus constituted, the ink supplied from the ink flow path

H1102 is ejected through the ejection outlet 1107
opposed to the corresponding electrothermal transducer
element H1103 by the pressure of the creation of the
bubble caused by heat generation of the electrothermal
5 transducer element H1103.

The electric wiring sheet H1300 is to
constitute the electric signal path for applying the
electric signal for ejecting the ink to the first
recording element substrate H1100, and is formed of a
10 polyimide base material and a wiring lead pattern of
copper foil thereon. Also, an opening H1303 for
setting the first recording element substrate H1100 is
formed, and adjacent the edge of the opening, an
electrical contact for connection with the electrode
15 portion H1104 of the first recording element substrate
H1100. Furthermore, the electric wiring sheet H1300 is
provided with an external signal input contact for
receiving the electric signal from the main assembly
apparatus, and an external signal input contact H1302
20 and the electrical contact H1304 are electrically
connected with each other by a continuous wiring lead
pattern of copper foil.

The electrical connection between the electric
wiring sheet H1300 and the first recording element
25 substrate H1100 are electrically connected by an
ultrasonic heat crimping method between the bump H1105
formed at the electrode portion H1104 of the first

recording element substrate H1100 and the electrical contact H1304 of the electric wiring sheet H1300 corresponding to the electrode portion H1104 of the first recording element substrate H1100.

5 On a flat surface around the first recording element substrate H1100 fixed at the ink retention member H1500 (that is, the surface faces to the recording material when the recording head H1000 is mounted on the carriage 102), a back side of a part of
10 an electric wiring tape H1300 is fixed by adhesive material. An unbonded portion of the electric wiring tape H1300 is bent and is fixed by an adhesive material on a side surface substantially perpendicular to the bonding surface of the ink retention member
15 H1500 for the first recording element substrate H1100.
(2) Second recording head H1001

 The second recording head H1001 functions to eject three color inks, namely, the cyan ink, the magenta ink and the yellow ink. As shown in Figure 9
20 which is an exploded perspective view, the second recording head H1001 comprises a second recording element substrate H1101, an electric wiring sheet H1301 (electric wiring member), and an ink retention member H1501. The structures of the second recording
25 head H1001 are similar to the first recording head H1000 described in the foregoing.

Figure 10 is a partly broken perspective view

to illustrate the structure of the second recording element substrate H1101. In the second recording element substrate H1101, three ink supply ports H1102 for the cyan ink, the magenta ink and the yellow ink
5 are formed and are extended in parallel with each other, as is different from the first recording element substrate H1100. At respective lateral sides of each of the ink supply port H1102, electrothermal transducer elements H1103 and ejection outlets H1107
10 are arranged staggered, generally along a line. On the Si substrate H1110a, similarly to the Si substrate H1110 of the first recording element substrate H1100, electric wiring, fuses or resistances and electrode portions are formed. On the Si substrate H1110a, ink
15 flow passage walls H1106 and ejection outlets H1107 are formation of resin material through a photolithography. At the electrode portion H1104 for supplying the electric power to the electric wiring, bumps H1105 of Au or the like are formed.

20 (Ink jet recording apparatus)

The description will be made as to a recording device on which the above-described recording head is mountable. Figure 12 is a schematic top plan view of an inside of an example of a recording device usable
25 with the ink jet recording head of the present invention.

As will be understood from Figure 12, the

recording device comprises a carriage 102 on which the recording head H1000 shown in Figure 5 and the recording head H1001 shown in Figure 8 are removably mountable at a correct position. The carriage 102 is
5 provided with an electrical connecting portion for transmitting driving signals or the like to the respective ejection portions through the external signal input contact provided on the recording heads H1000 and H1001.

10 As shown in Figures 5 and 8, the first recording head H1000 and the second recording head H1001 are guided to a predetermined position in the carriage 102 by a mounting guide H1560 for guiding the recording head to the head mounting position in the
15 carriage 102 and by an engaging portion H1930 for fixed in g the ink jet recording head H1000 relative to the ink jet recording apparatus, and then is fixed at the position. The ink jet recording head H1000 is provided with an abutting portion H1570 for
20 positioning itself to the predetermined mounting position in the carriage 102 in a X direction (carriage scanning direction), an abutting portion H1580 for a Y direction (a recording media feeding direction), and an abutting portion H1590 for the Z
25 direction (ink ejecting direction). By these abutting portions, the recording head H1000 is correctly positioned relative to the carriage 102, so that

proper electrical contact is established between the external signal input contacts H1302 provided on the electric wiring sheets H1300 and H1301 and the contact pins of the electrical connecting portion provided in the carriage 102.

The carriage 102 is support for reciprocal motion along the guiding shaft 103 provided in the main assembly of the apparatus and extended in the main scan direction. The recording heads H1000 and H1001 are carried on the carriage 102 such that direction in which the ejection outlets of each of the ejection portions are arranged crosses with the scanning direction of the carriage 102. The liquid is ejected from the ejection outlet arrays onto the recording material 108 fed to the position facing the ejection outlets by a pick-up roller 131 and a feeding roller 109.

By replacing the recording head H1000 with recording heads each having the same structures as the recording head H1001 but containing light magenta ink, light cyan ink and black ink, respectively, the printer can be operated as a photographic high image quality printer.

(Results of ESD (electrostatic discharge) experiments)

ESD experiments have been carried out with the second recording element substrate H1101 having the circuit shown in Figure 11. The results are shown in

Table 1.

The electric wiring sheet H1301 under the experiments has the ID contact pad H1302a, the VH contact pad H1302c, the GNDH contact pad H1302d at the positions shown in Figure 13. More particularly, the VH contact pad H1302c are disposed at one side of the ID contact pad H1302a, and the GNDH contact pad H1302d are disposed at the other side. The opening dimensions of each of the contact pad are 1.3 mm x 1.3 mm and are arranged at the interval of 2.0 mm. The base material of the electric wiring sheet H1301 is polyimide, and a plurality of wiring lines of copper foil are electrically connected to the ID pads H1104a, the VH pads H1104c and the GNDH contact pads H1104d, respectively.

In Figure 13, a semispherical test contact 140 is caused to approach to the ID contact pad H1302a at the position right above the ID contact pad H1302a and is supplied with the voltage of +20kV, and the electric discharging to the respective contact pads are observed. The experiments are carried out with four samples, and the results are as follows.

Table 1 (Occurrences of electric discharge)

	Locations		
5	ID pad	VH pad	GNDH pad

	Sample 1	Yes	Yes No
	Sample 2	No	No Yes
	Sample 3	No	Yes No
10	Sample 4	No	Yes Yes

	Frequencies of		
	occurrences	1/4	3/4 2/4

15

The results of experiments show that although the discharge is tried aiming at the ID contact pad H1302a, the discharge occurred to the ID contact pad H1302a only in one of the four samples. Therefore, it is understood that discharge to the ID contact pad can be effectively impeded by the existence of the VH contact pad and/or the GNDH contact pad adjacent the ID contact pad. In the case of sample 1 with which the discharge occurred to the ID contact pad, the discharge to the VH contact pad also occurred simultaneously. From this result, it is understood that discharge to the ID contact pad is diffused by

25

the existence of the adjacent VH contact pad and/or GNDH contact pad.

In the foregoing description, the storing element is provided in the recording element substrate.

5 But, the similar effects are provided when a similar storing element is provided in another substrate.

As described in the foregoing, in the recording head of this embodiment, one or both of the VH contact pad and the GNDH contact pad are disposed at both of
10 the sides of the ID contact pad adjacent thereto, so that discharge to the ID contact pad is effectively impeded. By doing so, the adverse influence, to the storing element, of the static electricity attack upon contact of the user's hand or finger to the head when
15 the head is mounted to the carriage or to the main assembly of the apparatus, is prevented. Recently, the circuit on the substrate for the ink jet recording is improved, it is quite durable against the static electricity, and therefore, the countermeasure
20 against the static electricity would be sufficient if the disposition of the contact pad of these embodiments of the present invention are employed.

The description will be made as to the positional relation among the ID contact pad, the VH
25 contact pad and the GNDH contact pad with more specific examples.

Embodiment 1

Referring to Figure 1, the description will be made as to an ink jet recording head according to the first embodiment of the present invention.

Figure 1 is an enlarged view of the external
5 signal input contact portion of the electric wiring sheet of the second recording head used with the ink jet recording head of this embodiment. Referring to Figure 1, the electric wiring sheet H1301 is provided with 32 external signal input contacts H1302. Of these
10 external signal input contacts H1302, six pads are ID contact pads H1302a which are disposed substantially at the central portion of the portion where the external signal input contacts H1302 are disposed. The ID contact pads H1302a are respectively connected to
15 the ID pads connected with the fuse H1117 (a simple connecting line or the resistance element (Figure 11)) provided at the opposite ends of each of the three ink supply ports H1102 of the second recording element substrate H1101 shown in Figure 10.

20 Six VH contact pads H1302c are disposed along one side of the array of the ID contact pads H1302a (the side above the array of the ID contact pads H1302a in Figure 1) adjacent the ID contact pad H1302a array. More particularly, in this embodiment, the VH
25 contact pads H1302c are immediately adjacent to the ID contact pad H1302a array (namely, with no ID contact pad H1302a therebetween). These VH contact pads H1302c

are electrically connected to the VH pads H1104c (Figure 11) provided in the electrode portion H1104 (Figure 10) at the opposite ends of the second recording element substrate H1101.

5 Six GNDH contact pads H1302d are arranged along the array of the ID contact pads H1302a on the other side, that is, the side below the array of the ID contact pads H1302a in Figure 1. More particularly, in this embodiment, the GNDH contact pads H1302d are
10 immediately adjacent to the ID contact pad H1302a array (namely, with no ID contact pad H1302a therebetween). These VH contact pads H1302 d are electrically connected to the GNDH pads H1104 (Figure 11) provided in the electrode portion H1104 (Figure
15 10) at the opposite ends of the second recording element substrate H1101.

The other external signal input contacts H1302 other than the ID contact pads H1302a, the VH contact pads H1302c and the GNDH contact pad H1302d, are used
20 for electric power supply to the transistors, sending and receiving signals such as control signals or the like.

In the case of the ink jet recording head of the present invention, the ID contact pads H1302a
25 which are relative weak against the attach of static electricity are positioned substantially at the central portion of the external signal input contact

portion H1302. This position is hard to be touched by the user, when the user manipulates the second recording head by hand. Usually, the user is more or less conscious so as not to touch the external signal input contact H1302, and therefore, the pads disposed at the center portion is not easily touched.

In addition, the ID contact pads H1302a are adjacent to and interposed between the VH contact pad H1302c and the GNDH contact pad H1302d, and therefore, if an electrically charged finger of the user is brought so close to the ID contact pad H1302a that electrical discharge occurs, the discharge tends to be toward the VH contact pad H1302c and/or to the GNDH contact pad H1302d rather than toward the ID contact pad H1302a. Thus, the structure of the present invention is such that peculiar information in the head is not broken, overwritten or rewritten.

Embodiment 2

Referring to Figure 2, the description will be made as to an ink jet recording head according to a second embodiment of the present invention.

Figure 2 is an enlarged view of an external signal input contact portion of electric wiring of a first recording head usable with an ink jet recording head according to this embodiment. Referring to Figure 2, the electric wiring sheet H1300 is provided with 21 external signal input contacts H1302. The first

recording head is for the black ink, and therefore,
the numbers of the electric power supply contacts, the
control signal contacts are smaller than the second
recording head for the cyan, magenta and yellow inks,
5 as described in the first embodiment.

However, the carriage 102 of the main assembly
of the ink jet recording apparatus is capable of
accepting the third recording head which is for the
photographic printing and which has the same structure
10 as the second recording head, at the position where
the first recording head is removed. Therefore, the
positions of the 21 external signal input contacts
H1302 correspond to the positions of the external
signal input contacts H1302 of the second recording
15 head when the head is mounted to the carriage 102.

The number of the ID contact pads H1302a of the
external signal input contacts H1302 on the electric
wiring sheet H1300, six, and the positions thereof are
substantially at the center of the portion where the
20 external signal input contacts H1302 are provided. The
ID contact pads H1302a are connected to the ID pads
which in turn is connected to a fuse H1117, a simple
wiring line or a resistance element, Figure 11)
disposed at each of the opposite ends of the ink
25 supply port H1102 of the first recording element
substrate H1100.

Four VH contact pads H1302c are arranged along

and adjacent to the array of the ID contact pad H1302a at one lateral side (above the array of the ID contact pads H1302a in Figure 2. More particularly, in this embodiment, the VH contact pads H1302c are immediately
5 adjacent to the ID contact pad H1302a array (namely, with no ID contact pad H1302a therebetween). The VH contact pads H1302c are connected to the VH pads H1104c (Figure 11) provided in the electrode portion H1104 (Figure 7) disposed at the opposite ends of the
10 first recording element substrate.

Four GNDH contact pads H1302d are arranged along and adjacent to the array of the ID contact pad H1302a at one lateral side (below the array of the ID contact pads H1302a in Figure 2. More particularly, in
15 this embodiment, the GNDH contact pads H1302 d are immediately adjacent to the ID contact pad H1302a array (namely, with no ID contact pad H1302a therebetween). The GNDH contact pads H1302d are connected to the GNDH pads H1104 (Figure 11) provided
20 in the electrode portion H1104 (Figure 7) at the opposite ends of the recording element substrate H1100.

The other external signal input contacts H1302 other than the ID contact pads H1302a, the VH contact pads H1302c and the GNDH contact pad H1302d, are used
25 for electric power supply to the transistors, sending and receiving signals such as control signals or the like.

According to the ink jet recording head of this embodiment, similarly to the first embodiment, the ID contact pads H1302a which are relative weak against the attach of static electricity are positioned substantially at the central portion of the external signal input contact portion H1302, and therefore, the user does not easily touch the ID contact pad H1302a.

In addition, the ID contact pads H1302a are adjacent to and interposed between the VH contact pads H1302c and the GNDH contact pads H1302d, and therefore, even when if an electrically charged finger of the user is brought so close to the ID contact pad H1302a that electrical discharge occurs, the discharge tends to be toward the VH contact pad H1302c and/or to the GNDH contact pad H1302d rather than toward the ID contact pad H1302a, and therefore, the peculiar information in the head is not easily broken, overwritten or rewritten.

Embodiment 3

Referring to Figure 3, the third embodiment will be described.

Figure 3 is an enlarged view of the external signal input contact portion of the electric wiring sheet of the second recording head used with the ink jet recording head of this embodiment. A second type recording head of this embodiment uses the second recording element substrate H1101 which is the same as

the first embodiment, and the difference from the first embodiment is only in the disposition of the external input contacts H1302 on the external electric wiring.

5 Six pads of 32 external signal input contacts H1302 provided on the electric wiring sheet H1301 are ID contact pads H1302a. The ID contact pads H1302a are arranged in a longitudinal direction (in the direction of the length of the electric wiring sheet H1301) at
10 the center of the portion where the external signal input contacts H1302 are provided.

 Along the array of the ID contact pads H1302a, six VH contact pads H1302c are arranged adjacent thereto at one lateral side thereof, and six GNDH
15 contact pads H1302d are arranged adjacent thereto at the other lateral side thereof. More particularly, in this embodiment, the VH contact pads H1302c are immediately adjacent to the ID contact pad H1302a array (namely, with no ID contact pad H1302a
20 therebetween), and the GNDH contact pads H1302 d are immediately adjacent to the ID contact pad H1302a array (namely, with no ID contact pad H1302a therebetween).

 According to the ink jet recording head of this
25 embodiment, similarly to the first embodiment, the ID contact pads H1302a which are relative weak against the attach of static electricity are positioned

substantially at the central portion of the external signal input contact portion H1302, and therefore, the user does not easily touch the ID contact pad H1302a.

In addition, the ID contact pads H1302a are
5 adjacent to and interposed between the VH contact pads H1302c and the GNDH contact pads H1302d, and therefore, even if an electrically charged finger of the user is brought so close to the ID contact pad H1302a that electrical discharge occurs, the discharge tends to be
10 toward the VH contact pad H1302c and/or to the GNDH contact pad H1302d rather than toward the ID contact pad H1302a, and therefore, the peculiar information in the head is not easily broken, overwritten or rewritten.

15 Embodiment 4

Referring to Figure 4, an ink jet recording head according to a fourth embodiment will be described.

Figure 4 is an enlarged view of the external
20 signal input contact portion of the electric wiring sheet of the second recording head used with the ink jet recording head of this embodiment. A second type recording head of this embodiment uses the second recording element substrate H1101 which is the same as
25 the first embodiment, and the difference from the first embodiment is only in the disposition of the external input contacts H1302 on the external electric

wiring.

Six pads of 32 external signal input contacts H1302 provided on the electric wiring sheet H1301 are ID contact pads H1302a. The ID contact pads H1302a are
5 disposed substantially at the central portion of the portion where the external signal input contacts H1302 are provided. Around the ID contact pads H1302a (above, below, left side and right side of the ID contact pads H1302a in Figure 4), the VH contact pads H1302c and/or
10 the GNDH contact pads H1302d are disposed at positions adjacent thereto. Each of the ID contact pads H1302a is interposed between the VH contact pads H1302c and the GNDH contact pads H1302d in the longitudinal direction and in the transverse direction. In other
15 words, two arrays of three ID contact pads H1302a extend inclined at the central portion of the portion where the external signal input contacts H1302 are provided, and three arrays which comprise six VH contact pads H1302c and six GNDH contact pads H1302d
20 extend so as to interpose the respective ones of the arrays of the ID contact pads H1302a.

According to the ink jet recording head of this embodiment, each of the ID contact pads H1302a are interposed between the VH contact pads H1302c or the
25 GNDH contact pads H1302d which are disposed around it, more particularly, at the top, bottom, left and right. For this reason, the peculiar information in the head

of this embodiment is less easily broken, overwritten or rewritten than in the heads of the other embodiments. More particularly, in this embodiment, the VH contact pads H1302c are immediately adjacent to the ID contact pad H1302a array (namely, with no ID contact pad H1302a therebetween), and the GNDH contact pads H1302 d are immediately adjacent to the ID contact pad H1302a array (namely, with no ID contact pad H1302a therebetween).

10 The ink jet recording head of any of the foregoing embodiments is not limited to those of the ejecting types, but is applicable to the ink jet recording heads of various ink ejecting types.

 The external signal input contacts in any of the foregoing embodiments, may be a pad connected to the similar set of pads. As to the ID contact pads, they may be usable as information writing pads when the storing element is an information writable (not only readable) element.

20 According to the foregoing embodiments, the problem of the overwriting or rewriting of individual information in the storing element due to the static electricity upon the head mounting, can be solved.

 While the invention has been described with reference to the structures disclosed herein, it is not confined to the details set forth and this application is intended to cover such modifications or

changes as may come within the purpose of the
improvements or the scope of the following claims.

WHAT IS CLAIMED IS:

1. A liquid ejecting head mountable to a liquid ejecting apparatus, said liquid ejecting head comprising:
 - a recording element for generating energy for effecting recording by ejecting liquid in response to a driving voltage applied thereto;
 - an electric power line, connected to said recording element, for supplying the driving voltage to said recording element;
 - a grounding electrical line, connected to said recording element, for electrically grounding said recording element;
 - a storing element for storing individual information which is capable of being read out with a voltage applied thereto which is lower than the driving voltage; and
 - a plurality of head electrical contacts electrically connectable to apparatus electrical contacts provided in the apparatus when said head is mounted to the apparatus, said head electrical contacts including:
 - a first electrical contact electrically connected with said storing element; and
 - a plurality of second contacts electrically connected with said recording element through said electric power line or said grounding line;wherein said first contact is provided in a region between two of said second contacts which are disposed adjacent to said first contact, respectively.
2. A liquid ejecting head according to Claim 1, wherein said first electrical contacts constitute a first contact array, and said second electrical contacts constitute second contact arrays which interpose said first contact array.
3. A liquid ejecting head according to Claim 2, wherein said first contact array does not comprise any of said second electrical contacts.
4. A liquid ejecting head according to Claim 2, wherein said second contact arrays do not comprise any of said first electrical contacts.
5. A liquid ejecting head according to Claim 1, wherein said first electrical contacts constitute first contact arrays, and said second electrical contacts constitute second contact arrays which directly interpose each of said first contact arrays.

6. A liquid ejecting head according to Claim 1, wherein said first contact is directly interposed between said second contacts in a first contact array direction and in a second contact array direction crossing with the first contact array direction.

7. A liquid ejecting head according to Claim 1, wherein the information is indicated by presence or absence of a electrical interconnection in said recording element.

8. A liquid ejecting head according to Claim 1, wherein said storing element comprises a fuse disconnectable by a external electric signal.

9. A liquid ejecting head according to Claim 1, wherein said storing element includes a resistance element.

10. A liquid ejecting head according to Claim 1, further comprising a liquid container for storing liquid.

11. A liquid ejecting apparatus usable with a liquid ejecting head for ejecting liquid, said apparatus comprising:
a liquid ejecting head according to Claims 1; and
a carriage reciprocable in a predetermined direction while carrying said liquid ejecting head.

12. A liquid ejecting head mountable to a liquid ejecting apparatus, said liquid ejecting head comprising:
a recording element for generating energy for effecting recording by ejecting liquid in response to a driving voltage applied thereto;
an electric power line, connected to said recording element, for supplying the driving voltage to said recording element;
a grounding electrical line, connected to said recording element, for electrically grounding said recording element;
a storing element for storing individual information which is capable of being read out with a voltage applied thereto which is lower than the driving voltage; and
a plurality of head electrical contacts electrically connectable to apparatus electrical contacts provided in the apparatus when said head is mounted to the apparatus, said head electrical contacts including:
a plurality of first electrical contacts electrically connected with

said storing element; and

a plurality of second contacts electrically connected with said recording element through said electric power line or said grounding line; wherein each of said first contacts is provided in a region surrounded at least by three of said second contacts which are disposed adjacent to said first contacts, respectively.

13. A liquid ejecting head according to Claim 12, wherein said first electrical contacts constitute a first contact array, and said second electrical contacts constitute second contact arrays which interpose said first contact array.

14. A liquid ejecting head according to Claim 12, wherein said first contact is directly interposed between said second contacts in a first contact array direction and in a second contact array direction crossing with the first contact array direction.

15. A liquid ejecting head according to Claim 12, wherein the information is indicated by presence or absence of a electrical interconnection in said recording element.

16. A liquid ejecting head according to Claim 12, wherein said storing element comprises a fuse disconnectable by a external electric signal.

17. A liquid ejecting head according to Claim 12, further comprising a liquid container for storing liquid.

18. A liquid ejecting apparatus usable with a liquid ejecting head for ejecting liquid, said apparatus comprising:
a liquid ejecting head according to Claims 12; and
a carriage reciprocable in a predetermined direction while carrying said liquid ejecting head.