

A DIGITAL AUDIO SIGNAL GENERATING APPARATUS

This invention relates generally to apparatus for generating a digital audio signal and, more particularly, is directed to a digital audio signal generating apparatus suitable in the application to electronic musical instruments, sound effect generator for amusement machines and the like.

As a sound source for electronic musical instruments or sound effect sound source for amusement machines, the following one is proposed in the prior art. According to this previously-proposed sound source, a rectangular wave signal, for example, is supplied to a plurality of preset frequency dividers each having different frequency-dividing ratio and different duty ratio. Sound source signals (i.e. so-called voices) from the respective frequency dividers are synthesized in a proper level. In that case, the original oscillation waveform may be a triangular wave, a sinusoidal wave or the like.

In some musical instrument such as piano and drums, the total sound generating period is divided to provide 4 intervals such as attack period, decay period, sustain period and release period, and an amplitude (level) of the signal in each interval presents a peculiar changed condition. Accordingly, a so-called ADSR (attack, decay, sustain, release) control is performed so as to cause the signal level of each voice to be changed similarly.

On the other hand, as a sound source for musical instruments, a so-called FM sound source is known, in which

a sine wave signal is frequency-modulated (FM) by a sine wave signal having a low frequency. According to this FM sound source, a modulation factor is made as a function of time and various kinds of sound signals (sound signal means an audio signal in this specification) can be obtained by the lesser sound source. The sound effect sound source may be a noise component (i.e. white noise component and the like).

In order to obtain real sounds of various musical instruments by using the afore-mentioned so-called electronic sound source, very complex signal processing is required and hence, the circuit scale of the audio signal generating apparatus is made large.

To solve the above-mentioned problem, recently, a so-called sampler sound source is proposed, in which real sounds of various musical instruments are digitally recorded, written in a memory (ROM) and a signal of a predetermined musical instrument is read from this memory.

In this sampler sound source, in order to save the storage capacity of memory, the digital audio signal is data-compressed and written in the memory, while the compressed digital signal read from the memory is data-expanded and is re-converted to the original digital sound signal. In this case, only the signal of sound having particular loudness (pitch) is written in the memory at every musical instrument, and the signal read from the memory is pitch-converted to generate a fundamental frequency signal of sound having a desired loudness.

Further, a signal waveform, appeared in the initial stage of sound generation and peculiar to each musical

instrument, is directly written in the memory and is read out of the memory. This signal waveform is what might be called a formant, and the formant means, in the case of, for example, piano, a sound such as an operation sound and the like generated when the pianist touches a keyboard of piano to cause a hammer to strike a key. In that case, a repetitive waveform portion of a fundamental cycle is written in the memory only by one cycle amount and is repeatedly read from the memory.

More specifically, upon reproduction, as shown in Fig. 1, subsequent to a formant component a of short time period, a fundamental frequency signal component b, which is formed of repetitive waveforms p, is obtained and thus a sound of a desired musical instrument can be obtained. In that event, in the case of sound of piano or the like, a natural sound of musical instrument can be reproduced by gradually decreasing the level of the waveform p in accordance with a predetermined rule.

According to the above-mentioned musical instruments, if a reverberation sound or the like is added to the reproduced musical instrument sound, then it will be possible to reproduce sounds of various tones. In particular, when the digital audio signal generating apparatus is employed as the sound effect generating apparatus for amusement machines, it is frequently requested to add the reverberation sound to the reproduced sound in order to gain presence satisfactorily.

When the reverberation sound is added to the digital audio signal, however, the digital audio signal is temporarily stored in a memory such as a random access

memory (RAM) or the like and is delay-processed by this memory, thereby generating a reverberation sound. This requires a memory of large storage capacity in which the digital audio signal is stored, which fact makes the apparatus complicated in arrangement.

Further, according to the previously-proposed reverberating apparatus, when control data from a central processing unit (CPU) is not defined because the power switch of the apparatus is just turned ON, a delay processing area is erroneously set in the sound source data writing area of the memory, which causes the apparatus to malfunction.

Further, when the FM operation is performed in order to gain various sounds in the sampler sound source, a signal source for frequency-modulation is required, which causes the circuit arrangement to become complicated.

Furthermore, when the amplitude-modulation (AM) is performed in order to achieve performance effect, there is then presented a similar problem.

In addition, the memory which temporarily stores the sound source data and control program required when processing the sound source data is requested to have a relatively large storage capacity, which unavoidably causes the circuit arrangement to become complicated.

It is an object of the present invention to provide an improved digital audio signal generating apparatus of simplified arrangement which can add a reverberation sound to a sound without providing a special memory.

5 According to the present invention, there is provided an apparatus for generating a digital audio signal comprising:

(a) memory means for storing a digital audio signal;

(b) control means for controlling a reading of said
10 digital audio signal from said memory means;

(c) signal processing means for performing a predetermined synthesis of said digital audio signal read by said control means so as to produce, on reproduction of the signal, a sound in a desired voice.

15 (d) temporary memory means used in the synthesis in said control means and said signal processing means; and

(e) means for setting a delay area in a vacant area of said temporary memory means so as to perform a delay processing, when a reverberation signal is added to the
20 digital audio signal processed by the synthesis in said signal processing means.

A plurality of digital audio signals may be generated using respective pitch converting means, and means may be provided for supplying the output of one of said pitch converting means to an other of the pitch converting means as a control signal, whereby a frequency-modulated digital audio signal is generated from said other pitch converting means.

Similarly a plurality of digital audio signals may be generated using respective amplitude control means, and means may be provided for supplying the output of one of said amplitude control means to an other of the amplitude control means as a control signal, whereby an amplitude-modulated digital audio signal is generated from said other amplitude control means.

An embodiment of the invention may be implemented using data processing apparatus comprising:

(1) first executing means having a first execution cycle to execute its operation in accordance with said cycle and for writing in and reading out data from a common memory;

(2) second executing means having a second execution

cycle different from said first execution cycle to execute its operation in accordance with said second cycle and for writing in and reading out data from said common memory;

(3) selecting means for selectively connecting one of
5 said first and second executing means to said common memory by one of said first and second executing means;

(4) control means for controlling said selecting means so that data can be written in and/or read from said common memory by said second executing means during a non-
10 access period in which data is not written in and/or read from said common memory by said first executing means; and

(5) holding means provided between said second executing means and said common memory for holding data so that a period in which said second executing means writes in
15 and/or reads data from said memory substantially coincides with said non-access period.

The invention will be further described by way of non-limitative example with reference to the accompanying drawings, in which:-

20 Fig. 1 is a schematic diagram to which reference will be made in explaining a reproducing operation of musical instrument sound;

Fig. 2 and 3 are block diagrams each showing a main portion of a digital audio signal generating apparatus
25 according to an embodiment of the present invention,

respectively;

Fig. 4 is a schematic block diagram showing a general or overall arrangement of one embodiment of the present invention;

5 Fig. 5 is a schematic diagram of an example of a random access memory;

Figs. 6A - 6C are spectrum diagrams of frequencies to which reference will be made in explaining the operation of the apparatus of this invention;

10 Fig. 7 is a block diagram showing a main portion of an arrangement of a computing section which is used to add a reverberation sound to a digital audio signal;

15 Fig. 8 is a block diagram showing a main portion of an arrangement of a computing section which is associated with the frequency-modulation;

Figs. 9A - 9C are schematic representations to which reference will be made in explaining the operation of the computing section of Fig. 8, respectively;

20 Fig. 10 is a block diagram showing an example of a synchronizing circuit used in the present invention;

Figs. 11A - 11D are timing charts to which reference will be made in explaining the operation of the synchronizing circuit of Fig. 10, respectively; and

25 Figs. 12A - 12G are timing charts to which reference will be made in explaining a timing at which an external random access memory should be controlled, respectively.

30 An apparatus for generating a digital audio signal according to an embodiment of the present invention will hereinafter be described with reference to Figs. 2 to 5.

Referring to the drawings, and initially to Fig. 4, a general or overall arrangement of the embodiment of the present invention will be explained hereinbelow.

Referring to Fig. 4, there is shown a sound source read only memory (ROM) such as a ROM cartridge or the like provided outside of the apparatus. In this sound source ROM 1, sound data of, for example, 16 bits, which are generated from various musical instruments and digitally recorded as mentioned before, are reduced in bit rate to, for example, 4 bits (i.e. BRR-encoded) and stored in block. In this embodiment, musical instrument tones such as tone of piano and so on are separately memorized (stored) in the form of a non-interval component called a formant component in the early stage of sound generation and an interval component which is a fundamental frequency signal of one cycle amount of sound of particular loudness.

In Fig. 4, reference numeral 10 generally designates a digital signal processing apparatus (DSP) which is provided as an electronic musical instrument. This digital signal processing apparatus 10 includes a signal processing section 11 and a register random access memory (RAM) 12. Of sound data from various kinds of sound sources stored in the ROM 1, a desired sound data is transferred through the signal processing section 11 to an external RAM 14 under the control of a central processing unit (CPU) 13. This external RAM 14 has a storage capacity of, for example, 64 kilo bytes and stores therein, in addition to the sound source data, program of CPU 13 and delay data used for reverberation sound addition processing. They are respectively used in a time-division manner upon use.

Similarly, the register RAM 12, which stores various control data and so on, is made operable by both of the signal processing section 11 and the CPU 13 in a time-division manner.

5 The sound source data read from the external RAM 14 is decoded to the original sound source data by the BRR decoding-processing which is opposite to the afore-mentioned BRR encoding-processing. If necessary, the decoded original sound source data undergoes various data processings such as
10 the above-mentioned ADSR-processing, pitch-conversion processing and the like. The digital audio signal thus processed is supplied to a digital-to-analog (D/A) converter 2, in which it is converted to an analog audio signal and is fed to a speaker 3.

15 The arrangement of a main component of one embodiment of the present invention will be explained with reference to Figs. 2 and 3.

 In this embodiment, 8 voices of #A, #B, ..., #H are synthesized or mixed and outputted as left and right-two
20 channel digital audio signals. The digital audio signals of the respective voices and the respective channels are computed in a time-division manner. In order to gain a better understanding of the present invention, imaginary hardwares of the same arrangement are prepared for each
25 voice and each channel in Figs. 2 and 3.

 In Fig. 2 (formed of Figs. 2A and 2B to permit a use of a suitably large scale), reference numerals 20A, 20B, ..., 20H respectively designate signal processing sections for voices #A, #B, ..., #H. These signal processing
30 sections 20A, 20B, ..., 20H are each supplied with desired

sound source data which are read from a sound source data storage section 14V in response to sound source selecting data SRC_a to SRC_h supplied to a terminal 15 of the external RAM 14. In this embodiment, the sound source data storage section 14V designates an area of the external RAM 14 in which there are written the sound source data and the program data of the CPU 13.

In this embodiment, when musical instrument tones, independently stored in the sound source ROM 1 in the form of non-internal component and the interval component, are reproduced, data of the non-interval component is supplied to the signal processing portion 20A of the voice #A. Whereas, the data of the interval component is supplied to the signal processing sections 20B to 20H of other voices under control of control data which will be explained later.

The sound source data supplied to the signal processing section 20A is supplied through a switch S_{1a} to a BRR decoder 21, in which it is data-expanded as set forth above and is fed through a buffer RAM 22 to a pitch converting circuit 23. The switch S_{1a} is opened and/or closed in response to control data KON (key ON) and KOF (key OFF) supplied thereto from the register RAM 12 (see Fig. 4) through terminals 31a and 32a. The pitch converting circuit 23 is supplied with pitch control data P(H) and P(L) from the register RAM 12 through a control circuit 24 for computing parameters or the like and a terminal 33a, and the control circuit 24 is supplied with a signal such as other voice #H through a terminal 34a and a switch S_{2a} . The switch S_{2a} is controlled in its connected state in response to control data FMON (FM ON) from the register RAM 12

through a terminal 35a.

The output of the pitch converting circuit 23 is supplied to a multiplier 26 and the multiplier 26 is supplied with control data ENV (envelope-control) and ADSR (ADSR-control) from the register RAM 12 through terminals 36a and 37a, control circuits 27 and 28 and a change-over switch S_{3a} . The change-over switch S_{3a} is changed in position in response to the most significant bit (MSB) of the control data ADSR.

When a noise is used as the effect sound source, an output of, for example, an M-series noise generator, though not shown, is employed instead of the output of the pitch converting circuit 23, and is then fed to the multiplier 26.

The output of the multiplier 26 is commonly supplied to second and third multiplier 29l and 29r, and control data LVL (left sound volume) and control data RVL (right sound volume) from the register RAM 12 are supplied to the multipliers 29l and 29r via terminals 38a and 39a, respectively.

An instantaneous value OUTX of the output of the multiplier 26 is supplied to the register RAM 12 through a terminal 41a, and is also supplied to a terminal 34b of the signal processing section 20B. A peak value ENVX of the output of the switch S_{3a} is supplied to the register RAM 12 via a terminal 42a. Further, an output at the terminal 41a of the signal processing section 20A may be supplied to a terminal 36b of the signal processing section 20B as shown by a broken line in Fig. 2.

Tables 1 and 2 illustrate maps of control data on the register RAM 12.

TABLE 1

Address	Register
00	LVL
01	RVL
02	P (L)
03	P (H)
04	Voice #A ADSR(1)
05	ADSR(2)
06	ENV
07	SRC
08	ENVX
09	OUTX
10 ~ 19	Voice #B
20 ~ 29	Voice #C
30 ~ 39	Voice #D
40 ~ 49	Voice #E
50 ~ 59	Voice #F
60 ~ 69	Voice #G
70 ~ 79	Voice #H

TABLE 2

Address	Register
0C 1C 2C 3C : :	NON KOF FMON NON (Noise ON) : :
0D 1D 2D 3D 4D 5D : :	MVL(L, R) EVL(L, R) EDL EFB EON ESA : :
0F ~ 7F	C ₀ ~ C ₇ (Coefficients)

The control data on the table 1 are prepared for each voice, and the control data on the table 2 are commonly prepared for 8 voices. The control data below the address 0D are associated with a block diagram forming Fig. 3 which will be explained below. Each of the registers on the tables 1 and 2 is of an 8-bit register.

Referring to Fig. 3, there are provided left-channel and right-channel signal processing sections 50L and 50R, respectively. The output of the second multiplier 29l of the signal processing section 20A of Fig. 2 is directly supplied to a main adder 51ml of the left-channel signal processing section 50L through a terminal TL_a, and is also fed to a sub-adder 51el through a switch S_{4a}. The output of the third multiplier 29r is directly supplied to a main adder 51mr of the right-channel signal processing section 50R through a terminal TR_a and is also supplied to a sub-adder 51er through a switch S_{5a}. Similarly, the respective outputs of the signal processing sections 20B to 20H of the voices #B to #H are supplied to adders 51ml, 51el and 51mr, 51er of the left-channel and right-channel signal processing sections 50L and 50R.

Switches S_{4a}, S_{5a}; S_{4b}, S_{5b}, ..., S_{4h}, S_{5h} corresponding to the same voices of both signal processing sections 50L and 50R are each opened and/or closed in a ganged relation in response to control data EON_a (echo-ON), EON_b, ..., EON_h supplied thereto from the register RAM 12 through terminals 61a, 61b, ..., 61h.

In that event, when the signal processing of the above-mentioned non-interval component is performed by the signal processing section 20A of the voice #A, the switches

S_{4a} and S_{5a} are controlled so as not to close, thereby preventing a reverberating sound (echo) from being added to the non-interval component.

5 The output of the main adder 51m2 is supplied to a multiplier 52, and a control data MVL (main sound volume) from the register RAM 12 is supplied to the multiplier 52 via a terminal 62. The output of the multiplier 52 is supplied to an adder 53.

10 The output of the sub-adder 51e2 is supplied through an adder 54, a left-channel echo control section 14E2 of the external RAM 14 and a buffer RAM 55 to a digital low-pass filter 56 such as a finite impulse response (FIR) filter. The echo control section 14E2 is supplied with control data ESA (echo start address) and EDL (echo delay) from the
15 register RAM 12 through the terminals 63 and 64.

In this embodiment, the left-channel and right-channel echo control sections 14E2 and 14Er are provided within the external RAM 14, if necessary. More specifically, as shown in Fig. 5, the storage capacity of a sound source data
20 storage section 14V of the external RAM 14 changes with the sound source to be employed. As a result, a vacant area 14Z in which there are stored no sound source data and control data is produced depending on the using condition. In that event, the left-channel and right-channel echo control
25 sections 14E2 and 14Er are set within the vacant area 14Z. Start addresses of the echo control sections 14E2 and 14Er are determined by the control data ESA, and the amount of address in which the echo control sections 14E2 and 14Er follow from the start address is determined by the control
30 data EDL. If the address amount is sufficient, then the

delay amount will be increased and the reverberation time will be increased.

Referring back to Fig. 3, the low-pass filter 56 is supplied with coefficient data C_0 to C_7 from the register RAM 12 through a terminal 66. The output of the low-pass filter 56 is fed through a multiplier 57 back to the adder 54, and is also supplied to a multiplier 58. The multipliers 57 and 58 are supplied with control data EFB (echo feedback) and EVL (echo sound volume) from the register RAM 12 through terminals 67 and 68, respectively. The output of the multiplier 58 is supplied to the adder 53, in which it is mixed to the output of the main adder 51m1 through the multiplier 52, and the mixed output is delivered through an over-sampling filter 59 to an output terminal Lout.

The external RAMs 14E_l and 14E_r of Fig. 3 constitute one portion of the external RAM 14 of Fig. 4 similarly to the external RAM 14V of Fig. 2 so that the signals are inputted and/or outputted for each voice and each channel in a time-division manner. Further, the buffer RAM 22 of Fig. 2 and the buffer RAM 55 of Fig. 3 are also operated in a time-division manner similarly as described above.

The operation of one embodiment of the present invention will be explained hereinafter.

The sound source data storage section 14V stores therein sound source data of various musical instruments such as piano, saxophone, cymbals and the like. In this case, the above-mentioned sound source data are assigned numbers 0 to 255, while sound source data having the non-interval component such as piano and the like are stored

in the storage section 14V so as to have numbers different from those of the non-interval component and the interval component. 8 sound source data, selected by the sound source selecting data SRC_a to SRC_h are processed by the signal processing sections 20A to 20H of respective voices in a time-division manner.

In this embodiment, a sampling frequency f_s is selected to be, for example, 44.1 kHz and computing processings of, for example, 128 cycles in total are performed in 8 voices and 2 channels within one sampling cycle ($1/f_s$). One computing cycle is, for example, 170 nanoseconds.

In this embodiment, unlike the ordinary operation, switches S_{1a} to S_{1h} indicating the sound start (key ON) and sound stop (key OFF) of respective voices are controlled by use of different flags. In other words, the control data KON (key ON) and KOF (key OFF) are respectively prepared. Both control data are 8 bits and are written in separate registers, and bits D_0 to D_7 of each control data correspond to key ON and key OFF of each of the voices #A to #H.

Therefore, the user (musical software producer) may set flag "1" only in the voice which the user wants to key ON or key OFF, so that the user is free from such a cumbersome work for making a program in which bits, not changed at every individual musical note, are temporarily written in a buffer register.

In this embodiment, when the sound source data, separated in the form of non-interval component and interval-component, are reproduced, the non-interval component data is read from the RAM 14V and the switch S_{1a} of the signal processing section 20A of the voice #A is

controlled to process the non-interval component a in the voice #A as shown in Fig. 6A. When the data of the non-interval component a are fully read from the RAM 14V, data of one cycle of the succeeding interval component is repeatedly read, and one of the switches S_{1b} to S_{1h} of any one of vacant signal processing sections 20B to 20H of voices #B to #H is controlled to signal-process the interval component of any one of the voices #B to #H. Assuming that the signal processing section 20B of voice #B is vacant, then the interval component b succeeding to the non-interval component a will be signal-processed by the signal processing section 20B as shown in Fig. 6B. In that event, the interval component b is converted to data of a predetermined pitch by the pitch converting circuit 23.

When sounds of different loudnesses derived from the same musical instrument are reproduced as an overlapped sound while the musical instrument tone formed of the non-interval component a and the interval component b is reproduced, as shown in Fig. 6A, the non-interval component a' similar to the non-interval component a is read from the RAM 14V, and is processed by the signal processing section 20A of the voice #A. In that event, the interval component b is being processed by the signal processing section 20B of the voice #B so that a interval component b' succeeding to the non-interval component a' is processed by the signal processing section of other vacant voice, for example, the signal processing section 20C of voice #C as shown in Fig. 6C. In that case, the interval component b' is converted to an interval component different from the interval component b by the pitch converting circuit 23. Then, respective

sounds are added by the main adders 51ml and 51mr or sub-adders 51el and 51er of the left-channel and right-channel signal processing sections 50L and 50R and are reproduced as a double sound.

5 In this embodiment, 8 voices of #A to #H are processed in a time-division manner so that the pitch converting circuit 23 performs the interpolation computing, i.e. over-sampling on the basis of input data of preceding and succeeding 4 samples, thus the pitch conversion being
10 performed at the same sampling frequency f_s as that used for the input data. The desired pitch is expressed by the control data P(H) and P(L).

 If the lower significant bit of the control data P(L) is selected to be zero, then it will be possible to avoid
15 that the interpolation data are irregularly selected and removed. Thus, it is possible to obtain a reproduced sound of high quality which is free from very small vibration in pitch.

 When the switch S_{2a} is closed by the control data FMON from the terminal 35a, then the audio signal data of, for
20 example, voice #H, supplied to the terminal 34a, is added to the pitch control data P(H) and P(L), whereby the audio signal of voice #A is frequency-modulated (FM).

 Thus, if the modulation signal has a very low frequency of, for example, several hertz, then the modulated signal
25 will be given vibrato. If the modulation signal has an audible or low frequency, then the tone quality of the reproduced sound of the modulated signal will be changed. Therefore, an FM sound source is provided by the sampler system without providing a sound source exclusively for
30 modulation. The control data FMON is written in the

register of 8 bits similarly to the afore-mentioned data KON, and the respective bits D_0 to D_7 thereof correspond to the voices #A to #H.

In the multiplier 26, the level of the output signal of the pitch converting circuit 23 is controlled in time on the basis of the control data ENV on ADSR. More specifically, when the MSB of the control data ADSR is "1", then the switch S_{3a} is connected in the illustrated state in Fig. 2, thereby performing the ADSR control. Whereas, when the MSB of the control data ADSR is "0", then the switch S_{3a} is connected in the opposite state in Fig. 2, the envelope control such as the fading and the like is performed.

For the envelop control, 5 modes such as direct designation, straight line or polygonal line fade-in and straight line or exponential fade-out can be selected by the upper 3 bits of the control data ENV. In that case, the present peak value is employed as the initial value of each mode.

In the ADSR control, the signal level is rectlineally increased only in the attack period and is exponentially decreased in the three periods such as decay period, sustain period and release period.

The durations of the fade-in period and fade-out period are properly determined for each mode in response to parameter values designated by the lower 5 bits of the control data ENV.

Similarly, the durations of the attack period and the sustain period are determined in response to parameter values designated by the upper and lower 4 bits of the control data ADSR(2). Further, the sustain level and the

durations of the decay period and the release period are determined in response to parameter values designated by 2 bits each of the control data ADSR(1).

In this embodiment, in order to reduce the number of computation, the signal level is rectilineally increased in the attack period of the ADSR mode. Alternatively, the ADSR mode is switched to the envelope mode, the polygonal line fade-in mode is made corresponding to the attack period and the exponential fade-out mode is made corresponding to the decay period, the sustain period and the release period, whereby the ADSR control can be manually performed more naturally.

When the signal output of the multiplier 26 and the envelope control input are supplied from the terminals 41a and 42a to the register RAM 12, and are rewritten at every sampling period and then a plurality of audio signals each having very different pitches are generated from the sound source data of, for example, the same musical instrument, it becomes possible to obtain an audio signal of desired envelope characteristic different from the predetermined ADSR pattern.

In the signal processing sections 50L and 50R of Fig. 3, the switches S_{4a} , S_{5a} to S_{4h} , S_{5h} are each closed by the control data EON (EON_a to EON_h) from the terminals 61a to 61h, thus the voices to be reverberated being selected. The control data EON are written in the 8-bit register as shown in the afore-mentioned table 2.

The delay times of echoes given to the respective voices from the sub-adder 51e1 are designated to be equal in the left and right channels in a range of from, for example,

0 to 250 milliseconds by the control data EDL supplied to the echo control portion 14E2 from the terminal 64.

Further, the amplitude ratio of the preceding and succeeding echoes is determined to be equal in phase in the left and right channels by the control data EFB of coded 8 bits supplied to the multiplier 57 from the terminal 67.

The control data ESA from the terminal 63 provides the upper 8 bits of the starting address of the portion used to control the echo (reverberation) in the external RAM 14.

10 The FIR filter 56 is supplied with the coefficients C_0 to C_7 of coded 8 bits from the terminal 66, whereby the pass-band characteristic of the FIR filter 56 is determined so as to provide a natural echo sound from an auditory sense standpoint.

15 The echo signal thus obtained is supplied to the multiplier 58, in which it is multiplied with the control data EVL from the terminal 68. Then, the multiplied echo signal is supplied to the adder 53, in which it is added with the main audio signal which is multiplied with the control data MVL by the multiplier 52. The control data MVL and EVL are 8 bits without codes and are mutually independent from each other. They are also independent in respect to the left and right channels.

25 Therefore, the main audio signal and the echo signal can be independently level-controlled, whereby a reproduced sound field is given full of presence as if the listeners were in the original acoustic space.

According to the electronic musical instrument of this embodiment, the non-interval component as the formant component is signal-processed by the signal processing

30

section 20A of the voice #A and the interval component is signal-processed by any one of the vacant signal processing sections 20B to 20H of the voices #B to #H, whereby the sound of musical instrument can be performed excellently by the sampler sound source including the non-interval component of seven overlapped sounds in 8 voices at maximum. Consequently, as compared with a case where 2 voices of the non-interval component and the interval component are assigned to each sound, much more multiplexed sound can be reproduced by the use of less voices.

Further, according to this embodiment, when the reverberation sound adding processing is performed by the signal processing sections 50L and 50R, the digital audio signal is delayed by the use of the vacant area of the external RAM 14 which is used to store sound source data. Therefore, the external RAM 14 is more effectively utilized and the RAM, exclusively used for delaying the digital audio signal, becomes useless. Therefore, the audio signal generating apparatus of this embodiment can be produced by the less memories and the circuit arrangement thereof can be simplified.

It is to be noted that the storage capacity, which can be determined by the delay-processing echo control sections 14E_l and 14E_r, is reduced in accordance with the increase of the storage capacity of the sound source data storage section 14V. This disadvantage can be removed by considering the total storage capacity of the sound source data storage section 14V and the echo control sections 14E_l and 14E_r may not exceed the total storage capacity of the external RAM 14 when musical software to be stored in the

sound source ROM 1 is manufactured.

Fig. 7 shows the arrangement of the computing section associated with the adding process of echo. In Fig. 7, like parts corresponding to those of Figs. 3 and 4 are marked with the same references and therefore need not be described in detail.

Referring to Fig. 7, there is shown a multiplier 71 which is supplied with outputs of the buffer RAM 55 and a Y_0 register 85 through a bus line 72. This multiplier 71 is also supplied with the output of the register RAM 12 through a bus line 73. The output of the multiplier 71 is supplied to a C register 82, and the output of the C register 82 is commonly supplied through an overflow limiter 83 and a level shifter 84 to the Y_0 register 85, a Y_1 register 86 and a Y_2 register 87. The output of the register 85 is supplied through the bus line 72 to the multiplier 71 as described above. An output of the register 86 is delivered to the outside. The output of the register 87 is supplied to the buffer RAM 55, and is also commonly supplied through a Z_4 register 88 to the register RAM 12 and the external RAM 14.

The operation of the main portion shown in Fig. 7 will be explained below.

When the sound volume of the left channel of, for example, voice #A is controlled, a left sound volume control coefficient [LVL] from the register RAM 12 and signal data x_e from the Y_0 register 85 are multiplied with each other by the multiplier 71. When the sound volume of the right channel is controlled, a right sound volume control coefficient [RVL] from the register RAM 12 and signal data x_e from the Y_0 register 85 are multiplied with each other by

the multiplier 71.

The computing sequences are expressed by the following equations (3) and (4)

$$x_e \cdot [LVL] + x_{Li-1} \rightarrow x_{Li} \quad \dots\dots (3)$$

$$5 \quad x_e \cdot [RVL] + x_{Ri-1} \rightarrow x_{Ri} \quad \dots\dots (4)$$

For other voices #B to #H, the sound volumes of the left and right channels are controlled similarly as described above.

10 According to this embodiment, the following computation is further performed in order to add the reverberation sound to the digital audio signal.

When the main sound volumes of the left and right channels are controlled, the main sound volume control coefficient [MVL] from the register RAM 12 and the signal data x_L and x_R , expressed by the equations (3) and (4) and derived from the Y_0 register 85, are multiplied by the multiplier 71. The resulting multiplied result is temporarily stored in the register 82.

20 When on the other hand the sub-sound volumes of the left and right channels are controlled, the audio data x_{LE} and x_{RE} of the voices to be selectively added with echoes are processed by the low-pass filter as described hereinbefore. Then, the thus processed audio data y_{LF} and y_{RF} are respectively multiplied with an echo feedback coefficient [EFB], added with the selected audio data x_{LE} and x_{RE} and are then fed to the external memories 14E1 and 14Er, respectively.

25 Then, the audio data y_{LF} and y_{RF} thus processed by the low-pass filter are multiplied with the echo sound volume control coefficient [EVL] and are added with the

30

afore-mentioned main sound volume data.

The computations as described above are expressed by the following equations (5) and (8).

$$Y_{LF} \cdot [EFB] + x_{LE} \longrightarrow Y_{LE} \quad \dots\dots\dots (5)$$

$$\left. \begin{array}{l} x_L \cdot [MVL] \longrightarrow C \\ Y_{LF} \cdot [EVL] + C \longrightarrow z_{7L} \end{array} \right\} \quad \dots\dots\dots (6)$$

$$Y_{RF} \cdot [EFB] + x_{RE} \longrightarrow Y_{RE} \quad \dots\dots\dots (7)$$

$$\left. \begin{array}{l} x_R \cdot [MVL] \longrightarrow C \\ Y_{RF} \cdot [EVL] + C \longrightarrow z_{7R} \end{array} \right\} \quad \dots\dots\dots (8)$$

The results computed by the equations (6) and (8) are supplied to in the buffer RAM 55 via the register 87 and stored therein.

While the present invention is applied to the sample sound source as described above, it is needless to say that the present invention can be suitably applied to desired sound sources.

As described above in detail, the echo signal delay area is provided in the vacant area of the memory in which the sound source data are stored and there is provided means for inhibiting the provision of the delay area, whereby the delay area can be prevented from being inadvertently provided in the memory at its area in which the sound source data are written. Thus, the memory exclusively for echo signal becomes unnecessary and the digital audio signal generating apparatus can be provided, which can stably and positively effect the reverberation.

A schematic block diagram forming Fig. 8 shows an arrangement of the computing section associated with the frequency modulation (FM). In Fig. 8, like parts corresponding to those of Fig. 7 are marked with the same

references and therefore need not be described in detail.

In Fig. 8, it will be seen that the multiplier 71 is supplied with the outputs of the register RAM 12 and the buffer RAM 22 through the bus line 72. This multiplier 71 is also supplied with outputs of ROMs 74 and 75 through the bus line 73. An output of a ROM 76 is supplied through a bus line 77 to an adder 81, and the output of the multiplier 71 is supplied to the adder 81. The output of the adder 81 is supplied to the C register 82. The output of the C register 82 is supplied through the bus line 77 to the adder 81, and is also commonly supplied through the overflow limiter 83 and the level shifter 84 to the Y_0 register 85, the Y_1 register 86 and Y_2 register 87. The outputs of the registers 85 and 87 are supplied to the multiplier 71 via the bus lines 72 and 73, and the output of the register 86 is fed to the outside.

The operation of the main portion shown in Fig. 8 will be explained below.

In the case of frequency modulation, assuming that y_0 is the instantaneous value (OUTX) of the audio signal of preceding voice, for example, voice #H, P is the value of pitch indicated by the P(H) and P(L) registers and that P_m is the value of pitch indicated after the frequency modulation, then the computation for frequency modulation will be expressed by the following equation (9)

$$P_m = P(1 + y_0) \quad \dots\dots (9)$$

Further, assuming that SL is the pitch data (slot value) on the RAM 22, then a pitch data (slot value) of the next sampling period will be expressed by the following equation (10)

$$SL_m = SL + P_m \quad \dots\dots (10)$$

The resultant SL_m is used to generate address data of the RAM 22 and the ROM 76 for pitch conversion computation, thereby generating the input data of the pitch converting circuit 23 and its pitch conversion filter coefficient.

In practice, the computing sequences are as follows.

In the case of FMON, a coefficient $[1/2]$ is generated from the ROM 74, and this coefficient $[1/2]$ is multiplied with the instantaneous value y_0 of the signal of voice #H from the Y_0 register 85 by the multiplier 71. The multiplied result and the constant $[1/2]$ from the ROM 76 are added to each other by the adder 81, whereby an intermediate value expressed by the following equation (11) is written in the Y_2 register 87 via the C register 82.

$$Y_0 \times 1/2 + 1/2 \longrightarrow (1 + y_0)/2 \quad \dots\dots (11)$$

Then, this intermediate value and the pitch value P from the register RAM 12 are multiplied with each other by the multiplier 71. The multiplied result and the constant $[0]$ from the ROM 76 are added to each other by the adder 81, and the computed value expressed by the following equation (12) is written in the C register 82.

$$P \times (1 + y_0)/2 + 0 \longrightarrow P_m/2 \quad \dots\dots (12)$$

Further, the slot value SL on the RAM 22 and the coefficient $[1/2]$ from the ROM 74 are multiplied with each other by the multiplier 71. The multiplied result and the computed value, expressed by the equation (12) and supplied through the bus line 77 from the register 82, are added to each other by the adder 81, and the added result is supplied through the register 82 and the like to the level shifter 84. This level shifter 84 performs the level-shifting

operation of $\times 2$, thereby supplying an output, expressed by the following equation (13), through the register 87 to the RAM 22.

$$(SL \times 1/2 + Pm/2) \times 2 \longrightarrow SLM \quad \dots\dots (13)$$

5 If the instantaneous value y_0 of the modulation signal is greater than 0 ($y_0 > 0$) for the modulated signal as shown in Fig. 9B, then the instantaneous frequency will be increased as shown in Fig. 9A. If the instantaneous value y_0 is less than 0 ($y_0 < 0$), then the instantaneous frequency
10 will be decreased as shown in Fig. 9C.

As described above, one output of the plurality of pitch converting means or the amplitude control means is supplied to other pitch converting means or amplitude control means as the control signal so as to obtain the
15 digital audio signal thus frequency-modulated or amplitude-modulated. Thus, the signal source, exclusively used for modulation, becomes unnecessary so that the digital audio signal generating apparatus of this embodiment can be simplified in construction.

20 Fig. 10 shows an example of a synchronizing circuit, by which the digital signal processing apparatus (DSP) 10 and the central processing unit (CPU) 13 can write data in and/or read data from the external RAM 14 in a time-division manner.

25 In this embodiment, as shown in Fig. 10, respective bus lines of the DSP 10 and the CPU 13 are connected to the external RAM 14 via latch circuits 10a and 13a and switches 97, 98 and 99. More specifically, address bus line, data bus line and control bus line of the DSP 10 are connected
30 through the latch circuit 10a to first fixed contacts 97a,

98a and 99a of the bus line change-over switches 97, 98 and 99. Address bus line, data bus line and control bus line of the CPU 13 are connected through the latch circuit 13a to second fixed contacts 97b, 98b and 99b of the change-over switches 97, 98 and 99. Movable contacts 97m, 98m and 99m of these switches 97, 98 and 99 are connected to address bus line, data bus line and control bus line of the external RAM 14.

A frequency signal from an oscillator 91 connected with a quartz oscillator 91a is supplied to first and second frequency dividers 92 and 93. A frequency-divided signal from the first frequency divider 92 is supplied to the DSP 10 as a clock signal and is also supplied to a time-division control circuit 94 as a control clock signal. The switches 97, 98 and 99 are changed in position in response to a switching control signal derived from the time-division control circuit 94.

A time-division signal from the time-division control circuit 94 is supplied to one input terminal of a comparator 95 and a machine cycle signal from the CPU 13 is supplied to the other input terminal of the comparator 95. The comparator 95 detects a phase difference between the switching timing of the switches 97 to 99 and the machine cycle of the CPU 13, and supplies its coincidence detected signal to one input terminal of an AND gate 96. A frequency-divided signal from the second frequency divider 93 is supplied to the other input terminal of the AND gate 96. An output signal of the AND gate 96 is supplied to the CPU 13 as a clock signal.

The operation of the synchronizing circuit of Fig. 10

will be explained with reference to timing charts forming Figs. 11A to 11D.

Let it be assumed that a clock signal (Fig. 11A), which results from frequency-dividing the frequency signal of the oscillator 91 by the first frequency divider 92, is supplied to the DSP 10. Then, the output signal of the first frequency divider 92 is supplied to the time-division control circuit 94, and this time-division control circuit 94 carries out such a time-division-control that 8 periods of the output signal from the first frequency divider 92 are taken as one period. Consequently, the time-division control circuit 94 generates as a time-division signal a signal which, as shown in Fig. 11B repeatedly goes to high level and low level at every 4 periods of the clock signal of the DSP 10.

The frequency-dividing ratio of the second frequency divider 93 is selected to be four times the frequency-dividing ratio of the first frequency divider 92, whereby the second frequency divider 93 generates a frequency signal having a frequency of $1/4$ of that of the clock signal from the DSP 10. This frequency signal is supplied to the CPU 13 as a clock signal as shown in Fig. 11C. In that event, the machine cycle of the CPU 13 becomes a signal which changes in synchronism with the time-division signal as shown in Fig. 11D. When the power switch of the digital audio signal generating apparatus is turned ON and so on, if the comparator 95 detects that the time-division signal and the machine cycle signal are inverted in phase, then the coincidence detected signal is not supplied to the AND gate 96 so that no clock signal is supplied to the CPU

13 from the AND gate 96 any more. In other words, the clock signal (Fig. 11C) of the CPU 13 loses its pulse shown by a broken line because the time-division signal and the machine cycle signal are different in phase. Thus, the machine cycle is moved by half cycle and is placed in a normal condition.

Further, the operation in which data is written in and/or read out of the external RAM 14 by the DSP 10 and the CPU 13 in a time-division manner will be explained with reference to Figs. 12A to 12G.

In this embodiment, one access time of the external RAM 14 is selected to be about 330 nanoseconds and one memory access time of the DSP 10 is selected to be about 240 nanoseconds. Further, one machine cycle of the CPU 13 is selected to be about one microsecond and about 375 nanoseconds in one machine cycle are employed as one memory access time.

Let it be assumed that the above-mentioned synchronizing circuit of Fig. 10 generates the clock signal of the DSP 10, the clock signal of the CPU 13 and the time-division signal in the normal states as shown in Figs. 12A, 12B and 12C. Then, in that event, each memory access period M_C of the CPU 13 is provided in the second half portion of one machine cycle S as shown in Fig. 12D. Then, as shown in Fig. 12E, two memory access periods M_{D1} and M_{D2} of the DSP 10 are provided in the first half portion of one machine cycle S .

On the other hand, one access time of the external RAM 14 is about 330 nanoseconds so that, as shown in Fig. 12G, three access periods M_{D1}' , M_{D2}' and M_C' each having equal

interval are provided in one machine cycle S as shown in Fig. 12G.

While the access periods of the DSP 10, CPU 13 and the external RAM 14 are not coincident as described above, according to this embodiment, the above-mentioned displacement of the access periods can be properly adjusted by the switching control of the switches 97 to 99 by the time-division control circuit 94 and the latch operations of the latch circuits 10a and 13a. To be more concrete, the time-division control circuit 94 generates such a switching control signal shown in Fig. 12F that on the basis of the time-division signal shown in Fig. 12C, the movable contacts 97m, 98m and 99m of the switches 97, 98 and 99 are connected to the first fixed contacts 97a, 98a and 99a during the first access period M_{D1}' and the second access period M_{D2}' of the external RAM 14 and that the movable contacts 97m, 98m and 99m of the switches 97, 98 and 99 are connected to the second fixed contacts 97b, 98b and 99b during the third access period M_C' . The latch circuit 10a connected to the DSP 10 is adapted to hold the signals supplied through the bus lines during the first access period M_{D1} of the DSP 10 until the first access period M_{D1}' of the external RAM 14 is ended, and is also adapted to hold the signals supplied through the bus lines during the second access period M_{D2} of the DSP 10 till the second access period M_{D2}' of the external RAM 14 is ended. In like a manner, the latch circuit 13a connected to the CPU 13 is adapted to hold the signals supplied through the bus lines during the access period M_C of the CPU 13 until the third access period M_C' of the external RAM 14 is ended. The latch operations of the

latch circuits 10a and 13a are controlled by, for example, the CPU 13.

As described above, the DSP 10 and the CPU 13 can share the single external RAM 14 in a time-division manner, whereby the external RAM 14 can be utilized more effectively. Thus, the external RAM 14 for processing the data of the DSP 10 and the CPU 13 can be constructed by less memories. Further, the different access periods of the DSP 10 and the CPU 13 are adjusted to be equal and in this embodiment, one accessing is performed at every period of about 330 nanoseconds. Therefore, the memory apparatus of relative low accessing speed, which can be relatively inexpensive, can be employed as the external RAM 14.

While the above-mentioned embodiment utilizes the combination of the DSP 10 of relatively high accessing speed and the CPU 13 relative low accessing speed, this invention is not limited to the above-mentioned combination and the access periods can be properly adjusted in accordance with the access speed of the combination of the data executing means and the memory.

Furthermore, according to the digital audio signal generating apparatus of this embodiment, since one external memory is commonly utilized by two sets of data executing means, the memory can be utilized more effectively and the memory can be saved.

Attention is directed to the following copending applications which were divided from the present application and describe and claim aspects of the above described apparatus.

5 British Patent Application No [9304331.3]
(Publication No.) describes and claims a digital
audio signal generating apparatus in which the output of one
of a number of pitch converting means is used as a control
signal input to another of them to produce a frequency
10 modulated digital audio signal.

 British Patent Application No [9304329.7]
(Publication No.) describes and claims a digital
audio signal generating apparatus in which the output of one
of a number of amplitude control means is used as a control
15 signal input to another of them to produce an amplitude
modulated digital audio signal.

 British Patent Application No [9304330.5]
(Publication No.) describes and claims a data
processing circuit in which two executing means, a
20 microprocessor and a digital signal processor access a
shared memory in a time-division multiplex fashion.

CLAIMS

1. An apparatus for generating a digital audio signal comprising:

- 5 (a) memory means for storing a digital audio signal;
(b) control means for controlling a reading of said digital audio signal from said memory means;
(c) signal processing means for performing a predetermined synthesis of said digital audio signal read by
10 said control means so as to produce, on reproduction of the signal, a sound in a desired voice.

(d) temporary memory means used in the synthesis in said control means and said signal processing means; and

- (e) means for setting a delay area in a vacant area
15 of said temporary memory means so as to perform a delay processing, when a reverberation signal is added to the digital audio signal processed by the synthesis in said signal processing means.

- 20 2. An apparatus for generating a digital audio signal according to claim 1, further comprising means for inhibiting an operation of the delay area setting means, wherein said vacant area can be prevented from being inadvertently provided in the memory means at its area in
25 which the sound source data are written.



3. An apparatus for generating a digital audio signal according to claim 1 or 2 in which a plurality of digital audio signals are generated using respective pitch converting means, comprising means for supplying the output
5 of one of said pitch converting means to another of said pitch converting means as a control signal, whereby a frequency-modulated digital audio signal is generated from said other pitch converting means.

10 4. An apparatus for generating a digital audio signal according to claim 1, 2 or 3 in which a plurality of digital audio signals are generated using respective amplitude control means, comprising means for supplying the output of
15 one of said amplitude control means to another of said amplitude control means as a control signal, whereby an amplitude-modulated digital audio signal is generated from said other amplitude control means.

5. Apparatus according to any one of the preceding
20 claims, and including data processing apparatus comprising:-

(1) first executing means having a first execution cycle to execute its operation in accordance with said cycle and for writing in and reading out data from a common memory;

25 (2) second executing means having a second executing cycle different from said first execution cycle to execute



its operation in accordance with said second cycle and for writing in and reading out data from said common memory;

(3) selecting means for selectively connecting one of said first and second executing means to said common memory so that data is written in and/or read from said common memory by one of said first and second executing means;

(4) control means for controlling said selecting means so that data can be written in and/or read from said common memory by said second executing means during a non-access period in which data is not written in and/or read from said common memory by said first executing means; and

(5) holding means provided between said second executing means and said common memory for holding data so that a period in which said second executing means writes in and/or reads data from said common memory substantially coincides with said non-access period.

6. Apparatus according to claim 5, wherein one of the first and second executing means is a digital signal processor.

7. Apparatus for generating a digital audio signal constructed and arranged to operate substantially as hereinbefore described with reference to and as illustrated in the accompanying drawings.
