

Description

The invention relates to a device for carrying out a therapeutic treatment, such as the removal of warts, on a part of the skin of a human or animal body by local freezing, said device comprising a spray can for accomodating a liquid refrigerant that boils within the temperature range of 0°C to -50°C , a pressure reducing and shut off valve to be operated with a finger on an end wall of the spray can, said valve being provided with a supply tube extending into the liquid phase of the refrigerant and with a discharge tube connected at a first end to an outlet of the valve.

A device of this type is known from GB-A-1 163 573. This device comprises an outer guard sleeve having extending within it an inner discharge tube of substantially smaller diameter connected at one end to the release valve of the spray can and terminating with a free end short of a free end of said guard sleeve, said guard sleeve having a vent aperture leading to the atmosphere upstream of the free end of the discharge tube. With such a device a liquid-tight seal around the mouth of the guard sleeve can be ensured.

It is generally known to carry out a therapeutic treatment, such as the removal of warts, on a part of the human or animal body by local freezing, the place to be treated being treated by means of a cotton wool bud or similar plug of absorbent material which has been cooled by means of a liquid refrigerant, which is present as liquid in the pressurised container and vaporises in escaping, at a temperature of less than 0°C , e.g. liquid nitrogen which has a boiling point of -180°C . The cotton bud is immersed in the liquid nitrogen and then brought into contact with the place to be treated.

This, as it were, classical use of liquid nitrogen is subject to a number of practical drawbacks under clinical conditions. The availability and shelflife of liquid nitrogen is subject to limitations. The liquid nitrogen is made available in special double-walled, thermally insulated containers which are usually available only for a short time, usually only one day, for the treatment of warts. The general practitioner therefore has to arrange a special surgery.

For the effective removal of undesirable tissues, such as warts, it is necessary to destroy the cell structure by freezing within a very short period of time and, in view of its very low boiling point under atmospheric conditions, liquid nitrogen is in fact particularly suitable for this purpose.

The object of the invention is therefore to provide a device which offers a number of advantages over the known device and lacks the draw-backs associated therewith.

According to the invention, this object is achieved in the general sense, in that in a device as described in the preamble, the second end of the discharge tube is provided with a cotton wool bud which is present downstream an outlet of the second end of the tube and around the outer surface of the second end, so that outward flow of the refrigerant takes place via the cotton wool bud when the valve is operated.

According to the invention, the refrigerant used is preferably a medium which is liquid even with a very low excess pressure and which is therefore kept in the liquid phase by its own gas phase without special cooling facilities, i.e. the major part of the volume of the reservoir contains liquid and a small quantity of gas, the liquid phase reducing to the extent that use occurs and the volume released being filled up by the gas phase. The outward flow takes place via the cotton wool bud on operating the valve. In this manner, the effect is obtained that refrigerants which have a boiling point is lower than 0°C rapidly bring about cell freezing as a result of further pressure reduction in the cotton wool bud and as a result of the large internal surface of the cotton wool bud which cause a lower temperature (measured at the cotton wool bud) than the boiling point of the refrigerant and are amply sufficient to bring about cell freezing in a short time.

Consideration must be given here to refrigerants which boil at a temperature situated between 0°C and -50°C . In particular, these are refrigerants which boil between -0.5°C and -43°C . As an example of a refrigerant with a boiling point of -0.5°C , mention may be made of n-butane; as an example of a refrigerant having a boiling point of approximately -43°C , mention may be made of propane.

Suitable refrigerants might be halogenated hydrocarbons, such as tetrafluoromethane, trifluoromethane, monochlorotrifluoromethane, hexafluoroethane, monobromotrifluoromethane, monochlorodifluoromethane, monochloropentafluoroethane, dichlorodifluoromethane, 1,2-dichloro-, 1,1,2,2-tetrafluoroethane, trichloromonofluoromethane, 1,1,2-trichloro-, 1,2,2-trifluoroethane and 1,1-difluoroethane, propane, n-butane, and isobutane. These are, however, often environmentally harmful. Dimethyl ether is to be preferred since it is environmentally acceptable.

The pressure of the gas phase is preferably kept below 5 bar, preferably even little more than atmospheric pressure.

With the device according to the invention it is therefore possible in a very simple manner and in a manner which can be immediately available to immediately generate very low temperatures which are considerably below the boiling point of the particular refrigerant itself.

The device can be implemented in various manners.

According to the invention, said device consists of a spray can containing the refrigerant, a pressure-reducing and shut-off valve to be operated with a finger on an end wall of the spray can with a supply tube extending into the liquid phase and a discharge tube, connecting to the discharge opening of the valve, on the end of which the cotton wool bud is situated. Spray cans are easily kept in stock without special facilities being necessary so that the practitioner can use the treatment at any instant and is no longer dependent on the delivery of a container filled with liquid nitrogen. This means an important reduction in costs and, consequently, also that the treatment can be carried out more easily and more cheaply.

Attention is drawn to the fact that spray cans containing a refrigerant are known per se, for example for use in electronics. Spray cans which deliver a jet of refrigerant are, however, less suitable for medical treatments since the jet is difficult to aim satisfactorily and the refrigerant splutters in all directions at the place to be treated, as a result of which unintended effects are obtained.

Preferably, the valve has a low flow rate capacity of not more than 60 ml/minute, preferably 30 ml/minute, so that when the knob of the valve is pressed in, a measured quantity of refrigerant can easily be released.

Attention is drawn to the fact that it is known from the laid-open Dutch Patent Application 7,308,008 that use is made of a liquid refrigerant with a low boiling point for carrying out cryosurgical treatments such as the removal of an eye lens affected by cataract in cataract operations making use of adhesion to the rod-shaped object which is brought to a low temperature by means of the refrigerant and which is brought into contact with the place to be treated, such as the eye lens. In this device, which is known per se and of small construction and which may be regarded as a throwaway article, the liquid refrigerant is also present in a container and flows out via a cotton wool plug on operating a valve. Said plug acts, however, as a means for the absorption of coolant liquid and not for the treatment. The refrigerant is used for cooling a rod which conducts heat rapidly and it is this rod which is used after cooling for carrying out the treatment. Said rod is situated at the end of the device opposite the plug.

Furthermore, it is known from German Offenlegungsschrift 3,340,991 that dimethyl ether is used as propellant but also as solvent in spray cans for spraying-in of drugs to treat disorders of the air passages in the human or animal mouth, nose and throat cavity. This does not involve the freezing of cells but the application of a drug.

The invention will now be explained in more detail with reference to the drawing and with reference to examples.

The drawing shows a spray can 1 with an end wall 2 in which a pressure-reducing shut-off valve, not shown, and which is concealed from the eye by a covering cap 3 and can be operated if the covering cap is removed in a known manner and as is usual for spray cans. The spray can 1 contains a liquid refrigerant 4, the level of which is indicated at 5 and above which the gas phase 6 is situated. The valve extends into the liquid phase 4 of the refrigerant by means of a hose of flexible tubing 7. The debouchment of the valve contains a tube 8 into which a thinner tube 9 or narrow pipe is inserted and secured, the outlet opening of which is surrounded by a cotton wool plug 11.

On operating the valve, a quantity of liquid refrigerant flows via hose 7 and the valve through the tubes 8, 9 into the cotton wool plug 11, distributes itself there immediately over the large surface of the plug, vaporises and cools said cotton wool plug 11 to a very low temperature.

Examples:

Mention is made below of a number of refrigerants, the latter being followed by their normal boiling point and the latter by the lowest temperature which it was possible to measure after 30 seconds at the cotton wool bud as a result of activating the expanding refrigerant.

Refrigerant	Boiling point	Effective treatment temperature
dimethyl ether	-24.8 °C	-45 °C
10 difluorodichloro- methane	-29.8 °C	-48 °C
n-butane	- 0.5 °C	-29 °C
isobutane	-11.7 °C	-35 °C
15 propane	-42.1 °C	-50 °C

Claims

20

1. Device for carrying out a therapeutic treatment, such as the removal of warts, on a part of the skin of a human or animal body by local freezing, said device comprising a spray can (1) containing a liquid refrigerant that boils within the temperature range of 0° to -50 °C (4), a pressure reducing and shut off valve to be operated with a finger on an end wall (2) of the spray can (1), said valve being provided with a supply tube (7) extending into the liquid phase (4) of the refrigerant and with a discharge tube (9) connected at a first end to an outlet of the valve, characterized in that the second end of the discharge tube (9) is provided with a cotton wool bud (11) which is present downstream an outlet (10) of the second end of the tube (9) and around the outer surface of the second end, so that outward flow of the refrigerant takes place via the cotton wool bud when the valve is operated.
2. Device as claimed in claim 1, characterized in that the valve has a low flow rate capability of not more than 60 ml per minute, preferably 30 ml per minute.
3. Device as claimed in claim 1 or 2, characterized in that the pressure of the gas phase (6) of the refrigerant (4) in the spray can (1) is less than 5 bar.

30

35

Patentansprüche

1. Vorrichtung zur Durchführung einer therapeutischen Behandlung, wie die Entfernung von Warzen, auf einem Teil der Haut eines menschlichen oder tierischen Körpers durch lokales Gefrieren, wobei diese Vorrichtung umfasst: einen Sprühbehälter (1), der eine im Temperaturbereich von 0° bis -50 °C siedende Kühlflüssigkeit (4) enthält, ein Ventil zur Druckverminderung und zum Schliessen, das mit einem Finger an einer Endwandung (2) des Sprühbehälters (1) zu betätigen ist, wobei dieses Ventil mit einem sich in die flüssige Phase (4) des Kühlmittels erstreckenden Zuleitungsrohr (7) und einem an einem ersten Ende mit einem Auslass des Ventils verbundenen Ausflussrohr (9) versehen ist, dadurch gekennzeichnet, dass das zweite Ende des Ableitungsrohrs (9) mit einem Wattebausch versehen ist, welche stromabwärts einer Auslassöffnung (10) des zweiten Endes des Rohre (9) und um die äussere Fläche des zweiten Endes angeordnet ist, so dass der Fluss des Kühlmittels nach aussen durch den Wattebausch hindurch stattfindet, wenn das Ventil betätigt wird.
2. Vorrichtung nach Anspruch 1, dadurch gekennzeichnet, dass das Ventil eine niedrige Durchflusskapazität von nicht mehr als 60 ml pro Minute und vorzugsweise 30 ml pro Minute aufweist
3. Vorrichtung nach Anspruch 1 oder 2, dadurch gekennzeichnet, dass der Druck der Gasphase (6) des Kühlmittels (4) im Sprühbehälter (1) weniger als 5 bar beträgt.

50

55



Refrigerant	Boiling point	Effective treatment temperature
-------------	---------------	---------------------------------

5

dimethyl ether	-24.8 °C	-45 °C
10 difluorodichloro-		
methane	-29.8 °C	-48 °C
n-butane	- 0.5 °C	-29 °C
isobutane	-11.7 °C	-35 °C
15 propane	-42.1 °C	-50 °C

Claims

20

1. Device for carrying out a therapeutic treatment, such as the removal of warts, on a part of the skin of a human or animal body by local freezing, said device comprising a spray can (1) containing a liquid refrigerant that boils within the temperature range of 0° to -50 °C (4), a pressure reducing and shut off valve to be operated with a finger on an end wall (2) of the spray can (1), said valve being provided with a supply tube (7) extending into the liquid phase (4) of the refrigerant and with a discharge tube (9) connected at a first end to an outlet of the valve, characterized in that the second end of the discharge tube (9) is provided with a cotton wool bud (11) which is present downstream an outlet (10) of the second end of the tube (9) and around the outer surface of the second end, so that outward flow of the refrigerant takes place via the cotton wool bud when the valve is operated.

30

2. Device as claimed in claim 1, characterized in that the valve has a low flow rate capability of not more than 60 ml per minute, preferably 30 ml per minute.

35

3. Device as claimed in claim 1 or 2, characterized in that the pressure of the gas phase (6) of the refrigerant (4) in the spray can (1) is less than 5 bar.

Patentansprüche

40

1. Vorrichtung zur Durchführung einer therapeutischen Behandlung, wie die Entfernung von Warzen, auf einem Teil der Haut eines menschlichen oder tierischen Körpers durch lokales Gefrieren, wobei diese Vorrichtung umfasst: einen Sprühbehälter (1), der eine im Temperaturbereich von 0° bis -50 °C siedende Kühlflüssigkeit (4) enthält, ein Ventil zur Druckverminderung und zum Schliessen, das mit einem Finger an einer Endwandung (2) des Sprühbehälters (1) zu betätigen ist, wobei dieses Ventil mit einem sich in die flüssige Phase (4) des Kühlmittels erstreckenden Zuleitungsrohr (7) und einem an einem ersten Ende mit einem Auslass des Ventils verbundenen Ausflussrohr (9) versehen ist, dadurch gekennzeichnet, dass das zweite Ende des Ableitungsrohrs (9) mit einem Wattebausch versehen ist, welche stromabwärts einer Auslassöffnung (10) des zweiten Endes des Rohre (9) und um die äussere Fläche des zweiten Endes angeordnet ist, so dass der Fluss des Kühlmittels nach aussen durch den Wattebausch hindurch stattfindet, wenn das Ventil betätigt wird.

50

2. Vorrichtung nach Anspruch 1, dadurch gekennzeichnet, dass das Ventil eine niedrige Durchflusskapazität von nicht mehr als 60 ml pro Minute und vorzugsweise 30 ml pro Minute aufweist

55

3. Vorrichtung nach Anspruch 1 oder 2, dadurch gekennzeichnet, dass der Druck der Gasphase (6) des Kühlmittels (4) im Sprühbehälter (1) weniger als 5 bar beträgt.

**Revendications**

- 5 1. Dispositif pour procéder à un traitement thérapeutique, tel que l'enlèvement de verrues, sur une partie de la peau d'un corps humain ou animal par congélation locale, ce dispositif comportant un récipient pulvérisateur (1) qui contient un liquide réfrigérant qui bout dans la gamme de températures de 0° à -50°C, une vanne de réduction de pression et de fermeture à actionner avec un doigt sur une paroi terminale (2) du récipient pulvérisateur (1), cette vanne étant pourvue d'un tube d'amenée (7) qui s'étend dans la phase liquide (4) du réfrigérant et d'un tube de décharge (9) relié en une première
- 10 (9) est pourvue d'un tampon de coton (11) qui est placé en aval d'un orifice de sortie (10) de la deuxième extrémité du tube (9) et autour de la surface extérieure de la deuxième extrémité, de sorte que l'écoulement du réfrigérant vers l'extérieur a lieu au travers du tampon de coton lorsque la vanne est actionnée.
- 15 2. Dispositif selon la revendication 1, caractérisé en ce que la vanne présente une faible capacité d'écoulement de moins de 60 ml par minute et de préférence de 30 ml par minute.
- 20 3. Dispositif selon la revendication 1 ou 2, caractérisé en ce que la pression de la phase gazeuse (6) du réfrigérant (4) dans le récipient pulvérisateur (1) vaut moins de 5 bar.

20

25

30

35

40

45

50

55