

Description

This invention relates generally to the field of controllers suitable for use with miniature personal communications devices, and more particularly to a switch function controller for use with digital electronic watches which incorporate a radio paging receiver.

The small physical size and form factor of wrist worn digital electronic watches having LCD or LED displays makes it very difficult to provide individual control switches for each and every function which can be provided in the watches. As a result, watch manufacturers have had to devote considerable effort to minimize the number of control switches required to set and control the watch functions. This has resulted in providing only a limited number of control switches providing multiple function capability on the watches. Selection and control of all of the available functions requires sequences of control switch operations to be performed which are not always readily apparent, even with the identification of the switch functions on the watch case.

When a radio paging receiver is also included in the same case as the watch, the problem is further complicated. This is due to the large number of distinctly different functions which are required for control of a paging receiver. It has been the experience of paging receiver manufacturers that these functions must be clearly identified to avoid confusion or the loss of messages due to improper operation of the controls by the user. Device case size limits simply adding additional control switches for the paging receiver functions. Multiplexing control of the additional functions required for the paging receiver functions with those of the watch functions using the same control switches can create confusion in the operation of the watch and paging receiver functions. Other problems, such as when to provide operation of the paging receiver or the watch functions by the control switches, how long and how often, and how to handle information delivered by the paging receiver have not been but need to be addressed.

It is an object of the present invention to provide an apparatus suitable for controlling the operation of a electronic watch and a paging receiver incorporated in a single wrist worn device.

It is a further object of the invention to provide an apparatus which minimizes the number of control switches required to operate the watch and paging receiver functions.

It is a further object of the invention to provide an apparatus which clearly identifies the functions provided by the control switches.

It is a further object of the invention to provide an apparatus which automatically provides operation of the paging receiver functions when control of these functions are required.

It is a further object of the invention to provide an

apparatus which automatically provides operation of the watch functions by the control switches, when not required to control the paging receiver functions.

It is a further object of the invention to provide an apparatus which allows manual selection of either watch functions or paging receiver functions.

It is a further object of the invention to provide an apparatus which controls the display of time information and message information under the control of the control switch functions.

A switch control interface arrangement is provided for a device normally generating and displaying time information, and also capable of receiving transmitted coded message signals. Switches for controlling the setting and display of time are provided. The device case is marked with permanent indicia positionally adjacent the switches for indicating the switch functions. The device includes a receiver circuit for receiving and decoding the transmitted coded message signals to provide control signals and information. A switch controller is coupled to the time generating circuit and to the receiver circuit and enables control of either the time generating circuit and receiver circuit by the switches. Control of the receiver circuit by the switches is automatically obtained when the control signals are derived in the receiver circuit.

In another embodiment of the present invention a display control interface arrangement is provided for a device normally generating and displaying time information, and also capable of receiving transmitted coded message signals. Switches for controlling the setting and display of time are provided. The device case is marked with permanent indicia positionally adjacent the switches for indicating the switch functions. The device includes a receiver circuit for receiving and decoding the transmitted coded message signals to provide control signals and message information. An input steering circuit is coupled to the time generating circuit and to the receiver circuit and enables control of either the time generating circuit or the receiver circuit by the switches. Outputs from the time generating circuit and the receiver circuit are coupled to an information selector circuit which selects either time or message information depending upon whether the time generating circuit or the receiver circuit is selected by the input steering circuit. Control of the receiver circuit and display of message information by the switches is automatically obtained when the control signals are derived in the receiver circuit.

In yet another embodiment of the present invention a display control interface arrangement is provided for a wrist worn device normally generating and displaying time information, and also capable of receiving transmitted coded message signals. The transmitted coded message signal include selective call signalling and message information. Switches for

controlling the setting and display of time are provided. The device case is marked with permanent indicia positionally adjacent the switches for indicating the switch functions. The device includes a receiver circuit for receiving and demodulating the coded message signals including the selective call signalling and message information. An identification storage element stores predetermined device identification information. A decoder compares the selective call signalling with the predetermined device identification information to provide control signals when the selective call signalling matches the predetermined device identification information. An input steering circuit is coupled to the time generating circuit and to the receiver circuit and enables control of either the time generating circuit or the receiver circuit by the switches. Outputs from the time generating circuit and the receiver circuit are coupled to an information selector circuit which selects either time or message information depending upon whether the time generating circuit or the receiver circuit is selected by the input steering circuit. The information selector circuit also electronically selects indicia displayed positionally adjacent the switches indicating the new switch functions which are also enabled when the receiver circuit is selected by the input steering circuit. Control of the receiver circuit by the switches, display of the message information, and display of indicia indicating new switch functions, is automatically obtained when the control signals are derived in the receiver circuit.

These and other objects and advantages of the present invention will become apparent to those skilled in the art upon consideration of the following description and accompanying drawings of the invention.

The features of the invention which are believed to be novel are set forth with particularity in the appended claims. The invention itself, together with further objects and advantages thereof, may be best understood by reference to the following description when taken in conjunction with the accompanying drawings, in the several figures of which like reference numerals identify identical elements, in which :

FIG. 1 is a simplified functional block diagram of the apparatus of the present invention.

FIG. 2 is an functional block diagram of the apparatus of the present invention illustrating the details of the functional blocks shown in FIG. 1.

FIGS. 3A to 3H are pictorial diagrams of the display portion of the device illustrating the switch control placement and indicia provided to control the operation of the apparatus of the present invention.

FIGS. 4A to 4D are flow diagrams illustrating the operation of the apparatus of the present invention.

FIGS. 5A to 5B are flow diagrams illustrating the operation of an alternate embodiment of the

apparatus of the present invention.

FIG. 6 is a functional block diagram of an embodiment of the present invention utilizing a microprocessor for controlling the operation of the apparatus.

Reference is now directed to the drawings, and in particular to FIG. 1, which represents a simplified functional block diagram for a device 10 constructed in accordance with the present invention. An electronic watch circuit 20, which is coupled to display controller 16, provides time information such as time and day and date, normally displayed on display 22. An antenna 12 is coupled to a paging receiver 14, which is also coupled to display controller 16. Paging receiver 14 receives transmitted coded message signals and displays the received message information on display 22 in place of the time. It will be appreciated by one skilled in the art that the time information being generated and displayed by watch circuit 20 may include other functions such as elapsed time, interval timer, and alarm, just to name a few. Control of watch circuit 20 and paging receiver 14 is provided by user control inputs 18, which couple to display controller 16. As will be described in greater detail later, control inputs 18 are intended to represent device switches 40, 42 and 44 illustrated in FIG. 3A.

In normal operation, the watch-pager arrangement of FIG. 1 functions like a watch with the present time displayed on display 22. The device switches, which are the control inputs 18, provide control of the watch functions through display controller 16. However, when transmitted coded message signals, or pages, are received and decoded by paging receiver 14, in a manner well known to one skilled in the art, a control signal is generated by paging receiver 14 which is coupled to display controller 16 causing the watch-pager arrangement to function as a display pager. This is effected by changing both the information displayed and the normal function of the device switches. Thus, immediately after the page has been received, the display indicates a message was received. Paging receiver 14 normally includes a memory for storage of the message information. Readout of the message information stored in the memory is then controllable by the same device switches normally used to control the watch functions.

Reference is next directed to FIG. 2 which shows a more detailed block diagram of the present invention. Display controller 16 is shown to consist of a switch interface controller 34 used for steering control inputs 18 to the appropriate section, either the watch, or time keeping circuit 20 or paging receiver 14. Implementations for watch circuit 20 and paging receiver 14 are separately well known to those skilled in the art, and will only be briefly described later. Outputs from watch circuit 20 and paging receiver 14 provide serial time and message information, respectively, to display selector 38. Display selector 38 is coupled to

switch interface controller 34 and selects time or message information for display depending upon which section of the watch-pager device is being controlled by switch interface controller 34. The information selected by display selector 38 is provided to display interface circuit 40 which, in the preferred embodiment of the present invention described, includes a serial driver circuit, such as the MC145000 master and MC145001 slave, serial multiplexed LCD driver circuits manufactured by Motorola, which is suitable for driving display 22. Display 22 comprises an LCD display suitable for displaying both time and message information, such as multiplexed LCD displays available from Seiko.

Paging receiver 14 consists of an antenna 12 coupled to receiver circuit 24 as shown in FIG. 2. Receiver 24 receives the transmitted coded message signals which normally consist of transmitted selective call signalling information and transmitted message information in a manner well known in the art. The transmitted coded message signals are demodulated in receiver 24, again in a manner well known to one skilled in the art, and provided at the output of receiver 24 as a stream of binary information representing demodulated coded message signals 25, consisting of selective call signalling information 25a and message information 25b. The output of receiver 24 is coupled to a decoder circuit 28. Decoder 28 has a second input from code memory, or code plug 26. Code plug 26 stores predetermined address information consisting of one or more addresses to which paging receiver 14 will respond. The demodulated selective call signalling information 25a is compared with the addresses stored in code plug 26 by decoder 28. If the selective call signalling information 25a matches one of the stored addresses, a control signal 29 is generated. Control signal 29 is coupled to memory 30 to effect any subsequently received message information 25b to be stored. It will be appreciated by one skilled in the art, that memory 30 may be capable of storing multiple messages received at different times. Control signal 29 also couples to switch interface controller 34 to effect control of paging receiver 14 by the device switches. After the message information 25b has been stored, decoder 28 generates an alerting signal 37 which is routed to display selector 38. Display selector 38 sends the alerting signal 37 to the alerting circuit 32. Alerting circuit 32 normally delivers an audible alert, although other forms a alert such as tactile could also be delivered. It will be appreciated the alerting circuit 32 may deliver alerting signals derived from watch circuit 20 during normal operation, such as when an alarm signals are generated by watch circuit 20.

Switch interface controller 34 also couples to timing generator circuit 36 as shown in FIG. 2. Timing generator 36 controls the time duration during which the received message information is displayed on display 22.

When switch interface controller 34 selects paging receiver 14 in response to control signal 29, a predetermined display time interval such as eight seconds is generated. Upon completion of the display time interval, timing generator 36 generates an output to cause switch interface controller 34 to again select the watch functions. In the preferred embodiment of the present invention, timing generator 36 also provides an output which couples to display selector 38 to provide the clock signals necessary to drive the serial display driver circuitry in display interface 40 which is subsequently coupled to display 22.

As described earlier, control inputs 18 correspond to the device switches 40, 42 and 44. To better understand their operation reference is made to FIG. 3A where the device switches are shown to include a display switch 40, a set switch 42 and a mode switch 44. The switch functions are permanently marked on the case of the watch-pager device and indicate functions controlled by the switches when in the normal watch, or time display mode. In the preferred embodiment of the present invention, operation of watch circuit 20 functions are described as follows. Actuation of display switch 40 while time information, such as present time 64 and AM/PM indicator 62 are being displayed on display 22 as shown in FIG. 3A causes day and date information 66 to be displayed, as shown in FIG. 3B, for a period of time, such as for a two second interval. Additional operations, such as display of seconds, are also controlled by the display switch 40. These time display operations are described in the flowcharts shown in FIGS. 4A and 4B to be described in greater detail later. Actuation of set switch 42 will place watch circuit 20 in the time setting mode as described in the flowchart shown in FIG. 4A, also to be described in greater detail later. Actuation of mode switch 44 will select control of paging receiver 14 by the device switches when time information is being displayed, to be described in detail with the flowchart shown in FIG. 4B.

When the paging functions are selected as previously described, display selector 38 changes from the time display shown in FIG. 3A to a message display such as that shown in FIG. 3C. As illustrated in FIG. 3C, in the preferred embodiment of the present invention, the received message information 25b stored in memory 30 is not immediately displayed, but rather the text message, "PAGE" 68, is displayed indicating the presence of a stored received message. A visual annunciator 70 consisting of five alphanumeric characters, "R", "1", "2", "3", and "4" provides information on the number of received messages currently stored in memory 30. All annunciators are shown in FIG. 3C for the sake of clarity. Normally when no messages have been stored, only the "R" indicator is displayed and cursor 72 would be positioned beneath the "R" indicator. When a first message is received, only the "R" and the "1" indicators are displayed with cur-

cursor 72 positioned immediately beneath the "1" indicator as shown in FIG. 3D. Cursor 72 remains beneath the current unread memory position indicator until the received message has been read, at which time cursor 72 would again shift to beneath the "R" indicator. Additional messages are indicated by the "2", "3" and "4" indicators. The preferred embodiment of the present invention described provides an indication for four received messages to be stored and identified by annunciator 70. The method for storing and displaying the received unread messages is described in detail in U.S. Patent Number 4,385,295 to Willard, et al, entitled "Pager with Visible Display Indicating Unread Messages" which is assigned to the assignee of the present invention, the disclosure of which is hereby incorporated for reference herein. It should be noted that other methods for displaying the number of received messages which are stored may be employed without departing from the scope or spirit of the present invention.

When the paging functions are selected by switch interface controller 34, switch labels indicating the new switch functions are also displayed. The new labels are provided by activating the appropriate portions of display 22 and include the labels "Reset" 46, "Time" 48 and "Hold On" 50 as shown in FIG. 3C. Display switch 40, used normally to control the display of time information as previously described, functions as a "Reset" switch 46 when paging receiver 14 is selected by switch interface controller 34. When "Reset" switch 46 is actuated, the audible alert generated by decoder 28 in response to receiving a page is suspended and the stored received message 76 is displayed as shown in FIG. 3E. The label identifying display switch 40 next changes to indicate a different switch function such as "Read" 52, also shown in FIG. 3E, after the audible alert has been reset and the received message has been initially read and displayed. Thus the preferred embodiment of the present invention provides multiple displayable labels for each switch, to clearly indicate the current switch function provided by that switch when multiple functions are provided by the switch. FIGS. 3C and 3E illustrate by example the multiple labels "Reset" 46 and "Read" 52 defining separate functions controlled by display switch 40.

Set switch 42, shown in FIG. 3E normally used to control the setting the time, functions as the "Hold On" switch 50 when paging receiver 14 is selected by switch interface controller 34. The "Hold on" switch 50 allows freezing the received message 76 on display 22 for as long as required by suspending timing generator 36 operation. After "Hold On" switch 50 has been actuated, the switch function changes to "Hold Off" switch 54 as shown in FIG. 3F. Depressing the "Hold Off" switch 54 restarts timing generator 36, thereby returning operation to the watch mode when the display time interval has elapsed.

Mode switch 44, shown in FIGS. 3A to 3H, used

to select the paging receiver function when present time is displayed, is used to manually reselect the normal watch or "Time" 48 function prior to timing generator 36 automatically restoring the time functions.

While the preferred embodiment of the present invention illustrates only a single twelve digit display, such as shown in FIG. 3E, it will be appreciated by one skilled in the art that longer messages may be transmitted, stored and displayed. One method of handling longer messages is shown in FIG. 3G. A message continuation annunciator 78 is displayed indicating further information has been received and the information may be read by actuating display switch 40 providing the "Read" 52 function to read out the next segment of the received message. Other methods, such as the use of multiple line displays can also be employed without departing from the scope or spirit of the present invention described herein.

FIG. 3H illustrates the information displayed when the paging receiver function is manually selected using mode switch 44 when no pages have been received and stored. Text indicating "No Page" 80 is generated by decoder 28 and displayed as shown. It should also be observed that the switch functions are changed and the new labels are displayed as a result of manually selecting the message display mode. The normal time display may be reselected by actuating mode switch 44 which provides selecting the "Time" 48 function.

Many such time set/display protocols are known, but the following is a description of that employed in the preferred embodiment of the present invention. Reference is now directed to the flowchart shown in FIG. 4A which describes the procedure to set the time for the watch-pager device 10. To enter the set time procedure at block 100, set switch 42 is actuated as shown at block 166 of the flowchart shown in FIG. 4C which describes the general operation of the watch-pager device 10 to be described in detail later. The display alternates between time and day/date displays as shown at block 102 in FIG. A. When display switch 40 is actuated at block 104, the seconds are displayed as shown at block 106. The seconds display shown at block 106 continues until display switch 40 is again actuated as shown at block 108, thereby returning the display to the alternating mode shown at block 102. If display switch 40 is not actuated as shown at block 104, and if set switch 42 is not actuated as shown at block 110, the display continues to alternate time and day/date information shown at block 102.

When set switch 42 is actuated as shown at block 110, the month is displayed as shown at block 112 thereby allowing the month to be set. When display switch 40 is actuated as shown at block 114 the month displayed is advanced to the next month as shown at block 116. If display switch 40 is not actuated as

shown at block 114 and set switch 42 is not actuated as shown at block 118, the month displayed continues as shown at block 112.

When set switch 42 is actuated as shown at block 118, the day is displayed as shown at block 120 thereby allowing the day to be set. When display switch 40 is actuated as shown at block 122 the day displayed is advanced to the next day as shown at block 124. If display switch 40 is not actuated as shown at block 114 and set switch 42 is not actuated as shown at block 126, the day displayed continues as shown at block 120.

When set switch 42 is actuated as shown at block 126, the hour is displayed as shown at block 128 thereby allowing the hours to be set. When display switch 40 is actuated as shown at block 130 the hour displayed is advanced to the next hour as shown at block 132. If display switch 40 is not actuated as shown at block 130 and set switch 42 is not actuated as shown at block 134, the hour displayed continues as shown at block 128.

When set switch 42 is actuated as shown at block 134 the minute is displayed as shown at block 136 thereby allowing the minutes to be set. When display switch 40 is actuated as shown at block 138 the minute displayed is advanced to the next minute 140. If display switch 40 is not actuated as shown at block 138 and set switch 42 is not actuated as shown at block 142, the minute displayed 136 continues as shown at block 136. When set switch 42 is actuated as shown at block 142 the normal time display is obtained as shown at block 146, thus completing the present time setting procedure started at block 100.

Reference is now directed the flowchart shown in FIG. 4B which describes the procedure to view day/date and seconds. To enter the view time procedure at block 148, display switch 40 is actuated as shown at block 168 of the flowchart shown in FIG. 4C which describes the general operation of the watch-pager device 10 to be described in detail later. The day/date are displayed as shown at block 150 when the view time procedure at block 148 is entered as shown in FIG. 4B. If display switch 40 is not actuated as shown at block 152 and the two second time period as shown at block 154 has not elapsed, the day/date displayed continues as shown at block 150. When the two second time period has elapsed as shown at block 154, the normal time display is obtained as shown at block 156, thus completing the view time procedure started at block 148.

If the display button is actuated as shown at block 152, then seconds are displayed as shown at block 158. If display switch 40 is not depressed as shown at block 160, the seconds displayed continues as shown at block 158. When display switch 40 is depressed as shown at block 160 are displayed, the normal time display is obtained as shown at block 156, thus completing the view time procedure started

at block 148.

It will be appreciated by those skilled in the art that other procedures to display time and day/date information may be employed without departing from the scope and spirit of the invention described. It will also be appreciated that other timing functions, well known to those skilled in the art, may also be employed without departing from the scope or spirit of the invention described.

Reference is now directed to FIG. 4C which describes the general operation of the watch-pager device 10. While the watch-pager device 10 described in the embodiment of the present invention does not have a power control switch, power is turned on as shown at block 162 when the battery has been replaced. Time is normally displayed as shown at block 164 when power is supplied. When the set switch 42 is actuated as shown in block 166, the time setting procedure as shown at block 100 is entered, as previously described. When the display switch 40 is actuated as shown in block 168, the view time procedure as shown at block 148 is entered, also as previously described. If a page has not been received as shown at block 170, but the mode switch 44 has been actuated as shown at block 172 the switch functions are modified as previously described, and new switch function labels are generated on the display as shown at block 174, placing the device in the message readout procedure shown at block 176. The message readout procedure shown at block 176 will be described in detail later.

When a page is received as shown at block 170 the received message is stored in memory 30 as shown at block 178. The display duration timeout is initialized as shown at block 180 and the switch functions are modified and new switch function labels are generated on the display as shown at block 182, thereby placing the device in the paging receiver mode. The text "Page" is generated and an audible alert is sounded as shown at block 184. If the mode switch 44, now having the "Time" select switch 48 function, is actuated as shown at block 186, the normal switch functions are restored, the displayed switch labels are cleared, and the audible alert is reset as shown at block 200, thereby returning the device to the normal time display mode shown at block 164. If the display switch 40, having the "Reset" switch 46 function, is actuated as shown at block 188, the audible alert is reset as shown at block 190, and the message readout procedure 176 is entered. If the set switch 42, having the "Hold On" switch 50 function, is actuated as shown at block 192, message timeout is inhibited as shown at block 194. The message displayed is frozen until the set switch 42, having the "Hold Off" switch 54 function, is actuated as shown at block 196. If the set switch 42, having the "Hold On" switch 50 function, was not actuated as shown at block 192, and message timeout occurs as shown at

block 198, the normal switch functions are restored, the displayed switch labels are cleared, and the audible alert is reset as shown at block 200, thereby returning the device to the normal time display mode shown at block 164.

Reference is now directed to the flowchart shown in FIG. 4D describes the procedure for reading out messages stored in the memory 30. The message readout procedure shown starting at block 176 when entered initializes the timing generator 36 as shown at block 202, thereby extending the display time duration a complete time interval. If a message has been stored as shown at block 204 the message is readout from memory as shown in block 206 and displayed on the display as shown in block 208.

When the display switch 40, having the "Read" switch 52 function, is actuated as shown at block 210, memory is checked for the presence of any additional messages as shown at block 222. If additional messages are stored, the timeout generator is reinitialized as shown at block 224, the next message is read as shown at block 206, and the message is displayed on the display as shown at block 208. This procedure is repeated until all messages stored in memory are read out. If another message was not stored in memory as shown in block 222, then the normal switch functions are restored, and the displayed switch labels are cleared as shown at block 226, thereby returning the device to the normal time display mode shown at block 228, thereby ending the message readout procedure started at block 176. When the set switch 42, having the "Hold On" switch 50 function, is actuated as shown at block 212 while the message is being displayed, the message timeout is inhibited as shown at block 214. The message will remain displayed on the display until the set switch 42, having the "Hold Off" switch 54 function, is actuated as shown at block 216. If the set switch 42, having the "Hold On" switch 50 function, was not actuated as shown at block 212, then message timeout may occur as shown at block 218. Memory is checked for the presence of additional messages as shown at block 222, and any additional messages stored are displayed as previously described.

If mode switch 44, having the "Time" select switch 48 function, is actuated as shown at block 220 then the normal switch functions are restored, and the displayed switch labels are cleared as shown at block 226, thereby returning the device to the normal time display mode shown at block 228, thereby ending the message readout procedure started at block 176.

Since it is possible to enter the message readout procedure by manually actuating the mode switch 44 as previously described at block 172, no messages may be stored as shown at block 204. When no messages are stored, the display would indicate the text "No Pages" as shown at block 230. When the set switch 42, having the "Hold On" switch 50 function, is

actuated as shown in block 232, the message timeout is inhibited as shown in block 234 freezing the "No Pages" display. When the set switch 42, having the "Hold Off" switch 54 function, is actuated as shown in block 236, message timeout can occur as shown at block 238, at which time the then the normal switch functions are restored, and the displayed switch labels are cleared as shown at block 226, thereby returning the device to the normal time display mode shown at block 228, thereby ending the message readout procedure started at block 176.

An alternate embodiment of the watch-pager device 10 is described in the flow charts shown in FIGS. 5A and 5B. Since most of the operation of the alternate embodiment of the device described in FIGS. 5A and 5B have been previously described with respect to FIGS. 4C and 4D, respectively, only the differences in operation will be described in detail here.

Reference is directed to the flowchart shown in FIG. 5A, and in particular to block 240, identified by a broken line outline, which shows that the time is stored in memory 30 after the received message was stored in memory 30 as shown at block 178. All other operations illustrated in the flow chart were previously described.

Reference is directed to the flowchart shown in FIG. 5B and in particular to block 206 which shows the received message is first read from memory 30 and then displayed as shown at block 208. The received message is displayed until a display timeout occurs as shown at block 242. The information displayed when the timeout occurs is checked as shown at block 244. Since the information displayed was a received message, the stored time information is read from memory 30 as shown at block 246 and displayed as shown at block 248. The next time the display timeout occurs as shown at block 242 the information displayed is again checked as shown at block 244. Since time information was displayed then the received message is again read from the memory 30 as shown at block 206 and displayed as shown at block 208, thus resulting in an alternating display of the received message and the received time. All other operation within the flow-chart are as has been previously described.

By providing the ability to store the time at which a message is received, it is possible to review the stored messages and to respond to them in an order of priority which is based upon the receipt of the earliest message with respect to the time received. This feature enhances the utility of a pager which has watch functions incorporated into it.

Referring now to FIG. 6, illustrated is an electrical block diagram of the apparatus of the present invention utilizing a microcomputer 81 for controlling the operation of the apparatus of the watch-pager 10 previously described. Microcomputer 81 performs the combined functions of display controller 16, including those of switch interface controller 34, timing

generator 36, display selector 38 and display interface 40, as well as the functions of decoder 28 and memory 30 of paging receiver 14 for the embodiment previously shown in FIG. 2.

Operation of the embodiment of the present invention as shown in FIG. 6 is as follows. Microcomputer 81 is a single chip microcomputer, such as the MC68HC05L6 manufactured by Motorola. Microcomputer 81 includes a CPU 82 for operational control. An internal buss 83 connects all of the elements of the microcomputer 81. An I/O port 84 provides communications to the circuits external to the microcomputer 81. A timer/counter and timer control 36 generates the display time duration interval for controlling the length of time the received message is displayed. Oscillator 86 provides the clock for operation of CPU 82, provides the reference clock for timer/counter 36, and provides the clock signals necessary to drive the on-board serial display driver 40. Oscillator 86 receives the operating oscillator frequency signal from real time clock 20. RAM 30 stores the messages as they are received for subsequent display as previously described. ROM 88 contains the firmware controlling microprocessor 81 operation. Programs, such as for decoding, for time setting and display, for message storage and display and for controlling the switch operations and displayed indicia, are included in ROM 88. An alert generator 90 provides the alerting signal in response to decoding the selective call signal information. And the on-board serial display driver 40 provides the proper signals for driving display 22.

Transmitted coded message signals including selective call signalling and message information are received by antenna 12 which is coupled to receiver 24. Receiver 24 demodulates the coded message signals providing selective call signalling and message information. The output of receiver 24 is coupled to I/O port 84 of microcomputer 81. Also coupled to I/O port 84 is code plug, or code memory 26 which stores the predetermined addresses for the watch-pager 10, as previously described.

Microcomputer 81 provides the decoder function, in a manner well known to those skilled in the art, providing internal control signals when the received selective call signalling matches the predetermined address information.

The message information received is stored in RAM 30. Alert generator 90 generates an alerting signal which is coupled to transducer driver 32. A second input to transducer driver 32 from I/O port 84 controls the alerting signal delivery to transducer 33, producing an audible alert. The second input to transducer driver 32 provides for such features as silent alerting, wherein the message is received and stored, however the alerting signal is inhibited from delivery to transducer 33. Selection of the silent alerting feature would be indicated by the absence of the audible alert annunciator 74, shown in FIG. 3C. Other features,

such as interrupting the audible alert are also controlled by the second input. ROM 88 is also read for the text information to be displayed indicating a message has been received. Information is also provided the display driver for properly displaying message annunciator 70 and cursor 72, and the switch labels, as previously described.

Display switch 40, set switch 42 and mode switch 44 are coupled to microcomputer 81 through I/O port 84 for providing control the the messages while the paging receiver mode of operation has been selected by microcomputer 81. After the received message has been read, or after the display time duration has elapsed, as previously described, microcomputer 81 resumes time display. A real time clock 20, such as the MC146818, manufactured by Motorola, provides all of the timing functions for the watch-pager 10, as well as provides the oscillator signal required for operation of the microcomputer 81. The real time clock provides the time, and day/date information which is updated once each second and read by microcomputer 81 for subsequent display. Readout and setting of the information of real time clock 20, is accomplished in a manner as previously described using display switch 40 and set switch 42. Other features such as alarm features are also provided by real time clock 20.

One additional circuit which is valuable for the operation of a watch-pager 10 which is worn on the wrist is battery saver circuit 92, not previously described in FIG. 2, although its inclusion would be obvious to one skilled in the art. Under control of microcomputer 81, the battery saver circuit 92 is periodically turned on and off, thereby conserving power by removing power from the receiver 24. The microcomputer 81 is able to periodically update the time display, and periodically control the battery saver circuit 92. If coded message signals are detected on the channel when receiver 24 is turned on by battery saver circuit 92, microcomputer 81 will suspend the operation of battery saver circuit 92 operation, until the coded message signals have been evaluated. As previously described, if the coded message signals match the predetermined address information, display of time information will be suspended, and operation of the switches returned to control the receiver and message delivery.

Claims

1. A switch control interface arrangement for a device normally generating and displaying time information, the device having a plurality of switches for controlling the time display, the switches including permanent indicia positionally adjacent the switches for indicating the switch functions, the device being further capable of receiving transmitted coded message signals, said arrangement comprising :

generator 36, display selector 38 and display interface 40, as well as the functions of decoder 28 and memory 30 of paging receiver 14 for the embodiment previously shown in FIG. 2.

Operation of the embodiment of the present invention as shown in FIG. 6 is as follows. Microcomputer 81 is a single chip microcomputer, such as the MC68HC05L6 manufactured by Motorola. Microcomputer 81 includes a CPU 82 for operational control. An internal buss 83 connects all of the elements of the microcomputer 81. An I/O port 84 provides communications to the circuits external to the microcomputer 81. A timer/counter and timer control 36 generates the display time duration interval for controlling the length of time the received message is displayed. Oscillator 86 provides the clock for operation of CPU 82, provides the reference clock for timer/counter 36, and provides the clock signals necessary to drive the on-board serial display driver 40. Oscillator 86 receives the operating oscillator frequency signal from real time clock 20. RAM 30 stores the messages as they are received for subsequent display as previously described. ROM 88 contains the firmware controlling microprocessor 81 operation. Programs, such as for decoding, for time setting and display, for message storage and display and for controlling the switch operations and displayed indicia, are included in ROM 88. An alert generator 90 provides the alerting signal in response to decoding the selective call signal information. And the on-board serial display driver 40 provides the proper signals for driving display 22.

Transmitted coded message signals including selective call signalling and message information are received by antenna 12 which is coupled to receiver 24. Receiver 24 demodulates the coded message signals providing selective call signalling and message information. The output of receiver 24 is coupled to I/O port 84 of microcomputer 81. Also coupled to I/O port 84 is code plug, or code memory 26 which stores the predetermined addresses for the watch-pager 10, as previously described.

Microcomputer 81 provides the decoder function, in a manner well known to those skilled in the art, providing internal control signals when the received selective call signalling matches the predetermined address information.

The message information received is stored in RAM 30. Alert generator 90 generates an alerting signal which is coupled to transducer driver 32. A second input to transducer driver 32 from I/O port 84 controls the alerting signal delivery to transducer 33, producing an audible alert. The second input to transducer driver 32 provides for such features as silent alerting, wherein the message is received and stored, however the alerting signal is inhibited from delivery to transducer 33. Selection of the silent alerting feature would be indicated by the absence of the audible alert annunciator 74, shown in FIG. 3C. Other features,

such as interrupting the audible alert are also controlled by the second input. ROM 88 is also read for the text information to be displayed indicating a message has been received. Information is also provided the display driver for properly displaying message annunciator 70 and cursor 72, and the switch labels, as previously described.

Display switch 40, set switch 42 and mode switch 44 are coupled to microcomputer 81 through I/O port 84 for providing control the the messages while the paging receiver mode of operation has been selected by microcomputer 81. After the received message has been read, or after the display time duration has elapsed, as previously described, microcomputer 81 resumes time display. A real time clock 20, such as the MC146818, manufactured by Motorola, provides all of the timing functions for the watch-pager 10, as well as provides the oscillator signal required for operation of the microcomputer 81. The real time clock provides the time, and day/date information which is updated once each second and read by microcomputer 81 for subsequent display. Readout and setting of the information of real time clock 20, is accomplished in a manner as previously described using display switch 40 and set switch 42. Other features such as alarm features are also provided by real time clock 20.

One additional circuit which is valuable for the operation of a watch-pager 10 which is worn on the wrist is battery saver circuit 92, not previously described in FIG. 2, although its inclusion would be obvious to one skilled in the art. Under control of microcomputer 81, the battery saver circuit 92 is periodically turned on and off, thereby conserving power by removing power from the receiver 24. The microcomputer 81 is able to periodically update the time display, and periodically control the battery saver circuit 92. If coded message signals are detected on the channel when receiver 24 is turned on by battery saver circuit 92, microcomputer 81 will suspend the operation of battery saver circuit 92 operation, until the coded message signals have been evaluated. As previously described, if the coded message signals match the predetermined address information, display of time information will be suspended, and operation of the switches returned to control the receiver and message delivery.

Claims

1. A switch control interface arrangement for a device normally generating and displaying time information, the device having a plurality of switches for controlling the time display, the switches including permanent indicia positionally adjacent the switches for indicating the switch functions, the device being further capable of receiving transmitted coded message signals, said arrangement comprising :



receiver means for receiving and decoding the transmitted coded message signals to derive control signals and information ;

means for internally generating time information and means for displaying the same ;

a plurality of control inputs ; and

switch controller means including input steering means coupled to said plurality of control inputs and further coupled to said time information generating means and to said receiver means for enabling control of said time information generating means and said receiver means by said control inputs, said switch controller means enabling control of said receiver means in response to the control signals.

2. The switch control interface arrangement according to claim 1 wherein said plurality of control inputs are coupled to the plurality of switches.

3. A switch control interface arrangement according to claim 2 wherein the transmitted coded message signals includes selective call signalling and wherein said receiver means comprises ;

a receiver portion for receiving and demodulating the transmitted coded message signals to derive the selective call signalling and message information ;

identification means for storing predetermined device identification information ; and

decoder means coupled to said identification means and responsive to the selective call signalling information for deriving control signals when the selective call signalling information matches the predetermined device identification information.

4. The switch control interface arrangement according to claim 3 wherein said decoder means further includes means for generating an alerting signal coupled to said switch controller means and said receiver means further includes alert delivery means coupled to said switch controller means, said switch controller means effecting the delivery of the alerting signal in response to the control signals.

5. A switch control interface arrangement according to claim 4 wherein the alerting signal delivered is audible.

6. A switch control interface arrangement according to claim 4 wherein said decoder means is responsive to said input steering means for interrupting the alerting signal in response to actuation of one of the plurality of switches.

7. The switch control interface arrangement according to claim 3 wherein said receiver means further comprises memory means coupled to said receiver portion and responsive to said decoder means for storing alert information in response to the control signals.

8. The switch control interface arrangement according to claim 7 wherein said memory means is

further responsive to said decoder means which is responsive to said switch controller means for effecting the delivery of the stored alert information in response to actuation of one of the plurality of switches.

9. The switch control interface arrangement according to claim 2 wherein said switch controller means further comprising switch duration generating means for enabling control of said receiver means for a predetermined time duration in response to the control signals.

10. The switch control interface arrangement according to claim 9 wherein said switch duration generating means is further responsive to at least one of the plurality of switches when the alert information is delivered for interrupting the control of said receiver means thereby effecting the display of time information.

11. The switch control interface arrangement according to claim 9 wherein said switch duration generating means is further responsive to at least one of the plurality of switches when time information is displayed for effecting enabling of control of said receiver means thereby effecting the delivery of alert information.

12. The switch control interface arrangement according to claim 1 wherein the time information represents at least time and date watch functions.

13. The switch control interface arrangement according to claim 1 wherein the device may be worn on the wrist.

14. A display control interface arrangement for a device normally generating and displaying time information, the device having a plurality of switches for controlling the time display, the switches including permanent indicia positionally adjacent the switches for indicating the switch functions, the device being further capable of receiving transmitted coded message signals, said arrangement comprising :

receiver means for receiving and decoding the transmitted coded message signals to derive control signals and information ;

means for internally generating time information and means for displaying the same ;

input steering means coupled to the plurality of switches and further coupled to said time information generating means and to said receiver means for enabling control of said time information generating means and said receiver means by said switches, said input steering means enabling control of said receiver means in response to the control signals ;

information selecting means coupled to said time information generating means and to said receiver means for selecting the display of time information and derived information, said information selecting means responsive to said input steering means for selecting the display of derived information in response to the control sig-



nals ; and

display interface means coupled to said display means and responsive to said information selecting means for effecting the display of selected information.

15. A display control interface arrangement according to claim 14 wherein the derived information displayed in response to the control signals is derived from the transmitted coded message signals.

16. A display control interface arrangement according to claim 15 wherein the transmitted coded message signals includes at least selective call signalling and message information and wherein said receiver means comprises ;

a receiver portion for receiving and demodulating the transmitted coded message signals to derive the selective call signalling and message information ;

identification means for storing predetermined device identification information ; and

decoder means coupled to said identification means and responsive to the selective call signalling information for deriving the control signals when the selective call signalling information matches the predetermined device identification information.

17. A display control interface arrangement according to claim 16 wherein said receiver means further comprises memory means coupled to said receiver portion and responsive to said decoder means for storing the message information in response to the control signals.

18. A display control interface arrangement according to claim 17 wherein said memory means is further responsive to the decoder means which is responsive to said input steering means for effecting the display of the stored message information in response to actuation of one of the plurality of switches.

19. The display control interface arrangement according to claim 14 whereby said information selecting means electronically selects indicia displayed on said display means positionally adjacent the plurality of switches indicating the new switch functions enabled in response to the control signals.

20. The display control interface arrangement according to claim 19 whereby said information selecting means is capable of selecting multiple indicia selectively displayed on said display means positionally adjacent at least one of the plurality of switches indicating the switch functions selectively enabled in response to the actuation of the one switch when the message information is displayed.

21. The display control interface arrangement according to claim 16 wherein said decoder means further includes means for generating an alerting signal coupled to said information selecting means and said receiver means further includes alert delivery means coupled to said information selecting means,

said information selecting means effecting the delivery of the alerting signal in response to the control signals.

22. The display control interface arrangement according to claim 21 wherein the alerting signal delivered is audible.

23. The display control interface arrangement according to claim 21 wherein said decoder means is responsive to said input steering means for interrupting the alerting signal in response to actuation of one of the plurality of switches.

24. The display control interface arrangement according to claim 16 wherein said display controller means further comprising display duration generating means coupled to said input steering means for enabling control of said receiver means for a predetermined time duration in response to the control signals.

25. The display control interface arrangement according to claim 24 wherein said display duration generating means is further responsive to at least one of the plurality of switches when the message information is displayed for interrupting the control of said receiver means thereby effecting the display of time information.

26. The display control interface arrangement according to claim 24 wherein said display duration generating means is further responsive to at least one of the plurality of switches when time information is displayed for effecting the enabling of control of said receiver means thereby effecting the display of message information.

27. The display control interface arrangement according to claim 14 wherein the time information represents at least time and date watch functions.

28. The display control interface arrangement according to claim 14 wherein the device may be worn on the wrist.

29. A display control interface arrangement for a wrist worn device normally generating and displaying time information, the device having a plurality of switches for controlling the time display, the switches including permanent indicia positionally adjacent the switches for indicating the switch functions, the device being further capable of receiving transmitted coded message signals including selective call signalling and message information, said arrangement comprising :

receiver means including a receiver portion, identification means and decoder means, said receiver portion for receiving and demodulating the transmitted coded message signals to derive selective call signalling and message information, said identification means for storing predetermined device identification information, and said decoder means coupled to said identification means and responsive to the selective call signalling information for deriving control signals when the selective call signalling matches the predeter-



mined device identification information ;
 means for internally generating time information
 and means for displaying the same ;
 input steering means coupled to the plurality of
 switches and further coupled to said time infor-
 mation generating means and to said receiver
 means for enabling control of said time infor-
 mation generating means and said receiver
 means by said switches, said input steering
 means enabling control of said receiver means in
 response to the control signals ;
 information selecting means coupled to said time
 information generating means and to said
 receiver means for selecting the display of time
 information and message information, said infor-
 mation selecting means responsive to said input
 steering means for selecting the message infor-
 mation in response to the control signals, said
 information selecting means further electronically
 selecting indicia displayed on said display means
 positionally adjacent the plurality of switches indi-
 cating the new switch functions enabled in re-
 sponse to the control signals ; and
 display interface means coupled to said display
 means and responsive to said information select-
 ing means for effecting the display of selected
 information.

30. The display control interface arrangement
 according to claim 29 wherein said receiver means
 further comprises memory means coupled to said
 receiver portion and responsive to the decoder means
 for storing the message information in response to the
 control signals.

31. The display control interface arrangement
 according to claim 30 wherein said memory means is
 further responsive to said decoder means which is
 responsive to said input steering means for effecting
 the display of the stored message information in re-
 sponse to actuation of one of the plurality of switches.

32. The display control interface arrangement
 according to claim 29 wherein said decoder means
 further includes means for generating an alerting sig-
 nal coupled to said information selecting means and
 said receiver means further includes alert delivery
 means coupled to said information selecting means,
 said information selecting means effecting the deliv-
 ery of the alerting signal in response to the control sig-
 nals.

33. The display control interface arrangement
 according to claim 32 wherein the alerting signal deliv-
 ered is audible.

34. The display control interface arrangement
 according to claim 32 wherein said decoder means is
 responsive to said input steering means for interrupt-
 ing the alerting signal in response to actuation of one
 of the plurality of switches.

35. The display control interface arrangement
 according to claim 29 wherein said display controller

means further comprising display duration generating
 means coupled to said input steering means for
 enabling control of said receiver means for a predeter-
 mined time duration in response to the control signals.

36. The display control interface arrangement
 according to claim 35 wherein said display duration
 generating means is further responsive to at least one
 of the plurality of switches when the message infor-
 mation is displayed for interrupting the control of said
 receiver means thereby effecting the display of time
 information.

37. The display control interface arrangement
 according to claim 35 wherein said display duration
 generating means is further responsive to at least one
 of the plurality of switches when time information is
 displayed for effecting enabling of control of said
 receiver means thereby effecting the display of mes-
 sage information.

38. The display control interface arrangement
 according to claim 29 wherein the time information
 represents at least time and date watch functions.

39. A method for controlling the display on a
 device normally generating and displaying time infor-
 mation, the device having a plurality of switches for
 controlling the time display, the switches including
 permanent indicia positionally adjacent the switches
 for indicating the switch functions, the device further
 capable of receiving transmitted coded message sig-
 nals, said method comprising the steps of :

receiving and decoding the transmitted coded
 message signals to derive control signals and
 message information ;

modifying the functions of the switches in re-
 sponse to the control signals ; and

electronically selecting indicia and displaying the
 same positionally adjacent the switches indicat-
 ing the new switch functions, whereby in re-
 sponse to receiving and decoding the coded
 message signals, the switch functions are
 changed allowing display of the derived message
 information.

40. The method of controlling the display on a
 device according to claim 39 further comprising the
 steps of :

storing the derived message information in re-
 sponse to the control signals ;

displaying predetermined alphanumeric text indi-
 cating a message has been received in the place
 of the time information in response to the control
 signals ; and

generating an audible alert in response to the
 control signals, whereby the message infor-
 mation received is stored and audible and visual
 indications are provided.

41. The method of controlling the display on a
 device according to claim 40 further comprising the
 steps of :

actuating a first switch for suspending the display



of the predetermined alphanumeric text and the generation of the audible alert and selecting the display of stored message information ; and displaying the stored message information, whereby the stored message information is displayed when the first switch of the plurality of switches is actuated.

42. The method of controlling the display on a device according to claim 40 further comprising the steps of :

actuating a second switch suspending the display of the predetermined alphanumeric text and the generation of the audible alert for effecting the display of time information ;
restoring the switches to the original functions ;
and
cancelling the display of the electronically selected indicia, whereby time information is again displayed and the display of the stored message information is terminated when the second switch of the plurality of switches is actuated.

43. The method of controlling the display of a device according to claim 42 further comprising the steps of :

actuating a second switch to manually select the display of stored message information when time information is displayed ;
electronically selecting indicia and displaying the same positionally adjacent the switches indicating the new switch functions in response thereto ;
and
displaying the stored message information, whereby stored message information may be displayed when time information is displayed by actuating the second switch.

44. The method of controlling the display on a device according to claim 40 further comprising the steps of :

generating a predetermined time period in response to the control signals ;
modifying the functions of the switches and electronically selecting indicia electronically and displaying the same positionally adjacent the switches indicating the new switch functions during the predetermined time period ;
generating an audible alert during the predetermined time period ;
displaying predetermined alphanumeric text indicating a message has been received during the predetermined time period
displaying time information upon completion of the predetermined time period ; and
restoring the switches to the original functions, whereby the display of stored message information is automatically terminated when a first switch is not actuated to display message information during the predetermined time period.

45. The method of controlling the display of a

device according to claim 44 further comprising the steps of :

actuating a first switch to select the display of message information during the predetermined time period ;
reinitializing the predetermined time period ; and
displaying the message information, whereby stored message information may be displayed during the predetermined time period by actuating the first switch.

46. The method of controlling the display of a device according to claim 44 further comprising the steps of :

actuating a second switch for suspending the display of predetermined alphanumeric text and selecting the display of the time information before completion of the predetermined time period ;
and
restoring the switches to the original functions ;
cancelling the display of the electronically generated indicia, whereby the display of the stored message information is terminated during the predetermined time period when the second switch is actuated.

Ansprüche

1. Schnittstelle einer Schaltersteuerung für ein Gerät, das normalerweise Zeitinformationen hervorbringt und zur Schau stellt, sowie mehrere Schalter für eine Einstellung der Zeitanzeige aufweist, die permanente, neben ihnen angeordnete Markierungen zur Anzeige der Schalterfunktionen enthalten, wobei das Gerät ferner als codierte Nachricht gesendete Signale zu empfangen imstande ist,

mit einer Empfangseinrichtung zum Empfang und Decodieren der als codierte Nachricht gesendeten Signale, um Steuersignale und Informationen abzuleiten,

mit Vorrichtungen, die intern Zeitinformationen hervorbringen und diese zur Schau stellen, mit mehreren Steuereingangsklemmen und mit einer Schaltersteuerung, die eine Eingangsleitvorrichtung enthält und mit den Steuereingangsklemmen, ferner mit der die Zeitinformationen hervorbringenden Vorrichtung und mit der Empfangseinrichtung verbunden ist, um über die Steuereingangsklemmen die die Zeitinformationen hervorbringenden Vorrichtungen und die Empfangseinrichtung einzustellen, wobei die Schaltersteuerung die Empfangseinrichtung in Abhängigkeit von den Steuersignalen einzustellen imstande ist.

2. Schnittstelle einer Schaltersteuerung gemäß Anspruch 1, bei der die Steuereingangsklemmen mit den Schaltern verbunden sind.

3. Schnittstelle einer Schaltersteuerung gemäß



Anspruch 2, bei der die als codierte Nachricht gesendeten Signale eine wahlweise Anrufsignalgabe enthalten, und bei der die Empfangseinrichtung die folgenden Bestandteile aufweist:

- einen Empfängerteil zum Empfang und Demodulieren der als codierte Nachricht gesendeten Signale, um die wahlweise Anrufsignalgabe und Nachrichten-Informationen abzuleiten;
- eine der Identifizierung dienende Vorrichtung zur Ablage von ein vorherbestimmtes Gerät identifizierenden Informationen und
- einen mit der der Identifizierung dienenden Vorrichtung verbundenen Decodierer, der auf die Informationen der wahlweisen Anrufsignalgabe zur Ableitung von Steuersignalen anspricht, wenn die Informationen der wahlweisen Signalgabe mit den ein vorherbestimmtes Gerät identifizierenden Informationen übereinstimmen.

4. Schnittstelle einer Schaltersteuerung gemäß Anspruch 3, bei der der Decodierer ferner Vorrichtungen zur Erzeugung eines Warnsignals aufweist, die mit der Schaltersteuerung verbunden sind, und die Empfangseinrichtung ferner einen mit der Schaltersteuerung verbundenen Alarmgeber enthält, wobei die Schaltersteuerung in Abhängigkeit von den Steuersignalen die Ausgabe des Warnsignals bewirkt.

5. Schnittstelle einer Schaltersteuerung gemäß Anspruch 4, bei der das ausgegebene Warnsignal hörbar ist.

6. Schnittstelle einer Schaltersteuerung gemäß Anspruch 4, bei der der Decodierer auf die Eingangsleitvorrichtung anspricht, um das Warnsignal entsprechend einer Betätigung eines der Schalter abzubrechen.

7. Schnittstelle einer Schaltersteuerung gemäß Anspruch 3, bei der die Empfangseinrichtung ferner einen mit dem Empfängerteil verbundenen Speicher enthält und auf den Decodierer anspricht, um der Warnung dienende Informationen in Abhängigkeit von den Steuersignalen abzulegen.

8. Schnittstelle einer Schaltersteuerung gemäß Anspruch 7, bei der der Speicher ferner auf den Decodierer anspricht, der auf die Schaltersteuerung reagiert, um die Ausgabe der gespeicherten, der Warnung dienenden Informationen bei einer Betätigung eines der Schalter zu bewirken.

9. Schnittstelle einer Schaltersteuerung gemäß Anspruch 2, bei der die Schaltersteuerung ferner eine die Schaltdauer hervorrufende Vorrichtung enthält, um eine Einstellung der Empfangseinrichtung während einer vorherbestimmten Zeitdauer in Abhängigkeit von den Steuersignalen zu ermöglichen.

10. Schnittstelle einer Schaltersteuerung gemäß Anspruch 9, bei der die die Schaltdauer hervorrufende Vorrichtung ferner auf mindestens einen der Schalter anspricht, wenn die der Warnung dienenden Informationen zum Abbruch der Steuerung der Emp-

fangseinrichtung ausgegeben werden, wodurch die Schautellung der Zeitinformationen bewirkt wird.

11. Schnittstelle einer Schaltersteuerung gemäß Anspruch 9, bei der die die Schaltdauer hervorrufende Vorrichtung ferner auf mindestens einen der Schalter anspricht, wenn die Zeitinformationen zur Schau gestellt werden, um eine Steuerung der Empfangseinrichtung zu ermöglichen und dadurch die Ausgabe der der Warnung dienenden Informationen zu bewirken.

12. Schnittstelle einer Schaltersteuerung gemäß Anspruch 1, bei der die Zeitinformationen mindestens Zeit- und Datumsfunktionen einer Uhr darstellen.

13. Schnittstelle einer Schaltersteuerung gemäß Anspruch 1, bei der das Gerät an dem Armband getragen werden kann.

14. Schnittstelle einer Bildsteuerung für ein Gerät, das normalerweise Zeitinformationen hervorbringt und zur Schau stellt, sowie mehrere Schalter für eine Einstellung der Zeitanzeige aufweist, die permanente, neben ihnen angeordnete Markierungen zur Anzeige der Schalterfunktionen enthalten, wobei das Gerät ferner als codierte Nachricht gesendete Signale zu empfangen imstande ist,

mit einer Empfangseinrichtung zum Empfang und Decodieren der als codierte Nachricht gesendeten Signale, um Steuersignale und Informationen abzuleiten,

mit Vorrichtungen, die intern Zeitinformationen hervorbringen und diese zur Schau stellen,

mit einer Eingangsleitvorrichtung, die mit den Schaltern, ferner mit der die Zeitinformationen hervorbringenden Vorrichtung und mit der Empfangseinrichtung verbunden ist, um eine Steuerung der die Zeitinformationen hervorbringenden Vorrichtung und der Empfangseinrichtung über die Schalter zu ermöglichen, wobei die Eingangsleitvorrichtung eine Steuerung der Empfangseinrichtung in Abhängigkeit von den Steuersignalen ermöglicht,

mit einer die Informationen auswählenden Vorrichtung, die mit der die Zeitinformationen hervorbringenden Vorrichtung und der Empfangseinrichtung verbunden ist, um die Wiedergabe von Zeitinformationen und abgeleiteten Informationen auszuwählen, wobei die die Informationen auswählende Vorrichtung auf die Eingangsleitvorrichtung anspricht, um die Wiedergabe der abgeleiteten Informationen in Abhängigkeit von den Steuersignalen auszuwählen, und

mit einer Schnittstelle für die Bildwiedergabe, die mit der Wiedergabe Einrichtung verbunden ist und auf die die Informationen auswählende Vorrichtung anspricht, um die Wiedergabe der gewählten Informationen zu bewirken.

15. Schnittstelle einer Bildsteuerung gemäß Anspruch 14, bei der die abgeleiteten, in Abhängig-



keit von den Steuersignalen zur Schau gestellten Informationen von den als codierte Nachricht gesendeten Signalen abgeleitet werden.

16. Schnittstelle einer Bildsteuerung gemäß Anspruch 15, bei der die als codierte Nachricht gesendeten Signale mindestens eine wahlweise Anrufsignalgabe und Nachrichten-Informationen enthalten und die Empfangseinrichtung die folgenden Bestandteile aufweist :

einen Empfängerteil zum Empfang und Demodulieren der als codierte Nachricht gesendeten Signale, um die wahlweise Anrufsignalgabe und die Nachrichten-Informationen abzuleiten, eine der Identifizierung dienende Vorrichtung zur Ablage von ein vorherbestimmtes Gerät identifizierenden Informationen und einen Decodierer, der mit der der Identifizierung dienenden Vorrichtung verbunden ist und auf die Informationen der wahlweisen Anrufsignalgabe zur Ableitung der Steuersignale anspricht, wenn die Informationen der Anrufsignalgabe mit den das vorherbestimmte Gerät identifizierenden Informationen übereinstimmen.

17. Schnittstelle einer Bildsteuerung gemäß Anspruch 16, bei der die Empfangseinrichtung ferner einen mit dem Empfängerteil verbundenen Speicher enthält, der auf den Decodierer anspricht, um in Abhängigkeit von den Steuersignalen die Nachrichten-Informationen abzuleiten.

18. Schnittstelle einer Bildsteuerung gemäß Anspruch 17, bei der der Speicher ferner auf den Decodierer anspricht, der auf die Eingangsleitvorrichtung anspricht, um die Wiedergabe der gespeicherten Nachrichten-Informationen bei einer Betätigung eines der Schalter zu bewirken.

19. Schnittstelle einer Bildsteuerung gemäß Anspruch 14, bei der die die Informationen auswählende Vorrichtung elektronisch die auf der Wiedergabe-Einrichtung dargestellten, neben den Schaltern angeordneten Markierungen auswählt, die die neuen Schalterfunktionen in Abhängigkeit von den Steuersignalen anzeigen.

20. Schnittstelle einer Bildsteuerung gemäß Anspruch 19, bei der die die Informationen auswählende Vorrichtung zahlreiche Markierungen auszuwählen imstande ist, die an der Wiedergabe-Einrichtung wahlweise zur Schau gestellt werden und neben mindestens einem der Schalter angeordnet sind, die die Schalterfunktionen anzeigen, die bei einer Betätigung eines der Schalter wahlweise ermöglicht werden, wenn die Nachrichten-Informationen zur Schau gestellt werden.

21. Schnittstelle einer Bildsteuerung gemäß Anspruch 16, bei der der Decodierer ferner eine Vorrichtung zur Erzeugung eines Warnsignals enthält, die mit der die Informationen auswählenden Vorrichtung verbunden ist, und die Empfangseinrichtung ferner einen Alarmgeber aufweist, der mit der die

Informationen auswählenden Vorrichtung verbunden ist, um in Abhängigkeit von den Steuersignalen die Ausgabe des Warnsignals zu bewirken.

22. Schnittstelle einer Bildsteuerung gemäß Anspruch 21, bei der das ausgegebene Warnsignal hörbar ist.

23. Schnittstelle einer Bildsteuerung gemäß Anspruch 21, bei der der Decodierer auf die Eingangsleitvorrichtung zum Abbruch des Warnsignals bei einer Betätigung eines von mehreren Schaltern anspricht.

24. Schnittstelle einer Bildsteuerung gemäß Anspruch 16, bei der die Steuerung der Wiedergabe ferner eine die Dauer der Wiedergabe festlegende Vorrichtung enthält, die mit der Eingangsleitvorrichtung verbunden ist, um eine Steuerung der Empfangseinrichtung während einer vorherbestimmten Zeitdauer in Abhängigkeit von den Steuersignalen zu ermöglichen.

25. Schnittstelle einer Bildsteuerung gemäß Anspruch 24, bei der die die Dauer der Wiedergabe festlegende Vorrichtung ferner auf mindestens einen Schalter anspricht, wenn die Nachrichten-Informationen zum Abbruch der Steuerung der Empfangseinrichtung zur Schau gestellt werden und dadurch die Wiedergabe der Zeitinformationen bewirkt wird.

26. Schnittstelle einer Bildsteuerung gemäß Anspruch 24, bei der die die Dauer der Wiedergabe festlegende Vorrichtung ferner auf mindestens einen der Schalter anspricht, wenn die Zeitinformationen zur Schau gestellt werden, um eine Steuerung der Empfangseinrichtung und dadurch die Wiedergabe der Nachrichten-Informationen zu bewirken.

27. Schnittstelle einer Bildsteuerung gemäß Anspruch 14, bei der die Zeitinformationen mindestens die Zeit- und Datumsfunktionen einer Uhr wiedergeben.

28. Schnittstelle einer Bildsteuerung gemäß Anspruch 14, bei der das Gerät an dem Armband getragen werden kann.

29. Schnittstelle einer Bildsteuerung für ein an einem Armband getragenes Gerät, das normalerweise Zeitinformationen hervorbringt und zur Schau stellt, sowie mehrere Schalter zur Einstellung der Zeitanzeige aufweist, die permanente, neben ihnen angeordnete Markierungen zur Anzeige der Schalterfunktionen enthalten, wobei das Gerät ferner als codierte Nachricht gesendete Signale zu empfangen imstande ist, zu denen eine wahlweise Anrufsignalgabe und Nachrichten-Informationen gehören, mit einer Empfangseinrichtung, die einen Empfängerteil, eine der Identifizierung dienende Vorrichtung und einen Decodierer enthält, wobei der Empfängerteil zum Empfang und Demodulieren der als codierte Nachricht gesendeten Signale vorgesehen ist, um eine wahlweise Anrufsignalgabe und Nachrichten-Informationen abzuleiten, die der Identifizierung dienende Vorrichtung zum



Speichern von ein vorherbestimmtes Gerät identifizierenden Informationen vorgesehen ist und der Decodierer mit der der Identifizierung dienenden Vorrichtung verbunden ist und auf die der wahlweisen Anrufsignalgabe dienenden Informationen zur Ableitung von Steuersignalen anspricht, wenn die wahlweise Anrufsignalgabe mit den das vorherbestimmte Gerät identifizierenden Informationen übereinstimmt, mit Vorrichtungen, die intern Zeitinformationen hervorbringen und diese zur Schau stellen, mit einer Eingangsleitvorrichtung, die mit den Schaltern, ferner mit der die Zeitinformationen hervorbringenden Vorrichtung und mit der Empfangseinrichtung verbunden ist, um über die Schalter eine Steuerung der die Zeitinformationen hervorbringenden Vorrichtung und der Empfangseinrichtung zu ermöglichen, während die Eingangsleitvorrichtung eine Steuerung der Empfangseinrichtung in Abhängigkeit von den Steuersignalen ermöglicht, mit einer die Informationen auswählenden Vorrichtung, die mit der die Zeitinformationen erzeugenden Vorrichtung und der Empfangseinrichtung zum Auswählen der Zeit- und Nachrichten-Informationen verbunden ist und auf die Eingangsleitvorrichtung anspricht, um in Abhängigkeit von den Steuersignalen die Nachrichten-Informationen auszuwählen, wobei die die Informationen auswählende Vorrichtung ferner elektronisch Markierungen auswählt, die auf der Wiedergabe-Einrichtung zur Schau gestellt werden und neben den Schaltern angeordnet sind, die die neuen Schaltfunktionen anzeigen, die in Abhängigkeit von den Steuersignalen ermöglicht werden, und mit einer Schnittstelle für die Wiedergabe, die mit der Wiedergabe-Einrichtung verbunden ist und auf die die Informationen auswählende Vorrichtung anspricht, um die Wiedergabe der gewählten Informationen zu ermöglichen.

30. Schnittstelle einer Bildsteuerung gemäß Anspruch 29, bei der die Empfangseinrichtung ferner Speicher enthält, die mit dem Empfängerteil verbunden sind und auf den Decodierer zur Ablage der Nachrichten-Informationen in Abhängigkeit von den Steuersignalen ansprechen.

31. Schnittstelle einer Bildsteuerung gemäß Anspruch 30, bei der der Speicher ferner auf den Decodierer anspricht, der auf die Eingangsleitvorrichtung reagiert, um die Wiedergabe der gespeicherten Nachrichten-Informationen bei einer Betätigung eines der Schalter zu bewirken.

32. Schnittstelle einer Bildsteuerung gemäß Anspruch 29, bei der der Decodierer ferner eine Vorrichtung zur Erzeugung eines Warnsignals enthält, die mit der die Informationen auswählenden Vorrichtung verbunden ist, und die Empfangseinrichtung fer-

ner eine Vorrichtung zur Ausgabe einer Warnung enthält, die mit der die Informationen auswählenden Vorrichtung verbunden ist, die in Abhängigkeit von den Steuersignalen die Ausgabe des Warnsignals bewirkt.

33. Schnittstelle einer Bildsteuerung gemäß Anspruch 32, bei der das ausgegebene Warnsignal hörbar ist.

34. Schnittstelle einer Bildsteuerung gemäß Anspruch 32, bei der der Decodierer auf die Eingangsleitvorrichtung zum Abbruch des Warnsignals bei einer Betätigung eines der Schalter anspricht.

35. Schnittstelle einer Bildsteuerung gemäß Anspruch 29, bei der die Wiedergabe-Steuerung ferner eine die Dauer der Wiedergabe festlegende Vorrichtung enthält, die mit der Eingangsleitvorrichtung verbunden ist, um eine Steuerung der Empfangseinrichtung während einer vorherbestimmten Zeitdauer in Abhängigkeit von den Steuersignalen zu ermöglichen.

36. Schnittstelle einer Bildsteuerung gemäß Anspruch 35, bei der die die Dauer der Wiedergabe festlegende Vorrichtung ferner auf mindestens einen der Schalter anspricht, wenn die Nachrichten-Informationen zur Schau gestellt werden, um die Steuerung der Empfangseinrichtung zu unterbrechen, die dadurch die Wiedergabe der Zeitinformationen bewirkt.

37. Schnittstelle einer Bildsteuerung gemäß Anspruch 35, bei der die die Dauer der Wiedergabe festlegende Vorrichtung ferner auf mindestens einen der Schalter anspricht, wenn die Zeitinformationen zur Schau gestellt werden, um eine Steuerung der Empfangseinrichtung zu ermöglichen, die dadurch die Wiedergabe der Nachrichten-Informationen bewirkt.

38. Schnittstelle einer Bildsteuerung gemäß Anspruch 29, bei der die Zeitinformationen mindestens Zeit- und Datumsfunktionen einer Uhr darstellen.

39. Verfahren zur Steuerung der Wiedergabe auf einem Gerät, das normalerweise Zeitinformationen hervorbringt und zur Schau stellt und mehrere Schalter zur Einstellung der Zeitwiedergabe hat, an denen ständige Markierungen zur Anzeige der Schalterfunktionen angeordnet sind, sowie als codierte Nachricht gesendete Signale zu empfangen imstande ist, wobei das Verfahren die folgenden Arbeitsschritte enthält:

die als codierte Nachricht gesendeten Signale zu empfangen und zu decodieren, um Steuersignale und Nachrichten-Informationen abzuleiten, die Funktionen der Schalter in Abhängigkeit von den Steuersignalen abzuändern und Markierungen elektronisch auszuwählen und diese, neben den Schaltern angeordnet, die die neuen Schalterfunktionen anzeigen, zur Schau zu stellen, wodurch in Abhängigkeit von dem Empfang und der Decodierung der Signale der



codierten Nachricht die Schalterfunktionen geändert werden, durch die die Wiedergabe der abgeleiteten Nachrichten-Informationen ermöglicht wird.

40. Verfahren zur Steuerung der Wiedergabe auf einem Gerät gemäß Anspruch 39 mit den weiteren Arbeitsschritten :

In Abhängigkeit von den Steuersignalen die abgeleiteten Nachrichten-Informationen zu speichern,
einen vorherbestimmten alphanumerischen Text zur Schau zu stellen, der anzeigt, daß in Abhängigkeit von den Steuersignalen eine Nachricht an der Stelle der Zeitinformationen empfangen worden ist, und
eine hörbare Warnung in Abhängigkeit von den Steuersignalen hervorzurufen, wobei die empfangenen Nachrichten-Informationen gespeichert werden und eine hörbare und visuelle Anzeige vorgesehen wird.

41. Verfahren zur Steuerung der Wiedergabe auf einem Gerät gemäß Anspruch 40 mit den weiteren Arbeitsschritten :

einen ersten Schalter zu betätigen, um die Wiedergabe des vorherbestimmten alphanumerischen Textes und die Hervorbringung der hörbaren Warnung aufzuschieben und die Wiedergabe abgelegter Nachrichten-Informationen zu wählen, und
die abgelegten Nachrichten-Informationen zur Schau zu stellen, wobei diese zur Schau gestellt werden, wenn der erste Schalter unter den zahlreichen Schaltern betätigt wird.

42. Verfahren zur Steuerung der Wiedergabe auf einem Gerät gemäß Anspruch 40 mit den weiteren Arbeitsschritten :

einen zweiten Schalter zu betätigen, der die Wiedergabe des vorherbestimmten alphanumerischen Textes und die Hervorbringung der hörbaren Warnung aufschiebt, um die Wiedergabe der Zeitinformationen zu bewirken, die Schalter auf ihre ursprüngliche Funktionen rückzustellen und
die Wiedergabe der elektronisch gewählten Markierungen zu löschen, wodurch die Zeitinformationen wieder zur Schau gestellt werden und die Wiedergabe der abgelegten Nachrichten-Informationen beendet wird, sobald der zweite Schalter unter den zahlreichen Schaltern betätigt wird.

43. Verfahren zur Steuerung der Wiedergabe eines Gerätes gemäß Anspruch 42 mit den weiteren Arbeitsschritten :

einen zweiten Schalter zu betätigen, um von Hand die Wiedergabe abgelegter Nachrichten-Informationen anzuwählen, wenn Zeitinformationen zur Schau gestellt werden,
Markierungen elektronisch auszuwählen und diese, neben den Schaltern angeordnet, zur

Schau zu stellen, die entsprechend die neuen Schalterfunktionen anzeigen, und
die gespeicherten Nachrichten-Informationen zur Schau zu stellen, wobei diese zur Schau gestellt werden können, wenn die Zeitinformationen durch eine Betätigung des zweiten Schalters zur Schau gestellt werden.

44. Verfahren zur Steuerung der Wiedergabe auf einem Gerät gemäß Anspruch 40 mit den weiteren Arbeitsschritten :

in Abhängigkeit von den Steuersignalen eine vorherbestimmte Zeitspanne festzulegen,
die Funktionen der Schalter abzuändern und elektronisch Markierungen auszuwählen und diese, neben den Schaltern angeordnet, die die neuer Schalterfunktionen anzeigen, während der vorherbestimmten Zeitspanne zur Schau zu stellen,
eine hörbare Warnung während der vorherbestimmten Zeitspanne hervorzubringen,
einen vorherbestimmten alphanumerischen Text zur Schau zu stellen, der anzeigt, daß eine Nachricht während der vorherbestimmten Zeitspanne empfangen worden ist,
am Ende der vorherbestimmten Zeitspanne Zeitinformationen zur Schau zu stellen und
die Schalter auf ihre ursprünglichen Funktionen rückzustellen, wobei die Wiedergabe der abgelegten Nachrichten-Informationen selbsttätig beendet wird, wenn ein erster Schalter nicht zur Wiedergabe von Nachrichten-Informationen während der vorherbestimmten Zeitspanne betätigt wird.

45. Verfahren zur Steuerung der Wiedergabe eines Gerätes gemäß Anspruch 44 mit den weiteren Arbeitsschritten :

einen ersten Schalter zu betätigen, um die Wiedergabe der Nachrichten-Informationen während der vorherbestimmten Zeitspanne zu wählen, die vorherbestimmte Zeitspanne erneut einzuleiten und
die Nachrichten-Informationen zur Schau zu stellen, wobei durch eine Betätigung des ersten Schalters gespeicherte Nachrichten-Informationen während der vorherbestimmten Zeitspanne zur Schau gestellt werden können.

46. Verfahren zur Steuerung der Wiedergabe eines Gerätes gemäß Anspruch 44 mit den weiteren Arbeitsschritten :

einen zweiten Schalter zu betätigen, um die Wiedergabe eines vorherbestimmten alphanumerischen Textes aufzuschieben und die Wiedergabe der Zeitinformationen vor dem Ende der vorherbestimmten Zeitspanne anzuwählen,

die Schalter auf die ursprünglichen Funktionen rückzustellen und

die Wiedergabe der elektronisch erzeugten Markierungen zu löschen, womit die Wiedergabe der



abgelegten Nachrichten-Informationen während der vorherbestimmten Zeitspanne beendet wird, sobald der zweite Schalter betätigt wird.

Revendications

1. Montage d'interface de commande par touches pour un composant normalement engendrant et affichant une information de temps, le composant ayant une pluralité de touches pour commander l'affichage du temps, les touches comprenant des signes indicateurs permanents, de position adjacente aux touches, pour indiquer les fonctions des touches, le composant étant, de plus, apte à recevoir des signaux émis de message codés, ledit montage comprenant :

- un moyen récepteur pour recevoir et décoder les signaux émis de message codés pour extraire des signaux de commande et des informations ;
- un moyen pour engendrer de façon interne de l'information de temps et un moyen pour afficher celle-ci ;
- une pluralité d'entrées de commande ; et
- un moyen contrôleur de touches comprenant un moyen de commande par les entrées couplé à ladite pluralité d'entrées de commande et, de plus, couplé audit moyen engendrant l'information de temps et audit moyen récepteur pour permettre la commande dudit moyen engendrant l'information de temps et dudit moyen récepteur par lesdites entrées de commande, ledit moyen contrôleur de touches permettant la commande dudit moyen récepteur en réponse aux signaux de commande.

2. Le montage d'interface de commande par touches selon la revendication 1 où ladite pluralité d'entrées de commande est couplée à la pluralité de touches.

3. Montage d'interface de commande par touches selon la revendication 2 où les signaux émis de message codés comprennent une signalisation d'appel sélectif et où ledit moyen récepteur comprend :

- une partie réceptrice pour la réception et la démodulation des signaux émis de message codés pour extraire l'information de signalisation d'appel sélectif et de message ;
- un moyen d'identification pour stocker une information prédéterminée d'identification de composant ; et
- un moyen décodeur couplé audit moyen d'identification et commandé par l'information de signalisation d'appel sélectif pour extraire des signaux de commande quand l'information de signalisation d'appel sélectif coïncide avec l'information d'identification de composant prédéterminée.

4. Le montage d'interface de commande par touches selon la revendication 3 où ledit moyen décodeur comprend, de plus, un moyen pour engendrer un

signal d'alerte couplé audit moyen contrôleur de touches et ledit moyen récepteur comprend, de plus, un moyen de fourniture d'alerte couplé audit moyen contrôleur de touches, ledit moyen contrôleur de touches effectuant la fourniture du signal d'alerte en réponse aux signaux de commande.

5. Montage d'interface de commande par touches selon la revendication 4 où le signal d'alerte fourni est audible.

6. Montage d'interface de commande par touches selon la revendication 4 où ledit moyen décodeur est commandé par ledit moyen de commande par les entrées pour interrompre le signal d'alerte en réponse à l'actionnement de l'une parmi la pluralité de touches.

7. Le montage d'interface de commande par touches selon la revendication 3 où ledit moyen récepteur comprend, de plus, un moyen mémoire couplé à ladite partie réceptrice et commandé par ledit moyen décodeur pour stocker l'information d'alerte en réponse aux signaux de commande.

8. Le montage d'interface de commande par touches selon la revendication 7 où ledit moyen mémoire est, de plus, commandé par ledit moyen décodeur qui est commandé par ledit moyen contrôleur de touches pour effectuer la fourniture de l'information d'alerte stockée en réponse à l'actionnement de l'une par la pluralité de touches.

9. Le montage d'interface de commande par touches selon la revendication 2 où ledit moyen contrôleur de touches comprend, de plus, un moyen engendrant une durée d'action de touche pour permettre la commande dudit moyen récepteur pendant une durée prédéterminée en réponse aux signaux de commande.

10. Le montage d'interface de commande par touches selon la revendication 9 où ledit moyen engendrant une durée d'action de touche est, de plus, commandé par au moins une parmi la pluralité de touches quand l'information d'alerte est fournie pour interrompre la commande dudit moyen récepteur, effectuant par là l'affichage d'une information de temps.

11. Le montage d'interface de commande par touches selon la revendication 9 où ledit moyen engendrant la durée d'action de touche est, de plus, commandé par au moins une parmi la pluralité de touches quand une information de temps est affichée, pour effectuer l'activation de la commande dudit moyen récepteur, effectuant par là la fourniture de l'information d'alerte.

12. Le montage d'interface de commande par touches selon la revendication 1 où l'information de temps représente au moins des fonctions montre de temps et date.

13. Le montage d'interface de commande par touches selon la revendication 1 où le composant peut être porté au poignet.



14. Montage d'interface de commande d'affichage pour un composant normalement engendrant et affichant une information de temps, le composant ayant une pluralité de touches pour commander l'affichage du temps, les touches comprenant des signes indicateurs permanents, de position adjacente aux touches, pour indiquer les fonctions des touches, le composant étant, de plus, apte à recevoir des signaux émis de message codés, ledit montage comprenant :

un moyen récepteur pour recevoir et décoder les signaux émis de message codés pour extraire des signaux de commande et des informations ;
un moyen pour engendrer de façon interne de l'information de temps et un moyen pour afficher celle-ci ;

un moyen de commande par les entrées couplé à la pluralité de touches et, de plus, couplé audit moyen engendrant l'information de temps et audit moyen récepteur pour permettre la commande dudit moyen engendrant l'information de temps et dudit moyen récepteur par lesdites touches, ledit moyen de commande par les entrées permettant la commande dudit moyen récepteur en réponse aux signaux de commande ;

un moyen de choix d'information couplé audit moyen engendrant l'information de temps et audit moyen récepteur pour choisir l'affichage d'une information de temps et de l'information extraite, ledit moyen de choix d'information étant commandé par ledit moyen de commande par les entrées pour choisir l'affichage de l'information extraite en réponse aux signaux de commande ;
et

un moyen d'interface d'afficheur couplé audit moyen afficheur et commandé par ledit moyen de choix d'information pour effectuer l'affichage d'une information choisie.

15. Montage d'interface de commande d'affichage selon la revendication 14 où l'information extraite affichée en réponse aux signaux de commande est extraite des signaux émis de message codés.

16. Montage d'interface de commande d'affichage selon la revendication 15 où les signaux émis de message codés comprennent au moins de la signalisation d'appel sélectif et une information de message et où ledit moyen récepteur comprend :

une partie réceptrice pour recevoir et démoduler les signaux émis de message codés pour extraire la signalisation d'appel sélectif et l'information de message ;

un moyen d'identification pour stocker une information prédéterminée d'identification de composant ; et

un moyen décodeur couplé audit moyen d'identification et commandé par l'information de signalisation d'appel sélectif pour extraire les signaux de commande quand l'information de signalisa-

tion d'appel sélectif coïncide avec l'information prédéterminée d'identification de composant.

17. Montage d'interface de commande d'affichage selon la revendication 16 où ledit moyen récepteur comprend, de plus, un moyen mémoire couplé à ladite partie réceptrice et commandé par ledit moyen décodeur pour stocker l'information de message en réponse aux signaux de commande.

18. Montage d'interface de commande d'affichage selon la revendication 17 où ledit moyen de mémoire est, de plus, commandé par le moyen décodeur qui est commandé par ledit moyen de commande par les entrées pour effectuer l'affichage de l'information de message stockée en réponse à l'actionnement de l'une parmi la pluralité de touches.

19. Le montage d'interface de commande d'affichage selon la revendication 14 où ledit moyen de choix d'information choisit, de façon électronique, des signes indicateurs affichés sur ledit moyen afficheur, de position adjacente à la pluralité de touches, indiquant les nouvelles fonctions des touches activées en réponse aux signaux de commande.

20. Le montage d'interface de commande d'affichage selon la revendication 19 où ledit moyen de choix d'information est apte à choisir des signes indicateurs multiples affichés de façon sélective sur ledit moyen afficheur et de position adjacente à au moins une parmi la pluralité de touches, indiquant les fonctions des touches activées de façon sélective en réponse à l'actionnement de la touche quand l'information de message est affichée.

21. Le montage d'interface de commande d'affichage selon la revendication 16 où ledit moyen décodeur comprend, de plus, un moyen pour engendrer un signal d'alerte couplé audit moyen de choix d'information et ledit moyen récepteur comprend, de plus, un moyen de fourniture d'alerte couplé audit moyen de choix d'information, ledit moyen de choix d'information effectuant la fourniture du signal d'alerte en réponse aux signaux de commande.

22. Le montage d'interface de commande d'affichage selon la revendication 21 où le signal d'alerte fourni est audible.

23. Le montage d'interface de commande d'affichage selon la revendication 21 où ledit moyen décodeur est commandé par ledit moyen de commande par les entrées pour interrompre le signal d'alerte en réponse à l'actionnement de l'une parmi la pluralité de touches.

24. Le montage d'interface de commande d'affichage selon la revendication 16 où ledit moyen contrôleur d'afficheur comprend, de plus, un moyen engendrant une durée d'affichage couplé audit moyen de commande par les entrées pour permettre la commande dudit moyen récepteur pendant une durée prédéterminée en réponse aux signaux de commande.

25. Le montage d'interface de commande d'affi-



chage selon la revendication 24 où ledit moyen engendrant la durée d'affichage est, de plus, commandé par au moins une parmi la pluralité de touches quand l'information de message est affichée, pour interrompre la commande dudit moyen récepteur, effectuant par là l'affichage d'une information de temps.

26. Le montage d'interface de commande d'affichage selon la revendication 24 où ledit moyen engendrant la durée d'affichage est, de plus, commandé par au moins une parmi la pluralité de touches quand une information de temps est affichée, pour effectuer l'activation de la commande dudit moyen récepteur, effectuant par là l'affichage de l'information de message.

27. Le montage d'interface de commande d'affichage selon la revendication 14 où l'information de temps représente au moins les fonctions montre de temps et de date.

28. Le montage d'interface de commande d'affichage selon la revendication 14 où le composant peut être porté au poignet.

29. Montage d'interface de commande d'affichage pour un composant porté au poignet normalement engendrant et affichant une information de temps, le composant ayant une pluralité de touches pour commander l'affichage du temps, les touches comprenant des signes indicateurs permanents, de position adjacente aux touches, pour indiquer les fonctions des touches, le composant étant, de plus, apte à recevoir des signaux émis de message codés comprenant de l'information de signalisation d'appel sélectif et de message, ledit montage comprenant :

un moyen récepteur comprenant une partie réceptrice, un moyen d'identification et un moyen décodeur, ladite partie réceptrice pour recevoir et démoduler les signaux émis de message codés pour extraire l'information de signalisation d'appel sélectif et de message, ledit moyen d'identification pour stocker une information prédéterminée d'identification de composant, et ledit moyen décodeur couplé audit moyen d'identification et commandé par l'information de signalisation d'appel sélectif pour extraire des signaux de commande quand la signalisation d'appel sélectif coïncide avec l'information prédéterminée d'identification de composant ;

un moyen pour engendrer de façon interne de l'information de temps et un moyen pour afficher celle-ci ;

un moyen de commande par les entrées couplé à la pluralité de touches et, de plus, couplé audit moyen engendrant l'information de touches et audit moyen récepteur pour permettre la commande dudit moyen engendrant l'information de temps et dudit moyen récepteur par lesdites touches, ledit moyen de commande par les entrées permettant la commande dudit moyen

récepteur en réponse aux signaux de commande ;

un moyen de choix d'information couplé audit moyen engendrant l'information de temps et audit moyen récepteur pour choisir l'affichage d'une information de temps et de l'information de message, ledit moyen de choix d'information commandé par ledit moyen de commande par les entrées pour choisir l'information de message en réponse aux signaux de commande, ledit moyen de choix d'information choisissant, de plus, de façon électronique, des signes indicateurs affichés sur ledit moyen afficheur, de position adjacente à la pluralité de touches, indiquant les nouvelles fonctions des touches activées en réponse aux signaux de commande ; et un moyen d'interface d'afficheur couplé audit moyen afficheur et commandé par ledit moyen de choix d'information pour effectuer l'affichage d'une information choisie.

30. Le montage d'interface de commande d'affichage selon la revendication 29 où ledit moyen récepteur comprend, de plus, un moyen mémoire couplé à ladite partie réceptrice et commandé par le moyen décodeur pour stocker l'information de message en réponse aux signaux de commande.

31. Le montage d'interface de commande d'affichage selon la revendication 30 où ledit moyen mémoire est, de plus, commandé par ledit moyen décodeur qui est commandé par les entrées pour effectuer l'affichage de l'information de message stockée en réponse à l'actionnement de l'une parmi la pluralité de touches.

32. Le montage d'interface de commande d'affichage selon la revendication 29 où ledit moyen décodeur comprend, de plus, un moyen pour engendrer un signal d'alerte couplé audit moyen de choix d'information et ledit moyen récepteur comprend, de plus, un moyen de fourniture d'alerte couplé audit moyen de choix d'information, ledit moyen de choix d'information effectuant la fourniture du signal d'alerte en réponse aux signaux de commande.

33. Le montage d'interface de commande d'affichage selon la revendication 32 où le signal d'alerte fourni est audible.

34. Le montage d'interface de commande d'affichage selon la revendication 32 où ledit moyen décodeur est commandé par ledit moyen de commande par les entrées pour interrompre le signal d'alerte en réponse à l'actionnement de l'une parmi la pluralité de touches.

35. Le montage d'interface de commande d'affichage selon la revendication 29 où ledit moyen contrôleur d'afficheur comprend, de plus, un moyen engendrant une durée d'affichage couplé audit moyen de commande par les entrées pour activer la commande dudit moyen récepteur pendant une durée prédéterminée en réponse aux signaux de



commande.

36. Le montage d'interface de commande d'affichage selon la revendication 35 où ledit moyen engendrant la durée d'affichage est, de plus, commandé par au moins l'une parmi la pluralité de touches quand l'information de message est affichée, pour interrompre la commande du moyen récepteur, effectuant par là l'affichage d'une information de temps.

37. Le montage d'interface de commande d'affichage selon la revendication 35 où ledit moyen engendrant la durée d'affichage est, de plus, commandé par au moins l'une parmi la pluralité de touches quand une information de temps est affichée, pour effectuer l'activation de la commande dudit moyen récepteur, effectuant par là l'affichage de l'information de message.

38. Le montage d'interface de commande d'affichage selon la revendication 29 où l'information de temps représente au moins des fonctions montre de temps et de date.

39. Méthode de commande de l'affichage sur un composant normalement engendrant et affichant une information de temps, le composant ayant une pluralité de touches pour commander l'affichage du temps, les touches comprenant des signes indicateurs permanents, de position adjacente aux touches, pour indiquer les fonctions des touches, le composant étant, de plus, apte à recevoir des signaux émis de message codés, ladite méthode comprenant les étapes de :

recevoir et décoder les signaux émis de message codés pour extraire des signaux de commande et de l'information de message ;
modifier les fonctions des touches en réponse aux signaux de commande ; et
choisir, de façon électronique, des signes indicateurs et afficher ceux-ci selon une position adjacente aux touches, indiquant les nouvelles fonctions des touches, ce qui fait qu'en réponse à la réception et au décodage des signaux de message codés, les fonctions des touches changent ce qui permet l'affichage de l'information de message extraite.

40. La méthode de commande de l'affichage sur un composant selon la revendication 39 comprenant, de plus, les étapes de :

stocker l'information de message extraite en réponse aux signaux de commande ;
afficher un texte alphanumérique prédéterminé indiquant qu'un message a été reçu, à la place de l'information de temps, en réponse aux signaux de commande ; et
engendrer une alerte audible en réponse aux signaux de commande, ce qui fait que l'information de message reçue est stockée et que des indications audibles et visuelles sont fournies.

41. La méthode de commande de l'affichage sur

un composant selon la revendication 40 comprenant, de plus, les étapes de :

actionner une première touche pour suspendre l'affichage du texte alphanumérique prédéterminé et la création de l'alerte audible et choisir l'affichage d'une information de message stockée ; et
afficher l'information de message stockée, ce qui fait que l'information de message stockée est affichée lorsque la première touche de la pluralité de touches est actionnée.

42. La méthode de commande de l'affichage sur un composant selon la revendication 40 comprenant, de plus, les étapes de :

actionner une seconde touche suspendant l'affichage du texte alphanumérique prédéterminé et la création de l'alerte audible pour effectuer l'affichage d'une information de temps ;
restaurer les touches dans les fonctions d'origine ; et
annuler l'affichage des signes indicateurs choisis de façon électronique, ce qui fait qu'une information de temps est à nouveau affichée et l'affichage de l'information de message stockée se termine lorsque la seconde touche de la pluralité de touches est actionnée.

43. La méthode de commande de l'affichage d'un composant selon la revendication 42 comprenant, de plus, les étapes de :

actionner une seconde touche pour choisir manuellement l'affichage de l'information de message stockée quand une information de temps est affichée ;
choisir, de façon électronique, des signes indicateurs et afficher ceux-ci selon une position adjacente aux touches, indiquant les nouvelles fonctions des touches en réponse à cela ; et
afficher l'information de message stockée, ce qui fait que l'information de message stockée peut être affichée quand une information de temps est affichée, en actionnant la seconde touche.

44. La méthode de commande de l'affichage sur un composant selon la revendication 40 comprenant, de plus, les étapes de :

engendrer une période de temps prédéterminée en réponse aux signaux de commande ;
modifier les fonctions des touches et choisir, de façon électronique, des signes indicateurs et afficher ceux-ci selon une position adjacente aux touches, indiquant les nouvelles fonctions des touches pendant la période de temps prédéterminée ;
engendrer une alerte audible pendant la période de temps prédéterminée ;
afficher un texte alphanumérique prédéterminé indiquant qu'un message a été reçu pendant la période de temps prédéterminée ;
afficher une information de temps à la fin de la



période de temps prédéterminée ; et
restaurer les touches dans les fonctions d'origine,
ce qui fait que l'affichage de l'information de mes-
sage stockée se termine automatiquement quand
une première touche n'est pas actionnée pour
afficher l'information de message pendant la
période de temps prédéterminée.

5

45. La méthode de commande de l'affichage d'un
composant selon la revendication 44 comprenant, de
plus, les étapes de :

10

actionner une première touche pour choisir l'affi-
chage de l'information de message pendant la
période de temps prédéterminée ;

ré-armer la période de temps prédéterminée ; et
afficher l'information de message, ce qui fait que
l'information de message stockée peut être affi-
chée pendant la période de temps prédétermi-
née, en actionnant la première touche.

15

46. La méthode de commande de l'affichage d'un
composant selon la revendication 44 comprenant, de
plus, les étapes de :

20

actionner une seconde touche pour suspendre
l'affichage d'un texte alphanumérique prédéterminé
et choisir l'affichage de l'information de temps avant
la fin de la période de temps prédéterminée ; et

25

restaurer les touches dans les fonctions d'ori-
gine ;

annuler l'affichage des signes indicateurs engen-
drés de façon électronique, ce qui fait que l'affichage
de l'information de message stockée se termine pen-
dant la période de temps prédéterminée lorsque la
seconde touche est actionnée.

30

35

40

45

50

55

21

