


Description

This invention relates to the preparation of alkanol alkoxylates via the catalyzed addition reaction of alkylene oxides with alkanols.

5 Alkanol alkoxylates (or simply alkoxylates, as the terminology is alternatively applied herein) are known materials having utility, for instance, as solvents, surfactants, and chemical intermediates. Alkoxylates in which the alkyl group has a number of carbon atoms in the detergent-range, i.e., from about 8 to 20, are common components of commercial cleaning formulations for use in industry and in the home.

Under conventional practice, alkoxylates are typically prepared by the addition reaction of alkylene
10 oxides with alkanols. In the particular case of the preparation of an ethoxylate the addition of a number (n) of ethylene oxide molecules to a single alkanol molecule may be illustrated by the equation



wherein R is an alkyl group and n is an integer equal to or greater than one.

Alkoxylation reactions between alkylene oxides and alkanols are known to be necessarily carried out in the presence of a catalyst, which may be either of acidic or, preferably, basic character. Suitable basic
20 catalysts are recognized to include the soluble basic salts of the alkali metals of Group I of the Periodic Table, e.g., lithium, sodium, potassium, rubidium, and caesium, and the soluble basic salts of certain of the alkaline earth metals of Group II, e.g., barium, strontium and calcium.

European Patent Applications Publication Nos. 26,544, 26,546, and 26,547 describe alkoxylation reactions catalyzed by soluble basic calcium compounds. U.S. Patent No. 4,302,613 describes the use of
25 certain calcium compounds as co-catalysts in alkoxylation reactions.

Following an alkoxylation reaction carried out in the presence of a soluble catalyst, it is generally necessary to neutralize the reaction mixture, typically to a pH of about 5.0 to 7.0 by addition of an organic acid, usually acetic acid. Neutralization is required because the presence of a quantity of base sufficient to
30 catalyze the alkoxylation would otherwise tend to render the product chemically unstable.

Although the use of the soluble basic calcium catalysts in the preparation of alkoxylates via the reaction between alkanols and alkylene oxides is attractive for reasons including narrow-range distribution of numbers of alkylene oxide moieties per molecule in the alkoxylate product, good catalyst activity and
35 selectively, and negligible catalyst—and catalyst residue—toxicity, the product obtained after neutralization with acetic acid has physical properties which render it unacceptable for many applications. The product is found to be a semi-solid or gel-like alkoxylate product of high viscosity. The handling properties of this product are in sharp contrast to those of the liquid products of common conventional alkoxylation processes, and present substantial difficulties in storage, transportation, formulation, and application in detergent and other uses.

It has now surprisingly been found that alkoxylation reactions carried out in the presence of soluble
40 calcium compounds can be utilized to prepare alkoxylate products which remain fluid after neutralization of the resulting reaction mixture if propionic acid and/or benzoic acid is utilized for neutralization purposes.

Accordingly, the present invention provides a process for the preparation of alkanol alkoxylates which comprises reacting at least one alkanol having 8 to 18 carbon atoms with at least one alkylene oxide having
45 2 to 4 carbon atoms at alkaline pH in the presence of one or more soluble calcium compounds, and reducing the pH of the resulting alkoxylation mixture to 7 or below by addition thereto of an acid comprising propionic acid, benzoic acid, or a mixture of propionic and benzoic acids.

The reaction of the alkanol with the alkylene oxide is preferably carried out at a temperature in the range from 90 to 250°C. A more preferred range is from 130 to 210°C, while a temperature from 145 to 190°C
50 is still more preferred. Considered most preferred is a reaction temperature in the range from 155 to 175°C.

Although the pressure under which the alkoxylation reaction is conducted is not critical to the invention, a total pressure in the range from atmospheric pressure to 10^6 Pa (gauge) (150 psig) is preferred. Under preferred conditions of temperature and pressure, the alkanol reactant is generally liquid and the alkylene
55 oxide reactant a vapour. The reaction is then most conveniently conducted by contacting gaseous alkylene oxide with a liquid solution of the alkoxylation catalyst in the alkanol. Since, as is known, there is a danger of explosion in alkylene oxides maintained in concentrated form at elevated temperature and pressure, the partial pressure of the alkylene oxide in the vapour phase is preferably limited, for instance, to less than 4×10^5 Pa (60 psia), and this reactant is diluted with an inert gas such as nitrogen, for instance, to a vapour phase concentration of 50 percent or less. The reaction can, however, be safely accomplished at greater alkylene oxide concentration, greater total pressure and greater partial pressure of alkylene oxide if
60 suitable precautions, known to the art, are taken to manage the risks of explosion. A total pressure of from 2.8 to 7.6×10^5 Pa (gauge) (40 to 110 psig), with an alkylene oxide partial pressure of from 1 to 4×10^5 Pa (15 to 60 psia) is particularly preferred, while a total pressure of from 3.5 to 6×10^5 Pa (gauge) (50 to 90 psig), with an alkylene oxide partial pressure of from 1.4 to 3.5×10^5 Pa (20 to 50 psia) is considered more preferred.

65 It is particularly preferred for the alkanols having from 8 to 18 carbon atoms to be primary alcohols,

largely on the basis of rate of the alkoxylation reaction. For reasons relating to the utility of the product alkoxylates in detergent formulations, preference may be expressed for alkanols within further restricted carbon number ranges. Thus, alkanols in the C₉ to C₁₆ range are preferred reactants, while those in the C₉ to C₁₅ range are considered more preferred and those in the C₁₁ to C₁₄ range most preferred. Still further preference for reason of product utility may be stated for alkanol reactants in which greater than 50 percent, more preferably greater than 70 percent, and most preferably greater than 90 percent of the alkanol molecules are of linear (straight-chain) carbon structure. Mixtures containing a variety of such alkanols, differing, for instance, with respect to carbon number and branching in the carbon chain, are suitable for purposes of the process of the invention and are in most cases preferred because of commercial availability.

The alkylene oxide (epoxide) reactant utilized in the process of the invention comprises one or more alkylene oxides, including ethylene oxide, propylene oxide, and the 1,2- and 2,3-butylene oxides. Particularly preferred are those having 2 or 3 carbon atoms, i.e. ethylene oxide and propylene oxide, while the use of ethylene oxide is most preferred. Mixtures of alkylene oxides are suitable, in which case the product of the invention will be a mixed alkoxide.

The calcium compound is advantageously a soluble basic calcium compound. The calcium compound preferably acts as principal alkoxylation catalyst, although, if desired, the reaction can be principally catalyzed by another basic alkoxylation catalyst with the calcium present serving another function. If the alkoxylation is principally catalyzed by a calcium compound, addition may be made to the alkoxylation reaction mixture of either a calcium compound which is soluble and basic *per se* or a precursor which is converted to a soluble basic form of calcium upon interaction with the alkoxylation process reactants and/or the specified reaction activator. The calcium compound is described as soluble in the sense that it is soluble in a mixture of liquid alkanol reactant and alkoxylate product to the extent necessary to promote the desired reaction. In general, at least 0.05 percent by mole (%m) of the calcium compound, calculated on moles of total alkanol reactant, should be present for the desired catalytic effect. Preferably, the calcium compound is present in the reaction mixture in a quantity in the range 0.1 to 10% m calculated on alkanol, while a quantity in the range 0.5 to 6% m is more preferred and from 1 to 4% m is considered most preferred. Within the preferred ranges, the rate of the alkoxylation reaction tends to increase as the process is carried out with increasing quantities of catalyst. The catalyst is described as basic in the conventional sense, indicating that a hydrolyzed sample of an alkoxylation reaction mixture containing the catalyst in a catalytically-effective quantity (e.g., a 10% w solution of the reaction mixture in water) has a pH greater than 7.0. For purposes of the invention, the overall reaction mixture is of basic pH. Examples of specific soluble, basic calcium compounds suitable for introduction into the reaction mixture as catalysts include the reaction products of calcium with various alcohols (for instance, alcoholates such as calcium alkoxides and phenoxides), as well as ammoniate, amide, thiolate, thiophenoxide and nitride compounds. Preferred for use as catalyst (or catalyst precursor) are the alcoholates, while the alkoxides in particular are considered more preferred. Each alkoxy group of such alkoxides has a carbon number that is preferably in the range from 1 to 30, more preferably in the range from 1 to 6. The most preferred calcium alkoxides are the C₁ to C₃ alkoxides, i.e., calcium methoxide, ethoxide and propoxide. Representative of suitable calcium catalyst precursors which are not *per se* soluble and/or basic but which are converted into soluble, basic compounds in the alkoxylation reaction mixture are the thiocyanates, and carboxylates, such as the formate, acetate, oxalate, citrate, benzoate, laurate, and stearate.

The alkoxylation reaction promoted by a soluble basic compound of calcium has been found to be of particular advantage in view of its selectivity for a product having a narrow range of alkylene oxide adducts, that is, for a mixture of alkoxylate molecules in which a relatively large proportion have a number (n) of alkylene oxide adducts within a relatively narrow range of values. It is known that alkoxylate products having such a narrow-range distribution are preferred for use in detergent formulations. (e.g. UK Patent Specification No. 1,462,134). Narrow-range alkoxylates are also known to be particularly valuable as chemical intermediates in the synthesis of certain carboxylated alkyl poly-ethers (U.S. Patent No. 4,098,818) and of certain alkyl ether sulphates (UK Patent Specification No. 1,553,561).

The relative selectivity of an alkoxylation process for a narrow-range product can be quantitatively expressed in terms of an index value (Q), calculated according to the equation $Q = \bar{n} P^2$ wherein $\bar{n}$ is a mean average adduct number, determined as the ratio of the total moles of alkylene oxide reacted to form alkoxylate, to the total moles of alkanol either unreacted or reacted to form alkoxylate, and wherein P represents the highest selectivity of the reaction (in percent by weight) for alkoxylate product having any single common adduct number. (For instance, if the reaction product contained 10 percent by weight of alkoxylate molecules characterized by an adduct number of 5 and lesser quantities of molecules having any other single adduct number, then P for the reaction product would equal 10). Higher values of Q indicate a more selective process and a more narrow-range product. For the typical ethoxylate products of greatest commercial interest, conventional alkoxylation of alkanols promoted by basic alkali metal (e.g. sodium or potassium) containing catalysts yields alkoxylates characterized by a value for Q of approximately 500, while a reaction promoted by a soluble, basic compound of calcium yields products characterized by a value for Q of approximately 1000 to 1200. Alkoxylation processes employing basic barium and strontium compounds as disclosed in U.S. Patents Nos. 4,210,764, 4,223,164 and 4,239,917 European Patent

Applications Publications Nos. 0026544, 0026546, and 0026547 also yield products having values of Q in the range from about 1000 to 1200.

Alkoxylation of alkanols in the presence of calcium catalysts also has advantage over reactions utilizing alkali metal catalysts with respect to the preparation of alkoxyates containing low levels of unreacted alkanol.

In terms of processing procedures, the alkoxylation reaction is preferably carried out by mixing the catalyst with the liquid alkanol reactant and then contacting the resulting solution with gaseous alkylene oxide at the specified temperature and pressure. The solution is then brought to the desired temperature and, by addition of alkylene oxide, preferably together with an inert gas, to the desired pressure. Alkoxylation typically commences after an induction period of a few minutes to a few hours. As the alkylene oxide is taken up in the reaction additional alkylene oxide is added, conveniently at a rate which maintains an approximately constant reaction pressure. Addition of alkylene oxide and its reaction to alkoxyate is continued until the product reaches the average alkylene oxide adduct number desired for the particular process. Generally, although not necessarily, the invention is best utilized in the preparation of alkoxyates having an average adduct number in the range 1 to 15, expressed in terms of the total moles of alkylene oxide reacted per mole of alkanol. For reasons relating to utility of the alkoxyate in the broadest commercial applications the process is continued to yield a product having an adduct number that is preferably in the range 2 to 12, more preferably 3 to 10, most preferably 4 to 9. The time required to complete a process in accordance with the invention, when using as catalyst one or more soluble, basic calcium compounds, is dependent both upon the degree of alkoxylation that is desired (i.e., upon the average adduct number of the product) as well as upon the rate of the alkoxylation reaction. This reaction rate is, in turn, dependent upon such parameters as reaction temperature, pressure, and catalyst concentration in the reaction mixture. Under most preferred operating conditions, preparation of an alkoxyate having an average alkylene oxide adduct number of about 3 can typically be accomplished in from 1 to 1.5 hours, while preparation of a product having an average adduct number of about 10 would require about 2.5 to 4.5 hours. These reaction times are merely illustrative and may be substantially reduced by operation at the higher reaction temperatures and/or pressures, although often at the expense of a selectivity loss in the utilization of the reactants to the desired alkoxyate products.

Following the alkoxylation reaction between the alkanol and alkylene oxide reactants under conditions of alkaline pH and in the presence of the soluble calcium compound, the alkoxyate product mixture is neutralized by addition of an acid. As used herein, neutralization means decreasing the pH of the basic reaction mixture to a value which is equal to or less than 7. For purposes of the present invention, this acid comprises one or more compounds selected from the group consisting of propionic acid and benzoic acid. Use of one or both of the indicated acids for neutralization of the basic, calcium-containing reaction mixture has been found to be critical to the preparation of a product having desirable properties. For instance, neutralization of the reaction mixture with these acids yields a product having essentially the same low viscosity, high clarity, and low colour as are characteristic of the unneutralized mixture. However, if instead of the propionic or benzoic acids, other carboxylic acids, for example, formic, acetic, butyric, hexanoic, oxalic, tartaric and citric acids, are added to the same reaction mixture for neutralization purposes, the mixture thickens to a gel-like consistency and/or forms a precipitate. Moreover, such gel formation in the alkoxyate appears unique to the presence of calcium ions. Alkali metal, e.g., sodium and potassium, and other alkaline earth metals, e.g., barium and strontium, when present in alkoxylation mixtures do not give rise to similar gelation problems.

Apart from use of the specified acids, procedures suitable for the neutralization step of the invention are not found to be critical. In general, procedures as have been employed in the prior art to accomplish neutralization of basic alkoxylation reaction mixtures can also be employed in carrying out the invention. Preferably, the acid is mixed directly with the basic reaction mixture, after the mixture has first been cooled to a temperature below that at which the alkoxylation was conducted, for instance, a temperature in the range from 20°C to 100°C. As in conventional practice, the quantity of acid is that sufficient to effectively inactivate the basic alkoxylation catalyst. Neutralization to a pH in the range from 5 to 7 is preferred. Neutralization to a pH in the range from 5 to 7 is preferred, while a pH in the range from 5.5 to 6.5 is considered most preferred.

The present invention is most effective when essentially only the propionic and/or benzoic acids are added to the alkoxylation reaction mixture for neutralization purposes. However, the gel and precipitate inhibiting properties of these acids are also at least partially effective when employed in mixtures with other acids, e.g., a mixture containing equal quantities by weight of propionic acid and acetic acid.

In terms of distinctions in the quality of the neutralized alkoxylation product, the process of the invention is applied to best advantage when the specified acid is added to an alkoxylation mixture containing more than about 200 ppmw (parts per million by weight) calcium, particularly from 500 to 10,000 ppmw calcium, and most particularly 1,000 to 5,000 ppmw calcium.

The invention is further illustrated by the following examples and by reference to the accompanying drawing which shows variation in viscosity of calcium-containing alkanol ethoxyate neutralized in accordance with the invention with propionic acid and for comparison purposes with acetic acid.

Example 1

A process according to the invention was conducted under the following procedures:

An alkoxylation reaction was carried out in a 300 ml stainless steel autoclave reactor. The alkanol reactant was a "Neodol" 23 Alcohol (trademark), characterized as a mixture of primary, 80% linear (20% branched) alkanols containing twelve and thirteen carbon atoms (about 40% by mole C_{12} , 60% by mole C_{13}). Initially, the liquid alkanol reactant was dried to a water content about 40 ppm (as indicated by Karl Fischer water analysis) by sparging nitrogen at 130°C for 35 minutes. To 65 grams (335 millimoles) of the dried alkanol was added 1.6 grams (10 millimoles) of calcium ethoxide as alkoxylation catalyst. The resulting catalyst solution in the alkanol reactant was sparged with nitrogen at 130°C for 30 minutes. The solution was then transferred to the reactor under a nitrogen atmosphere, and the system was sealed, heated to 170°C and pressurized with nitrogen and alkylene oxide reactant, in this case ethylene oxide, to a total pressure of 4.8×10^5 Pa (gauge) (70 psig), 3.8×10^5 Pa (55 psia) nitrogen and 2×10^5 Pa (30 psia) ethylene oxide. Alkoxylation (ethoxylation) commenced immediately and the temperature was maintained at 170°C. Ethylene oxide was added to the reactor system at a rate sufficient to maintain substantially constant reaction pressure. About 96 grams (2.17 moles) of ethylene oxide was added over a three hour period. The reactor was then maintained at 170°C for an additional 30 minutes without addition of further ethylene oxide, to consume unreacted ethylene oxide in the system.

Following the alkoxylation step, 100 grams of the reaction product mixture was cooled to about 70°C and transferred under nitrogen to a sample bottle. This mixture contained in solution about 2500 parts per million by weight (ppmw) of calcium ion. Titration of the product mixture with aqueous hydrochloric acid indicated a content of 0.107 milliequivalent of calcium ion per gram of alkoxyate. Neutralization was accomplished by mixing the 100 grams of alkoxylation product with 10.7 milliequivalents of propionic acid. The neutralized mixture was maintained at 70°C for thirty minutes and then cooled to about 25°C. Hydrolysis of an aliquot of the neutralized mixture at 25°C indicated a pH of about 7.0.

The product of this process was a clear, nearly colourless solution characterized by low viscosity and an absence of precipitate formation.

Example 2

The procedures of Example 1 were again followed, in this case, however, utilizing benzoic acid in the place of propionic acid in the neutralization step. Again the product was a clear, essentially colourless solution, without noticeable precipitate, having acceptably low viscosity.

Comparative Examples

The procedures were again followed with substitution in the neutralization step of a number of other carboxylic acids the use of which is not in accordance with the invention. The use of acetic acid resulted in an apparently homogeneous semi-solid or gelatinous product. Butyric acid and hexanoic acid were responsible for production of a two phase mixture containing roughly equal quantities of a lower gel phase and an upper liquid phase. Formic acid, oxalic acid, and carbonic acid each resulted in formation of a white precipitate.

Example 3

A series of experiments was carried out to quantify aspects of the invention relating to viscosity of neutralized calcium-containing alkoxyate products. Alkoxylation reaction mixtures containing catalytic quantities of calcium in solution and having alkaline pH were simulated by addition of various levels of calcium ethoxide to a previously-prepared ethoxyate product. This ethoxyate product has been prepared by reaction between the "Neodol" 23 Alcohol and an average of 6.5 moles of ethylene oxide per mole of alkanol, in the presence of a potassium hydroxide catalyst, followed by neutralization with acetic acid. Although the calcium-containing ethoxyate mixtures thus obtained also contained a residue of both potassium (about 1040 ppmw) and acetate ions, this was determined not to have significant influence upon the desired comparisons.

After addition of the calcium ethoxide to the ethoxyate, the resulting mixtures were sparged with nitrogen at 130°C for one hour to remove ethanol formed by transalcoholysis reaction. The liquid mixtures were then cooled to 50°C and neutralized by addition with mixing of either propionic acid (according to the invention) or acetic acid (comparative, not according to the invention). Acid was added until the pH of a hydrolyzed aliquot decreased to 7.0 (± 0.2).

The absolute viscosity, in Pa.s, of each resulting neutralized, calcium-containing alkoxyate mixture was determined at one or more temperatures. Results are presented in the following Table I and also in the attached drawing.

TABLE I

Experiment number	Calcium ion concentration (ppmw)	Acid used in neutralization	Temperature of viscosity measurement (°C)	Absolute viscosity (Pa.s)
0	0	acetic	25	0.110
10			38	0.031
1	250	acetic	38	0.195
2	500	acetic	38	0.225
15	3	acetic	38	0.420
4	1250	acetic	38	0.475
20	5	acetic	25	4.500
			38	0.590
6	750	propionic	25	0.126
25	7	propionic	38	0.060
8	2500	propionic	25	0.310
30			38	0.081

The influence of both the calcium ion concentration and the acid utilized for neutralization on the viscosity of the resulting ethoxylate mixture are readily apparent from the comparisons presented in the Table and the drawing. Particularly notable are the benefits provided by neutralization with propionic acid of ethoxylation mixtures having a concentration of calcium ion in excess of about 1000 ppmw, as would typically result from the use of a calcium compound as an alkoxylation catalyst. At such levels of calcium, the viscosities of the propionic acid neutralized ethoxylates are roughly an order of magnitude less than those neutralized with acetic acid.

Example 4

This example illustrates that the presence of calcium ion and the nature of the acid used for neutralization have a like effect upon the viscosity of different alkoxyate mixtures. Several different alkoxyate products were prepared by reacting substantially primary and linear alkanols of several carbon number ranges with amounts of ethylene oxide, in different average molar ratios of ethylene oxide to alkanol (i.e., n in formula III herein). As in Example 3, these reactions were conducted using potassium hydroxide as catalyst and acetic acid to neutralize the reaction mixture. Calcium ethoxide was added to each of the different ethoxylates to simulate a calcium-containing alkoxylation mixture of alkaline pH. Each mixture contained 2500 ppmw of calcium ion. Following addition of the calcium ethoxide, the mixtures were sparged with nitrogen at 130°C for one hour, and cooled to 50°C. Each mixture was divided into equal portions; one of which was neutralized with acetic acid while the other was neutralized with propionic acid in accordance with the invention. Sufficient acid was added so that the pH of a hydrolyzed aliquot of the neutralized mixture had a pH of 7.0 (± 0.2). Viscosities were determined at 38°C. Results are summarized in Table II.

TABLE II
Ethoxylate preparation

(16)

	Alkanol carbon No.	Average value of n	Calcium ion concentration (ppmw)	Acid	Viscosity at 38°C (Pa.s)
5	12 to 15	3	2500	propionic	0.017
				acetic	3.500
10	12 to 15	9	2500	propionic	0.440
				acetic	2.440
15	12 to 15	12	2500	propionic	0.375
				acetic	1.162
	9 to 11	6	2500	propionic	0.177
20				acetic	1.120
	14 and 15	7	2500	propionic	0.242
25				acetic	0.770
	14 and 15	13	2500	propionic	0.550
				acetic	6.800
30	12 and 13	3	2500	propionic	0.180
				acetic	1.600

35 Claims

1. A process for the preparation of alkanol alkoxylates by reacting at least one alkanol having 8 to 18 carbon atoms with at least one alkylene oxide having 2 to 4 carbon atoms at alkaline pH in the presence of one or more soluble calcium compounds, and reducing the pH of the resulting alkoxylation mixture to 7 or below by addition thereto of an acid characterized in that propionic acid, benzoic acid or a mixture of propionic and benzoic acids is used.

2. A process according to claim 1, characterized in that the acid is propionic acid.

3. A process according to claim 1 or claim 2, characterized in that the alkanol or alkanols have 9 to 15 carbon atoms.

4. A process according to any of claims 1 to 3, characterized in that alkylene oxide or oxides have 2 or 3 carbon atoms.

5. A process according to any of claims 1 to 4, characterized in that the alkylene oxide is ethylene oxide.

6. A process according to any one of claims 1 to 5 characterized in that the calcium compound is a soluble, basic calcium compound.

50

Patentansprüche

1. Ein Verfahren zur Herstellung von Alkanolalkoxylaten durch Umsetzen mindestens 1 Alkanols mit 8 bis 18 Kohlenstoffatomen mit mindestens einem Alkylenoxid mit 2 bis 4 Kohlenstoffatomen bei alkalischem pH-Wert in Gegenwart einer oder mehrerer löslicher Calciumverbindungen, und durch Herabsetzung des pH-Wertes der erhaltenen Alkoxylatmischung auf den Wert 7 oder darunter durch Zugabe einer Säure, dadurch gekennzeichnet, daß Propionsäure, Benzoesäure oder eine Mischung aus Propionsäure und Benzoesäure verwendet werden.

2. Ein Verfahren gemäß Anspruch 1, dadurch gekennzeichnet, daß die Säure Propionsäure ist.

3. Ein Verfahren gemäß Anspruch 1 oder 2, dadurch gekennzeichnet, daß das Alkanol bzw. die Alkanole 9 bis 15 Kohlenstoffatome aufweist (aufweisen).

4. Ein Verfahren gemäß einem der Ansprüche 1 bis 3, dadurch gekennzeichnet, daß das Alkylenoxid oder die Alkylenoxide 2 oder 3 Kohlenstoffatomen aufweisen.

5. Ein Verfahren gemäß einem der Ansprüche 1 bis 4, dadurch gekennzeichnet, daß das Alkylenoxid Äthylenoxid ist.

TABLE II
Ethoxylate preparation

(16)

	Alkanol carbon No.	Average value of n	Calcium ion concentration (ppmw)	Acid	Viscosity at 38°C (Pa.s)
5	12 to 15	3	2500	propionic	0.017
				acetic	3.500
10	12 to 15	9	2500	propionic	0.440
				acetic	2.440
15	12 to 15	12	2500	propionic	0.375
				acetic	1.162
	9 to 11	6	2500	propionic	0.177
20				acetic	1.120
	14 and 15	7	2500	propionic	0.242
25				acetic	0.770
	14 and 15	13	2500	propionic	0.550
				acetic	6.800
30	12 and 13	3	2500	propionic	0.180
				acetic	1.600

35 Claims

1. A process for the preparation of alkanol alkoxylates by reacting at least one alkanol having 8 to 18 carbon atoms with at least one alkylene oxide having 2 to 4 carbon atoms at alkaline pH in the presence of one or more soluble calcium compounds, and reducing the pH of the resulting alkoxylation mixture to 7 or below by addition thereto of an acid characterized in that propionic acid, benzoic acid or a mixture of propionic and benzoic acids is used.

2. A process according to claim 1, characterized in that the acid is propionic acid.

3. A process according to claim 1 or claim 2, characterized in that the alkanol or alkanols have 9 to 15 carbon atoms.

4. A process according to any of claims 1 to 3, characterized in that alkylene oxide or oxides have 2 or 3 carbon atoms.

5. A process according to any of claims 1 to 4, characterized in that the alkylene oxide is ethylene oxide.

6. A process according to any one of claims 1 to 5 characterized in that the calcium compound is a soluble, basic calcium compound.

50

Patentansprüche

1. Ein Verfahren zur Herstellung von Alkanolalkoxylaten durch Umsetzen mindestens 1 Alkanols mit 8 bis 18 Kohlenstoffatomen mit mindestens einem Alkylenoxid mit 2 bis 4 Kohlenstoffatomen bei alkalischem pH-Wert in Gegenwart einer oder mehrerer löslicher Calciumverbindungen, und durch Herabsetzung des pH-Wertes der erhaltenen Alkoxyatmischung auf den Wert 7 oder darunter durch Zugabe einer Säure, dadurch gekennzeichnet, daß Propionsäure, Benzoesäure oder eine Mischung aus Propionsäure und Benzoesäure verwendet werden.

2. Ein Verfahren gemäß Anspruch 1, dadurch gekennzeichnet, daß die Säure Propionsäure ist.

3. Ein Verfahren gemäß Anspruch 1 oder 2, dadurch gekennzeichnet, daß das Alkanol bzw. die Alkanole 9 bis 15 Kohlenstoffatome aufweist (aufweisen).

4. Ein Verfahren gemäß einem der Ansprüche 1 bis 3, dadurch gekennzeichnet, daß das Alkylenoxid oder die Alkylenoxide 2 oder 3 Kohlenstoffatomen aufweisen.

5. Ein Verfahren gemäß einem der Ansprüche 1 bis 4, dadurch gekennzeichnet, daß das Alkylenoxid Äthylenoxid ist.



6. Ein Verfahren gemäß einem der Ansprüche 1 bis 5, dadurch gekennzeichnet, daß die Calciumverbindung eine lösliche, basische Calciumverbindung ist.

Revendications

5

1. Un procédé pour la préparation d'alcoylates d'alcanol en faisant réagir au moins un alcanol ayant 8 à 12 atomes de carbone avec au moins un oxyde d'éthylène ayant 2 à 4 atomes de carbone à un pH alcalin en présence d'un ou plusieurs composés solubles du calcium et en abaissant le pH du mélange d'alcoylation résultant à 7 ou au-dessous par addition d'un acide à ce mélange, caractérisé en ce qu'on

10

utilise de l'acide propionique, de l'acide benzoïque ou un mélange des acides propionique et benzoïque.

2. Un procédé selon la revendication 1, caractérisé en ce que l'acide est de l'acide propionique.



3. Un procédé selon la revendication 1 ou la revendication 2, caractérisé en ce que l'alcanol ou les alcanols ont 9 à 15 atomes de carbone.

15

4. Un procédé selon l'une quelconque des revendications 1 à 3, caractérisé en ce que l'oxyde ou les oxydes d'alcoylène ont 2 ou 3 atomes de carbone.

5. Un procédé selon l'une quelconque des revendications 1 à 4, caractérisé en ce que l'oxyde d'alcoylène est de l'oxyde d'éthylène.

6. Un procédé selon l'une quelconque des revendications 1 à 5, caractérisé en ce que le composé du calcium est un composé basique soluble du calcium.

20

25

30

35

40

45

50

55

60

65

