

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
22 March 2001 (22.03.2001)

PCT

(10) International Publication Number
WO 01/19464 A1

(51) International Patent Classification⁷: A63B 37/14

(21) International Application Number: PCT/US00/25402

(22) International Filing Date:
14 September 2000 (14.09.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/398,917 16 September 1999 (16.09.1999) US
09/398,919 16 September 1999 (16.09.1999) US

(71) Applicant: CALLAWAY GOLF COMPANY [US/US];
2285 Rutherford Road, Carlsbad, CA 92008 (US).

(72) Inventor: OGG, Steven, S.; 979 Turnstone Road, Carlsbad, CA 92009 (US).

(74) Agent: CATANIA, Michael, A.; 2285 Rutherford Road, Carlsbad, CA 92008 (US).

(81) Designated States (*national*): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— With international search report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A GOLF BALL WITH AN AERODYNAMIC SURFACE ON A POLYURETHANE COVER



(57) Abstract: A dimple pattern for a golf ball (20) with a thermoset polyurethane cover (21) is disclosed herein. The dimple pattern has multiple sets of dimples (34, 36, 38, 40, 42, 44 and 46), each set of dimples (34, 36, 38, 40, 42, 44 and 46) having a different diameter. A preferred set of dimples (34, 36, 38, 40, 42, 44 and 46) is seven different dimples (34, 36, 38, 40, 42, 44 and 46). The dimples (34, 36, 38, 40, 42, 44 and 46) may cover as much as eighty-six percent of the surface (22) of the golf ball (20). The unique dimple pattern allows a golf ball (20) with a thermoset polyurethane cover (21) to have shallow dimples (34, 36, 38, 40, 42, 44 and 46) with steeper entry angles. The unique dimple pattern also allows a golf ball (20) with a thermoset polyurethane cover (21) to have greater low speed lift with a lower high speed drag.