

INSECT TRAP

FIELD OF THE INVENTION

- 5 This invention relates to an improved insect trap suitable for trapping of flying insects including mosquitoes, sand flies, wasps, fleas, midges and the like.

BACKGROUND TO THE INVENTION

- 10 Conventional insect traps of one type are relatively compact and include a housing, a source of light located in the housing and a capture or immobilization medium such as a sheet having adhesive impregnated thereon or entrapment container for retention of flying insects after they have entered the housing through an opening thereof after being attracted by the light source. Such insect traps are described in US Patents
15 4400903, 4332100, 4930251, 5231792, 5301456, 5365690, 5513465, 5915948, 5974727, 6502347, 6886292 and 7284350. While these insect traps are relatively inexpensive, they are inefficient because a light source does not have the same attraction to flying insects as for example carbon dioxide which is a very strong attractant for mosquitoes for example who can detect carbon dioxide from a long
20 distance away from the trap location i.e. about 70-100 metres away.

- It was also well known to incorporate a fan or air blower in insect traps of the type described above which could produce a draught of air within the housing to force insects into an entrapment chamber or immobilization medium such as an adhesive
25 impregnated sheet. However while the inclusion of the fan or air blower provided an increase in overall effectiveness in trapping ability they were not as efficient as insect traps which used carbon dioxide as an attractant lure. These types of insect traps are described in US Patents 4127961, 6574914, 6840003 and 7191560.

- 30 There was another type of conventional insect trap which used carbon dioxide as an attractant lure and in this case it was normally necessary to generate the carbon dioxide in situ. Thus in one form it was necessary to generate carbon dioxide by

catalytic conversion from a hydrocarbon fuel such as propane. This is described for example in US Patents 6145243, 6718685, 6779296, 6840005, 6892492, 6925752 and 7293388. Other means of generating carbon dioxide include reacting acetic acid with baking soda as described in US Patents 4506473 and 6920716. Another method of generating or passing the carbon dioxide to the insect trap was to pass the carbon dioxide through a vertically extending exhaust tube to minimize cooling and minimize condensation of moisture as described in US Patent 6662489. In US Patent 5382422 reference is made to preparing and delivering a gas mixture of liquid chemical compounds such as octenol acetone soluble in liquid carbon dioxide to be used as an enhanced attractant for biting insects.

However it will be appreciated that such means of generating or supplying carbon dioxide to the insect traps were expensive but also complicated the overall structure of the insect trap. However a more relevant problem was that the carbon dioxide gas was supplied as a constant flow which was relatively ineffective in attracting insects to the trap.

It is therefore an object of the invention to provide an insect trap that is simple to operate and effective in use.

20

The insect trap of the invention includes a housing having located therein:

- (i) a gas bottle or container
- (ii) one or more modulators having a viscous medium to produce a pulsed flow of gas; and
- (iii) a capillary tube interconnecting the gas bottle or container and a respective modulator wherein said capillary tube has a restricted zone to decrease the flow of gas therethrough whereby the pulsed flow of gas is caused to flow out of the housing at a greatly reduced rate compared to a flow rate that would be produced if the restricted zone was absent.

30

The housing is suitably compact and may have a central cavity or space for location of the gas bottle. A single modulator may be used or a plurality of modulators may

also be used wherein each modulator contains an attractant lure specific to a particular winged insect. Thus for example, if three modulators are used the trap may be used for attraction of wasps, mosquitoes and sandflies as described hereinafter.

- 5 The housing may also be provided with a suitable insect immobilization device such as capture medium suitably in the form of paper or sticky paper located in a mounting frame which is releasably connected to an interior of the housing. Alternatively use may be made of an entrapment container. The housing may also include a plurality of grilles having air slots for entry of insects into a hollow interior of the housing.
- 10 Suitably there may be provided a pair of grilles in a front wall of the housing and a pair of grilles located in a rear wall of the housing wherein each pair of grilles are located in side parts or wings of the housing symmetrically assigned with regard to the central cavity or space.
- 15 Preferably the housing has a top wall, bottom wall and side walls which are all formed from translucent or transparent material so that light from a light assembly located within the housing may be refracted as it passes through the walls of the housing. Alternatively the housing may be predominantly formed from the translucent or transparent material.
- 20 The light assembly is preferably powered by a solar panel which is connected to or located adjacent an LED unit.

- In another aspect of the invention there is provided a method of producing a pulsed flow of gas such as carbon dioxide from a container or source of said gas which includes the steps of:-
- 25

- (i) reducing the flow rate of the gas by passing the gas through a capillary tube having at least one restricted zone; and
- 30 (ii) passing said gas through one or more modulators containing a viscous medium to produce the pulsed flow of gas.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Reference may now be made to a preferred embodiment of the insect trap of the invention as shown in the attached drawings wherein:

5

FIG 1 is an exploded perspective view of a front side of the insect trap;

FIG 2 is an exploded perspective view of a rear side of the insect trap shown in FIG 1;

10

FIG 3 is a front perspective and assembled view of the insect trap shown in FIG 1 showing the capture frame and associated capture sheet removed therefrom for reasons of clarity;

15

FIG 4 is a similar view shown in FIG 3 but showing a rear assembled view of the fly trap shown in FIG 3;

FIG 5 is an exploded underside view of the light assembly incorporated in the fly trap shown in FIG 1;

20

FIG 6 is a similar view to that shown in FIG 5 from the top of the light assembly;

FIGS 7, 8 and 9 are different perspective views of the gas bottle and associated modulators which are used in the insect trap shown in FIG 1;

25

FIG 10 is a perspective view of an assembled insect trap shown in FIG 1 with a transparent cover removed showing incorporation of the gas bottle and modulators shown in FIGS 7, 8 and 9;

30

FIG 11 is a plan view of the insect trap shown in FIG 10 with a top plate removed again showing incorporation of the gas bottle and associated modulators shown in FIGS 7,8 and 9;

FIGS 12, 13, 14 and 15 show various views of the assembled insect trap of the invention;

FIGS 16 -19 show details of the capillary tubes connecting each modulator to the gas bottle; and

FIGS 19A - 27 refer to another embodiment of the invention in relation to formation of the restricted zone.

In FIG 1 there is shown insect trap 10 having a front wall assembly 11 having peripheral frame 12; grilles 13 each having air slots 14, a front transparent cover 15 bounded by grilles 13 on each side, and locating projections or sockets 16 and 17 which engage with corresponding projections or sockets 16A and 17A shown on peripheral frame 12A of rear wall assembly 18. Each grille 13 may engage in snap fit or interference fit with associated apertures 13A located in frames 12 and 12A.

Peripheral frame 12 also has bottom locating projections 19 which engage with corresponding projections 20 on peripheral frame 12A of rear wall assembly 18 so that each wall assembly 11 and 18 may be snap fitted together so as to be totally supported by legs 21 of rear wall assembly 18. There are also provided additional locating projections 18A on peripheral frame 12 shown in FIG 2 which engage with corresponding locating sockets 18B on peripheral frame 12A.

There is also shown capture plates or frames 22, capture sheets 23 which are slidably retained within an internal space 24 of each capture plate 22, light assembly 24A, gas bottle 25, a support frame 26 for modulators 27, 28 and 29 which are each retained in associated sockets 30 of support frame 26. There is also provided manifold 31 interconnecting gas bottle 25 and each modulator 27, 28 and 29 so that

gas bottle 25 is in fluid communication with a hollow interior of each modulator 27, 28 and 29. There is also provided an actuator button or a rotary on-off control 32 for actuating flow of gas from gas bottle 25 to modulators 27, 28 and 29. On-off control 32 may be connected to a needle valve, ball valve or any other valve 32A for
5 controlling the flow of gas from bottle 25.

Rear wall assembly 18 also includes grilles 34 each engageable with associated apertures 33 of peripheral frame 12A in a similar manner to grilles 13 engaging with apertures 13A. There is also shown a rear plate or cover 36 made up of transparent
10 material which covers an access window or space 35 to gas bottle 25 and associated modulators 27, 28 and 29. There is also provided top plate 37 having aperture 38 for retention of light assembly 24A.

In FIG 2 there is shown recess 39 in peripheral frame 12 for accommodation of gas
15 bottle 25 and associated modulators 27, 28 and 29 and retaining lugs 40 in aperture 13A for retention of grilles 34 whereby lugs 40 engage with slots 40A. There are also provided slots 41 in rear plate 36 which engage with retaining apertures 42 in lugs 43. Peripheral frame 12A is also provided with mating recess 44 which mates with corresponding recess 39 to provide a central compartment 61 shown in FIG 10 to
20 enclose gas bottle 25 and modulators 27, 28 and 29.

In FIGS 3-4 there is shown an assembled view of insect trap 10 from a front view and rear view respectively. It will be noted that each capture frame 22 and associated capture sheet 23 are retained in an associated slot 45 of insect trap 10.

25

It will also be appreciated from a view of FIGS 3-4 that insect trap 10 instead of being formed from interconnecting front and rear wall assemblies 11 and 18 as shown in FIGS 1-2 can be made as a one piece moulding from suitable transparent or translucent plastics material.

30

In FIGS 5-6 there is shown light assembly 24A having housing 46, solar panel 49, LED unit 47 and plastics refraction plate 50 wherein light from LED unit 47 will be refracted as it passes through plate 50.

5 In FIGS 7-9 there is shown gas bottle 25 and associated modulators 27, 28 and 29. Each modulator has a pair of opposed housing components 51 and 52 shown in FIG 8 with manifold 31 having an intermediate part 53 and inlet component or nozzle 54 being of smaller diameter than intermediate part 53. Inlet component or nozzle 54 has a bore of about 0.50 to 1.00mm and carbon dioxide gas from gas bottle 25 may
10 flow continuously into inner passage 55 of modulator 27 where it may encounter an attachment medium 57A which may contain a viscous component such as honey. Suitable attractant lures for the insect may include a variety of attractant lures as described in International Publication WO/2010/012031 which is reproduced herein in its entirety. Thus for example, suitable attractant lures may be selected from suitable
15 food grade constituents that with the aid of natural moisture contained in the medium produce a certain amount of carbon dioxide that will supplement the flow of gas from gas bottle 25. Volatile attractant lures may include lactic acid, octenol including l-octen-3-ol, L-lysine, acetone valeric acid and kairomones. Instead of honey molasses or syrups may form examples of viscous substances that may be combined
20 with the volatile attractant lure. Suitable viscous substances may have a viscosity in the range of 500-30,000 cp. There also may be used other attractant lures which are a food grade component such as mushroom extract, sugar, ammonium bicarbonate and sodium chloride. Such components can be dissolved in a suitable solvent which be cider vinegar, red wine or white wine.

25 While only one modulator 27 may be used within the scope of the invention it is preferred that specific attractant lures may be differently formulated to attract different biting insects and that such different attractant lures may be used in modulators 28 and 29. Thus for example lures specific for paper wasps or yellow jacket species
30 may be used. Such lures contain as one component acetic acid and as another component a compound selected from isobutanol, racemic 2-methyl-1-butanol, S-(-)-2-methyl-1-butanol, 2-methyl-2-propanol, heptyl butyrate and butyl butyrate. This

attractant lure is described in US Patent 6083498. Another attractant lure which may be used in modulator 29 may be an attractant lure for sand flies as described in US Patent 4886662 which contains alpha-terpineol as an active component.

5 However it will be appreciated that each of modulators 27, 28 and 29 will have a viscous component which will have the important ability of causing carbon dioxide to be expelled from outlet 57 of outer passage 56 in a pulsed or intermittent flow so that separate plumes of attractant lure and CO₂ may be expelled through grilles 13 and 34 as described in International Publication WO/2010/012031. The flow of gas in
10 modulator 27 is shown by the arrows in full outline in FIG 7. Modulator support frame 26 also includes attachment apertures 26A for attachment to frame 12 or 12A by suitable fasteners (not shown).

FIG 7 also shows a manifold or manifold assembly 31 which may be directly attached to an outlet 33A of gas bottle 25 by welding or by screw threaded engagement at
15 33B.

In FIG 10 there is shown the insect trap 10 after removal of transparent cover 15 and also illustrating compartment 61 for gas bottle 25 and associated modulators 27, 28 and 29. Each of modulators 27, 28 and 29 are contained in associated holders 30.
20 Also shown are webs 26C interconnecting holders 30.

In FIG 11 it is shown that gas bottle 25 and associated modulators 27, 28 and 29 in compartment 61 are centrally located and wings or side parts 62 and 63 are symmetrically orientated in regard to compartment 61.

25 FIGS 12-13 show the presence of transparent front cover 15 and transparent rear cover 36 for gas bottle 25 and associated modulators 27, 28 and 29. Each of side parts 62 and 63 may be formed from translucent material so that light from light assembly 24A may be totally visible through covers 15 and 36 and side parts 62 and
30 63. In fact side parts 62 and 63 may be formed from refractive material so that light from light assembly 24A is bent as it passes through top wall 37 and peripheral frames 12 and 12A and this will provide a greater attraction to insects. In fact light

from light assembly 24A may extend from trap 10 in all directions as shown by arrows A, B, C, D and E in FIG 13 and arrow F in FIG 12.

FIGS 14 and 15 also show that top plates or cover 37 and base wall 64 may be also formed from translucent material so that light from light assembly 24A may also shine through top cover 37 and base wall 64 as shown by arrows I, J, K, L, G, H, M and N.

It will also be appreciated that legs 21 may be replaced or fitted into spikes (not shown) for retention of insect trap 10 within the ground if desired.

In FIG 16 there is shown a sectional view through trap 10 through line A-A shown in FIG 3 in top plan. There is shown an internal mechanism 64 of conduits whereby carbon dioxide is transported to modulators 27, 28 and 29 through capillary tubes 65, 66 and 67 which communicate with each of modulators 27, 28 and 29 through inlets 68, 69 and 70. Each capillary tube 65, 66 and 67 is crimped or twisted as shown by crimped or restricted zone 71 in FIGS 16-17 and the crimped or restricted zone 71 has a diameter of from 0.005 to 0.2mm compared to an unrestricted part 72 of capillary tube 65, 66 and 67 which can have a diameter of 0.025 to 1.25 mm. The restricted zone 71 may have a gas flow of 5-39g of gas per day and more suitably 18g per day.

It will also be appreciated that crimped or restricted zone 71 will greatly increase frictional contact of the gas with an internal surface of restricted zone 71 and this will greatly reduce the flow of gas through restricted zone 71. The length of restricted zone 71 may also vary from 10-125mm. Obviously the greater the length of restricted zone 71 the greater reduction in gas flow may be achieved.

It is also preferred that multiple restricted zones 71 may be used but it is preferred that there is only a single restricted zone 71.

Instead of using a twisted or crimped zone 71 as shown in FIGS 16-17 a restricted zone 73 may be used which is of much smaller diameter than unrestricted part 72 as shown in FIGS 18-19.

5 Reference may be made to another embodiment of the invention as shown in FIGS 19A - 27 wherein reference is made to an adjustment body which may produce the restricted zone discussed above but such restricted zone will be produced within a capillary tube by use of one or more pressurizing devices which upon contact with the capillary tube will produce the restricted zone but upon withdrawal of the pressurizing
10 device(s) from the capillary tube the restricted zone may no longer be present. This embodiment takes advantage of the natural resilience or elasticity of the material which forms the capillary tube which for example may be copper or plastics material. Thus the pressurizing device(s) may only make bearing contact with the capillary tube to produce the restricted zone and thus the flow rate of gas can be calculated as may
15 be required. The flow rate may be measured by passing the capillary tube or adjustment body under water to gauge the size of the bubbles being generated. Thus it will be appreciated that such restricted zone may not be permanent but may be temporarily caused by contact with the pressurizing devices which may be a plurality or pair of adjustment nuts for example. By opening up the transverse dimension or
20 diameter of the capillary tube this may also remove impurities from the gas after passage through the restricted zone.

In FIGS 19A -25 reference is made to an adjustment body 80 having an end flange 81, transverse passage 82 having a pair of adjustment nuts 83 each having a
25 respective outer end 84 having a hexagonal shaped recess 85 for engagement by a suitable tool such as an Allan key (not shown) or other type of hexagonal key. The adjustment body 80 also includes a longitudinal passage 86 which contains the capillary tube 87. There is also provided a spigot 88 which may be used for engagement with a hose 89 shown in FIG 26 for transmission of carbon dioxide gas
30 to a modulator housing 28. The capillary tube 87 may be made of copper or similar material which extends from one end 91 of adjustment body 80 and which is welded

thereto shown at 92. The other end of capillary tube 87 extends through spigot 88 and is welded to end 93 of spigot 88 as shown at 94.

5 Spigot 88 is also provided with a bearing ridge 89A, tapered end 89B and flat 89C for retention of hose 89 shown in FIG 26. FIG 25A shows formation of restricted zone 95 which is formed in capillary tube 87 by pressure or the force generated by flat bearing faces 96 of each adjustment nut 83 on capillary tube 87.

FIG 26 shows connection of hose 89 to spigot 88 of adjustment body 80. Hose 89 is also connected to a connection body or nozzle 97 having a hollow bore 98 which
10 extends through a side wall 28A of modular 28 as shown in FIG 26. Connection body 97 may be similar to body 53 shown in FIG 7 having inlet 54. Hose 89 may be connected to spigot 99 in a similar manner as connection of hose 89 to spigot 88 described above. Gas flows through hollow bore 98 to inner tube 55 of modulator 28.

15 FIG 26 also shows how adjustment body 80 may have connected thereto a large hexagonal nut 100 which has a threaded internal part 101 for connection to a suitable inlet of a gas bottle (not shown).

FIG 27 shows another arrangement involving use of adjustment body 80 in being
20 connected to the modulator 108 described in International Publication WO2010/012031 which has a housing component 102 and inner tube or insertion tube 103 which also has a finger aperture 104, ribs 105 separated by spaces or gaps 106, and socket 107 for connection with connection body or nozzle 97 having a hollow bore 98 wherein spigot 99 having O-ring 99A is engageable in hollow bore 109
25 of socket 107. Modulator 108 also has reinforcing ribs 110. Bore 98 is in flow communication with internal passage 103 as shown. Hose 89 is connected to connector body 97 and at its other end is adjustment body 80 connected to hexagonal nut 100 as shown in FIG 26.

30 Thus another aspect of the invention provides a conduit assembly interconnecting a modulator as shown in WO2010/012031 or modulator 28 wherein the conduit assembly at one end has a connector body fitted to the modulator for discharge of

gas such as CO₂ into a hollow interior of the modulator to produce a pulsed flow of gas and the conduit assembly at another end is attached to an adjustment body having a restricted zone in a capillary tube for reducing the flow rate of the gas wherein the adjustment body is connected to a gas source such as a gas bottle. The
5 invention may also include within its scope the adjustment body *per se*.

It will be appreciated with the advent of the present invention that a small gas bottle of carbon dioxide of around 500g may last for a month 24/7 because of the fact that a very small pulsed flow of gas is produced in bubbles or plumes interposed between
10 plumes of attractant lure as shown in International Publication WO/2010/012031. The insect trap of the invention does not need to be connected to an electrical source of power such as the mains or a battery. Also a gas regulator is not required. Also by the use of a very simple mechanism as shown in FIGS 18-19 complicated connection mechanisms to a source of carbon dioxide as described in the prior art discussed
15 above are not required or needed.

The invention in another aspect may include a method of controlling flow of carbon dioxide from a container of carbon dioxide which includes the steps of:-

- 20 (i) attaching a manifold assembly containing a capillary tube which has a restricted zone to an outlet of the container; and
(ii) causing carbon dioxide to flow through the manifold assembly at a reduced flow rate compared to the situation when the restricted zone is not present.

25

The invention also included within its scope the manifold assembly *per se*.

CLAIMS:

1. An insect trap including a housing having located therein:
 - (i) a gas bottle or container
 - 5 (ii) one or more modulators having a viscous medium to produce a pulsed flow of gas
 - (iii) a capillary tube interconnecting the gas bottle or container and a respective modulator wherein said capillary tube has a restricted zone to decrease the flow of gas therethrough whereby the pulsed flow of gas is caused to flow out of the housing at a greatly reduced rate compared to a flow rate that would be produced if the restricted zone was absent.
2. An insect trap as claimed in claim 1 wherein the viscous medium has one or more attractable lures for insects.
3. An insect trap as claimed in claim 1 or 2 wherein the housing has a central cavity or space for location of the gas bottle or container.
- 15 4. An insect trap as claimed in any one of claims 1, 2 or 3 wherein a single modulator is contained within the housing.
5. An insect trap as claimed in any one of claims 2 or 3 wherein a plurality of modulators are used wherein each modulator contains an attractant specific to a particular winged insect.
- 20 6. An insect trap as claimed in any one of claims 1 – 5 wherein the housing contains an insect immobilization device or entrapment container releasably mounted therein.
7. An insect trap as claimed in claim 6 wherein the immobilization device has capture medium located in a mounting frame which is releasably mounted to an interior of the housing.
- 25 8. An insect trap as claimed in any one of claims 1 – 7 wherein the housing has one or more grilles having air slots for entry of insects into the housing.
9. An insect trap as claimed in claim 8 wherein said housing has a pair of said grilles located in a front wall and a rear wall of the housing.
- 30

10. An insect trap as claimed in any one of claims 1 – 9 wherein the housing is formed from predominantly transparent or translucent material whereby light from inside the housing may be refracted as it passes through the housing.
- 5 11. An insect trap as claimed in claim 10 wherein the housing has a top wall, bottom wall and a continuous side wall all formed from said transparent or translucent material.
12. An insect trap as claimed in claim 10 or 11 wherein the housing has a light assembly located within the housing.
- 10 13. An insect trap as claimed in claim 12 wherein the light assembly includes a solar panel and a LED unit wherein the LED unit is powered by the solar panel.
14. An insect trap as claimed in any one of claims 1 – 13 wherein the restricted zone is formed by crimping or twisting the capillary tube.
- 15 15. An insect trap as claimed in any one of claims 1 – 14 wherein the restricted zone has a diameter of from 0.005 to 0.2mm compared an unrestricted part of the capillary tube having a diameter of 0.025 to 1.25mm.
16. An insect trap as claimed in any one of claims 1 - 15 wherein the restricted zone is adjustable in regard to diameter or lateral dimension.
- 20 17. An insect trap as claimed in claim 16 wherein said restricted zone is formed temporarily within said capillary tube by use of one or more pressurising devices which upon contact with the capillary tube will produce the restricted zone which is adjustable but upon withdrawal of the pressurising devices the restricted zone will no longer be present.
- 25 18. A conduit assembly interconnecting a modulator at one end and connectable to a gas bottle or container at another end, said conduit assembly having (i) a connector body fittable to the modulator for discharge of gas such as carbon dioxide into a hollow interior of the modulator, and (ii) an attachment body having a capillary tube which incorporates a restricted zone for reducing the flow rate of the gas.
- 30 19. A conduit assembly as claimed in claim 18 wherein the attachment body is adjustable in relation to controlling the amount of pulses of gas passed into the modulator.

20. A conduit assembly as claimed in claim 18 which includes one or more pressurising devices for temporarily forming said restricted zone upon contact with the capillary tube but upon withdrawal of the pressurising device(s) the restricted zone is absent.
- 5 21. An attachment body for attachment to a gas bottle or container having a longitudinal bore and a capillary tube located in said longitudinal bore and a passage located transverse to the longitudinal bore combining one or more pressurising devices for pressurising the capillary tube for forming a restricted zone wherein an amount of said gas pulses may be regulated as said gas
- 10 pulses pass through the capillary tube in use.
22. A method of producing a pulsed flow of gas from a container or source of said gas which includes the steps of:
- (i) reducing the flow rate of the gas by passing the gas through a capillary tube having at least one restricted zone; and
- 15 (ii) passing said gas through one or more modulators containing a viscous medium to produce a pulsed flow of gas.