

**Structured cross-channel packing element with reduced material
requirement**

- 5 The present invention relates to a structured cross-channel packing element for a column for mass transfer and/or heat exchange between a heavy fluid phase and a light fluid phase.

Structured packing elements are used in mass transfer columns, such as for
10 instance in fractionation columns, distillation columns, absorption columns, extraction columns or flue gas scrubbers. The structured packings elements serve for the improvement of the mass transfer and/or heat transfer between at least two fluid phases of different density, wherein the structured packings elements are typically operated in counter-current flow. While in distillation and absorption
15 applications, the light phase is a gas or vapor and the heavy phase is a condensate or liquid, in extraction processes both phases are liquids with different density. The structured packing elements comprise a plurality of different layers, each of which providing surface area for the heavier phase that trickles down along the surface of the layer and spreads. In addition, between the different
20 layers of the structured packing elements open spaces are provided, which are filled with the light phase (e.g. vapor or gas in distillation) and provide a path for the light phase to ascend, while it is driven by a pressure gradient. The pressure gradient is required to overcome the flow resistance. In the typical case of counter-current mass transfer, the average flow direction of the light phase is from bottom
25 to top of the structured packing element and thus opposite to the average flow direction of the heavy phase. By allowing the one heavy phase to spread on the surface of the structured packing element, an interface is created between the at least two phases so that an efficient heat and mass transfer between the phases is

established at the interface. There may also be applications with more than one heavy phase. An example is extractive distillation.

A mass transfer column usually comprises several beds of structured packing
5 elements. Typically, a distributor is arranged on top of each bed to evenly
distribute the heavy phase over the cross-section of the bed, while leaving enough
space for the light phase to ascend through it. Moreover, often a grid-like holding
device and a collector are arranged below each bed, wherein the grid-like
10 structure keeps the bed at its position and the collector collects the heavy phase
trickling down from the bed, while sufficient open space is left in the collector for
the light phase to ascend.

A common type of structured packing elements is the so-called cross-channel
corrugated sheet packing, which is assembled from a plurality of for instance
15 corrugated sheets, which are arranged parallel and in touching contact with each
other. Typically, the corrugated metal sheets are fixed with each other by means of
several rods penetrating the corrugated sheets perpendicular to the longitudinal
section of the corrugated sheets, wherein the rods are fixed with the first and last
corrugated sheet by means of a washer and a nut or by bending the rod. Each
20 corrugated sheet comprises a plurality of periodic deformations, such as
alternately oriented peaks and valleys, wherein adjacent corrugated sheets are
oriented such that the corrugations of the adjacent corrugated sheets intersect in
crisscross fashion with the corrugations of the corrugated sheets extending
obliquely relative to the vertical or longitudinal direction, thus forming inclined
25 channels which continuously cross one another. These channels positively
influence the flows of the gas phase and of the liquid phase within the packing and
facilitate the mass transfer between the phases. That is, the gas phase and the
liquid phase are brought into contact in the channels of the structured packing
element and the mass transfer as well as the heat transfer between the phases is
30 thus facilitated. More specifically, ascending gas comes into contact with liquid,

which is present on the surface of the sheets forming the channels when it flows downwardly through the mass transfer column. During this contact, a component enriched in the gas can transfer into the liquid and vice versa; this means that an efficient mass transfer can take place. Such packings are described for example in
5 DE 1 253 673, in CA 1270751 and in US 6,206,349 B1.

The amount of mass transfer per unit time is proportional to the area of the interface between the gas and the liquid, wherein the area of the interface gets larger with increasing portion of the surface of the packing element's layers which
10 is wetted by the liquid. Cross-channel corrugated sheet packings made of metal gauze are known to have an excellent wettability thanks to a good spreading of the heavy phase on the surface of the corrugated sheets due to capillary force of the metal gauze and thus – on account of the excellent wettability – a high mass transfer efficiency. Examples for such structured packing elements are the Sulzer
15 packing types BX and CY, which had been first presented in the sixties of the 20th century. Another example of such a structured packing element is described in EP 1 477 224 A1. However, metal wire gauze is an expensive material. On account of this reason it has been tried to replace the gauze material by a corrugated metal sheet with a large number of small openings. An example is the commercially
20 available Montz-Pak Type BSH. During operation of the mass transfer column the openings of this packing are filled with the heavy phase due to the capillary force. The wettability of such corrugated, relatively finely structured perforated metal sheets is worse than that of the packings based on metal gauze, and the production of the sheet is still relatively expensive, partly due to the slow
25 production process associated with the fine structure.

As set out above, it is important for a high mass transfer efficiency that the surface of the structured packing element is well covered by liquid, since failure results in a waste of packing material as the light phase is not as much in contact with the
30 heavy phase as it could be given the physical area of the packing. Alternative

suggestions to promote the spreading of the heavy phase over the surface of the layers - instead of using metal gauze or corrugated, very fine expanded metal sheets as material for the structured packing element - are to provide the layers with perforation and another surface texture, such as described in US 4,296,050, 5 in GB 1,569,828, in US 4,981,621 and in EP 3 003 550 A1.

In order to further improve the use of the surface of the structured packing element it was already proposed in DE 38 18917 C1 and in CN 882 00252 U to provide cross-channel corrugated sheet packings made of perforated layers having a high 10 void fraction, i.e. a high ratio of the total area of the openings in the layer divided by the sheet area of the layer. More specifically, DE 38 18917 C1 discloses structured packing elements made of sheet layers comprising openings, which are separated from each other by separating elements. The edges of the openings are provided with protruding rims, wherein the rims of adjacent openings are 15 alternating extending upwardly from the upper side of the surface and downwardly from the lower side of the surface of the sheet layers. Moreover, DE 38 18917 C1 teaches that the openings of the layers shall be 3- to 7-times larger than the width of the separating elements located between the adjacent openings. This results in a structured packing element made of open metal sheets with very high void 20 fraction in the order 50% or more. CN 882 00252 U discloses a structured packing element made of perforated sheets having a thickness of 0.1 to 0.5 mm. The openings have a rhombic shape, wherein the width of the openings is between 2 and 3 mm and wherein the percentage of open area on the sheet, i.e. the void fraction, is 40% to 50%. Thus, both prior art documents teach to provide structural 25 packing elements comprising sheet layers having rather high void fractions of more than 40% and preferably of about 50%. In contrast thereto, classical structured packing elements have drastically lower void fractions of at most 10%.

Structured packing elements based on another principle than cross-channel 30 corrugated sheet packings are for instance described in EP 0 069 241 A1, in US

4,304,738 and in EP 0 250 061 A1. The layers of these structured packing elements consist of expanded sheet metal, wherein the layers assume a certain layer width due to the expansion process. However, in contrast to cross-channel corrugated sheet packings the layers of these structured packing elements are not
5 corrugated and not deformed except for the deformation that comes along with the expansion process. This limits the open space for the ascending vapor. Therefore, the mass transfer efficiency is not optimal, because the open space between the layers does not provide a well-defined path driving the ascending vapor in a way that promotes a homogenous distribution over the whole cross-section plane of the
10 structured packing element. It would be desirable to impose on the vapor a certain direction by means of an additional degree of freedom when defining the shape of the packing.

Apart from a high mass transfer efficiency, the capacity is an important aspect for
15 a structured packing element. As the flow rates of the light and heavy phases in a structured packing element increase, the pressure drop in the structured packing element increases. At a certain pressure drop, gravity is not strong enough to counteract the friction between the two phases and the heavy phase or liquid, respectively, is entrained in the light phase or gas, respectively, and thus cannot
20 descend anymore along the structured packing element. At this point, the mass transfer breaks down and this situation is called flooding. This flooding point determines the capacity of a structured packing element, i.e. the capacity of a structured packing element is characterized by pairs of maximum flow rates of the counter-current phases beyond which an increase of either of the two flow rates
25 leads to flooding. The flooding point relates to a characteristic pressure drop, which is generally in the order of 10 mbar per meter packing height.

It would be optimal for a structured packing element to have an excellent mass transfer efficiency as well as an excellent capacity, because this would allow to
30 reduce the diameter and/or height of the mass transfer column at a given capacity

and thereby to minimize the investment costs for the mass transfer column.

However, these two characteristics depend on opposite trends with regard to the specific area and other geometrical parameters. More specifically, a high specific area, i.e. a high quotient of the geometrical area of the structured packing element

- 5 divided by the volume it occupies, leads to an intensive contact between the light and heavy phases, why a respective structured packing element has a high mass transfer efficiency, which is commonly expressed in terms of number of theoretical stages per meter packing height NTSM. However, a structured packing element with a high specific area is characterized by a high flow resistance for the light
10 phase, why a respective structured packing element has - at a given flow rate of the light phase - a higher pressure drop per packing height and thus a lower capacity than a packing with a lower specific area.

In view of the above, the object underlying the present invention is to provide a

- 15 cost efficient multi-purpose structured packing element having a higher mass transfer efficiency at a given capacity or a higher capacity at a given mass transfer efficiency or a lower weight at a given mass transfer efficiency, respectively.

In accordance with the present invention, this object is satisfied by providing a
20 structured cross-channel packing element for a column for mass transfer and/or heat exchange between a heavy and a light fluid phase, wherein the structured cross-channel packing element comprises at least two adjacent layers made of expanded metal sheets each comprising openings, which are surrounded and separated from each other by separating elements, wherein at least two of the at

- 25 least two layers are arranged in the longitudinal direction of the packing element parallel and in touching contact with each other so that an open space extending from one end to the opposite end of the at least two layers is provided between them so that at least one of the heavy and the light fluid phase may flow through it, wherein the ratio between the average width of at least one and preferably at least
30 50% of the separating elements between adjacent openings and the sheet

material thickness is at least 15, wherein the ratio between the maximum distance between at least two of the at least two layers measured in the plane being perpendicular of the longitudinal direction and the average width of the separating elements is at least 4, and wherein the ratio between the distance between two openings being in the direction perpendicular to the stretch direction of the expanded metal sheet adjacent to a separating element and the average width of this separating element is preferably for at least 50% of all separating elements 4 to 6, wherein the distance between two openings is measured by determining the distance between the outermost point of one side of the edge of one of the openings in the direction perpendicular to the stretch direction of the expanded metal sheet and the outermost point of the same side of the edge of an adjacent opening in the same direction of the expanded metal sheet, wherein the longitudinal direction of the packing element is as defined in the specification, wherein the stretch direction of the expanded metal sheet is the direction being perpendicular to the longitudinal direction of the structured cross-channel packing element, and wherein the average width of a separating element is determined by dividing up the separating element into individual sections $i=1, 2, 3 \dots n$ each having a section length d_i , wherein for each of the sections the shortest distance b_i between the adjacent edges within the sections is measured and the sum of the products $d_i \cdot b_i$ is divided by the sum of d_i to yield the average width b of the separating element.

This solution bases on the surprising finding that the mass transfer efficiency at a given capacity can be significantly improved, if the average width of the separating elements between adjacent openings is relatively large compared to the openings (namely, the ratio between the distance between two openings being in the direction perpendicular to the stretch direction (which is the direction perpendicular to the longitudinal direction) of the expanded metal sheet adjacent to a separating element and the average width of this separating element is 4 to 6) and significantly wider than the sheet material thickness (namely, in 15 times or more).

This was in particular unexpected, because it is in contradiction to the teaching of DE 38 18917 C1 and CN 882 00252 U. The two prior art documents imply that a free film hanging between the separating elements contributes twice to the mass transfer area and thus suggest to further minimize the width of the separating
5 elements and to remove even more of the physical area. In view of this, it was even more surprising that by adjusting the aforementioned parameters as described above, the mass transfer efficiency at a given capacity is significantly improved.

10 A further significant advantage of the structured packing element in accordance with the present invention is that it does not at all base on the use of expensive layer material. Rather, the layers are simply produced of expanded metal sheets, i.e. by cutting and stretching a thin metal plate and then in a second step deforming the expanded metal sheet to, for instance, corrugated sheets. Thus, a
15 cost-efficient raw material is used and the required amount of material of this cost-efficient raw material is even reduced by stretching it. All in all, the present invention provides a cost-efficient multi-purpose structured cross-channel packing element having a higher mass transfer efficiency at a given capacity or a higher capacity at a given mass transfer efficiency, respectively.

20 The longitudinal direction of the structured cross-channel packing element is the direction from the top area to the bottom area of the structured cross-channel packing element when it is incorporated in a mass transfer and/or heat exchange column, i.e. the longitudinal direction is the direction from the top to the bottom of
25 the mass transfer and/or heat exchange column. In other words, it is the intended gravity-driven flow direction of the heavier phase during the operation of the structured cross-channel packing element and mass transfer and/or heat exchange column, respectively. More specifically, the longitudinal direction of the structured cross-channel packing element may be determined as follows: The
30 structured cross-channel packing element is placed on a horizontal area so that

the layers of the structured cross-channel packing element being arranged in parallel and in touching contact with each other extend in the vertical direction and so that the open spaces (or channels, respectively, which are surrounded and thus defined by the periodic deformations of the layers) extending from one end to the opposite end of the layers extend from the top to the bottom of the structured cross-channel packing element. The longitudinal direction is then the direction from the top to the bottom of the so arranged structured cross-channel packing element, or – in other words: Heavy phase, for instance water, which is dropped onto the top of the so arranged structured cross-channel packing element flows gravity-driven downwards along the open spaces, wherein the longitudinal direction is the average flow direction of the heavy phase.

The maximum distance (subsequently also referred to or abbreviated as "D") is closely related to the layer width (subsequently also referred to or abbreviated as "W"), which is the extension of one single layer measured in the above-mentioned plane. The value of W is typically around half of D. The open space between the two layers is obtained thanks to the layer width W. The maximum distance D between two adjacent layers of the structured packing element measured in the plane being perpendicular of the longitudinal direction denotes according to the present invention the distance between the layers, if the distance between the layers is constant over the entire surfaces of the adjacent layers, such as in the case of two parallel flat sheets. If the distance between the layers is not constant over the entire surfaces of the adjacent layers, i.e. if the distance between different surface portions of the layers differ, the maximum distance D between the two adjacent layers is the distance between those surface portions of both layers, where the distance in the plane being perpendicular to the longitudinal direction between both layers is maximal. More specifically, the maximum distance D between two adjacent layers of the structured packing element measured in the plane being perpendicular of the longitudinal direction denotes according to the present invention the distance between the two most distant points A and B,

whereby point A is on the first layer and point B is on the second layer. Two parallel planes are defined, one comprises point A, the other point B. These two parallel planes are oriented essentially parallel to the orientation of the two layers. The distance D is defined as the distance between these two parallel planes.

5

In accordance with the present invention, the structured packing element comprises at least two layers being arranged in the longitudinal direction parallel with each other. Parallel arrangement of two layers means in accordance with the present invention that one of the layers is inclined by an angle of at most $\pm 20^\circ$,
10 preferably of at most $\pm 10^\circ$, more preferably of at most $\pm 5^\circ$, still more preferably of at most $\pm 2^\circ$ with regard to the other layer and is most preferably not inclined at all with regard to the other layer.

Moreover, in accordance with the present invention, the ratio between the average
15 width of at least 50% of the separating elements between adjacent openings and the sheet material thickness is at least 15. This means that for at least 50% of the separating elements the ratio between the average width of the respective separating element and the sheet material thickness is at least 15. Preferably, the ratio between the average width of at least 75%, more preferably of at least 80%,
20 still more preferably of at least 90%, yet more preferably of at least 95% and most preferably of all of the separating elements between adjacent openings and the sheet material thickness is at least 15.

Sheet material thickness means in accordance the thickness of the material, which
25 constitutes or forms the layer, respectively. Since in accordance with the present invention the layer is made by an expanded metal sheet, the sheet material thickness is the sheet thickness. Should the sheet thickness vary over the area of the layer, the sheet material thickness is the thickness of the sheet measured at one of the outer edges of the sheet material thickness by means of, for instance, a
30 micrometer screw. For instance, the thickness of the material forming the layer is

measured at at least two, preferably at at least three and more preferably at at least five locations at one or more of the outer edges with the micrometer screw, before the obtained numeric values are summed up and averaged by dividing the sum by the number of measurements. Good results are for instance obtained,

- 5 when the thickness is measured at 2 to 20, preferably 2 to 10, more preferably 3 to 10 and most preferably 5 to 10 locations at one or more of the outer edges of the layer with the micrometer screw, wherein the different locations are about 3 cm distant from each other along the outer edge. A micrometer screw is a known measurement device comprising one fixed and one moveable measurement area,
- 10 wherein the moveable measurement area is adjustable with a fine thread. Both measurement areas may contact or touch each other, respectively, if the moveable measurement area is completely moved to the fixed measurement area. Both measurement areas are flat and circular, wherein the diameter of both measurement areas are preferably 5 to 6 mm.

15

The average width (subsequently also referred to or abbreviated as "b") of a separating element is determined in accordance with the present invention by measuring the distance between the two parallel adjacent edges of the separating element, if the separating element has a uniform width. If the separating element

20 does not have a uniform width, the average width b of a separating element is determined by dividing up the separating element into individual sections $i=1, 2, 3 \dots n$ each having a section length d_i . For each of the sections, the shortest distance b_i between the adjacent edges within the sections is measured. The sum of the products $d_i \cdot b_i$ divided by the sum of d_i yields the average width b of the

25 separating element. The higher the non-uniformity of the separating element, the more and shorter sections must be chosen. Preferably, the number n of individual sections i taken for the measurement per separating element is 1 to 1000, more preferably 5 to 100 and most preferably 5 to 20, such as 8 to 15. For instance, 5 sections are selected per cm of a separating element.

30

Preferably, the average width b of a separating element is determined on a top view or on a plan view of one of the openings being adjacent to the separating element. This is advantageously achieved by taking a photographic picture of an opening. The top view of an opening is made by making a photographic picture of an opening after having flattened the respective expanded metal sheet by laying the expanded metal sheet on a flat surface, putting a plate on the top of the expanded metal sheet and then pressing the plate downwards with a sufficiently low pressure so as to just flatten the expanded metal sheet for removing the periodic deformations, but without changing the geometry and dimensions of the separating elements and openings, i.e. without changing the geometry and dimensions of the grid-structure of the expanded metal sheet. The plan view of an opening is made on expanded metal sheet in its form as it is used in the structured cross-channel packing element, i.e. without having flattened or otherwise mechanically processed it. More specifically, the plan view of an opening is taken along the normal axis of the plane defined by the adjacent edges of the opening. In some cases, such a plane is not well defined. In this case, the most suitable view is obtained by trial and error. Several pictures, such as at least five pictures or preferably at least 10 pictures, from various angles are taken. The picture that renders the opening largest is then considered as the plan view of the opening.

One reference length z may be used to determine lengths and sizes on the plan view as well as on the top view. This is best achieved by identifying or marking a certain distance z on the real object in the neighborhood of the opening and measuring its length. The ratio between the effective length z' of this distance on the plan view or top view, respectively, and the distance z measured on the real object is used for scaling all other distances that are measured on the plan view. For example, the real length of a segment width is obtained by $b_i = b_i' \cdot (z/z')$, whereas primed variables denote the lengths measured on the plan view or top view, respectively, and non-primed variables the real length.

In accordance with the present invention, the hydraulic diameter d of an opening is calculated with the formula $4 A / P$, wherein A is the cross-sectional area of the opening and P is the perimeter of the same opening. The cross-sectional area of the opening can be determined by using basic measures (such as shape length and height) and a basic geometric formula (known from Euclidean geometry), if the shape of the opening is simple, e.g. a flat triangle, rectangle, quadrilateral, trapezoid or the like. Preferably, the area is determined on a top view or on a plan view of the opening. Complex shapes can be approximated and subdivided in a number $j=1, 2, 3 \dots m$ of simple shapes having an area A_j . The area of these shapes can again be calculated using basic measures and basic geometric formula. The area A of the opening is obtained by summing up all areas A_j determined in the opening. The more complex the shape of the opening is, the more subdivisions are required. Preferably, the number m of individual simple shape sections j taken for the measurement is 1 to 1000, preferably 5 to 100, more preferably 5 to 20, such as 8 to 15. As before, the real lengths are determined based on the ratio z/z' defined above.

The perimeter of an opening of simple shape can be determined using basic measures and basic geometric formula. In the most general case, the top view or plan view of the opening is used. The perimeter of the opening is subdivided in a number of $k=1, 2, 3 \dots K$ individual straight lines P_k that approximate the opening best and represent it by a closed polygon. By summing up the lengths of these straight lines, the perimeter P is obtained. Again, the lengths must be translated into real lengths using the ratio z/z' as defined above.

Methods of numeric image processing may be used to determine the average width b , the area A of an opening and its perimeter P . In this case, the basic unit is determined by the size of a pixel. To translate pixel-based lengths and areas, the ratio z/z' must be defined in an appropriate way as e.g. explained above. Grey values can be used to identify pixels that belong to a separating element and

others that belong to the opening. Areas can be calculated in straight forward manner by summing the pixels and multiplying the sum by the real area of a pixel (in relation to the real object). When determining the width b_i or a length d_i of a segment trigonometric rules must be applied if the width orientation is not parallel
5 to the sides of the pixels.

More details about measuring methods and illustrative examples are given further below in connection with the figures.

10 In accordance with the present invention, the layers of the structured cross-channel packing element are made of expanded metal sheets, which are produced by expanding a sheet metal, i.e. by cutting and stretching a sheet metal. Therefore, the resulting openings are typically of an essentially elliptic, lenticular, trapezoidal or rhombic and usually of an essentially lenticular or trapezoidal shape.

15 Thus, as schematically shown in the figures and as described in detail further below, each expanded metal sheet is in fact a grid comprising openings, wherein each opening is surrounded by separating elements having each a width b , wherein the separating elements of adjacent openings are connected with each other at junction points. The hydraulic diameter is generally unknown, but it can be
20 determined as set out above or calculated from the commonly used characteristic dimensions as explained below. Expanded sheets are typically characterized by the dimensions of their openings and the (average) widths of the separating elements b . The openings, which are usually essentially lenticular or trapezoidal shaped, have thus a shorter and a longer characteristic length, wherein the shorter
25 characteristic length (subsequently also referred to or abbreviated as " e_2 ") of an opening is the maximal dimension of the opening in the stretch direction of the expanded metal sheet and the longer characteristic length (subsequently also referred to or abbreviated as " e_1 ") of an opening is the maximal dimension of the opening in the direction perpendicular to the stretch direction of the expanded
30 metal sheet. The stretch direction of the expanded metal sheet is that direction,

along which the sheet metal has been stretched during the production of the expanded metal sheet. More specifically, the stretch direction is according to the present invention the direction being perpendicular to the longitudinal direction of the structured cross-channel packing element. Thus, the direction being

5 perpendicular to the stretch direction is the longitudinal direction of the structured cross-channel packing element. The (average) widths of the separating elements b and the characteristic lengths of the openings determine the distances between adjacent openings. The distance between openings being adjacent in the stretch direction of the expanded metal sheet differ from the distance between openings

10 being adjacent in the direction perpendicular to the stretch direction of the expanded metal sheet. Subsequently, the distance between a first opening and a second opening being in the stretch direction of the expanded metal sheet adjacent to each other is also referred to or abbreviated as u_2 , whereas the distance between the first opening and a third opening being in the direction

15 perpendicular to the stretch direction of the expanded metal sheet adjacent to the first opening is also referred to or abbreviated as u_1 . These distances u_1 and u_2 may be measured as explained in detail below under reference to the figures. The following equations could be used to determine the hydraulic diameter (subsequently also referred to or abbreviated as " d ") of the respective opening if

20 the openings are of approximately rhombic shape:

$$e_1 = u_1 - b \sqrt{1 + u_1^2/u_2^2}$$

$$e_2 = e_1 \cdot u_2/u_1$$

$$d = e_1 \cdot e_2 / \sqrt{e_1^2 + e_2^2}$$

25 If the ratio of e_2/e_1 is around 0.5 or below, as it is realistic for expanded metal sheets, the following simplified equations for e_1 and e_2 may be used to determine the hydraulic diameter d of the respective opening:

$$e_1 = u_1 - b \cdot u_1/u_2$$

$$e_2 = u_2 - b$$

Furthermore, expanded metal sheet can be characterized by means of the stretching factor, which is defined as $u_2/2b$. The inverse of the stretching is a good indication of the material savings that can be realized compared to a solid metal sheet. More details about these dimensions with an illustrative example are given
5 further below in connection with the figures.

In accordance with the present invention, the packing element is a structured cross-channel packing element. Accordingly, it is preferred that at least 50%, preferably at least 75%, more preferably at least 80%, still more preferably at least
10 90%, yet more preferably at least 95% and most preferably all of the at least two layers are made of expanded metal sheets and comprise periodic deformations, wherein the layers are oriented such that the periodic deformations of the adjacent layers intersect in crisscross fashion with the periodic deformations of the layers extending obliquely relative to the longitudinal direction. At least 50%, preferably at
15 least 75%, more preferably at least 80%, still more preferably at least 90%, yet more preferably at least 95% and most preferably each of the layers contact(s) each of the adjacent layers at points of intersection between the periodic deformations of the layer and those of the adjacent corrugated layers and wherein the open space between the at least two layers is defined by the periodic
20 deformations. Preferably, the distance between the uppermost points of two adjacent periodic deformations of a layer is, depending on the surface area, between 10 and 25 mm and more preferably between 13 and 23 mm.

Good results are in particular achieved, when the stretching factor of the expanded
25 metal sheet of the at least two layers is between 1.1 and 1.5 and more preferably between 1.2 and 1.35.

In accordance with the present invention, the distance u_1 is measured by determining the distance between the outermost point of one side of the edge of
30 one of the openings in the direction perpendicular to the stretch direction of the

expanded metal sheet and the outermost point of the same side of the edge of an adjacent opening in the same direction of the expanded metal sheet. For instance, if a photographic picture of a top view or plan view of a layer of the structured cross-channel packing element is made, wherein the stretch direction is shown in the vertical direction of the photographic picture and the direction perpendicular to the stretch direction is shown in the horizontal direction of the photographic picture, the distance u_1 may be determined as the distance between the outermost point of the left side of the edge of an opening and the outermost point of the left side of the edge of an opening being adjacent to the opening in the same direction of the expanded metal sheet.

In order to particularly precisely determine the distance u_1 , the distance between the outermost point of one side of the edge of an opening in the direction perpendicular to the stretch direction of the expanded metal sheet and the outermost point of the same side of the edge of the fifth or n -th adjacent opening thereto arranged in the direction perpendicular to the stretch direction of the expanded metal sheet may be measured and divided by four or $(n-1)$.

Even more preferably, the distance u_1 is determined by measuring the distance between the outermost point of one side of the edge of an opening in the direction perpendicular to the stretch direction of the expanded metal sheet and the outermost point of the same side of the edge of the tenth adjacent opening thereto arranged in the direction perpendicular to the stretch direction of the expanded metal sheet may be measured and divided by nine.

In accordance with the present invention, the ratio between the distance u_1 between two openings being in the direction perpendicular to the stretch direction of the expanded metal sheet adjacent to a separating element and the average width of this separating element is for at least 50% of all separating elements 4 to 6. Good results are in particular achieved, when the ratio between the distance u_1

and the average width b of at least 75%, more preferably of at least 80%, still more preferably of at least 90%, yet more preferably of at least 95% and most preferably of all separating elements is 4 to 6, preferably 4.5 to 5.5 and more preferably 4.9 to 5.1.

5

In a further development of the idea of the present invention, the distance u_1 is preferably for at least 50%, more preferably for at least 75%, even more preferably for at least 80%, still more preferably for at least 90%, yet more preferably for at least 95% and most preferably for all openings 5 to 20 mm. More preferably, the distance u_1 is preferably for at least 50%, more preferably for at least 75%, even more preferably for at least 80%, still more preferably for at least 90%, yet more preferably for at least 95% and most preferably for all openings is 7.5 to 15 mm and most preferably 9 to 11 mm.

10

15 According to a further particular embodiment of the present invention, the ratio between the distance u_2 between a first opening and a second opening being in the stretch direction of the expanded metal sheet adjacent to each other and the distance u_1 between the first opening and a third opening being in the direction perpendicular to the stretch direction of the expanded metal sheet adjacent to each other is 0.4 to 0.7, wherein the distance u_2 is measured by determining the distance between the outermost point of a side of the edge of the first opening in the stretch direction of the expanded metal sheet and the outermost point of the same side of the edge of the adjacent second opening being adjacent in the stretch direction of the expanded metal sheet, and wherein the distance u_1 is measured as described above.

20

25

Likewise to determining the distance u_1 , the distance u_2 is preferably measured by determining the distance between the outermost point of a side of the edge of the first opening in the stretch direction of the expanded metal sheet and the outermost point of the same side of the edge of the fifth or even tenth (n -th)

30

adjacent opening thereto arranged in the stretch direction of the expanded metal sheet and by dividing the distance by four or nine ($n-1$), respectively.

- Good results are in particular achieved, when the ratio between the distance u_2 and the distance u_1 is for at least 50%, preferably for at least 75%, more preferably for at least 80%, still more preferably for at least 90%, yet more preferably for at least 95% and most preferably for all openings 0.4 to 0.7, more preferably 0.45 to 0.70 and most preferably 0.49 to 0.55.
- 10 In addition, it is preferred that the distance u_2 is for at least 50%, preferably for at least 75%, more preferably for at least 80%, still more preferably for at least 90%, yet more preferably for at least 95% and most preferably for all openings 2 to 8 mm, more preferably 3 to 7 mm and most preferably 4 to 6 mm.
- 15 In accordance with a further particular embodiment of the present invention, the average width b of at least one separating element between adjacent openings is between 70% and 125% of the average hydraulic diameter d of the adjacent openings.
- 20 In a further development of the idea of the present invention, it is suggested that the average width b of at least 50%, preferably of at least 75%, more preferably of at least 80%, still more preferably of at least 90%, yet more preferably of at least 95% and most preferably of all separating elements between adjacent openings is between 70% and 125% of the average hydraulic diameter d of the adjacent
- 25 openings. More preferably, the average width b of at least 50%, preferably of at least 75%, more preferably of at least 80%, still more preferably of at least 90%, yet more preferably of at least 95% and most preferably of all separating elements between adjacent openings is between 75% and 100% of the average hydraulic diameter d of the adjacent openings.

In order to achieve an optimal spreading of the heavy phase on the layer surface, it is preferred that the average width b of at least 50%, preferably of at least 75%, more preferably of at least 80%, still more preferably of at least 90%, yet more preferably of at least 95% and most preferably of all separating elements between adjacent openings is 1.5 to 4.0 mm. More preferably, the average width b of at least 50%, preferably of at least 75%, more preferably of at least 80%, still more preferably of at least 90%, yet more preferably of at least 95% and most preferably of all separating elements between adjacent openings is 1.6 to 3.5 mm and most preferably 1.8 to 3.0 mm.

10

In accordance with the present invention, the ratio between the average width b of at least at least 50% of the separating elements between adjacent openings and the layer material thickness (subsequently also referred to or abbreviated as "s") is at least 15. Particular good results are obtained, when the ratio between the average width b of at least 50% of the separating elements between adjacent openings and the layer material thickness is at least 18. Preferably, the ratio between the average width of at least 75%, more preferably of at least 80%, still more preferably of at least 90%, yet more preferably of least 95% and most preferably of all of the separating elements between adjacent openings and the sheet material thickness is at least 18.

20

In accordance with the present invention, the ratio between the maximum distance D between at least two adjacent of the at least two layers measured in the plane being perpendicular of the longitudinal direction and the average width b of the separating elements is at least 4. This means that the ratio between the maximum distance D between at least two adjacent of the at least two layers measured in the plane being perpendicular of the longitudinal direction and the average width b of at least 50%, preferably of at least 75%, more preferably of at least 80%, still more preferably of at least 90%, yet more preferably of at least 95% and most preferably of all of the separating elements is at least 4.

30

Particular good results are obtained, when the ratio between the maximum distance measured in the plane being perpendicular of the longitudinal direction and the average width of the separating elements between at least 50%,
5 preferably between at least 75%, more preferably between at least 80%, still more preferably between at least 90%, yet more preferably between at least 95% and most preferably between all of the at least two layers is at least 4.

Moreover, it is preferred that the ratio between the maximum distance D between
10 at least 50%, preferably between at least 75%, more preferably between at least 80%, still more preferably between at least 90%, yet more preferably between at least 95% and most preferably between all of the at least two layers measured in the plane being perpendicular of the longitudinal direction and the average width b of the separating elements is at least 5 and more preferably at least 8.

15 In a further development of the idea of the present invention, it is suggested that the ratio of the maximum distance D between at least 50%, preferably between at least 75%, more preferably between at least 80%, still more preferably between at least 90%, yet more preferably between at least 95% and most preferably between
20 all of the at least two layers measured in the plane being perpendicular of the longitudinal direction and the average width b of the separating elements is 4 to 15, preferably 5 to 13 and most preferably 8 to 12.

Good results are in particular obtained, if the maximum distance D between at
25 least 50%, preferably between at least 75%, more preferably between at least 80%, still more preferably between at least 90%, yet more preferably between at least 95% and most preferably between all of the at least two layers measured in the plane being perpendicular of the longitudinal direction is 8 to 80 mm, preferably 12 to 51 mm and most preferably 16 to 30 mm. Accordingly, it is

preferable that the layer width W is 4 to 40 mm, more preferably 6 to 25.5 mm and most preferably 8 to 15 mm.

In accordance with a particular preferred embodiment of the present invention, for
5 at least one of the at least two layers the ratio of the total area of the openings in
the layer divided by the sheet area of the layer, i.e. the void fraction of the layer, is
between 20% and 38%. The sheet area A_s of a layer is according to the present
invention the sum of the physical area of all of the separating elements measured
10 only on one side and the total area of the openings enclosed by the separating
elements. The total area of the openings is just the sum of the (cross-sectional)
areas A of the openings. Furthermore, the sheet area A_s of a structured packing
element is the sum of the sheet areas of the layers included in the structured
packing element. As set out above, the void fraction of the packing layer is the
15 ratio of the total area of the openings in this layer divided by the sheet area of this
layer.

Preferably, for at least 50%, more preferably for at least 75%, still more preferably
for at least 80%, still more preferably for at least 90%, yet more preferably for at
least 95% and most preferably for all of the at least two layers the void fraction of
20 the layer is between 20% and 38%. This allows to obtain the advantages of the
present invention to a particularly high extent.

Furthermore, it is preferred that for at least 50%, more preferably for at least 75%,
still more preferably for at least 80%, still more preferably for at least 90%, yet
25 more preferably for at least 95% and most preferably for all of the at least two
layers the void fraction of the layer is between 25% and 35% and most preferably
between 28% and 32%. This leads to a particularly excellent wetting of the layers
of the structured packing element in accordance with the present invention.

Particularly good results are obtained, if the grid-structure of the expanded metal sheets is uniform, i.e. when all or at least most of the openings and separating elements are identical or at least highly similar to each other. In view of this, it is preferred that at least 50%, more preferably at least 75%, yet more preferably at least 80%, still more preferably at least 90%, yet more preferably at least 95% and most preferably all of the openings of each of the at least two layers have a hydraulic diameter d , which is between 50 and 150%, preferably between 70 and 130%, more preferably between 80 and 120% and most preferably between 90 and 110% of the average hydraulic diameter d of all openings.

10

It is preferred that the hydraulic diameter d of at least 50%, preferably of at least 75%, more preferably of at least 80%, still more preferably of at least 90%, yet more preferably of at least 95% and most preferably of all of the openings of each of the at least two layers is 1.25 to 5.0 mm. Even more preferably the hydraulic diameter d of at least 50%, preferably of at least 75%, more preferably of at least 80%, still more preferably of at least 90%, yet more preferably of at least 95% and most preferably of all of the openings of each of the at least two layers is 2.0 to 4.0 mm most preferably 2.2 to 3.5 mm.

15

In accordance with an alternative embodiment of the present invention, at least 50%, preferably at least 75%, more preferably at least 80%, still more preferably at least 90%, yet more preferably at least 95% and most preferably all of the openings have a shorter characteristic lengths e_2 of 1.0 to 4.0 mm and preferably 2.0 to 3.0 mm and a longer characteristic lengths e_1 of 2.0 to 8.0 mm, preferably 2.5 to 7.0 mm and most preferably 3.0 to 6.0 mm. As set out above, the shorter characteristic length e_2 of an opening is the maximal dimension of the opening in the stretch direction of the expanded metal sheet and the longer characteristic length e_1 of an opening is the maximal dimension of the opening in the direction perpendicular to the stretch direction of the expanded metal sheet.

20

25

30

In a further development of the idea of the present invention, it is suggested that the ratio between the shorter characteristic length e_2 of an opening and the longer characteristic length e_1 of the same opening is for at least 50%, preferably for at least 75%, more preferably for at least 80%, still more preferably for at least 90%,
5 yet more preferably for at least 95% and most preferably for all of the openings 0.4 to 0.7, preferably 0.45 to 0.6 and most preferably 0.49 to 0.55. As set out above, the shorter characteristic length e_2 of an opening is the maximal dimension of the opening in the stretch direction of the expanded metal sheet and the longer
10 characteristic length e_1 of an opening is the maximal dimension of the opening in the direction perpendicular to the stretch direction of the expanded metal sheet.

The present invention is not particularly limited concerning the material of the expanded metal sheets of the structured packing element. For instance, the expanded metal sheets may be made of stainless steel or a compound selected
15 from the group consisting of aluminum, copper, titanium, zirconium and alloys.

Preferably, the sheet material thickness s of each expanded metal sheet is $s = 0.05$ to 0.50 mm, more preferably $s = 0.08$ to 0.20 mm and most preferably $s = 0.09$ to 0.15 .

20 Usually, at least 50%, more preferably at least 75%, even more preferably at least 80%, still more preferably at least 90%, yet more preferably at least 95% and most preferably all of the openings of the layers of the structured packing element have an essentially elliptic, lenticular or trapezoidal cross-section.

25 After production, i.e. cutting and stretching of a metal plate, the resulting expanded metal sheet is not flat anymore. This is the result of deformation, distortion, bending or vaulting of individual separating elements and a relative deformation of separating elements compared to others, e.g. by tilting. Other features like burrs
30 may have resulted from a punching process and therefore contribute to the

thickness. The resulting dimension of the expanded metal sheet is called grid thickness (subsequently also referred to or abbreviated as "g") and may be identical to the layer material thickness (which is the case, if the expanded sheet is flat, because it has been flattened by rolling) or up to several times larger than the layer material thickness. The grid thickness is typically in the order of magnitude of the width b of the separating element and should not be much larger than the width b. Hence, the ratio of the grid thickness g to average width b of the separation elements ranges from more than 0 up to approximately 1.2, more preferably from 0.4 to 1 and most preferably from 0.5 to 0.8. The grid thickness g is significantly smaller than the maximum distance D between two adjacent layers measured in the plane perpendicular of the longitudinal direction.

It is further preferred that the ratio between the average grid thickness g of each layer and the sheet material thickness s is at least 6.

Good results are in particular achieved, when the average grid thickness g of each layer (32, 32') is 1.0 to 1.4 mm, preferably 1.1 to 1.3 mm and more preferably 1.15 to 1.25 mm.

The grid can also be flattened by pressing a plate on top of it as described above.

Another embodiment of the present invention comprises the rolling of the expanded metal sheet so as to provide an expanded metal sheet with a textured surface. More specifically, each of the periodic deformations, such as in particular corrugations, may have a trickle surface including a patterned front including a plurality of protuberances and depressions defining continuous crossing capillary channels. The protuberances may be disposed in abutting relation with adjacent protuberances and may have side walls defining channels therebetween and a patterned back identical to the front and defining continuous crossing capillary channels, such as it is described e.g. in EP 0190435 B1. The protuberances may

have a similar range of height as the grid thickness g without any further treatment.

Preferably, the ratio of the maximum distance D to the grid thickness g (i.e. D/g) is
5 at least 3.

Good results are in particular obtained, when the ratio between the maximum distance D between each adjacent of the at least two layers measured in the plane being perpendicular of the longitudinal direction and the average hydraulic
10 diameter d of the openings is at most 15.

Expanded metal sheets provide, as shown in figure 7c, a rough and a smooth side. Preferably, the single layers of the structured cross-channel packing element are arranged so that onto the rough side of layer an adjacent layer is arranged
15 with its rough side and that onto the smooth side of layer an adjacent layer is arranged with its smooth side.

In a further development of the idea of the present invention, it is suggested that at least 50%, preferably at least 75%, more preferably at least 80%, still more
20 preferably at least 90%, yet more preferably at least 95% and most preferably all of the at least two layers comprise periodic deformations, wherein the open space between the at least two layers is defined by the periodic deformations. It is particularly preferred that all layers of the structured packing element of the present invention comprise such periodic deformations, i.e. that the structured
25 packing element of the present invention does not include any flat layers. Preferably, the angle (subsequently also referred to or abbreviated as " α ") between each of the periodic deformations with respect to the longitudinal direction is 10° to 60° , more preferably 20° to 50° and most preferably 25° to 47° , wherein the periodic deformations of adjacent layers are preferably oriented in
30 opposing directions.

For instance, the periodic deformations may be corrugations comprising a plurality of alternately oriented peaks and valleys, wherein the peaks of a layer contact the valleys of an adjacent layer and the valleys of a layer contact the peaks of an adjacent layer, wherein adjacent layers are oriented such that the peaks and valleys of the adjacent layers intersect in crisscross fashion with the peaks and valleys of the layers extending obliquely relative to the longitudinal direction. Therefore, it is preferred that at least 50%, preferably at least 75%, more preferably at least 80%, still more preferably at least 90%, yet more preferably at least 95% and most preferably all of the at least two layers comprise periodic deformations, wherein the periodic deformations of the cross-package element are corrugations comprising a plurality of alternately oriented peaks and valleys, wherein the peaks of a layer contact the valleys of an adjacent layer and the valleys of a layer contact the peaks of an adjacent layer, wherein adjacent layers are oriented such that the peaks and valleys of the adjacent layers intersect in crisscross fashion with the peaks and valleys of the layers extending obliquely relative to the longitudinal direction. Of course, it is also possible that not all peaks of a layer contact one or more valleys of an adjacent layer, but that rather a part of the peaks of a layer contact one or more valleys of an adjacent layer and vice versa. However, between two adjacent layers at least three touching points should be present. Preferably at 30 to 90% and more preferably at 50 to 80% of the locations, where peaks and valleys of adjacent layers are opposite of each other, no touching contact is present, wherein at the remaining locations the respective peaks and valleys of adjacent layers touch each other.

Good results are in particular obtained in this embodiment, when the angle α between each of the peaks and each of the valleys with respect to the longitudinal direction is 10° to 60°, preferably 20° to 50° and most preferably 25° to 47°, wherein the peaks and valleys of adjacent layers are preferably oriented in opposing directions. This allows a uniform distribution of the light phase over at

least one direction of the cross-section the structured packing element. The angles should not be too large to minimize pressure drop and maximize capacity.

In order to reduce the pressure loss of the structured packing element, it is
5 proposed in a further development of the idea of the present invention that the peaks and valleys are bended in the terminal portions of the layers in relation to the peaks and valleys of the central portion being arranged between the terminal portions so that the flow resistance in the terminal zones of the structured packing element is reduced with respect to that of the zone arranged between the terminal
10 zones. Accordingly, the peaks and valleys of the layers of this embodiment do not extend linearly. Preferably, the peaks and valleys are bended in the terminal portions of the layers so as to extend at least essentially vertically. Essentially vertical means that the peaks and valleys are not inclined at the lower and upper edges of the layers more than 10°; preferably not more than 5° and more
15 preferably not more than 2° to the vertical direction. The terminal zones are the uppermost and the lowermost zones of the layers extending from the upper and lower edges of the layers 30%, preferably 25% and more preferably 20% or less along the sheet length, which is the direction along the longitudinal direction of the layer. Each of the terminal zones may have peaks and valleys with a different
20 height than those of the central zone, which is the zone of the layer between the two terminal zones. Instead of providing such bends or different heights in both terminal zones, they may only be present in one of the terminal zones.

In accordance with an alternative embodiment of the present invention, the
25 periodic deformations are waves having a square, a triangular, a sinusoidal or a meander-type cross-section comprising peaks and valleys, wherein the peaks of a layer contact the valleys of an adjacent layer, and the valleys of a layer contact the peaks of another adjacent layer, wherein adjacent layers are oriented such that the peaks and valleys of the adjacent layers intersect in crisscross fashion with the

peaks and valleys of the layers extending obliquely relative to the longitudinal direction.

Good results are in particular obtained in this embodiment, when the angle α
5 between each of the peaks and each of valleys with respect to the longitudinal direction is 10° to 60° , preferably 20° to 50° and most preferably 25° to 47° , wherein the peaks and valleys of adjacent layers are preferably oriented in opposing directions. This allows a uniform distribution of the light phase over at least one direction of the cross-section of the structured packing element.

10

The present invention is not particularly limited concerning the number of layers contained therein. The number of layers in a packing element depends on the diameter of the mass transfer column and the required specific area a_M for the mass transfer. The more surface is required, i.e. the higher the specific area, the
15 more layers will be present, and the maximum distance D will be smaller, accordingly. Although the structured packing element is generally of cylindrical shape with a round cross-section, there may also be cross-sections of other shapes, e.g. rectangular ones, depending on the shape of the heat and/or mass transfer column. If the column has a large diameter, the element is commonly
20 subdivided into segments or tiles to reduce weight and to allow piece-wise installation.

Particular good combinations of mass transfer efficiency and capacity are obtained, when the structured packing element according to the present invention
25 has a specific area a_M of 60 to $750 \text{ m}^2/\text{m}^3$, 120 to $500 \text{ m}^2/\text{m}^3$ and most preferably 200 to $450 \text{ m}^2/\text{m}^3$.

The specific area a_M is defined as the geometrical area A_M of the structured packing element divided by the volume V_M that the structured packing element
30 occupies. The geometrical area A_M of the structured packing element is the sum of

the geometrical area of all layers comprised in the element, wherein the geometrical area of a layer adds up both sides of the layer as if there were no openings or holes. In other words, the geometrical area is approximately obtained by multiplying the sheet area A_s of the packing layers by two because both sides
5 of the layers account for the geometrical area.

The sheet area A_s of a structured packing layer is obtained by adding both the area of the openings in the layer and the physical area A_P of the layer. A_P counts only surface that is physically present. Holes or openings do not contribute to the
10 value. The sheet area A_s of the structured packing element is obtained by summing the sheet area of all layers comprised therein.

The physical area A_P of a structured packing layer is the sum of the surface measured on one selected side of all separating elements included in the
15 structured packing layer. The edges of the layer material thickness s do not contribute to this area. The physical area A_P of the packing is the sum of the physical area of all layers comprised therein.

Apart from the definitions a_M , A_M , A_s and A_P for areas, the expressions "surface"
20 and "surface area" are used in a more qualitative or intuitive manner in the description of the present invention.

Preferably, the structured packing element has a height of 100 to 300 mm and preferably of 150 to 250 mm.
25

In accordance with a further aspect, the present invention relates to a mass transfer column comprising at least one structured packing element as described above.

Preferably, the mass transfer column comprises 1 to 10, more preferably 2 to 8 and most preferably 2 to 4 beds, wherein each bed comprises at least one structured packing element as described above. Preferably, one bed comprises 2 to 20, more preferably 4 to 15 and most preferably 6 to 10 structured packing elements. In order to achieve a very good gas distribution in the bed, two adjacent structured packing elements are rotated along the axis of the column that is generally parallel to the longitudinal direction. The angle of rotation is around 50 to 120°, more preferably 70° to 110° and most preferably 80° to 100°.

10 In addition, it is preferred that the mass transfer column comprises a distributor above each of the beds of structured packing elements so as to allow to at least essentially homogeneously distribute the heavy phase during the operation of the mass transfer column over the cross-section of the structured packing element bed.

15 In accordance with a further preferred embodiment of the present invention, it is proposed that the mass transfer column comprises below the bottom of each bed of structured packing element a collector, which allows to collect the heavy phase trickling down the surfaces of the layers of the structured packing elements during the operation of the mass transfer column.

Specific embodiments in accordance with the present invention are subsequently described with reference to the appended drawings and by examples.

25 Fig. 1 is a schematic side view of a mass transfer column including several structured cross-channel packing elements according to one embodiment of the present invention.

- Fig. 2a is an explosion view of a part of the sheets of a structured cross-channel packing element according to one embodiment of the present invention.
- 5 Fig. 2b is a schematic side view of the structured cross-channel packing element shown in figure 2a.
- Fig. 2c shows two layers of the structured cross-channel packing element shown in figure 2a.
- 10 Fig. 3 is a fragmentary view of a structured cross-channel packing element according to another embodiment of the present invention.
- Fig. 4a-f are schematic views of different embodiments of the grid structure of the expanded metal sheets of the layers of the structured cross-channel packing element according the present invention.
- 15 Fig. 5a-b are schematic views illustrating the determination of the average width of a separating element and of the average hydraulic diameter of an opening.
- 20 Fig. 6 illustrates the determination of the least deformed portion of a structured cross-channel packing element made of corrugated layers.
- 25 Fig. 7a is a schematic top view of an expanded metal sheet of a layer of a structured cross-channel packing element according to another example of the present invention.
- Fig. 7b-c are schematic views along the planes A and B, respectively, of fig. 7a.
- 30

- Fig. 8 is a schematic plan view of an expanded metal sheet of a layer of a structured cross-channel packing element shown in fig. 7.
- 5 Fig. 9 shows schematic views of the cross-section of a packing layer to illustrate the definitions of the areas A_P (Figure 9b), A_S (Figure 9c), A_M , V_M and a_M (Figure 9d).
- 10 Fig. 10 shows the efficiency curves obtained in example 1 and comparative example 1 for a head pressure of the distillation column of 960 mbar.
- Fig. 11 shows the efficiency curves obtained in example 1 and comparative example 1 for a head pressure of the distillation column of 100 mbar.
- 15 Fig. 12 shows the pressure drops obtained in example 1 and comparative example 1 for a head pressure of the distillation column of 100 mbar.
- Fig. 13 shows the efficiency curves obtained in example 2 and comparative examples 2 and 3 for a head pressure of the distillation column of 960 mbar.
- 20 Fig. 14 shows the efficiency curves obtained in example 2 and comparative examples 2 and 3 for a head pressure of the distillation column of 100 mbar.
- 25 Fig. 15 shows the pressure drops obtained in example 2 and comparative examples 2 and 3 for a head pressure of the distillation column of 100 mbar.

Figure 1 shows is a schematic side view of a mass transfer column 10 and more specifically a distillation column 10 according to one embodiment of the present invention (the transparent inside of the figure is only for illustrative purposes). Also for illustrative purposes, the grid structure of the layers in not shown in figure 1, but only in figure 4. The distillation column 10 comprises a plurality of structured cross-channel packing elements 12, which are arranged in form of two beds 14, 14'. Above each of the two beds 14, 14' a distributor 16, 16' is arranged to evenly distribute the liquid over the cross-section of the bed, while leaving enough space for the vapor to ascend through it. Below each bed 14, 14' a grid-like holding device 18 and a collector 20 are arranged, wherein the grid-like holding device 18 keeps the bed 14 at its position and the collector 20 collects the liquid trickling down from the bed 14, while sufficient open space is left in the collector for the vapor to ascend.

During the operation of the distillation column 10, gas ascends as light phase from the bottom to top, whereas liquid as heavy phase descends in counter-current from the top to the bottom of the distillation column 10. More specifically, the liquid is essentially homogenously distributed by the distributor 16 over the cross-section of the bed 14 and trickles down along the surfaces of the layers of the structured cross-channel packing elements 12. Between the different layers of the structured cross-channel packing elements 12 open spaces are provided, which are filled with the gas and provide a path for the gas to ascend, while it is driven by a pressure gradient. By allowing the liquid to spread on the surface of the layers of the structured cross-channel packing elements 12, a large interface is created between the two phases so that an efficient heat and mass transfer between the liquid and the gas is established at the interface. At the bottom of the bed 14, the liquid is collected in the collector 20 and guided via the pipe 22 down to the distributor 16' above the second bed 14'.

Figures 2a to 2c show a structured cross-channel packing element 12 of the so-called cross-channel corrugated sheet packing type. For illustrative purposes, the grid structure of the layers is not shown in figure 2, but only in figure 4. The structured cross-channel packing element 12 is assembled from a plurality of

5 corrugated sheets 24, 24', which are parallel and in touching contact with each other. Each of the corrugated sheets 24, 24' is a grid as described above and as described in further detail below according to figures 4. At the bottom right of figure 2c the grid-structure of a part of the corrugated sheet 24 is schematically indicated. As it is understood from the above specification, indeed all of the

10 corrugated sheets 24, 24' consists of such grids, which is not shown in figures 2a to 2c only for illustrative reasons. In the present embodiment, the corrugated sheets 24, 24' are made of expanded sheet material, i.e. they are prepared by cutting and stretching a thin metal plate and then deforming the expanded sheet metal to corrugated sheets 24, 24'.

15 The corrugated metal sheets 24, 24' are fixed with each other by means of several rods (not shown) penetrating the corrugated sheets 24, 24' perpendicular to the longitudinal section of the corrugated sheets 24, 24', wherein the rods are fixed with the first and last corrugated sheet by means of a washer and a nut or by

20 bending the rods or by any other means (not shown). Each corrugated sheet 24, 24' comprises a plurality of alternately oriented peaks 26 and valleys 28, wherein adjacent corrugated sheets 24, 24' are oriented such that the corrugations 26, 28 of the adjacent corrugated sheets 24, 24' intersect in crisscross fashion with the corrugations 26, 28 of the corrugated sheets 24, 24' extending obliquely relative to

25 the longitudinal direction, thus forming inclined channels 30 which continuously cross one another. More specifically, angle α between each of the peaks 26 and each of the valleys 28 with respect to the longitudinal direction V is 10° to 60° , preferably 20° to 50° and most preferably 25° to 47° , wherein the peaks 26 and valleys 28 of adjacent layers 32, 32' or 24, 24', respectively, are oriented in

30 opposing directions. The channels 30 define a maximum distance D between

adjacent corrugated sheets 24, 24', such as for example of 20 mm. These channels 30 positively influence the flows of the gas phase and of the liquid phase within the structured packing cross-channel element 12 and facilitate the mass transfer between the phases. That is, the gas phase and liquid phase are brought
5 into contact in the channels 30 of the structured cross-channel packing element 12 and the mass transfer as well as the heat transfer between the phases is thus facilitated. More specifically, ascending gas comes into contact with liquid, which is present on the surface of the corrugated sheets 24, 24' defining the channels 30, when it flows downwardly through the mass transfer column. All in all, the light
10 phase flows through the open space or channels 30, respectively, without a bypass flow through the openings 40 of the grid 38 of the layers 32, 32' of the structured cross-channel packing element 12. This leads to a particular efficient mass and energy transfer between the light and heavy phases. Moreover, the crisscross fashion of the channels 30 leads to an optimal distribution of the phases
15 from left to right.

Figure 3 shows a fragmentary view of a structured cross-channel packing element in accordance with an alternative embodiment. The structured cross-channel packing element of figure 3 is similar to that shown in Figures 2a to 2c except that
20 corrugated sheets 24, 24' do not comprise linear extending peaks and valleys, but that the peaks 26, 26' and valleys of the corrugated sheets 24, 24' are bended in the terminal portions 33, 33' so as to extend in the terminal portions 33, 33' of the corrugated sheets 24, 24' essentially in the vertical direction. In Figure 3, the solid lines depict the peaks 26 of the corrugations in the face of the corrugated sheet 24
25 presented to the viewer, while the broken lines 26' depict the peaks of the corrugations in the corresponding face of the corrugated sheet 24' immediately behind the one in view. By bending the terminal portions or zones 33, 33', respectively, so as to extend in the terminal portions 33, 33' of the corrugated sheets 24, 24' essentially in the vertical direction, the flow resistance of the
30 terminal portions 33, 33' of the corrugated sheets 24, 24' is reduced compared to

the flow resistance of the portions being located between the terminal portions 33, 33' of the corrugated sheets 24, 24'. This leads to a reduced pressure loss of the structured cross-channel packing element. The terminal zones are the uppermost and the lowermost zones 33, 33' of the corrugated sheets 24, 24' extending from
5 the upper and lower edges of the corrugated sheets 24, 24' 30%, preferably 25% and more preferably 20% or less along the length of the corrugated sheets 24, 24', which is the direction along the longitudinal direction of the corrugated sheets 24, 24'. Each of the terminal zones 33, 33' may have peaks 26, 26' and valleys with a different height than those of the central zone, which is the zone of the layer
10 between the two terminal zones 33, 33'. Such features as the different height or the bend may be present in both terminal zones 33, 33' of the corrugated sheets 24, 24' only.

Figures 4a to 4f are schematic views of different embodiments of the grid 38 that
15 forms the layers 32 of the structured cross-channel packing element 12 according to the present invention, which are for instance suitable to be used in a structured cross-channel packing element as shown in any of figures 2a to 2c and 3. The grid 38 of the layer 32 of the structured cross-channel packing element shown in figure 4a comprises openings 40 with a quadrilateral cross-section, wherein the openings
20 40 are surrounded and separated from each other by separating elements 42. The separating elements 42 are thin strips with an average width b of, for example, 2 mm, wherein the separating elements 42 completely surround the openings 40. The two side lengths a_1 , a_2 of the openings 40 are selected so as to result in an opening 40 with a suitable hydraulic diameter d of, for instance, 3 mm. As known
25 in the field, the hydraulic diameter d may be calculated in accordance with the formula $4 A / P$, wherein A is the cross-sectional area of the opening 40 and P is the perimeter of the opening 40.

The grid 38 is simply produced of expanded sheet material, i.e. by cutting and stretching a thin metal plate and then deforming the expanded sheet metal to the desired form, such as to a corrugated sheet.

- 5 Grids 38 with a different geometry of the openings 40 and a different geometry of the separating elements 42 are shown in figures 4b to 4f. The openings 40 of the grids 38 of figures 2b and 2c are quadrilateral, whereas the openings 40 of the grid 38 of figure 2d are irregular and the openings 40 of the grids 38 of figures 2e and 2f are ellipsoid. They may also be of lenticular shape.

10

- Subsequently, the determination of the width b of a separating element 42 and of the hydraulic diameter d of an opening 40 of the grid 38 of a structured packing element in accordance with the present invention is described under reference to figures 5a and 5b. First of all, several plan views of one of the openings 40, 40' of the structured packing element 12 are made by taking three photographic pictures 15 44a, 44b, 44c of the opening 40 under different angles. The plan views of the opening 40 photographic pictures 44a, 44b, 44c are taken along the normal axis of the plane defined by the adjacent edges 48, 48' of the separating element 42. The photographic picture 44b that renders the opening 40 largest is then taken as the plan view of the opening 40. One reference length z is used to determine lengths and sizes on the plan view. This is achieved by identifying or marking a certain distance z on the real object in the neighborhood of the opening 40 and measuring its length. The ratio between the effective length z' of this distance on the plan view and the appearing distance z measured on the real object is used for scaling 20 all other distances that are measured on the plan view.

- For determining the width b of a separating element 42, the separating element 42 of the plan view is divided up into individual sections 46 designated $i=1, 2, 3 \dots n$ each having a section length d_i . For each of the sections, the shortest distance b_i 30 between the adjacent edges 48, 48' within the sections 46 is measured. The sum

of the products $d_i b_i$ divided by the sum of d_i multiplied with the coefficient z/z' yields the average width b of the separating element 42.

The hydraulic diameter of the opening 40 is calculated with the formula $4 A / P$,
5 wherein A is the cross-sectional area of the opening 40 and P is the perimeter of the same opening 40. The cross-sectional area of the opening 40 is subdivided in a number $j=1, 2, 3 \dots m$ of sections 50 each having a simple shape. The area of each section 50 is designated A_j and is calculated using basic measures and basic geometric formula. The area A of the opening 40 is obtained by summing up all
10 areas A_j determined in the opening 40.

The perimeter P of the opening 40' is determined by subdividing the perimeter P of the opening 40' in a number of $k=1, 2, 3 \dots K$ individual straight lines P_k that approximate the opening 40' best and represent it by a closed polygon. By
15 summing up the lengths of these straight lines P_k , the perimeter P is obtained. Again, the lengths must be translated into real lengths using the ratio z/z' as defined above.

Figure 6 illustrates the determination of the least deformed portion of a structured
20 packing element made of corrugated sheets 24, 24' as layers 32, 32'. As set out above, in preferred embodiments of the present invention, the layers 32, 32' of the structured packing element 12 are made of expanded sheet metal, i.e. by cutting and stretching a thin metal plate and then deforming the expanded sheet metal to, for instance, corrugated sheets 24, 24'. After this processing, the openings and
25 separating elements are likely to be distorted and/or stretched around the peaks 26 and the valleys 28 of the corrugations of the corrugated sheets 24, 24'.

However, the inclined flanks, which are defined by the approximately straight portion of the grid connecting the peaks 26 and the valleys 28, include openings
30 and separating elements of almost unmodified sizes, because deformation is less

pronounced there. It is therefore preferred according to the present invention to measure the dimensions only in the portion of the layer that is less deformed, which is designated a "least deformed portion" of the corrugated sheets 24, 24'. This "least deformed portion" is defined as follows: The corrugated sheet has an

5 average layer width W. This average layer width is determined by the amplitude of the majority of the peaks 26 and valleys 28 of the layer 24. An upper and a lower plane represented by two dashed lines in the figure below are drawn to touch the majority of the peaks 26 and the valleys 28 of the layer. The distance between these two dashed lines is called average layer width W, and it is typically around

10 half the maximum distance D. The value W is very often a constant value, but it may vary in the most general case as the two planes do not need to be parallel and a packing element may contain layers of different width. A third center plane 52 is defined, which is placed in such a way, that from each point on this center plane 52, the distance measured to the upper and the lower plane is identical. The

15 least deformed portion of the corrugated layer 24, which shall be considered when determining the characteristic dimensions of the grid, is bordered by an upper and a lower limiting plane 54, 54', which is positioned at $\pm 20\%$, more preferably $\pm 30\%$ and most preferably $\pm 40\%$ of W around the center plane 52. The openings and separating elements in this least deformed portion, i.e. the openings and

20 separating elements found between these two limiting planes 54, 54', are analyzed when determining the parameters, such as average hydraulic diameter of the holes and average widths of the separating elements. According to one embodiment of the present patent application for at least 90% of the holes between the limiting planes the following is valid: Each opening with its

25 surrounding system of separating elements shall have the same appearance and identical hydraulic diameter d. The surrounding separating elements shall on average have the same width b. A structured packing element layer that fulfills this statement is considered a layer made of a uniform grid.

The above observations are also valid for layers of any different shape. It is not limited to corrugated layers.

Fig. 7a is a schematic top view of an expanded metal sheet of a layer of a
5 structured cross-channel packing element according to another example of the
present invention. The top view has been made by taking a photographic picture of
the expanded metal sheet after having flattened the expanded metal sheet by
laying the expanded metal sheet on a flat surface, putting a plate on the top of the
expanded metal sheet and then pressing a plate on the top of the expanded metal
10 sheet downwards with a sufficiently low pressure so as to just flatten the expanded
metal sheet, without changing the geometry and dimensions of the separating
elements and openings. The expanded metal sheet comprises openings 40, 40',
40'', 40''' having an essentially trapezoidal form, which are separated from each
other by the separating elements 42. Accordingly, the openings 40, 40', 40'' have
15 a shorter characteristic length e_2 and a longer characteristic length e_1 , wherein the
shorter characteristic length e_2 of an opening 40, 40', 40'' is the maximal
dimension of the opening in the stretch direction SD of the expanded metal sheet
and the longer characteristic length e_1 of an opening 40, 40', 40'' is the maximal
dimension of the opening in the direction perpendicular to the stretch direction SD
20 of the expanded metal sheet. The stretch direction SD of the expanded metal
sheet is that direction, along which the sheet metal has been stretched during the
production of the expanded metal sheet. For instance, the longer characteristic
length e_1 of the openings 40, 40', 40'' is determined by measuring the distance
between the outermost left point to the outermost right point of the edge of the
25 opening 40'' in the direction perpendicular to the stretch direction SD of the
expanded metal sheet, whereas the shorter characteristic length e_2 of the
openings 40, 40', 40'' may be determined by measuring the distance between the
uppermost point and the lowermost point of the edge of the opening 40. In order to
particularly precisely determine the characteristic lengths e_1 and e_2 , the respective
30 dimensions may be measured for at least 5 different openings 40, 40', 40'' and

more preferably for at least 10 different openings 40, 40', 40'' and by then dividing the sum of the measured values by five or ten, respectively.

The distance u_1 between two openings 40, 40', 40'' being in the direction

5 perpendicular to the stretch direction SD of the expanded metal sheet adjacent to each other and separated by a separating element 42 is determined by measuring the distance between the outermost point of a side of the edge of the opening 40 and the outermost point of the same side of the edge of the opening 40'' being adjacent in the direction perpendicular to the stretch direction SD of the expanded

10 metal sheet. In figure 7a, the distance u_1 is determined by measuring the distance between the outermost point of the left side of the edge of the opening 40 and the outermost point of the left side of the edge of the opening 40'' being adjacent in the direction perpendicular to the stretch direction SD of the expanded metal sheet. In addition, the distance u_2 between two openings 40, 40' being in the

15 stretch direction SD of the expanded metal sheet adjacent to each other and separated by separating element 42 is determined by measuring the distance between the outermost point of a side of the edge of the opening 40 in the stretch direction SD of the expanded metal sheet and the outermost point of the same side of the edge of the opening 40' being adjacent in the stretch direction SD of

20 the expanded metal sheet. In figure 7a, the distance u_2 is determined by measuring the distance between the uppermost point of the upper side of the edge of the opening 40 in the stretch direction SD of the expanded metal sheet and the uppermost point of the upper side of the edge of the opening 40' being adjacent in the stretch direction SD of the expanded metal sheet. In order to particularly

25 precisely determine the distance u_1 , the distance u_1 may be determined by measuring the distance between the outermost point of one side of the edge of an opening 40 in the direction perpendicular to the stretch direction of the expanded metal sheet and the outermost point of the same side of the edge of the fifth or tenth adjacent opening in the same direction of the expanded metal sheet and by

30 dividing the distance by four or nine, respectively. Likewise thereto, the distance u_2

may be determined by measuring the distance between the outermost point of a side of the edge of the opening 40 in the stretch direction of the expanded metal sheet and the outermost point of the same side of the edge of the fifth or tenth adjacent opening thereto arranged in the stretch direction of the expanded metal sheet and by dividing the distance by four or nine, respectively.

Again, the dimensions determined on the photographic picture may be translated into the real lengths by using the coefficient z/z' as defined above.

10 From the aforementioned values, the area of the openings 40, 40', 40'', 40''' and the length of the perimeter P length can be obtained by the following equations if the openings are of exactly rhombic shape:

$$A = e_1 \cdot e_2 / 2$$

$$P = 2 \cdot \sqrt{(e_1^2 + e_2^2)}$$

15

Furthermore, expanded metal sheet can be characterized by means of the stretching factor, which is defined as $f_s = u_2/2b$.

Fig. 7b and 7c are schematic views along the planes A of fig. 7a and B of fig. 7b, respectively. As shown in these figures, the expanded metal sheet resulting from the production process, i.e. by cutting and stretching a metal plate, is not flat anymore. This is the result of deformation, distortion, bending or vaulting of individual separating elements and a relative deformation of separating elements compared to others, e.g. by tilting. Other features like burrs may have resulted from a punching process and therefore contribute to the thickness. The resulting dimension of the expanded metal sheet is the grid thickness g and may be identical to the layer material thickness (which is the case, if the expanded sheet is flat, because it has been flattened by rolling) or up to several times larger than the layer material thickness. Another embodiment of the present invention comprises the rolling of the expanded metal sheet so as to provide an expanded metal sheet

with a textured surface. More specifically, each of the periodic deformations, such as in particular corrugations, may have a trickle surface including a patterned front including a plurality of protuberances and depressions defining continuous crossing capillary channels. The protuberances may be disposed in abutting
5 relation with adjacent protuberances and may have side walls defining channels therebetween and a patterned back identical to the front and defining continuous crossing capillary channels, such as it is described e.g. in EP 0190435 B1. The protuberances may have a similar range of height as the grid thickness g without any further treatment. The grid thickness g is typically in the order of magnitude of
10 the width b of the separating element and should not be much larger than the width b . Hence, the ratio of the grid thickness g to average width b of the separation elements ranges most preferably from 0.5 to 0.8. The grid thickness g is significantly smaller than the maximum distance D between two adjacent layers measured in the plane perpendicular of the longitudinal direction.

15

Fig. 8 is a schematic plan view of the expanded metal sheet of a layer of the structured cross-channel packing element shown in fig. 7. The plan view is obtained as described above.

20 Figure 9 shows schematic views of the cross-section of a packing layer in order to explain how to distinguish the various expressions for the area of surfaces. Figure 9a shows a cross-section of a typical layer of the structured packing element 12. The material forming the separating elements 42 is represented by the black lines, whereas the white portions represent openings 40, 40' in the layer 32, 32'. Each
25 black portion is a cross-section through a separating element 42. The thickness of the black lines represents the layer material thickness s . In Figures 8b to 8d the areas on this layer are represented just by thinner lines that follow the layer contour. The physical area A_P of a structured packing layer 32, 32' is shown in Figure 9b. It is the sum of the surface measured on one selected side of all its
30 separating elements 42. The edges (having a typical width s) 48, 48' of the

separating elements 42 do not contribute to this area. Rather, A_P counts only surface that is physically present. Thus, holes do not contribute to the value. The physical area A_P of the structured packing element 12 is the sum of the physical area A_p of all layers 32, 32' comprised therein. Figure 9c defines the sheet area A_s of a packing layer. It is obtained by adding both the area of the openings in the layer and the physical area A_p of the layer. The sheet area A_s of the structured packing element 12 is obtained by summing the sheet area A_s of all layers 32, 32' comprised therein. The geometrical area of the layer A_M as defined in Figure 9d adds up both sides of the layer as if there were no openings 40, 40' or holes. In other words, the geometrical area A_M is approximately obtained by multiplying the sheet area A_s of the packing layers by two, because both sides of the layers account for the geometrical area A_M . The specific area a_M is defined as the geometrical area A_M of the structured packing element divided by the volume V_M that the structured packing element occupies.

15

Examples and Comparative Examples

Structured packing element 12 as shown in Figure 2 were tested in a distillation column. The commonly known standard procedure determines the pressure drop over the packing bed and the mass transfer efficiency using a binary mixture under total reflux condition. Patent EP 0 995 958 B1 describes such a test with oxygen and argon at a pressure of 22 psia. US 6,874,769 B2 describes to test structured packing elements by using the close-boiling binary mixture para- and ortho-xylene. A binary mixture of similar ideal characteristics as the latter was used in the present invention, namely monochlorobenzene (as low-boiler) and ethylbenzene (as high-boiler). Other standard close-boiling ideal binary mixtures to assess the performance of distillation equipment are specified in U. Onken, W. Arlt: "Recommended Test Mixtures for Distillation Columns", 2nd Ed. 1990, The Institution of Chemical Engineers, Rugby, England. ISBN 0-85295-248-1.

- The bottom of a distillation column was filled with a sufficient amount of the binary mixture to maintain a decent liquid level during operation of the column. The reboiler was started, a part of the liquid mixture was continuously vaporized, and the vapor rose towards the head of the column. The flow rate of the vapor can be
- 5 expressed in terms of the factor F and is commonly determined indirectly via the energy balance at the reboiler or at the condenser at the column head. The condenser cooled the vapor such that it condensed back to liquid. Under the preferred total reflux conditions, the entire amount of liquid was sent back to the top of the packing bed, where it was distributed by means of a distributor. The
- 10 distributor is typically a device comprising channels that receive the liquid and provide an evenly spaced set of orifices through which the liquid can trickle down onto the top packing of the structured packing bed. After trickling through the structured packing bed, the entire amount of liquid was collected at the bottom of the column or at the bottom of the bed by means of a collector from where it was
- 15 sent back to the bottom of the column. At the bottom the liquid joined the liquid pool from which it was vaporized again. A constant head pressure p was established by controlling the cooling duty of the condenser in combination with a vacuum pump to remove surplus inert gases.
- 20 After a certain time of operation at constant reboiler duty a steady state condition was achieved. At this point, the pressure drop over the packing bed and temperatures at relevant points along the column were read, and top and bottom samples of the mixture were taken from the distributor at the top of the packing bed and from the collector at the lower end of the packing bed or from the sump.
- 25 Several operating points were measured by varying the heat (and cooling) duty, which affects the factor F (vapor flow) and the related liquid flow through the packing bed while the head pressure was kept unchanged. The same experiment was repeated for several settings of the head pressure.

The compositions of the samples were analyzed by means of a calibrated gas chromatograph. The top and bottom samples varied by the amount of low-boiler they contain. More low-boiler, i.e. the compound with the lower boiling temperature, was found in the top sample than in the bottom sample. Once the
5 binary compositions were known, the equation according to Fenske (M. R. Fenske, Ind. Engng. Chem. 24, p. 482, 1932) was applied to determine the number of Theoretical Stages per Meter (NTSM). Sometimes, the inverse value HETP was used, which is called Height Equivalent to a Theoretical Plate.
HETP = 1 / NTSM

10

A high NTSM (or a low HETP) means a good mass transfer efficiency.

The factor F is defined by:

$$F = v_G \sqrt{\rho_G}$$

15 wherein v_G is the average velocity of the rising vapor, which can be determined from the mass flow rate via an energy balance at the reboiler. The second variable ρ_G is the vapor density at the relevant vapor/liquid equilibrium. Due to the change in pressure and temperature along the column the vapor density and other physical properties of the fluids varied along the column, but the relevant
20 information is available for the binary mixture. Such variations require to select an appropriate definition of the factor F. It may be determined by means of the properties valid under the conditions at the top or at the bottom of the packing bed. Alternatively, an average value may be computed taking into account the variation over the entire bed. For comparison purpose any of the possible approaches
25 works, provided the same approach is used for all tests.

A high factor F means a high mass flow rate in the column. The value of F that is achievable is usually limited by the flooding which determines the capacity of a packing. Sometimes the capacity factor c is used instead of F, which is obtained by dividing F by the square root of the density difference of the liquid and the
30 vapor.

The pressure drop over the packing bed was another relevant result of the experiment. It was obtained as the difference of the pressure readings at the top and at the bottom of the packing bed after dividing by the bed height H_B :

$$\Delta P / \Delta z = (p_{\text{top}} - p_{\text{bottom}}) / H_B$$

Five kinds structured packing elements were used in the examples and comparative examples, which were named P1-250, R-250, P2-500, P3-500 and R-500. While the structured packing elements P1-250 and P2-500 were cross-channel corrugated sheet packings made of layers according to the present invention, the structured packing elements P3-500, R-250 and R-500 were structured packing elements not in accordance with the present invention. More specifically, the structured packing elements R-250 and R-500 were known standard cross-channel corrugated sheet packings with punched holes (leading to approximately 10% void fraction of the layers) and surface texturing as described in GB 1,569,828 and in US 4,981,621, which are commercially distributed under the names Mellapak 250.Y and Mellapak 500.X. All structured packing elements had a height of around 200 mm. The relevant parameters of the aforementioned structured packing elements are summarized in table 1.

Table 1

Parameter	P1-250	P2-500	P3-500	R-250	R-500
Angle of corrugation α	45°	30°	30°	45°	30°
Specific area a_M (m ² /m ³)	250	500	500	250	500
Hydraulic diameter d (mm)	2.46	2.46	1.54		
Width of separating element b (mm)	2	2	0.7		
$b/d =$	81%	81%	45%		
Max. distance D (mm)	22.5	13	13	22.5	13
$D/b =$	11.3	6.5	18.6		
Side length a_1 (mm)	3.1	3.1	1.9		

Longer distance u_1 (mm)	10	10	5		
$u_1/b =$	5	5	7.2		
Shorter distance u_2 (mm)	5	5	2.5		
Longer diagonal e_1 (mm)	5.5	5.5	3.4		
Diagonal ratio e_2/e_1	0.5	0.5	0.5		
Grid thickness g (mm)	1.2	1.2	0.75		
Void fraction of the layer	30%	30%	47%	10%	10%
Layer material thickness s (mm)	0.1	0.1	0.1	0.1	0.1
$b/s =$	20	20	7		
	this invention		prior art	prior art	

Example 1 and Comparative Example 1

The structured packing element according to the invention P1-250 and the
 5 reference structured packing element R-250 not in accordance with the present
 invention were tested in a distillation column with 1 m inner diameter at total reflux
 using monochlorobenzene and ethylbenzene at head pressures of $p=960$ mbar
 (close to atmospheric) and $p=100$ mbar. The packing beds were 4.3 m high. The
 obtained efficiency curves are shown in Figure 10 and Figure 11. In both cases,
 10 the structured packing element P1-250 according to the invention showed in
 comparison to the reference structured packing element R-250 a higher mass
 transfer efficiency (higher NTSM) and even a slightly extended capacity, which is
 characterized by the factor F , where the efficiency suddenly plummets. It is
 remarkable and surprising that the structured packing element P1-250 with 30%
 15 less material usage (and 20% less physical area A_P) than the reference structured
 packing element R-250 achieves the better mass transfer result.

The pressure drops of both structured packing elements is shown in Figure 12 and
 were very similar. Accordingly, the structured packing element P1-250 according
 20 to the invention had a higher pressure drop at low F -factor, but the slope was

lower, which provided the new packing with its capacity advantage and a lower pressure drop at high flow rates.

Example 2 and Comparative Examples 2 to 3

5

The structured packing element P2-500 according to the invention and the reference structured packing element R-500 were tested in a column with 0.25 m inner diameter at total reflux using monochlorobenzene and ethylbenzene at head pressures of $p=960$ mbar and $p=100$ mbar. Furthermore, the structured packing element P3-500 was tested. Despite its similarity with P2-500, structured packing element P3-500 was quite different in as much as significant geometrical parameters are set to values outside the numeric value ranges as specified in the present invention. More specifically, for the structured packing element P3-500 the ratio of the distance u_1 between adjacent openings measured perpendicular to the stretch direction and the average width of the separating elements u_1/b was 7.2 and the ratio of the average width of the separating elements to the layer material thickness b/s was 7, i.e. both of these ratios were outside the numeric value ranges as specified therefore in the present invention. The packing beds with P2-500 and P3-500 were 2.4 m high and the packing bed with the reference R-500 had a height of 2.6m.

The obtained efficiency curves for these structured packing elements are shown in Figure 13 and Figure 14 and the obtained pressure drops for these structured packing elements in Figure 15.

25 The better efficiency of the structured packing element P2-500 according to the present invention in comparison to the structured packing elements P3-500 and R-500 (not in accordance with the present invention) can be easily derived in Figures 13 and 14 for both, a head pressure of 960 mbar as well as a head pressure of 100 mbar. The spread in mass transfer efficiency is especially striking at the low head pressure. Interestingly, P3-500 has a nice capacity, but the efficiency is

30

significantly below that of R-500. Both structured packing elements P2-500 and P3-500 have initially a higher pressure drop than that of R-500, but as F increases, they gain advantage and the higher capacity of both can also be recognized in this graph.

List of Reference Numerals and Abbreviations

5	10	Mass transfer column / distillation column
	12	Structured cross-channel packing element
	14, 14'	Beds of structured packing elements
	16, 16'	Distributor
	18	Holding device
10	20	Collector
	22	Pipe
	24, 24'	Corrugated sheets
	26	Peak of a layer
	26'	Peak of an adjacent layer
15	28	Valley
	30	Channel / open space
	32, 32'	Layers
	33, 33'	Terminal portions of a corrugated sheet
	34	Dimple
20	36	Dimple valley wall
	38	Grid
	40, 40', 40'', 40'''	Opening of the grid
	42	Separating element of the grid
	44a, 44b, 44c	Photographic pictures of an opening taken under different
25		angles
	46	Section of a separating element
	48, 48'	Edges of a section of a separating element
	50	Section of an opening
	52	Center plane

54, 54'		Upper and lower limiting planes determining the least deformed portion of a structured packing element made of corrugated layers
5	A	Cross-sectional area of an opening
	a_1	Side length of an opening
	a_2	Second side length of an opening
	a_M	Specific area of a packing or a layer
	A_j	Area of a section of the opening
10	A_M	Geometrical area
	A_P	Physical area
	A_s	Sheet area
	b	Average width of the separating elements
	b_i	Shortest distance between the adjacent edges of a section of
15		the separating element
	d	Average hydraulic diameter of the openings
	d_i	Length of a section of the separating element
	e_1	Longer characteristic length of the opening
	e_2	Shorter characteristic length of the opening
20	g	Grid thickness
	s	Layer material thickness
	D	Maximum distance between at least adjacent of the at least two layers / corrugated sheets
	P	Perimeter of an opening
25	P_k	Straight lines of perimeter sections of an opening
	SD	Stretch direction of expanded metal sheet
	u_1	Distance between two openings being adjacent in the direction perpendicular to the stretch direction of the expanded metal sheet

	u_2	Distance between two openings being adjacent in the stretch direction of the expanded metal sheet
	V	Longitudinal direction, which is usually the vertical direction
	W	Average layer width of a layer or a corrugated sheet
5	z	Reference length of the layer
	z'	Reference length on plan view of photographic picture
	α	Angle between each of the peaks and each of the valleys with respect to the longitudinal direction
10		