

THERMAL CONDUCTIVE CYLINDER INSTALLED WITH U-TYPE CORE PIPING AND LOOP PIPING

BACKGROUND OF THE INVENTION

5 (a) Field of the Invention

The present invention relates to a thermal conductive cylinder installed with U-type core piping and loop piping for being installed within the thermal storage body (500) composed of natural thermal storage body, such as shallow surface of the earth, or pool, lake, river,
10 ocean, etc, or artificial objects in solid, or gaseous, or liquid state; wherein the thermal conductive cylinder installed with U-type core piping and loop piping is constructed through that the piping segments of fluid inlet terminal and/or outlet terminal of the U-type core piping and loop piping are directly made of thermal insulating material, or thermal insulating
15 structure is installed between the inlet terminal and the outlet terminal; so as to prevent thermal energy loss because of thermal conduction between adjacent piping segments of inlet terminal and outlet terminal on the same side when thermal conductive fluid with temperature difference passing through.

20 (b) Description of the Prior Art

Traditionally, thermal energy loss often occurs in U-type piping device of U-type piping heat exchanger, because of thermal conduction by temperature difference between adjacent piping segments of fluid inlet terminal and fluid outlet terminal installed on the same side when fluid
25 with temperature difference passing through.

SUMMARY OF THE INVENTION

The present invention relates to radial U-type pipelines for passing thermal energy through each other, wherein the piping segments of the
30 U-type fluid piping inlet terminal and/or outlet terminal, which are radial

U-type pipelines for passing thermal energy through each other, are directly made of thermal insulating material, or thermal insulating structure is installed between the inlet terminal and the outlet terminal; and the above piping system is installed within the thermal conductive cylinder made of thermal conductive material; so as to prevent thermal energy loss because of thermal conduction by temperature difference between adjacent piping segments with temperature difference of inlet terminal and outlet terminal installed on the same side when fluid with temperature difference passing through.

10

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows an embodiment of conventional U-type piping (100) installed within the thermal storage body (500);

FIG. 2 shows an embodiment of conventional U-type piping (100) installed within the columnar thermal conductive body (300), wherein the columnar thermal conductive body (300) is placed within the thermal storage body (500);

FIG. 3 is a structural schematic view showing that two or more radially arranged U-type piping sections are installed within thermal conductive cylinder, and the thermal insulating structure is installed at where close to the peripheral of piping group with same flow direction which concentrates toward axial core, according to the present invention;

FIG. 4 is a section view of FIG. 3;

FIG. 5 is a structural schematic view of an embodiment showing that multiple sets of U-type piping jointly connects to the first fluid inlet and outlet terminal (1101) of the common piping (200) constituted by larger diameter piping installed at the core of the columnar thermal conductive body (300), according to the present invention;

FIG. 6 is a section view of FIG. 5;

FIG. 7 is a schematic view of an embodiment, showing that piping

segments of first fluid inlet and outlet terminal (101) and second fluid inlet and outlet terminal (102) in U-type wavy piping (600) are wavyly arranged along the axial direction and near the edge of the columnar thermal conductive body (300), according to the present invention;

5 FIG. 8 is a section view of FIG. 7;

FIG. 9 is a schematic view of an embodiment, showing that the piping segment of the first fluid inlet and outlet terminal (101) in U-type wavy piping (600) is placed near the center of the columnar thermal conductive body (300), the piping segment between the second fluid inlet and outlet terminal (102) is placed near the periphery of the columnar thermal conductive body (300), and the U-type wavy piping (600) between the two piping segments is wavyly arranged along the axial direction and near the edge of the columnar thermal conductive body (300), according to the present invention;

15 FIG. 10 is a section view of FIG. 9;

FIG. 11 is a schematic view of an embodiment, showing that the spiral piping segment of the first fluid inlet and outlet terminal (101) and the second fluid inlet and outlet terminal (102) in U-type spiral piping is spirally arranged along the axial direction and near the edge of the columnar thermal conductive body (300), according to the present invention; and

FIG. 12 is a section view of FIG. 11.

DESCRIPTION OF MAIN COMPONENT SYMBOLS

- 25 100: U-type piping
101: First fluid inlet and outlet terminal
102: Second fluid inlet and outlet terminal
111: Thermal conductive fluid
200: Common piping
30 300: Columnar thermal conductive body

- 400: Thermal insulating device
- 500: Thermal storage body
- 600: U-type wavy piping
- 700: Central piping of U-type spiral piping
- 5 800: U-type spiral piping
- 1101: First fluid inlet and outlet terminal

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention relates to a thermal conductive cylinder
10 installed with U-type core piping and loop piping for being installed
within the thermal storage body (500) composed of natural thermal
storage body, such as shallow surface of the earth, or pool, lake, river,
ocean, etc, or artificial objects in solid, or gaseous, or liquid state; wherein
the thermal conductive cylinder installed with U-type core piping and
15 loop piping is constructed through that the piping segments of fluid inlet
terminal and/or outlet terminal of the U-type core piping and loop piping
are directly made of thermal insulating material, or thermal insulating
structure is installed between the inlet terminal and the outlet terminal; so
as to prevent thermal energy loss because of thermal conduction between
20 adjacent piping segments of inlet terminal and outlet terminal on the same
side when thermal conductive fluid with temperature difference passing
through.

As for the thermal conductive cylinder installed with U-type core
piping and loop piping of the present invention, each of the U-type piping
25 (100) is used for passing through one or more following thermal
conductive fluid (111), including for passing through:

- 1) liquid state fluid;
- 2) gaseous state fluid;
- 3) liquid to gaseous state fluid; and
- 30 4) gaseous to liquid state fluid.

Traditionally, thermal energy loss often occurs in U-type piping device of U-type piping heat exchanger, because of thermal conduction by temperature difference between adjacent piping segments of fluid inlet terminal and fluid outlet terminal installed on the same side when fluid with temperature difference passing through, which is illustrated by examples as followings:

FIG. 1 shows an embodiment of conventional U-type piping (100) installed within the thermal storage body (500). When the thermal conductive fluid (111) passing through the piping segment of the first fluid inlet and outlet terminal (101) and the adjacent piping segment of the second fluid inlet and outlet terminal (102) respectively installed on the same side of the U-type piping (100) are in temperature difference, the two piping segments will produce thermal conduction and therefore result in thermal energy loss.

FIG. 2 shows an embodiment of conventional U-type piping (100) installed within the columnar thermal conductive body (300), wherein the columnar thermal conductive body (300) is placed within the thermal storage body (500).

When the columnar thermal conductive body (300) is installed at the thermal conductive cylinder installed with U-type core piping and loop piping of the thermal storage body (500) composed of natural thermal storage body, such as shallow surface of the earth, or pool, lake, river, ocean, etc, or artificial objects in solid, or gaseous, or liquid state, and the thermal conductive fluid (111) with temperature difference passes through the first fluid inlet and outlet terminal (101) and the second fluid inlet and outlet terminal (102) of the U-type piping, there will be thermal energy loss, because of thermal conduction between adjacent piping segments of the first fluid inlet and outlet terminal (101) and the second fluid inlet and outlet terminal (102) installed on the same side.

The present invention relates to a thermal conductive cylinder

installed with U-type core piping and loop piping for being installed within the thermal storage body (500) composed of natural thermal storage body, such as shallow surface of the earth, or pool, lake, river, ocean, etc, or artificial objects in solid, or gaseous, or liquid state; wherein
5 the thermal conductive cylinder installed with U-type core piping and loop piping is constructed through that the piping segments of the U-type fluid piping inlet terminal and/or outlet terminal, which are radial U-type pipelines for passing thermal energy through each other, are directly made of thermal insulating material, or thermal insulating structure is installed
10 between the inlet terminal and the outlet terminal; so as to prevent thermal energy loss because of thermal conduction between adjacent piping segments of inlet terminal and outlet terminal on the same side when thermal conductive fluid with temperature difference passing through.

FIG. 3 is a structural schematic view showing that two or more
15 radially arranged U-type piping sections are installed within thermal conductive cylinder, and the thermal insulating structure is installed at where close to the peripheral of piping group with same flow direction which concentrates toward axial core, according to the present invention.

FIG. 4 is a section view of FIG. 3.

20 As shown in FIG. 3 and FIG. 4, the main components are as followings:

---U-type piping (100): made of U-type tubular body for the thermal conductive fluid (111) passing through, wherein the U-type piping (100) is used for being installed within the columnar thermal conductive body
25 (300) composed of solid state or colloidal object; each of the U-type piping (100) has the first fluid inlet and outlet terminal (101) and the second fluid inlet and outlet terminal (102), the piping segments near the first fluid inlet and outlet terminal (101) are concentrated adjacent installed at the core of the columnar thermal conductive body (300), and
30 the piping segments near the second fluid inlet and outlet terminal (102)

are radially arranged along the axial direction and near the edge of the columnar thermal conductive body (300);

---Columnar thermal conductive body (300): made of thermal conductive material, wherein the columnar thermal conductive body (300) has columnar structure with various geometric shape sections, such as circle, oval, square, rectangular, or star, for coating the U-type piping (100) and the thermal insulating device (400); and

---Thermal insulating device (400): related to thermal insulating structure constituted by the followings with thermal insulating effects, such as solid, flexible body, or foam, or enveloped colloid, gas, or liquid, or vacuum structure, for being placed between the piping segments near the first fluid inlet and outlet terminal (101) of each of the U-type piping (100), which are concentrated adjacent installed at the axial core of the columnar thermal conductive body (300), and the piping segments near the second fluid inlet and outlet terminal (102) of each of the U-type piping, or for being substituted by the piping segments near the first fluid inlet and outlet terminal (101) directly made of thermal insulating material or enveloped by thermal insulating material; by way of the above thermal insulating structure, for substantially reducing thermal energy loss caused by thermal conduction between adjacent piping segments of the first fluid inlet and outlet terminal (101) and the second fluid inlet and outlet terminal (102) on the same side of the U-type piping (100).

As for the thermal conductive cylinder installed with U-type core piping and loop piping of the present invention, it further can have multiple sets of U-type piping jointly connected to the first fluid inlet and outlet terminal (1101) of the common piping (200) constituted by larger diameter piping installed at the axial core of the columnar thermal conductive body (300), and be installed with the second fluid inlet and outlet terminal (102) in radially arrangement along the axial direction of the columnar thermal conductive body (300).

FIG. 5 is a structural schematic view of an embodiment showing that multiple sets of U-type piping jointly connects to the first fluid inlet and outlet terminal (1101) of the common piping (200), which is constituted by larger diameter piping and installed at the core of the columnar thermal
5 conductive body (300), according to the present invention.

FIG. 6 is a section view of FIG. 5.

As shown in FIG. 5 and FIG. 6, it is mainly constituted by at least two U-type piping (100) for the thermal conductive fluid (111) passing through, wherein each of the U-type piping (100) is used for being
10 installed within the columnar thermal conductive body (300) composed of solid state or colloidal object; each of the U-type piping (100) is jointly connected to the first fluid inlet and outlet terminal (1101) of common piping (200) which is constituted by larger diameter piping and installed at the axial core of the columnar thermal conductive body (300), and is
15 installed with the second fluid inlet and outlet terminal (102) and piping segments radially arranged along the axial direction of the columnar thermal conductive body (300); the first fluid inlet and outlet terminal (1101) of common piping (200) is placed at the axial core of the columnar thermal conductive body (300), and is further installed with the thermal
20 insulating device (400) between the piping segments near the second fluid inlet and outlet terminal (102) of each U-type piping (100), and the piping segments near the second fluid inlet and outlet terminal (102) of each U-type piping (100) are radially arranged along the axial direction and near the edge of the columnar thermal conductive body (300); and

25 ---Columnar thermal conductive body (300): made of thermal conductive material, wherein the columnar thermal conductive body (300) has columnar structure with various geometric shape sections, such as circle, oval, square, rectangular, or star, for coating the U-type piping (100) and the thermal insulating device (400); and

30 ---Thermal insulating device (400): related to thermal insulating

structure constituted by the followings with thermal insulating effects, such as solid, flexible body, or foam, or enveloped colloid, gas, or liquid, or vacuum structure, for being placed between the piping segments near the second fluid inlet and outlet terminal (102) of the U-type piping (100) and the piping segments near the first fluid inlet and outlet terminal (1101) of the common piping (200), or for being substituted by the piping segments near the first fluid inlet and outlet terminal (101) directly made of thermal insulating material or enveloped by thermal insulating material; by way of the above structure, for reducing thermal energy loss caused by thermal conduction between the piping segments of the first fluid inlet and outlet terminal (1101) of the common piping (200) and the second fluid inlet and outlet terminal (102).

FIG. 7 is a schematic view of an embodiment, showing that piping segments of first fluid inlet and outlet terminal (101) and second fluid inlet and outlet terminal (102) in U-type wavy piping (600) are wavyly arranged along the axial direction and near the edge of the columnar thermal conductive body (300), according to the present invention.

FIG. 8 is a section view of FIG. 7.

As shown in FIG. 7 and FIG. 8, the main components are as followings:

---U-type wavy piping (600): made of U-type wavy pipe body for the thermal conductive fluid (111) passing through, wherein the U-type wavy piping (600) is used for being installed within the columnar thermal conductive body (300) composed of solid state or colloidal object; the feature is that the U-type wavy piping (600) is wavyly placed around the axial direction and near the edge of the columnar thermal conductive body (300) with upper and lower wavy bending, and the both ends of the U-type wavy piping (600) have the first fluid inlet and outlet terminal (101) and the second fluid inlet and outlet terminal (102) which are interlinked;

---Columnar thermal conductive body (300): made of thermal conductive material, wherein the columnar thermal conductive body (300) has columnar structure with various geometric shape sections, such as circle, oval, square, rectangular, or star, for coating the U-type wavy piping (600) and the thermal insulating device (400); and

---Thermal insulating device (400): related to thermal insulating structure constituted by the followings with thermal insulating effects, such as solid, flexible body, or foam, or enveloped colloid, gas, or liquid, or vacuum structure, for being placed between the piping segments near the first fluid inlet and outlet terminal (101) of the U-type wavy piping (600), which are concentrated adjacent installed at the axial core of the columnar thermal conductive body (300), and the piping segments near the second fluid inlet and outlet terminal (102) of U-type wavy piping (600), or for being substituted by the piping segments near the first fluid inlet and outlet terminal (101) directly made of thermal insulating material or enveloped by thermal insulating material; by way of the above thermal insulating structure, for substantially reducing thermal energy loss caused by thermal conduction between adjacent piping segments of the first fluid inlet and outlet terminal (101) and the second fluid inlet and outlet terminal (102) on the same side of the U-type wavy piping (600).

FIG. 9 is a schematic view of an embodiment, showing that the piping segment of the first fluid inlet and outlet terminal (101) in U-type wavy piping (600) is placed near the center of the columnar thermal conductive body (300), the piping segment between the second fluid inlet and outlet terminal (102) is placed near the periphery of the columnar thermal conductive body (300), and the U-type wavy piping (600) between the two piping segments is wavyly arranged along the axial direction and near the edge of the columnar thermal conductive body (300), according to the present invention.

FIG. 10 is a section view of FIG. 9.

As shown in FIG. 9 and FIG. 10, the main components are as followings:

---U-type wavy piping (600): made of U-type wavy pipe body for the thermal conductive fluid (111) passing through, wherein the U-type wavy piping (600) is used for being installed within the columnar thermal conductive body (300) composed of solid state or colloidal object; the feature is that the U-type wavy piping (600) is wavyly placed around the axial direction and near the edge of the columnar thermal conductive body (300) with upper and lower wavy bending, the both ends of the U-type wavy piping (600) have the first fluid inlet and outlet terminal (101) and the second fluid inlet and outlet terminal (102) which are interlinked, in which the piping segment of the first fluid inlet and outlet terminal (101) is placed near the center of the columnar thermal conductive body (300), the piping segment between the second fluid inlet and outlet terminal (102) is placed near periphery of the columnar thermal conductive body (300), and the U-type wavy piping (600) between the two piping segments is wavyly arranged along the axial direction and near the edge of the columnar thermal conductive body (300);

---Columnar thermal conductive body (300): made of thermal conductive material, wherein the columnar thermal conductive body (300) has columnar structure with various geometric shape sections, such as circle, oval, square, rectangular, or star, for coating the U-type wavy piping (600) and the thermal insulating device (400); and

---Thermal insulating device (400): related to thermal insulating structure constituted by the followings with thermal insulating effects, such as solid, flexible body, or foam, or enveloped colloid, gas, or liquid, or vacuum structure, for being placed between the piping segments near the first fluid inlet and outlet terminal (101) of the U-type wavy piping (600), which are concentrated adjacent installed at the axial core of the columnar thermal conductive body (300), and the piping segments near

the second fluid inlet and outlet terminal (102) of U-type wavy piping (600), or for being substituted by the piping segments near the first fluid inlet and outlet terminal (101) directly made of thermal insulating material or enveloped by thermal insulating material; by way of the above thermal insulating structure, for substantially reducing thermal energy loss caused by thermal conduction between adjacent piping segments of the first fluid inlet and outlet terminal (101) and the second fluid inlet and outlet terminal (102) on the same side of the U-type wavy piping (600).

FIG. 11 is a schematic view of an embodiment, showing that the spiral piping segment of the first fluid inlet and outlet terminal (101) and the second fluid inlet and outlet terminal (102) in U-type spiral piping is spirally arranged along the axial direction and near the edge of the columnar thermal conductive body (300), according to the present invention.

FIG. 12 is a section view of FIG. 11.

As shown in FIG. 11 and FIG. 12, the main components are as followings:

---U-type spiral piping (800): made of U-type spiral pipe body for the thermal conductive fluid (111) passing through, wherein the U-type spiral piping (800) is used for being installed within the columnar thermal conductive body (300) composed of solid state or colloidal object; the feature is that the U-type spiral piping (800) is spirally placed around the axial direction and near the edge of the columnar thermal conductive body (300), and the both ends of the U-type spiral piping (800) have the first fluid inlet and outlet terminal (101) and the second fluid inlet and outlet terminal (102) which are interlinked, in which the first fluid inlet and outlet terminal (101) placed at the top end of the center of the spiral structure directly leads to the bottom of the U-type spiral piping (800) via the central piping of U-type spiral piping (700), and the second fluid inlet and outlet terminal (102) is placed at the top end of the U-type spiral

piping (800) spirally up its own run;

---Columnar thermal conductive body (300): made of thermal conductive material, wherein the columnar thermal conductive body (300) has columnar structure with various geometric shape sections, such as
5 circle, oval, square, rectangular, or star, for coating the U-type spiral piping (800) and the thermal insulating device (400); and

---Thermal insulating device (400): related to thermal insulating structure constituted by the followings with thermal insulating effects, such as solid, flexible body, or foam, or enveloped colloid, gas, or liquid,
10 or vacuum structure, wherein the piping segment of the central piping the U-type spiral piping (700) of the U-type spiral piping (800), which is placed at the axial core of the columnar thermal conductive body (300) and leads up to the first fluid inlet and outlet terminal (101), is directly made of thermal insulating material or enveloped by thermal insulating
15 material, or the thermal insulating device (400) is placed between the U-type spiral piping (800) around and near the edge of the columnar thermal conductive body (300) spirally up its own run leading to the second fluid inlet and outlet terminal (102) and the piping segment of the central piping of U-type spiral piping (700); by way of the above thermal
20 insulating device (400), for substantially reducing thermal energy loss caused by thermal conduction between the central piping of U-type spiral piping (700) installed at the center of the bottom of the same U-type spiral piping (800) leading up to the first fluid inlet and outlet terminal (101), and the U-type spiral piping (800) leading to the second fluid inlet and
25 outlet terminal (102).

CLAIMS

1. A thermal conductive cylinder installed with U-type core piping and loop piping for being installed within the thermal storage body (500) composed of natural thermal storage body, such as shallow surface
5 of the earth, or pool, lake, river, ocean, etc, or artificial objects in solid, or gaseous, or liquid state; wherein the thermal conductive cylinder installed with U-type core piping and loop piping is constructed through that the piping segments of fluid inlet terminal and/or outlet terminal of the U-type core piping and loop piping are
10 directly made of thermal insulating material, or thermal insulating structure is installed between the inlet terminal and the outlet terminal; so as to prevent thermal energy loss because of thermal conduction between adjacent piping segments of inlet terminal and outlet terminal on the same side when thermal conductive fluid with
15 temperature difference passing through; and wherein each of the U-type piping (100) is used for one or more following thermal conductive fluid (111) passing through, including:
 - 1) liquid state fluid;
 - 2) gaseous state fluid;
 - 20 3) liquid to gaseous state fluid; and
 - 4) gaseous to liquid state fluid.
2. The thermal conductive cylinder installed with U-type core piping and loop piping as claimed in Claim 1, including the structure wherein two or more radially arranged U-type piping sections are
25 installed within thermal conductive cylinder, and the thermal insulating structure is installed at where close to the peripheral of piping group with same flow direction which concentrates toward axial core; the main components are as followings:
---U-type piping (100): made of U-type tubular body for the thermal
30 conductive fluid (111) passing through, wherein the U-type piping

(100) is used for being installed within the columnar thermal conductive body (300) composed of solid state or colloidal object; each of the U-type piping (100) has the first fluid inlet and outlet terminal (101) and the second fluid inlet and outlet terminal (102),
5 the piping segments near the first fluid inlet and outlet terminal (101) are concentrated adjacent installed at the core of the columnar thermal conductive body (300), and the piping segments near the second fluid inlet and outlet terminal (102) are radially arranged along the axial direction and near the edge of the
10 columnar thermal conductive body (300);

---Columnar thermal conductive body (300): made of thermal conductive material, wherein the columnar thermal conductive body (300) has columnar structure with various geometric shape sections, such as circle, oval, square, rectangular, or star, for
15 coating the U-type piping (100) and the thermal insulating device (400); and

---Thermal insulating device (400): related to thermal insulating structure constituted by the followings with thermal insulating effects, such as solid, flexible body, or foam, or enveloped colloid,
20 gas, or liquid, or vacuum structure, for being placed between the piping segments near the first fluid inlet and outlet terminal (101) of each of the U-type piping (100), which are concentrated adjacent installed at the axial core of the columnar thermal conductive body (300), and the piping segments near the second
25 fluid inlet and outlet terminal (102) of each of the U-type piping, or for being substituted by the piping segments near the first fluid inlet and outlet terminal (101) directly made of thermal insulating material or enveloped by thermal insulating material; by way of the above thermal insulating structure, for substantially reducing
30 thermal energy loss caused by thermal conduction between

adjacent piping segments of the first fluid inlet and outlet terminal (101) and the second fluid inlet and outlet terminal (102) on the same side of the U-type piping (100).

3. The thermal conductive cylinder installed with U-type core piping and loop piping as claimed in Claim 1, including the structure wherein multiple sets of U-type piping jointly connects to the first fluid inlet and outlet terminal (1101) of the common piping (200), which is constituted by larger diameter piping and installed at the core of the columnar thermal conductive body (300); and wherein it is mainly constituted by at least two U-type piping (100) for the thermal conductive fluid (111) passing through, wherein each of the U-type piping (100) is used for being installed within the columnar thermal conductive body (300) composed of solid state or colloidal object; each of the U-type piping (100) is jointly connected to the first fluid inlet and outlet terminal (1101) of common piping (200) which is constituted by larger diameter piping and installed at the axial core of the columnar thermal conductive body (300), and is installed with the second fluid inlet and outlet terminal (102) and piping segments radially arranged along the axial direction of the columnar thermal conductive body (300); the first fluid inlet and outlet terminal (1101) of common piping (200) is placed at the axial core of the columnar thermal conductive body (300), and is further installed with the thermal insulating device (400) between the piping segments near the second fluid inlet and outlet terminal (102) of each U-type piping (100), and the piping segments near the second fluid inlet and outlet terminal (102) of each U-type piping (100) are radially arranged along the axial direction and near the edge of the columnar thermal conductive body (300); and
- Columnar thermal conductive body (300): made of thermal conductive material, wherein the columnar thermal conductive

body (300) has columnar structure with various geometric shape sections, such as circle, oval, square, rectangular, or star, for coating the U-type piping (100) and the thermal insulating device (400); and

5 ---Thermal insulating device (400): related to thermal insulating structure constituted by the followings with thermal insulating effects, such as solid, flexible body, or foam, or enveloped colloid, gas, or liquid, or vacuum structure, for being placed between the piping segments near the second fluid inlet and outlet terminal
10 (102) of the U-type piping (100) and the piping segments near the first fluid inlet and outlet terminal (1101) of the common piping (200), or for being substituted by the piping segments near the first fluid inlet and outlet terminal (101) directly made of thermal insulating material or enveloped by thermal insulating material; by
15 way of the above structure, for reducing thermal energy loss caused by thermal conduction between the piping segments of the first fluid inlet and outlet terminal (1101) of the common piping (200) and the second fluid inlet and outlet terminal (102).

4. The thermal conductive cylinder installed with U-type core piping
20 and loop piping as claimed in Claim 1, including the structure wherein the piping segments of the first fluid inlet and outlet terminal (101) and the second fluid inlet and outlet terminal (102) in U-type wavy piping (600) are wavyly arranged along the axial direction and near the edge of the columnar thermal conductive body
25 (300); the main components are as followings:

---U-type wavy piping (600): made of U-type wavy pipe body for the thermal conductive fluid (111) passing through, wherein the U-type wavy piping (600) is used for being installed within the columnar thermal conductive body (300) composed of solid state
30 or colloidal object; the feature is that the U-type wavy piping (600)

- is wavily placed around the axial direction and near the edge of the columnar thermal conductive body (300) with upper and lower wavy bending, and the both ends of the U-type wavy piping (600) have the first fluid inlet and outlet terminal (101) and the second fluid inlet and outlet terminal (102) which are interlinked;
- 5 ---Columnar thermal conductive body (300): made of thermal conductive material, wherein the columnar thermal conductive body (300) has columnar structure with various geometric shape sections, such as circle, oval, square, rectangular, or star, for coating the U-type wavy piping (600) and the thermal insulating device (400); and
- 10 ---Thermal insulating device (400): related to thermal insulating structure constituted by the followings with thermal insulating effects, such as solid, flexible body, or foam, or enveloped colloid, gas, or liquid, or vacuum structure, for being placed between the piping segments near the first fluid inlet and outlet terminal (101) of the U-type wavy piping (600), which are concentrated adjacent installed at the axial core of the columnar thermal conductive body (300), and the piping segments near the second fluid inlet and outlet terminal (102) of U-type wavy piping (600), or for being substituted by the piping segments near the first fluid inlet and outlet terminal (101) directly made of thermal insulating material or enveloped by thermal insulating material; by way of the above thermal insulating structure, for substantially reducing thermal energy loss caused by thermal conduction between adjacent piping segments of the first fluid inlet and outlet terminal (101) and the second fluid inlet and outlet terminal (102) on the same side of the U-type wavy piping (600).
- 25 5. The thermal conductive cylinder installed with U-type core piping and loop piping as claimed in Claim 1, including the structure
- 30

wherein the piping segment of the first fluid inlet and outlet terminal (101) in U-type wavy piping (600) is placed near the center of the columnar thermal conductive body (300), the piping segment between the second fluid inlet and outlet terminal (102) is placed near the periphery of the columnar thermal conductive body (300), and the U-type wavy piping (600) between the two piping segments is wavyly arranged along the axial direction and near the edge of the columnar thermal conductive body (300); the main components are as followings:

---U-type wavy piping (600): made of U-type wavy pipe body for the thermal conductive fluid (111) passing through, wherein the U-type wavy piping (600) is used for being installed within the columnar thermal conductive body (300) composed of solid state or colloidal object; the feature is that the U-type wavy piping (600) is wavyly placed around the axial direction and near the edge of the columnar thermal conductive body (300) with upper and lower wavy bending, the both ends of the U-type wavy piping (600) have the first fluid inlet and outlet terminal (101) and the second fluid inlet and outlet terminal (102) which are interlinked, in which the piping segment of the first fluid inlet and outlet terminal (101) is placed near the center of the columnar thermal conductive body (300), the piping segment between the second fluid inlet and outlet terminal (102) is placed near periphery of the columnar thermal conductive body (300), and the U-type wavy piping (600) between the two piping segments is wavyly arranged along the axial direction and near the edge of the columnar thermal conductive body (300);

---Columnar thermal conductive body (300): made of thermal conductive material, wherein the columnar thermal conductive body (300) has columnar structure with various geometric shape

sections, such as circle, oval, square, rectangular, or star, for coating the U-type wavy piping (600) and the thermal insulating device (400); and

5 ---Thermal insulating device (400): related to thermal insulating structure constituted by the followings with thermal insulating effects, such as solid, flexible body, or foam, or enveloped colloid, gas, or liquid, or vacuum structure, for being placed between the piping segments near the first fluid inlet and outlet terminal (101) of the U-type wavy piping (600), which are concentrated adjacent
10 installed at the axial core of the columnar thermal conductive body (300), and the piping segments near the second fluid inlet and outlet terminal (102) of U-type wavy piping (600), or for being substituted by the piping segments near the first fluid inlet and outlet terminal (101) directly made of thermal insulating material
15 or enveloped by thermal insulating material; by way of the above thermal insulating structure, for substantially reducing thermal energy loss caused by thermal conduction between adjacent piping segments of the first fluid inlet and outlet terminal (101) and the second fluid inlet and outlet terminal (102) on the same side of the
20 U-type wavy piping (600).

6. The thermal conductive cylinder installed with U-type core piping and loop piping as claimed in Claim 1, including the structure wherein the spiral piping segment of the first fluid inlet and outlet terminal (101) and the second fluid inlet and outlet terminal (102) in
25 U-type spiral piping is spirally arranged along the axial direction and near the edge of the columnar thermal conductive body (300), and the main components are as followings:

---U-type spiral piping (800): made of U-type spiral pipe body for the thermal conductive fluid (111) passing through, wherein the
30 U-type spiral piping (800) is used for being installed within the

columnar thermal conductive body (300) composed of solid state or colloidal object; the feature is that the U-type spiral piping (800) is spirally placed around the axial direction and near the edge of the columnar thermal conductive body (300), and the both ends of the U-type spiral piping (800) have the first fluid inlet and outlet terminal (101) and the second fluid inlet and outlet terminal (102) which are interlinked, in which the first fluid inlet and outlet terminal (101) placed at the top end of the center of the spiral structure directly leads to the bottom of the U-type spiral piping (800) via the central piping of U-type spiral piping (700), and the second fluid inlet and outlet terminal (102) is placed at the top end of the U-type spiral piping (800) spirally up its own run;

---Columnar thermal conductive body (300): made of thermal conductive material, wherein the columnar thermal conductive body (300) has columnar structure with various geometric shape sections, such as circle, oval, square, rectangular, or star, for coating the U-type spiral piping (800) and the thermal insulating device (400); and

---Thermal insulating device (400): related to thermal insulating structure constituted by the followings with thermal insulating effects, such as solid, flexible body, or foam, or enveloped colloid, gas, or liquid, or vacuum structure, wherein the piping segment of the central piping the U-type spiral piping (700) of the U-type spiral piping (800), which is placed at the axial core of the columnar thermal conductive body (300) and leads up to the first fluid inlet and outlet terminal (101), is directly made of thermal insulating material or enveloped by thermal insulating material, or the thermal insulating device (400) is placed between the U-type spiral piping (800) around and near the edge of the columnar thermal conductive body (300) spirally up its own run leading to

the second fluid inlet and outlet terminal (102) and the piping segment of the central piping of U-type spiral piping (700); by way of the above thermal insulating device (400), for substantially reducing thermal energy loss caused by thermal conduction between the central piping of U-type spiral piping (700) installed at the center of the bottom of the same U-type spiral piping (800) leading up to the first fluid inlet and outlet terminal (101), and the U-type spiral piping (800) leading to the second fluid inlet and outlet terminal (102).

10