

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
19 January 2006 (19.01.2006)

PCT

(10) International Publication Number
WO 2006/007380 A3

(51) International Patent Classification⁷: **B65C 1/00**

(21) International Application Number:

PCT/US2005/021194

(22) International Filing Date: 16 June 2005 (16.06.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/579,677 16 June 2004 (16.06.2004) US

(71) Applicant (for all designated States except US): **ROLLS-ROYCE NAVAL MARINE, INC.** [US/US]; 110 Norfolk Street, Walpole, MA 02081 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **ATTWATER, Iain, J.** [GB/US]; 426 Gold Course Drive, Arnold, MD 21012 (US). **CAYOCCA, Iver, D.** [US/US]; 616 Madeira Avenue, Coral Gables, FL 33134 (US). **SHANKS, Richard, J.** [GB/US]; 514 MacMillan Court, Arnold, MD 21012 (US).


(74) Agent: **KLIMA, Timothy, J.**; 500 Ninth Street Southeast, Washington, DC 20003 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: METHOD OF OPERATING A SHIPLIFT



(57) Abstract: A platform includes main transverse beams ("MTBs"), each supported by at least one hoist. It is determined whether a load on any MTB is different from the load on any other MTB by more than a predetermined amount. An MTB which has a load different from the load on any other MTB by more than a predetermined amount is selected and then vertically moved with respect to the other MTBs within a predetermined safety limit to transfer load between the selected MTB and the other MTBs while monitoring the loads on each MTB and the position of the selected MTB as vertical movement of the selected MTB proceeds. The monitored loads and position are compared with the safety limit; and the movement of the selected MTB stopped when either the desired load transfer is completed or the safety limit has been met.

WO 2006/007380 A3



Published:

— with international search report

(88) Date of publication of the international search report:

2 March 2006

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.