

DESCRIPTION

PAPER CONVEYING APPARATUS, IMAGE FORMING
APPARATUS AND INK-JET RECORDING APPARATUS

5

TECHNICAL FIELD

The present invention relates to a paper conveying apparatus, an image forming apparatus and an ink-jet recording apparatus; more particularly to a
10 paper conveying apparatus, an image forming apparatus and an ink-jet recording apparatus that have a print receiving member arranged opposed to a print head.

BACKGROUND ART

15 Conventionally, an ink-jet recording apparatus used as an image recording apparatus (image forming apparatus) such as a printer, a facsimile, a copier or the like can form an image on a sheet of paper (not necessarily limited to paper but whatever is used to
20 form an image thereon) by ejecting ink droplets from a nozzle of an ink-jet head thereto. Since deviation of the positional relationship between the sheet of paper and the ink-jet head may degrade image quality, it is required to convey the sheet of paper with accuracy.

25 Since the ink-jet recording apparatus allows

ink droplets to adhere on a sheet of paper, the paper tends to become corrugated. Namely, within a few seconds after the ink droplets adhere on the paper, the paper swells and then becomes corrugated, which is known as so-called cockling. Typically, when an image is printed on a sheet of paper, there are margins formed on the right, left, top, and bottom of the paper. Therefore, tensile stress is caused between the right (left) margin and a printed area adjacent to the right (left) margin, which pulls both the margins inward, thereby causing both side portions of the paper to rise. If this happens, the paper cannot be flat in relation to the ink-jet head, and a gap between the paper and the ink-jet head varies, thereby distorting the image. Moreover, a large corrugation of the paper causes a problem in that the image printed on the paper may be defective and the ink-jet head may be damaged or broken since the paper can contact the ink-jet head.

In order to eliminate such disadvantages, an image forming apparatus such as an ink-jet printer has been proposed in recent years, where a conveyor roller is disposed in both the upstream and the downstream end of a paper conveying direction so as to maintain the flatness of the paper in relation to the ink-jet head. Such an image forming apparatus can prevent the paper

from becoming corrugated during printing (See, patent-related publications listed below).

[Patent-related document 1] Japanese Patent Application Laid-Open Publication No. H7-125364.

5 [Patent-related document 2] Japanese Patent Application Laid-Open Publication No. H7-132659.

[Patent-related document 3] Japanese Patent Application Laid-Open Publication No. H9-24650.

10 [Patent-related document 4] Japanese Patent Application Laid-Open Publication No. 2001-261188.

However, in such an ink jet recording apparatus where the conveyor rollers are provided in the upstream and the downstream end of the paper along the conveying direction, an image is printed on the paper while the conveyer rollers are holding the leading and the rear ends of the paper. Therefore, a relatively larger non-printed zone has to be allocated at the upper and lower portions of the paper (i.e., the leading margin and the rear margin), which leads to another problem in that the printable area becomes smaller.

15
20

The present invention has been made in view of the above, and may provide a paper conveying apparatus, an image forming apparatus and an ink-jet recording apparatus that can press side portions of paper downward so as to allow the paper to bend downward.

25

DISCLOSURE OF THE INVENTION

An embodiment of the present invention provides a paper conveying apparatus including a first
5 paper pressing member configured to press one side portion of a sheet of paper that may be conveyed therethrough, the side portion extending along a paper conveying direction.

Another embodiment of the present invention
10 provides the paper conveying apparatus, where the first paper pressing member is disposed so that a downstream portion thereof along the paper conveying direction lies outward in a direction transverse to the paper conveying direction from an upstream portion thereof.

15 Another embodiment of the present invention provides the paper conveying apparatus, where the first paper pressing member is disposed so that a center of a downstream portion thereof along the paper conveying direction lies outward in a direction transverse to the
20 paper conveying direction from a center of an upstream portion thereof.

Another embodiment of the present invention provides the paper conveying apparatus, where the first paper pressing member is disposed so that a center of a
25 downstream portion thereof along the paper conveying

direction lies outward in a direction transverse to the paper conveying direction from a corresponding one edge of the sheet of paper.

Another embodiment of the present invention provides the paper conveying apparatus, where the first paper pressing member is disposed so that a middle portion thereof between a downstream portion thereof and an upstream portion thereof along the paper conveying direction lies outward from a corresponding one edge of the sheet of paper.

Another embodiment of the present invention provides the paper conveying apparatus, where the first paper pressing member becomes narrower toward a downstream end thereof along the paper conveying direction.

Another embodiment of the present invention provides the paper conveying apparatus further including one or more supporting members configured to support the sheet of paper from below.

Another embodiment of the present invention provides the paper conveying apparatus further including a second paper pressing member configured to press the other side portion of the sheet of paper.

Another embodiment of the present invention provides the paper conveying apparatus, where the second

paper pressing member is symmetric in shape with the first paper pressing member in relation to the paper conveying direction.

Another embodiment of the present invention
5 provides the paper conveying apparatus, further including one or more third paper pressing members capable of pressing the sheet of paper between the first and the second paper pressing members.

Another embodiment of the present invention
10 provides the paper conveying apparatus, where the first or the second paper pressing member presses one side portion of the sheet of paper and one of the one or more third paper pressing members presses the other side portion of the sheet of paper, and where the one of the
15 one or more third paper pressing members is disposed symmetrically with the first or the second paper pressing member in relation to the paper conveying direction.

Another embodiment of the present invention
20 provides the paper conveying apparatus further including one or more paper pressing amount limiting members disposed below the sheet of paper and configured to be substantially vertically movable so as to limit an amount of pressing on the sheet of paper caused by the
25 first paper pressing member, the second paper pressing

member, the third paper pressing member, or a combination thereof.

Another embodiment of the present invention provides the paper conveying apparatus further including
5 one or more supporting members configured to support the sheet of paper from below, where the one or more paper pressing amount limiting members push from below the sheet of paper that is held from below by the supporting member and pressed from above by the first paper
10 pressing member, the second paper pressing member, the third paper pressing member, or a combination thereof, so as to limit the amount of pressing from above.

Another embodiment of the present invention provides the paper conveying apparatus, wherein each of
15 the one or more third paper pressing members is disposed between every adjacent two of the supporting members, and wherein one of the one or more supporting members, the corresponding one of the one or more paper pressing amount limiting members, and the corresponding one of
20 the one or more third paper pressing members are disposed in this order in a direction transverse to the paper conveying direction.

Another embodiment of the present invention provides the paper conveying apparatus, wherein each of
25 the one or more third paper pressing members is disposed

between every adjacent two of the supporting members,
and wherein one of the one or more third paper pressing
members, the corresponding one of the one or more
supporting members, and the corresponding one of the one
5 or more paper pressing amount limiting members are
disposed in this order in a direction transverse to the
paper conveying direction.

Another embodiment of the present invention
provides the paper conveying apparatus, where each of
10 the one or more paper pressing amount limiting members
is disposed below a corresponding one of the one or more
third paper pressing members.

Another embodiment of the present invention
provides the paper conveying apparatus, where one of the
15 one or more paper pressing amount limiting members is
disposed between the first paper pressing member and the
third paper pressing member adjacent to the first paper
pressing member.

Another embodiment of the present invention
20 provides the paper conveying apparatus, where one of the
one or more paper pressing amount limiting members is
disposed between the second paper pressing member and
the third paper pressing member adjacent to the second
paper pressing member.

25 Another embodiment of the present invention

provides the paper conveying apparatus, where at least one of the one or more paper pressing amount limiting members is disposed outward in a direction transverse to the paper conveying direction from a corresponding edge
5 of the sheet of paper.

Another embodiment of the present invention provides the paper conveying apparatus, where a first set of the one or more paper pressing amount limiting members is disposed below the corresponding third paper
10 pressing members and where a second set of the one or more paper pressing amount limiting members is disposed between every adjacent two of the third paper pressing members.

Another embodiment of the present invention
15 provides the paper conveying apparatus further including: a print receiving member disposed opposing a print head that prints on the sheet of paper; a conveying roller configured to convey the sheet of paper to the print receiving member; and a pressing roller
20 configured to press the sheet of paper on the conveying roller, where at least one of the first, the second, and the third paper pressing members is configured to press the sheet of paper on the print receiving member.

Another embodiment of the present invention
25 provides the paper conveying apparatus further including

-10-

one or more supporting members disposed on the print receiving member so as to support the sheet of paper from below.

Another embodiment of the present invention provides an image forming apparatus comprising at least the paper conveying apparatus.

Another embodiment of the present invention provides an ink-jet recording apparatus comprising at least the paper conveying apparatus.

According to the embodiments of the present invention, there is provided a paper conveying apparatus, an image forming apparatus and an ink-jet recording apparatus that can press side portions of paper downward so as to allow the paper to bend downward.

15

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic cross-sectional view of an ink-jet recording apparatus according to an embodiment of the present invention.

FIG. 2 is a schematic perspective view of a print receiving member and the vicinity thereof in the ink-jet recording apparatus according to the embodiment of the present invention.

FIG. 3 is a plan view of the print receiving member of the ink-jet recording apparatus according to

25

the embodiment of the present invention.

FIG. 4 is a front view of pressing members and the vicinity thereof in the ink-jet recording apparatus according to the embodiment of the present invention.

5 FIGS. 5(a) and 5(b) show other examples of the pressing members having different shapes.

FIGS. 6(a) through 6(f) show still other examples of the pressing members having different shapes.

10 FIGS. 7(a) through 7(d) show still other examples of the pressing members having different shapes.

FIG. 8 is a plan view of the print receiving member in which the pressing members are disposed differently from the pressing members in FIG. 3.

15 FIGS. 9(a) through 9(c) are front views of the pressing amount limiting members disposed in three respective positions in relation to the pressing members.

FIG. 10 is a front view of the pressing amount limiting members disposed outside the corresponding one of the pressing members.

20 FIG. 11 is a plan view of the print receiving member in which each of the pressing amount limiting members is disposed outside the corresponding one of the pressing members.

25 FIG. 12 is a front view of the pressing amount limiting members disposed below the corresponding

pressing members.

FIG. 13 is a plan view of the print receiving member in which the pressing amount limiting members are disposed below the corresponding pressing members.

5 FIG. 14 is a front view for depicting that a sheet of paper which has the edge thereof extending beyond the pressing member is dealt with by the pressing members and the pressing amount limiting members.

10 FIG. 15 is another front view of the pressing amount limiting members disposed below the corresponding pressing members except for the outmost (leftmost) pressing member.

15 FIG. 16 is another plan view of the print receiving member in which the pressing amount limiting members disposed below the corresponding pressing members except for the outmost (leftmost) pressing member.

20 FIG. 17 is a front view of the pressing amount limiting members are disposed inside the corresponding one of the pressing members.

FIG. 18 is a plan view of the print receiving member in which the pressing amount limiting members are disposed inside the corresponding one of the pressing members.

25 FIG. 19 is another front view of the pressing

amount limiting members disposed inside the corresponding one of the pressing members except for the outmost (leftmost) pressing member.

FIG. 20 is another plan view of the print
5 receiving member in which the pressing amount limiting members are disposed inside the corresponding one of the pressing members except for the outmost (leftmost) pressing member.

FIGS. 21(a) and 21(b) are schematic side views
10 for explaining how the pressing members and the pressing amount limiting member may function differently depending on the size of the paper.

FIGS. 22(a) and 22(b) are schematic side views
illustrating that two pressing amount limiting members
15 are arranged between the pressing members.

BEST MODE FOR CARRYING OUT THE INVENTION

Referring to the accompanying drawings, a paper conveying apparatus, an image forming apparatus
20 and an ink jet recording apparatus according to embodiments of the present invention are described hereinafter. Since the following embodiments are illustrated only as preferred embodiments of the present invention, technologically preferable limitations are
25 added thereto. However, the present invention is not

limited to the embodiments disclosed herein unless a particular limitation is recited in the following description.

[Ink-jet recording apparatus]

5 FIG. 1 is a schematic cross-sectional view of an ink-jet recording apparatus according to one embodiment of the present invention. The recording apparatus houses a printing mechanism portion 2 configured to have a carriage 13 movable along the main
10 scanning direction (perpendicular to the paper surface of FIG. 1) in a recording apparatus body 1, a recording head 14 composed of an ink-jet head mounted on the carriage 13, and an ink cartridge 15 configured to supply ink to the recording head 14, or the like. The
15 details thereof are described hereinafter.

In the lower portion of the recording apparatus body 1, a paper feed cassette 4 into which plural sheets of paper 3 can be placed from the front portion thereof is removably loaded. By the way, the
20 paper 3 can be fed from a paper feed tray (not shown) instead of the paper feed cassette 4.

The paper 3 that has once been placed in the paper feed cassette 4 is conveyed through a path defined by a paper feed roller 21 and a friction pad 22 which
25 can cooperatively separate one sheet of paper 3 from

other sheets of paper 3 in the paper feed cassette 4, a conveyance roller 24 which reverses the direction of the paper 3 conveyed from the paper feed cassette 4 to feed the paper 3 forward, and a conveyance roller 26 that
5 defines an ejection angle of the paper 3 that has been ejected from the conveyance roller 24 and an associated conveyance roller 25 that is disposed pressed toward the circumferential surface of the conveyance roller 24. Having traveled through this path, the paper 3 finally
10 reaches the printing mechanism portion 2.

The printing mechanism portion 2 is composed of the carriage 13, the recording head 14, and the ink tank 15, or the like, and functions to print the paper 3.

The carriage 13 is held by a main guide rod 11
15 and a sub guide rod 12 supported by right and left side plates (not shown) so as to slidably move in the main scanning direction (perpendicular to the paper surface of FIG. 1).

The recording head 14 is mounted on the
20 undersurface of the carriage 13 so as to eject ink droplets downward. The recording head 14 is composed of the ink-jet head having nozzles for ejecting ink droplets of yellow (Y), cyan (C), magenta (M), and black (Bk). By the way, the recording head 14 may be composed
25 of plural heads that are disposed side-by-side in the

main scanning direction and eject ink droplets of respective colors. In addition, the recording head 14 may be composed of one head having nozzles capable of ejecting ink droplets of corresponding colors.

5 Below the recording head 14, a print receiving member 27 is arranged as a guide configured to guide the paper 3.

 The ink tank (ink cartridge) 15 is configured to supply ink of each color to the corresponding
10 recording head 14. The ink tank 15 is replaceably mounted on the carriage 13.

 On the paper 3 conveyed to the printing mechanism portion 2 is printed an image by the recording head 14, and then the paper 3 with the image thereon is
15 further conveyed to a paper ejection tray 6 by a configuration described below.

 Downstream from the print receiving member 27 along the paper conveying direction (or along the rightward direction in FIG. 1), a conveyor roller 31 and
20 a spur 32 are arranged for conveying forward (or rightward) the paper 3. Additionally, downstream from the conveyor roller 31 and the spur 32, guide members 35, 36 are arranged so as to define a paper ejection path. Furthermore, downstream therefrom, a paper ejection
25 roller 33 and a spur 34 are arranged for conveying the

paper 3 toward the paper ejection tray 6.

[Print receiving member 27]

Referring to FIG. 2, the print receiving member 27 is detailed hereinafter. FIG. 2 is a schematic perspective view of the print receiving member 27 and the vicinity thereof in the ink-jet recording apparatus 1 according to this embodiment of the present invention. FIG. 3 is a plan view of the print receiving member 27 of the ink-jet recording apparatus 1 according to this embodiment of the present invention. FIG. 4 is a front view of pressing members 101, 102 and the vicinity thereof in the ink-jet recording apparatus 1 according to this embodiment of the present invention.

Referring to FIG. 2, the print receiving member 27 is provided with plural ribs (supporting members) 29. The ribs 29 are arranged so as to define a predetermined gap between the paper 3 and the recording head 14. As shown in FIG. 2, the outermost ribs of the plural ribs 29 are positioned slightly inside the side edge of the paper 3. Preferably, the distance between each of the outermost ribs 29 and the corresponding side edge of the paper 3 is less than or equal to 10 mm. More preferably, the distance therebetween is less than or equal to 5 mm. An attachment portion 28 is provided with the plural pressing members 101, 102, which are

discussed in detail below.

The paper 3 conveyed to the print receiving member 27 is pressed downward by the pressing members 101, 102 and conveyed on and along the ribs 29 disposed on the print receiving member 27. In this manner, a predetermined gap between the paper 3 and the print head 14 is defined. Onto the paper 3 are adhered ink droplets ejected from the print head 14 and thus a predetermined image is formed thereon.

Among the plural pressing members 101, 102, the outermost pressing members 101 (first and second paper pressing members) on both sides can press respective side portions of the paper 3 downward. This allows the side portions of the paper 3 to be bent downwardly in areas outside the outermost ribs 29 (see FIG. 4), thereby preventing the side portions from rising. By the way, a "side portion" here should be understood as being an area near the paper edge extending along the paper conveying direction.

In addition, due to such bending of the paper 3 in both side portions, the paper 3 can be maintained flat even between two adjacent ribs, therefore maintaining constant the gap between the paper 3 and the recording head 14. Moreover, the paper 3 is prevented from contacting the recording head 14 even if the paper

3 swells after absorbing ink droplets, thereby preventing the image thereon from being degraded and the recording head 14 from being damaged.

As stated above, due to a simple configuration
5 of the plural ribs 29 disposed on the print receiving member 27 so as to oppose the recording head 14, the pressing members 101 disposed so as to press the side portions of the paper 3 downward, and the pressing members 102 arranged between every two adjacent ribs in
10 this non-limiting embodiment, the paper 3 is prevented from contacting the recording head 14.

[Pressing member]

Next, the pressing members 101, 102 attached to the attachment portion 28 are described in detail.
15 Each of pressing members 101, 102 according to this embodiment is attached to the attachment portion 28 at the upstream side (or "A" side in FIG. 3) of the print receiving member 27 and extends toward the downstream side (or "B" side in FIG. 3), as shown in FIG. 3.
20 Particularly, the pressing members 101 are arranged outside the outmost ribs 29, thereby preventing the side portions of the paper 3 from rising, as described above.

In addition, since the pressing members 101 are arranged in a symmetric relationship with each other
25 as shown in FIG. 3, the paper 3 is prevented from rising

to a substantially equal degree in both side portions.

By the way, when a paper having a smaller width than the paper 3 illustrated in FIG. 3 is conveyed, other pressing members (i.e., pressing members 102) positioned inside the pressing members 101 can press the side portions of the paper downward. For example, the pressing members 102 (a third paper pressing member) can press downward on the side portions of the paper illustrated by a dotted line in FIG. 3. Therefore, the narrower paper can also be prevented from rising upward in both side portions.

By the way, the pressing members 101, 102 shown in FIG. 3 are arranged symmetrically in relation to a central point of the print receiving member 27, since the paper rests on the print receiving member 27 so that the center of the paper coincides with the central point of the receiving member 27. In contrast, the pressing members 101, 102 may be arranged asymmetrically as shown in FIG. 8, which is suitable when the paper is left-aligned. Specifically, when the paper 3 shown by a dotted line in FIG. 8, which is narrower than the paper 3 shown by a solid line, is conveyed therein, the right edge of the narrower paper can be pressed downward by either one of the pressing members 102.

FIGS. 5(a) and 5(b) show additional examples of the pressing member 101 according to this embodiment of the present invention. As shown in FIG. 5(a), the pressing member 101 has a distal point B which is a
5 downward point in the paper conveying direction. The distal point B lies outward (leftward in FIG. 5(a)) and downstream from a center point A on the upstream side of the pressing member 101.

Additionally, the distal point B is disposed
10 outside the edge (dotted line) of the paper. Moreover, not only the distal point B but at least a portion on the downstream side thereof is also disposed outside the edge of the paper.

As shown in FIG. 5(b), the pressing member 101
15 as the other example has a distal point C that lies outward (leftward in FIG. 5(b)) and downstream from a corner point D on the upstream side thereof.

FIGS. 6(a) through 6(f) show still other examples of the pressing member 101. All the pressing
20 members 101 illustrated therein are disposed so as to press the left side portion of the paper downward.

The pressing members 101 having such shapes as illustrated in FIGS. 5(a), 5(b), and 6(a) through 6(f) can apply a greater pressing force to the side portion
25 of the paper as the paper proceeds downward, thereby

assuredly preventing the side portion of the paper from rising upward.

Moreover, even when the side portion of the paper shifts slightly in the direction transverse to the paper conveying direction, the edge of the paper can touch the pressing member 101 and be pressed downward. Therefore, the side portion of the paper 3 can be bent downward by a weaker pressing force.

Furthermore, since the side portion of the paper, which is easily bent or warped upward, can be pressed downward, the paper is prevented from being contaminated or jammed.

In addition, since the pressing member 101 is narrower in the downstream portion thereof than in the upstream portion thereof, the pressing member 101 can press the side portion of the paper downward with a weaker force, thereby allowing the paper to be kept flat as a whole and thus providing a better quality image. If the pressing force becomes too strong, the paper cannot be maintained flat, since the stronger force may cause the paper to drop between the ribs, which in turn makes it difficult to maintain the paper flat in relation to the recording head 14 (FIG. 1).

Additionally, the outmost ribs 29, which are disposed near the side portions of the paper, can help

keep the paper flat, thereby providing a better quality image. Moreover, since the pressing members 101 are disposed outside the outmost ribs 29, the pressing members 101 can prevent the side portion of the paper
5 from rising upward.

FIGS. 7(a) through 7(d) show various other examples of the pressing members 101. Specifically, FIGS. 7(a) through 7(c) show pressing members having identical widths along the paper conveying direction,
10 which are different from the pressing members 101 illustrated in FIGS. 5(a), 5(b), and FIGS. 6(a) through 6(f).

More specifically, as shown in FIG. 7(a), the pressing member 101 is disposed so that a center point B at the rear (or downstream) end thereof lies outside the
15 paper edge whereas a center point A at the front (or upstream) end thereof lies substantially above the paper edge shown by a dotted line.

In FIG. 7(b), the pressing member 101 is
20 disposed so that the center point B at the rear (or downstream) end thereof lies outside the paper edge whereas the center point A at the front (or upstream) end thereof lies inside the paper edge.

In FIG. 7(c), the pressing member 101 is
25 disposed so that the center points A and B lie inside

the paper edge. Although not only the point A but also the point B lies inside the paper edge in this case, at least a portion of the pressing member 101 can extend outward from the paper edge. Therefore, this pressing member 101 can also press the paper edge downward.

In FIG. 7(d), the pressing member 101 has a rectangular shape and is disposed so that both the center point B at the rear (or downstream) end thereof and the center point A at the front (or upstream) end thereof lie substantially above the paper edge.

Even these pressing members 101 illustrated in FIGS. 7(a) through 7(d) can prevent the paper from rising upward evenly in both side portions of the paper when the pressing members 101 are disposed on both sides of the print receiving member 27. In addition, such pressing members 101 can prevent the side portions of the narrower paper from rising upward.

[Pressing amount limiting member]

Next, a pressing amount limiting member according to one embodiment of the present invention is described. In the foregoing embodiments, the pressing members 101 press the paper outside the outmost ribs 29 downward. In addition, since plural pressing members 102 are disposed on the inner side of the pressing members 101, even when narrower paper is used, the paper

can be bent downward on both side portions (see FIG. 3).

However, the plural pressing members 102 may press the paper downward to a greater extent between all adjacent ribs 29, which may cause the paper, which has
5 to be kept flat in relation to the recording head 14, to be unnecessarily bent. In order to prevent such unnecessary bending, a pressing amount limiting member 30 is provided in this embodiment. That is, an amount of pressing on the paper caused by the pressing members
10 102 can be adjusted by adjusting the elevation of the pressing amount limiting member 30.

The pressing amount limiting member 30 is disposed on the print receiving member 27. Specifically, the pressing amount limiting member 30 may be disposed
15 in three positions in relation to the pressing members 101, 102 as shown in FIGS. 9(a) through 9(c), although the position cannot be strictly limited to the three positions as long as the pressing amount limiting member 30 can restrict the amount of pressing the paper 3
20 caused by the pressing members 102.

In FIG. 9(a), the pressing amount limiting member 30 is disposed outside (or on the left-hand side of) the pressing member 102 between the ribs 29. In FIG. 9(a), the pressing amount limiting member 30 is disposed
25 below the pressing member 102. In other words, the

pressing amount limiting member 30 is disposed so that a portion of the paper pressed downward by the pressing member 102 is held by the pressing amount limiting member 30. In FIG. 9(c), the pressing amount limiting member 30 is disposed inside (or on the right-hand side of) the pressing member 102 between the ribs 29. The pressing amount limiting members 30 disposed as shown in FIGS. 9(a) through 9(c) are discussed in detail hereinafter.

10 First, the pressing amount limiting member 30 disposed outside the pressing member 102 is described with reference to FIGS. 9(a), 10, and 11. FIG. 10 is an explanatory view showing that each of additional pressing amount limiting members 30 is disposed outside
15 the corresponding one of the pressing members 102. FIG. 11 is a plan view of the print receiving member 27 in which each of the additional pressing amount limiting members 30 is disposed outside the corresponding one of the pressing members 102. It should be understood from
20 FIGS. 10 and 11 that a rib 29, a pressing amount limiting member 30, and a third paper pressing member 102 are disposed in this order in a direction from the side edge to the center of the paper 3. The amount of pressing the paper 3 caused by the pressing members 102
25 can be adjusted by adjusting the elevation of the

-27-

pressing amount limiting members 30 so disposed.

As shown in FIG. 10, the pressing amount limiting members 30 have a lower height (vertical length) than the ribs 29. In other words, the pressing amount limiting members 30 are not required to have a height higher than or equal to the ribs 29 because the pressing amount limiting members 30 are not configured to adjust the gap between the paper 3 and the recording head 14, whereas the ribs 29 disposed on the print receiving member 27 are configured to define the gap. In addition, the height of the pressing amount limiting members 30 is not limited to a particular value as long as the pressing amount limiting members 30 can limit the amount of pressing the paper 3 caused by the pressing members 102.

Next, the pressing amount limiting member 30 disposed below the pressing member 102 is described with reference to FIGS. 9(b), and 12 through 16. FIG. 12 is another explanatory view showing that additional pressing amount limiting members 30 are disposed below the respective pressing members 102. FIG. 13 is a plan view of the print receiving member 27 in which the additional pressing amount limiting members 30 are disposed below the respective pressing members 102. Additionally, FIG. 14 shows a situation where the paper

-28-

3 is wider and the paper edge thereof extends beyond the pressing member 101. The amount of pressing the paper 3 caused by the pressing members 102 can be adjusted by adjusting the elevation of the pressing amount limiting members 30 so disposed.

Although FIGS. 12 through 14 each shows an additional pressing amount limiting member 30 disposed below the pressing member 101, such a pressing amount limiting member 30 is not always necessary as shown in FIGS. 15 and 16. Even in these cases, the side portion of the paper 3 can be pressed downward by the pressing member 101, and the paper 3 can be kept flat in relation to the recording head 14 (FIG. 1) since the amount of pressing the paper 3 caused by the pressing members 102 can be limited by the pressing amount limiting members 30 below the pressing members 102.

Then, the pressing amount limiting member 30 disposed inside (or on the right-hand side of) the pressing member 102 is described with reference to FIGS. 17 through 20 as well as FIG. 9(c). FIG. 17 is an explanatory view showing that each of the additional pressing amount limiting members 30 is disposed inside the corresponding one of the pressing members 102. FIG. 17 is a plan view of the print receiving member 27 in which each of the additional pressing amount limiting

members 30 is disposed inside the corresponding one of the pressing members 102. It should be understood from FIGS. 17 and 18 that a rib 29, a third pressing member 102, and a pressing amount limiting member 30 are disposed in this order in a direction from the side edge to the center of the paper 3. The amount of pressing the paper 3 caused by the pressing members 102 can be adjusted by adjusting the elevation of the pressing amount limiting members 30 so disposed.

Although FIGS. 17 and 18 show a pressing amount limiting member 30 disposed between the pressing member 101 and the outermost rib 29, such a pressing amount limiting member 30 is not always necessary as shown in FIGS. 19 and 20. In these cases, the pressing member 101 can press the side portion of the paper 3 downward. Besides, the amount of pressing the paper 3 caused by the pressing members 102 can be limited by the pressing amount limiting members 30 disposed inside the pressing members 102, so that the paper 3 is kept flat in relation to the recording head 14.

Referring to FIGS. 21(a) and 21(b), it is next described how the pressing members 101, 102 and the pressing amount limiting member 30 may function differently depending on the size of the paper 3.

FIG. 21(a) is an explanatory view showing how

the pressing amount limiting member 30 functions to limit the amount of pressing the paper 3 caused by the pressing member 102 when a sheet of paper 3 larger than the paper which the pressing member 102 is supposed to
5 press downward is conveyed therein. In this case, the side portion of the larger paper 3 is pressed downward by not the pressing member 102 but the pressing member 101 in order to prevent the side portion from rising; and the print area of the larger paper 3 is kept flat in
10 relation to the recording head 14 (FIG. 1) by the pressing member 102 and the pressing amount limiting member 30 that limits the amount of pressing on the larger paper 3 caused by the pressing member 102, thereby providing a better quality image thereon.

15 On the other hand, when a sheet of paper 3 that is narrower than the paper 3 illustrated in FIG. 21(a) is conveyed to the print receiving member 27 (FIG. 11) as shown in FIG. 21(b), the narrower paper 3 can be pressed downward by the pressing member 102. In this
20 case, a relatively large area of the side portion of the paper 3 may be pressed downward by the pressing member 102, since no image is printed on the side portion.

In addition, it can be contemplated as other embodiments according to the present invention that
25 plural pressing amount limiting members X are disposed

outside the corresponding pressing members 102 and plural pressing amount limiting members Y below the corresponding pressing members 101, 102.

The pressing amount limiting members X
5 function to limit the amount of pressing the paper 3 caused by the associated pressing members 102 when the edge of the paper 3 reaches the pressing member 101 (see FIG. 22(a)). Thus, the paper 3 can be kept flat in relation to the recording head 14 (FIG. 1) in an area in
10 which the pressing amount limiting member X limits the pressing amount, for better print quality. In addition to the pressing amount limiting members X, the pressing amount limiting members Y can demonstrate a pressing amount limiting effect by adjusting the elevation
15 thereof. Therefore, the paper 3 can be kept flat in relation to the recording head 14 (FIG. 1).

On the other hand, when a narrower paper whose edge does not reach the pressing member 101 is conveyed therein, the pressing amount limiting member Y disposed
20 below the associated pressing member 102 that presses the side portion of the paper 3 downward can limit the amount of pressing the paper 3 caused by the pressing member 102. In addition, adjusting the elevation of the pressing amount limiting members (i.e., 30, X, Y) can
25 reduce or increase the limiting amount caused by the

pressing members 102.

As stated above, according to this embodiment in which the plural pressing amount limiting members 30, X, Y are provided, the pressing amount limiting effect
5 can be appropriately exhibited depending on user needs.

By the way, the present invention is not limited to the embodiments specifically disclosed herein, but various alterations and modifications may be applied without departing from the scope of the invention set
10 forth in accompanying claims.

The present application is based on Japanese Patent Applications No. 2006-146861, filed on May 26, 2006, and No. 2007-065640, filed on March 14, 2007 with the Japanese Patent Office, the entire contents of which
15 are hereby incorporated by reference.

-33-

CLAIMS

1. A paper conveying apparatus comprising:

5 a first paper pressing member configured to press one side portion of a sheet of paper that may be conveyed through the apparatus, the side portion extending along a paper conveying direction.

2. The paper conveying apparatus of claim 1, wherein
10 the first paper pressing member is disposed so that a downstream portion of the member along the paper conveying direction lies outward in a direction transverse to the paper conveying direction from an upstream portion of the member.

15

3. The paper conveying apparatus of claim 1, wherein the first paper pressing member is disposed so that a center of a downstream portion of the member along the paper conveying direction lies outward in a direction
20 transverse to the paper conveying direction from a center of an upstream portion of the member.

4. The paper conveying apparatus of claim 1, wherein the first paper pressing member is disposed so that a
25 center of a downstream portion of the member along the

paper conveying direction lies outward in a direction transverse to the paper conveying direction from a corresponding edge of the sheet of paper.

5 5. The paper conveying apparatus of claim 1, wherein the first paper pressing member is disposed so that a middle portion of the member between a downstream portion of the member and an upstream portion of the member along the paper conveying direction lies outward
10 from a corresponding edge of the sheet of paper.

6. The paper conveying apparatus of claim 1, wherein the first paper pressing member becomes narrower toward a downstream end of the member along the paper conveying
15 direction.

7. The paper conveying apparatus of claim 1, further including one or more supporting members configured to support the sheet of paper from below.

20

8. The paper conveying apparatus of claim 1, further including a second paper pressing member configured to press another side portion of the sheet of paper.

25 9. The paper conveying apparatus of claim 8, wherein

the second paper pressing member is symmetric in shape with the first paper pressing member in relation to the paper conveying direction.

- 5 10. The paper conveying apparatus of claim 8, further including one or more third paper pressing members capable of pressing the sheet of paper between the first and the second paper pressing members.
- 10 11. The paper conveying apparatus of claim 10, wherein the first or the second paper pressing member presses one of the side portions of the sheet of paper and one of the one or more third paper pressing members presses the other of the side portions of the sheet of paper,
15 and wherein the one of the one or more third paper pressing members is disposed symmetrically with the first or the second paper pressing member in relation to the paper conveying direction.
- 20 12. The paper conveying apparatus of claim 10, further including one or more paper pressing amount limiting members disposed below the sheet of paper and configured to be substantially vertically movable so as to limit an amount of pressing on the sheet of paper caused by the
25 first paper pressing member, the second paper pressing

-36-

member, the third paper pressing member, or a combination thereof.

13. The paper conveying apparatus of claim 12, further
5 including one or more supporting members configured to support the sheet of paper from below, wherein the one or more paper pressing amount limiting members push from below the sheet of paper that is held from below by the supporting member and pressed from above by the first
10 paper pressing members, the second paper pressing member, or the third paper pressing member, or a combination thereof, so as to limit the amount of pressing from above.

15 14. The paper conveying apparatus of claim 13, wherein each of the one or more third paper pressing members is disposed between every adjacent two of the supporting members, and wherein one of the one or more supporting members, the corresponding one of the one or more paper
20 pressing amount limiting members, and the corresponding one of the one or more third paper pressing members are disposed in this order in a direction transverse to the paper conveying direction.

25 15. The paper conveying apparatus of claim 13, wherein

each of the one or more third paper pressing members is disposed between every adjacent two of the supporting members, and wherein one of the one or more supporting members, the corresponding one of the one or more third
5 paper pressing members and the corresponding one of the one or more paper pressing amount limiting members are disposed in this order in a direction transverse to the paper conveying direction.

10 16. The paper conveying apparatus of claim 12, wherein each of the one or more paper pressing amount limiting members is disposed below a corresponding one of the one or more third paper pressing members.

15 17. The paper conveying apparatus of claim 12, wherein one of the one or more paper pressing amount limiting members is disposed between the first paper pressing member and the third paper pressing member adjacent to the first paper pressing member.

20

18. The paper conveying apparatus of claim 12, wherein one of the one or more paper pressing amount limiting members is disposed between the second paper pressing member and the third paper pressing member adjacent to
25 the second paper pressing member.

19. The paper conveying apparatus of claim 12, wherein at least one of the one or more paper pressing amount limiting members is disposed outward in a direction
5 transverse to the paper conveying direction from a corresponding edge of the sheet of paper.

20. The paper conveying apparatus of claim 12, wherein a first set of the one or more paper pressing amount
10 limiting members is disposed below the corresponding third paper pressing members, and wherein a second set of the one or more paper pressing amount limiting members is disposed between every adjacent two of the third paper pressing members.

15

21. The paper conveying apparatus of claim 10, further including:

a print receiving member disposed opposing a print head that prints on the sheet of paper;

20 a conveying roller configured to convey the sheet of paper to the print receiving member; and

a pressing roller configured to press the sheet of paper on the conveying roller;

wherein at least one of the first, the second, and
25 the third paper pressing members is configured to press

the sheet of paper on the print receiving member.

22. The paper conveying apparatus of claim 21, further including one or more supporting members disposed on the
5 print receiving member so as to support the sheet of paper from below.

23. An image forming apparatus comprising at least the paper conveying apparatus of claim 1.

10

24. An ink-jet recording apparatus comprising at least the paper conveying apparatus of claim 1.