

5

10

15 "Method and System for providing a session in a heterogeneous environment"

20

TECHNICAL FIELD

The present invention relates generally to system and method of providing an external device with a session in a distributed computerized environment, wherein the session requires establishing conversations between the external device and the system operating in a client/server mode. More particularly, the invention relates to methods and systems wherein possibly very heterogeneous conversations have to share a common session.

25

BACKGROUND

Many existing systems are configured to provide an external device with a session comprising various conversations between software applications of the system and the external device and wherein the external device and the system operate in a client/server mode.

30

These existing solutions have turn out to be efficient for homogenous environments, i.e, environments wherein the software applications involved in a session use a common protocol.

35

However, with these existing systems it is particularly difficult to have conversations using different protocols while sharing a common context for the entire session. Most often, the context for a given session must be duplicated for each protocol used by the involved application servers. Such existing solutions consume
5 processing and data storage capabilities. In particular existing systems do not provide efficient solutions to migrate gradually from applications using given protocols to applications using other protocols while sharing the same context.

Additionally, independently of the protocols used by the conversations, when the
10 external device operates in a server mode in regard to the system operating in a client mode, and when the system comprises a number of application servers, it is particularly complex to have all conversations sharing a common session. In existing solutions the system is provided with a dedicated application server configured to merge the queries from the system into the same outbound conversation with the
15 external device. However, these dedicated application servers undergo an important load which decreases the throughput of these existing systems or renders them poorly reliable or complex.

Therefore, a general objective of the present invention is to solve or to limit at
20 least one of the above mentioned shortcomings of the existing solutions.

More particularly, an objective of the present invention is to describe a solution wherein an external device is provided with a unified view of a session comprising heterogeneous conversations that must share a common context.
25

SUMMARY

The foregoing and other objectives are overcome, and other advantages are realized, in accordance with the embodiments of this invention.
30

The present invention discloses a method of providing an external device with a session, wherein the session requires establishing conversations between the external device and application servers of a system. The external device and the system operate in a client/server mode, the system operating in one mode among the client
35 mode and the server mode, the external device operating in the other mode among the client mode and the server mode.

Each application server processes at least a software application, at least some of the application servers being arranged to store in data storage means at least a part of a context of the session, allowing thereby to distribute the context through various application servers linked to the session.

- 5 The system is provided with at least a routing means configured to establish, for a given session, a conversation between the external device and one of the application servers. Establishing the conversation comprises the following steps performed at the routing means with at least one data processor:
- receiving a call from one among the application server and the external
10 device to reach the other among the application server and the external device;
 - determining if the call comprises a session identifier (ID),
 - If the call does not comprise a session ID, then opening a session for said conversation, creating a session ID that uniquely identifies said session, adding the session ID to the call, storing the session ID and routing the call to
15 the other among the application server and the external device, establishing thereby the conversation;
 - If the call already comprises a session ID, then routing the call to the other among the application server and the external device and allowing said conversation to join an already opened session that is uniquely identified by
20 said session ID, thereby establishing the conversation and enabling the conversation to share the context of an already opened session.

Another aspect of the present invention relates to a non-transitory computer-readable medium that contains software program instructions, where execution of the
25 software program instructions by at least one data processor results in performance of operations that comprise execution of the method as in any one of the preceding features and steps.

According to another aspect, the invention relates to a system comprising means
30 configured to execute the method as in any one of the preceding features and steps.

Another aspect of the present invention is a system for providing an external device with a session wherein the session requires establishing conversations between the external device and application servers comprised in the system, the system being
35 configured to operate in a client/server mode with the external device. The system operates in one among the client mode and the server mode and the external device

operates in the other one among the client mode and the server mode. Each application server is arranged to process at least a software application. Each application server runs on a machine. At least some of the machines are provided with data storage means. At least some of the application servers are arranged to store in data storage means at least a part of a context of the session, allowing thereby distributing the context through various application servers linked to the session.

The system comprises routing means comprising at least a data processor configured to establish the conversation between the external device and the application servers. The one or more routing means are configured to:

- receive a call from one among the application server and the external device to reach the other among the application server and the external device;
- determine if the call comprises a session identifier (ID),
 - If the call does not comprise a session ID, then opening a session for said conversation, creating a session ID that uniquely identifies said session, adding the session ID to the call and storing the session ID, routing the call to the other among the application server and the external device, establishing thereby the conversation;
 - If the call already comprises a session ID, then routing the call to the other among the application server and the external device and allowing said conversation to join an already opened session that is uniquely identified by said session ID, thereby establishing the conversation and enabling the conversation to share the context of said already opened session.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing and other aspects of the embodiments of this invention are made more evident in the following Detailed Description, when read in conjunction with the attached Drawing Figures, wherein:

Figure 1 depicts an example of a system according to an embodiment of the invention wherein an external device is provided with a session comprising conversations using different protocols.

Figure 2 depicts another example of system according to an embodiment of the invention system wherein an external device is provided with a session comprising conversations using different protocols.

Figure 3 shows an example of a system according to an embodiment of the invention wherein various application servers of the system share a common outbound conversation with an external device.

5 Figure 4 depicts an example of a system according to an embodiment of the invention wherein an external device operates with the system in a client mode and wherein another application server operates with the system in a server mode while all conversations between the external devices and the system share a common context.

10 Figure 5 shows an example of a system according to an embodiment of the invention wherein an external device inherits from a previous session security settings in view of using them for a subsequent session.

DETAILED DESCRIPTION

15 Some advantageous features and steps will be described below. Then some exemplary embodiments and use cases will be further detailed in regard with the drawings.

20 The present invention discloses a method of providing an external device with a session, wherein the session requires establishing conversations between the external device and application servers of a system. The external device and the system operate in a client/server mode, the system operating in one mode among the client mode and the server mode, the external device operating in the other mode among the client mode and the server mode.

25 Each application server processes at least a software application, at least some of the application servers being arranged to store in data storage means at least a part of a context of the session, allowing thereby to distribute the context through various application servers linked to the session.

30 The system is provided with at least a routing means configured to establish, for a given session, a conversation between the external device and one of the application servers. Establishing the conversation comprises the following steps performed at the routing means with at least one data processor:

- receiving a call from one among the application server and the external device to reach the other among the application server and the external device;
- 35 • determining if the call comprises a session identifier (ID),

- If the call does not comprise a session ID, then opening a session for said conversation, creating a session ID that uniquely identifies said session, adding the session ID to the call, storing the session ID and routing the call to the other among the application server and the external device, establishing thereby the conversation;
- If the call already comprises a session ID, then routing the call to the other among the application server and the external device and allowing said conversation to join an already opened session that is uniquely identified by said session ID, thereby establishing the conversation and enabling the conversation to share the context of an already opened session.

Thus the invention enables a conversation to open and to uniquely identify a session and then to have another conversation that can join that session. These conversations can thus share the context of that session whatever is their protocol. The external device can therefore be provided with a unified and consistent view of the session comprising the joined conversations.

Providing the user with a unified view of the session means that the user does not notice that the various software applications are processed by various and independent application servers. Thus, the number of software applications and the application servers involved in the session is transparent to the user. The user interacts with the system as if it is one unique application server and machine.

Several transactions and conversations can share the same inbound session if the system operates in a server mode with the external device, or can share the same outbound conversation if the system operates in a client mode with the external device.

Additionally, although the external device is provided with a unified and consistent view of the session, additional application servers can be added to the system with few or no impact on pending sessions, increasing thereby the processing capacity of the system. In addition, although the external device is provided with a unified and consistent view of the session, additional software applications can be integrated to the system with few or no impact on pending sessions, integrating thereby new services.

Optionally, the method according to the invention may comprise any one of the additional but not limitative features and steps:

- Preferably, each application server processes one single software application.
- 5 Thus each application server is dedicated to one single software application.

The conversation to be established has a first session ID and uses a first protocol and at least another conversation has the same session ID and uses a second protocol.

- 10 Thus, according to a particularly advantageous but non limitative feature of the invention, all conversations whatever are the software application that they call can share the same session, whatever is their protocol. For instance, the external device can open a session with a first transaction that calls a first software application and uses a first communication protocol. Then the external device can call, through the
- 15 same session, a second software application that uses a second communication protocol.

- This feature of the invention is particularly advantageous for conducting gradually a migration from some software applications to other software applications using another protocol. Indeed, the invention allows integrating and processing new software
- 20 applications while sharing the context of the previous software applications. Migration can therefore be conducted gradually which is much safer than conducting in one step a migration for all software applications.

- Existing systems do not provide efficient solutions to conduct a gradual migration from applications using given protocols to applications using other protocols while
- 25 sharing the same context.

Preferably, the routing means is an enterprise service bus.

- The system comprises a plurality of routing means. For a given session one
- 30 routing means among the plurality of routing means is a main routing means in charge of routing transactions between the external device and the system.

The step of allowing said conversation to join an already opened session that is uniquely identified by said session ID comprises the following steps performed at the routing means receiving the call:

- polling the other routing means to know which one among the plurality of routing means is the main routing means for said already opened session and then,
- Forwarding the transaction to the main routing means.

5

Preferably, the routing means are at least an enterprise service bus (ESB). An ESB comprises a plurality of ESB component in charge of routing the transactions. A call reaching an ESB component with a request to join a session is forwarded to the ESB component in charge of that session through polling all ESB components with the session ID of that session.

10

According to an embodiment of the invention, the external device operates in a client mode in regard with the system operating in a server mode.

15 The external device can be composed of several heterogeneous components accessing the system with heterogeneous protocols.

Thus, for such use case, the external device can provide a unified view of the session, even if using several conversations to access the server, as if only one conversation is used.

20 All the components of the external device having the same session ID will send transactions to the application server as if they were a single device using a single conversation.

According to another embodiment of the invention, the external device operates in a server mode in regard with the system operating in a client mode.

25

Thus, for such use case, the external device can be provided with a unified view of the session as if all conversations and transactions of that session and coming from the various application servers were coming from one single application server. Thus the invention alleviates the need of having a software application dedicated to merging queries from the system into a common outbound conversation with the external device.

30

All application servers receiving calls sharing the same session ID can share the same outbound conversation with the external device. More precisely, all conversations from application servers having the same session ID share a common portion of conversation, which is the outbound portion between the routing means and the external device.

35

According to another embodiment of the invention, the external device operates in a client mode in regard with the system operating in a server mode and an additional external device operates in a server mode in regard with the system operating in a client mode.

After the step of receiving a call at the routing means and before the step of determining if the call comprises a session identifier (ID), the method comprises an additional step of determining that the call requires joining an already opened session.

The step of determining that the call requires joining an already opened session comprises receiving a request to join an already opened session. The request to join an already opened session is referred to as implicit. Preferably, the request to join an already opened session is held in a session layer of the protocol of said call.

Alternatively, the step of determining that the call requires joining an already opened session comprises the following step: the routing means determines that the received call comes from or requires to be routed to an application server processing a software application dedicated to requests to join an already opened session, which indicates to the routing means that the received call must join an already opened session. The request to join an already opened session is referred to as explicit.

The explicit request to join an already opened session can be sent by an external device.

Alternatively, implicit request to join an already opened session can be sent by the system. Several application servers can therefore share a common outbound conversation with the external device.

Conversation Properties

Advantageously, a given conversation of a session is provided with a property that controls the closure of the session.

A property is configured to close the session upon closure of said given conversation. This property is referred to as a "be owner property"

Another property is configured to close the session upon closure of said given conversation and if no other conversation is still opened for that session and is

configured to keep the session opened upon closure of said given conversation and if at least another conversation is still open for that session

This property is referred to as a "simple share property".

5 Another property is configured to close the session after the end of a predetermined inactivity time period starting upon closure of said given conversation, and if no other conversation is still opened for that session. Then upon closure of the conversation, any new conversation can join the session. during a predetermined time period. This property is referred to as a "Keep on exit property".

10 Advantageously, upon closure of a session the routing means sends to all application servers sharing a conversation for that session a notification of session closure.

Preferably, a routing means in charge of the session keeps a reference of all application servers operating for that session. Thanks to these references, the routing
15 means can inform the application servers that the session is closed.

Upon reception at an application server of the notification of session closure, then said application server closes the conversation(s) that it handles for that session.

If the application server is provided with data storage means configured to store a
20 part of the session context, the method comprises an additional step of deleting said part of the session context upon reception of the notification of session closure. Therefore, the use of processing and storage capabilities is optimized.

According to a preferred embodiment, the application servers form groups of
25 application servers dedicated to a software application, each application server of the same group processing independently the software application to which the group is dedicated, application servers storing a part of the context of a session defining thereby for each session a set of application servers having each an affinity with the user session, the method comprising the following steps:

- 30
- at the routing means, assigning to the session a correlation record (DCX) arranged to comprise affinity keys, each affinity key indicating the application server that has an affinity with the session for a given software application,
 - propagating the correlation record with the transaction, allowing thereby the
35 routing means to target the application servers that are linked to the context of that session.

According to a non limitative embodiment, the session ID is stored in the correlation record.

5 All application servers are independent of each other. They do not know the existence or location of each other. Only the correlation record that is read by the routing means allows establishing a conversation between the software applications.

Thus, the affinity key is a reference added to the correlation record that allows the routing means to target the application server using the part of the context linked to the session that is relevant to process the transaction.

10

Advantageously, the session ID is stored along with the correlation record or is stored in the correlation record.

Thus, the session ID is propagated along with the Affinity Keys to all application servers involved in the session. The session ID of a given session can thereby be implicitly shared with all application servers holding the session context for that session.

20 The session IDs are created by the routing means. The one or more routing means know how to reach every single application servers. Thus, the one or more routing means know the presence of each application server and where that application server is located. The one or more routing means also knows on which application servers a given software application is processed. Preferably:

- the correlation record is stored in data storage means associated to a routing means in charge of the session;
- the main routing means is the routing means that receives the user request;
- 25 – the affinity keys are set by the routing means.

Security settings, Cloning of security context

According to a preferred embodiment, the external device operates in a client mode and the system operates in a server mode. The external device requests to open a new session while inheriting security settings from an already opened session.

30 Inheriting security settings comprises duplicating a part of the context of the already opened session, said part of context containing security settings of the already opened session.

The context of the new session is independent of the context of the already opened session excepted for the part of the context containing security settings.

35

Requesting to open a new session while inheriting security settings from an already opened session, comprises the following steps performed at the routing means:

- receiving from the external device a request to open a new session and a session ID identifying the already opened session,
- 5 - thanks to said session ID, retrieving the security settings of the already opened session,
- propagating said security settings with the conversation of the new session.

Therefore, various sessions can be opened, each having a dedicated applicative context, while sharing the same security settings. Only the part of the context that
10 relates to security settings is duplicated. The remaining of the context is not duplicated.

Independence of each session is thus maintained while alleviating the need for performing an authentication for each session.

Therefore a high number of requests can be sent to the system while limiting the load of application servers dedicated to security controls and cumbersome
15 authentications. The invention also circumvents the need of processing queries by pools of conversations.

Preferably, security settings generated by a conversation of the already opened session are received and stored at the routing means in association with the session ID of that already opened session. Then, a conversation of a new session can provide the
20 routing means with the session ID of the already opened session for retrieving the security settings of the latter, alleviating thereby the need of authenticating at each new session.

According to a preferred embodiment, all the sessions sharing the same security context are linked, so the external device can close all the sessions in one single
25 request. Similarly, a remote security administrator can request closure of all sessions sharing the same security context in one request.

The request for sharing security context can be performed explicitly using a dedicated service call. Alternatively, it can be performed implicitly, through a request hold in a session layer of the protocol, allowing thereby sending parallel stateless
30 queries to the system while using the same authentication.

In the context of the invention, an external device is a system such as a processing unit, a personal computer, a smart phone, a database equipped with a processing unit, a data store etc.

35 According to an embodiment, the external devices operate with the system in a client mode with the system that operates in a server mode. Thus, external devices can

send queries to the system. Typically, this type of external device gathers personal computer of user, servers running websites etc. For instance such an external device is a website enabling users to book and purchase travel and tourism products and services. Typical products relate to flight, train, car rental or hotel. The external device
5 can also be a system forming part of a reservation system and which sends queries related to travel availability (typically queries related flight availability).

According to another embodiment, the external devices operate in a server mode, the system operating in a client mode. Typical examples of such external devices are processing units or data stores that provide the system with data. For
10 instance such an external device is a data store operated by a corporation providing travel and tourism products and services. The data store can be an inventory in charge of availability of flights and operated by an airline or by a global distribution system (GDS).

A conversation is a communication between two components, the components
15 being an external device and an application server of the system or being two application servers of the system. Only one protocol is used per conversation.

A transaction comprises all conversations and processing that are required to fulfill a query. A call is initiated by any one of an external device or an application server to establish a conversation.

20 A session usually comprises a plurality of conversations and may comprise a plurality of transactions. A session is associated to a context. The context can be generated by the application servers and/or can be provided by an external device.

In the present invention, the user context also referred to as context is a context
25 related to a user and relevant to process a session. It represents all the functional and technical information that are used by the system for this specific user to perform the requested functionalities, e.g. in the travel reservation system, the reservation (shopping) session context which is linked to an active end-session.

A part of the user context may be data provided by the user such as user
30 personal references, a departure date, an origin or a destination. A part of the user context may be required by a software application linked to the storage means. The part of the user context may also be data generated by the software application. For instance, the part of the user context may relate to flight availability retrieved by the software application or to prices computed or retrieved by the software application. The
35 part of the user context may also relate to a passenger name record (PNR) or a part of a PNR.

As illustrated on Figure 1, the system comprises routing means 10, 11, 12, 13 configured to route transactions. Preferably, the routing means is an enterprise service bus. Alternatively, the routing means can also be a router or any other means able to route a transaction to an appropriate application server. In the following, the routing means will be referred to as ESBs, whatever is their nature: enterprise service bus, router etc.

For each user session, one ESB is in charge of the session. This ESB is referred to as the main ESB. Preferably, the main ESB is the ESB 10 that receives the request from the user. When the main ESB comprises several ESB components, for each session there is preferably one component that is in charge of said session. Said component is referred to as the main ESB component.

Preferably, the system comprises a plurality of machines. Each machine is a hardware device that comprises at least a processing means running at least an application server. At least some of the machines also comprise data storage means. At least an application server runs on a machine. The application server A1, A2, ...C4..., uses the processing means. At least some of the application servers also use the data storage means. Thus an application server is linked to processing means and eventually to data storage means.

According to a particular embodiment, a plurality of application servers runs on a single machine. Each application server may use its own processor means and eventually its own eventual data storage means. Alternatively, a plurality of application servers may share the same processor and eventually the same data storage means.

According to another embodiment, only one application server runs for a given machine. Thus, according to this other embodiment, routing a transaction to a machine will also mean routing a transaction to an application server in the description below.

Each application server processes a software application.

Advantageously, the same software application is independently processed by a plurality of application servers, these application servers running on the same machine or on different machines.

The system can also be referred to as a platform.

Application servers are organized into groups 20, 30, 40. Application servers are also referred to as machines.

Each application server of the same group of application servers processes the same software application.

Then a given software application can be processed in parallel on a number of application servers. For instance, each application server A1, A2, ..., A8 of group 20 processes the software application A. Each application server B1, B2, ..., B8 of group 30 processes the software application B. Each application server C1, C2, C3, C4 of
5 group 40, processes the software application C.

For a given session there is only one application server that operates per software application. Thus, among a group of application servers that process the same software application, one application server is dedicated to that given session.

Each application server that needs to store data is provided with data storage
10 means. The application server dedicated to a given session uses the storage means of the machine on which it runs. This application server dedicated to a given session can thus store in these storage means the part of the user context that is relevant for the software application processed by this application server.

Thus, the context of the user is distributed over a possible very large number of
15 application servers, each part of the user context being stored locally. As depicted on Figure 1, the context of user U_a comprises the parts a₀, a₁, a₂, a₃ and is distributed through the application servers A₃, B₈, C₄. a₀ is stored in the data storage of the main ESB. A₀ contains the session ID referencing the user session and all the data related to the conversations opened with user and the application servers. Eventually, a₀ also
20 comprises a correlation record. The correlation record (DCX) will be further detail below.

Therefore, all application servers that are dedicated to a given user session form a set of application servers having each an affinity with that session.

25 A solution that allows heterogeneous conversations to share a common session will be now detailed.

External device 200 sends a call to system 100. ESB 10 receives the call (step 101). No previous conversation has been opened by external device 200 for that session. This call 101 does not comprise any session identifier (session ID). Then ESB
30 10 creates a session ID and stores the session ID. ESB 10 also routes the call to an application server that processes the software application called by the external device 200 (step 102). ESBs are configured to know which group of application servers processes the software application requested by external device 200.

Thus a conversation is established between external device 200 and application
35 server A₃ that is dedicated to process software application. Application server A₃ processes the transaction. A part a₁ of context is created and stored in the data storage

means associated to A_3 . A_3 calls another software application (software application B). Such call is also referred as a collateral call. ESB 11 is in charge of routing calls coming from the group of application servers that are dedicated to process software application B.

5 ESB 11 selects, for instance through load balancing rules, application server B8 among the group 30 of application servers that are dedicated to process software application B and routes the transaction to B8 generating thereby a conversation between application servers A_3 and B8 (step 103). Such conversation is also referred to as a collateral conversation. B8 processes the transaction and creates a part of
10 context for that session. This part a_2 of context is stored in data storage means provided with application server B8.

After processing, application server B8 calls software application C. ESB 13 in charge of routing calls from group 30 of application servers that are dedicated to process software application B selects application server C_4 . The transaction is routed
15 to application server C_4 (step 104). Application server C_4 processes the transaction and creates a part a_3 of the context for that session.

Thus the transaction comprises steps 101, 102, 103, 104.

Therefore, the session comprising all mentioned conversations has a context comprising parts a_0 , a_1 , a_2 , a_3 . Said context is distributed through a plurality of
20 application servers.

External device 200 opens another conversation (step 105). Previously, external device 200 has retrieved the session ID created by the ESB 10.

External device also requests that this other conversation joins the session opened with the previous conversation.

25 Such request to join the already opened session can be explicit or implicit.

An explicit request means that external device 200 calls a software application dedicated to requests for join session. ESB 10 identifies the software application that is called by external device 200 and determines that the new conversation of ESB 10 must share the already opened session.

30 An implicit request means that the call from ESB 10 comprises a header comprising a request for join session. More precisely, the session layer of the protocol of this new conversation holds a request for join session.

When ESB 10 determines that the new conversation is expected to join an already opened session, then the ID session of that new conversation is checked.

35 If ESB 10 holds an identical session ID, then it means that this ESB 10 is the ESB managing the already opened session. Then, ESB 10 allows the call from external

device 200 to reach the required application server and to join the already opened session.

If ESB 10 does not hold an identical session ID, then it polls the other ESB or other components of ESB in order to identify which ESB or component of ESB is in charge of the already opened session having an identical session ID. Such ESB (or
5 ESB component) in charge of a session is referred to as the main ESB (respectively main ESB component) for that session.

When the main ESB is identified, the ESB that received the call from external device 200 forwards the request to join the session to the main ESB. In the use case
10 illustrated at Figure 1, the main ESB is also the ESB that receives the second transaction from the external device 200.

Once the main ESB has received the request to join the session, then the new conversation shares the already opened session, and can therefore share the context of the already opened session.

15 A particularly advantageous use case of the invention relates to session wherein various conversations use different protocols. Thanks to the invention, each conversation whatever is its protocol can share the context of the other conversations.

For example, transaction 2 comprising conversations illustrated by steps 105, 106 can share the context of transaction 1 comprising conversations illustrated by
20 steps 101, 102, 103 and 104.

Referring to Figure 1, external device 200 requests to open a new conversation with another protocol while sharing the context of previous conversations.

As mentioned above these features of the invention are particularly advantageous to migrate services using a protocol to other services using another
25 protocol.

The invention is not limited by the number of conversations joining a session. Additionally, the invention is not limited by the number of different protocols used by the various conversations joining a session.

30 **Figure 2** depicts another use case wherein the invention turns out to be particularly advantageous. In this embodiment, ESB are included in service integrator (SI). The SI comprises a plurality of multiplexers MUX 1, MUX 2, MUX 3 that are configured to receive calls from external devices such as external device 200 and from various application servers of the system 100. The SI also comprises servers such as
35 SRV1 and SRV2 having each a function of routing means.

In this embodiment, application servers are referred to as open back ends (OBEs). OBEs are gathered into groups 20, 30, 40 of OBEs. Group 20 gathers OBE A₁, OBE A₂, OBE A₃ that each processes software application A. Group 30 comprises OBE B₁ and B₂ that each processes software application B. Group 40 comprising OBE C₁ that processes software application C.

External device 200 sends a call to SI that reaches MUX 1 (step 201). This call uses a protocol referred to as Protocol 1. MUX 1 routes the call to SRV2 (step 202). As no session ID is comprised in this call, SRV2 opens a session and creates a session ID. Session ID is stored at SRV2. SRV2 determines that software application A is called and selects application server OBE A₁ among group 20. SRV2 creates a correlation record (DCX) that indicates that application server OBE A₁ is the application server that is linked to that session among application servers dedicated to process software application A. Such indication is referred to as an Affinity Key. Then, Affinity Key of the DCX indicates that OBE A₁ has an affinity with that session.

A general description and exemplary embodiments of the correlation record, its functionalities and its advantages are available in a co-pending patent application filed in the name of the Applicant of the present patent application, having the same priority date as the present patent application and entitled: "Method and System for providing a session involving a plurality of software applications".

SRV2 routes the call to OBE A₁ (step 203) establishing thereby a conversation between external device 200 and OBE A₁ through the SI. OBE A₁ processes the call. It eventually stores a part of the context of the session in the storage means that it uses.

Preferably, OBE A₁ creates a reference, referred to as the Applicative Context Key, which indicates how to retrieve the part of the context that it has stored. The Applicative Context Key is stored in the DCX. Therefore, next time OBE A₁ will receive a call for that session, it will be able to easily retrieve the part of the context that it holds for that session.

The DCX as enriched with the Applicative Context Key is returned back to SRV2 (step 204). SRV2 stores the DCX as enriched by OBE A₁.

Results of processing along with the DCX are sent to the external device 200 through MUX 1 (steps 205, 206). The session ID is also sent to the external device 200.

According to a specific and non limitative embodiment, the session ID may be stored in the DCX. Thus, as the DCX is propagated to each call and collateral call of each conversation, the session ID will also be propagated and cascaded. When

external device 200 is provided with the results of the processing or with the DCX only, this first conversation ends.

Then, external device 200 opens another conversation using a protocol 2 (step 207).

5 This call contains the session ID retrieved from the first conversation and reaches MUX 2. MUX 2 is dedicated to calls using protocol 2.

 This call contains a request to join already an opened conversation. MUX 2 polls all routing means (SRV1 and SRV2) with the session ID sent by external device 200. SRV2 identifies that it already holds an identical session ID. MUX 2 then forwards to
10 SRV2 the request to join a session (step 208).

 Then SRV2 allows this new call to share the already opened session. The context of the session is therefore available to the new conversation. SRV2 determines that an application server dedicated to software application B is called and selects one of these application servers as no request of affinity is set yet for that software
15 application. OBE B₂ is selected. An affinity for that group 30 is set and the DCX is enriched with an Affinity Key pointing to OBE B₂.

 The request of affinity is part of the ESB configuration. Based on a transaction parameters, such as the source, the destination and the software application of the transaction reaching an ESB, that ESB, thanks to its configuration is able to determine
20 whether the transaction must be processed taking into account an affinity. Thus, static information (configuration of the ESB) is taken into account in order to determine whether an affinity is requested while. The content of the DCX is dynamic information.

 The transaction is then routed to OBE B₂ (step 209). OBE B₂ processes the transaction. It stores a part of the context in the storage means of the machine on
25 which it runs and enriches accordingly the DCX with an Applicative Context Key. DCX is returned back to SRV2 (step 210) where it is stored. Results of processing along with enriched DCX are routed to external device 200 (step 211).

 A step 212, external device 200 requests to open another conversation using another protocol (protocol P3). MUX 3 is in charge of managing calls using protocol 3.
30 ID of the session is included in the call and allows MUX 3 to forward the request for join session to SRV2 holding the same session ID and managing that session (step 213).

 SRV2 then opens the session to this new conversation. Conversation using protocol 3 can thus share the context created by the conversations using protocol 1 and protocol 2.

35 Thus, SRV2 identifies that software application B is called. Thanks to the DCX, SRV2 determines that an affinity is requested for that software application and targets

application server OBE B₂. The transaction is then routed with the DCX to OBE B₂ and a conversation is opened between external device 200 and OBE B₂ (step 214). Applicative Context Key of the DCX allows OBE B₂ to retrieve the part of the context that it holds. OBE B₂ processes the transaction. Eventually, OBE B₂ updates the Applicative Context Key and sends back the transaction along with the DCX to SRV2 (step 215). SRV2 stores the DCX as enriched.

Results of processing performed by OBE B₂ along with the DCX are sent to external device 200.

This exemplary embodiment clearly illustrates that the invention allows conversations using different protocols to share the same context through sharing the same session.

This turns out to be particularly advantageous for migrating from a protocol to another while sharing the same context. Thus, migration can be conducted gradually, for instance service by service.

This use case also illustrates the advantages to propagate the correlation record along with the session ID while limiting traffic and routings.

Figure 3 illustrates other advantages of the invention. In this use case, the external device 300 operates in a server mode in regard with the system 100 operating in a client mode. For instance, the external device is a system held by a provider of data while the system comprises application servers that need to retrieve and to process these data.

Although the system comprises a plurality of application servers, it interacts with the external device as if it comprises a single application server. ESB 15 receives a call from an application server A₂ of group 20 of application servers that are dedicated to process software application A (step 301). This call is intended to reach external device 300. As this call does not comprise session ID, ESB 15 opens a session and creates a session ID. This session ID uniquely identifies session a. ESB 15 stores said session ID and routes the call to external device 300 (step 302). A conversation is therefore opened between application server A₂ and external device 300. Responses from external device 300 are received at ESB 15 which routes said responses to the application server A₂ having called external device 300. Session ID is also sent to this application server.

Then, another call reaches ESB 15 (step 303). This call comes from application server B₃. The call contains a request to join a session already opened and contains the session ID previously created by ESB 15. Said session ID has been propagated from application server A₂ to eventually other application servers or to another external

device operating in a client mode with the system, before reaching application server B₃.

ESB 15 opens the session previously opened so that the call from B₃ can share the same outbound conversation with external device 300.

5 Similarly, a call from application server C₂ opens a conversation that share the previously opened session. A₂, B₃ and C₂ then share with external device 300 the same outbound conversation thanks to the session ID. Preferably, the session ID is stored in a DCX propagated to all application servers having an affinity with the context of session a. Preferably, the DCX is stored at the ESB in charge of managing said user
10 session.

Similarly, another session (session b) is opened. A₅, B₅, C₄ share the same outbound conversation thanks to another session ID uniquely identifying session b. A₅, B₅ and C₄ respectively hold parts b₁, b₂ and b₃ of the context of user session b.

Similarly, user session c is opened. A₄, B₇, C₃ share the same outbound
15 conversation toward external device 300' thanks to another session ID, uniquely identifying session c. A₄, B₇, C₃ respectively store parts c1, c2, c3 of the context of user session c. Therefore, external device 300' interacts with many application servers as if these application servers were a single application server.

The request to share a session can be explicit or implicit. As detailed previously,
20 a call reaching an ESB component with a request to join a session is forwarded to the ESB component in charge of that session through polling all ESB components with the session ID of that session.

The use case depicted on Figure 3 clearly illustrates that the system can share a common outbound conversation with an external device whatever are the originators of
25 calls from system 100. Therefore external device interacts with system 100 as if all application servers were a single application server.

The context of the session can therefore be distributed without impacting the various external devices. This is very advantageous when the system is operated by a corporation that is different from the one operating the external device.

30 Additionally, the invention allows adding a group 60 of application servers to a group 20 of application servers with no impact on the external device. Processing capacity can therefore be easily increased. In addition, adding a group 50 of application servers D1, D2, D3, D4 dedicated to a new service D is totally transparent to the external device. The application servers of group 50 can run on the same machine or
35 can each run on a dedicated machine. Thus the invention alleviates the need to

change the initial system configuration. Enhanced services can therefore be offered to users (not illustrated on Figure 3).

Advantageously, when joining a session, a conversation has a property that defines to which extent it controls the closure of the session. The three properties
5 below allow managing efficiently the session, enabling for instance to optimize the use of storage capacity for that session.

When the conversation is set with a first property, the session closes upon closure of the conversation. This property is referred to as a "be owner property".

When the conversation is set with a second property, the session closes upon
10 closure of the conversation and provided no other conversation is still opened for that session. If at least another conversation is still opened for that session and even if the conversation set with the second property closes, the session remains opened. This property is referred to as a "simple share property".

When the conversation is set with a third property, the conversation closes the
15 session after the end of a predetermined time period starting upon closure of the conversation. Then upon closure of the conversation, any other conversation or any new conversation can join the session during a predetermined time period. This property is referred to as a "Keep on exit property".

20 Preferably, upon closure of a session the routing means sends to all application servers sharing a conversation with that session a notification of session closure. Then all application servers close their conversation opened for that session.

Preferably, a routing means in charge of the session keeps a reference of all application servers operating for that session. Thanks to these references, the routing
25 means can inform the application servers that the session is closed.

Figure 4 depicts another exemplary use case of the invention wherein the system interacts with an external device 200 operating in a client mode with the system 100, while an external device 300 operates in a server mode with the system 100. A
30 possibly high number of external devices 200 and a possibly high number of external devices 300 could interact with the system. This use case combines the features and advantages of previously described use cases of figures 1, 2 and 3.

In particular, external device 200 can open a stateful transaction with external device 300 through some application servers of the system 100 (application server A_3 as
35 as illustrated on figure 4). The transaction comprises the conversations 401, 402, 403.

External device 200 can open a subsequent transaction sharing the context of the previous transactions. The subsequent transaction comprises the conversations 404, 405, 406, 407.

Conversations 404, 405 are processed on different application servers than conversations 401, 402 of the previous transaction.

However, previous and subsequent transactions share the same stateful conversation (403, 407).

Thus, external device 300 interacts with all application servers as if they were a single application server. Previous and subsequent transactions could possibly use different protocols. The session ID propagated with each transaction allows sharing the context of the session comprising both transactions.

Other advantageous features of the invention will be now detailed with reference to **Figure 5**. A conversation can request the creation of a new session and a new context for that session while inheriting security settings from the already opened session.

The new session, also referred to as the subsequent session or cloned session, has its own context excepted regarding the security settings and can therefore be considered as a session that is cloned from the session already opened.

This allows an external device to open several cloned sessions and then to have several applicative contexts while performing one authentication to the system. Thus, only a part of the context of the already opened session is duplicated to the cloned sessions. This part of context relates to security settings.

Preferably, all cloned sessions are linked to the previously opened session. Thus, all cloned sessions can be closed with one single request. All cloned sessions can be closed upon closure of the previous session. Alternatively, all cloned sessions can be closed on request of a security administrator.

As for join session, a request to open a cloned session can be performed explicitly through calling a dedicated software application or implicitly with a dedicated header embedded in the call.

Using implicit cloned sessions, an external device operating in a client mode in regard with the system operating in a server mode can send parallel stateless queries to the system while performing a single authentication.

With existing systems, parallel queries requiring each to have a dedicated context necessitate each to perform an authentication. Application servers dedicated to authentication are therefore massively called which leads to a low reliability or requires

costly equipments. Other existing solutions are based on pools of conversations, one single authentication being required for a pool of conversations. Although these solutions alleviate the need to authenticate for each query, they require important changes in existing equipments.

5 Referring to figure 5, external device 200 calls ESB 10 (step 501). ESB opens a session and creates a session ID. ESB routes the call to an application server A_2 in charge of security checkings (step 502). Application server A_2 processes the transaction and generates security credentials that are sent back to external device through ESB 10 (step 504). ESB 10 stores session ID and security settings. Eventually,
10 application server A_2 calls another application server (C_2) creating another part of the context for that session (step 503).

External device 200 then sends another call to ESB 10. Typically, this call is another query that must be processed by system 100 (step 505).

The call contains the session ID of the session already opened. Additionally, the
15 call contains a request to clone the session already opened. ESB 10 in charge of the previously opened session retrieves the security settings taking into account the session ID. The part a_0 of the context of the previous session and that contains the security settings are duplicated to form a part of the context a_0' for the cloned session. Then transaction for that cloned session containing the security settings is routed to the
20 relevant application server (B_3) (step 506). Said relevant application server is not an application server dedicated to generating security settings. However this relevant application checks whether the received transaction comprises required security settings.

Application server B_3 can therefore process the transaction and enrich the
25 context of the cloned session. Results of the processing are sent to the ESB and the query from external device 200 is fulfilled (step 507).

The cloned session therefore comprises its own context excepted a_0' regarding the security settings i.e., the applicative context of the cloned session is independent of the one of the already opened session.

30 From the above description, it appears that the present invention provides a way to give a unique view of a fully distributed client application, all parts of the possibly distributed external device using the same outbound or inbound conversation with the system.

35 Additionally, the present invention provides a way to manage the same session from heterogeneous communication protocols. This eases the migration from a protocol to another or the integration of heterogeneous external devices.

It also provides a way to manage several context sessions and stateless parallel queries in a single security session.

5 The foregoing description has provided by way of exemplary and non-limiting examples a full and informative description of various method, apparatus and computer program software for implementing the exemplary embodiments of this invention. However, various modifications and adaptations may become apparent to those skilled in the relevant arts in view of the foregoing description, when read in conjunction with the accompanying drawings and the appended claims. As but some examples, the use of other similar or equivalent data structures and logic flows may be attempted by those skilled in the art. However, all such and similar modifications of the teachings of this invention will still fall within the scope of the embodiments of this invention.

Furthermore, some of the features of the exemplary embodiments of this invention may be used to advantage without the corresponding use of other features. 15 As such, the foregoing description should be considered as merely illustrative of the principles, teachings and embodiments of this invention, and not in limitation thereof.

CLAIMS

1. Method of providing an external device with a session in a distributed computerized environment, wherein the session requires establishing conversations between the external
5 device and application servers of a system, the external device and the system operating in a client/server mode, the system operating in one mode among the client mode and the server mode, the external device operating in the other mode among the client mode and the server mode, characterized in that each application server processes at least a software application, at least some of the application servers being arranged to locally store in data
10 storage means at least a part of a context of the session, allowing thereby to distribute the context through various application servers;

in that at least a routing means comprised in the system performs a step of establishing, for a given session, a conversation between the external device and at least one of the application servers;

15 and in that establishing the conversation comprises the following steps performed at the routing means with at least one data processor:

- receiving a call from one among the application server and the external device to reach the other among the application server and the external device;
- determining if the call comprises a session identifier (ID),

20 - if the call does not comprise a session ID, then opening a session for said conversation, creating a session ID that uniquely identifies said session, adding the session ID to the call, storing the session ID and routing the call to the other among the application server and the external device, establishing thereby the conversation;
25 - if the call already comprises a session ID, then routing the call to the other among the application server and the external device thereby establishing the conversation and allowing said conversation to join an already opened session that is uniquely identified by said session ID through enabling the conversation to share the context of said already opened session;

wherein the system comprises a plurality of routing means, wherein for a given session one
30 routing means among the plurality of routing means is a main routing means in charge of routing transactions between the external device and the system;

and wherein the step of allowing said conversation to join an already opened session that is uniquely identified by said session ID comprises the following steps performed at the routing means receiving the call: polling the other routing means to identify which one among the
35 plurality of routing means is the main routing means for said already opened session and then forwarding the transaction to the main routing means.

2. The method according to the preceding claim, wherein the established conversation has a first session ID and uses a first protocol and wherein at least another conversation has the same session ID and uses a second protocol different from the first protocol.

5

3. The method according to any one of the preceding claims, wherein the external device operates in a client mode in regard with the system operating in a server mode.

10

4. The method according the preceding claim, wherein all application servers receiving calls having the same session ID share the same inbound session with the external device.

5. The method according to any one of claims 1 or 2, wherein the external device operates in a server mode in regard with the system operating in a client mode.

15

6. The method according the preceding claim, wherein all application servers receiving calls sharing the same session ID share the same outbound conversation with the external device.

20

7. The method according to any one of the preceding claims, wherein the external device operates in a client mode in regard with the system operating in a server mode and wherein an additional external device operates in a server mode in regard with the system operating in a client mode.

25

8. The method according to any one of the preceding claims, wherein after the step of receiving a call at the routing means and before the step of determining if the call comprises a session identifier (ID), the method comprises an additional step of determining that the call requires joining an already opened session.

30

9. The method according to the preceding claim, wherein the step of determining that the call requires joining an already opened session comprises receiving a request to join an already opened session and wherein the call comprises a header comprising a request to join a session.

35

10. The method according to claim 8, wherein the step of determining that the call requires joining an already opened session comprises the following step: the routing means determines that the received call comes from or requires to be routed to an application

server that processes a software application dedicated to requests to join an already opened session, which indicates to the routing means that the received call must join an already opened session.

5 11. The method according to any one of the preceding claims, wherein a given conversation of a session is provided with a property that controls the closure of the session.

12. The method according to the preceding claim, wherein the property is configured to close the session upon closure of said given conversation.

10

13. The method according to claim 11, wherein the property is configured to close the session upon closure of said given conversation and if no other conversation is still opened for that session and wherein the property is configured to keep the session opened upon closure of said given conversation and if at least another conversation is still open for that session

15

14. The method according to claim 11, wherein the property is configured to close the session after the end of a predetermined inactivity time period starting upon closure of said given conversation.

20

15. The method according to any one of the preceding claims, wherein upon closure of a session the routing means sends to all application servers sharing a conversation for that session a notification of session closure.

25 16. The method according to any one of the preceding claims, wherein the system comprises application servers forming groups of application servers dedicated to a software application, each application server of the same group processing independently the software application to which the group is dedicated, application servers storing a part of the context of a session defining thereby for each session a set of application servers having
30 each an affinity with the user session, the method comprising the following steps at the routing means:

- assigning to the session a correlation record arranged to comprise affinity keys, each affinity key indicating the application server that has an affinity with the session for a given software application,

- propagating the correlation record with the transaction to an application server that is relevant to process the transaction, allowing thereby all the routing means to target the application servers that are linked to the context of that session.

5 17. The method according to any one of the preceding claims, wherein the external device operates in a client mode and the system operates in a server mode, wherein the external device requests to open a new session while inheriting security settings from an already opened session, wherein inheriting security settings comprises duplicating a part of a context of the already opened session, said part of context containing security settings of
10 the already opened session and wherein the new session has a context that is independent of the context of the already opened session excepted for a part of its context containing security settings.

18. The method according to the preceding claim, wherein requesting to open a new
15 session while inheriting security settings from an already opened session, comprises the following steps performed at the routing means:

- receiving from the external device a request to open a new session and a session ID identifying the already opened session,
- retrieving the security settings of the already opened session based on said session
20 ID,
- propagating said security settings with a conversation of the new session.

19. A non-transitory computer-readable medium that contains software program instructions, where execution of the software program instructions by at least one data
25 processor results in performance of operations that comprise execution of the method as in any one of the preceding claims.