

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

9902778-1



RTMP COPY

+
IPER+
Replacement

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT) sheet

(51) International Patent Classification ⁶: C04B 7/00, C08J 3/40, 5/11, 51/00, 3/00, 69/00	A1	(11) International Publication Number: WO 98/31643 (43) International Publication Date: 23 July 1998 (23.07.98)
(21) International Application Number: PCT/US98/00893 ✓ (22) International Filing Date: 20 January 1998 (20.01.98) ✓ (30) Priority Data: 60/039,149 21 January 1997 (21.01.97) ✓ US (71) Applicant: W.R. GRACE & CO.-CONN. [US/US]; 1114 Avenue of the Americas, New York, NY 10036 (US). ✓ (72) Inventors: DARWIN, Charles, Darwin; 9009 Blue Pool, Columbia, MD 21045 (US). TAYLOR, Robert, T.; 794 Southern Hills Drive, Arnold, MD 21012 (US). JEKNAVORIAN, Ara, A.; 4 Percheron Road, Chelmsford, MA 01824 (US). SHEN, Ding, Feng; 1 Park Street, Lexington, MA 02174 (US). (74) Agents: BAKER, William, L. et al.; W.R. Grace & Co.-Conn., 62 Whittemore Avenue, Cambridge, MA 02140 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, ID, IL, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>

(54) Title: EMULSIFIED COMB POLYMER AND DEFOAMING AGENT COMPOSITION AND METHOD OF MAKING SAME**(57) Abstract**

Exemplary emulsion admixture for use in hydraulic cement compositions formed by emulsifying an antifoaming agent, surfactant, and a comb polymer having a carbon-containing backbone to which are attached cement-anchoring members and oxyalkylene groups. A method of making a stable emulsion admixture comprising the comb polymer, as well as a hydraulic cement composition comprising the admixture, are also described.