

## FIXATION SYSTEM FOR HYDRAULIC JACKING SYSTEM

### Field of the Invention

**[0001]** The present invention relates generally to an offshore self-elevating platform and more particularly to a fixation system for a hydraulic jacking system that can be employed in an offshore self-elevating platform.

### Background of the Invention

**[0002]** Offshore self-elevating platforms have been widely employed in offshore exploration and production for oil or gas, as well as in other offshore markets such as for offshore electrical stations, construction support and accommodations. The self-elevating platforms usually comprise a deck structure with a top platform for providing a working area and accommodating various working instruments, and a plurality of legs along which the deck structure can be jacked up or down.

**[0003]** Self-elevating platforms are preferred when offshore platforms need to be installed independently on site or to be moved to new locations from time to time. Self-elevating platforms may be used in many offshore industries such as oil and gas drilling or production, construction, accommodation and so on. Several different approaches may be used for providing the elevation means required for a self-elevating platform. Hydraulic jacking systems are commonly used in self-elevating platforms for lowering the legs from an afloat condition and for raising the hull out of the water. The hydraulic jacks can be arranged in many ways to achieve this. One such arrangement is illustrated in FIGS 1 and 2.

**[0004]** FIG 1 shows a basic arrangement of a self-elevating platform. In this arrangement, the self-elevating platform **1** comprises a deck structure **10**, a plurality of legs **20**, and a plurality of footings **30**, where the plurality of legs **20** pass through the deck structure **10** and are supported by the plurality of footings **30**. In order to provide the elevating means for raising and lowering the deck structure **10** relative to the legs **20**, the self-elevating platform **1** is further equipped with a jacking system **40**. When installed on site, the footings **30** provide support in a seabed **S** and the deck structure **10** is elevated above the water level **W**. The plurality of legs **20** have lifting points **21** to provide engagement means between the legs **20** and the jacking system **40**. In this illustration the lifting points **21** are illustrated as holes

through the leg, but these could also be provided by other means known in the industry. The platform may have three or more legs, and arrangements with three, four and six legs are common.

[0005] FIG 2 shows a schematic view of the jacking system **40** of FIG 1. The jacking system **40** is shown using a tubular leg **20** with pin holes **21** to engage the leg. The jacking system **40** comprises a jackcase structure **41** with a first locking pin **42**, a jacking yoke **43** with a second locking pin **44**, and a plurality of jacking cylinders **45** with a first end and second end, where the first end of the jacking cylinders **45** is supported by the jackcase structure **41**, and the second end of the jacking cylinders **45** by the jacking yoke **43**. The jacking system **40** operates in a push mechanism when raising the deck structure **10** out of the water and in a pull mechanism when retrieving the legs **20** to move to a new location. The first locking pin **42** holds the legs **20** when retracting the jacking cylinder, and the second locking pin **44** holds the legs **20** during jacking. In the position shown, the second locking pin **44** is engaged while the first locking pin **42** is disengaged. In this condition the weight of the deck structure **10** is carried by the hydraulic cylinders **45**.

[0006] In FIG 2, only one locking pin is visible at each elevation (at jackcase and at yoke) for simplicity of illustration. However, it is understood that several locking pins may be employed. Common systems will usually consist of two to four locking pins at each elevation, and in some cases a larger number of pins may be used. Likewise, the number of jacking cylinders can vary. In most instances, either one or two cylinders are employed for each locking pin position used.

[0007] The jacking system **40** shown in FIG 2 allows the deck structure **10** to be lifted as described below. In this description, the procedure is described using a single leg as shown in FIG 2. The jacking systems **40** at multiple legs would be coordinated when lifting to ensure even elevation of the deck structure **10**. Where differential leg positions occur, jacking would pause at each instance that any leg reaches a retraction position, so that the cylinders on the relevant leg can be retracted and the second locking pin is re-engaged before continuing with jacking on all legs.

[0008] Beginning with the arrangement shown in FIG 2, the second locking pin **44** is engaged and the weight of the deck structure **10** is supported by the hydraulic cylinders **45**. From this position, the hydraulic cylinders **45** would be extended until a lifting point **21** is

aligned with the first locking pin **42**. The first locking pin **42** can then be engaged and the load transferred to the first locking pin **42** such that the second locking pin **44** can be disengaged. With the second locking pin **44** disengaged, the hydraulic cylinders then retract the yoke **43** until the second locking pin **44** is aligned with a next lifting point **21**. The second locking pin **44** is then engaged and the load transferred back to the hydraulic cylinders **45** before disengaging the first locking pin **42**. The hydraulic cylinders **45** can then be extended to continue with the deck raising operation. This process is repeated until the desired deck elevation is reached.

**[0009]** Once the deck structure **10** has been elevated, there are two options to lock the deck structure **10** in position. If the seabed **S** is even and footings **30** have undergone equal penetration into the seabed **S**, the lifting points on each leg will be aligned, and the hull can be jacked up or down until a lifting point **21** is aligned with the first locking pin **42**. The first locking pin **42** can then be used to lock the platform in place and the load in the hydraulic cylinders **45** can be removed. In many cases, however, the seabed **S** is uneven and/or footings **30** of the platform will undergo different amounts of penetration into the seabed **S**. In this case, the lifting points **21** on the legs **20** across multiple legs will not align at a single elevation and so it is not possible to use the fixed pins **42** to support the deck structure **10**. In this case, the hydraulic cylinders **45** must continue to support the weight of the deck structure **10** while in place.

**[0010]** The second scenario described above may be acceptable for short term applications; however, in longer term applications, it is desirable to provide a more direct means of securing the leg-deck connection such that the hydraulic cylinders can be stored, and/or maintained, without needing to carry the weight of the deck structure **10**.

### **Summary of the Invention**

**[0011]** The present invention provides a self-elevating platform. In one embodiment, the self-elevating platform comprises a deck structure, a plurality of legs, a plurality of footings, and a jacking system, wherein the plurality of legs pass through the deck structure and are supported by the plurality of footings; and wherein the jacking system comprises a jackcase structure with a first locking pin, a jacking yoke with a second locking

pin, a plurality of jacking cylinders with a first end and second end, where the first end of the jacking cylinders is supported by the jackcase structure, and the second end of the jacking cylinders by the jacking yoke; and a fixation system comprising a plurality of tension rods, wherein each tension rod has a first end and a second end, and wherein the first end of the tension rods is securely coupled with the jacking yoke, and the second end of the tension rods is securely coupled with the deck structure; thereby when the plurality of tension rods secures the jacking yoke to the deck structure, the load can be removed from the hydraulic cylinders and transferred to the fixation system.

**[0012]** In another embodiment of the self-elevating platform, the first end of the tension rods is provided with a thread passing through an opening provided in the jacking yoke and secured using a first nut, and the second end of the tension rods is provided with a thread passing through an opening in the deck structure and secured using a second nut.

**[0013]** In another embodiment of the self-elevating platform, the first end of the tension rods is provided with a thread passing through an opening provided in the jacking yoke and secured using a first nut, and the second end of the tension rods is permanently fixed to the deck structure.

**[0014]** In another embodiment of the self-elevating platform, the first end of the tension rods is permanently fixed to the jacking yoke, and the second end of the tension rods is provided with a thread passing through an opening in the deck structure and secured using a second nut. In a further embodiment of the self-elevating platform, the hydraulic cylinders are repositioned to substantially align with the location of the tension rods.

**[0015]** The objectives and advantages of the claimed subject matter will become apparent from the following detailed description of preferred embodiments thereof in connection with the accompanying drawings.

### **Brief Description of the Drawings**

**[0016]** Preferred embodiments according to the present invention will now be described with reference to the Figures, in which like reference numerals denote like elements.

[0017] FIG 1 shows a block diagram of the basic arrangement of a self-elevating platform in the prior art.

[0018] FIG 2 shows a block diagram of the basic arrangement of a hydraulic jacking system in the prior art.

[0019] FIG 3 shows a block diagram of a hydraulic jacking system comprising a fixation system in accordance with one embodiment of the present invention.

[0020] FIG 4 shows a block diagram of a hydraulic jacking system comprising a fixation system in accordance with another embodiment of the present invention.

[0021] FIG 5 shows a block diagram of a hydraulic jacking system comprising a fixation system in accordance with yet another embodiment of the present invention.

[0022] FIG 6 shows a block diagram of a hydraulic jacking system comprising a fixation system in accordance with another embodiment of the present invention.

### **Detailed Description of the Invention**

[0023] The present invention may be understood more readily by reference to the following detailed description of certain embodiments of the invention.

[0024] Throughout this application, where publications are referenced, the disclosures of these publications are hereby incorporated by reference, in their entireties, into this application in order to more fully describe the state of art to which this invention pertains.

[0025] The present invention provides a fixation system for fixing the leg-deck structure connection for a self-elevating platform that utilizes a hydraulic jacking system. The fixation system comprises a plurality of adjustable tension rods that are so arranged to tie the jacking yoke to the deck in order to secure the yoke in position when the deck structure is elevated. In this way, a direct load path between the leg and deck structure is provided and the load can be released from the hydraulic cylinders in order for them to be maintained, or even removed for storage while the deck is elevated. This is desirable, particularly for cases where the platform is to remain at a single location for a period of several years.

[0026] Referring now to FIG 3, there is provided a fixation system in accordance with one embodiment of the present invention. As shown in FIG 3, the jacking system **40** is similar to that shown in FIG 2 except for the inclusion of a fixation system. The fixation system comprises a plurality of tension rods **51** securing the jacking yoke **43** to the deck structure **10**, where each tension rod **51** has a first end and a second end. The first end of the tension rods **51** is provided with a thread passing through an opening **52** provided in the jacking yoke **43** and secured using a first nut **53**, and the second end of the tension rods **51** is provided with a thread passing through an opening **54** in the deck structure **10** and secured using a second nut **55**. The tension rods **51** are provided with a sufficient length of thread such that various positions of the jacking yoke **43** can be accommodated. In general, the yoke position is allowed to vary by a distance at least equal to the distance between the lifting points **21**, thus allowing adjustment to any final leg position.

[0027] The fixation system shown in FIG 3 is able to be operated in the following way. During jacking operations, the tension rod **51**, the first nut **53**, and the second nut **55** can be removed and jacking can proceed as described in the description of FIG 2. When the hull reaches its final elevation, with the second locking pin **44** engaged, the tension rod **51**, the first nut **53**, and the second nut **55** can be moved into the position shown in FIG 3, for example by inserting the tension rod **51** through the decks structure **10** and the jacking yoke **43**, and then securing the tension rod **51** in position using the first and second nuts **53**, **55**. Once the tension rods **51** and nuts **53**, **55** are in position and sufficiently tightened to avoid slack, the load can be removed from the hydraulic cylinders **45** and transferred to the fixation system.

[0028] Referring now to FIG 4, there is provided a fixation system in accordance with another embodiment of the present invention. The fixation system shown in FIG 4 is similar to the fixation system shown in FIG 3 except that the second end of the tension rods **51** is permanently fixed to the deck structure **10** for example by welding. In this embodiment, jacking is carried out with the tension rods **51** in position, but with the nuts **53** removed, or moved to a higher position on the thread whereby it does not interfere with the movement of the jacking yoke **43**. This embodiment is convenient as it removes the need to lift the tension rods **51** into position and also removes the need to secure the second end of the tension rods **51** on location. The nut **53** can also be stored on the thread during jacking as long as it is moved to a location beyond the range of motion of the jacking yoke **43**, which removes the need to lift the nut **53** into position.

**[0029]** Referring now to FIG 5, there is provided a fixation system in accordance with yet another embodiment of the present invention. The fixation system shown in FIG 5 is similar to the fixation system shown in FIG 3 except that the first end of the tension rods **51** is permanently fixed to the jacking yoke **43** for example by welding. In this embodiment, jacking is carried out with the tension rods **51** in position, but with the nut **55** removed, or removed to a location on the thread whereby it does not come into contact with the deck structure **10** with the movement of the jacking yoke **43**. This embodiment is convenient as it removes the need to lift the tension rods **51** into position and also removes the need to secure the first end of the tension rods **51** on location. The nut **55** can also be stored on the thread during jacking as long as it is moved to a location which avoids contact with the deck structure **10** taking into account the range of motion of the jacking yoke **43**. This removes the need to lift the nut **55** into position. In contrast to the embodiment shown in FIG 4, this embodiment enables the nut **55** to be mounted under the deck structure **10**, where it can be better protected from the environment.

**[0030]** Referring now to FIG 6, there is provided a fixation system in accordance with another embodiment of the present invention. The fixation system shown in FIG 6 is similar to the fixation system shown in FIG 5 except that the hydraulic cylinders **45** are repositioned to substantially align with the location of the tension rods **51**. In this embodiment, the first end of the tension rods **51** is permanently fixed to the jacking yoke **43** for example by welding. In this embodiment, jacking is carried out with the tension rods **51** in position, but the nut **55** removed, or removed to a location on the thread whereby it does not come into contact with the deck structure **10** with the movement of the jacking yoke **43**. As in the case of the fixation system shown in FIG 5, this embodiment is convenient as it removes the need to lift the tension rods into position and also removes the need to secure the first end of the tension rods **51** on location. The nuts **55** can also be stored on the thread during jacking as long as it is moved to a location which avoids contact with the deck structure **10** taking into account the range of motion of the jacking yoke **43**. This removes the need to lift the nut **55** into position. In addition, the alignment of the hydraulic cylinders **45** and tension rods **51** enable more efficient design of the jacking yoke structure as the lifting and fixation locations can be arranged more favorably. It also allows for a more compact design as the hydraulic cylinders **45** and tension rods **51** occupy the same horizontal space on the yoke **43**, removing the need

for these to be spread out. This allows the system to be used on smaller diameter legs, and allows a greater number of lifting points to be accommodated if required.

[0031] There is a large range over which the present invention could be used; the parameters will vary however depending on the type of platform, water depth, etc. The following exemplary parameters are provided for the sole purpose of illustrating the application of the present invention.

[0032] Leg diameter – preferably to be 1.5m to 5m, with common size of about 3.5m.

[0033] Hydraulic cylinders – preferably to have lifting capacity of 200 to 800 metric tonnes (MT), with common capacity of about 500 MT.

[0034] Pin hole diameter – preferably range of 200mm to 600mm, with common size of about 350mm.

[0035] Pin hole spacing –preferably to be 0.6m to 2.5m, with common size of about 1.5m.

[0036] Jacking yoke – will be sized according to leg diameter and the load required.

[0037] Tension rods – preferably to be steel bars, with diameter of 60mm to 250mm.

[0038] Length of tension rods will be based on, pin hole spacing and the dimension of the yoke and main deck structures to make sure it is long enough.

[0039] While preferred embodiments of the present subject matter have been described, it is to be understood that the embodiments described are illustrative only and that the scope of the invention is to be defined solely by the appended claims when accorded a full range of equivalence, many variations and modifications naturally occurring to those of skill in the art from a perusal hereof.

CLAIMS

What is claimed is:

1. A self-elevating platform comprising:
  - a deck structure;
  - a plurality of legs having a plurality of evenly spaced pin holes;
  - a plurality of footings; and
  - a plurality of jacking systems, wherein one jacking system is disposed with one leg;wherein the plurality of legs pass through the deck structure and are supported by the plurality of footings; and
  - wherein the jacking system comprises:
    - a jackcase structure with a first removable locking pin, wherein the jackcase structure is fixed onto the deck structure;
    - a jacking yoke with a second removable locking pin;
    - a plurality of jacking cylinders with a first end and second end, where the first end of the jacking cylinders is supported by the jackcase structure, and the second end of the jacking cylinders by the jacking yoke;
  - wherein during retraction of a jacking process, the first removable locking pin is engaged with the jackcase structure so that load path is directly from the plurality of legs to the first removable locking pin and then to the jackcase structure; and
  - wherein during pushing of the jacking process, the second removable locking pin is engaged with the jacking yoke so that the load path is from the plurality of legs, through the second removable locking pin, to the jacking yoke, through the plurality of jacking cylinders and then into the jackcase structure;
  - and
  - a fixation system comprising a plurality of tension rods, wherein each tension rod has a first end and a second end, and wherein the first end of the tension rods is capable of being securely coupled with the jacking yoke, and the second end of the tension rods is capable of being securely coupled with the deck structure;thereby when the jacking process is stopped and the second removable locking pin is still engaged with the jacking yoke, and the plurality of tension rods secures the jacking yoke to the deck structure, the load path is from the plurality of legs, through the second removable

locking pin, to the jacking yoke, through the plurality of tension rods, and then into the deck structure.

2. The self-elevating platform of claim 1, wherein the first end of the tension rods is provided with a thread passing through an opening provided in the jacking yoke and secured using a first nut, and the second end of the tension rods is provided with a thread passing through an opening in the deck structure and secured using a second nut.

3. The self-elevating platform of claim 1, wherein the first end of the tension rods is provided with a thread passing through an opening provided in the jacking yoke and secured using a first nut, and the second end of the tension rods is permanently fixed to the deck structure.

4. The self-elevating platform of claim 1, wherein the first end of the tension rods is permanently fixed to the jacking yoke, and the second end of the tension rods is provided with a thread passing through an opening in the deck structure and secured using a second nut.

5. The self-elevating platform of claim 4, wherein the hydraulic cylinders are positioned to substantially align with the location of the tension rods.