

DESCRIPTION

SUPPORTING STRUCTURE OF FLOATING CHASSIS OF DISC APPARATUS

1. Field of the Invention

5 The present invention relates to a disc apparatus such as CD players, and more particularly to a floating chassis support mechanism suitable for a vehicle mount disc apparatus.

10 The present invention also relates to a vehicle mount disc reproduction apparatus in which a reproduction unit chassis is supported in a floating state by a main chassis with springs and dampers, and more particularly to a lock position of the reproduction unit chassis when a disk is unloaded or loaded.

15 2. Description of the Related Art

20 An example of the structure of a conventional floating chassis support mechanism for vehicle mount CD players will be described with reference to Figs. 11 to 13. A floating chassis 11 shown in Figs. 11 and 12 supports thereon a disc motor 7, a pickup 9, and a pickup transport mechanism. The floating chassis is supported in a floating state by a main chassis (not shown) by dampers 4, 4, 4 and unrepresented coil springs during disk reproducing. At least one of the dampers 4, 4, 4 is
25 disposed in a projection area of a disc during disk

reproducing.

In loading/unloading a disc 15, the floating chassis 11 is locked to the main chassis by an unrepresented lock mechanism, and the disc 15 is squeezed between a disk
5 guide 1 and a disc transport roller 2 and transported between a reproduction position and a disk insert port while the disk transport roller 2 rotates.

As the disc 15 is transported to the reproduction position, the transport roller 2 lowers and detaches from
10 the disc 15 and the lock mechanism releases a lock of the floating chassis 11. Thereafter, the disc 15 is clamped between a turntable 8 fixedly connected to a rotary shaft of the disc motor 7 and an unrepresented clasper and then it is rotated. The optical pickup 9 is fed along a disc
15 radial direction to reproduce information from the disc.

In the above-described conventional floating chassis support mechanism, since the damper 4 is disposed in the projection area of the disc 15, the depth from the upper surface of the disc 15 to the lower surface of the damper
20 4 is a total $T = H1 + H2 + H3$ as shown in Fig. 13, where H1 is a distance from the upper surface of the disc 15 to the upper surface of the floating chassis 11, H2 is a thickness of the floating chassis 11, and H3 is a thickness from the lower surface of the floating chassis
25 11 to the lower surface of the disc 15. Since the depth

from the upper surface of the disc 15 to the lower surface of the damper 4 is large, the total height of the apparatus becomes large.

5 Summary of the Invention

 The invention has been made under the above-described circumstances. It is therefore an object of the invention to provide a floating chassis support mechanism for disc apparatuses capable of thinning the
10 apparatus by reducing the necessary size from the upper surface of a loaded disc to the lower surface of a damper.

 It is another object of the invention to provide a vehicle mount disc reproduction apparatus having the
15 floating chassis support mechanism described above, capable of loading and unloading a disc with a short transport distance.

 In a floating chassis support mechanism for a disc apparatus of this invention for supporting a floating
20 chassis with springs and dampers vertically from the opposite side of a loaded disc, the dampers are disposed outside of a projection area of the disc, and an area of the floating chassis supported by the dampers is retracted toward the disk side more than a lower surface
25 of the disc.

In the floating chassis support mechanism, the damper is fitted in a tubular portion of a main chassis and a damper pusher is fitted in the main chassis to push a bottom surface of the damper and mount the damper on
5 the main chassis.

In the floating chassis support mechanism, the spring for supporting the floating chassis is fitted around an outer wall of the tubular portion of the main chassis, and engaged with a projection formed on the
10 tubular portion.

In a vehicle mount disc reproduction apparatus with the floating chassis support mechanism of this invention having a reproduction unit chassis supported in a floating state by a main chassis with springs and
15 dampers, the reproduction unit chassis is locked to the main chassis in a state shifted toward a disc insert port when a disk is loaded or unloaded.

BRIEF DESCRIPTION OF THE DRAWINGS

20 Fig. 1 is a plan view of a floating chassis support mechanism for vehicle mount CD players according to an embodiment of the invention.

Fig. 2 is a side view showing the outline structure of a vehicle mount CD player.

25 Fig. 3 is a cross sectional view taken along 3-3 in

Fig. 1.

Fig. 4 is a perspective view of a mount for damper of a main chassis of the vehicle mount CD player.

Fig. 5A is a plan view showing a mount for damper of a main chassis of the vehicle mount CD player, and Fig. 5B is an enlarged cross sectional view taken along 5B-5B in Fig. 5A.

Fig. 6 is a cross sectional view taken along 6-6 in Fig. 5A.

Fig. 7 is a broken view showing main parts of the vehicle mount CD player.

Fig. 8 is a plan view illustrating a reproduction state of a vehicle mount disc reproduction apparatus.

Fig. 9 is a plan view of the conventional vehicle mount disc reproduction apparatus when a disk is loaded or unloaded.

Fig. 10A is a plan view showing the outline structure of a vehicle mount disc reproduction apparatus according to an embodiment of the invention.

Figs. 10B to 10D are diagrams illustrating the outline of the operation of a lock of a vehicle mount disc reproduction apparatus of the invention.

Fig. 11 is a plan view showing an example of a conventional floating chassis support mechanism for vehicle mount CD players.

Fig. 12 is a side view showing the outline structure of the vehicle mount CD player.

Fig. 13 is a cross sectional view taken along 13-13 in Fig. 11.

5

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

A floating chassis support mechanism for vehicle mount CD players according to an embodiment of the invention will be described with reference to Figs. 1 to 7. A floating chassis 3 shown in Figs. 1 and 2 supports thereon a disc motor 7, a pickup 9, and a pickup transport mechanism. The floating chassis is supported in a floating state by a main chassis 10 shown in Figs. 10B to 10D by means of dampers 4, 4, 4 and coil springs 5 shown in Figs. 5 to 7 during disk reproducing. All the dampers 4, 4, 4 are disposed outside of a projection area of a disc during disk reproducing.

In loading/unloading a disc 15, the floating chassis 3 is locked to the main chassis by a lock mechanism (25, 21a shown in Figs. 10B to 10D), and the disc 15 is squeezed between a disk guide 1 and a disc transport roller 2 and transported between a reproduction position and a disk insert port while the disk transport roller 2 rotates.

As the disc 15 is transported to the reproduction

position, the transport roller 2 lowers and detaches from the disc 15 and the lock mechanism (25, 21a) releases a lock of the floating chassis 3. Thereafter, the disc 15 is clamped between a turntable 8 fixedly connected to a rotary shaft of the disc motor 7 and an unrepresented clamper and then it is rotated. The optical pickup 9 is fed along a disc radial direction to reproduce information from the disc.

Fig. 4 shows a mount of the damper 4, the mount being formed on the main chassis 10. As shown, the main chassis 10 is formed with a tubular portion 10a and a flange 10b integral with the tubular portion 10a. The tubular portion 10a is formed with projections 10d, 10d extending outward. The flange 10b is formed with three projections 10c, 10c, 10c. In Fig. 4, two projections 10c, 10c are shown.

Fig. 7 illustrates a disassembled state of the damper 4 and the coil spring 5. The damper 4 shown in Fig. 7 is an envelope made of elastic material such as rubber in which viscous fluid is hermetically filled, and has a recess 4a formed in the head thereof. A shaft 3a mounted upright on the floating chassis 3 is inserted into this recess 4a. The damper 4 is inserted into the main chassis 10 and fixed thereto with a damper pusher 6 fitted in the main chassis 10.

The damper pusher 6 is made of a plate spring and has three tongues bent from the bottom thereof, the tongues being formed with holes 6a, 6a, 6a. As shown in Fig. 5A, these holes 6a, 6a, 6a engage with the
5 projections 10c, 10c, 10c of the main chassis 10. The damper 4 can be mounted on the main chassis 10 with ease by inserting the damper 4 into the main chassis 10 and fitting the damper pusher 6 into the main chassis 10. Since the damper pusher 6 is made of a plate spring, the
10 mount area for the damper 4 can be made thin. The damper pusher 6 may be made of a resin mold.

The coil spring 5 is extended between the main chassis 10 and the floating chassis 3. As shown in Fig. 5B, the lower end of the coil spring 5 engages with a
15 projection 10d of the main chassis 10. Since the coil spring 5 can be temporarily engaged with the projection 10d, an assembly work becomes easy. Fig. 6 shows a mount state of the damper 4 and coil spring 5.

Fig. 3 shows the positional relationship between a
20 loaded disc 15 and the dampers 4. Since the dampers 4 are disposed outside of the projection area of the disc 15, the area of the floating chassis 3 supported by the dampers 4 can be set higher than the other area. Namely, the area of the floating chassis 3 in the projection area
25 of the disc 15 is set lower than the mount positions of

the dampers 4. As shown in Fig. 3, the depth from the upper surface of the disc 15 to the lower surface of the damper 4 is a total $t = h_2 + h_3$ where h_2 is a thickness of the floating chassis 3 and h_3 is a distance from the floating chassis 3 to the lower surface of the damper 4.

A distance h_1 from the upper surface of the disc 15 to the upper surface of the floating chassis 3 corresponds to H_1 of the conventional example shown in Fig. 13. The distance from the upper surface of the disc 15 to the lower surface of the damper 4 can be shortened by this distance h_1 . Accordingly, the apparatus can be thinned more than a conventional apparatus by the distance h_1 shown in Fig. 3.

According to 1DIN of the German Industrial Standards, a vehicle mount acoustic apparatus is housed in a space having a width of 180 mm and a height of 50 mm. The height of a vehicle mount CD player embodying the present invention was possible to be set to 25 mm, irrespective of a use of a large stroke damper for vehicle mount apparatuses.

According to the floating chassis support mechanism for disc apparatuses of this invention, a vehicle mount apparatus using a large stroke damper can be thinned. An assembly work of a damper mechanism such as dampers and coil springs becomes easy.

Of a disc reproduction apparatus with a floating chassis support mechanism of this invention, an example of a vehicle mount disc reproduction apparatus in which a reproduction unit chassis is supported in a floating
5 state by a main chassis with springs and dampers, will be described with reference to Figs. 8 and 9. Fig. 8 shows a reproduction state of a disc 29, and Fig. 9 shows a state that a disc 29 is loaded or unloaded.

A reproduction unit chassis 22 shown in Figs. 8 and
10 9 is used for supporting a pickup and a disc drive unit, and has a mechanism necessary for reproducing the disc 29. This reproduction unit chassis 22 is supported by a main chassis 21 with vibration damping mechanisms 28 each constituted of a damper 24 and a tension coil spring 23,
15 in order not to transmit external vibrations to the reproduction unit chassis 22.

Since the reproduction unit chassis 22 is supported in a floating state by the vibration damper mechanisms 28, it moves in four directions indicated by arrows in
20 Fig. 8, relative to the main chassis 21. In order to maintain a sufficient space of such a relative motion, the reproduction unit chassis 22 is disposed generally at the center of the space of the main chassis 21 in a natural state.

25 When the disc 29 is loaded or unloaded, the

reproduction unit chassis 22 is locked to the main chassis 21 by rotating lock arms 25, 25,... and engaging them with shafts 21a, 21a,... mounted upright on the main chassis 21, in order to correctly align the disc 29 with
5 a disc insert port 26, as shown in Fig. 9.

The lock arms 25, 25,... are rotatively supported by the reproduction unit chassis 22, and rotated by the lock mechanisms shown in Figs. 10B to 10D. In a reproduction state, the lock arms 25, 25,... are at positions spaced
10 from the shafts 21a, 21a,... as shown in Fig. 8. In a conventional vehicle mount disc reproduction apparatus, the reproduction unit chassis 22 is locked at the position same as that in the natural state during the reproduction.

15 In the above-described vehicle mount disc reproduction apparatus, the reproduction unit chassis 22 is locked at the position remote from the disc insert port 26 when the disc 29 is loaded or unloaded. Therefore, a motion distance of the disc 29 to the
20 reproduction position becomes long, and the disc 29 is required to be transported to the deeper position of the apparatus. It is therefore difficult to load the disk 29 by holding only its peripheral areas without touching the recording surface thereof. This may cause the disk 29 to
25 drop and be damaged or the recording surface may be

touched and stained. Therefore, data read errors may occur during disc reproduction.

Furthermore, since the projection amount of the disc 29 from the apparatus is small, it is difficult to unload
5 the disc 29 without touching the disc recording surface. This may cause the disk 29 to drop and be damaged or the recording surface may be touched and become dirty. Therefore, data read errors may occur during the next disc reproduction.

10 A vehicle mount disc reproduction apparatus improving the above points will be described with reference to Fig. 10A. Fig. 10A shows the outline structure of a vehicle mount disc reproduction apparatus according to an embodiment of the invention. In Fig.
15 10A, a reproduction unit chassis 22 indicated by solid lines shows a loading state or an unloading state, and that indicated by two-dot chain lines shows a reproduction state. Similar to the above example, the reproduction unit chassis 22 is used for supporting a
20 pickup and a disc drive unit, and has a mechanism necessary for reproducing the disc 29. This reproduction unit chassis 22 is supported by a main chassis 1 with vibration damping mechanisms 28 each constituted of a damper 24 and a tension coil spring 23, in order not to
25 transmit external vibrations to the reproduction unit

chassis 22.

The reproduction unit chassis 22 is disposed generally at the center of the space of the main chassis 21, as indicated by two-dot chain lines. When the disc 29 is loaded or unloaded, the reproduction unit chassis 22 is moved by the lock mechanisms shown in Figs. 10B to 10D to a disc insert port, and locked at the position near the disc insert port, as indicated by solid lines. For this lock, two lock arms 25 and two shafts 21a similar to the example shown in Figs. 8 and 9 are used.

An outline of the lock mechanism for the vehicle mount disc reproduction apparatus will be described with reference to Figs. 10B to 10D. Mounted on a reproduction unit chassis 101 are a first slider 103, an actuator 104, pinions 105 and 117, a shift 116, first to fifth gears 106 to 110, a rack 111, a second slider 112, and an arm 113. The pinions 105 and 117 are fixed to opposite ends of the shaft 116 and rotate synchronously. A power from the actuator 104 is transmitted via the first to fifth gears 101 to 110 to the rack 111 to move the second slider 112 in a direction A. As the second slider 112 moves, the pinion 105 rotate and this rotation force is transmitted via the shaft 116 to the first slider 103 which in turn moves in the direction A synchronously with the second slider 112. As the first and second sliders

103 and 112 moves in the direction A and enters grooves
of the first and second holders 114 and 115 mounted on a
main chassis 102, the reproduction unit chassis 101 is
pushed along a direction B and locked to the main
5 chassis.

According to the vehicle mount disc reproduction
apparatus of this invention, since the distance from the
reproduction unit chassis and disc insert port is short
when a disc is loaded, the disc can be loaded with ease
10 without touching the disc recording surface. Therefore,
the disc is prevented from being made dirty and data read
errors are prevented.

Furthermore, since the distance from the
reproduction unit chassis and disc insert port is short
15 when a disc is unloaded, the disc can be unloaded with
ease without touching the disc recording surface.

A different floating chassis support mechanism may
be used for the vehicle mount disc reproduction apparatus
shown in Figs. 8 to 10D, independently of the floating
20 chassis support mechanism shown in Figs. 1 to 7.

25



CLAIMS

1. A floating chassis support mechanism for a disc reproduction apparatus for supporting a floating chassis
5 (3) with springs (5) and dampers (4) vertically from a lower surface of a loaded disc (15), wherein the dampers are disposed outside of a projection area of the disc, and an area of the floating chassis supported by the dampers is set higher than the other area of the floating
10 chassis.
2. A floating chassis support mechanism according to claim 1, wherein the damper is fitted in a tubular portion (10a) of a main chassis (10) and a damper pusher
15 (6) is fitted in the main chassis to push a bottom surface of the damper and mount the damper on the main chassis.
3. A floating chassis support mechanism according to
20 claim 2, wherein the spring for supporting the floating chassis is fitted around an outer wall of the tubular portion of the main chassis, and engaged with a projection (10d) formed on the tubular portion.
- 25 4. A vehicle mount disc reproduction apparatus having a

This Sheet Has Been Replaced

THIS SHEET HAS BEEN
REPLACED



reproduction unit chassis (22) supported during
reproduction in a floating state by a main chassis (21)
with springs (23) and dampers (24), the dampers being
disposed outside of an area of a projection of a disc,
5 and an area of the floating chassis supported with the
dampers being set higher than the other area of the
floating chassis, wherein when the disc is loaded or
unloaded, the reproduction unit chassis is locked to the
main chassis in a state shifted toward a disc insert port
10 (26).

5. A floating chassis support mechanism according to
claim 1, wherein a thickness of the mechanism corresponds
to a depth from an upper surface of the disc to a lower
15 surface of the damper which is a sum of a thickness (h2)
of the floating chassis and a distance (h3) from a lower
surface of the floating chassis to the lower surface of
the damper.

20 6. A floating chassis support mechanism according to
claim 1, wherein the damper is made of an elastic
envelope in which viscous fluid is hermetically filled.

7. A floating chassis support mechanism according to
25 claim 1, wherein the damper has a recess (4a) formed in





an upper region thereof, and a shaft (3a) mounted on the floating chassis (3) is inserted into the recess to mount the damper on the floating chassis.

- 5 8. A floating chassis support mechanism according to claim 1, wherein the spring is a coil spring fitted around the damper.
9. A floating chassis support mechanism according to
10 claim 2, wherein the damper pusher is a plate spring.
10. A floating chassis support mechanism according to claim 2, wherein said damper pusher is a molded product made of a resin material.
- 15
11. A floating chassis support mechanism according to claim 2, wherein the damper pusher has tongues (6a) with holes into which projections (10c) mounted on the main chassis are inserted to fix the damper pusher to the main
20 chassis.
12. A floating chassis support mechanism according to claim 2, wherein the tubular portion has a height covering generally a half height of the damper from the
25 bottom, the remaining height of the damper projecting out

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED



of the tubular portion.

13. A floating chassis support mechanism according to claim 12, wherein the spring surrounds the damper at the
5 remaining height.

14. A vehicle mount disc reproduction apparatus according to claim 4, wherein the reproduction unit chassis includes a lock member (25), the lock member is
10 locked to a shaft (21a) mounted on the main chassis to set the reproduction unit chassis to a shifted position toward the disc insert port, when the disc is loaded or unloaded.

15 15. A vehicle mount disc reproduction apparatus according to claim 4, wherein the spring and the damper constitute a vibration attenuation mechanism (28) for suppressing vibrations from being transmitted to the reproduction unit chassis.

20

16. A vehicle mount disc reproduction apparatus having a reproduction unit chassis (22) supported in a floating state by a main chassis (21) with springs (23) and dampers (24), wherein the reproduction unit chassis is
25 locked to the main chassis at a shifted position toward a



THIS SHEET HAS BEEN
REPLACED



disc insert port (26) when a disc is loaded or unloaded.

5

10

15

20

25

THIS SHEET HAS BEEN
REPLACED

FIG. 1






FIG. 2**FIG. 3**





FIG. 4**FIG. 5A****FIG. 5B****FIG. 6**

FIG. 7






FIG. 8**FIG. 9**


FIG. 10A

FIG. 10B




FIG. 10C




FIG. 10D





FIG. 11

FIG. 12





FIG. 13





CLAIMS

1. A floating chassis support mechanism for a disc reproduction apparatus for supporting a floating chassis (3) with springs (5) and dampers (4) vertically from a lower surface of a loaded disc (15), wherein the dampers are disposed outside of a projection area of the disc, and an area of the floating chassis supported by the dampers is provided in a direction where the supported area from a damper holding portion of a main chassis (10) is away from the lower surface of the disc.
2. A floating chassis support mechanism according to claim 1, wherein the damper is fitted in a tubular portion (10a) of the main chassis (10) and a damper pusher (6) is fitted in the main chassis to push a bottom surface of the damper and mount the damper on the main chassis.
3. A floating chassis support mechanism according to claim 2, wherein the spring for supporting the floating chassis is fitted around an outer wall of the tubular portion of the main chassis, and engaged with a projection (10d) formed on the tubular portion.
4. A vehicle mount disc reproduction apparatus having a





reproduction unit chassis (22) supported during
reproduction in a floating state by a main chassis (21)
with springs (23) and dampers (24), the dampers being
disposed outside of an area of a projection of a disc,
5 and an area of the floating chassis supported with the
dampers being set higher than the other area of the
floating chassis, wherein when the disc is loaded or
unloaded, the reproduction unit chassis is locked to the
main chassis in a state shifted toward a disc insert port
10 (26).

5. A floating chassis support mechanism according to
claim 1, wherein a thickness of the mechanism corresponds
to a depth from an upper surface of the disc to a lower
15 surface of the damper which is a sum of a thickness (h2)
of the floating chassis and a distance (h3) from a lower
surface of the floating chassis to the lower surface of
the damper.

20 6. A floating chassis support mechanism according to
claim 1, wherein the damper is made of an elastic
envelope in which viscous fluid is hermetically filled.

7. A floating chassis support mechanism according to
25 claim 1, wherein the damper has a recess (4a) formed in





an upper region thereof, and a shaft (3a) mounted on the floating chassis (3) is inserted into the recess to mount the damper on the floating chassis.

5 8. A floating chassis support mechanism according to claim 1, wherein the spring is a coil spring fitted around the damper.

9. A floating chassis support mechanism according to
10 claim 2, wherein the damper pusher is a plate spring.

10. A floating chassis support mechanism according to claim 2, wherein said damper pusher is a molded product made of a resin material.

15

11. A floating chassis support mechanism according to claim 2, wherein the damper pusher has tongues (6a) with holes into which projections (10c) mounted on the main chassis are inserted to fix the damper pusher to the main
20 chassis.

12. A floating chassis support mechanism according to claim 2, wherein the tubular portion has a height covering generally a half height of the damper from the
25 bottom, the remaining height of the damper projecting out

This Sheet Has Been Replaced



AMENDED SHEET

THIS SHEET HAS BEEN
REPLACED



of the tubular portion.

13. A floating chassis support mechanism according to claim 12, wherein the spring surrounds the damper at the remaining height.

14. A vehicle mount disc reproduction apparatus according to claim 4, wherein the reproduction unit chassis includes a lock member (25), the lock member is locked to a shaft (21a) mounted on the main chassis to set the reproduction unit chassis to a shifted position toward the disc insert port, when the disc is loaded or unloaded.

15. A vehicle mount disc reproduction apparatus according to claim 4, wherein the spring and the damper constitute a vibration attenuation mechanism (28) for suppressing vibrations from being transmitted to the reproduction unit chassis.

16. A vehicle mount disc reproduction apparatus having a reproduction unit chassis (22) supported in a floating state by a main chassis (21) with springs (23) and dampers (24), wherein the reproduction unit chassis is locked to the main chassis at a shifted position toward a



disc insert port (26) when a disc is loaded or unloaded.



5

10

15

20

25

19

AMENDED SHEET

THIS SHEET HAS BEEN
REPLACED

05 FEB 2002



CLAIMS

1. A floating chassis support mechanism for a disc reproduction apparatus for supporting a floating chassis (3) with springs (5) and dampers (4) vertically from a lower surface of a loaded disc (15), wherein the dampers (4) are disposed outside of a projection area of the disc (15), and an area of the floating chassis (3) supported by the dampers (4) is set higher than the other area of the floating chassis (3),

characterized in that

an upper surface of said damper supported area of said floating chassis (3) is set higher than a lower surface of said disc (15).

2. The floating chassis support mechanism according to claim 1, wherein a thickness of the mechanism corresponding to a depth (t) from an upper surface of the disc (15) to a lower surface of the damper (4) is a sum of a thickness (h_2) of the floating chassis (3) and a distance (h_3) from a lower surface of the floating chassis (3) to the lower surface of the damper (4).

3. The floating chassis support mechanism according to claim 1 or 2, wherein the damper (4) is fitted in a tubular portion (10a) of a main chassis (10) and a damper pusher (6) is fitted in the main chassis (10) to push a bottom surface of the damper (4) and mount the damper (4) on the main chassis (10).

4. The floating chassis support mechanism according to claim 3, wherein the spring (5) for supporting the floating chassis (3) is fitted around an outer wall of the tubular portion (10a) of the main chassis (10), and engaged with a projection (10d) formed on the tubular portion (10a).



05 FEB 2002

5. A floating chassis support mechanism according to claim 3 or 4, wherein the damper pusher (6) is a plate spring.
6. The floating chassis support mechanism according to claim 3 or 4, wherein said damper pusher (6) is a molded product made of a resin material.
7. The floating chassis support mechanism according to any of claims 3 to 6, wherein the damper pusher (6) has tongues (6a) with holes into which projections (10c) mounted on the main chassis (10) are inserted to fix the damper pusher (6) to the main chassis (10).
8. The floating chassis support mechanism according to any of claims 3 to 7, wherein the tubular portion (10a) has a height covering generally a half height of the damper (4) from the bottom, the remaining height of the damper (4) projecting out of the tubular portion (10a).
9. The floating chassis support mechanism according to claim 8, wherein the spring surrounds the damper at the remaining height.
10. The floating chassis support mechanism according to any preceding claim, wherein the damper (4) is made of an elastic envelope in which viscous fluid is hermetically filled.
11. The floating chassis support mechanism according to any preceding claim, wherein the damper (4) has a recess (4a) formed in an upper region thereof, and a shaft (3a) mounted on the floating chassis (3) is inserted into the recess to mount the damper (4) on the floating chassis (3).
12. The floating chassis support mechanism according to any preceding claim, wherein the spring (5) is a coil spring fitted around the damper (4).
13. The floating chassis support mechanism according to any preceding claim, wherein when the disc (29) is loaded or unloaded, the floating chassis (22) is locked to a main chassis (21) in a state shifted toward a disc insert port (26).



05 FEB 2002

14. The floating chassis support mechanism according to claim 13, wherein the floating chassis (22) includes a lock member (25), the lock member (25) is locked to a shaft (21a) mounted on the main chassis (21) to set the floating chassis (22) to a shifted position toward the disc insert port (26), when the disc (29) is loaded or unloaded.

15. The floating chassis support mechanism according to any preceding claim, wherein the spring (5; 23) and the damper (4; 24) constitute a vibration attenuation mechanism (28) for suppressing vibrations from being transmitted to the floating chassis (3; 22).

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G11B 33/08, B60R 11/02	A1	(11) International Publication Number: WO 99/10889 (43) International Publication Date: 4 March 1999 (04.03.99)
(21) International Application Number: PCT/JP98/03550 (22) International Filing Date: 10 August 1998 (10.08.98) (30) Priority Data: 9/242152 22 August 1997 (22.08.97) JP 9/250070 29 August 1997 (29.08.97) JP (71) Applicant (for all designated States except US): KABUSHIKI KAISHA KENWOOD [JP/JP]; 14-6, Dougenzaka 1-chome, Shibuya-ku, Tokyo 150-0043 (JP). (72) Inventors; and (75) Inventors/Applicants (for US only): IMAI, Tsutomu [JP/JP]; 4-3-5-8, Nogami-cyo, Ohme-shi, Tokyo 198-0032 (JP). HAGA, Yosuke [JP/JP]; 663-1, Bessho-cyo, Ohmiya-shi, Saitama 331-0041 (JP). SASADA, Takeharu [JP/JP]; Room A101, 860, Yokokawa-cyo, Hachioji-shi, Tokyo 193-0823 (JP). MASUDA, Shinji [JP/JP]; 384, Shimoda, Hino-shi, Tokyo 191-0023 (JP). ONO, Atsumi [JP/JP]; Room 202, 3-16-2, Minami Ohsawa, Hachioji-shi, Tokyo 192-0364 (JP). MURAKAMI, Midori [JP/JP]; 5-28-16, Honda, Kokubunji-shi, Tokyo 185-0011 (JP). (74) Agents: OKABE, Masao et al.; No.602 Fuji Building, 2-3, Marunouchi 3-chome, Chiyoda-ku, Tokyo 100-0005 (JP).		(81) Designated States: CN, ID, KR, SG, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(54) Title: SUPPORTING STRUCTURE OF FLOATING CHASSIS OF DISC APPARATUS (57) Abstract A floating chassis support mechanism is provided which can thin a disc reproduction apparatus. In the floating chassis support mechanism for a disc reproduction apparatus for supporting a floating chassis (3) with springs and dampers (4) vertically from the opposite side of a loaded disc (15), the damper (4) is disposed outside of a projection area of the disc, and an area of the floating chassis (3) supported by the dampers (4) is retracted toward the disc side more than a lower surface of the disc (15). 