

9901348-4
190515



PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : C11D 7/08, 7/18, 7/38	A1	(11) International Publication Number: WO 98/11191 (43) International Publication Date: 19 March 1998 (19.03.98)
(21) International Application Number: PCT/US97/16380 (22) International Filing Date: 10 September 1997 (10.09.97) (30) Priority Data: ① 96870117.7 13 September 1996 (13.09.96) EP (34) Countries for which the regional or international application was filed: BE et al. (71) Applicant (for all designated States except US): THE PROCTER & GAMBLE COMPANY [US/US]; One Procter & Gamble Plaza, Cincinnati, OH 45202 (US). (72) Inventors; and ① (75) Inventors/Applicants (for US only): SCIALLA, Stefano [IT/IT]; Via F.B. Rastrelli, 81, I-00128 Rome (IT); MASOTTI, Valentina [IT/IT]; Via Pertini, 5, I-40033 Casalecchio di Reno (IT). (74) Agents: REED, T., David et al.; The Procter & Gamble Company, 5299 Spring Grove Avenue, Cincinnati, OH 45217 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.
(54) Title: PEROXYGEN BLEACHING COMPOSITIONS COMPRISING PEROXYGEN BLEACH AND ATMP, SUITABLE FOR USE AS A PRETREATER FOR FABRICS (57) Abstract The present invention relates to aqueous, acidic compositions comprising a peroxygen bleach and ATMP. The present invention further encompasses a process for pretreating soiled fabrics whereby the loss of tensile strength in said fabric is reduced and the color/dye damage of said fabric is reduced.		