

- 1 -

Attorney Docket 01997/175W01

A FACE RECOGNITION SYSTEMBackground of the Invention

The invention relates to a system for identifying
 5 members of a viewing audience.

For a commercial television network, the cost of
 its advertising time depends critically on the popularity
 of its programs among the television viewing audience.
 Popularity, in this case, is typically measured in terms
 10 of the program's share of the total audience viewing
 television at the time the program airs. As a general
 rule of thumb, advertisers prefer to place their
 advertisements where they will reach the greatest number
 of people. Thus, there is a higher demand among
 15 commercial advertisers for advertising time slots along
 side more popular programs. Such time slots can also
 demand a higher price.

Because the economics of television advertising
 depends so critically on the tastes and preferences of
 20 the television audience, the television industry invests
 a substantial amount of time, effort and money in
 measuring those tastes and preferences. One preferred
 approach involves monitoring the actual viewing habits of
 a group of volunteer families which represent a cross-
 25 section of all people who watch television. Typically,
 the participants in such a study allow monitoring
 equipment to be placed in their homes. Whenever a
 participant watches a television program, the monitoring
 equipment records the time, the identity of the program
 30 and the identity of the members of the viewing audience.
 Many of these systems require active participation by the
 television viewer to obtain the monitoring information.
 That is, the viewer must in some way interact with the
 equipment to record his presence in the viewing audience.
 35 If the viewer forgets to record his presence the

This Sheet Has Been Replaced



REPLACED SHEETS		SG
☒	Description	: paged 1 to 10 to paged 10 to 10
☒	Claim(s)	: paged 1 to 10 to paged 10 to 10
☐	Drawing(s)	: paged 1 to 10 to paged 10 to 10
☐	Abstract	: paged 1 to 10 to paged 10 to 10
DATE OF RECEIPT		

monitoring statistics will be incomplete. In general, the less manual intervention required by the television viewer, the more likely it is that the gathered statistics on viewing habits will be complete and error free.

5 Systems have been developed which automatically identify members of the viewing audience without requiring the viewer to enter any information. For example, U.S. 4,858,000 to Daozehng Lu, issued August 15, 10 1989 describes such a system. In the system, a scanner using infrared detectors locates a member of the viewing audience, captures an image of the located member, extracts a pattern signature for the captured image and then compares the extracted pattern signature to a set of 15 stored pattern image signatures to identify the audience member.

Summary of the Invention

In general, in one aspect, the invention is a recognition system for identifying members of an audience. The invention includes an imaging system which 20 generates an image of the audience; a selector module for selecting a portion of the generated image; a detection means which analyzes the selected image portion to determine whether an image of a person is present; and a 25 recognition module for determining whether a detected image of a person resembles one of a reference set of images of individuals.

Preferred embodiments include the following features. The recognition module also determines which 30 one, if any, of the individuals in the reference set the detected image resembles. The selection means includes a motion detector for identifying the selected portion of the image by detecting motion and it includes a locator module for locating the portion of the image



corresponding to the face of the person detected. In the recognition system, the detection means and the recognition module employ a first and second pattern recognition techniques, respectively, to determine
5 whether an image of a person is present in the selected portion of the image and both pattern recognition techniques employ a set of eigenvectors in a multi-dimensional image space to characterize the reference set. In addition, the second pattern recognition
10 technique also represents each member of the reference set as a point in a subspace defined by the set of eigenvectors. Also, the image of a person is an image of a person's face and the reference set includes images of faces of the individuals.

15 Also in preferred embodiments, the recognition system includes means for representing the reference set as a set of eigenvectors in a multi-dimensional image space and the detection means includes means for representing the selected image portion as an input
20 vector in the multi-dimensional image space and means for computing the distance between a point identified by the input vector and a subspace defined by the set of eigenvectors. The detection means also includes a thresholding means for determining whether an image of a
25 person is present by comparing the computed distance to a preselected threshold. The recognition module includes means for representing each member of the reference set as a corresponding point in the subspace. To determine the location of each point in subspace associated with a
30 corresponding member of the reference set, a vector associated with that member is projected onto the subspace.

The recognition module also includes means for projecting the input vector onto the subspace, means for
35 selecting a particular member of the reference set, and



means for computing a distance within the subspace between a point identified by the projection of the input vector onto the subspace and the point in the subspace associated with the selected member.

5 In general, in another aspect, the invention is a method for identifying members of an audience. The invention includes the steps of generating an image of the audience; selecting a portion of the generated image; analyzing the selected image portion to determine whether
10 an image of a person is present; and if an image of a person is determined to be present, determining whether the image of a person resembles one of a reference set of images of individuals.

One advantage of the invention is that it is fast,
15 relatively simple and works well in a constrained environment, i.e., an environment for which the associated image remains relatively constant except for the coming and going of people. In addition, the invention determine whether a selected portion of an
20 image actually contains an image of a face. If it is determined that the selected image portion contains an image of a face, the invention then determine which one of a reference set of known faces the detected face image most resembles. If the detected face image is not
25 present among the reference set, the invention reports the presence of a unknown person in the audience. The invention has the ability to discriminate face images from images of other objects.

Other advantages and features will become apparent
30 from the following description of the preferred embodiment and from the claims.

Description of the Preferred Embodiment

Fig. 1 is a block diagram of a face recognition system;



Fig. 2 is a flow diagram of an initialization procedure for the face recognition module;

Fig. 3 is a flow diagram of the operation of the face recognition module; and

5 Fig. 4 is a block diagram of a motion detection system for locating faces within a sequence of images.

Structure and Operation

Referring to Fig. 1, in an audience monitoring system 2, a video camera 4, which is trained on an area
10 where members of a viewing audience generally sit to watch the TV, sends a sequence of video image frames to a motion detection module 6. Video camera 4, which may, for example, be installed in the home of a family that has volunteered to participate in a study of public
15 viewing habits, generates images of TV viewing audience. Motion detection module 6 processes the sequence of image frames to identify regions of the recorded scene that contain motion, and thus may be evidence of the presence of a person watching TV. In general, motion detection
20 module 6 accomplishes this by comparing successive frames of the image sequence so as to find those locations containing image data that changes over time. Since the image background (i.e., images of the furniture and other objects in the room) will usually remain unchanged from
25 frame to frame, the areas of movement will generally be evidence of the presence of a person in the viewing audience.

When movement is identified, a head locator module 8 selects a block of the image frame containing the
30 movement and sends it to a face recognition module 10 where it is analyzed for the presence of recognizable faces. Face recognition module 10 performs two functions. First, it determines whether the image data within the selected block resembles a face. Then, if it



does resemble a face, module 10 determines whether the face is one of a reference set of faces. The reference set may include, for example, the images of faces of all members of the family in whose house the audience
5 monitoring system has been installed.

To perform its recognition functions, face recognizer 10 employs a multi-dimensional representation in which face images are characterized by a set of eigenvectors or "eigenfaces". In general, according to
10 this technique, each image is represented as a vector (or a point) in very high dimensional image space in which each pixel of the image is represented by a corresponding dimension or axis. The dimension of this image space thus depends upon the size of the image being represented
15 and can become very large for any reasonably sized image. For example, if the block of image data is N pixels by N pixels, then the multi-dimensional image space has dimension N^2 . The image vector which represents the $N \times N$ block of image data in this multi-dimensional image space
20 is constructed by simply concatenating the rows of the image data to generate a vector of length N^2 .

Face images, like all other possible images, are represented by points within this multi-dimensional image space. The distribution of faces, however, tends to be
25 grouped within a region of the image space. Thus, the distribution of faces of the reference set can be characterized by using principal component analysis. The resulting principal components of the distribution of faces, or the eigenvectors of the covariance matrix of
30 the set of face images, defines the variation among the set of face images. These eigenvectors are typically ordered, each one accounting for a different amount of variation among the face images. They can be thought of as a set of features which together characterize the
35 variation between face images within the reference set.

Each face image location within the multi-dimensional image space contributes more or less to each eigenvector, so that each eigenvector represents a sort of ghostly face which is referred to herein as an eigenface.

5 Each individual face from the reference set can be represented exactly in terms of a linear combination of M non-zero eigenfaces. Each face can also be approximated using only the M' "best" faces, i.e., those that have the largest eigenvalues, and which therefore account for the
10 most variance within the set of face images. The best M' eigenfaces span an M' -dimensional subspace (referred to hereinafter as "face space") of all possible images.

 This approach to face recognition involves the initialization operations shown in Fig. 2 to "train"
15 recognition module 10. First, a reference set of face images is obtained and each of the faces of that set is represented as a corresponding vector or point in the multi-dimensional image space (step 100). Then, using principal component analysis, the distribution of points
20 for the reference set of faces is characterized in terms of a set of eigenvectors (or eigenfaces) (step 102). If a full characterization of the distribution of points is performed, it will yield N^2 eigenfaces of which M are non-zero. Of these, only the M' eigenfaces corresponding
25 to the highest eigenvalues are chosen, where $M' < M \ll N^2$. This subset of eigenfaces is used to define a subspace (or face space) within the multidimensional image space. Finally, each member of the reference set is represented by a corresponding point within face space
30 (step 104). For a given face, this is accomplished by projecting its point in the higher dimensional image space onto face space.

 If additional faces are added to the reference set at a later time, these operations are repeated to update
35 the set of eigenfaces characterizing the reference set.

After face recognition module 10 is initialized, it implements the steps shown in Fig. 3 to recognize face images supplied by face locator module 8. First, face recognition module 10 projects the input image (i.e., the image presumed to contain a face) onto face space by projecting it onto each of the M' eigenfaces (step 200). Then, module 10 determines whether the input image is a face at all (whether known or unknown) by checking to see if the image is sufficiently close to "face space" (step 202). That is, module 10 computes how far the input image in the multi-dimensional image space is from the face space and compares this to a preselected threshold. If the computed distance is greater than the preselected threshold, module 10 indicates that it does not represent a face image and motion detection module 6 locates the next block of the overall image which may contain a face image.

If the computed distance is sufficiently close to face space (i.e., less than the preselected threshold), recognition module 10 treats it as a face image and proceeds with determining whose face it is (step 206). This involves computing distances between the projection of the input image onto face space and each of the reference face images in face space. If the projected input image is sufficiently close to any one of the reference faces (i.e., the computed distance in face space is less than a predetermined distance), recognition module 10 identifies the input image as belonging to the individual associated with that reference face. If the projected input image is not sufficiently close to any one of the reference faces, recognition module 10 reports that a person has been located but the identity of the person is unknown.

The mathematics underlying each of these steps will now be described in greater detail.

Calculating Eigenfaces

Let a face image $I(x,y)$ be a two-dimensional N by N array of (8-bit) intensity values. The face image is represented in the multi-dimensional image space as a vector of dimension N^2 . Thus, a typical image of size 256 by 256 becomes a vector of dimension 65,536, or, equivalently, a point in 65,536-dimensional image space. An ensemble of images, then, maps to a collection of points in this huge space.

Images of faces, being similar in overall configuration, are not randomly distributed in this huge image space and thus can be described by a relatively low dimensional subspace. Using principal component analysis, one identifies the vectors which best account for the distribution of face images within the entire image space. These vectors, namely, the "eigenfaces", define the "face space". Each vector is of length N^2 , describes an N by N image, and is a linear combination of the original face images of the reference set.

Let the training set of face images be $\Gamma_1, \Gamma_2, \Gamma_3, \dots, \Gamma_M$. The average face of the set is defined by

$$\Psi = (M)^{-1} \sum_n \Gamma_n, \quad (1)$$

where the summation is from $n = 1$ to M . Each face differs from the average by the vector $\Phi_i = \Gamma_i - \Psi$. This set of very large vectors is then subject to principal component analysis, which seeks a set of M orthonormal vectors, u_n , which best describes the distribution of the data. The k th vector, u_k , is chosen such that:

$$\lambda_k = (M)^{-1} \sum_n (u_k^T \Phi_n)^2 \quad (2)$$

is a maximum, subject to:

$$u_l^T u_k = \delta_{lk} = \begin{cases} 1, & \text{if } l = k \\ 0, & \text{otherwise} \end{cases} \quad (3)$$

The vectors u_k and scalars λ_k are the eigenvectors and eigenvalues, respectively, of the covariance matrix

$$C = (M)^{-1} \sum_n \phi_n \phi_n^T \quad (4)$$

$$= AA^T$$

5 where the matrix $A = [\phi_1 \ \phi_2 \ \dots \ \phi_M]$. The matrix C , however, is N^2 by N^2 , and determining the N^2 eigenvectors and eigenvalues can become an intractable task for typical image sizes.

If the number of data points in the face space is
10 less than the dimension of the overall image space (namely, if, $M < N^2$), there will be only $M - 1$, rather than N^2 , meaningful eigenvectors. (The remaining eigenvectors will have associated eigenvalues of zero.) One can solve for the N^2 -dimensional eigenvectors in this
15 case by first solving for the eigenvectors of an M by M matrix - e.g. solving a 16×16 matrix rather than a $16,384$ by $16,384$ matrix - and then taking appropriate linear combinations of the face images ϕ_i . Consider the eigenvectors v_i of $A^T A$ such that:

$$20 \quad A^T A v_i = \mu_i v_i \quad (5)$$

Premultiplying both sides by A , yields:

$$AA^T A v_i = \mu_i A v_i \quad (6)$$

from which it is apparent that $A v_i$ are the eigenvectors of

$$25 \quad C = AA^T.$$

Following this analysis, it is possible to construct the M by M matrix $L = A^T A$, where $L_{mn} = \phi_n^T \phi_m$, and find the M eigenvectors, v_i , of L . These vectors determine linear combinations of the M training set face
30 images to form the eigenfaces u_i :

$$u_i = \sum_{k=1}^M v_{ik} \phi_k, \quad i = 1, \dots, M. \quad (7)$$

With this analysis the calculations are greatly reduced, from the order of the number of pixels in the images (N^2) to the order of the number of images in the training set (M). In practice, the training set of face images will be relatively small ($M \ll N^2$), and the calculations become quite manageable. The associated eigenvalues provide a basis for ranking the eigenvectors according to their usefulness in characterizing the variation among the images.

In practice, a smaller M' is sufficient for identification, since accurate construction of the image is not a requirement. In this framework, identification becomes a pattern recognition task. The eigenfaces span an M' -dimensional subspace of the original N^2 image space. The M' significant eigenvectors of the L matrix are chosen as those with the largest associated eigenvalues. In test cases based upon $M=16$ face images, $M'=7$ eigenfaces were found to yield acceptable results, i.e., a level of accuracy sufficient for monitoring a TV audience for purposes of studying viewing habits and tastes.

A new face image (Γ) is transformed into its eigenface components (i.e., projected into "face space") by a simple operation,

$$w_k = u_k^T (\Gamma - \Psi), \quad (8)$$

for $k = 1, \dots, M'$. This describes a set of point-by-point image multiplications and summations, operations which may be performed at approximately frame rate on current image processing hardware.

The weights form a vector $\Omega^T = [w_1 w_2 \dots w_{M'}]$ that describes the contribution of each eigenface in representing the input face image, treating the eigenfaces as a basis set for face images. The vector may then be used in a standard pattern recognition algorithm to find which of a number of pre-defined face

classes, if any, best describes the face. The simplest method for determining which face class provides the best description of an input face image is to find the face class k that minimizes the Euclidian distance

5 $\epsilon_k = \|(\Omega - \Omega_k)\|^2, \quad (9)$

where Ω_k is a vector describing the k th face class. The face classes Ω_i are calculated by averaging the results of the eigenface representation over a small number of face images (as few as one) of each individual. A face
10 is classified as belonging to class k when the minimum ϵ_k is below some chosen threshold ϵ_0 . Otherwise the face is classified as "unknown", and optionally used to create a new face class.

Because creating the vector of weights is
15 equivalent to projecting the original face image onto the low-dimensional face space, many images (most of them looking nothing like a face) will project onto a given pattern vector. This is not a problem for the system, however, since the distance ϵ between the image and the
20 face space is simply the squared distance between the mean-adjusted input image $\Phi = \Gamma - \Psi$ and $\Phi_f = \sum \omega_k u_k$, its projection onto face space (where the summation is over k from 1 to M'):

$\epsilon^2 = \|\Phi - \Phi_f\|^2 \quad (10)$

25 Thus, there are four possibilities for an input image and its pattern vector: (1) near face space and near a face class; (2) near face space but not near a known face class; (3) distant from face space and near a face class; and (4) distant from face space and not near a known face
30 class.

In the first case, an individual is recognized and identified. In the second case, an unknown individual is present. The last two cases indicate that the image is not a face image. Case three typically shows up as a
35 false positive in most other recognition systems. In the

described embodiment, however, the false recognition may be detected because of the significant distance between the image and the subspace of expected face images.

Summary of Eigenface Recognition Procedure

5 To summarize, the eigenfaces approach to face recognition involves the following steps:

- 10 1. Collect a set of characteristic face images of the known individuals. This set may include a number of images for each person, with some variation in expression and in lighting. (Say four images of ten people, so $M = 40$.)
- 15 2. Calculate the (40×40) matrix L , find its eigenvectors and eigenvalues, and choose the M' eigenvectors with the highest associated eigenvalues. (Let $M' = 10$ in this example.)
3. Combine the normalized training set of images according to Eq. 7 to produce the $(M' = 10)$ eigenfaces u_k .
- 20 4. For each known individual, calculate the class vector Ω_k by averaging the eigenface pattern vectors Ω (from Eq. 9) calculated from the original (four) images of the individual. Choose a threshold θ_g which
25 defines the maximum allowable distance from any face class, and a threshold θ_f which defines the maximum allowable distance from face space (according to Eq. 10).

5. For each new face image to be identified, calculate its pattern vector Ω , the distances ϵ_i to each known class, and the distance ϵ to face space. If the distance $\epsilon > \theta_t$, classify the input image as not a face. If the minimum distance $\epsilon_k \leq \theta_a$ and the distance $\epsilon \leq \theta_t$, classify the input face as the individual associated with class vector Ω_k . If the minimum distance $\epsilon_k > \theta_a$ and $\epsilon \leq \theta_t$, then the image may be classified as "unknown", and optionally used to begin a new face class.
6. If the new image is classified as a known individual, this image may be added to the original set of familiar face images, and the eigenfaces may be recalculated (steps 1 - 4). This gives the opportunity to modify the face space as the system encounters more instances of known faces.

In the described embodiment, calculation of the eigenfaces is done offline as part of the training. The recognition currently takes about 400 msec running rather inefficiently in Lisp on a Sun 4, using face images of size 128x128. With some special-purpose hardware, the current version could run at close to frame rate (33 msec).

Designing a practical system for face recognition within this framework requires assessing the tradeoffs between generality, required accuracy, and speed. If the face recognition task is restricted to a small set of people (such as the members of a family or a small company), a small set of eigenfaces is adequate to span the faces of interest. If the system is to learn new

faces or represent many people, a larger basis set of eigenfaces will likely be required.

Motion detection and head tracking

In the described embodiment, motion detection
5 module 6 and head locator module 8 locates and tracks the
position of the head of any person within the scene
viewed by video camera 4 by implementing the tracking
algorithm depicted in Fig. 4. A sequence of image frames
30 from video camera 4 first passes through a spatio-
10 temporal filtering module 32 which accentuates image
locations which change with time. Spatio-temporal
filtering module 32 identifies the locations of motion by
performing a differencing operation on successive frames
of the sequence of image frames. In the output of the
15 spatio-temporal filter module 32, a moving person "lights
up" whereas the other areas of the image containing no
motion appear as black.

The spatio-temporal filtered image passes to a
thresholding module 34 which produces a binary motion
20 image identifying the locations of the image for which
the motion exceeds a preselected threshold. That is, it
locates the areas of the image containing the most
motion. In all such areas, the presence of a person is
postulated.

25 A motion analyzer module 36 analyzes the binary
motion image to watch how "motion blobs" change over time
to decide if the motion is caused by a person moving and
to determine head position. A few simple rules are
applied, such as "the head is the small upper blob above
30 a larger blob (i.e., the body)", and "head motion must be
reasonably slow and contiguous" (i.e., heads are not
expected to jump around the image erratically).

The motion image also allows for an estimate of
scale. The size of the blob that is assumed to be the

moving head determines the size of the subimage to send to face recognition module 10 (see Fig. 1). This subimage is rescaled to fit the dimensions of the eigenfaces.

5 Using "face space" to locate the face

Face space may also be used to locate faces in single images, either as an alternative to locating faces from motion (e.g. if there is too little motion or many moving objects) or as a method of achieving more
10 precision than is possible by use of motion tracking alone.

Typically, images of faces do not change radically when projected into the face space; whereas, the projection of non-face images appear quite different.
15 This basic idea may be used to detect the presence of faces in a scene. To implement this approach, the distance ϵ between the local subimage and face space is calculated at every location in the image. This calculated distance from face space is then used as a
20 measure of "faceness". The result of calculating the distance from face space at every point in the image is a "face map" $\epsilon(x,y)$ in which low values (i.e., the dark areas) indicate the presence of a face.

Direct application of Eq. 10, however, is rather
25 expensive computationally. A simpler, more efficient method of calculating the face map $\epsilon(x,y)$ is as follows.

To calculate the face map at every pixel of an image $I(x,y)$, the subimage centered at that pixel is projected onto face space and the projection is then
30 subtracted from the original subimage. To project a subimage Γ onto face space, one first subtracts the mean image (i.e., Ψ), resulting in $\Phi = \Gamma - \Psi$. With Φ_f being the projection of Φ onto face space, the distance measure at a given image location is then:

$$\begin{aligned}
 \epsilon^2 &= \|\mathbf{s} - \mathbf{s}_f\|^2 \\
 &= (\mathbf{s} - \mathbf{s}_f)^T (\mathbf{s} - \mathbf{s}_f) \\
 &= \mathbf{s}^T \mathbf{s} - \mathbf{s}^T \mathbf{s}_f + \mathbf{s}_f^T (\mathbf{s} - \mathbf{s}_f) \\
 &= \mathbf{s}^T \mathbf{s} - \mathbf{s}_f^T \mathbf{s}_f
 \end{aligned} \tag{11}$$

5 since $\mathbf{s}_f \perp (\mathbf{s} - \mathbf{s}_f)$. Because $\mathbf{s}_f$ is a linear combination of the eigenfaces ($\mathbf{s}_f = \sum_i \omega_i \mathbf{u}_i$) and the eigenfaces are orthonormal vectors,

$$\mathbf{s}_f^T \mathbf{s}_f = \sum_i \omega_i^2 \tag{12}$$

and

$$10 \quad \epsilon^2(x, y) = \mathbf{s}^T(x, y) \mathbf{s}(x, y) - \sum \omega_i^2(x, y) \tag{13}$$

where $\epsilon(x, y)$ and $\omega_i(x, y)$ are scalar functions of image location, and $\mathbf{s}(x, y)$ is a vector function of image location.

The second term of Eq. 13 is calculated in practice by a correlation with the L eigenfaces:

$$\begin{aligned}
 \sum_i \omega_i^2(x, y) &= \sum_i \mathbf{s}^T(x, y) \mathbf{u}_i \\
 &= \sum_i (\Gamma(x, y) - \Psi)^T \mathbf{u}_i \\
 &= \sum_i (\Gamma^T(x, y) \mathbf{u}_i - \Psi^T \mathbf{u}_i) \\
 &= \sum_i (I(x, y) \otimes \mathbf{u}_i - \Psi^T \mathbf{u}_i)
 \end{aligned} \tag{14}$$

20 where $\otimes$ is the correlation operator. The first term of Eq. 13 becomes

$$\begin{aligned}
 \mathbf{s}^T(x, y) \mathbf{s}(x, y) &= (\Gamma(x, y) - \Psi)^T (\Gamma(x, y) - \Psi) \\
 &= \Gamma^T(x, y) \Gamma(x, y) - 2\Psi^T \Gamma(x, y) + \Psi^T \Psi \\
 &= \Gamma^T(x, y) \Gamma(x, y) - 2\Gamma(x, y) \otimes \Psi + \Psi^T \Psi
 \end{aligned} \tag{15}$$

25 so that

$$\begin{aligned}
 \epsilon^2(x, y) &= \Gamma^T(x, y) \Gamma(x, y) - 2\Gamma^T(x, y) \otimes \Psi + \\
 &\quad \Psi^T \Psi + \sum_i (\Gamma(x, y) \otimes \mathbf{u}_i - \Psi \otimes \mathbf{u}_i)
 \end{aligned}$$

(15)

30 Since the average face Ψ and the eigenfaces $\mathbf{u}_i$ are fixed, the terms $\Psi^T \Psi$ and $\Psi \otimes \mathbf{u}_i$ may be computed ahead of time.

Thus, the computation of the face map involves only $L + 1$ correlations over the input image and the computation of the first term $\Gamma^T(x, y) \Gamma(x, y)$. This is computed by squaring the input image $I(x, y)$ and, at each

image location, summing the squared values of the local subimage.

Scale invariance

Experiments reveal that recognition performance
5 decreases quickly as the head size, or scale, is
misjudged. It is therefore desirable for the head size
in the input image must be close to that of the
eigenfaces. The motion analysis can give an estimate of
head size, from which the face image is rescaled to the
10 eigenface size.

Another approach to the scale problem, which may
be separate from or in addition to the motion estimate,
is to use multiscale eigenfaces, in which an input face
image is compared with eigenfaces at a number of scales.
15 In this case the image will appear to be near the face
space of only the closest scale eigenfaces.
Equivalently, the input image (i.e., the portion of the
overall image selected for analysis) can be scaled to
multiple sizes and the scale which results in the
20 smallest distance measure to face space used.

Other embodiments are within the following claims.
For example, although the eigenfaces approach to face
recognition has been presented as an information
processing model, it may also be implemented using simple
25 parallel computing elements, as in a connectionist system
or artificial neural network.

What is claimed is:





CLAIMS

1 1. A recognition system for identifying members
2 of an audience, the system comprising:
3 an imaging system which generates an image of the
4 audience;
5 a selector module for selecting a portion of said
6 generated image;
7 a detection means which analyzes the selected
8 image portion to determine whether an image of a person
9 is present; and
10 a recognition module responsive to said detection
11 means for determining whether a detected image of a
12 person identified by said detection means resembles one
13 of a reference set of images of individuals.

1 2. The recognition system of claim 1 wherein said
2 recognition module also determines which one, if any, of
3 the individuals in said reference set said detected image
4 resembles.

1 3. The recognition system of claim 1 wherein said
2 selection means comprises a motion detector for
3 identifying the selected portion of said image by
4 detecting motion.

1 4. The recognition system of claim 3 wherein said
2 selection means further comprises a locator module for
3 locating the portion of said image corresponding to a
4 face of the person based on motion detected by said
5 motion detector.

1 5. The recognition system of claim 1 wherein said
2 detection means employs a first pattern recognition
3 technique to determine whether an image of a person is
4 present in the selected portion of the image.





1 6. The recognition system of claim 5 wherein said
2 recognition module employs a second pattern recognition
3 technique to determine whether the detected image of a
4 person resembles one of said reference set.

1 7. The recognition system of claim 6 wherein said
2 first pattern recognition technique employs a set of
3 eigenvectors in a multi-dimensional image space to
4 characterize said reference set.

1 8. The recognition system of claim 7 wherein said
2 second pattern recognition technique also employs said
3 set of eigenvectors.

1 9. The recognition system of claim 8 wherein said
2 second pattern recognition technique also represents each
3 member of said reference set as a point in a subspace
4 defined by said set of eigenvectors.

1 10. The recognition system of claim 9 wherein
2 said image of a person is an image of a person's face and
3 wherein said reference set comprises images of faces of
4 said individuals.

1 11. The recognition system of claim 1 further
2 comprising means for representing said reference set as a
3 set of eigenvectors in a multi-dimensional image space
4 and wherein said detection means comprises means for
5 representing said selected image portion as an input
6 vector in said multi-dimensional image space and means
7 for computing the distance between a point identified by
8 said input vector and a subspace defined by said set of
9 eigenvectors.





- 21 -

1 12. The recognition system of claim 11 wherein
2 said detection means further comprises a thresholding
3 means for determining whether an image of a person is
4 present by comparing said computed distance to a
5 preselected threshold.

1 13. The recognition system of claim 12 wherein
2 said recognition module comprises means for representing
3 each member of said reference set as a corresponding
4 point in said subspace.

1 14. The recognition system of claim 13 wherein
2 the location of each point in subspace associated with a
3 corresponding member of said reference set is determined
4 by projecting a vector associated with that member onto
5 said subspace.

1 15. The recognition system of claim 14 wherein
2 said recognition module further comprises means for
3 projecting said input vector onto said subspace.

1 16. The recognition system of claim 15 wherein
2 said recognition module further comprises means for
3 selecting a particular member of said reference set and
4 means for computing a distance within said subspace
5 between a point identified by the projection of said
6 input vector onto said subspace and the point in said
7 subspace associated with said selected member.

1 17. The recognition system of claim 15 wherein
2 said recognition module further comprises means for
3 determining for each member of said reference set a
4 distance in subspace between the location associated with
5 that member in subspace and the point identified by the
6 projection of said input vector onto said subspace.

This Sheet Has Been Replaced





1 18. The recognition system of claim 17 wherein
2 said image of a person is an image of a person's face and
3 wherein said reference set comprises images of faces of
4 said individuals.

1 19. A method for identifying members of an
2 audience, the method comprising:
3 generating an image of the audience;
4 selecting a portion of said generated image;
5 analyzing the selected image portion to determine
6 whether an image of a person is present; and
7 if an image of a person is determined to be
8 present in said selected image portion, determining
9 whether said image of a person resembles one of a
10 reference set of images of individuals.

1 20. The method of claim 19 further comprising the
2 step of determining which one, if any, of the members of
3 said reference set said image of a person resembles.

1 21. The method of claim 19 wherein the image of
2 the audience is a sequence of image frames and wherein
3 the method further comprises detecting motion within the
4 sequence of image frames and wherein the selected image
5 portion is determined on the basis of the detected
6 motion.

1 22. The method of claim 19 further comprising the
2 step of representing said reference set as a set of
3 eigenvectors in a multi-dimensional image space and
4 wherein the step of analyzing the selected image portion
5 to determine whether an image of a person is present
6 comprises representing said selected image portion as a
7 input vector in said multi-dimensional image space and





- 23 -

8 computing the distance between a point identified by said
9 input vector and a subspace defined by said set of
10 eigenvectors.

1 23. The method of claim 22 wherein the step of
2 analyzing the selected image portion to determine whether
3 an image of a person is present further comprises
4 comparing said computed distance to a preselected
5 threshold.

1 24. The method of claim 23 wherein the step of
2 determining whether said image of a person resembles a
3 member of said reference set comprises representing each
4 member of said reference set as a corresponding point in
5 said subspace.

1 25. The method of claim 24 wherein the step of
2 determining whether said image of a person resembles a
3 member of said reference set further comprises
4 determining the location of each point in subspace
5 associated with a corresponding member of said reference
6 set by projecting a vector associated with that member
7 onto said subspace.

1 26. The method of claim 25 wherein the step of
2 determining whether said image of a person resembles a
3 member of said reference set further comprises projecting
4 said input vector onto said subspace.

1 27. The method of claim 26 wherein the step of
2 determining whether said image of a person resembles a
3 member of said reference set further comprises selecting
4 a member of said reference set and computing a distance
5 within said subspace between a point identified by the
6 projection of said input vector onto said subspace and





- 24 -

7 the point in said subspace associated with said selected
8 member.

1 28. The method of claim 26 wherein the step of
2 determining whether said image of a person resembles a
3 member of said reference set further comprises
4 determining for each member of said reference set a
5 distance in subspace between the location for that member
6 in subspace and the point identified by the projection of
7 said input vector onto said subspace.

1 29. The method of claim 28 wherein said image of
2 a person is an image of a person's face and wherein said
3 reference set comprises images of faces of said
4 individuals.

This Sheet Has Been Replaced

