

S P E C I F I C A T I O N

PROCESS FOR MAKING A DISPOSABLE DIAPER

5 TECHNICAL FIELD OF THE INVENTION

This invention relates to a disposable diaper.

BACKGROUND ART OF THE INVENTION

Japanese Utility Model Publication No. 1993-39531A
10 discloses a pants-type wearing article. In this wearing article,
tape fasteners folded in a Z-shape or an inverted Z-shape so
as to be unfolded in a waist-surrounding direction when these
tape fasteners are used are provided on a surface of the rear
waist region facing a garment the wearer puts on in the vicinity
15 of the rear waist region's both side edges along which the rear
waist region is overlaid and joined together with the front waist
region. Top section of the tape fasteners corresponding to the
top of the Z-shape is coated on its under surface with a
self-adhesive. The tape fasteners may be unfolded and anchored
20 to the wearing article at its appropriate positions to tighten
the waist-surrounding dimension or to retain the used diaper
in a rolled up state.

The invention described in the above-cited Publication

certainly provides a pants-type wearing article having tape fasteners but not provides a process for making such a wearing article. While it is obviously possible to attach tape fasteners one by one to a wearing article, this invention aims to attach
5 tape fasteners to a wearing article, for example, a disposable diaper in a remarkably efficient manner in the process for continuously making the wearing article.

DISCLOSURE OF THE INVENTION

10 According to this invention, there is provided a process for making a disposable diaper, the diaper having a surface facing a wearer's body and a surface facing a garment the wearer puts on and contoured by front and rear ends extending in a transverse direction and a pair of side edges extending in
15 parallel to each other in a longitudinal direction crossing the transverse direction, the diaper being composed of, in the longitudinal direction, a front waist region adjacent to the front end, a rear waist region adjacent to the rear end and a crotch region extending between these waist regions, and the
20 front or rear waist region of the surface facing a garment the wearer puts on being provided in the vicinity of the side edges with tape fasteners folded so that the tape fasteners are unfolded in the transverse direction. This invention includes

the steps of:

- a) feeding continuously a first web in the transverse direction wherein the first web comprises a plurality of backsheets defining the surface of the diaper destined to face a garment the wearer puts on, having a pair of side edges and successively connected one to another along the side edges so as to be continuous in the transverse direction;
- b) feeding tape fastener members to the first web fed in the step a), wherein each of the tape fastener members extending in the transverse direction has longitudinally opposite end portions and an intermediate portion extending between the opposite end portions, one of the opposite end portions is folded in a Z-shape and the other is folded in an inverted Z-shape, which respectively have a top section, a bottom section and an intermediate section lying between said top and bottom sections, said top sections of the Z-shape and the inverted Z-shape are coated on under surfaces with first adhesives and bottom sections are coated on under surfaces with a second adhesives, and bonding the tape fastener members by means of the second adhesives to the surface destined to face a garment the wearer puts on in the front regions or rear waist regions of the backsheets being contiguous one to another along the side edges in the first web so that the tape fastener members cross the

side edges, respectively; and

- c) cutting the first web together with the tape fastener members along the side edges so that said top sections are formed with end portions positioned on said side edges wherein said end
- 5 portions are held and pulled by the wearer's fingers in the transverse direction when said tape fastener members are used.

This invention may be implemented also in manners as follows:

- (1) The first web is fed in the step a) in the condition that
- 10 the first web is overlaid with a second web which is continuous in the transverse direction and destined to be a topsheet defining the surface facing the wearer's body and liquid-absorbent cores arranged at intervals in the feeding direction of these first and second webs between these first
- 15 and second webs.

(2) The first web is destined to define the surface of an open-type disposable diaper facing a garment the wearer puts on.

- (3) The first web is destined to be the backsheet defining the surface of a pants-type disposable diaper facing a garment the
- 20 wearer puts on and after the first web has been folded back along a line bisecting a vertical dimension of the first web so that a region of the first web destined to form the front waist regions and a region of the first web destined to form the rear waist

3 MARCH 2006

- 5 -

regions are directly or indirectly overlaid each other, the folded back two regions are joined together at zones each having a desired width along lines to define the side edges of the diaper and thereafter the tape fastener members are bonded to the first
5 web by means of the second adhesives on both sides of the respective zones of desired width so as to cross the respective zones.

BRIEF DESCRIPTION OF THE DRAWINGS

10 Fig. 1 is a partially cutaway plan view showing a disposable diaper;

Fig. 2 is a cross-sectional view taken along a line II - II in Fig. 1;

15 Fig. 3 is a diagram illustrating a manner in which the tape fasteners are used;

Fig. 4 is a diagram illustrating another manner in which the tape fasteners are used;

Fig. 5 is a diagram illustrating a part of the process for making a disposable diaper;

20 Fig. 6 is a cross-sectional view taken along a line VI - VI in Fig. 5;

Fig. 7 is a cross-sectional view similar to Fig. 6 illustrating another embodiment of the tape fastener member;

3 MARCH 2006

-6-

Fig. 8 is a partially cutaway perspective view showing a pants-type disposable diaper;

Fig. 9 is a cross-sectional view taken along a line IX - IX in Fig. 8;

5 Fig. 10 is a perspective view of a pants-type disposable diaper illustrating a manner in which the tape fasteners are used;

Fig. 11 is a diagram illustrating a part of the process for making a pants-type disposable diaper;

10 Fig. 12 is a cross-sectional view taken along a line XII - XII in Fig. 11; and

Fig. 13 is a diagram similar to Fig. 11 illustrating a part of the process for making a pants-type disposable diaper.

15 DESCRIPTION OF THE BEST MODE FOR WORKING OF THE INVENTION

Details of the process for making a disposable diaper proposed by this invention will be more fully understood from the description given hereunder with reference to the accompanying drawings.

20 Fig. 1 is a partially cutaway plan view showing a disposable diaper 1 made by the process according to this invention and Fig. 2 is a cross-sectional view taken along a line II - II in Fig. 1. The diaper 1 comprises a liquid-pervious

3 MARCH 2006

-7-

topsheet 2 facing a wearer's body, a liquid-impervious backsheet 3 facing a garment the wearer puts on and a liquid-absorbent core 4 interposed between these two sheets 2, 3. Fig. 1 is the plan view showing the diaper 1 with the backsheet 3 on the upper side and the topsheet 2 on the under side. The diaper 1 is contoured by front and rear ends 11, 12 extending in parallel to each other in a transverse direction and a pair of side edges 13 extending in parallel to each other in a longitudinal direction orthogonal to the transverse direction. The diaper 1 is composed of, in the longitudinal direction, a front waist region 6 put aside toward the front end 11, a rear waist region 7 put aside toward the rear end 12 and a crotch region 8 extending between these two waist regions 6, 7. In the crotch region 8, the side edges 13 curve inward. Respective portions of the top- and backsheets 2, 3 extend outward beyond a peripheral edge of the core 4 and are overlaid and joined together by means of a hot melt adhesive (not shown) to form a front flap 16, a rear flap 17 and side flaps 18. In the front flap 16 and the rear flap 17, waist-surrounding elastic members 19 are bonded in a stretched state to the inner surface of at least one of the top- and backsheets 2, 3. In the side flaps 18, thigh-surrounding elastic members 21 are stretched along the curved side edges 13 and bonded in this stretched state to the inner surface of

3 MARCH 2006

- 8 -

at least one of the top- and backsheet 2, 3. In the rear waist region 7, tape fasteners 30 are attached to the backsheet 3 in the vicinity of the respective side edges 13. The tape fasteners 30 are folded so that these tape fasteners 30 may be unfolded outward beyond the respective side edges 13.

As viewed in Fig. 2, each of the tape fasteners 30 consists of a top tape section 31, a bottom tape section 32 and an intermediate tape section 33 lying between these top and bottom tape sections 31, 32. The top tape section 31 has an inner end portion 36, an outer end portion 37 and an intermediate portion 38 with respect to the diaper 1 and these portions 36 - 38 are coated on the under surfaces thereof with the first adhesive 39. The bottom tape section 32 also has an inner end portion 41, an outer end portion 42 and an intermediate portion 43 and these portions 41 - 43 are coated on the under surfaces thereof with the second adhesive 44. Similarly, the intermediate tape section 33 has an inner end portion 46, an outer end portion 47 and an intermediate portion 48 and these portions 46 - 48 are coated on the under surfaces thereof with the third self-adhesive 49. The inner end portion 36 of the top tape section 31 is temporarily fixed to an upper surface 32a of the bottom tape section 32 but firmly bonded to the folded upward inner end portion 46 of the intermediate tape section 33. The

3 MARCH 2006

-9-

outer end portion 37 of the top tape section 31 extends outwardly of the diaper 1 beyond respective outer end portions of the bottom tape section 32 and the intermediate tape section 33. The first self-adhesive 39 coating the outer end portion 37 is covered
5 with a small film strip 51. The intermediate portion 38 of the top tape section 31 is temporarily fixed to an upper surface 33a of the intermediate tape section 33. The bottom tape section 32 is firmly bonded over its substantially full length to an outer surface (upper surface as viewed in Fig. 2) of the backsheet
10 3. The outer end portion 42 of the bottom tape section 32 is folded upward and firmly bonded to the outer end portion 47 of the intermediate tape section 33 by means of the third self-adhesive 49. Except for the folded inner end portion 46 bonded to the top tape section 31 and the outer end portion 47
15 bonded to the outer end portion 42 of the bottom tape section 32, the intermediate tape section 33, i.e., the intermediate portion 48 thereof is temporarily fixed to the upper surface 32a of the bottom tape section 32. The top tape section 31, the intermediate tape section 33 and the bottom tape section
20 32 arranged in this manner form the continuous tape fastener folded in a Z-shape. The outer end portion 37 of the top tape section 31 may be held together with the small film strip 51 by fingers and pulled in the direction P outwardly of the diaper

3 MARCH 2006

- 10 -

1 to peel the temporarily fixed portions off one from another
and thereby to unfold the tape fastener 30 as indicated by
imaginary lines. In order to facilitate the first adhesive 39
to be peeled off from the bottom tape section 32 and the
5 intermediate tape section 33 and/or in order to facilitate the
third adhesive 49 to be peeled off from the bottom tape section
32, these tape sections 32, 33 may be coated with a suitable
release agent such as silicone oil.

Figs. 3 and 4 are diagrams illustrating manners in which
10 the tape fasteners 30 are used. Referring to Fig. 3, the tape
fasteners 30 are fully unfolded from the rear waist region 7
of the diaper 1 put on a wearer's body and detachably fixed to
the front waist region 6. Referring to Fig. 4, the used diaper
1 has been rolled up and retained by the tape fasteners 30 in
15 such a rolled up state. In this way, the tape fasteners 30 are
useful not only to put the diaper 1 on the wearer's body but
also to maintain the used diaper 1 in a rolled up state for
disposal thereof.

Fig. 5 is a diagram illustrating a part of the process
20 for continuously making the diapers 1. In a series of steps
(1) - (3) illustrated in the lower part of this diagram, an arrow
pointing leftward indicates a machine direction MD. In the step
(1), a continuous diaper 65 is fed in the machine direction MD.

3 MARCH 2006

- 11 -

The continuous diaper 65 comprises continuous liquid-pervious web 62 destined to define the topsheet 2 of the diaper 1, continuous liquid-impervious web 63 placed on the web 62 and destined to define the backsheet 3 of the diaper 1 and the cores 4 at intervals arranged in the machine direction MD at given intervals and interposed between these webs 62, 63. These webs 62, 63 are overlaid and joined together by means of a hot melt adhesive (not shown) around the respective cores 4. Of the continuous diaper 65, a dimension in a direction CD orthogonal to the machine direction MD corresponds to a longitudinal dimension of the individual diaper 1 and an imaginary line A extending in the cross direction CD indicates a position representing each of the side edges 13 of the individual diaper 1. In these two webs 62, 63, a plurality of topsheets 2 are contiguous one to another along respective side edges 13 and a plurality of backsheets 3 are contiguous one to another along the respective side edges 13. The core 4 is placed between each pair of the adjacent imaginary lines A, A and the overlaid webs 62, 63 are cut out approximately in the middle of the imaginary line A to form a circular opening 66.

In the step (2), the tape fastener members 67 are fed from a series of steps (a) - (d) illustrated in the upper part of the diagram and these tape fastener members 67 are attached to

the continuous diaper 65 traveling in the machine direction MD so that these tape fastener members 67 may cross the respective imaginary lines A.

In the step (3), the continuous diaper 65 is cut along
5 the imaginary lines A together with the taper fastener members 67 and the individual diapers 1 shown in Fig. 1 are obtained. Peripheral edges of the openings 66 formed in the continuous diaper 65 are destined to define the curved side edges 13 of the diaper 1 in its crotch region 8.

10 In a series of steps (a) - (d) illustrated in the upper part of Fig. 5, the tape fastener members 67 are prepared. In the step (a), continuous tape 367 destined to define the tape fastener members 67 is fed from the right hand toward the left hand as viewed in the diagram. In the step (b), the continuous
15 tape 367 is cut in the transverse direction to obtain the individual tape fastener members 67. In the step (c), the tape fastener members 67 obtained in the step (b) are rotated by 90° so that the members 67 may extend in the machine direction MD. In the step (d), the tape fastener members 67 rotated in this
20 manner are fed to the continuous diaper 65. It is possible to feed the continuous tape 367 in the cross direction CD rather than in the machine direction MD as illustrated and, in this case, the individual tape fastener members 67 obtained by cutting

3 MARCH 2006

- 13 -

the continuous tape 367 are also fed in the cross direction CD to the continuous diaper 65.

Fig. 6 is a cross-sectional view of the continuous diaper 65 including the tape fastener members 67 shown in Fig. 5 as taken along a line VI - VI in Fig. 5. The tape fastener member 67 is symmetric about the imaginary line A, so the left half of the member 67 is not illustrated for the purpose of simplification. The tape fastener member 67 comprises a first tape section 131 crossing the imaginary line A and extending in the machine direction MD, the bottom tape section 32 bonded to the liquid-impervious web 63 on both sides of the imaginary line A by means of the second adhesive 44 and the intermediate tape section 33 temporarily fixed to the upper surface 32a of the bottom tape section 32 by means of the third adhesive 49. The first tape section 131 is temporarily fixed to the upper surface of the intermediate tape section 33 by means of a self-adhesive 139 and this self-adhesive 139 is covered with a small plastic film strip 151 in the vicinity of the imaginary line A. These continuous diaper 65 and tape fastener members 67 may be cut along the respective imaginary lines A to obtain the individual diapers 1 and the tape fasteners 30 attached thereto as shown in Fig. 1 wherein the liquid-pervious web 62 and the liquid-impervious web 63 respectively define the

3 MARCH 2006

- 14 -

topsheet 2 and the backsheet 3. The first tape section 131,
the adhesive 139 and the small plastic film strip 151 in the
tape fastener member 67 may be cut along the imaginary line A
to obtain the top tape section 31, the first adhesive 39 and
5 the small plastic film strip 51 of the tape fastener 30 shown
in Fig. 2. The bottom tape section 32 and the second adhesive
44 of the tape fastener member 67 respectively define the bottom
tape section 32 and the second adhesive 44 of the diaper 1 and
the intermediate tape section 33 and the third adhesive 49
10 respectively define the intermediate tape section 33 and the
third adhesive 49 of the diaper 1. Referring to Fig. 6, of two
tape fasteners 30 obtained from one and same tape fastener member
67, the tape fastener 30 lying on the right side of the imaginary
line A - A is folded in a Z-shape and the tape fastener 30 lying
15 on the left side is folded in an inverted Z-shape.

Such a process for continuously making the individual
diapers 1 characterized in that the continuous diaper 65 is cut
together with the tape fastener members 67 is more advantageous
than the process of well known art according to which the tape
20 fasteners 30 are separately prepared and attached to the diapers
1 one by one. The process according to this invention enables
steps of cutting base material for the tape fasteners 30 to be
eliminated by one step.

Fig. 7 is a diagram similar to Fig. 6 illustrating another embodiment of this invention. The tape fastener member 67 used in this continuous diaper 65 comprises the top tape section 31, the bottom tape section 32 and a second tape section 133 interposed between these two tape sections 31, 32 wherein the second tape section 133 extends beyond the imaginary line A. The tape fastener member 67 may be cut together with the continuous diaper 65 along the imaginary line A to form the tape fasteners 30 on both sides of the imaginary line A similarly to the case of the tape fastener member 67 in Fig. 6. The top tape section 31 in this tape fastener member 67 and the first adhesive 39 applied on the under surface of this tape section 31 function in the same manner as the top tape section 31 and the first adhesive 39 applied to the under surface of this tape section 31 shown in Fig. 2. The bottom tape section 32 in the tape fastener member 67 and the second adhesive 44 applied on the under surface of this section 32 function also in the same manner of those in Fig. 2. While the second tape section 133 and a adhesive 149 applied on the under surface of the second tape section 133 function in the same manner as the intermediate tape section 33 and the third adhesive 49 in Fig. 2, a portion 147 of the second tape section 133 extending beyond the outer end portion 42 of the bottom tape section 32 to the imaginary

3 MARCH 2006

- 16 -

line A is longer than the portion 47 of the tape fastener 30 in Fig. 2 and firmly bonded to the liquid-impervious web 63. In the diaper 1 using the second tape section 133, the tape fastener 30 may be pulled leftward in the direction P as viewed
5 in Fig. 7 with the outer end portion 37 of the top tape section 31 held by fingers to unfold the top tape section 31, the bottom tape section 32 and the second tape section 133 in the same manner as the tape fastener 30 in Fig. 2. It should be understood that the portion 147 of the second tape section 133 remains bonded
10 to the backsheet 3 defined by the second web 63. In the tape fastener 30 according to this embodiment, the portion 147 bonded to the backsheet 3 over a relatively large area is effective to prevent a force tending to peel the bottom tape section 32 off from the backsheet 3 from acting upon the bottom tape section
15 32.

Fig. 8 is a partially cutaway perspective view showing a pants-type disposable diaper 201 made by the process according to this invention. The diaper 201 comprises a liquid-pervious topsheet 202, a liquid-impervious backsheet 203 and a
20 liquid-absorbent core 204 disposed between these two sheets 202, 203 so as to configure a front waist region 206, a rear waist region 207 and a crotch region 208. The front and rear waist regions 206, 207 are overlaid together in the vicinity of

transversely opposite side edges 213 thereof and joined together at bonding zones 210 arranged at intervals in the longitudinal direction of the diaper 201 so as to define a waist-hole 271 and a pair of leg-holes 272. A waist-surrounding elastic member 219 is attached in a stretched state to a peripheral edge portion of the waist-hole 271 and thigh-surrounding elastic members 221 are attached in a stretched state to peripheral edge portions of the leg-holes 272. The rear waist region 207 is provided with tape fasteners 230 in the vicinity of the respective side edges 213.

Fig. 9 is a cross-sectional view taken along a line IX - IX in Fig. 8. In the diaper 201, the front and rear trunk regions 206, 207 are overlaid together in the vicinity of the side edges 213 and the top- and backsheets 202, 203 are joined together at the bonding zones 210. The tape fastener 230 is identical to the tape fastener 30 in Fig. 2, so the regions of the tape fastener 230 are designated by the reference numerals added 200 to the reference numerals of the corresponding tape fastener 30. The tape fastener 230 can be unfolded with the outer end portion 237 of the top tape section 231 held by fingers so as to extend in the direction P beyond the side edge 213 of the rear waist region 207 to the front waist region 206.

Fig. 10 is a perspective view of a pants-type disposable

3 MARCH 2006

- 18 -

diaper 201 illustrating a manner in which the tape fasteners 230 are used. In the case of the diaper 201 shown in Fig. 10, the front waist region 206 is pulled toward the rear waist region 207 using the tape fasteners 230 so that the diaper 201 may be tucked to alleviate overabundance in the waist-surrounding direction. This tape fastener 230 also is useful to retain the used diaper in a rolled up state as the tape fastener 30 of Fig. 5 is.

Fig. 11 is a diagram illustrating a part of the process for continuously making the diaper 201 having the tape fasteners 230. In the step (1), continuous diaper 265 destined to be the pants-type diapers 201 is fed from the right hand toward the left hand as viewed in Fig. 11, i.e., in the machine direction MD. The continuous diaper 265 is similar to the continuous diaper 65 of Fig. 5 except that a continuous liquid-pervious web 262 is placed on a continuous liquid-impervious web 263 and the cores 204 are interposed between these webs 262, 263. In the step (2), the continuous diaper 265 is folded back along the center line C bisecting a dimension of the continuous diaper 265 in the cross direction CD crossing the machine direction MD with the liquid-pervious web 262 inside. In the step (3), the bonding zones 210 are formed on both sides of the imaginary line A extending in the cross direction CD in the middle between

3 MARCH 2006

- 19 -

each pair of the adjacent cores 204, 204 so that two layers of the continuous diaper 265 formed by folding back may be at intervals joined together. In the step (4), the tape fastener members 267 are fed so as to cross the bonding zones 210 in the machine direction MD and bonded to the liquid-impervious web 263 on both sides of the bonding zones 210. In the step (5), the continuous diaper 265 is cut along the imaginary lines A together with the tape fastener members 267 and the individual pants-type diapers 201 are obtained.

Fig. 12 is a cross-sectional view taken along a line XII - XII in Fig. 11. On both sides of the respective imaginary lines A extending across the continuous diaper 265, the liquid-pervious web 262 and the liquid-impervious web 263 destined to form the front waist regions 206, on one hand, and the liquid-pervious web 262 and the liquid-impervious web 263 destined to form the rear waist regions 207, on the other hand, are welded together in the bonding zones 210. Similarly to the tape fastener member 67 shown by Fig. 5, the tape fastener member 267 has the uppermost first tape section 131 crossing the bonding zones 210 formed on both sides of the imaginary line A. This tape fastener member 267 may be cut along the imaginary line A to obtain the tape fastener 230 shown in Fig. 10.

Fig. 13 is a diagram similar to Fig. 11 illustrating a

part of the process for making the pants-type disposable diaper 201 comprising steps different from those in the process illustrated by Fig. 11. Referring to Fig. 13, in the step (3), the tape fastener members 267 are fed to the continuous diaper 5 265 so as to cross the respective imaginary lines A and bonded to the liquid-impervious web 263. In the step (4), the bonding zones 210 are formed on both sides of the respective imaginary lines A. In the case that the liquid-pervious web 262 and the liquid-impervious web 263 are made of a thermoplastic material 10 having a relatively low softening temperature such as polyethylene or polypropylene and the tape fastener member 267 is made of a thermoplastic material having a relatively high softening temperature such as polyester, the liquid-pervious web 262 and the liquid-impervious web 263 may be heat-sealed 15 above the tape fastener member 267 to form the bonding zones 210 and thereby to obtain the pants-type diaper 201 having the arrangement similar to that shown by Fig. 12.

It is possible without departing from the scope of this invention to use, in the process illustrated by Figs. 11 and 20 13, the tape fastener member 67 shown in Fig. 6 instead of the tape fastener member 267 shown in Fig. 12. In the process illustrated by Fig. 11, it is possible without departing from the scope of this invention to directly joined two layers of

3 MARCH 2006

- 21 -

the folded back liquid-impervious web 263 without interposition of the liquid-pervious web 262 in the bonding zones 210. The liquid-pervious web 62, 262 and the liquid-impervious web 63, 263 are preferably made of a heat-sealable sheet material
5 containing thermoplastic synthetic resin over 50 wt%. This invention may be implemented in a manner that the tape fasteners 30, 230 are attached to the front waist region 6, 206 instead of attaching them to the rear waist region 7, 207 as for the diaper 1, 201 as illustrated.

10 The process according to this invention for making the disposable diapers is primarily characterized in that the continuous diaper is cut together with the tape fastener members and thereby the individual diapers are obtained. Thus the time and labor required to prepare the tape fasteners for production
15 of the disposable diaper can be alleviated.

3 MARCH 2006

- 22 -

C L A I M S

1. A process for making a disposable diaper, said diaper having a surface facing a wearer's body and a surface facing
5 a garment the wearer puts on and contoured by front and rear ends extending in a transverse direction and a pair of side edges extending in parallel to each other in a longitudinal direction crossing said transverse direction, said diaper being composed of, in said longitudinal direction, a front waist region adjacent
10 to said front end, a rear waist region adjacent to said rear end and a crotch region extending between these waist regions, and said front or rear waist region of said surface facing a garment the wearer puts on being provided in the vicinity of said side edges with tape fasteners folded so that said tape
15 fasteners are unfolded in said transverse direction, said process comprising the steps of:
- a) feeding continuously a first web in said transverse direction wherein said first web comprises a plurality of back sheets defining said surface of said diaper destined to face a garment
20 the wearer puts on, having said pair of side edges and successively connected one to another along said side edges so as to be continuous in said transverse direction;
- b) feeding tape fastener members to said first web fed in said

step a), wherein each of said tape fastener members extending in said transverse direction has longitudinally opposite end portions and an intermediate portion extending between said opposite end portions, one of said opposite end portions being
5 folded in a Z-shape and an inverted Z-shape which respectively have a top section, a bottom section and an intermediate section lying between said top and bottom sections, top sections are coated on under surfaces with first adhesives and bottom sections are coated on under surfaces with second adhesives, and bonding
10 said tape fastener members by means of said second self-adhesive to said surface destined to face a garment the wearer puts on in said front regions or rear waist regions of said backsheet being contiguous one to another along said side edges in said first web so that said tape fastener members cross said side
15 edges, respectively; and
c) cutting said first web together with said tape fastener members along said side edges so that said top sections are formed with end portions positioned on said side edges wherein said end portions are held and pulled by the wearer's fingers in the
20 transverse direction when said tape fastener members are used.

2. The process according to Claim 1, wherein said first web is fed in said step a) in the condition that said first web is

overlaid with the second web which is continuous in said transverse direction and destined to be a topsheet defining said surface facing the wearer's body and liquid-absorbent cores arranged at intervals in the feeding direction of these first
5 and second webs between these first and second webs.

3. The process according to Claim 1 or 2, wherein said first web is destined to define the surface of an open-type disposable diaper facing a garment the wearer puts on.

10

4. The process according to Claim 1 or 2, wherein said first web is destined to be said backsheet defining the surface of a pants-type disposable diaper facing a garment the wearer puts on and after said first web has been folded back along a line
15 bisecting a vertical dimension of said first web so that a region of said first web destined to form the front waist regions and a region of said first web destined to form the rear waist regions are directly or indirectly overlaid each other, said folded back two regions are joined together at zones each having a desired
20 width along lines destined to define said side edges of said diaper and thereafter said tape fastener members are bonded to said first web by means of said second adhesives on both sides of respective said zones of desired width so as to cross

3 MARCH 2006

- 25 -

respective said zones.