

High load balanced rudder

The invention relates to a high load balanced rudder for ships with a rudder blade, whereby the rudder blade is rotatable over a rudder post and the rudder post is placed in a rudder port and the rudder port is supported over a fixed leading head on the hull of the ship.

With rudders, the direction of motion of a ship can be influenced in the wished manner. To this, semi-balanced, partially balanced and fully balanced rudders are known to the skilled in the art for shipbuilding or to the shipbuilding engineer. This being, the rudder blade is fixedly connected with a rudder post which penetrates into the inside of the hull of a ship and which is twisted with the aid of a steering gear in a way known in itself in order to give to the rudder blade the wished angle of incidence with respect to the hull of the ship. This being, the rudder blade is placed under the hull of the ship in such a manner that it is flowed by a propeller downflow of the propeller to drive the ship.

When the rudder blade is in a set position, in particular for high ship speeds, big efforts appear which act onto the rudder blade. In order to absorb them better and to be able to induce them into the hull of the ship, it is known for semi-balanced or partially balanced rudders to fix the proper rudder blade for example over a rudder pintle to a rudder support.

To this, the document DE 198 41 392 A1 discloses a high load balanced rudder for which the rudder blade is positioned with its rudder post in a rudder support hollow column. An additional fixed leading head serves for the support of the rudder support hollow column, leading head which is placed before the rudder support hollow column, this being seen in the direction of motion, and over which this column is connected with the hull of the ship. Thus, the forces and loads appearing with the incidence of the

rudder blade can be better induced into the hull of the ship over this leading head so that in particular the construction of the rudder support hollow column must be designed of less massive type. Here the leading head is configured such that its lower edge is always situated above the propeller downflow. It is thus achieved that the lower part of the rotatable rudder blade is completely flown by the propeller downflow and thus the surface available for changing the direction is maximized.

This dimensioning of the leading head can however result in that still high forces and loads act onto the rudder blade so that the rudder blade must have a bigger cross-section for stability reasons and consequently the leading head must also be dimensioned sufficiently big so that the flow resistance of this high load balanced rudder is increased, which is not desired.

Thus, the aim of the invention is to create a high load balanced rudder which has a reduced flow resistance and which has however a sufficient stability.

This aim is achieved by the characteristics indicated in claim 1.

As core idea of this very invention, a leading head known in itself of a high load balanced rudder is extended downwards, this being seen in the vertical direction, so that it penetrates in particular into the propeller downflow of the propeller placed in front of the rudder, this being seen in the direction of motion. This means that the lower edge of the leading head or its lower surface is positioned within a diameter range of the driving propeller of the ship. Thus, the leading head is at least partially flown by the propeller and the surface of the rudder blade which is loaded directly by the propeller downflow is reduced accordingly. Furthermore, a lower rudder port bearing with which the rudder post is positioned rotatable in the rudder port, is configured reinforced in order to be able to

better absorb the forces and loads acting onto the rudder blade and to induce them over the rudder port into the hull of the ship. This being, the reinforcement, i.e. the dimensioning as well as the design of this rudder port bearing is to be designed by the skilled in the art according to technical parameters.

The advantage of the invention consists in that, due to the configuration extended downwards of the leading head, the lower rudder port bearing can also be directly supported on the extended leading head or is adjoining to this so that the forces acting onto the lower rudder port bearing are diverted immediately over the structure of the leading head into the hull of the ship. Thus, the forces and loads of the rudder are absorbed more effectively or fully absorbed by the leading head. Thus, the profile or the cross-section surface of the rudder blade - this being seen as a top view - can be reduced since the rudder blade must absorb less forces than in the prior art. In particular the flow resistance of the rudder is thus reduced. A rudder configured in this manner is particularly appropriate for slow-speed ships with a high total weight such as, for example, tankers or bulkers.

Advantageous configurations of the invention are characterized in the subclaims.

With the dimensioning of the leading head indicated in claim 2, it is guaranteed that on the one hand the leading head is extended sufficiently far downwards so that the forces and loads can be sufficiently absorbed over the reinforced lower rudder port bearing and on the other hand the flown fixed surface of the leading head which penetrates into the propeller downflow is dimensioned in such a manner that a satisfactory maneuverability of the ship is guaranteed.

It is clear to the skilled in the art that the high load balanced rudder which is described here can be equipped with an additional rudder fin as indicated in claim 3 in order to be able to use smaller rudder angles in particular for small course corrections or for the course support. The actuation of the rudder fin can take place in connection with the rudder blade in a manner known in itself.

Furthermore, it is proposed in claim 4 that the profiles of the leading head as well as of the rudder blade of the high load balanced rudder are adapted to each other so that there does not appear here any unnecessary swirl in particular at the junction of the leading head with the rudder blade and that the flow resistance of the whole high load balanced rudder is as low as possible.

An embodiment is characterized in claim 5 for which the reinforcement of the lower rudder port bearing can be designed with a different thickness, this being seen in axial direction of the rudder post, in order to obtain here an optimal adaptation to the effectively most favourable leading head structure and to the leading head profile for a material using as low as possible. This being, the dimension or dimensioning of the reinforcement can be configured increasing or decreasing from the top to the bottom. In any case, the port tube and the bearing housing are integrated into the leading head.

Two embodiments of the invention are explained in more detail below by means of the attached drawings.

Fig. 1 shows a high load balanced rudder in cross-section.

Fig. 2 shows a further high load balanced rudder in cross section.

The basic structure of a high load balanced rudder 100 is schematically represented in fig. 1 and 2. The high load balanced rudder 100 comprises

a rudder blade 10 which is fixedly connected with a rudder post 11. The rudder post 11 is positioned twistable in a rudder port 12 or in a rudder support hollow column. This being, the rudder port 12 is fixedly connected with the hull 13 of the ship. A steering gear which is not represented here for simplifying the representation serves for actuating the rudder blade 10 in a manner known in itself.

A leading head 14 fixedly connected with the hull 13 is additionally provided, the lower edge 15 of which or a lower surface penetrating downwards, this being seen in the vertical direction, as far as this lower edge 15 penetrates into the propeller downflow 16 of a driving propeller 17 with the diameter D of the ship.

Furthermore, a lower rudder port bearing 18 of the rudder post 11 is configured reinforced, as it is indicated here schematically with the reinforcements 19.

Due to the extended embodiment of the leading head 14, the lower rudder port bearing 18 can be positioned in such a way that it is situated with the leading head 14 or with its lower edge 15 at the same level so that by an incidence of the rudder blade 10 the forces and loads acting thereon can be derived over the reinforcements 19 directly into the leading head 14 and thus into the hull 13 of the ship. Preferably the leading head 14 penetrates into a range between 10 % to 20 % of the diameter D of the propeller downflow 16.

For the configuration of the reinforcement 19, it is proposed that this reinforcement increases in its diameter either from the top to the bottom, this being seen in axial direction of the rudder post, as represented in fig. 1, or decreases as represented in fig. 2. Thus, an optimal dimensioning is possible to the forces which effectively act onto the lower rudder port

bearing 18 and no superfluous material is needed for realizing the reinforcements.

List of reference numerals

- 100 High load balanced rudder
- 10 Rudder blade
- 11 Rudder post
- 12 Rudder port
- 13 Hull of the ship
- 14 Leading head
- 15 Lower edge
- 16 Propeller downflow
- 17 Propeller
- 18 Lower rudder port bearing
- 19 Reinforcement
- D Diameter of the propeller

Claims

1. Heavy-duty high-balanced rudder (100) for ships with a propulsion propeller (17) and a rudder blade (10), whereby the rudder blade (10) is arranged so as to be rotatable by means of a rudder shaft (11), and the rudder shaft (11) is arranged in a rudder case or tube (12), and the rudder case or tube (12) is supported by means of a fixed guide head (14) to a hull (13) of the ship, characterised in that
a lower edge (15) of the guide head (14) extends into the propeller current by an area of 10 % to 20 % of the diameter (D) of the propulsion propeller (17) and a lower rudder case or tube bearing (18) is designed to be reinforced (19), whereby the reinforcement (19) of the lower rudder case bearing (18) exhibits varying thicknesses axially to the rudder shaft (11).
2. Heavy-duty high-balanced rudder according to Claim 1, characterised in that
an additional oar fin (10) is provided for at the rudder blade.
3. Heavy-duty high-balanced rudder according to one of Claims 1 or 2, characterised in that
the profile of the rudder blade (10) and the profile of the guide head (14) are matched to each other in order to reduce the flow resistance.
4. High load balanced rudder according to any of the claims 1 to 3, characterized in
that a profile of the rudder blade (10) as well as a profile of the leading head (14) are adapted to each other for reducing the flow resistance.
5. High load balanced rudder according to any of the claims 1 to 4, characterized in
that a reinforcement (19) of the lower rudder port bearing (18) has different thicknesses axially to the rudder post (11).