INTENSIFIER RAM BLOWOUT PREVENTER

CROSS-REFERENCE TO RELATED APPLICATIONS

[001] The present application claims the priority benefit of the co-pending United States Provisional Application for Patent, having the Application Serial Number 61/861,095, filed August 1, 2013, which is incorporated by reference herein in its entirety.

FIELD

[002] Embodiments usable within the scope of the present disclosure relate, generally, to blowout preventers ("BOPs"), e.g., usable in conjunction with subterranean and/or subsea wellbores, and more specifically, to blowout preventers adapted to provide enhanced/intensified pressure to the rams thereof when actuated.

BACKGROUND

[003] BOPs are commonly used for well control in oil and gas wells and other subterranean exploration and production activities, especially during drilling operations, completion operations, and production of hydrocarbons (or other matter) encountered under pressure from a well. The use of BOPs is required by law in most regions where oil and gas drilling operations are performed

[004] BOPs have been used in the oil and gas industry for nearly a century, as illustrated in U.S. Patent No. 1,569,247, which is incorporated by reference herein in its entirety. Conventional BOPs utilize radially opposing hydraulic ram blocks. As hydraulic fluid is forced into a piston configured within the rams inside each ram module, the rams converge (e.g., move in an inward direction), typically to contact one another to seal a wellbore. While rams can be used to cut and/or displace a tubular, or seal around a tubular, various types of BOPs can be used to seal a well independent of whether the wellbore contains a tubular. Controlling unwanted or unexpected pressure in a wellbore is critical to maintaining a safe work environment and safe equipment, and preserves both the environment and the reservoir.

[005] Different types of BOPs have evolved over the years to address different problems in various drilling scenarios. Standard practice in the offshore oil and gas industry is the use of tall

"stacks" of multiple BOPs, which may vary in type, configuration, as well as redundancy of features.

[006] Standard practice in the oil and gas industry involves use of ram-type blowout preventers. Ram-type blowout preventers are generally regarded as reliable in situations in which the highest, most dangerous pressures may be encountered. Since the development of the first BOPs in the 1920s, the design/configuration of ram-type BOPs has changed only slightly, at least in terms of mechanical function, and these changes are generally limited to the addition of hydraulic force and modern controls. Radially opposing ram blocks, that is, ram blocks positioned on opposite sides of the wellbore and contained in a BOP housing, are generally hydraulically actuated to "close", and make contact in the center of the wellbore, providing a seal against wellbore pressure. In this closing operation, a seal may be formed around any tubular in the wellbore, through contact between rams if using blind ram blocks (e.g. no tubulars), or through contact between rams when shear rams are used, e.g., to shear and seal tubular(s). The rams generally include ram block sealing surfaces formed from extendable, expandable, extrudable rubber, or rubber "packers" on the ends thereof, that are formed with the required shape and flexibility to form a seal around a tubular, or against an opposing ram in the case of shearing or in the absence of a tubular.

[007] The BOP housing that contains the ram cavity and ram blocks has an open center for placement over the wellbore and allowing space for tubulars, such as a drill string, that may pass through the BOP housing and into or above the wellbore. Recently, in order to generate sufficient pressure during actuation to shear tubulars of significant strength, the movement of pistons in the rams requires a great deal of external room—significant external space sufficient for placement of large hydraulic cylinders and an accordingly large amount of hydraulic fluid. This required space is seen in the form of the lateral extension of roughly linear hydraulic cylinders away from, and transverse or perpendicular to, the main BOP housing, and opposite an opposing ram block. The introduction of hydraulic fluid under pressure into the cylinder actuates the ram(s) toward a closed position. Thus, large cylinders and external housings (extending in opposite directions from the ram block, laterally outward from the BOP housing) are critical to the function of conventional BOPs. These cylinders with their external housings require great amounts of space in both lateral directions and add great mass to the entire BOP in order to increase force necessary to execute a closing operation. As such, conventional BOPs

possess a large and unwieldy footprint, requiring extensive planning as well as powerful equipment for placement over the wellbore.

[008] U.S. Patent Number 7,779,918, which is incorporated by reference herein in its entirety, describes a compact wellbore control device that utilizes hydraulic pistons to actuate linkages that in turn force rams together in a "close" operation. This wellbore control device appears to provide a relatively compact, although mechanically complex, means of severing a small diameter tubular, such as the referenced workstring, within a riser pipe, but is primarily suitable only for operations performed on a relatively small diameter tubular.

[009] U.S. Patent Number 8,353,338, which is incorporated by reference herein in its entirety, describes an alternate means of hydraulically moving a shear assembly outward with the trailing edge of a shear assembly, rather than the leading edge, moving slightly across the wellbore and executing the shear of a tubular. As noted, traditional ram BOPs utilize the leading edge of a shear assembly that is making an inward, or toward and then slightly across the wellbore movement, in a sealing and shearing operation.

[0010] It should be well noted that tubular shearing (and resultant sealing) operations require more force than other BOP closing operations. Typically, the increased energy required for shearing operations is generated by adding booster cylinders to the end of existing ram hydraulic cylinders. The added booster cylinders add mass and further increase the already-large BOP footprint.

[0011] A flanged, bolt-on "bonnet," or a hinged "door," with a contiguous (from the flange or door) extended hydraulic cylinder housing is the typical means by which a conventional BOP cylinder is attached the BOP housing. As described previously, this flanged or hinged housing extends perpendicularly or transversely outward from the main BOP housing. Such bonnets are typically bolted to the main BOP body with a number of large, heavy bolts, while hinged doors are joined to the main BOP body by large hinges. Removal of the bolts and/or hinges is a very time-intensive and laborious endeavor. In recent years, "boltless" doors have been developed, which utilize a different locking mechanism, though large hinges on the doors still consume significant space, which is compounded by the large swing-arc space required to open the door. Accommodations for large hinge doors may interfere with placement of other equipment and/or service efforts under certain circumstances.

[0012] Ram BOPs traditionally utilize "open" and "close" ports in the BOP body to channel hydraulic fluid to the rams and actuate them toward the open or close position, respectively. As fluid enters one end of a ram cylinder on one side of the piston-ram-shaft assembly, it will displace fluid contained in the cylinder on the other side of the piston. BOPs are designed with appropriate ports, passageways and accumulators to accommodate the fluid movement that actuates a BOP between open and close positions. A closing operation closes the rams when required, and the "open" operation retracts the rams to an open position when deemed appropriate and safe.

[0013] Conventional BOPs are relatively reliable, if cumbersome, having a significant number of moving parts and wear parts. The power of a conventional BOP to deliver sealing or shearing force remains closely correlated to the BOP's size, with an increase in deliverable force resulting in a significant increase in the footprint of the BOP. Due to the fact that modern wells are drilled to significant depths and encounter very significant pressures, both on land and in offshore subsea installations, BOPs and BOP stacks are becoming extremely heavy and occupy enormous footprints. Yet even with the size and power of conventional BOPs, serious pressure-related oilfield accidents and mishaps continue to plague the industry.

SUMMARY

[0014] Embodiments usable within the scope of the present disclosure relate to methods for controlling, sealing, and/or shearing and sealing wellbore tubulars, through hydraulic and/or gas assisted operations, and devices (e.g., blowout preventers) capable of such methods. Embodied BOPs can utilize fewer and simpler parts than conventional BOPs, while applying equal or greater force to the rams thereof, significantly reducing the mass and footprint of devices when compared to conventional BOP housings, cylinders, bolt-on bonnets, and/or hinged doors. For example, embodiments usable within the scope of the present disclosure can be utilized without requiring bonnets or doors. Further, embodiments usable within the scope of the present disclosure include BOPs that are generally failsafe under nearly any circumstances.

[0015] In an embodiment, a blowout preventer can include an integrated, self-contained pressure intensifier usable to deliver force/pressure to the BOP rams in excess of conventional alternatives. In the event hydraulic power is unavailable for any reason, one or more embodiments can include a gas reservoir in communication with the intensifier, adapted to

release gas to apply sufficient pressure to the intensifier to independently perform a sealing and/or shearing operation. In an embodiment, the BOP can provide compact footprint and/or weight, e.g., through using no bonnets or doors, and thereby eliminating the use of cumbersome bolts and/or similar attachment features used in conjunction with bonnets and doors. For example, in an embodiment, a single locking pin or screw could be used to provide access to a ram module, enabling efficient ram maintenance, while reducing the overall weight and footprint of the device. This reduction in structure, weight, and footprint can be accomplished using a method for actuation of the rams that deviates from conventional alternatives.

[0016] In an embodiment, an intensifier can be an integral and enclosed part within the BOP housing. In use, the intensifier can enable application of an intensified hydraulic pressure, e.g., through use of a piston, plunger, and/or similar member having sides with differing surface areas to multiply the pressure received at a first side of the intensifier, and applying this multiplied force to the rams to perform a sealing and/or shearing operation. Force applied to the rams in this manner can be significantly greater than that of a comparably sized conventional BOP, and provide adequate sealing and/or shearing force for any conceivable wellbore incident. For example, use of enhanced pressure/force applied to the rams can enable embodied BOPs to efficiently shear any oilfield tubular, including exotic and/or modern, high-strength tubular materials that can often become an impediment for conventional BOP rams.

[0017] In an embodiment, all intensified pressure can be contained within the upper housing and ram module of the BOP, thereby eliminating the possibility of pressure being released by exterior fittings or fasteners. A lower housing can be included (e.g., a bolt-on circular and/or "washer" shaped plate, with ram shaft access ports), that can be rotated relative to the upper housing to position the ram shaft access ports in any desired and/or convenient orientation.

[0018] In an embodiment, the BOP can be provided with a circular and/or cylindrical shape, e.g., concentric to the wellbore, which provides the BOP with an exceptionally strong and compact form lacking any structural corners or structural welds that could become potential failure points. The circumferential strength of such a shape can enable the BOP to withstand greater pressures while utilizing less mass and material than conventional ram BOPs. In various embodiments (e.g., circular-shaped BOPs), no welding is required, but rather only machining of the BOP, resulting in easier and/or more efficient manufacture.

[0019] In an embodiment, the BOP can include an associate gas reservoir (e.g., bolted or otherwise mounted to the BOP). In use, the gas booster reservoir can be used in conjunction with the BOP's hydraulics to boost hydraulic pressure, or in the event that hydraulic pressure is unavailable for any reason, the gas booster reservoir can be provided with sufficient fluid and/or components to be used independently, in place of hydraulic power, to move the BOP rams toward a closed position unassisted. The gas booster reservoir may be constructed so as to be sufficiently robust to execute any required shearing and sealing operation, including shearing of modern and/or exotic and/or high strength tubular materials. The gas booster reservoir can include a release valve that may be actuated by a variety of methods. Use of a gas reservoir can enable an embodied BOP to be generally failsafe. For example, while use of a gas booster reservoir is not required for normal function of various embodiments of the disclosed blowout preventer, use of such reservoirs may become standard practice in the industry.

[0020] In various embodiments, a blowout preventor can utilize approximately one half the number of parts found in a conventional BOP, or fewer, such as through the elimination of bonnets and doors, structural configurations to reduce mass/footprint, etc. As described previously, elimination of bonnets an doors results in the elimination of associated bolts, hinges, and similar mounting features. In an embodiment, hydraulic ram modules can be retained in place by a sufficiently robust retaining member, such as an insertable member, thus eliminating the need for bolts and conventional bonnet/door assemblies while simplifying the manufacture, assembly and maintenance of the BOP. For example, in an embodiment, ram module maintenance can be performed by simply removing a locking pin or screw that allows the retaining member to slide outward (e.g., laterally or perpendicularly) relative to the rear portion of the ram module, thereby allowing removal of the ram module itself, e.g., for maintenance, as needed.

[0021] In an embodiment, an indicator (e.g., a mechanical indicator) can be used, e.g., to verify the position of the piston ram shaft and ram block piston. For example, the piston ram shaft can include an access tube permitting external access to the hollow cylindrical center of the piston ram shaft. A position indicator rod may positioned in association with the ram shaft, to slide inward toward the wellbore and outward away from the wellbore as the ram shaft moves. A locking device, such as a ball screw may function as the position indicator, moving inward to lock the piston ram shaft if hydraulic power is disengaged, while also serving as a visual

indicator of inward piston ram shaft and ram block movement. Such indicators can provide a continuous visual reference by which an external observer can verify ram piston and shaft position, without relying on other mechanisms. In an embodiment, electronic sensors, such as linear transducers or can be incorporated; however, a mechanical ram position indicator can be included for use in the event electronic sensors are unavailable for any reason.

[0022] In an embodiment, a BOP can include a ram shaft locking device usable to retain a ram shaft in a closed position even at times when hydraulics have been bled off after a closing operation.

[0023] Although several embodiments and advantages thereof are described herein, any particular embodiment need not contain all of the advantages and/or features listed. Furthermore, additional advantages and/or features can become apparent through a reading of the appended Detailed Description and accompanying figures, and the features and advantages of the disclosed subject matter are not limited to the foregoing.

BRIEF DESCRIPTION OF DRAWINGS

[0024] **FIG. 1** is a side cross-sectional view of an embodiment of a blowout preventer (BOP) usable within the scope of the present disclosure, depicted in an open position, illustrating cut-away views of a pressure intensification system, a gas booster reservoir, a ram module, and a locking mechanism (shown as a hydraulically actuated ball screw).

[0025] **FIG. 2** is a side cross-sectional view of the BOP of Figure 1 in a closed position, e.g., after travel of an intensifier piston in an upward direction, such that resulting fluid pressure moves the piston ram shaft and associated components in an inward direction (e.g., toward the wellbore.)

[0026] **FIG. 3** is a side cross-sectional view of one half of the BOP of Figure 1, shown in the position, illustrating a view parallel to the piston ram shaft and ball screw and perpendicular to retaining members usable to retain the ram module.

[0027] **FIG. 4** is a side cross-sectional view of the half of the BOP of Figure 1 not shown in Figure 3, depicted in a closed position, illustrating a view parallel to the piston ram shaft and ball screw and perpendicular to the retaining members.

[0028] **FIG. 5** is a top cross-sectional view of the BOP of Figure 1, illustrating opposing ram block assemblies, retaining members, and a round outer circumference of the BOP housing.

[0029] **FIG. 6** shows a side view of the exterior of the BOP of Figure 1, illustrating retaining members perpendicular to the ball screws and oriented such that the retaining members could be removed in a direction inward and/or outward from the figure.

[0030] **FIG. 7** shows a side view of exterior of the BOP of Figure 1, rotated ninety degrees from the view shown in Figure 6, illustrating retaining members perpendicular to the ball screw and to the field of view.

[0031] **FIG. 8** shows a top isometric view of the exterior of the BOP of Figure 1, in which retaining members and an open central portion of the BOP, placeable over a borehole, are visible.

[0032] **FIG. 9A** shows a side view of the exterior of an embodiment of the gas booster reservoir, shown in Figure 1 in conjunction with the BOP depicted therein.

[0033] **FIG. 9B** shows a side cross-sectional view of the gas booster reservoir of Figure 9A, illustrating porting on a side thereof.

DETAILED DESCRIPTION

[0034] Referring to **FIG. 1, FIG. 2, FIG. 3,** and **FIG. 6**, an embodiment of a blowout preventor (BOP) usable within the scope of the present disclosure is shown ,the BOP including an upper housing **34** joined to one or more lower housings **38**, and similarly, joined to a gas booster reservoir housing **31** by a plurality of fasteners **22**, such as studs, socket head cap screws, or other types of fasteners. For example, Figures 1-3 depict a fastener inserted at the lower left portion thereof, proximate to the outer edge/circumference of the BOP. The number, type, and arrangement of fasteners can be varied depending on operational requirements, and usable fasteners can include studs, bolts, screws, or any other type of fastener and can be secured, for example, using retaining members such as nuts (e.g., nylon insert lock nuts, polymer insert lock nuts), or socket head cap screws. While Figures 1-3 depict fasteners such as studs or socket head cap screws extending through the lower housing **38** and gas booster reservoir housing **31** into the upper housing **34**, it should be understood that separate sets of fasteners could be used to attach each housing portion, and that in various embodiments two or more housing portions could be integral with one another. In an embodiment, the same fastener **22** size can be used on a variety of BOP sizes, facilitating manufacture, repair, replacement, maintenance, and maintaining an inventory of parts. In an embodiment, a flanged connection or other type connection can be

utilized in place of the studded connection or in addition thereto. For ease of manufacture, assembly and maintenance, in one embodiment, the upper housing **34** is joined to the lower housing **38** at an attachment point below intensifier piston **56,** with the fasteners **22** being inserted from the bottom of the BOP.

[0035] In the depicted embodiment, a button-style **6** piston ram shaft **18**, although it should be understood that the piston ram shaft **18** can have any design and/or configuration, depending on the operational constraints related to a wellbore. In an embodiment, the piston and ram shaft can be a single unit, e.g., a "piston ram shaft" **18**. However, as described previously, the BOP can be adapted to accept different styles of piston-ram shaft to ram block configurations, including but not limited to the depicted piston ram shaft **18**, ram module **16,** and piston ram shaft retainer ring **60.** The BOP, ram cavity **4** shown in **FIG. 3** and ram module **16** can be modified to accept virtually any piston assembly from any manufacturer. Seal sub assemblies **39**, **58** and **61** can be utilized to seal across separate solid surfaces that may experience some movement, vibration and/or shifting.

[0036] Referring to FIG. 1 and FIG. 2, a side cross-sectional view the embodied BOP is shown, with an axial opening extending through the center, e.g., for placement over a borehole or wellbore. The depicted BOP is generally contiguous and roughly cylindrical in shape. Figure 1 depicts the BOP in an open position, while Figure 2 depicts the BOP in a closed position, e.g., after a closing operation has been executed. The BOP is actuated (e.g., toward a closed position) as hydraulic fluid flows under pressure through either a close port **30**, or through a multi-port valve **55**, in which case hydraulic fluid would flow through seal sub assembly **39,** through check valve **52**, and to the low pressure side **53** underneath the intensifier piston **56**. As hydraulic fluid flows to the low pressure side **53** under the intensifier piston **56**, pressure is exerted on the bottom of the intensifier piston **56**, thereby moving the intensifier piston **56** upward and exerting pressure on the intensified pressure chamber **68**, located above the intensifier piston **56**. Additionally, as intensifier piston **56** is forced upward, any gas or fluid contained in the intensifier gas accumulation chamber **70** can be compressed. In an embodiment, the intensifier gas accumulation chamber **70** can be filled with a compressible fluid or gas, such that the compression of the fluid or gas does not significantly impede the travel of intensifier piston **56**. Alternatively, such fluid or gas can be vented through a vent port vent port **28**, e.g., into the atmosphere and/or another region external to the BOP. In an embodiment, fluid or gas in

intensifier gas accumulation chamber **70** could be captured by an accumulating device (not shown). In another embodiment, gas or fluid can be retained in the intensifier gas accumulation chamber **70**, such that the compressed fluid can exert a downward force on intensifier piston **56**, e.g., to assist in an open operation after a closing operation has been executed.

[0037] As described previously, Figures 1-3 show a representative fastener **22** positioned in the lower left portion of the BOP; however, in various embodiments, a plurality of fasteners can be spaced about the circumference of the BOP to join the upper housing **34,** lower housing **38,** and gas booster reservoir housing **31** (if present) at multiple connection points.

[0038] The intensifier piston **56** can function to conceptually divide the housing into a low pressure side **53** (e.g., below intensifier piston **56)** and a high pressure side (e.g., the intensified pressure chamber **68** and portions of the BOP above the intensifier piston) caused by the relative difference in surface areas of the bottom of intensifier piston **56** and the portion of intensifier piston **56** disposed in the intensified pressure chamber **68**. In use, the hydraulic pressure of fluid on each side of the intensifier piston **56** varies in the same ratio, or proportion, of the larger geometric area (the bottom side of the piston) to the smaller area (the top side of the piston). For example, a desired intensified pressure can be achieved simply by constructing an intensifier piston and volumetric cavity to desired proportions, creating the desired ratio, or factor of intensified fluid pressure, as well as a desired volume of fluid.

[0039] Figures 3 and 4 depict exploded cross-sectional views of the left and right halves, respectively, of the BOP. In use, the "high pressure" hydraulic fluid in the intensified pressure chamber **68** can be forced through high pressure passageway **71** and through a seal sub assembly **58**, to the proximal or "close" side of the FIG. 3 and FIG. 4 piston ram shaft **18** (e.g. the side of the piston ram shaft **18** closest to the ball screw assembly **35**). This fluid in turn exerts pressure on and actuates the piston ram shaft **18**, causing the piston ram shaft to move inward toward the wellbore **64**, thereby advancing the attached ram block **14** inward for sealing and/or shearing of a wellbore tubular and/or the wellbore **64**. A closing operation, shown completed in FIG. 4, can result in sealing, or shearing and resultant sealing, depending on the ram block **14** configuration used. During a closing operation, hydraulic fluid can travel farther through the intensified pressure chamber **68** and into ram module **16** arriving at the base, or back side, of the piston ram shaft **18**, through seal sub assembly **61**, into the open port passageway **72**, and exit the upper BOP housing **34** at the open port **26**, to which a hydraulic pumping unit or accumulator device

(not shown) may be attached. When hydraulic fluid flows into the open port passageway **72,** the fluid entering the passageway can pass out of both opposing ram modules **16**. The passageway connected between both ram modules **16** is shown in Figures 1-4 as dashed line, which is also part of open port passageway **72.** In one embodiment, hydraulic fluid does not begin to flow into open port passageway **72** until the piston ram shaft **18** is fully deployed. In another embodiment, there a valve on open port **26** can be closed during a closing operation, then opened to release the pressure exerted on piston ram shaft **18** and permit movement of the ram shaft **18** in a reverse direction. Alternatively or additionally, such a valve could also be located in an external accumulator or hydraulic pumping unit.

[0040] When a gas booster reservoir **32** is used in lieu of the release of hydraulic fluid, the vent port **28** can be retained in a closed position to allow gas to accumulate in the intensifier gas accumulation chamber **70** rather than passing through the vent port **28**. Alternatively, the vent port **28** can be open to allow gas to flow therethrough at a desired pressure, e.g., into an accumulator device (not shown) or hydraulic pumping unit (not shown).

[0041] If the BOP has been activated and is in a closed position, as shown in FIG. 4, the BOP can be returned to an open position by retracting the ram block **14** and piston ram shaft **18**. For example, flow can be reversed from an external hydraulic pumping unit (not shown) or accumulator (not shown) to pass through the "open" port **26** and through the open port passageway **72** and seal sub assembly **61**, exert pressure on the "open" side of piston ram shaft **18** and actuate piston ram shaft **18** in an outward direction away from wellbore **64**, simultaneously retracting ram block **14** away from wellbore **64**. During an opening operation, hydraulic fluid can pass through high pressure passageway **71** and exert pressure on intensifier piston **56**, causing the intensifier piston to travel downward toward its starting or "open" position. If an external accumulator or capturing device (not shown) or hydraulic pumping unit (not shown) is used in association with the gas accumulation chamber **70**, travel of the intensifier piston **56** can possibly create a vacuum in the gas accumulation chamber **70**, resulting in fluid or gas being drawn in from the vent port **28**. The vent port **28** could also draw fluid from an ambient environment external to the BOP, e.g., in the absence of an external accumulator or pumping unit. At the conclusion of an opening operation, the piston ram shaft **18** and intensifier piston **56** can be returned to their or starting positions, as shown in FIG. 1 and FIG. 3.

[0042] Although the hydraulic actuation of the intensifier piston **56** can result in the application of a significant amount of force to the piston ram shaft **18** and ram block **14** in a sealing and/or shearing operation, a situation may arise in which an operator may wish to verify that a shearing and/or sealing operation has been completed successfully. For example, an operator may wish to verify that adequate force has been applied to shear any tubular of any material, and to obtain visual conversation that the ram blocks **14** have traveled a sufficient distance to ensure tubular shear.

[0043] Actuation of the intensifier piston **56** results in the entry of high pressure fluid in the intensified pressure chamber **68**, at a multiplied pressure of that of the fluid entering the "close" port **30** or multi-port valve **55**. Conventional ram BOPs may operate, for example, with ram cylinder input pressures of 5,000 psi, or a similar pressure. Depending on intensifier geometry used in the embodiments described herein, if an input pressure of 5,000 psi passes through the "close" port **30** or multi-port valve **55**, the resulting intensified pressure to actuate piston ram shaft **18** and ram block **14**, could be, for example, five times the pressure entering the "close" port (e.g., approximately 25,000 psi). Such pressures are unprecedented in the art of blowout preventers and far exceed the pressure required to shear any tubular currently known. Should an operator deem that hydraulic pressure alone may be, for any reason, inadequate to execute a tubular shearing operation, the gas booster reservoir **32** can be used to provide additional pressure to assist the hydraulics, provided the gas booster is charged at a higher pressure than the hydraulics. If used in this manner, the gas booster reservoir **32** can release gas through the multi-port valve **55** and apply additional pressure to the hydraulic fluid that has already entered through the "close" port **30**. Pressure from the gas booster reservoir **32** can similarly be multiplied by the intensifier piston, resulting in higher pressure in the intensified pressure chamber **68** and driving the piston ram shaft **18** and ram block **14**. The multi-port valve **55** releasing gas booster reservoir **32** gas can be actuated by any means, including, without limitation, mechanical, hydraulic, electrical, wireless and/or acoustic switching, with appropriate timing devices correlated to the flow through the "close" port **30** or flow through multi-port valve **55**. In an embodiment, the gas booster reservoir **32** can be adapted for remote actuation/operation, e.g., at the exterior of the BOP body itself, such as by an ROV (remotely operated vehicle). Therefore, the gas booster reservoir **32** can operate as a fail-safe, in addition to or in lieu of providing additional pressure for sealing/shearing operations.

[0044] Referring to FIG. 3 and FIG. 4, verification of successful sealing and/or shearing operation, and/or verification of function of the ram module **16** and piston ram shaft **18** in general, can be indicated by the position of a ram position indicator rod **37**. In the depicted embodiment, the position indicator is shown as a ball screw. The depicted ram position indicator rod **37** functions mechanically, and is comprised of a rod that may be contained inside a space in the center of piston ram shaft **18** and may be attached, in this inner space, to the edge of the piston ram shaft **18** closest to the ram block **14**. The ram position indicator rod **37** can move inward into the inner diameter of a roughly cylindrically shaped space in the piston ram shaft, and thus, follow piston ram shaft **18** during performance of a closing operation. As shown, the roughly cylindrically shaped space and walls within which position indicator rod **37** travels can include a hollow central portion of the piston ram shaft **18** and a portion of ram module **16.** The depicted ram position indicator rod **37** is roughly concentrically disposed relative to the center of the piston ram shaft **18.** In one embodiment, the ram position indicator rod **37** can include a ball screw or lead screw. In the case of a ball screw, the ball screw may be contained inside a space in the center of piston ram shaft **18** and, while not attached, may be in close proximity to the edge of the piston ram shaft **18** closest to the ram block **14**, and in an embodiment, could be permitted to touch the edge of the piston ram shaft **18.** In the case of a ball screw, during a closing operation, a motor operated by hydraulic fluid flow and pressure from the operation can force the ball screw inward into the roughly cylindrically shaped space, as high pressure hydraulic fluid forces the piston ram shaft **18** inward toward the wellbore **64**. As such, the ram position indicator rod **37** "follows" the ram block **14** inward toward the wellbore **64.** The ram position indicator rod **37** can be calibrated to travel inward in direct proportion to the distance the piston ram shaft **18** moves inward. The ram position indicator rod **37** can protrude externally from the upper housing **34** and provide a visual indication of a position of ram block **14** and piston ram shaft **18** position in relation to the BOP and the wellbore **64**. While FIG. 3 and FIG. 4 depict a ball screw that serves the function of ram position indicator rod **37**, with visible indication provided by how far the ball screw has traveled toward the wellbore **64**, other types of members capable of moving relative to other portions of the BOP and/or indicating the position of the ram piston can be used without departing from the scope of the present disclosure.

[0045] FIG. 9A depicts a side view of the exterior of the gas booster reservoir used in conjunction with the BOP shown in Figure 1, the reservoir including a housing with charge port

and multi-port valve. FIG. 9B shows a side, cross-sectional view of the gas booster reservoir. As described previously, in the event hydraulic fluid pressure is unavailable or undesired for use for any reason, the gas booster reservoir housing **31**, containing gas booster reservoir **32**, can be used. In an embodiment, the reservoir can be attached (e.g., bolted) to the lower housing **38**, and may be operated independently (e.g., independent of the hydraulic operation of the remainder of the BOP). As such, in various embodiments, a closing operation can be executed without use of external hydraulic pressure, e.g., via fluid entering the "close" port **30** or multi-port valve **55**, by instead utilizing fluid within the gas booster reservoir. For example, in a scenario where external hydraulic lines have been destroyed in an emergent incident, a self-contained, enclosed, integrated gas booster reservoir **32** can be actuated as described previously to release gas (or another fluid) through multi-port valve **55**, and can be filled and/or pressurized sufficiently that independent of external hydraulic pressure, the gas booster reservoir can supply sufficient pressure on its own, taking into account the pressure multiplication of the intensifier piston **56**, to seal and/or shear and seal the wellbore **64** tubulars or seal an open wellbore **64**. In various embodiments, the gas booster reservoir **32** can be designed for a single use, e.g., until the gas booster reservoir **32** is recharged through the gas charge port **50**. For example, while pressure may be bled off from the depicted gas booster reservoir to enable retraction of piston ram shaft **18** and ram block **14** to the open position shown in FIG. 1 and FIG. 3, the depicted gas booster reservoir **32** will not recharge through this process, but can be recharged through the gas charge port **50** to enable the gas booster reservoir to perform a subsequent closing operation. In other embodiments, however, the gas booster reservoir could be designed to receive reverse flow during an opening operation, to recharge automatically (e.g., via a compressor), and/or could be provided with sufficient gas and/or pressure to perform multiple closing operations. The depicted gas booster reservoir **32** is usable as an attachment to the BOP, which may be bolted and/or otherwise secured thereto, as shown in FIG. 1, FIG. 2, FIG. 3, FIG. 4, FIG. 6 and FIG. 7, utilizing sealing surface **48**, which can include, for example, a seal ring fitting snugly between gas booster reservoir housing **31** and lower housing **38**. In one embodiment, an applicable seal ring, not shown in detail, can have the shape of a contiguous, large washer, with appropriate adaptations for elastomeric or other sealing surfaces, and can extend from the outer circumference of the BOP at sealing surface **48** to the axial bore extending through the center over the wellbore **64**, with said seal ring also having a hole of similar or identical diameter

through the center thereof. While Figure 9B depicts the gas booster reservoir **32** having a cavity usable to contain compressed gas, in various embodiments, a gas booster reservoir could contain a manufactured, ready-made compressed gas cylinder or other compressed gas vessel, or a plurality of such cylinders or vessels. Such vessels could be configured and connected so as to charge and operate in the same or similar manner as the depicted gas booster reservoir **32.**

[0046] Referring to FIG. 5, a top, cross-sectional view of the BOP of Figure 1 is shown, illustrating opposing ram modules **16**, ram block **14** assemblies, retaining members **12** and the outer, round circumference of the BOP housing comprised in part by upper housing **34**. The wellbore **64** is visible in the approximate center of this overhead view.

[0047] As shown in FIG. 6 and FIG 7, in an embodiment, for ease of manufacturing, maintenance, assembly, and/or transport, an upper housing **34**, a lower housing **38**, and a gas booster reservoir housing **31** (if used) can be constructed separately (e.g., for subsequent assembly). The depicted upper housing **34** contains the ram module **16**, open port **26** (which may attach to an external accumulator (not shown) or hydraulic pumping unit (not shown)), intensifier piston **56** and high pressure passageway **71**. The upper housing **34** can provide for easy and fast access to the ram module **16** and any associated components, e.g., by removing the retaining member(s) **12** and extracting the ram module **16**. In an embodiment, the retaining components and/or ram module can be designed for removal using a ROV or other means (e.g., during subsea operations). As described previously, in various embodiments, the gas booster reservoir housing **31** can include a bolt-on module attachable to lower housing **38**. In an embodiment, the gas booster reservoir housing **31** may not be required for the BOP to function, e.g., using hydraulic actuation via "close" port **30**; however, the gas booster reservoir can add a failsafe measure, e.g., for redundancy and/or verification, and can also be used in conjunction with hydraulic actuation to provide increased pressure.

[0048] Referring to FIG. 3 and FIG. 4, when performing a closing operation under normal conditions, in one embodiment, hydraulic power can be used to actuate piston ram shaft **18** by flowing hydraulic fluid either from a line exiting the BOP itself or from an external source to power a hydraulic motor, which actuates the ball screw acting as ram position indicator rod **37**. As the closing operation initiates, the piston ram shaft **18** moves toward the wellbore **64** and stops its advancement when the two opposing ram blocks **14** reach the farthest extension point toward and/or into, the wellbore **64**. The advanced, seated ball screw, can contact the piston ram

shaft **18** functions, such that the ball screw functions not only as a ram position indicator rod **37**, but also serves to mechanically lock the piston ram shaft **18** and ram block **14** in the closed position, providing added assurance that the piston ram shaft **18** and ram block **14** cannot retract until actuated to do so. A variety of hydraulic configurations, including hydraulically operated motors, control, porting and redundant features, e.g., to enhance reliability, may accommodate ball screw assembly **35** to achieve desired function and fit. While use of a ball screw assembly **35** can add mass and/or slightly increase the footprint of the BOP, ball screw assemblies are generally significantly smaller than the ram cylinder extensions and boosters used with conventional BOPs. Other types of indicators, such as another type of mechanical indicator or screw, a mechanical or electronic counter with visible indicators actuated by motion of the ball screw and/or of the hydraulic motor, calibrated to indicate distance traveled by piston ram shaft **18**, could be used without departing from the scope of the present disclosure.

[0049] Referring to **FIG. 7**, a side view of the exterior of the BOP is shown, at a position located behind the ball screw, ball screw assembly **35** and piston ram shaft **18,** in which the gas charge port **50** and multi-port valve **55** are visible as well. The ram module **16** is shown retained in place by a retaining member **12**. The depicted retaining member includes retaining pins or screws **66** used to fix the retaining member **12** in place, thereby preventing lateral movement thereof; however any manner of connector can be used without departing from the scope of the present disclosure, and in various embodiments, retaining members able to be secured in place in the absence of connectors (e.g., via force/interference fit, snapping and/or locking features, etc.) can be used. Identical or similar retaining pins or screws **66** can be used to secure an identical or similar retaining member on the opposing side of the BOP, not visible in Figure 7. Removal of the retaining member(s) **12** can enable efficient access for removal or insertion of ram modules **16**. In an embodiment, the ram module **16** can be inserted or removed from the ram cavity **4** as a complete unit, containing all associated ram components. The retaining member(s) **12** function to retain the ram module **16** in a generally fixed position relative to the BOP, e.g., when the ram module is activated and the piston ram shaft **18** causes the ram module **16** to exert force radially outward from the wellbore **64** as the piston ram shaft **18** moves inward toward the wellbore **64**. As such, the retaining member **12** and ram module **16** can be sufficiently robust (e.g., comprised of sufficient mass and material strength) to withstand the forces created by the intensifier piston **56** during a closing operation.

[0050] BOP pressure control operations typically require an open access passageway extending through the entirety of the external BOP housing to the wellbore **64**. In the depicted embodiment, **FIG. 1, FIG. 2, FIG. 3, FIG. 4, FIG. 6 and FIG. 8** show a wellbore access passageway(s) **65** located on a side of the BOP, and in various embodiments, a wellbore access passageway could be located on each side of the lower housing **38**, e.g., placed roughly in opposition to one another. In an embodiment, an API studded flange connection can be utilized at the outer circumference of the BOP, e.g., at the opening of the wellbore access passageway **65**.

[0051] **FIG. 6** shows a side view of the exterior of the BOP, generally perpendicular to the length of the ram modules **16**, piston ram shafts **18** and ball screws acting as ram position indicator rods **37**. In an embodiment, the retaining members **12** can be used as lifting points, e.g., for maneuvering the BOP, and can be removed by removing retaining pins or screws **66** therefrom, as shown in FIG. 7, then pulling the retaining members **12** away from the BOP (e.g., laterally, outward from the drawing). In an embodiment, the retaining members and/or retaining pins/screws can be configured for access and manipulation by a ROV (e.g., during subsea operations), enabling remote removal of retaining members **12** and interchanging of ram modules **16**, e.g., as part of a maintenance operation.

[0052] As such, embodiments usable within the scope of the present disclosure can include a compact, stackable, high pressure, ram-type blowout preventer that is scalable in size (e.g., to accommodate various sizes of wellbores and associated equipment). Such BOPs can include a generally cylindrical upper and lower housing having an opening in the center through which at least one tubular may pass, e.g., for placement over a wellbore. An integrated intensifier can be positioned wholly within the BOP housing, having a low pressure side with greater surface area than a high pressure side, for actuation by hydraulic fluid or one or more gasses. In use, hydraulic fluid or gas exerts a force on the low pressure side, causing the high pressure side to exert a force on hydraulic fluid or one or more gasses gas, such that the fluid or gas at the high pressure side is at a higher pressure than fluid or gas at the low pressure side. As such, the fluid or gas on the high pressure side delivers an intensified pressure to hydraulic rams sufficient to perform a sealing and/or shearing operation.

[0053] In an embodiment, a BOP can include an insertable hydraulic ram module, held in place by retaining members or similar locking members, without the need for bonnets or doors.

[0054] In an embodiment, a BOP can include an attachable compressed gas reservoir. The gas reservoir could be usable to replace or supplement use of the hydraulic fluid or gas to enhance and/or independently perform a sealing and/or shearing operation.

[0055] In an embodiment, a BOP can include an indicator device (e.g., a mechanical indicator) usable to indicate the position of the hydraulic rams.

[0056] In an embodiment, a BOP can include a ball screw that is driven toward the wellbore as the hydraulic rams move during a sealing and/or shearing operation, such that the ball screw prevents unassisted retraction of the hydraulic rams, thereby impeding the hydraulic rams in the event of loss of pressure in the hydraulic fluid or gas used to drive the rams. The ball screw can be driven by a hydraulic motor that can be powered by hydraulic fluid on either the low or high pressure side of the intensifier and/or by an external fluid source. The ball screw can also function as an indicator device, usable to visually verify a position of the rams.

[0057] Embodied BOPs can be provided in stacks of two or more blowout preventers, and in various embodiments, can employ seal subs. In an embodiment, one or more interlocking "L" shaped fingers can act as locking connections and appropriate seals, enabling a first BOP to be stacked atop a second BOP, one of the BOPs having a plurality of "L" shaped protrusions while the other has a series of corresponding "L" shaped recessions/cutouts adapted to receive the protrusions. In use, after receiving the protrusions within corresponding recessions, one of the BOPs can be rotated relative to the other to lock the BOPs together. In an embodiment, a seal sub assembly can bridge the BOP surfaces, and the "L" shaped connections can be located behind the seal sub.

[0058] Although reference is made throughout the application to use of hydraulic fluid, it should be understood that any fluid, including liquids and gasses, could be employed without departing from the scope of the present disclosure. Furthermore, although discussed with specific reference to oil and/or gas wells, the disclosed subject matter has application in other areas that will be apparent to one skilled in the art after reading this disclosure, and this application is intended to include such other areas.

CLAIMS

1. An apparatus for containing pressure associated with a well, the apparatus comprising:

   a housing;

   a ram fluid chamber within the housing;

   a ram piston within the housing, wherein the ram piston comprises a first end engaged with a ram and a second end in communication with the ram fluid chamber, and wherein the ram piston is movable between a closed position in which the ram at least partially obstructs the well and an open position; and

   an intensifier piston within the housing, wherein the intensifier piston comprises a first end in communication with the ram fluid chamber and a second end in communication with a primary fluid source, and wherein the second end of the intensifier piston comprises a surface area larger than that of the first end of the intensifier piston,

   wherein, at a first pressure, fluid from the primary fluid source applies a force to the second end of the intensifier piston to move the intensifier piston, wherein movement of the intensifier piston applies a second pressure to fluid in the ram fluid chamber, wherein the second pressure is greater than the first pressure, and wherein the second pressure applies a force to the ram piston to urge the ram toward the closed position.

2. The apparatus of claim 1, wherein the ram piston and the intensifier piston are substantially in vertical alignment.

3. The apparatus of claim 1, wherein the ram piston is adapted for movement along a first axis and the intensifier piston is adapted for movement along a second axis, and wherein the second axis is perpendicular to the first axis.

4. The apparatus of claim 1, wherein the intensifier piston comprises a top side positioned opposite the second end of the intensifier piston and laterally offset from the first end of the intensifier piston, the apparatus further comprising a clearance space within the housing positioned above the top side and laterally offset from the first end of the intensifier piston for accommodating movement of the intensifier piston.

5. The apparatus of claim 4, wherein the intensifier piston is adapted to move in a first direction responsive to the force applied to the second end thereof by fluid from the primary fluid source thereby compressing fluid in the clearance space, and wherein the intensifier piston is adapted to move in a second direction responsive to force from compressed fluid in the clearance space in the absence of the force applied by the fluid from the primary fluid source.

6. The apparatus of claim 1, wherein the intensifier piston comprises an L-shaped half cross-sectional shape.

7. The apparatus of claim 1, further comprising a secondary fluid source within the housing and associated with the second end of the intensifier piston, wherein the secondary fluid source is actuatable to provide fluid to the second end of the intensifier piston at a pressure sufficient to cause movement of the ram independent of the primary fluid source.

8. The apparatus of claim 7, wherein the secondary fluid source comprises a gas reservoir, a gas generating material, or combinations thereof.

9. The apparatus of claim 8, wherein the gas reservoir is substantially in vertical alignment with the ram piston and the intensifier piston.

10. The apparatus of claim 1, wherein the housing comprises a generally circular horizontal cross-sectional shape.

11. The apparatus of claim 10, wherein the housing comprises a first portion containing the ram piston, wherein the first portion is adapted to contain the second pressure, and a second portion positioned below the first portion, wherein the second portion is attachable to the first portion in a plurality of rotational positions.

12. The apparatus of claim 1, further comprising an insertable retaining member for retaining the ram piston within the housing, wherein the insertable retaining member is outwardly movable in a lateral direction relative to the housing.

13. The apparatus of claim 12, wherein the ram piston is outwardly removeable in a lateral direction relative to the housing for accommodating repair, replacement, or maintenance thereof.

14. The apparatus of claim 1, further comprising a mechanical indicator engaged with the ram piston for verifying a position of the ram piston relative to the housing.

15. The apparatus of claim 14, wherein the mechanical indicator comprises an elongate member positioned within an orifice of the ram piston and movable relative thereto, a locking member movable inward relative to the ram piston to lock the ram piston in the closed position, or combinations thereof.

16. The apparatus of claim 1, further comprising a locking member movable to retain the ram piston in the closed position independent of pressure applied to the ram piston by fluid in the ram fluid chamber.

17. The apparatus of claim 1, wherein the intensifier piston is adapted to move in an upward direction responsive to the force applied to the second end thereof by fluid from the primary fluid source, and wherein the intensifier piston is adapted to move in a downward direction responsive to gravity in the absence of the force applied by the fluid from the primary fluid source.

18. An apparatus for containing pressure associated with a well, the apparatus comprising:

a ram piston comprising an end in communication with a fluid chamber;

an intensifier piston comprising a first end in communication with the fluid chamber and a second end in communication with an actuator, wherein the second end comprises a surface area greater than that of the first end; and

a housing containing the ram piston, the fluid chamber, and the intensifier piston,

wherein actuation of the actuator applies a first pressure to the second end of the intensifier piston to move the intensifier piston, and wherein movement of the intensifier piston applies a second pressure greater than the first pressure to the end of the ram piston to move the ram piston.

19. The apparatus of claim 18, wherein the housing comprises a generally circular horizontal cross-sectional shape.

20. An apparatus for containing pressure associated with a well, the apparatus comprising:

a housing comprising a generally circular cross-sectional shape;

a ram at least partially positioned within the housing;

a ram fluid chamber within the housing;

a ram piston within the housing, wherein the ram piston comprises a first end engaged with the ram and a second end in fluid communication with the ram fluid chamber;

an intensifier piston within the housing, wherein the intensifier piston comprises a first end in communication with the ram fluid chamber and a second end in communication with a primary fluid source, and wherein the second end of the intensifier piston comprises a surface area larger than that of the first end of the intensifier piston;

a clearance space within the housing, wherein the clearance space is adapted to accommodate movement of the intensifier piston,

wherein fluid from the primary fluid source applies a first pressure to the second end of the intensifier piston to move the intensifier piston in a first direction, wherein movement of the intensifier piston in the first direction applies a second pressure greater than the first pressure to fluid in the ram fluid chamber and compresses fluid in the clearance space, wherein the second pressure applied to fluid in the ram fluid chamber applies a force to the ram piston to urge the ram toward a closed position that at least partially obstructs the well,

and wherein the intensifier piston is adapted to move in a second direction opposite the first direction responsive to force from compressed fluid in the clearance space in the absence of the force applied by the fluid from the primary fluid source, and wherein movement of the intensifier piston in the second direction releases pressure from the ram fluid chamber to permit movement of the ram piston away from the closed position.