WHAT IS CLAIMED IS:

1. An apparatus comprising:

at least one processor; and

at least one non-transitory memory including computer program code, the at least one memory and the computer program code configured to, with the at least one processor, cause the apparatus to:

determine initiation for an uplink small data transmission for the apparatus;

trigger a report, where the report is triggered by the determined initiation for the small data transmission;

determine at least one predetermined condition;

based upon the at least one predetermined condition, determine to cancel the report triggered by the initiation for the small data transmission; and

transmit the uplink small data transmission.

2. The apparatus as claimed in claim 1, where the report comprises a power headroom report.

3. The apparatus as claimed in claim 1 or 2, where the at least one predetermined condition comprises the apparatus not expecting a subsequent transmission after the uplink small data transmission.

4. The apparatus as claimed in claim 1 or 2, where the apparatus is configured to determine that a subsequent

transmission after the uplink small data transmission is expected.

5. The apparatus as claimed in claim 1, where the at least one predetermined condition comprises both the report and another report are triggered and the another report being sent with the uplink small data transmission, where:

the report comprises a power headroom report and the another report comprises a buffer status report, or

the report comprises the buffer status report and the another report comprises the power headroom report.

6. The apparatus as claimed in claim 5, where the at least one memory and the computer program code are configured to, with the at least one processor, cause the apparatus to cancel the report relative to the another report for the uplink small data transmission based upon whether a subsequent transmission is expected by the apparatus.

7. The apparatus as claimed in claim 1, where the report comprises a buffer status report.

8. The apparatus as claimed in claim 7, where the at least one memory and the computer program code are configured to, with the at least one processor, cause the apparatus to determine whether to cancel another report based upon the at least one predetermined condition.

9. The apparatus as claimed in claim 8, where the at least one memory and the computer program code are configured to, with the at least one processor, cause the apparatus to cancel the report when the apparatus has determined that a subsequent transmission is not expected after the uplink

small data transmission and after the apparatus determined that a buffer status report has been cancelled.

10. The apparatus as claimed in claim 8, where the another report comprises a power headroom report.

11. The apparatus as claimed in claim 1 or 2, where the at least one predetermined condition comprises a condition where a single-shot uplink small data transmission is allowed.

12. The apparatus as claimed in claim 1 or 2, where the at least one predetermined condition comprises a condition where a single-shot uplink small data transmission is supported by the apparatus.

13. The apparatus as claimed in claim 1 or 2, where the at least one predetermined condition comprises when an available power headroom for a serving cell is above a threshold.

14. The apparatus as claimed in claim 1 or 2, where the at least one memory and the computer program code are configured to, with the at least one processor, cause the apparatus to prevent cancelling of the report when the apparatus applies a power backoff to meet maximum permissible exposure.

15. The apparatus as claimed in claim 1 or 2, where the at least one memory and the computer program code are configured to, with the at least one processor, cause the apparatus to cancel the report based upon the determination to cancel the report.

16. The apparatus as claimed in any one of claims 1-15, where the at least one memory and the computer program code

are configured to, with the at least one processor, cause the apparatus to receive instructions from a network entity to be used to at least partially determine the at least one predetermined condition.

17. A method comprising:

determining initiation for an uplink small data transmission for a user equipment;

triggering a report, where the report is triggered by the determined initiation for the small data transmission;

determining at least one predetermined condition;

based upon the determined at least one predetermined condition, determining to cancel the report triggered by the initiation for the small data transmission; and

transmitting the uplink small data transmission.

18. An apparatus comprising:

at least one processor; and

at least one non-transitory memory including computer program code, the at least one memory and the computer program code configured to, with the at least one processor, cause the apparatus to:

determine information of at least one predetermined condition to cause a user equipment, after an uplink small data

transmission has been determined to be initiated, to perform at least one of:

cancel a report triggered by the initiation for the small data transmission, or

prevent triggering of the report to accompany the small data transmission; and

transmit the information to the user equipment.

19. An apparatus comprising:

at least one processor; and

at least one non-transitory memory including computer program code, the at least one memory and the computer program code configured to, with the at least one processor, cause the apparatus to:

determine initiation for an uplink small data transmission for the apparatus;

determine at least one predetermined condition;

based upon the at least one predetermined condition and the determined initiation for the small data transmission, determine to have a report triggered; and

transmit the uplink small data transmission.

20. An apparatus comprising:

at least one processor; and

at least one non-transitory memory including computer program code, the at least one memory and the computer

program code configured to, with the at least one processor, cause the apparatus to:

determine initiation for an uplink small data transmission for the apparatus;

determine at least one predetermined condition;

based upon the at least one predetermined condition, determine whether to transmit a report with the uplink small data transmission, where the report is configured to be at least partially triggered by the determined initiation for the small data transmission; and

transmit the uplink small data transmission.