(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
16 January 2003 (16.01.2003)

PCT

(10) International Publication Number
WO 03/005438 A2

(51) International Patent Classification[7]: H01L 21/768

(21) International Application Number: PCT/US02/20704

(22) International Filing Date: 25 June 2002 (25.06.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/302,469 2 July 2001 (02.07.2001) US

(71) Applicant *(for all designated States except US)*: **DOW CORNING CORPORATION** [US/US]; 2200 West Salzburg Road, P.O. Box 994, Midland, MI 48686-0994 (US).

(72) Inventors; and

(75) Inventors/Applicants *(for US only)*: **MEYNEN, Herman** [BE/BE]; Hazenpad, 15, B-3210 Lubbeek (BE). **WEIDNER, William, Kenneth** [US/US]; 1516 6th Street, Bay City, MI 48708 (US). **IACOPI, Francesca** [IT/BE]; Ljzerenmolenstraat 154/24, B-3001 Leuven (BE). **MALHOUITRE, Stephane** [FR/BE]; Alfons Roelandtsstraat 5, B-3010 Kessel-lO (BE).


(74) Common Representative: **BROWN, Catherine, U.**; Intellectual Property Dept.-Mail CO1232, Dow Corning Corporation, 2200 West Salzburg Road, P.O. Box 994, Midland, MI 48686-0994 (US).

(81) Designated States *(national)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.

(84) Designated States *(regional)*: ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent

[Continued on next page]

(54) Title: IMPROVED METAL BARRIER BEHAVIOR BY SIC:H DEPOSITION ON POROUS MATERIALS



(57) Abstract: A sealing dielectric layer is applied between a porous dielectric layer and a metal diffusion barrier layer. The sealing dielectric layer closes the pores on the surface and sidewalls of the porous dielectric layer. This invention allows the use of a thin metal diffusion barrier layer without creating pinholes in the metal diffusion barrier layer. The sealing dielectric layer is a CVD deposited film having the composition $Si_xC_y:H_z$.

WO 03/005438 A2

(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for all designations*

— *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)*

— *of inventorship (Rule 4.17(iv)) for US only*

Published:

— *without international search report and to be republished upon receipt of that report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.