

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : A47L 13/24	A1	(11) International Publication Number: WO 97/06722 (43) International Publication Date: 27 February 1997 (27.02.97)
---	-----------	---

(21) International Application Number: PCT/EP96/01982

(22) International Filing Date: 10 May 1996 (10.05.96)

(30) Priority Data:
95202243.2 18 August 1995 (18.08.95) EP

(34) Countries for which the regional or international application was filed: ES et al.

(71) Applicant (for all designated States except US): MINNESOTA MINING AND MANUFACTURING COMPANY [US/US]; 3M Center, P.O. Box 33427, Saint Paul, MN 55133-3427 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): CABRERO GOMEZ, Estrella [ES/ES]; 3M España S.A., Fabrica De Rivas Del Jarama, Apartado 25, E-28529 Madrid (ES). CELADA GUTIERREZ, Juan, Jose [ES/ES]; 3M España S.A., Fabrica De Rivas Del Jarama, Apartado 25, E-28529 Madrid (ES). GUILLEN LOPEZ, Alfonso [ES/ES]; 3M España S.A., Fabrica De Rivas Del Jarama, Apartado 25, E-28529 Madrid (ES). BARANDIARAN ALDASORO, Felipe [ES/ES]; 3M España S.A./N.V., Fabrica De Rivas Del Jarama, Apartado 25, E-28529 Madrid (ES). MARTIN RIVERA, Carmen

[ES/ES]; 3M España S.A., Fabrica De Rivas Del Jarama, Apartado 25, E-28529 Madrid (ES).

(74) Agent: HILL, Cecilia, A.; 3M Europe S.A./N.V., Hermeslaan 7, B-1831 Diegem (BE).

(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: MOPS

(57) Abstract

A strip mop has a head (101) comprising a holder (103) which is attached to the mop handle (104) and in which a replaceable strip assembly (126, Fig. 21) is located. The strip assembly is formed from layers of absorbent web material cut into strips (102) over part of their length, the uncut parts being located in the holder (103). When the strips (102) become worn, the holder (103) is opened (Fig. 18) so that the strip assembly (126) can be removed and replaced by another.

