

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
5 July 2007 (05.07.2007)

PCT

(10) International Publication Number
WO 2007/074470 A1

(51) International Patent Classification:
C09J 7/02 (2006.01) *G06F 3/02* (2006.01)

(21) International Application Number:
PCT/IN2006/000126

(22) International Filing Date: 27 March 2006 (27.03.2006)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
1625/MUM/2005
27 December 2005 (27.12.2005) IN

(71) Applicant (for all designated States except US): **PRS SOLUTIONS PRIVATE LIMITED** [IN/IN]; 63, Bombay Samachar Marg., Mumbai 400 001, Maharashtra State (IN).

(72) Inventors: **MANNA, Prafulla, Kumar**; 251/252, Garden Court, LBS Marg, Ghatkopar (west), Mumbai 400 086, Maharashtra State (IN). **SHENOY, Nityananda, Shekar**; 3/11, Jagdish Kunj, Rafi Ahmed Kidwai Road, Wadala, Mumbai 400 031, Maharashtra State (IN). **SHROFF, Pradip, Hiralal**; 1802, Wallace Apartments, Slater Road, Mumbai 400 007, Maharashtra State (IN).

(74) Agent: **SHAH BHARAT SHANTILAL**; 1, God's Gift, St. Francis Road, Vile-Parle (West), Mumbai 400 056, Maharashtra State (IN).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))
- of inventorship (Rule 4.17(iv))

Published:

- with international search report
- with amended claims and statement

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: HEAT SENSITIVE, SOLVENT SENSITIVE, TEMPER EVIDENT, MULTIPURPOSE SECURITY LABEL AND THE METHOD OF MANUFACTURING THE SAME

(57) Abstract: A method of manufacturing "heat sensitive, solvent sensitive, tamper evident multi purpose security label" comprising coating the formulated compound to constitute a film on a double sided silicone resin coated substrate and thereafter coated with high tack adhesive on double side silicone resin coated substrate and then by laminating the said film is slitted to desired length and size.



WO 2007/074470 A1

SUMMARY OF THE INVENTION

Fraudsters are a constant source of grave concern to brand owners since they are involved in counterfeit, retail theft, parallel trading, brand piracy and product tampering. Billions of dollars are invested every year in building reputed brands and the importance for protecting the same against the ever present threat posed by counterfeiters and forgers is increasingly being recognized. Huge sum of money is invested in promoting and building a brand through extensive painstaking and complex marketing plans goes down the drains due to brand piracy. The recent breed of fraudsters are armed with sophisticated manufacturing and detecting equipments coupled with enhanced technical knowledge. Hence, in the light of these facts, the traditional security measures adopted by brand owners are of little help in the current scenario. The need of the hour is requirement of a foolproof solution to curb this menace.

As a positive step towards providing a solution to tackle this issue a method is developed of using a unique label to prevent this illegal activity. The present invention provides a "Guaranteed" solution to brand owners, various industries manufacturing their products, components, parts, assemblies and users of such products, instruments such as energy meters etc. to safeguard their brands by curbing pilferage and vandalism by counterfeiters and subsequently avoid massive revenue losses. This product offers a perfect balance of advanced effectiveness versus the cost for the same.

The present invention relates to the development and process of manufacturing of tamper evident, destructible with temperature and solvent sensitive (destructible) film having inherent property of exhibiting different coloured glow when exposed to UV light or optionally in-built silver/bronze or other sparkling colour. This film is print-receptive and can be easily printed with water based printing inks, invisible and other security inks available in the market.

This product is formulated by a combination of thermoplastic Acrylic polymer with a vinylic copolymer in ratios of 10:3 to 10:1 to form a paste made in regular aromatic solvent. This paste is coated on a double sided silicone resin coated substrate by

conventional method of coating equipment to form a uniform film. The film formed thereafter has a thickness of 80 to 115 microns. The film has a special property of being strong enough to facilitate dispensing in its final (label) form at the same time strength low enough to prevent its removal from the substrate without tearing in the end product form. This film is coated with a special high tack adhesive by the transfer adhesive technique to convert the film into a self-adhesive which forms the basic raw material for the manufacturing of the said tamper evident, destructible with heat and solvent destructible labels. For achieving this the high tack adhesive is coated on double sided silicone resin coated substrate and laminated with the said film. The double sided silicone resin coated substrate utilized for the first step of film forming is removed by rewinding the stock on the mechanical rewinder to get the heat sensitive, solvent sensitive, tamper evident multi purpose security label (SURECOM) .

The process of applying the high tack adhesive is by conventional method of coating equipment followed by using known drying-methods. This special high tack adhesive is capable of adhering to regular substrates as well as low energy surfaces like polypropylene polyethylene etc. The special high tack adhesive is manufactured by blending various materials comprising natural and/or synthetic rubbers, tackifying resins of natural/synthetic type, antioxidants followed by solvating with hydrocarbon/ aromatic solvents to form a compound of proper consistency to facilitate coating and texture commensurate to the coating equipment. This special high tack adhesive of the present invention includes a tackifier which can be formed of hydrocarbon resins, rosin and rosin derivatives, polyterpenes, coumarone-indene resins, any compatible conventional tackifier or mixtures thereof along with mineral oils which are used as plastisizers.

The material used for the double sided silicone resin coated substrate could be papers like Glassine, Kraft or polymeric films like Polyester, Polyethylene, Polyvinyl Chloride etc or polycoated papers.

The stock formed herewith utilizing the aforesaid technique and ingredients is utilized as the basic raw material which goes into the making the novel labels. For achieving this,

the heat sensitive, solvent sensitive, tamper evident multi purpose Security Label (SURECOM) is slit in to desired width.

The following is the schematic representation of the construction of the heat sensitive, solvent sensitive, tamper evident multi purpose Security Label (SURECOM):

FFFFFFFFFFFFFFFFF ----- Tamper evident, heat sensitive,
solvent sensitive film.

AAAAAAAAAAAAAAAAA ----- High tack adhesive

LLLLLLLLLLLLLLLL-----Double sided Silicone resin
coated substrate