

312837.02

ARCHIVING DATA IN A VIRTUAL APPLICATION ENVIRONMENT

BACKGROUND OF THE INVENTION

Losing data is an unfortunate reality for many computer users. Data can be lost under a variety of conditions and circumstances. Hardware failure, malicious or accidental deletion are common culprits for data loss. To compensate or protect oneself
5 against loss in these circumstances, many computer users wisely create duplicate, backup copies of important data and/or programs.

Unfortunately, there are also many ways in which data may become lost irrespective of whether a valid backup copy of the data has been made and is available.
10 In particular, over time the programs, the operating systems, and/or the hardware become no longer available. When this occurs, a computer user cannot access critical data, even when an otherwise viable backup copy of that data exists.

For example, data may be stored by a proprietary database and then archived. At some time later, when that data is needed, the proprietary database program (or the
15 operating system that supports that database program, or the hardware upon which that operating system runs) is no longer available or in use. Thus, even though the database has been maintained as a valid archive, the contents of the database are inaccessible.

There are, of course, niche markets that specialize in retrieving data created by and/or stored on archaic computer systems or software. Their techniques vary widely.
20 One technique is to maintain old computer hardware, operating systems, and software. Another, widely divergent technique involves "cracking open" the data stored by proprietary systems, extracting it using sophisticated software techniques and expertise. In all cases, there is a substantial expense for retrieving data that has been archived but

312837.02

whose corresponding programs, operating systems, or hardware is no longer readily available.

SUMMARY OF THE INVENTION

According to aspects of the present invention, a computer system suitable for
5 archiving data with a corresponding application program in a virtual application
environment is presented. The computer system includes a processor, a memory, and a
storage. The computer system also includes an operating system, data to be archived, and
an application program that correspond to the data, such that the application program can
operate on the data. The computer system also includes a virtual application environment
10 generator. An example of a virtual application environment generator is Microsoft
Corporation's Virtual Server Migration Tool. In response to an instruction to archive the
data, the virtual application environment generator generates a virtual application
environment. The virtual application environment comprises the data, the corresponding
application program, and the operating system.

15 According to additional aspect of the present invention, a computer-readable
medium bearing computer-executable instructions is presented. When executed on a
computer system, the computer-executable instructions carry out a method for archiving
data in a virtual application environment. The method comprises receiving a request to
archive the data. A virtual application environment is then generated. The virtual
20 application environment includes the data, an application program suitable for operating
on the data, and an operating system suitable for supporting the execution of the
application program. The virtual application environment is the stored in storage.

According to yet further aspects of the present invention, a method for archiving
data in a virtual application environment is presented. The method comprises receiving a
25 request to archive data. A virtual application environment is then generated. The virtual
application environment includes the data, an application program suitable for operating
on the data, and an operating system suitable for supporting the execution of the
application program. The virtual application environment is the verified to determine
whether it is suitable for execution on a virtual machine corresponding to a computer
30 system upon which the operating system and the application program can function. If the

312837.02

virtual application environment is suitable for execution on the virtual machine, the virtual application environment is then stored in a storage.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing aspects and many of the attendant advantages of this invention will become more readily appreciated as the same become better understood by reference to the following detailed description, when taken in conjunction with the accompanying drawings, wherein:

FIGURE 1 is a block diagram illustrating an exemplary operating environment suitable for implementing aspects of the present invention;

FIGURE 2 is a block diagram illustrating an exemplary computer system suitable for archiving data into a virtual operating environment;

FIGURE 3 is a flow diagram illustrating an exemplary routine for archiving data according to aspects of the present invention; and

FIGURE 4 is a flow diagram illustrating an exemplary routine for retrieving archived data from an virtual application environment.

DETAILED DESCRIPTION

FIGURE 1 is a block diagram illustrating an exemplary operating environment 100 suitable for implementing aspects of the present invention. The exemplary operating environment 100 includes a computer system 102, shown in FIGURE 1 in logical layers for illustration purposes. In particular, the exemplary computer system 102 includes a hardware layer 104, an operating system layer 106, and an application layer 108.

The hardware layer 104 includes components such as the processor, memory, mass storage (such as hard drives, optical drives, and the like), graphics display subsystems, and the like. The operating system layer 106, as the name suggests, includes the operating system which supports the application layer 108. This layer also typically includes configuration settings, including user preferences and program settings for application programs in the application layer. The application layer 108 includes software programs and/or services such as application programs 110 and 112, as well as the supporting files, user created data (114 and 116), and the like.

312837.02

While FIGURE 1 illustrates the applications 110 and 112 as single modules, those skilled in the art will appreciate that almost all application programs are typically not monolithic bodies of code. Instead, application programs are typically comprised of various components, including code modules, text modules, data files, resources, configuration files, and the like. Thus, the illustration of application programs 110 and 112 (and others throughout the following discussion) as single component entities should be viewed as a logical construct for illustration purposes, and should not be viewed as limiting upon the present invention.

In addition to application program components, as a product of using most application programs, users typically create data files 114 and 116. In fact, such data files are typically what is most important to the user. More particularly, the application program, if corrupted or deleted from a computer system, can typically be restored from the media with which the user was provided when the application program was purchased. However, the data files created by the application programs, such as data files 114 and 116, are the product of user interactions and creations, and as such, are unique and should be preserved against accidental, malicious, or inadvertent loss.

According to aspects of the present invention, in order to preserve the data files such that they can be used at a future time when the application program, operating system, and/or hardware is no longer available or useable, the data files are archived in a virtual operating environment 122 which can be stored on media such as optical disks, hard drives, or other backup services such as online storage. The virtual operating environment 122 includes the operating system and application programs necessary to operate on the co-archived data files.

According to aspects of the present invention, the virtual operating environment 122 is generated such that it can be executed on a virtual machine. As those skilled in the art will appreciate, a virtual machine is an abstraction of computer hardware, implemented in software, that can then be executed on other computer hardware. Generating and using virtual machine technology is known in the art. For example, Microsoft Corporation's Virtual Server Migration Tool is one example of a product that generates a virtual machine. As shown in FIGURE 1, the virtual machine 124 is generated by a virtual machine generator 126. While not shown, the

312837.02

virtual machine 124 may be stored on any number of backup or storage targets including, but not limited to, magnetic tape, hard disk storage, optical media, and the like.

By generating the virtual operating environment to run on a virtual machine, such as virtual machine 124, it is no longer necessary to maintain the computer hardware 104 in order to access the data generated by obsolete application programs. Thus, after years have passed and the hardware, the operating system, and the application programs are no longer commercially available, the archived data, such as data file 114 or 116, is still accessible. Using the virtual machine technology, implementing a virtual machine 124 corresponding to the hardware from which the virtual operating environment 122 was generated, the data is accessible on virtually any computer hardware running any operating system.

In order to ensure that the virtual operating environment 122 can later be executed, in one embodiment, the virtual operating environment includes information identifying the virtual machine platform, i.e., the corresponding computer hardware from which the virtual operating environment was generated.

The virtual operating environment 122 is created using a virtual operating environment generator 118 that converts the data files, the application program or programs, and the operating system into the virtual operating environment 122. In particular, virtual operating environment generator 118 determines which components (especially with regard to a particular application program) need to be included in the virtual operating environment 122 such that the application program corresponding to the subject matter data file can operate.

According to one embodiment, the virtual operating environment generator 118 includes all application programs and the operating system on the computer system 102 into the virtual application environment 122, thereby ensuring that all components of the application program corresponding to the subject matter data file are included. Alternatively, the virtual operating environment generator 118 uses an application manifest 120 that identifies the components of an application program that should be included in the virtual application environment 122. Of course, other information may also be used to determine the components of an application program, such as installation manifests, operating system registry information, and the like.

312837.02

In at least one embodiment of the present invention, the virtual application environment 122 is generated such that it operates as a bootable device. In other words, the virtual application environment 122 can function as the boot device of actual computer hardware, or of a virtual machine.

5 FIGURE 2 is a block diagram illustrating an exemplary computer system 200 suitable for archiving data into a virtual operating environment 122. In particular, the computer system 200 includes computer hardware 104, an operating system 106, one or more application programs 110 and 112, as well as corresponding data files 114 and 116. As shown in FIGURE 2, the computer hardware includes a processor 202, a memory 204,
10 and a storage 206. Of course, as those skilled in the art will appreciate, these hardware components are illustrative of the many components that make up the computer hardware, and should not be viewed as limiting upon the present invention.

The exemplary computer system 200 also includes a virtual application environment generator 118. As indicated above, the virtual application environment
15 generator 118 combines the data file, such as data file 114, with its corresponding application program and the operating system operating on the computer hardware 104, into a virtual application environment 122 (FIGURE 1). However, it should be appreciated that while the virtual application environment generator 118 is illustrated as residing upon the exemplary computer system 200, in an alternative embodiment, the
20 virtual application environment generator is on an external computer system, and configured to operated remotely on the exemplary computer system 202.

FIGURE 3 is a flow diagram illustrating an exemplary routine 300 for archiving data in a virtual application environment 122 according to aspects of the present invention. Beginning at block 302, a request to archive a data file is received. At
25 block 304, the application program (or programs) associated with the data file, its components and associated files, are identified. As discussed above, the application program's components may be identified using an application manifest 120, using computer system settings such as registry entries, using installation manifests, and the like.

30 In an alternative embodiment, a request to archive a volume may be received. As those skilled in the art will appreciate, a volume may include any number of data files, some of which created by disparate application programs. Thus, similar to the logic

312837.02

described above, an exemplary routine would identify, for each data file in the volume to be archived, the corresponding application program (or programs) for inclusion in the virtual application environment 122.

At block 306, the virtual application environment 122, including the identified application program components, the data file, and an operating system capable of operating the application program is generated. The virtual application environment 122 may also include information identifying the virtual machine or actual computer hardware upon which the virtual application environment can execute.

At decision block 308, the virtual application environment 122 is optionally validated to determine whether it can be executed on a virtual machine corresponding to the computer hardware from which the components of the virtual application environment were generated. If the virtual application environment 122 proves invalid, at block 310 an error is reported, and thereafter the routine 300 terminates.

If the virtual application environment 122 is properly validated, at block 312, the virtual application environment is stored. Thereafter, the routine terminates.

It should be appreciated that while the above description of routine 300 treats the data file as a single object, in fact the data to be archived may comprise a plurality of files and components, and the present invention should not be construed as limited to archiving a single data file in the virtual application environment 122.

FIGURE 4 is a flow diagram illustrating an exemplary routine 400 for retrieving archived data from a virtual application environment 122. Beginning at block 402, a request to restore data from a virtual application environment 122 is received. At block 404, the virtual application environment 122 is obtained.

At block 406, information regarding the virtual machine 124 corresponding to and necessary to support the virtual application environment 122 is obtained. At block 408, the virtual machine 124 corresponding to virtual application environment 122 is executed (if it is not already executing). Of course, as discussed earlier, the virtual application environment 122 may be executed on a virtual machine 124, or alternatively, on computer hardware (not shown) corresponding to the original computer hardware on which the virtual application environment 122 was generated.

312837.02

Executing the virtual application environment 122 may involve booting the virtual application environment upon the virtual machine. In such case, the virtual application environment 122 should be configured to operate as a bootable device.

5 Once the virtual application environment 122 is executing, at block 410, the application program corresponding to the data file which is to be retrieved is executed. At block 412, the data is extracted using the corresponding application program, either in an automated manner, or at the direction of a computer user. Thereafter, the routine 400 terminates.

10 While the preferred embodiment of the invention has been illustrated and described, it will be appreciated that various changes can be made therein without departing from the spirit and scope of the invention.

312837.02

The embodiments of the invention in which an exclusive property or privilege is claimed are defined as follows:

1. A computer system for archiving data with its corresponding application program in a virtual application environment, the computer system comprising:

a processor;

a memory; and

a storage;

wherein the computer system includes an operating system, data to be archived, and a corresponding application program suitable for operating on the data;

and wherein the computer system also includes a virtual application environment generator that, in response to a instruction to archive the data, generates a virtual application environment comprising the data, the corresponding application, and the operating system.

2. The computer system of Claim 1, wherein the virtual application environment is generated to operate on a virtual machine corresponding to the computer system.

3. The computer system of Claim 2, wherein the virtual application environment is further generated to operate as a bootable device on a virtual machine corresponding to the computer system.

4. The computer system of Claim 2, wherein the virtual application environment includes information that identifies the virtual machine upon which the virtual application environment can operate.

5. The computer system of Claim 1, wherein the computer system further includes a plurality of application programs, and wherein the virtual application environment is generated to include all of the application programs from the computer system.

6. The computer system of Claim 1, wherein the computer system further includes a plurality of application programs, and wherein the virtual application

312837.02

environment generator generates the virtual application environment such that only the corresponding application program is included with the operating system and data.

7. The computer system of Claim 6, wherein virtual application environment generator determines which of the plurality of application programs is the corresponding application program according to an application manifest.

8. The computer system of Claim 7, wherein the corresponding application program comprises a plurality of components distributed on the computer system, and where the virtual application environment generator identifies the components of the corresponding application program and includes them as the corresponding application program in the virtual application environment.

9. A computer-readable medium bearing computer-executable instructions which, when executed on a computer system, carry out a method for archiving data in a virtual application environment, the method comprising:

receiving a request to archive data;

generating a virtual application environment, wherein the virtual application environment includes the data, an application program suitable for operating on the data, and an operating system suitable for supporting the execution of the application program; and

storing the virtual application environment in a storage.

10. The computer-readable medium of Claim 9, wherein the virtual application environment is generated for execution on a virtual machine corresponding to the computer system.

11. The computer-readable medium of Claim 10, wherein the virtual application environment is further generated to operate as a bootable device when executed on a virtual machine corresponding to the computer system.

12. The computer-readable medium of Claim 12, wherein the virtual application environment is further generated to include information for identifying the virtual machine upon which the virtual application environment may be executed.

312837.02

13. The computer-readable medium Claim 9, wherein the method further comprises verifying whether the generated virtual application environment is executable on a virtual machine corresponding to the computer system.

14. The computer-readable medium of Claim 9, wherein the virtual application environment is generated to include a plurality of application programs installed on the computer system, and wherein at least one of the plurality of application programs is suitable for operating on the data.

15. The computer-readable medium Claim 9, wherein the method further comprises identifying an application program suitable for operating on the data according to an application manifest, and including the identified application program in the virtual application environment.

16. A method for archiving data in a virtual application environment, the method comprising:

receiving a request to archive data;

generating a virtual application environment, wherein the virtual application environment includes the data, an application program suitable for operating on the data, and an operating system suitable for supporting the execution of the application program;

verifying whether the virtual application environment is suitable for execution on a virtual machine corresponding to a computer system upon which the operating system and the application program can function; and

storing the virtual application environment in a storage if the virtual application environment is suitable for execution on the virtual machine.

17. The method of Claim 16, wherein the virtual application environment is further generated to operate as a bootable device when executed on a virtual machine corresponding to the computer system.

18. The method of Claim 17, wherein the virtual application environment is generated to include a plurality of application programs installed on the computer system, and wherein at least one of the plurality of application programs is suitable for operating on the data.

312837.02

19. The method of Claim 17 further comprising identifying an application program suitable for operating on the data according to an application manifest, and including the identified application program in the virtual application environment as the application program suitable for operating on the data.

20. The method of Claim 16 wherein the data to be archived comprises a plurality of data files corresponding to at least two distinct application programs, and wherein the method further comprises for each data file in the data to be archived, identifying a corresponding application program suitable for operating on the data file, and wherein generating the virtual application environment further comprises generating the virtual application environment to include the identified application programs suitable for operating on each data file in the data to be archived.