

METHODS AND SYSTEMS FOR CONTROLLING THE PRODUCTS OF COMBUSTION

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of U. S. Provisional Application No.
5 61/105,331 filed October 14, 2008.

FIELD OF THE INVENTION

[0002] Embodiments of the invention relate to methods and systems for controlling the products of combustion. More particularly, methods and systems for obtaining substantially stoichiometric combustion in an oxy-fuel type combustion reaction are provided.

10

BACKGROUND OF THE INVENTION

[0003] This section is intended to introduce various aspects of the art, which may be associated with exemplary embodiments of the present disclosure. This discussion is believed to assist in providing a framework to facilitate a better understanding of particular aspects of the present invention. Accordingly, it should be understood that this section
15 should be read in this light, and not necessarily as admissions of prior art.

[0004] Some approaches to lower CO₂ emissions include fuel de-carbonization or post-combustion capture. However, both of these solutions are expensive and reduce power generation efficiency, resulting in lower power production, increased fuel demand and increased cost of electricity to meet domestic power demand. Another approach is an oxy-
20 fuel gas turbine in a combined cycle. However, there are no commercially available gas turbines that can operate in such a cycle.

[0005] The original oxy-fuel concept is based on the combustion of hydrocarbons with pure oxygen, which results in extremely high temperatures. Such high temperatures lead to problems in combustor life and also the development of Polycyclic Aromatic Hydrocarbons (PAHs), which lead to soot production. Numerous solutions to these issues have been
25 attempted with varying levels of success, including using carbon dioxide as a mass flow gas through the turbine instead of air. However, this approach and others require specialized turbine equipment that is not yet commercially available.

[0006] U.S. Pat. No. 5,724,805 discloses a power plant having a gas turbine fueled by
30 hydrocarbons mixed with an oxygen/carbon dioxide mixture. However, the disclosure states that the O₂/CO₂ mixture has more O₂ than air and therefore burns at very high temperatures requiring a large combustor chamber to allow time for the combustion gasses to gradually cool so less carbon monoxide (CO) is produced. As such, a specialized, non-standard combustor must be used for the techniques in the '805 reference to be practiced.

[0007] As such, there is still a substantial need for methods and systems to effectively control the temperature and composition of combustion product streams.

SUMMARY OF THE INVENTION

[0008] One embodiment of the present invention discloses a combustion control system.

5 The combustion control system comprises a combustor consisting of at least a primary combustion zone and a burnout zone; a high concentration carbon dioxide (CO₂) supply (the diluent supply); an oxygen supply stream configured to combine with at least a first portion (the primary diluent flow) of the high concentration CO₂ stream to form an oxygenation stream substantially comprising oxygen and CO₂ and having an oxygen to CO₂ ratio; and a
10 combustion fuel stream with a flow and a composition. The system further includes a combustor configured to mix and combust the oxygenation and combustion fuel streams within a primary combustion zone and a burnout zone in which a second part of the diluent supply (the secondary diluent) is added to form combustion products stream with a temperature and a composition; at least one temperature sensor configured to measure the
15 temperature of the combustion products stream after the exit of the combustor, wherein the temperature of the combustion products stream is used to adjust the flow rate of the secondary diluent to obtain the desired temperature at the exist of the combustor; and at least one oxygen analyzer configured to measure the amount of oxygen in the composition of the combustion products stream, wherein the amount of oxygen in the combustion product is
20 used to regulate the flow rate of the oxygen supply stream to achieve substantially stoichiometric combustion.

[0009] In some embodiments, the combustion fuel stream may be comprised of at least a high quality fuel gas stream, a low heating value fuel gas stream, and optionally, a high concentration CO₂ makeup stream. The separate streams may be operatively connected to a
25 summation controller connected to the flow controllers for the individual streams to control the flow and composition of the combustion fuel stream to regulate the temperature of combustion and avoid flame burnout. In some embodiments, each of the streams may be operatively connected to a flow controller controlled by a central control system.

[0010] In additional embodiments, the combustor may include a first mix zone
30 configured to mix the first portion of the high concentration CO₂ stream and the oxygen supply stream to form the oxygenation stream; a primary combustion zone configured to house the combustion reaction which produces the combustion products stream; and a burnout zone configured to deliver the second portion of the high concentration CO₂ stream to the combustor to regulate the temperature of the combustor and the combustion products

stream. In one exemplary embodiment, a catalyst is added to the initial high temperature combustion zone to catalyze the combustion reaction. In another alternative embodiment, the second mix zone may be configured to pre-mix the oxygenation and combustion fuel streams or concurrently mix the streams with the combustion reaction.

5 [0011] Another embodiment of the present invention discloses a combustion control method. The method comprising providing a high concentration CO₂ stream, an oxygen supply stream, and a combustion fuel stream, wherein each stream has a flow rate and a composition; combining at least a first portion of the high concentration CO₂ stream and oxygen supply stream to form an oxygenation stream; combusting the oxygenation stream
10 and the combustion fuel stream in a combustor to form a combustion products stream with a temperature and a composition; sensing the oxygen content of the combustion products stream; and adjusting the flow rate of the oxygen supply stream until the combustion products stream is substantially stoichiometric.

[0012] In a third embodiment of the present invention, a combustion system is provided.
15 The combustion system includes a combustion fuel stream comprising substantially hydrocarbons and carbon dioxide (CO₂) and having an initial fuel to CO₂ ratio; an oxygenation stream comprising substantially oxygen and carbon dioxide (CO₂), wherein the combustion fuel stream and the oxygenation stream are combined to form the combustion reactants stream having a combined fuel to oxygen ratio regulated to meet a desired
20 equivalence ratio (defined as the ratio of the actual fuel-to-oxidizer ratio to the stoichiometric fuel-to-oxidizer ratio) and a combined initial CO₂ to fuel ratio regulated to provide a desired combustion temperature within the primary combustion zone; a secondary diluent comprising substantially carbon dioxide (CO₂); and a combustor configured to combust the combustor inlet stream to produce the primary combustion product comprising substantially water and
25 carbon dioxide, wherein the primary combustion product is mixed with the secondary diluent to form a combustion products stream having a temperature and a final CO₂ to fuel ratio.

BRIEF DESCRIPTION OF THE DRAWINGS

[0013] The foregoing and other advantages of the present invention may become apparent upon reviewing the following detailed description and drawings of non-limiting
30 examples of embodiments in which:

[0014] FIGs. 1A-1E illustrate four alternative exemplary control schematics in accordance with certain aspects of the present invention;

[0015] FIG. 2 illustrates a schematic of an exemplary combustor as it might be configured for use in the alternative exemplary systems of FIGs. 1A-1E.

[0016] FIG. 3 is an exemplary flow chart of a method of operating the system of FIGs. 1A-1E;

DETAILED DESCRIPTION

[0017] In the following detailed description section, the specific embodiments of the present invention are described in connection with preferred embodiments. However, to the extent that the following description is specific to a particular embodiment or a particular use of the present invention, this is intended to be for exemplary purposes only and simply provides a description of the exemplary embodiments. Accordingly, the invention is not limited to the specific embodiments described below, but rather, it includes all alternatives, modifications, and equivalents falling within the true spirit and scope of the appended claims.

[0018] The term "stoichiometric combustion," as used herein, refers to a combustion reaction having a volume of hydrocarbons (e.g. fuel) and a volume of oxygen, where the volume of oxygen is just enough to combust or burn all or nearly all of the volume of hydrocarbons to produce a volume of combustion products having almost no oxygen remaining and almost no hydrocarbons remaining.

[0019] The term "primary residence time," as used herein, is the time required in a combustor to produce a combustion products stream at about equilibrium conditions at the local conditions of pressure and temperature.

[0020] Embodiments of the present disclosure provide combustion processes and systems designed for oxy-fuel combustion in a gas turbine. Preferred embodiments of the invention address problems associated with high temperature oxy-fuel combustion, such as the development of Polycyclic Aromatic Hydrocarbons (PAH's), which lead to soot production and production of problematic combustion products such as oxygen and carbon monoxide (or similar products of incomplete combustion). One exemplary embodiment of the combustion system design includes a high concentration carbon dioxide (CO₂) stream that is divided into at least a primary diluent and secondary diluent and an oxygen supply stream configured to combine with the primary diluent to produce an oxygenation stream substantially comprising oxygen (O₂) and carbon dioxide (CO₂) (e.g. "synthetic air"). The system further includes a combustion fuel stream and a combustor, wherein the combustor, which consists of at least a primary combustion zone and a burnout zone, is configured to mix and combust the combustion fuel stream and the oxygenation streams in a substantially stoichiometric combustion reaction to form a primary combustion products stream substantially comprising water (steam) and CO₂. In addition, the primary combustion

product stream may be diluted with the secondary diluent to form a secondary combustion product stream.

[0021] Note, that in some embodiments, a high pressure combustion (e.g. greater than about 10 atmospheres) process may be utilized. The adiabatic flame temperature in the primary combustion zone can be controlled by varying the ratio of CO₂ mixed with the oxygen when forming the oxygenation stream. The temperature of the combustion products stream may be controlled independently to obtain the desired temperature or other properties of the combustion products at the exit of the combustor. As such, in some embodiments, the system will include a temperature sensor for measuring the combustion products stream and the percentage amount of CO₂ in the combustion products stream may be increased to decrease the temperature of the combustion products stream or decreased to increase the temperature.

[0022] In some embodiments of the present invention, CO₂ and oxygen are mixed to make a "synthetic air" (e.g. an oxygenation stream). The amount of CO₂ mixed with the oxygen provides a way to control the temperature of the primary combustion product stream and also another variable to help control the composition of the products of the combustion. The combustor design may include quench ports to provide additional CO₂ to the burnout zone to prevent the high temperatures of combustion from impinging on the combustor can. Additional embodiments of the system include a control system that measures the amount of hydrocarbon going to the combustor and calculates and controls the correct amount of oxygen needed for the combustion. The control system will also utilize feedback from instrumentation on the products of combustion to update the oxygen supply stream flow controller to ensure the desired combustion is achieved to provide the correct amount of oxygen to the oxygenation stream. A catalytic post combustion step is also optionally provided, which may be required depending on the hydrocarbon mixture that is used for the combustor. This catalytic step will reduce the oxygen in the primary combustion products stream down to the low levels required to avoid serious corrosion problems in the enhanced oil recovery (EOR) facilities.

[0023] Some embodiments of the present invention include methods of operating an oxy-fuel combustion system to provide the benefits and advantages of the disclosed systems. For example, one embodiment includes combining the combustion fuel stream with the oxygenation stream and combusting these streams in a combustor to form the combustion products stream. The combustion fuel and oxygenation streams may be pre-mixed or concurrently combined and combusted and may include a catalyst in some embodiments,

depending on the composition and rates of the various streams. The method further includes sensing or detecting the temperature and/or composition of the combustion product stream and adjusting the flow rate of at least one of the combustion fuel and oxygenation streams until the combustion is at substantially stoichiometric conditions.

5 **[0024]** The methods and systems of the present disclosure may be utilized in a variety of applications, including a combustion gas turbine burner system. The gas turbine may be an integrated turbine operating on a single shaft, a multiple-shaft system, or a non-integrated system with an external burner, and may even be utilized with an independent compressor and hot gas expander, depending on the temperatures, volumes, and other variables of the
10 particular system. The methods and systems may be utilized to beneficially increase combustion efficiency (e.g. reduce the amount of unburned or partially combusted fuel and/or oxygen) and provide greater control of turbine inlet temperature across a range of load conditions.

[0025] At least one benefit of the disclosed systems and methods includes the flexibility
15 to use a commercial gas turbine combustion can type system with an oxy-fuel/co-generation type of system, such as the ultra-low emission power generation systems and processes disclosed in U.S. Pat. App. No. 61/072,292. By controlling the amount of CO₂ mixed with the oxygen to form the oxygenation stream, the temperature and composition of the primary combustion products stream can also be controlled. Application of the disclosed systems and
20 methods may avoid the need to develop a new combustor can for a gas turbine, permitting the use of “off-the-shelf” gas turbine combustor technology in such a system.

[0026] The combustor utilized could be similar to those used in the gasification process where oxygen and hydrocarbons react in a reducing atmosphere using steam to moderate the temperature. In the present invention, CO₂ would be used in place of the steam to moderate
25 the temperature. Using steam is expensive and would also result in the formation of additional hydrogen in the products of combustion which is not desired in the present cycle. By mixing the CO₂ with the oxygen, it may also be possible to use a more conventional diffusion type combustor similar to those used in existing gas turbines where CO₂ would be used instead of air to cool the combustion liners. Combustion at near stoichiometric
30 conditions is preferred to eliminate the cost of excess oxygen removal.

[0027] Embodiments of the present invention provide additional benefits. The present systems and methods enable an operator or automated system to control the temperature of the primary combustion zone separately from the temperature of the combustion product stream and control the products of combustion, such as limiting the amount of corrosive

carbon monoxide and oxygen in the combustion product, therefore enabling the use of the combustion product in enhanced oil recovery (EOR) operations, which require the elimination of such corrosive components. Additionally, the disclosed systems and methods can adapt to changes in the quality of available fuel gas. For example, if a low heating value (e.g. less than 40 percent (%) methane) fuel gas is provided, such as from a low quality gas reservoir or a reservoir after CO₂ breakthrough, the systems and methods can adjust the ratio of oxygen in the oxygenation stream and/or add or increase the amount of high quality fuel gas or spiking fuel gas (e.g. hydrogen gas) to the combustion process to maintain the proper temperature and composition in the combustion products stream.

10 [0028] Referring now to the figures, FIGs. 1A-1D illustrate four alternative exemplary control schematics in accordance with certain aspects of the present invention. In particular, FIG. 1A is a basic exemplary system. The system **100** includes a high concentration carbon dioxide (CO₂) stream **102** that may be split into at least a primary diluent stream **102a** and a second diluent stream **102b**, and an oxygen supply stream **104**, which may be combined with
15 the primary diluent stream **102a** to form an oxygenation stream **106** having an oxygen to CO₂ ratio. A combustion fuel stream **108** is also provided, which may be comprised substantially of methane (CH₄) or may include a mixture of light hydrocarbons, heavier hydrocarbons, hydrogen (H₂), and inert gasses, such as carbon dioxide, depending on the source. A combustor (e.g. combustor can) **110** is also provided, which in the preferred embodiment is
20 divided into two parts, a primary combustion zone **110a** and a burnout zone **110b**, and which is configured to receive at least the oxygenation stream **106** and the combustion fuel stream **108**, mix and combust the oxygenation and combustion fuel streams **106** and **108** in the primary combustion zone **110a** at a desired flame temperature and primary residence time inside the combustor sufficient to produce a hot products stream (not shown) near
25 equilibrium conditions and then dilute the hot products stream with the secondary diluent within the burnout zone **110b** to form the combustion products stream **112a**, which may be fed into an expansion device **111** (e.g. a gas turbine or hot gas expander), which is operatively connected to a load controller **111'** to form an expanded products stream **112b**. The expanded products stream **112b** may be split to form stream **113**, which may form at
30 least a portion of the high concentration CO₂ stream **102** and a secondary stream **128**, which may be utilized for enhanced oil recovery (EOR), sequestration, or another purpose. The system **100** further includes at least one of a temperature sensor **114** and an oxygen analyzer **126** configured to measure the temperature and oxygen content, respectively, of the combustion products stream **112a** or the expanded products stream **112b**. Temperature data

from the temperature sensor **114** is used to control the flow rate of the secondary diluent stream **102b** and to regulate the temperature of the combustion products stream **112a**. The flow rate of the oxygen supply **104** is adjusted in proportion to the flow rate of the combustion fuel supply **108**. Oxygen data from the oxygen analyzer **126** is used to adjust the proportioning factor of the flow rate of the oxygen supply stream **104** to the combustion fuel supply **108** until a substantially stoichiometric combustion is achieved.

[0029] Still referring to FIG. 1, the system **100** further includes a central controller **115** operatively connected to a first flow controller **116a** for controlling the primary diluent **102a**; a second flow controller **118** for controlling the oxygen supply **104**; a third flow controller **120** for controlling the combustion fuel stream **108**; and a fourth flow controller **116b** for controlling the secondary diluent stream **102b**. The central controller **115** may also be connected to the temperature sensor **114** and the oxygen sensor **126** to determine the amount of unburned oxygen in the combustion products stream **112a** or the expanded products stream **112b** and use those measurements to control the flow of the oxygen supply stream **104**. The central controller **115** may also control the flow rate of the combustion fuel stream **108** and the oxygen supply stream **104** to maintain desired stoichiometry as the load condition changes.

[0030] The high concentration carbon dioxide (CO₂) stream (or “diluent supply stream”) **102** may come from any convenient source. For example, at least a portion of the diluent supply stream **102** may be derived from diverting or splitting at least a portion of the expanded products stream **112b** via recycle stream **113**. However, the system **100** may be located near another source of high concentration CO₂, such as an external pipeline network, a high CO₂ gas well, a gas treatment plant, or other source. In addition, recycle stream **113** may include some treatment, such as a filtering system like a membrane, mole sieve, absorption, adsorption, or other system to remove potentially dangerous or undesirable components, such as un-reacted oxygen or hydrocarbons. In particular, if the oxygen analyzer determines that the expanded products stream **112b** has high levels of oxygen, then the expanded products stream **112b** should not be used as a diluent, like in the secondary diluent stream **102b**. Similarly, high levels of unreacted hydrocarbons may also be unacceptable, depending on the combustor **110** and may need to be removed or separated before use as a secondary diluent stream **102b**. However, it is preferred and intended that the combustion product stream **112a** has undergone a substantially stoichiometric combustion, so it should have less than about 3.0 volume percent (vol%) oxygen, or less than about 1.0 vol% oxygen, or less than about 0.1 vol% oxygen, or even less than about 0.001 vol% oxygen and

less than about 3.0 volume percent (vol%) hydrocarbons, or less than about 1.0 vol% hydrocarbons, or less than about 0.1 vol% hydrocarbons, or even less than about 0.001 vol% hydrocarbons.

[0031] The secondary stream (or “remainder stream”) **128** may be used for sales, used in another process requiring high concentration carbon dioxide, or compressed and injected into a terrestrial reservoir for enhanced oil recovery (EOR), sequestration, or another purpose. Like with recycle stream **113**, stream **128** may need to undergo some conditioning before use to remove potential contaminants or reactants like nitrogen oxides (NO_x) or oxygen. Again, it is preferred and intended that stream **104** includes substantially no nitrogen, and that stream **112a** has undergone a substantially stoichiometric combustion, so it should have less than about 3.0 volume percent (vol%) oxygen, or less than about 1.0 vol% oxygen, or less than about 0.1 vol% oxygen, or even less than about 0.001 vol% oxygen and less than about 3.0 volume percent (vol%) NO_x, or less than about 1.0 vol% NO_x, or less than about 0.1 vol% NO_x, or even less than about 0.001 vol% NO_x.

[0032] The oxygen supply stream **104** may be provided by an air separation unit (ASU) or other process or system providing high purity oxygen. The separated nitrogen may be used in another related process, such as in a nitrogen injection well as disclosed in U.S. Pat. App. No. 61/072,292. In one exemplary embodiment, the oxygen supply stream **104** may include from about 90 vol% to about 99.9 vol% oxygen with the remainder argon and may include trace amounts of nitrogen and carbon dioxide. In another exemplary embodiment, the oxygen supply stream may include from about 95 vol% to about 96 vol% oxygen with about 4 vol% to about 5 vol% argon and less than about 0.2 vol% carbon dioxide.

[0033] The central controller **115** may be any type of control system configured to receive data inputs, such as flow rates and compositions, and send signals to control flow rates via, for example, valves, pumps, compressors, and any other device that may be used to adjust a flow rate. In one exemplary embodiment, the central controller **115** may include a programmable computer having user input devices such as a keyboard and mouse, user output devices such as a monitor and speakers, and may operate using active memory (RAM), and be operably connected to hard disk drives, optical drives, network drives, and databases via a LAN, WAN, Wi-Fi, or other external network.

[0034] The flow controllers **116a**, **116b**, **118**, and **120** may include programmable automated controllers for receiving and processing signals from the central controller **115**, and may be operably connected to flow valves or vanes, vents, or other means of increasing or decreasing the flow of a substantially gaseous stream. Additionally, in one exemplary

embodiment, the flow controllers **116a**, **116b**, **118**, and **120** may be operably connected to flow and/or composition sensors, which may provide additional data input, such as to verify changes in the flow rates of the respective streams controlled by the flow controllers. In order to maintain flame stability and effective control, it may be beneficial to utilize a high speed controller for any or all of the controllers **116a**, **116b**, **118**, and **120**.

[0035] Although flow controller **116b** may be an active sensor as described above, the flow rate of the secondary diluent stream **102b** may be uncontrolled in one exemplary embodiment. For example, the combustor **110** may include a liner having one or more quench ports (e.g. dilution holes) with a particular pattern and hold size designed to provide dilution and control temperatures in the combustor **110**. Hence, the flow rate of the secondary diluent stream **102b** may be primarily dependent upon the hardware design of the quench ports in the combustor **110** and the pressure, temperature and composition of diluent supply stream **102**. Additionally, the flow controller **116b** may still be useful for shutting off the flow of secondary diluent **102b** in case of shut down, contamination of the secondary diluent **102b**, or some other reason. In some embodiments, the central controller **115** may further include two out of three voting for certain sensors, such as the temperature sensor **114** and the oxygen analyzer **126**. The control system, including the central controller **115** may also be configured with at least one safety interlock and/or shutdown logic and an alarm if the system **100** gets out of control to protect the downstream machinery.

[0036] The temperature sensor **114** may be a single sensor or may additionally include a backup sensor for redundancy or an array of sensors in and around the combustion products stream **112a** or the expanded products stream **112b** to ensure accurate temperature readings. Any type of appropriate temperature sensor may be used, although the sensor chosen should have a high resistance to heat and be able to effectively operate at temperatures at or above about 2,000 degrees Fahrenheit (°F) or even above about 2,200 °F. In some exemplary embodiments of the described inventive system **100**, the temperature sensor **114** may send data directly to the CO₂ flow controller **116b**, or may send data to the central controller **115**, which then controls the response of the flow controller **120**. Alternatively, the temperature sensor **114** may also send data directly to the combustion fuel stream flow controller **120**. Additionally and alternatively, the temperature sensor **114** may take data from inside the combustor **110** near the exhaust or downstream of the burnout zone **110b** after exiting, at multiple locations along the combustion products stream **112a** and expanded products stream **112b**, or some combination thereof. The temperature of the streams **112a** and **112b** should be limited to within certain operating parameters, which will depend highly on the equipment

in use, the type of combustion fuel stream and other input streams available, the potential uses for the remainder stream **128**, and other factors.

[0037] Generally, the temperature in the primary combustion zone **110a** should be below about 3,500 °F to avoid NO_x production and because most commercial combustors **110** cannot operate above such temperatures, but this limitation may be set higher if the material of the combustor **110** can operate at higher temperatures and there is no nitrogen in the system **100**. The temperature is preferably less than about 2,500°F at the inlet of the expander **111**. Such high temperatures also contribute to the formation of undesirable Polycyclic Aromatic Hydrocarbons (PAH's), which lead to soot production. However, the temperature in the primary combustion zone **110a** must be sufficiently high to avoid flame burnout, which is done by regulating the oxygen to CO₂ ratio based on the temperature of the reactants entering the primary combustion zone and the heat release available from the specific fuel **108** and sufficiently high to effectively combust substantially all of the oxygen (O₂) and hydrocarbons (e.g. stoichiometric combustion temperature) to produce the expanded products stream **112b** requiring only limited conditioning before use in enhanced oil recovery (EOR) or as a diluent in the system **100**. For many cases, the preferred temperature of the combustion product stream **112a** will be from at least about 1,500 °F to at most about 2,500 °F or from at least about 1,600 °F to at most about 1,900 °F. For many cases, the preferred adiabatic flame temperature within the primary combustion zone will be from at least 2,450 °F to at most 3,500 °F unless improved materials of construction and no nitrogen is present in the combustion reactants in which case the upper limit may be increased.

[0038] The oxygen analyzer **126** may be a single sensor, may include additional sensors for redundancy, or an array of sensors at multiple locations to ensure accurate measurements. For example, a plurality of lambda or wideband zirconia O₂ sensor may be used to provide feedback to one of the central controller **115** and/or the oxygen supply stream flow controller **118**. If the lambda sensor is used, the central controller **115** may be configured to dither the ratio of the fuel in the combustion fuel stream **108** to the oxygen in the oxygen supply stream **104** as the oxygen content of the combustion products stream **112a** varies from a stoichiometric coefficient below 1.0 to above 1.0. The dithering process is similar to those used in the automotive industry for internal combustion engines. In any case, the oxygen content of the combustion products stream is preferably low, from less than about 3.0 volume percent (vol%) to less than about 1.0 vol% to less than about 0.1 vol% to less than about 0.001 vol%. If the amount of oxygen is too high, then the flow rate of the oxygen supply

stream **104** is reduced. In turn, this may lower the flame temperature, as discussed above, requiring an adjustment of the flow of the combustion fuel stream **108**.

[0039] FIG. 1B illustrates the basic exemplary system as shown in FIG. 1A, but with additional, optional features configured to further treat or condition the products streams **112a** and **112b**. As such, FIG. 1B may be best understood with reference to FIG. 1A. The system **140** includes all of the features disclosed with respect to FIG. 1A, but further includes a post-combustion catalysis apparatus **146** configured to reduce the oxygen and carbon monoxide content in the products streams **112a** and **112b** and a combustion fuel bypass stream **142** with a flow and a composition and having a flow controller **144** for controlling the flow rate of the combustion fuel bypass stream **142**. The oxygen analyzer **126** may be operatively connected to the flow controller **144** directly or indirectly via the central controller **115**. Additional flow controllers and oxygen analyzers (not shown) may be required in certain specific embodiments where the combustion fuel bypass stream **142** is split or stream **128** is looped, as discussed further below.

[0040] The catalysis apparatus **146** may be a single device or a plurality of devices in parallel or series, but is preferably a small device requiring only a small amount of power to operate. In particular, the catalysis apparatus **146** may be a carbon monoxide reduction catalyst and/or an oxygen reduction catalyst that is normally used in Heat Recovery Steam Generators (HRSG's) to meet emissions requirements. Such a system is generally not designed to remove large amounts of oxygen, but if significant amounts of oxygen remain in the expanded products stream **112b**, the expanded product stream **112b** may need to recycle through the catalysis apparatus **146** more than once before it is compressed and injected for enhanced oil recovery (EOR). As such, in some embodiments, another oxygen analyzer (not shown) may be needed after the catalysis apparatus **146** to ensure that the injection stream **128** is sufficiently low in oxygen (e.g. less than about 0.5 volume percent (vol%) oxygen or less than about 0.1 vol%) to avoid corrosion of the compression and injection equipment and avoid souring the reservoir by injecting oxygen that can react with the hydrocarbons remaining in the reservoir.

[0041] The combustion fuel bypass stream (e.g. second portion of the combustion fuel stream) **142** is configured to be combined with the expanded products stream **112b** downstream from where recycle flow stream **113** is divided from the expanded product stream **112b**, and is preferably introduced upstream from the catalysis apparatus **146** so that the additional hydrocarbons may be used in the catalysis apparatus **146** to improve oxygen removal efficiency. However, in some alternative embodiments, the bypass stream **142** may

be split and introduced before and after the catalysis apparatus **146**. In the embodiment where the EOR stream **128** is looped back to the catalysis apparatus **146**, it may be beneficial to introduce a portion of the bypass stream **142** into the EOR stream **128** before looping it back to the catalysis apparatus **146**. Beneficially, the bypass stream **142** is configured to
5 reduce the volume percent of oxygen in the EOR stream **128** before compression and injection into a reservoir to substantially avoid corrosion of injection and compression equipment and souring the hydrocarbons remaining in the injection reservoir.

[0042] FIG. 1C is an illustration of a third exemplary embodiment of the system of FIG. 1A, which may or may not include the features disclosed in the illustration of the
10 embodiment of FIG. 1B. As such, FIG. 1C may be best understood with reference to FIGs. 1A and 1B. The system **150** includes a hydrocarbon analyzer **152** configured to measure the amount of hydrocarbons in the composition of the products streams **112a** and/or **112b**, a high quality fuel gas supply **108a** controlled by a flow controller **154**, and a low heating value fuel gas supply **108b** controlled by a flow controller **156**. Flow controller **156** may be directly
15 connected to the hydrocarbon analyzer **152** and/or may be connected via central controller **115**. The flow controllers **154**, **156**, and optionally **120** may be operatively connected to a summation controller **158**, which may be connected to the central controller **115** directly or via oxygen supply controller **118**.

[0043] The high quality fuel gas stream **108a** may be comprised of substantially pure
20 methane (e.g. about 99 vol%) and alternatively may comprise a “spiking” fuel gas such as hydrogen, higher hydrocarbons (C_3+) or any combination thereof. The composition of the high quality fuel gas stream **108a** will primarily vary depending on the needs of the system **150** and the availability of various fuel types, but preferably will not include significant quantities of inert gases (e.g. nitrogen, carbon dioxide, etc.) or acid gases (e.g. sulfur dioxide,
25 hydrogen sulfide, etc.). High quality fuel gas stream **108a** may be from any reasonable source, but is preferably available from a nearby gas production field rather than imported from a significant distance. Specifically, if the stream **108a** is hydrogen, it may be provided from an auto-thermal reforming (ATR) process performed on a gas production stream from a nearby production gas field (not shown).

30 [0044] The low heating value fuel gas stream **108b** may be comprised of less than about 80 vol% methane, less than about 60 vol% methane, less than about 40 vol% methane, or even less than about 20 vol% methane. The low heating value stream **108b** may also include small amounts of heavier hydrocarbons such as ethane and propane. In most cases, the majority of the remainder of the stream **108b** will be inert gases such as carbon dioxide, but

in some cases, there will be small amounts of nitrogen, hydrogen sulfide, helium, and other gases. Preferably, all non-hydrocarbons and all inert gases other than carbon dioxide will be separated out of the stream **108b** prior to mixing and combustion.

[0045] In one exemplary embodiment, the flow and composition of the two hydrocarbon containing streams **108a** and **108b** are used to calculate the oxygen requirement to operate the combustor **110** and provide the set point for the oxygen supply flow controller **118**. The calculation will provide the amount of oxygen needed for a stoichiometric combustion in the combustor **110**. The flows and compositions of the streams may change over the life of the system **150**, depending on the source of the streams **108a** and **108b**. For example, the low heating value fuel gas **108b** may originate from an EOR well having a high methane content in early production (e.g. above about 80 vol%). In such a case, there may be little or no flow through the high quality fuel gas stream **108a**. However, when breakthrough occurs, the flow from the low heating value fuel gas stream **108b** may comprise very low methane content (e.g. less than about 20 vol%). In that case, the flow from the high quality fuel gas stream **108a** is increased to add hydrocarbons to the combustion fuel stream **108**.

[0046] FIG. 1D is an illustration of a fourth exemplary embodiment of the system of FIG. 1A, which may or may not include the features disclosed in the illustration of the embodiment of FIGs. 1B and 1C. As such, FIG. 1D may be best understood with reference to FIGs. 1A-1C. The system **160** further includes a high concentration CO₂ makeup stream **108c** with a flow and composition and a flow controller **162** operatively attached thereto. The CO₂ makeup supply stream **108c** may be combined with streams **108a** and **108b** to generate a combustion fuel gas stream **108** having a substantially constant composition over the life of the system **160**. The approach is similar to the system **150**, but the physical characteristics of the combustor could be designed specifically for the composition of **108** and still burn fuels that have variable composition **108b**. The CO₂ stream **108c** may be split from the expanded products stream **112b** or originate from another source.

[0047] FIG. 1E is an illustration of a fourth exemplary embodiment of the system of FIGs. 1A-1D. As such, FIG. 1E may be best understood with reference to FIGs. 1A-1D. The system **170** includes a combustion fuel stream **108** comprising substantially hydrocarbons and carbon dioxide (CO₂) and having an initial fuel to CO₂ ratio; an oxygenation stream **106** comprising substantially oxygen and carbon dioxide (CO₂), wherein the combustion fuel stream **108** and the oxygenation stream **106** are combined to form a combustor inlet stream **172** having a combined fuel to oxygen ratio configured to meet an optimal equivalence ratio and a combined initial CO₂ to fuel ratio configured to provide an optimal combustion

temperature; a secondary diluent stream **102b**; and a combustor **110** configured to combust the combustor inlet stream **172** to produce a hot products stream **174** comprising substantially water and carbon dioxide, wherein the hot products stream **174** is mixed with the secondary diluent stream **102b** to form a combustion products stream **112a** having a temperature and a
5 final CO₂ to fuel ratio.

[0048] In some exemplary embodiments, the hydrocarbons in the combustion fuel stream **108** are comprised substantially of methane and the fuel to oxygen molar ratio is from about 1.9:1 mol fuel to mol oxygen to about 2.1:1 mol fuel to mol oxygen or from about 1.95:1 mol fuel to mol oxygen to about 2.05:1 mol fuel to mol oxygen. These molar ratios are
10 approximately equivalent to stoichiometric ratios of 0.9:1 to about 1.1:1. In additional exemplary embodiments, the hydrocarbons in the combustion fuel stream **108** are comprised substantially of methane and the final CO₂ to fuel ratio is from about 10:1 mol CO₂ to mol fuel to about 30:1 mol CO₂ to mol fuel or from about 15:1 mol CO₂ to mol fuel to about 25:1 mol CO₂ to mol fuel or from about 20:1 mol CO₂ to mol fuel to about 23:1 mol CO₂ to mol
15 fuel.

[0049] In at least one exemplary embodiment, the system **170** further includes a high quality fuel gas stream **108a** with a flow and a composition; a low heating value fuel gas stream **108b** with a flow and composition; and a high concentration CO₂ makeup stream **108c** configured to combine with the high quality fuel gas stream **108a** and the low heating value
20 fuel gas stream **108b** to form the combustion fuel stream **108** and maintain a constant initial fuel to CO₂ ratio of the combustion fuel stream **108**. Additional embodiments may include an oxygen supply stream **104** with a flow and a composition; and a high concentration CO₂ mixing stream **102a** with a flow and a composition configured to combine with the oxygen supply stream **104** to form the oxygenation stream **106**.

[0050] In yet another exemplary embodiment, the system **170** additionally includes at least one temperature sensor **114** configured to measure the temperature of the combustion products stream **112a** and/or expanded products stream **112b** (and optionally the hot products stream **174**) wherein the temperature of the streams **112a** or **112b** are used to calculate the flow rate of at least one of the high concentration CO₂ mixing stream **102a**, the high
30 concentration CO₂ makeup stream **108c**, and the secondary diluent stream **102b**, to regulate the temperature of combustion; at least one oxygen analyzer **126** configured to measure the amount of oxygen in the composition of the products streams **112a** and/or **112b**, wherein the amount of oxygen in the products streams **112a-112b** is used to optimize the flow rate of the oxygen supply stream **104** to achieve substantially stoichiometric combustion; and at least

one hydrocarbon analyzer **152** configured to measure the amount of hydrocarbons in the composition of the products streams **112a-112b**, wherein the amount of hydrocarbons in the composition of the products streams **112a-112b** is used to optimize the flow rate of the oxygen supply stream **104** to achieve substantially stoichiometric combustion. The system
5 **170** may also include a gas turbine **111** having a load and a load controller **111'** configured to measure the load, wherein the load measurement is used to maintain the combined fuel to oxygen ratio as the load changes.

[0051] FIG. 2 illustrates a schematic of an exemplary combustor as it might be configured for use in the alternative exemplary systems of FIGs. 1A-1D. As such, FIG. 2
10 may be best understood with reference to FIGs. 1A-1D. The combustor system **200** comprises a first mix zone **202**, a second mix zone **204**, an initial high temperature primary combustion zone **205**, a burnout zone **206**, and optional fuel injection nozzles **208a** and **208b**. The hot products stream (or "primary combustion products stream") **212** is produced from primary combustion zone **205**. Note, that in some exemplary embodiments, a high pressure
15 combustion process (e.g. greater than about 10 atmospheres) may be utilized.

[0052] The first mix zone **202** is configured to mix the primary diluent stream **102a** with the oxygen supply stream **104** to form the oxygenation stream **106**. The second mix zone **204** is configured to mix the oxygenation stream **106** and the combustion fuel stream **108**. In one embodiment the streams **106** and **108** may be pre-mixed in the second mix zone **204** and then
20 directly flow into the primary combustion zone **205**. In another embodiment, which is referred to as non-premixed, the second mixing zone **204** and the primary combustion zone **205** overlap and occur concurrently, as in a diffusion burner type of arrangement. The primary combustion zone **205** includes a burner, a flame, and the combustion reaction itself, which produces the hot products stream **212**. The burnout zone **206** delivers the secondary
25 diluent stream **102b** to the combustor **110** to regulate the temperature of the combustor **110** and the combustion products stream **112a**.

[0053] In some exemplary embodiments of the combustor **110**, the burnout zone **206** comprises one of a passive dilution zone having a series of holes configured to cool and quench the liner of the combustor **110**; an active dilution zone having at least one quench port
30 configured to actively deliver at least a portion of the secondary diluent stream **102b** to the combustor **110** to mix with the primary combustion products stream **212**; a series of staged quench ports to actively control a temperature pattern through the burnout zone **206**; and any combination thereof. In addition, the burnout zone **206** may include a pressure transducer or other sensor **210** to monitor and measure pressure oscillations in the combustor **110**, which


are a sign of flame blowout. An oxygen analyzer (not shown) may also be included in the combustor **110** to provide another input to the oxygen feedback loop.

[0054] In one exemplary embodiment of the non-premixed arrangement, the combustion fuel streams **108a** and **108b** may be introduced in separate nozzles **208a** and **208b** that are
 5 configured based on the volume flow of the respective stream, or mixed and injected as a mixed combination of the combustion fuel stream **108** through a single injector.

[0055] The combination of the oxygenation stream **106** and the combustion fuel stream **108** in the combustor **110** is configured to maintain a minimum adiabatic flame temperature and flame stability to combust all or nearly all of the oxygen in the oxygenation stream **106**
 10 (e.g. a stoichiometric reaction is preferred). In terms of heating value, the oxygenation stream **106** has no heating value, the high quality fuel gas stream **108a** may have a relatively high value (e.g. from at least 500 British thermal units per standard cubic foot (BTU/scf) to about 950 BTU/scf) and the low heating value fuel gas stream **108b** has a relatively low heating value (e.g. from about 150 BTU/scf to about 450 BTU/scf).

15 [0056] The combustor **110** may be a standard external combustor or may be a customized or modified combustor. Examples of applicable combustor types include an oxyClaus burner, a partial oxidation (POX) burner, auto-thermal reforming (ATR) burner, and gas turbine diffusion combustors. Note that each burner type may require some modification to work with a substantially CO₂ stream.

20 [0057] In one exemplary embodiment, the second mix zone **204** and nozzles **208a** and **208b** may be configured to mix the combustion fuel stream **108** and the oxygenation stream **106** in a highly turbulent manner to ensure a homogeneous mixture is achieved. During operation, the primary combustion zone **205** produces temperatures up to about 2,200 °C. With the addition of the quench gas **102b**, the combustion products stream **112a** is expected
 25 to be up to about 1,400 °C as it enters the burnout zone **206**. Additional quench gas **102b** may be introduced via the outer wall of the burnout zone **206** generating a sort of “gas envelope” to keep the wall of the combustor **110** notably cooler than the flame **205**. In one exemplary embodiment, the cooling stream **102b** may be stripped of hydrocarbons to minimize soot formation, if necessary. In another exemplary embodiment, the combustion
 30 takes place at higher than atmospheric pressure, such as above about 10 atmospheres. The reaction generates water (vapor) and carbon dioxide as shown by the equations below (the carbon dioxide entering the chamber generally remains unreacted):



[0058] FIG. 3 is an exemplary flow chart of a method of operating the system of FIGs. 1A-1D. As such, FIG. 3 may be best understood with reference to FIGs. 1A-1D. The method 300 begins at block 302, then includes providing 304 a high concentration CO₂ stream 102, an oxygen supply stream 104, and a combustion fuel stream 108, wherein each stream has a flow rate and a composition; splitting 306 the high concentration CO₂ stream 102 into a primary diluent stream 102a and a secondary diluent stream 102b, each having a flow rate; adjusting 308 the primary diluent stream flow rate independently of the overall flow rate of the high concentration CO₂ stream; combining 310 the primary diluent stream 102a and the oxygen supply stream 104 to form an oxygenation stream (e.g. "synthetic air") 106; combusting 312 the oxygenation stream 106 and the combustion fuel stream 108 in a primary combustion zone 110a of the combustor 110 to form a combustion products stream 112a with a temperature and a composition; sensing 314 the oxygen content of the combustion products stream 112a; and adjusting 316 the flow rate of the oxygen supply stream 104 until the combustion products stream 112a is substantially stoichiometric using the sensed oxygen content. In one embodiment, the method 300 includes sensing 314 the temperature of the combustion products stream 112a and adjusting 316 the flow rate of the primary diluent stream 102a to regulate the temperature of combustion using the sensed temperature. In one embodiment, the method includes directing 318 a portion of the combustion products stream 112a to an enhanced oil recovery (EOR) process.

20

EXAMPLES

[0059] Some exemplary gas stream compositions are provided in the tables below as examples of gas streams at different stages of production in a single gas production field, or different gas production fields. Table 1 provides specific stream compositions and flow rates for a production well at or near the beginning of production.

Component	Stream 104	Stream 108b	Stream 108a	Stream 102a	Stream 112
O2	95.59%	0	0	0	0.44%
CO2	0	0	0	76.23%	61.83%
CH4	0	0	100%	0	0.00%
CO	0	0	0	0	0.85%
OH	0	0	0	0	0.12%
H2	0	0	0	0	0.09%
H2O	0	0	0	16.99%	30.42%
Ar	4.26%	0	0	6.78%	6.34%
Misc	0.15%	0	0	0	0%
Total	100.00%	0.00%	100.00%	100.00%	100.09%
Pressure					
psig	300	300	300	300	250
Temp (deg F)	755	500	160	540	1701.7
LB Moles	13474.1	0	6464.1	143859.5	163798
Flow (lb/hr)	436010	0	103425	6282874	6822309

Table 1: Start-up

[0060] Table 2 provides specific stream compositions and flow rates for a production well after CO₂ breakthrough.

Component	Stream 104	Stream 108a	Stream 108b	Stream 102a	Stream 112
O2	95.59%	0	0	0	0.014%
CO2	0	88.16%	0	0	64.15%
CH4	0	5.21%	100%	0	0.00%
C2	0	2.76%	0	0	0.00%
C3	0	1.25%	0	0	0.00%
CO	0	0%	0	0	0.028%
OH	0	0%	0	0	0.004%
H2	0	0%	0	0	0.236%
H2O	0	0%	0	0	31.02%
N2	0	1%	0	0	0.84%
Ar	4.26%	0	0	0	0.40%
Misc	0.15%	1.77%	0	0	3.3%
Total	100.00%	100.00%	100.00%	0.00%	100.00%
Pressure					
psig	300	300	300	300	250
Temp (deg F)	755	500	160	540	1701.7
LB Moles	13474.1	136739.7	171.8	0	150386
Flow (lb/hr)	412653	5639146	2748	0	6054547

Table 2: Post Breakthrough

[0061] While the present invention may be susceptible to various modifications and alternative forms, the exemplary embodiments discussed above have been shown only by way of example. However, it should again be understood that the invention is not intended to

be limited to the particular embodiments disclosed herein. Indeed, the present invention includes all alternatives, modifications, and equivalents falling within the true spirit and scope of the appended claims.

Claims:

What is claimed is:

1. A combustion system, comprising:
 - a high concentration carbon dioxide (CO₂) stream;
 - 5 at least one CO₂ flow regulation device configured to adjust an overall flow rate of the high concentration CO₂ stream and split the high concentration CO₂ stream into a primary diluent stream having a flow rate and a secondary diluent stream having a flow rate, wherein the at least one flow regulation device is further configured to adjust the primary diluent stream flow rate independently of the overall flow rate of the high concentration CO₂ stream;
 - 10 an oxygen supply stream having a flow rate;
 - at least one oxygen flow regulation device configured to adjust the oxygen supply stream flow rate;
 - a mixing device arranged to combine the primary diluent stream and the oxygen supply stream to form an oxygenation stream having a flow rate and an oxygen to CO₂ ratio;
 - 15 a combustion fuel stream having a flow rate and a composition; and
 - a combustor consisting of at least a primary combustion zone and a burnout zone, wherein the combustor is configured to mix and combust the oxygenation stream and the combustion fuel stream within the primary combustion zone at a flame temperature and a primary residence time sufficient to produce a hot products stream at about equilibrium
 - 20 conditions.
2. The system of claim 1, wherein the combustor is configured to dilute the hot products stream with the secondary diluent within the burnout zone to form a combustion products stream having a lower temperature than the hot products stream.
3. The system of claim 2, further comprising:
 - 25 a control system, comprising:
 - a first controller configured to regulate the flow rate of the oxygen supply stream in proportion to the flow rate of the combustion fuel stream so as to produce near stoichiometric combustion in the primary combustion zone; and
 - a second controller configured to regulate the oxygen to CO₂ ratio of the
 - 30 oxygenation stream by controlling the primary diluent stream flow rate to produce a primary combustion zone flame temperature configured to provide: an adequate margin between a combustor average velocity, a blow-off limit of the combustor, and the primary residence time within the combustor sufficient to produce a combustion products stream at about equilibrium conditions.

4. The system of claim 3, further comprising an expansion device configured to expand the combustion products stream to form an expanded products stream having a lower temperature than the combustion products stream.

5. The system of claim 4, the control system further comprising at least one temperature sensor operatively connected to the control system and the CO₂ flow regulation device and configured to measure the temperature of the combustion products stream and send a signal to the control system, which is configured to adjust the secondary diluent flow rate based on the temperature of the combustion products stream to produce a desired temperature of the secondary combustion products stream at some location after an exit of the combustion system.

6. The system of claim 5, further comprising at least one oxygen sensor located in the expanded products stream at a location spaced from the exit of the expansion device configured to measure the amount of oxygen in the expanded products stream and send a signal to the control system, wherein the control system is configured to adjust an oxygen to fuel ratio of oxygen in the oxygenation stream and fuel in the combustion fuel stream to achieve a substantially stoichiometric combustion as indicated by a near zero oxygen content in the expanded products stream and a measurable oxygen content in the expanded products stream if the oxygen proportion is increased by a small amount.

7. The system of claim 6, further comprising
at least one load controller configured to control the flow rate of the combustion fuel stream to maintain a desired load condition in the expansion device.

8. The system of claim 1, wherein the flow rate of the secondary diluent stream is controlled passively based on a pressure drop of at least one flow restriction in the flow path of the high concentration CO₂ stream and the secondary diluent stream.

9. The system of claim 6, further comprising a central controller operatively connected to:
the at least one temperature sensor and the at least one oxygen analyzer;
a first flow controller for controlling the primary diluent stream;
a second flow controller for controlling the oxygen supply flow rate;
a third flow controller for controlling the combustion fuel flow rate; and
a fourth flow controller for controlling the secondary diluent stream.

10. The system of claim 4, wherein the combustion products stream is comprised substantially of water and carbon dioxide (CO₂) and the high concentration CO₂ stream is at least partially comprised of the CO₂ portion of the expanded products stream .

11. The system of claim 10, wherein at least a portion of the CO₂ portion of the expanded products stream is utilized for enhanced oil recovery (EOR).

12. The system of claim 11, further comprising a post-combustion catalysis apparatus configured to reduce the oxygen content in the combustion products stream prior to utilization for enhanced oil recovery (EOR).

13. The system of claim 12, further comprising a stream splitter along the combustion fuel stream configured to split the combustion fuel stream into a first portion configured to enter the combustor and a second portion configured to bypass the combustor and mix with the expanded products stream upstream of the post-combustion catalysis apparatus to form an enhanced oil recovery injection stream.

14. The system of claim 1, the combustion system further comprising a first mix zone located upstream from the combustor and configured to mix the primary diluent stream and the oxygen supply stream to form the oxygenation stream.

15. The system of claim 1, further comprising a catalyst, wherein the catalyst is added to the primary combustion zone to catalyze the combustion reaction.

16. The system of claim 14, further comprising a second mix zone configured to pre-mix the oxygenation stream and the combustion fuel stream at a location selected from the group consisting of: upstream of the primary combustion zone and in the primary combustion zone such that oxygenation stream and the combustion fuel stream are mixed and combusted approximately concurrently.

17. The system of claim 12, wherein the burnout zone comprises a feature selected from the group consisting of: a passive dilution zone having a series of holes configured to cool and quench a liner of the combustor; an active dilution zone having at least one quench port configured to actively deliver the secondary diluent to the combustor to mix with the combustion products stream; a series of staged quench ports to actively control a temperature pattern through the burnout zone; and any combination thereof.

18. The system of claim 9, wherein the oxygenation stream comprises from at least about 5 volume percent oxygen to at least about 40 volume percent oxygen and the remaining portion of the oxygenation stream comprises from at least about 95 volume percent CO₂ to about 99.9 volume percent CO₂.

19. The system of claim 9, further comprising:

a high quality fuel gas stream with a flow and a composition; and

a low heating value fuel gas stream with a flow and composition configured to combine with the fuel gas stream to form the combustion fuel stream.

20. The system of claim 19, further comprising:

a fifth flow controller for controlling the high quality fuel gas stream;

a sixth flow controller for controlling the low heating value fuel gas stream; and

a summation controller operatively connected to the fifth and sixth flow controllers configured to control the flow and composition of the combustion fuel stream to regulate the temperature of combustion and avoid flame burnout.

21. The system of claim 20, further comprising at least one hydrocarbon analyzer configured to measure the amount of hydrocarbons in the composition of the combustion products stream and operatively connected to at least the sixth flow controller to control the amount of low heating value fuel gas to avoid flame blowout in the combustor.

22. The system of claim 19, further comprising a high concentration CO₂ makeup stream with a flow and composition configured to combine with the low heating value fuel gas stream and the high quality fuel gas stream to form the combustion fuel stream, wherein the high concentration CO₂ makeup stream is operatively connected to a seventh flow controller operatively connected to the summation controller configured to adjust the flow of each of the streams to generate a substantially constant flow and composition in the combustion fuel stream.

23. A combustion control method, comprising:

providing a high concentration CO₂ stream, an oxygen supply stream, and a combustion fuel stream, wherein each stream has a flow rate and a composition;

splitting the high concentration CO₂ stream into a primary diluent stream and a secondary diluent stream, each having a flow rate;

adjusting the primary diluent stream flow rate independently of the overall flow rate of the high concentration CO₂ stream;

combining the primary diluent stream and the oxygen supply stream to form an oxygenation stream; and

combusting the oxygenation stream and the combustion fuel stream in a primary combustion zone of a combustor to form a combustion products stream with a temperature and a composition.

24. The method of claim 23, further comprising:

sensing the oxygen content of the combustion products stream; and

adjusting the flow rate of the oxygen supply stream until the combustion products stream is substantially stoichiometric using the sensed oxygen content.

25. The method of claim 24, further comprising:

sensing the temperature of the combustion products stream; and

adjusting the flow rate of the secondary diluent stream to a burnout zone of the combustor to regulate the temperature of combustion using the sensed temperature.

26. The method of claim 25, further comprising providing a high quality fuel gas stream, a low heating value fuel gas stream, and the primary diluent stream; and combining the high

quality fuel gas stream with the low heating value fuel gas stream and the primary diluent stream to form the combustion fuel stream.

27. The method of claim 26, further comprising controlling the flow of the high concentration CO₂ stream, the oxygen supply stream, the high quality fuel gas stream, the low heating value fuel gas stream, and the primary diluent stream with flow controllers, wherein the flow controllers are operatively connected to a central controller.

28. The method of claim 23, further comprising pre-mixing the oxygenation stream and the combustion fuel stream in the primary combustion zone of the combustor.

29. The method of claim 23, further comprising catalyzing the combustion reaction by adding a catalyst to the primary combustion zone.

30. The method of claim 25, further comprising sensing the amount of unreacted hydrocarbons in the combustion product stream; and

controlling the flow of the low heating value fuel gas stream based on the amount of unreacted hydrocarbons in the combustion products stream.

31. The method of claim 25, further comprising maintaining a substantially constant flow and composition of the combustion fuel stream by controlling the flow of each of the high quality fuel gas stream, the low heating value fuel gas stream, and primary diluent stream.

32. A combustor system, comprising:

a combustion fuel stream comprising substantially hydrocarbons and carbon dioxide (CO₂) and having an initial fuel to CO₂ ratio;

an oxygenation stream comprising substantially oxygen and carbon dioxide (CO₂), wherein the combustion fuel stream and the oxygenation stream are combined to form a combustor inlet stream having a combined fuel to oxygen ratio configured to meet an optimal equivalence ratio and a combined initial CO₂ to fuel ratio configured to provide an optimal combustion temperature;

a diluent stream comprising substantially carbon dioxide (CO₂); and

a combustor configured to combust the combustor inlet stream to produce a hot products stream comprising substantially water and carbon dioxide, wherein the hot products stream is mixed with the diluent stream to form a combustion products stream having a temperature and a final CO₂ to fuel ratio.

33. The system of claim 32, wherein the hydrocarbons are comprised substantially of methane and the fuel to oxygen ratio is from about 0.9:1 mol fuel to mol oxygen to about 1.1:1 mol fuel to mol oxygen.

34. The system of claim 32, wherein the hydrocarbons are comprised substantially of methane and the final CO₂ to fuel ratio is from about 20:1 mol CO₂ to mol fuel to about 25:1 mol CO₂ to mol fuel.

35. The system of claim 32, further comprising:

5 a high quality fuel gas stream with a flow and a composition;
a low heating value fuel gas stream with a flow and composition; and
a high concentration CO₂ makeup stream configured to combine with the high quality fuel gas stream and the low heating value fuel gas stream to form the combustion fuel stream and maintain a constant initial fuel to CO₂ ratio of the combustion fuel stream.

10 36. The system of claim 35, further comprising:

an oxygen supply stream with a flow and a composition; and
a high concentration CO₂ mixing stream with a flow and a composition configured to combine with the oxygen supply stream to form the oxygenation stream.

37. The system of claim 36, further comprising:

15 at least one temperature sensor configured to measure the temperature of the combustion products stream, wherein the temperature of the combustion products stream is used to calculate the flow rate of a stream selected from the group consisting of: the high concentration CO₂ mixing stream, the high concentration CO₂ makeup stream, the diluent stream, and any combination thereof, to regulate the temperature of combustion;

20 at least one oxygen analyzer configured to measure the amount of oxygen in the composition of the combustion products stream, wherein the amount of oxygen in the combustion products stream is used to optimize the flow rate of the oxygen supply stream to achieve substantially stoichiometric combustion; and

25 at least one hydrocarbon analyzer configured to measure the amount of hydrocarbons in the composition of the combustion products stream, wherein the amount of hydrocarbons in the composition of the combustion products stream is used to optimize the flow rate of the oxygen supply stream to achieve substantially stoichiometric combustion.