

METHOD AND ARRANGEMENT FOR GROWING PLANTS

Technical field

The present invention relates to a method and arrangement for growing plants in a vertical greenhouse. More
5 specifically the present invention relates to a method and an arrangement for growing plants in an industrial manner in a vertical greenhouse.

Description of the prior art

A problem in urbanized areas is that food, once grown and
10 harvested in farms in other regions and countries must travel long distances to reach the consumers in the cities. Such food transports consume energy and adds to the traffic congestion in the cities. A further problem is that
greenhouses are often situated far outside urban areas and
15 urban customer's food budget therefore goes to pay for transportation as well as storage.

Hence, growing food crops in vertical greenhouses in cities would help reduce both environmental pollution caused by transportation and transportation costs since the plants are
20 grown where the consumers are. Moreover, vertical greenhouses would be space-efficient and would be adapted for expanding cities where there is a shortage of space. Additionally, vertical greenhouses would be built close to the customers; consequently, the produce would be delivered
25 fresh and at a lower price.

The US3432965 patent document discloses a hydroponics apparatus for automatic germination of seed, growth of produce therefrom and harvesting of produce. A major
disadvantage with this apparatus is that it is not adapted
30 for industrial scale production of plants and crops in urban

areas since the surface area for the crops to grow is highly limited, as indicated in the specific examples. Moreover, the examples, as well as the claims, clearly illustrate that a plurality of containers holding seeds are connected to a pair of parallel and spaced apart members and that the containers are conveyed horizontally along these members. However, a major disadvantage with this system is that the distance between the parallel members is limited, and this system is therefore not adapted for tall plants. Hence, this system is not applicable for growing all sizes of plants and crops. Additionally, the horizontal conveying system is inflexible and does not provide means for long distance transport of plants vertically and diagonally, which makes this system vulnerable in case of malfunction of the horizontal conveying system. Furthermore, the hydroponics apparatus is not modifiable to be integrated with space-efficient vertical greenhouses since the hydroponics apparatus employs a horizontal means of conveying containers. Interestingly, it is not even suggested that the hydroponics apparatus can be integrated or connected with any type of greenhouse. Another disadvantage is that the seeds are not sown in pots, which makes this system inflexible since seeds which have not germinated cannot be removed efficiently. Yet a further disadvantage is that pots are not sterilised after harvest together with the growing medium; hence a method of decreasing waste is not indicated in US3432965.

The patent application WO2010/138027 describes a conveying system and a method for conveying containers. The system and method is primarily intended for moving containers with plants in greenhouses for cultivating plants. However, this document does not (i) disclose any specific methods and

arrangements for cultivating plants, (ii) indicate a cultivation system wherein pots are sterilised after harvest together with the growing medium in order to decrease waste, and (iii) describe the use of pumice for growing plants.

5 Furthermore, the greenhouse described in WO2010/138027 does not comprise a sowing device, a germination device, a device for movement of pots into and/or out of trays, an elevator which moves trays with pots with germinated seeds to the starting position of the top of the track, a sterilisation
10 device, and an optional biogas production facility. More importantly, the transport of trays is inflexible since it is dependent on the conveying device, and any other means of transporting the trays along and/or between the tracks has not been disclosed.

15 The patent application US 2009/0307973 A1 describes a vertically-integrated greenhouse which provides a system of food production in buildings and which can be installed in a double-skin façade. The trays with plants are arranged and affixed to a tray suspension system to which the trays are
20 adjustably affixed one above another in parallel vertical rows and can be vertically raised or lowered. However, a major disadvantage with this system is that the distance between the trays has to be increased as the plants grow which limits the number of trays in circulation. Hence, this
25 system is not adapted for industrial growth of plants and crops.

Summary of the invention

An important objective of the present invention is to provide a flexible and automated method and arrangement for
30 cultivating all sizes of plants, as well as to provide a

higher surface area for the crops to grow in, and thereby provide means for industrial scale production of crops.

An objective of the present invention is to provide a method and an arrangement for an energy efficient method of growing
5 plants.

A further objective of the present invention is to provide a method and an arrangement for industrial growth of plants which requires a minimum of space and energy.

At least one of these objectives is provided with a method
10 and an arrangement according to the independent claim.

Additional advantages are provided with the features of the dependent claims.

A method according to the invention for cultivating plants comprises the steps of sowing seeds in the growing medium in
15 sterilised pots using a sowing device and allowing the seeds to germinate in a germination device. The pots are automatically moved through a greenhouse to allow the germinated seeds to grow into plants, which are then harvested using a harvester. After harvest the pots are
20 sterilised together with the growing medium in a sterilisation device in order to provide sterilised pots with a growing medium. The method provides for efficient growth of plants and may be performed with a minimum of human intervention. By not exchanging the growing medium,
25 but instead sterilising the pot with the growing medium the waste from the method is drastically decreased in comparison with traditional methods.

Any growing medium that has been lost during harvest may be refilled before sowing.

The growing medium may be any growing medium that is suitable for re-use after sterilisation without being removed from the pot. The growing medium is preferable pumice, which surprisingly has shown to be very suitable to use in a method according to the invention.

The size of the pumice effects its suitability for growth of plants. A suitable particle size of the pumice for growing vegetables such as *Brassica rapa* var. *chinensis*, *Brassica rapa* spp. *Nipposinica*, *Chrysanthemum coronarium* and many other vegetables is 0,5-3 mm. Such pumice is sold as Hekla green. A major part of the pumice preferably has a particle size of 0,5-3 mm.

The pots may have an essentially quadratic shape viewed from above. This is an advantageous shape to handle for automatic devices that are to handle the pots.

The height, width and length of the pots may be in the interval 0,03-0,3 metres, preferably 0,05-0,2 metres and most preferred in the interval 0,07-0,12 metres. With such dimensions a sufficient amount of growing medium may be contained in the pot for the above mentioned plants to grow. It is favourable not to exceed the mentioned dimensions as this will add to the mass that has to be transported in the system and will thus add to the energy consumption of the method. Furthermore, it is advantageous not to increase the height of the pots also for the reason that the watering of the plants may be more difficult if the pots are made too high. If the pots are made too high it is not possible to let them absorb water from below.

The pots may have at least two opposite walls that are slightly inclining so that the cross-sectional area of the

pots decreases towards the bottom of the pots. This will make it easier to remove the pots from a support.

The pots with germinated seeds are preferably placed in trays. In this way a large number of pots may be controlled
5 in a more simple way. With the pots being placed in trays it is preferable to have the above mentioned inclining walls as this facilitates the removal of the pots from the trays.

The pots may be removed from the trays before germination but after sterilisation so that the trays are sterilised at
10 the same time as the pots. By removing the pots from the trays the pots may be placed in contact with each other during sowing and germination. This saves space and thus decreases the size and cost of the devices for handling the pots during sowing and germination. During sowing and
15 germination the plants do not extend outside the pot. During growth the plants may grow to extend outside the pot making it necessary to arrange the pots at a distance from each other.

The trays may have a decreasing width towards the bottom,
20 which corresponds to the width of the pots. By having corresponding shapes of the pots and the trays the pots may be well supported in the trays.

The trays may be elongated with a length axis to allow a single row of pots to be placed in the tray along the length
25 axis. By having only a single row of pots arranged in the trays the distance between the pots may be varied in one dimension during growth of the plants. This makes it possible to adapt the size between the pots as a function of the size of the plants during the growth. This makes it
30 possible to use the space in the greenhouse more

efficiently. Alternatively it is of course possible to have trays which allow more than one row of pots.

The method may also comprise the step of, before placing the pots in the trays, controlling that the seeds in the pots
5 have germinated so that only pots in which the seeds have germinated are placed in the trays. This is important in order to optimize the output of the method. In this way no pots without plants will be transported through the greenhouse.

10 The method may comprise the step of using a greenhouse with a track comprising at least two essentially parallel beams for supporting the trays, which track has a form resembling a helix, on which track the trays are arranged to be moved so that they are exposed to sunlight. By using such a
15 greenhouse an efficient use of the ground is provided, which is advantageous if the method is to be used in a city.

The method may comprise the use of a greenhouse in which the trays on the tracks are to be arranged with their length axes perpendicular to the beams of the tracks. This is
20 advantageous in that the distance between the pots in one direction may easily be adapted to the size of the plants.

The method may also include the step of intermittently watering the plants by intermittently providing water to the trays, wherein the pots and the trays are arranged for the
25 growing medium in the pots to absorb water in the trays. This is an uncomplicated way of watering the plants as the growing media in the pots absorb the necessary amount of water.

The method may comprise the step of providing the trays with
30 a bottom that is inclined at an angle of 0,5-2 degrees to

the horizontal direction. By providing the trays with an inclining bottom the water will stream along the tray. In this way water will be provided to all pots in the tray. With an inclining bottom it is also avoided that water forms static puddles in which germs and bacteria may grow.

The sterilisation may be performed by heating of the pots with the growing medium. By performing the sterilisation by heating the use of chemicals is avoided which may be advantageous.

10 The heating may be performed using steam. The use of steam is an uncomplicated way of sterilising the growing media, the pot and the tray.

Alternatively the heating may be performed using microwave radiation to heat the residual water in the pots, to thereby heat the growing medium and the pots. This is a fast and efficient way of heating the growing medium.

The time period during which the pots are heated may be chosen so that the majority of the bacteria is killed.

20 According to a second aspect of the present invention an arrangement for cultivating plants is provided, which apparatus comprises

a sowing device for sowing seeds in a growing medium arranged in pots,

a germination device for allowing the seeds to germinate in the pots,

a greenhouse for allowing the germinated seeds to grow to plants,

means for moving the pots through the greenhouse,

a harvester for harvesting the grown plants, and

a sterilisation device for sterilising the pots with
the growing medium after harvest in order to provide
5 sterilised pots with a growing medium.

The arrangement according to the second aspect of the
invention provides for efficient growth of plants and may be
performed with a minimum of human intervention. By not
exchanging the growing medium, but instead sterilising the
10 pot with the growing medium the waste from the method is
drastically decreased in comparison with traditional
methods.

The arrangement may comprising an arrangement device (i.e. a
device for movement of pots) for arrangement of the pots in
15 trays with a length axis. By arranging the pots in trays it
is possible to minimize the size of the pots, and thus also
the weight of the growing medium, while maintaining a stable
arrangement of the pots during growth.

The trays may have a decreasing width towards the bottom,
20 which corresponds to the width of the pots. By having the
pots and the trays arranged in this way the pots are well
supported by the trays and will also be relatively easily
removable due to the decreasing width of the pots. Pinching
of the pots in the trays is avoided due to the decreasing
25 width of the pot.

The trays may be elongated to allow a single row of pots to
be placed in the tray along the length axis. With such trays
the distance between the trays and thus also the pots may be
varied.

The means for moving may comprise a track comprising at least two essentially parallel beams for supporting the trays, which track may have a form resembling a helix, and at least one conveying device which is arranged to travel
5 along the track and which comprises a tray moving unit, which after passing plant tray is arranged to move at least one tray one step along the track, the conveying device thus moving containers stepwise along the track during the travel along the track. Such means for moving requires a limited
10 power as only a small number of trays are moved simultaneously. Alternatively the means for moving may comprise standard conveyor belts which are arranged to move the trays.

Alternatively the track may be divided in a number of track
15 portions connected by track connection means, such as, e.g., an elevator. The track portions may be horizontal.

The tracks may be arranged for arrangement of the trays on the tracks with their length axes perpendicular to the beams of the tracks. By arrangement of the trays in this way the
20 distance between the pots may be easily variable in one direction.

The track may be arranged inclined at an angle of 0,5-2 degrees to the horizontal direction, which hinders water from remaining on the bottom of the trays. Thus, the pots
25 may be provided with water by providing the trays with water at the high end. The water will then flow down the tray and pass the pots. The growing medium in the pots will absorb water, and the remaining water may flow out of the tray through an opening provided at the lower end of the tray.

The arrangement may comprise watering means arranged for intermittently providing water to the trays at the highest side of the trays. By intermittently providing water to the trays the watering may be performed more economically.

- 5 The watering means may comprise pipes situated at distances corresponding to the length of the steps of the stepwise movement of the trays. Thus, the trays are moved to positions corresponding to the positions of the pipes.

The arrangement may further comprise a system for
10 continuously purifying excess water that flows out from the openings in the trays. The excess water may pass through a mechanical filter for separating plant parts and pumice from the water. A biological filter comprising zeolite and pumice may be used to purify the water from pathogens and
15 metabolites. A second mechanical filter may be used to separate zeolite and pumice particles from the water purified by the biological filter. A UV filter may also be employed if necessary. The excess water which has passed through the various filters can be collected in buffer
20 tanks. The recycled excess water may be mixed with nutrient, fertilizer and fresh water, and then pumped back to the relevant parts of the arrangement.

The arrangement may be integrated or connected with a biogas production plant, so that organic waste from the harvest is
25 transported to the biogas production plant and bionutrients from the biogas production is transported to the means for sowing seeds in pots. Such an integration of a biogas production plant gives mutual advantages by providing a way of dispensing the waste products from one process to the
30 benefit of the other process.

The arrangement may also comprise means for inspection that the seeds in the pots have germinated. Such means may be comprised of a camera connected to a computer. By providing such means pots in which the seeds have not germinated may
5 be returned to the sowing device. In this way the efficiency of the arrangement may be optimised.

The trays may comprise a unique identification tag such as Radio Frequency Identification (RFID) tag or barcode, and scanning devices can be placed in various parts of the
10 arrangement. Hence, the movement of the trays within a track portion, as well as, between one track portion and another track portion below, can be monitored and controlled.

Short description of the drawings

15 In the following preferred embodiments of the invention will be described with reference to the appended drawings on which:

Fig 1 shows schematically, partly in cross-section, a building for industrial growth of plants.

20 Fig 2 shows in cross section the bottom of the building shown in Fig 1.

Fig 3 shows partly in cross section a building for industrial growth of plants according to an alternative embodiment of the present invention.

25 Fig 4 shows schematically an arrangement for cultivating plants according to an embodiment of the present invention.

Fig 5 is a flow diagram of a process for growing plants according to an embodiment of the present invention.

Fig 6 shows a tray and a robot for arranging and/or removing pots from the tray.

Fig 7 shows schematically a germination device for germination of seeds in the pots.

- 5 Fig 8 shows in cross section a tray with pots that is used in a process for industrial growth of plants according to an embodiment of the present invention.

Fig 9 is an exploded view of the tray and pots shown in Fig 8.

- 10 Fig 10 shows schematically a harvester used in the method and arrangement of the invention.

Fig 11 shows in cross section the track for the arrangement of trays with pots and plants according to an embodiment of the present invention.

- 15 Fig 12 shows the track for the arrangement of trays with pots and plants according to an alternative embodiment of the present invention.

Description of preferred embodiments of the invention

- 20 In the following description of preferred embodiments the same reference numerals will be used for similar features in the different figures. It is to be noted that the figures are not drawn to scale.

- Fig 1 shows, partly in cross-section, an arrangement according to an embodiment of the invention in the form of a building 1 for industrial growth of plants. The main part of the building is a greenhouse 2 in which two parallel tracks 3, 3', are arranged for supporting trays (Fig 3). The tracks 3, 3', have a form resembling a twinning helix, on which tracks 3, 3', the trays (Fig 3) are arranged to be moved
- 25

from the top of the building to the bottom of the building so that the plants are exposed to sunlight. The tracks 3, 3' can each comprise up to 4 parallel track portions (14). A sowing device, a germination device, a harvester and a sterilisation device (Fig 2) are arranged in the bottom of the building 1. The building 1 also comprises an elevator 4 for moving trays from the bottom of the building to the start of the track at the top of the building 1.

Fig 2 shows in cross section the bottom of the building shown in Fig 1. In Fig 2 it is shown how the tracks enters the bottom floor of the building 1. The trays are then passed through the harvester 5, and the sterilisation device 6. The pots are then removed from the trays and passes the sowing device 7, and the germination device 8 before the pots are arranged in the trays and lifted up to the top of the building by means of the elevator 4.

Fig 3 shows partly in cross section a building 1 for industrial growth of plants according to an alternative embodiment of the present invention. In the embodiment shown in Fig 3 the greenhouse comprises a track 3 with a number of track portions 14 with a length axis 15 for the arrangement of trays 9. The track portions are connected with track connecting means 18, which each have a length axis 19 and which connect the track portions 14. The trays 9 are elongated with a length axis 16 and arranged for placement of pots 17 in a single row along the length axis 16 of the tray. Growing medium in which plants are to grow is arranged in the pots 17. The track portions 14 are arranged for trays 9 to be arranged with their length axes 16 perpendicular to the length axes 15 of the track portions 14. In the shown embodiment the track connecting means comprises inclining

straight paths 18 with length axes 19, wherein the paths 18 are arranged for transportation of trays 9 with their length axes 16 parallel to their direction of transportation. The straight paths 18 are arranged for the trays to slide down
5 (diagonally) from one track portion 14 to another track portion 14 below. Furthermore, this embodiment also provides flexible means for trays to bypass a hindrance or a stop in the transportation route, e.g. caused by malfunction in the vertical transportation route of the elevator, by providing
10 diagonal means of transport of trays in the greenhouse.

Watering means in the form of water outlets 10, of which only three are shown, are provided to intermittently provide water to the trays 9 on the track portions 14. The water outlets 10 are arranged at a distance corresponding to the
15 intended pitch 12 between the trays 9. In this way each one of the trays 9 may be provided with water at each time. The time interval between the points of time when the trays 9 are provided with water is adapted to the vegetable in the pots 17 of the tray 9.

20 The description of the placement of trays on the track is valid also for the embodiment of Fig 1.

The greenhouses described above are preferred embodiments of the greenhouse according to the invention. However,
according to the invention it is possible to use any other
25 type of greenhouse in which plants are automatically moved.

Fig 4 shows schematically an arrangement 1 for cultivating plants according to an embodiment of the present invention. Fig 5 is a flow diagram of a process for growing plants according to an embodiment of the present invention. The
30 arrangement and the method will be described in the

following.

The growing medium in the pots 17 may be any growing medium, which is suitable for repeated cultivation of plants, so that new seeds may be sowed in the pots after harvest
5 without having to exchange the growing medium. A suitable growing medium is pumice. Pumice is available from many different sources and may have different properties. A suitable particle size of the pumice for growing vegetables such as *Brassica rapa* var. *chinensis*, *Brassica rapa* spp.
10 *Nipposinica*, *Chrysanthemum coronarium* and many other vegetables is 0,5-3 mm. Such pumice is sold as Hekla green. The volume of the growing medium is suitably about 0,5-1 litres. Pots and trays are described in more detail below with reference to Fig 8 and 9.

15 The pots with the growing medium are provided to the sowing device 7, in which seeds are sowed in the growing medium in the pots. This corresponds to step 32 in Fig 3. The sowing device 7 may comprise a machine such as a robot that puts the seeds into the growing medium and provides a suitable
20 amount of water to the growing medium. In the sowing device 7 the growing medium in the pots may also be provided with nutrients and fertilizers to enhance the growing of the plants.

Alternatively the sowing device is only partially automated.
25 The sowing of the seeds may be performed manually by a person operating the sowing device. The sowing device may then perform only parts of the sowing operation.

After the sowing the pots 17 are moved by a machine or manually to a germination device 8, in which the sowed seeds
30 are allowed to germinate. This corresponds to step 33 in Fig

3. In the germination device 8 the temperature and humidity are optimised to enhance germination and the pots 17 may also be provided with water at suitable intervals. The temperature and humidity in the germination device 8 are kept suitable for the specific seeds to germinate. The pots 17 are kept in the germination device 8 for a predetermined time after which they are transported manually or automatically to means for inspection 24.

In the means for inspection 24 the pots are inspected manually or by an automated system utilising a digital camera 23, to determine whether the seeds have germinated or not. The pots 17 in which the seeds have not germinated are sent back to the filling station 21 while the pots 17 in which the seeds have germinated are sent to the arrangement device 25 (i.e. the device for movement of pots).

In the arrangement device 25 (i.e. the device for movement of pots) the pots are placed in a single row in elongated trays 9. The pots 17 are placed in the trays 9 manually or automatically. The trays 9 are then moved to the greenhouse 2.

In the greenhouse the trays are moved automatically along the track 3, 3', in the greenhouse 2, as has been described above, to allow the germinated seeds to grow into plants. This corresponds to step 34 in Fig 3. The track in the greenhouse extends from a starting position, which preferably is situated at the top of the greenhouse, to an end position, which preferably is situated at the bottom of the greenhouse. By arranging the track inclining from the starting position to the end position the gravity will help moving the trays along the track. The track in the greenhouse 2 is described in more detail in connection with Figs

11 and 12. During movement through the greenhouse 2 the
pumice in the pots is provided with water by intermittently
providing water to the trays 9 in which the pots 17 are
arranged. The pots 17 are arranged to allow the pumice in
5 the pots 17 to absorb water from the trays 9.

After having passed the greenhouse the plants are ready for
harvest and are sent to a harvester 5 in which the grown
plants are harvested. This corresponds to step 35 in Fig 5.
The plants are inspected preferably before harvesting to
10 determine that the grown plants fulfil predetermined
requirements on size and or quality. The inspection may be
fully automated using a camera connected to a computer,
which may determine the size and the colour of the plants
from the image taken with the camera. Plants that do not
15 fulfil the predetermined requirements are preferably sent to
a biogas production plant 28, which preferably is integrated
with or directly connected to the arrangement 1. The
harvested plants may be packed and sold in a facility
integrated with the arrangement 1. Alternatively the plants
20 are packaged and transported to a sales facility, such as a
supermarket.

After harvest the trays 9, the pots 17 and the growing
medium in the pots 17 are sterilised by moving the trays and
the pots containing the growing medium, into a sterilisation
25 device 6 in which the trays and pots are subjected to steam.
After the sterilisation device the trays 9 are moved through
a cooling device 30 in which the trays 9, the pots 17 and
the growing medium are allowed to cool off. After the trays
9 have cooled off the trays 9 are transported to the
30 separating device 40 in which the pots 17 are removed from

the trays 9 and moved into the sowing device 7 described above.

Fig 6 shows the separating device 40 or alternatively the arrangement device 25 (i.e. device for movement of pots) for movement of pots 17 into or out from a tray 9. The device 5 25, 40 comprises a robot 42. In the separating device the robot 42 removes the sterilised pots 17 from the trays 9 and arranges them on a pallet 41. In the arrangement device (i.e. device for movement of pots) the robot 42 moves pots 10 17 with germinated seeds from the pallet 41 to the tray 17.

Fig 7 shows the germination device 8 into which pallets 41 with trays 9 are moved for germination.

Fig 8 shows a cross section of a tray 9 with pots 17 with plants 32. Fig 9 is an exploded view of a tray 9 with pots 15 17 and plants 32. As is shown in Fig 7 the tray consists of a bottom 44 and a lid 45. Holes 34 are formed in the lid in order to receive the pots 17. Water containers 56 are formed at both ends of the tray 8.

Fig 10 shows a specific embodiment of harvester 5, referred 20 to as harvesting unit 46, for harvesting the grown plants 43. Three parallel conveyor belts 47 move trays 9 with plants 43 into the harvesting unit 46. The empty trays are moved out of the harvester on second conveyor belts 48. The harvested plants are transported on third conveyor belts 49. 25 A camera 50 is provided to inspect the harvested plants. Alternatively a camera may be arranged to inspect the plants in the trays before harvest. The sterilisation device 6 may be integrated in the harvesting unit 46.

Fig 11 shows a cross section of the track 14 in more detail 30 according to an embodiment of the invention. The track 14

comprises a first beam 51 and a second beam 52. A tray 9 with a number of pots 17 is supported by the first beam 51 in one end of the tray 9 and by the second beam 52 in the other end of the tray 9. A conveying device 53 is arranged to travel along the first beam 51 and comprises a tray moving unit 55 which after passing a tray 9 is arranged to move the tray 9 one step along the track portion 14. Water outlets 10 are arranged at the first beam 51. Pots 17, in which plants 43 grow, are arranged in the trays 9.

Fig 12 shows a cross section of the track portion 14 in more detail according to an alternative embodiment of the invention. Only the differences between the embodiment of Fig 5 and Fig 6 will be described. The track portion 14 comprises a third beam 54 on which the conveying device 53 is arranged. Furthermore, the second beam 52 is arranged supporting the tray 9 at a position between the ends of the tray 9.

CLAIMS

21

1. A method for cultivating plants (43) in a building (1) including a greenhouse (2), comprising the steps of,

5

sowing seeds in a growing medium in sterilised pots (17) using a sowing device (7), wherein the sowing device (7) also provides water, nutrient and/or fertilizers to the growing medium,

10

allowing the seeds in the pots (17) to germinate in a germination device (8),

15

controlling whether the seeds in the pots (17) have germinated,

20

placing only pots (17) with germinated seeds into trays (9) with length axis (16) using a device for movement of pots (25),

25

automatically moving the pots through the greenhouse (2) to allow the germinated seeds to grow into plants (43), wherein the greenhouse comprises at least two parallel tracks (3, 3') for moving trays (9) from a starting position at the top of the building (1) to an end position at the bottom of said building, wherein said tracks are divided in a number of horizontal track portions (14) connected by track connecting means (18),

30

moving the trays (9) to a track portion (14) of one of said parallel tracks (3, 3') using an elevator (4), wherein the trays (9) are moved from the bottom of the building to a start position of the track portion (14) at the top of the building (1),

moving trays (9) through the greenhouse (2) by conveying means,

sliding down trays with their length axis (16) parallel to their direction of transportation from one track portion (14) to another track portion (14) below using said track connecting means (18), said track connecting means being arranged as inclining paths with length axis (19),

harvesting the grown plants (43) using a harvester (5), and

sterilising the pots with the growing medium, in a sterilisation device (6) after harvest in order to provide sterilised pots (17) with a growing medium.

2. The method according to claim 1, wherein the trays (9) are moved through the greenhouse (2) by conveying means comprising a track portion (14) comprising a first beam (51) and a second beam (52), wherein the trays (9) are supported by the beams, and a conveying device (53) arranged to travel along the first beam (51) and comprising tray moving unit (55), which after passing one of the trays (9) moves the tray (9) one step along the track portion (14), the conveying device (53) thus moving trays (9) stepwise along the track portion (14) during the travel along the track (14).
3. The method according to any one of the preceding claims, comprising the steps of sowing seeds in medium in pots (17) which have at least two opposite walls that are

slightly inclining, placing said pots (17) in trays (9) which have a decreasing width towards the bottom, and wherein the trays allow a single row of pots (17) to be placed in the tray (9) along the length axis (16), and
5 placing said trays (9) on the track (14) with their length axes (16) perpendicular to the beams (51, 52) of the track (14).

4. The method according to any one of the preceding claims,
10 comprising the step of intermittently watering the plants (43) by intermittently providing water to the trays (9), and further comprising the step of using trays (9) with a bottom that is inclined at an angle of 0,5-2 degrees to the horizontal direction, wherein the remaining water
15 flows out of the tray through an opening provided at the lower end of the tray.

5. The method according to claim 4, comprising steps for continuously purifying and recycling excess water that
20 flows out from the openings in the trays, wherein the excess water passes through (i) a mechanical filter for separating plant parts and growing medium from the water, (ii) a biological filter comprising zeolite and pumice for purifying the water from pathogens and metabolites,
25 (iii) a second mechanical filter for separating zeolite and growing medium particles from the water purified by the biological filter, and/or (iv) a UV filter, and wherein the excess water which has passed through the various filters is collected and thereafter mixed with
30 nutrient, fertilizer and/or fresh water, and then pumped back to the arrangement (1) for watering and providing plants with nutrient and fertilizer.

6. The method according to anyone of the preceding claims,
wherein the step of controlling that the seeds in the
pots (17) have germinated including using an automated
means for inspection (24) utilizing a digital camera (23)
5 connected to a computer.

7. The method according to anyone the preceding claims, com-
prising the step of harvesting the grown plants (43) us-
ing harvester (5) with a harvesting unit (46), wherein
10 three parallel first conveyor belts (47) move trays (9)
with plants (43) into harvesting unit (46) where the emp-
ty trays are moved out of the harvester on second convey-
or belts (48), and the harvested plants are transported
on third conveyor belts (49) where a camera (50) connect-
15 ed to a computer is provided to inspect the harvested
plants to determine the size and colour of the plants.

8. The method according to anyone of the preceding claims,
wherein organic wastes from the harvest inspection com-
prising plants that do not fulfill predetermined require-
20 ments, are sent to a biogas production plant (28) wherein
bionutrients from the biogas production are transported
to the sowing device (7).

9. The method according to anyone of the preceding claims,
comprising the step of sterilising the pots with the
growing medium (17) using a sterilisation device (6) in
which the trays and pots are subjected to steam, and the
trays (9) are thereafter moved through a cooling device
25 (30) in which the trays (9), the pots (17) and the grow-
ing medium are allowed to cool off and are transported to
a separating device (40), in which the pots (17) are re-
moved from the trays (9) and moved into the sowing device
30 (7).

10. The method according to anyone of the preceding claims,
wherein the sterilisation is performed using microwave
radiation to heat residual water in the pots, to thereby
5 heat the growing medium and the pots.

11. The method according to anyone of claims 1-10, further
comprising scanning unique identification tags of said
trays such as Radio Frequency Identification (RFID) tags
10 or barcodes in order to monitor and control movement of
the trays.

12. Arrangement (1) for cultivating plants (43) in a building
(1) with a greenhouse (2), characterized by,

15 a sowing device (7) for sowing seeds in a growing
medium arranged in pots (17), wherein the sowing device
(7) also is arranged for providing water, nutrient and/or
fertilizers to the growing medium,

20 a germination device (8) for allowing the seeds to
germinate in the pots (17),

25 means for inspection (24) for determining whether
the seeds have germinated,

a device for movement of pots (25), for placement
of pots (17) into trays (9) with length axis (16),

30 a greenhouse (2) for allowing the germinated seeds
to grow to plants (43), wherein the greenhouse comprises
two parallel tracks (3, 3') for moving trays (9) from a
start position at the top of the building to an end posi-
tion at the bottom of the building, wherein said tracks

are divided in a number of horizontal track portions (14) connected by track connecting means (18),

an elevator (4) for moving trays (9) to a track portion (14) of parallel tracks 3, 3', wherein the elevator (4) moves trays (9) from the bottom of the building to a start position of the track portion (14) at the top of the building (1),

conveying means for moving the trays (9) through the greenhouse (2),

wherein said track connecting means (18) are arranged as inclining paths with length axis (19), wherein the paths are arranged for transportation of trays (9) with their length axis (16) parallel to their direction of transportation, wherein said track connection means (18) are arranged for the trays to slide down from one track portion (14) to another track portion (14) below,

a harvester (5) for harvesting the grown plants (43), and,

a sterilisation device (6) for sterilising the pots (17) with the growing medium after harvest in order to provide sterilised pots (17) with a growing medium.

13. The arrangement according to claim 12, wherein the conveying means for moving the trays (9) through the greenhouse (2) comprises a track portion (14) comprising a first beam (51) and a second beam (52), wherein the trays (9) are supported by said beams, and a conveying device

(53) arranged to travel along the first beam (51) and comprising tray moving unit (55), which after passing one of the trays (9) moves the tray (9) one step along the track portion (14), the conveying device (53) thus moving
5 trays (9) stepwise along the track portion (14) during the travel along the track portion (14).

14. The arrangement according to any one of the preceding claims 12 and 13, wherein the pots (17) have at least two
10 opposite walls that are slightly inclining so that the cross-sectional area of the pots (17) decreases towards the bottom of the pots (17), and wherein the trays (9) have a decreasing width towards the bottom, which corresponds to the width of the pots (17), and wherein the
15 trays (9) are elongated to allow a single row of pots (17) to be placed in the tray (9) along the length axis (16), and wherein the track portion (14) is arranged for arrangement of the trays (9) on the track portion (14) with their length axes (16) perpendicular to the beams
20 (51, 52) of the track portion (14).

15. The arrangement (1) according to anyone of claims 12-14, wherein watering means are arranged for intermittently providing water to the trays (9) at the highest side, and
25 wherein the track portion (14) is arranged at inclined at an angle of 0,5-2 degrees to the horizontal direction, which hinders water from remaining on the bottom of the trays (9), and wherein the remaining water flows out of the tray through an opening provided at the lower end of
30 the tray.

16. The arrangement according to claim 15 as dependent on claim 14, wherein the watering means comprises pipes (10)

situated at distances corresponding to the length of the steps of the stepwise movement of the trays (9).

17. The arrangement to claim 15, comprising means for continuously purifying and recycling excess water that flows out from the openings in the trays, wherein the excess water passes through mechanical filters, biological filters and/or UV filters, and wherein the excess water which has passed through the filters is collected and thereafter mixed with nutrient, fertilizer and/or fresh water, and then pumped back to the arrangement (1) for watering and providing plants with nutrient and fertilizer.

18. The arrangement according to anyone of claims 12-17, wherein the means for inspection (24) that the seeds in the pots (17) have germinated includes an automated system utilizing a digital camera (23) connect to a computer.

19. The arrangement according to anyone of claims 12-18, wherein the harvester (5) comprises a harvesting unit (46) for harvesting the grown plants (43) wherein three parallel first conveyor belts (47) move trays (9) with plants (43) into harvesting unit (46), where the empty trays are moved out of the harvester on second conveyor belts (48), and the harvested plants are transported on third conveyor belts (49) where a camera (50) is provided to inspect the harvested plants to determine the size and colour of the plants of the harvested plants.

20. The arrangement according to anyone of claims 12-19, wherein organic wastes from the harvest inspection comprising plants that do not fulfil the predetermined re-

quirements, are sent to a biogas production plant (28) integrated or connected to arrangement (1), wherein bio-nutrients from the biogas production are transported to a sowing device (7) for sowing seeds.

5

21. The arrangement according to anyone of claims 12-20, comprising a sterilisation device (6) in which the trays and pots are subjected to steam, a cooling device (30) in which the sterilized trays (9), pots (17) and growing medium are allowed to cool off, a separation device (40) by which the pots (17) are removed from the trays (9) and moved into the sowing device (7).

10

22. The arrangement according to anyone of the preceding claims 12-21, wherein the sterilisation device comprises a microwave radiation source in order to employ microwave radiation to heat residual water in the pots, to thereby heat the growing medium and the pots.

15

23. The arrangement according to anyone of claims 12-22, wherein said trays comprise unique identification tags such as Radio Frequency Identification (RFID) tags or barcodes, and wherein said arrangement further comprises scanning devices, such that movement of the trays can be monitored and controlled.

20

25