

TRANSBODY COMMUNICATION SYSTEMS EMPLOYING COMMUNICATION CHANNELS

CROSS-REFERENCE TO RELATED APPLICATIONS

5

Pursuant to 35 U.S.C. § 119 (e), this application claims priority to the filing dates of the United States Provisional Patent Application Serial Nos.: 60/990,562 filed November 27, 2007; 60/990,567 filed November 27, 2007 and 60/990,572 filed November 27, 2007; which applications are incorporated herein by reference
10 for all purposes.

BACKGROUND

Communications play an important role in today's world. Transbody communications, for example, are finding increasing use in medical applications.
15 The term "transbody communications" generally refers to transmission of a signal from an in vivo location to a receiver location, e.g., a second in vivo location, a receiver location extracorporeally associated with the body, etc.

Communications, however, may be susceptible to errors. In particular, noisy transmission environments may distort and corrupt communication data.
20 The noisy transmission environments include the body. Additionally, communication devices may err in signal generation and measurement related to the communication data.

Further, various devices and combinations of devices may exact high power consumption, resulting in a relatively short life cycle for the devices inside
25 the body. Such a short life cycle may result in replacement surgeries and other inconvenient, expensive, and / or high-risk procedures.

As such, there is a continued need for accurate communications and error-free data provided via long-lasting devices. Of particular interest is development of communications channels that may be readily deployed to reliably
30 communicate information from an in vivo location to a receiver positioned in, or in close physical proximity to, a body.

Summary

An embodiment of a system of the present invention may include an in vivo transmitter to transmit an encoded signal; a transbody functionality module to facilitate communication of the encoded signal; and a receiver to receive the encoded signal to at least facilitate accurate transbody communications and conserve power consumption. An embodiment of the system may further include at least one of a beacon functionality module, a frequency hopping functionality module, and a collision avoidance functionality module. Related methods and apparatus are also provided.

According to an aspect of the present invention, there is provided a system comprising: an in vivo transmitter to transmit an encoded signal; a transbody functionality module to facilitate communication of the encoded signal; and a receiver to receive the encoded signal; wherein the receiver comprises a wake up module to periodically wake up the receiver from a sleep mode to a first energy consumption mode to detect the transmitted encoded signal during a first period, wherein when the receiver detects the transmitted encoded signal during the first period, the receiver transitions to a second energy consumption mode that is greater than the first energy consumption mode, and wherein when the receiver does not detect the transmitted encoded signal during the first period, the receiver transitions back to the sleep mode.

According to another aspect of the present invention, there is provided a method comprising: transmitting, via an in vivo transmitter, an encoded signal; facilitating, via a transbody functionality module, communication of the signal; and receiving, via a receiver, the encoded signal; wherein receiving the encoded signal by the receiver further comprises: periodically waking up the receiver from a sleep mode to a first energy consumption mode to detect the transmitted encoded signal during a first period, wherein when the receiver detects the transmitted encoded signal during the first period, transitioning the receiver to a second energy consumption mode that is greater than the first energy consumption mode, and wherein when the receiver does not detect the transmitted encoded signal during the first period, transitioning the receiver back to the sleep mode.

According to yet another aspect of the present invention, there is provided an article, comprising: a storage medium having instructions, that when executed by a computing platform, result in execution of a method of providing transbody communications employing communication channels in a living body, the method comprising: transmitting, via an in vivo transmitter, an encoded signal; facilitating, via a transbody functionality module, communication of the signal; and receiving, via a receiver, the encoded signal wherein receiving the encoded signal by the receiver further comprises: periodically waking up the receiver from a sleep mode to a first energy consumption mode to detect the transmitted encoded signal during a first period, wherein when the receiver detects the transmitted encoded signal during the first period, transitioning the receiver to a second energy consumption mode that is greater than the first energy consumption mode, and wherein when the receiver does not detect the transmitted encoded signal during the first period, transitioning the receiver back to the sleep mode.

BRIEF DESCRIPTION OF THE FIGURES

FIGURE 1 illustrates a communication environment, including a transbody communication system having a transbody functionality module.

5 **FIGURE 2** illustrates the transbody functionality module of **FIGURE 1** in greater detail.

FIGURE 3A illustrates a beacon wakeup module providing a sniff period longer than a transmit signal repetition period.

10 **FIGURE 3B** illustrates a beacon wakeup module providing a short but frequent sniff period and a long transmit packet are provided.

FIGURE 4A illustrates a resonant, narrow band analog circuit.

FIGURE 4B illustrates classic power detection circuit.

FIGURE 5 illustrates beacon functionality having a long period of a continuous wave tone.

15 **FIGURE 6** illustrates a beacon functionality wherein a beacon is associated with one frequency and a message is associated with another frequency.

FIGURE 7 illustrates a beacon functionality associated with a two-beacon scheme.

20 **FIGURE 8** illustrates a beacon functionality associated with a beacon signal where frequency is a function of time.

FIGURE 9 further illustrates a beacon functionality associated with a beacon signal where frequency is a function of time.

25 **FIGURE 10** illustrates a collision avoidance functionality having one collision avoidance technique.

FIGURES 11A – 11D illustrate a collision avoidance functionality having another collision avoidance approach.

FIGURES 12A and 12B illustrate a collision avoidance functionality having a technique to detect a low amplitude signal in a noisy environment.

30

DETAILED DESCRIPTION

Transbody communication systems employing communication channels
5 are provided. Various aspects facilitate accurate communications in noisy
environments as well as provide enhanced power conservation features. More
particularly, various aspects may be associated with transbody communication
systems, e.g., an in vivo transmitter and a signal receiver (sometimes referred to
herein as a "receiver") associated with a body. The receiver may be configured
10 to receive and decode a signal from the in vivo transmitter. Various aspects of
the invention are characterized by employing a specific communication channel
having transbody functionality, e.g., via a transbody functionality module.
Related methods are also provided.

The invention may have broad applicability to medical and non-medical
15 fields. The medical fields include, for example, transbody communications
systems associated with various medical and therapeutic devices, e.g., cardiac
devices, ingestible devices, etc. The non-medical fields include, for example,
body associated devices such as gaming devices incorporating physiologic
sensing functionality, etc.

20 **FIGURE 1** illustrates a communication environment 100, including a
transbody communication system 102. The transbody communication system
102 comprises, for example, an in vivo transmitter 104, a transbody functionality
module 106, and a receiver 108. In various aspects, the in vivo transmitter 104
transmits a signal, e.g., an encoded signal, via the transbody communication
25 module 104 to the receiver 108, as hereinafter described in detail.

1.0 In Vivo Transmitter

Implementations of the in vivo transmitter may vary widely. Generally, an
in vivo transmitter 102 includes any in vivo device capable of transmitting a
30 signal, e.g., an encoded signal.

In various aspects, the in vivo transmitter 102 may be associated with
various devices, e.g., cardiac-related devices, ingestible devices, neural-
stimulation related devices, medications, etc. The in vivo transmitter 102, for

example, may be wholly or partially integrated with such a device, medication, etc.

One example of such a device is a pharma-informatics enabled pharmaceutical composition, described in PCT Application Serial No. 5 US2006/016370. Another example is an ingestible event marker (IEM) and a personal receiver, described in U.S. Provisional Patent Application Serial No. 60/949,223. Still another example is a smart parenteral device, described in PCT/US2007/15547. Yet another example is a smart implantable fluid transport device, described in U.S. Provisional Patent Application Serial No. 60/989,078. 10 Still further examples include implantable physiologic event recorders, described in U.S. Patent Nos. 5,919,210, 5,989,352, 6,699,200, and 6,895,275; various systems and methods described in PCT application WO2006/116718. Still further examples include PCT application serial Nos. PCT/ US2007/022257; PCT/US07/24225; PCT/US08/56296; PCT/US2008/56299 and PCT/US08/77753; 15 and well as United States Provisional Application Nos. 61/034,085 and 61/105,346. Each of the foregoing is herein incorporated in its entirety by reference.

The signal transmitted by the device generally includes any signal, data, identifier, representative thereof, etc. Signals include encoded signals, e.g., 20 encode at origin and decoded at destination. Examples of signals include an identifier of a pharmaceutical, a parenteral delivery device, an ingestible event marker, etc., *supra*.

2.0 Transbody Functionality Module

25 The signal may be transmitted from the in vivo transmitter 104 via the transbody functionality module 106 to the receiver 108. The transbody functionality module 106 generally uses protocol(s), communication channels, etc., capable of facilitating accurate receipt of signals, data, etc. and / or facilitating low power consumption. Such transbody functionality modules 106 30 include beacon functionality; frequency hopping functionality, and collision avoidance functionality. Each of the foregoing is discussed in detail hereinafter.

In various aspects, the transbody functionality module 106, and / or one or a combination of its submodules (described hereinafter), may be implemented as

software, e.g., digital signal processing software; hardware, e.g., a circuit; or combinations thereof.

Communication media for transmission may vary. In one aspect, the body of a patient may be employed as a conduction medium for the signal. As such,
5 the signal is conducted between the in vivo transmitter and the receiver via body fluids, etc. In another aspect, the signal is transmitted via radio frequency (RF) transmission. One skilled in the art will recognize that other communication media are also possible.

FIGURE 2 illustrates the transbody functionality module 106 of **FIGURE 1**
10 in greater detail. In various aspects, the transbody functionality modules includes a beacon functionality module 200, a frequency hopping functionality module 202, and a collision avoidance functionality module 204.

2.1 BEACON FUNCTIONALITY MODULE

15 Various aspects may employ the beacon functionality module 200. In various aspects, the beacon functionality module 200 may employ one or more of the following: a beacon wakeup module 200A, a beacon signal module 200B, a wave/frequency module 200C, a multiple frequency module 200D, and a modulated signal module 200E.

20 The beacon functionality module 200 may be associated with beacon communications, e.g., a beacon communication channel, a beacon protocol, etc. For the purpose of the present disclosure, beacons are typically signals sent either as part of a message or to augment a message (sometimes referred to herein as "beacon signals"). The beacons may have well-defined characteristics,
25 such as frequency. Beacons may be detected readily in noisy environments and may be used for a trigger to a sniff circuit, such as those described above.

In one aspect, the beacon functionality module 200 may comprise the beacon wakeup module 200A, having wakeup functionality. Wakeup functionality generally comprises the functionality to operate in high power modes
30 only during specific times, e.g., short periods for specific purposes, e.g., to receive a signal, etc. An important consideration on a receiver portion of a system is that it be of low power. This feature may be advantageous in an implanted receiver, to provide for both small size and to preserve a long-functioning electrical supply from a battery. The beacon wakeup module 200A

may enable these advantages by having the receiver operate in a high power mode for very limited periods of time. Short duty cycles of this kind can provide optimal system size and energy draw features.

In practice, the receiver may "wake up" periodically, and at low energy consumption, to perform a "sniff function" via, for example, a sniff circuit. For the purpose of the present application, the term "sniff function" generally refers to a short, low-power function to determine if a transmitter is present. If a transmitter signal is detected by the sniff function, the device may transition to a higher power communication decode mode. If a transmitter signal is not present, the receiver may return, e.g., immediately return, to sleep mode. In this manner, energy is conserved during relatively long periods when a transmitter signal is not present, while high-power capabilities remain available for efficient decode mode operations during the relatively few periods when a transmit signal is present.

Several modes, and combination thereof, may be available for operating the sniff circuit. By matching the needs of a particular system to the sniff circuit configuration, an optimized system may be achieved.

FIGURE 3A illustrates the beacon wakeup module 200A wherein a sniff period 300 is longer than a transmit signal repetition period 302. The time function is provided on the x axis. As shown, the transmit signal repeats periodically, with a sniff function also running. In practice, effectively, the sniff period 300 is typically longer than the transmit signal repetition period 302. In various aspects, there may be a relatively a long period of time between the sniff periods. In this way, the sniff function, e.g., implemented as a sniff circuit, is guaranteed to have at least one transmission to occur each time the sniff circuit is active.

FIGURE 3B illustrates the beacon wakeup module 200A wherein a short but frequent sniff period 306 and a long transmit packet 308 are provided. The sniff circuit will activate at some point during the transmit time. In this manner, the sniff circuit may detect the transmit signal and switch into a high power decode mode.

An additional beacon wakeup aspect is to provide the "sniffing" function in a continuous mode. In contrast to the approaches provided above, this aspect of the transbody beacon transmission channel may exploit the fact that the total energy consumption is the product of average power consumption and time. In

this aspect, the system may minimize the total energy consumption by having very short periods of activity, in which case the periods of activity are averaged down to a small number. Alternately, a low continuous sniff activity is provided. In this case, the configuration provides a sufficiently low power so that the
5 transmission receiver runs continuously with a total energy consumption at an appropriate level for the parameters of a specific system.

The system may be passive. Two examples of circuit implementations are provided.

FIGURE 4A illustrates a resonant, narrow band analog circuit 400,
10 including input antenna 402, inductor 404, and capacitors 406. In various aspects, the resonant, narrow band analog circuit 400 may have a high impedance. An LC resonator may be provided that is tuned to the frequency of the transmitted signal. The voltage across the LC circuit may be measured, and run into a comparator. When the voltage measurement exceeds a certain value,
15 a gate may be triggered. The circuitry goes then into a high power mode.

FIGURE 4B shows a classic power detect circuit 408. The power detect circuit 408 may be of those known in the art, such as those used in an AM radio to give a light signal that indicates receipt of a radio signal. In one aspect, the power detect circuit 408 is an LC resonant circuit, i.e., a tank circuit. When a
20 signal of the LC resonant frequency is present, the LC tank circuit 'rings up'. Because the circuit has a high Q, its voltage increases dramatically. That voltage is rectified by the diode. When that voltage exceeds a threshold set by V_{ref} , a comparator is triggered. The comparator informs the microprocessor that a signal/circuit is present and directs it to enter the high power mode.

25 Each of the above-described circuits may be very low powered and may comprise only passive components, with the exception of the comparator. The comparator may also be of very low power. Each circuit may operate continuously. Each circuit may inform the microprocessor when a transmitter is present, e.g., a signal is transmitted, to go into the high power mode. For each of
30 these circuits, a useful prerequisite may be a well defined frequency for the transmitter.

A type of beacon signal associated with the present transbody communication channel is a continuous wave, single frequency tone. In such a

case, the continuous single frequency tone triggers either of the circuits in **FIGURES 4A** or **4B**, when they are tuned to the correct frequency.

The beacon signal module 200B may provide for beacon signals to be detected digitally, as shown in **FIGURES 3A** or **3B**. This may be accomplished by
5 sampling the beacon signals with an A->D converter. The beacon signals are put in a digital processing system. Beacon signals are detected by a single frequency tone which has a very strong characteristic.

Examples of such systems are provided in **FIGURE 5**.

FIGURE 5 illustrates beacon functionality having a long period of a
10 continuous wave tone, e.g., via the wave/frequency module 200C. In one aspect, the beacon signal consists of a long period of the continuous wave tone. This continuous wave tone has both a modulated portion, which holds the information, and unmodulated portion. In this frequency domain, there is typically a period of well defined frequency. The modulation tends to smear the frequency spectrum.
15 This portion of the wave tone serves as the beacon. It has a single tone in the frequency domain, and is easily recognizable in the spectrogram.

Either of the methods shown previously can detect the single frequency tone. This frequency tone alerts the processing circuitry that a message is coming. It then it moves into decode mode so that the message can be
20 understood. In **FIGURE 5**, this is shown as one packet.

FIGURE 6 illustrates beacon functionality wherein a beacon is associated with one frequency, e.g., a beacon channel, and a message is associated with another frequency, e.g., a message channel. This configuration may be advantageous, for example, when the system is dealing with multiple transmit
25 signals. The solid line represents the beacon from Transmit Signal 1. The dashed line represents the beacon from Transmit Signal 2. In various transmission situations, the Transmit Signal 2's beacon might overlap with that of Transmit Signal 1, as depicted.

Message Signal 1 and Message Signal 2 can be at different frequencies
30 from their respective beacons. One advantage may be that the beacon from Transmit Signal 2 does not interfere with the message from Transmit Signal 1 at all, even though they are transmitted at the same time. By contrast, if an approach were taken in the example shown in **FIGURE 5**, the beacon from the

second transmit signal would most likely obscure the message from the first transmit signal.

In this case, the beacon channel is a well defined frequency band. A message is provided in the channel where the data are actually transmitted.

5 Interference between different messages in the message channel can be handled through collision avoidance, described below. While **FIGURE 6** is shown with two transmitters, it will be apparent to one of ordinary skill in the art to modify the system so as to scale it to many more transmitters. The requirements of a particular system may, to some extent, dictate the particular architecture of that

10 system.

FIGURE 7 illustrates beacon functionality associated with a two-beacon scheme, e.g., Beacon 1 and Beacon 2. In this case, there is a well-defined mathematical relationship between the frequency of the beacon channel and the frequency of the message channel. If the beacon is a continuous wave signal, or

15 a signal with a very simple modulation, it will be a simple matter to detect the carrier frequency of the beacon signal. In one case, for example, the beacon is at frequency $2f$, and the message is at frequency f , as shown in **FIGURE 7**. In this case, the value of f can be determined from the beacon channel. As a result, if the message is to be demodulated, the frequency is known exactly.

20 This aspect may be used, *inter alia*, to address frequency uncertainty. This approach may provide a workable system for message channel modulations which do not have well defined carrier frequencies.

One example of such message channel modulations is spread spectrum modulations. An attempt to determine the frequency of a spread spectrum modulation in and by itself, can be difficult because there is not a well defined

25 peak in the frequency spectrum. However, having the beacon channel accompanying the message channel with a well-defined mathematical relationship allows the message channel frequency to be determined precisely from the beacon channel. The message channel can then be demodulated

30 based on that information.

The above description is of a beacon as a continuous single frequency tone. However, in another aspect, the beacon could have a simple modulation on it. An example of such an aspect is using on-off keying (OOK), or simple frequency modulation. In various aspects, of particular utility is a frequency key

shifting (FSK) two tone beacon signal created by two different divide ratios of the master silicon oscillator. This may provide both a unique spectral signature and the frequency ratio of the two tones are invariant to the frequency drift of the silicon oscillator, e.g., an IEM silicon oscillator. The frequency ratio metric may
5 provide a high probability that the signal detected is sourced by the preferred source device, e.g., the IEM. This approach gives the beacon a distinctive signature that is uniquely identifiable from other interferers. In this manner, the system does not risk confusing the beacon with other jammers from the environment. One key characteristic of the frequency is that it stands out as
10 distinctive, and still has a well-defined mathematical relationship in terms of carrier frequency.

FIGURE 8 illustrates beacon functionality associated with a beacon signal where frequency is a function of time. One problem that can occur with transmitters is that the carrier frequency is set by a silicon oscillator, and not by a
15 crystal oscillator. This introduces a large uncertainty in characteristic frequency. Determination of that frequency may be a key challenge, both in terms of decoding the packet and detecting the beacon frequency.

The circuits provided in **FIGURES 4A** and **4B** provide an example of this approach. If these circuits have high power (Q), the frequency uncertainty may
20 cause the beacon to fall outside of the response function of the sniff circuits. Thus, as illustrated in **FIGURES 8** and **9** another type of beacon may be employed. Frequency 700 is ramped over some range, providing a message. Two narrow band filters are provided. The signal is ramped from an f_{high} to an f_{low} . Two narrow band filters are tuned to f_1 and f_2 , e.g., via the multiple
25 frequency module 200D. Frequencies f_1 and f_2 fall between f_{high} and f_{low} .

The output of the filter at f_1 shows no power, shows a blip in power as the beacon frequency is ramped through f_1 at time t_1 , and then shows no power. Similarly, the output of the filter at f_2 would show no power, show a blip in power as the beacon frequency is ramped through f_2 at time t_2 , and then shows no
30 power.

By building a timed-window comparator, an analog sniff circuit is employed which triggers on the time difference between t_1 and t_2 . This can be implemented digitally or in an analog approach. In this case, when the circuit is

set on time t_1 , if time t_2 falls within some defined window t_0 , it indicates that a signal is present.

The ramp is a very distinctive signature. Frequency f_1 firing will be detected, and (by example) 10ms later, f_2 firing is detected. If those two events
5 happen within the defined time interval t_0 , plus or minus t' , it indicates that a signal is present. The wakeup circuit is then triggered. The resulting design provides a very low power analog circuit. An important application of the circuit is to determine the frequency as shown in **FIGURE 8**.

The beacon may be modulated to assure that its signature will be
10 distinctive, e.g., via the modulated signal module 200E. One approach to this method is to have the beacon alternate between two frequencies. When this alternation is detected with the well-defined frequency difference and well-defined time period, the confidence level can be very high that a beacon had been detected, rather than some background signal. A similar result can be achieved
15 with on-off keying, in a frequency modulation keying approach.

Any standard modulation technique can be applied to a beacon to give it a distinctive character. In various aspects, data may be imprinted on the beacon, to avoid it being confused with any other signal. In various aspects, the sniff circuit triggers only on the beacon.

20 There are multiple beacon approaches available to avoid interference. In the idea related to **FIGURE 6**, if there are two beacons transmitting at the same time, transmitter 1 could have beacons at multiple frequencies, e.g., via multiple frequency module 200D, to avoid effects from interference. In a related approach, the aspect is simply to have beacons at different frequencies to avoid
25 contention between the beacons.

In various aspects, a frequency ratio of a beacon and data channel is invariant to frequency error in the ingestible event marker system to provide additional assurance of detection of the encoded signal.

30

2.2 FREQUENCY HOPPING FUNCTIONALLITY MODULE

Various aspects may employ frequency hopping functionality module. The frequency hopping functionality module 202 may be associated with the specific

communications channel(s), frequency hopping protocol, etc. As such, various aspects may utilize one or more frequency hopping protocols. For example, the receiver may search the designated range of frequencies in which the transmission could fall. When a single proper decode is achieved, the in vivo
5 transmitter has accomplished its mission of communicating its digital information payload to the receiver.

The transmitted frequency uncertainty provided by random frequency hopping, e.g., via a random module 202A, may create multiple benefits. One such benefit, for example, may be easy implementation on a small die. To
10 illustrate, the in vivo transmitter carrier frequency oscillator can be an inaccurate free running oscillator that is easily implemented on a small portion of a 1 mm die. Accuracies on the order of +/- 20 are easily tolerated. This is because the receiver employs frequency searching algorithms.

Another such benefit may be extended battery life. To illustrate, over the
15 course of the transmitter battery life, e.g., three to ten minutes, the probability of the transmitter transmitting on a clear channel that can be received by the frequency agile receiver may be significantly enhanced due to random frequency hopping.

Still another benefit may be minimized collision events in high volume
20 environments. To illustrate, minimization of collision probability when multiple in vivo transmitters, e.g., ingestible event markers, are potentially transmitting simultaneously, such as in instances where the multiple ingestible event markers are ingested concurrently or in close temporal proximity. Stated differently, without frequency hopping functionality, there may be a high probability that
25 ingestible event markers of a similar lot will transmit on the same (or nearly the same) frequency, resulting in multiple collisions.

In certain aspects, the useful frequency spectrum for use in volume conduction applications ranges from about 3 kHz to 150 kHz. Through detailed animal studies it has been observed that in some environments, the in vivo
30 transmitter, *supra*, having a received signal level in the range of 1 to 100 μ V may compete with narrow band interfering signals on the order of hundreds to thousands of μ V in the same frequency spectrum. To mitigate the destructive nature of interfering signals, a frequency hopping channel or protocol may be

employed in which the in vivo transmitter randomly frequency hops a narrow band transmitted signal, e.g., a modulated signal such as a binary phase shift keying (BPSK) signal or FSK signal, output on each transmission.

5

2.3 COLLISION AVOIDANCE FUNCTIONALITY MODULE

Various aspects may employ a collision avoidance functionality module. The collision avoidance functionality module may be associated with the specific communications channel(s), collision avoidance protocols, etc. As such, various aspects may utilize various collision avoidance protocol techniques associated with the specific communications channel(s). Collision avoidance techniques may be particularly useful, for example, in environments where two or more in vivo transmitters are present, e.g., where an individual ingests multiple IEMs. In such an environment, if the various in vivo transmitters send their signals continuously, the transmission of one may obscure the transmission from all the other in vivo transmitters. As a result, failure to detect signals may increase significantly.

Various aspects may include various collision avoidance approaches, alone or in various combinations.

One such approach employs multiple transmit frequencies. By using frequency-selective filtering, the transmitter broadcasting at f_1 can be distinguished from the transmitter broadcasting at f_2 , even if they are transmitting simultaneously. An alternative to this approach is illustrated in **Figure 9**.

FIGURE 10 illustrates a first collision avoidance technique, e.g., via a transmitter module 204A, wherein Transmitter 1 is broadcasting on f_1 . Transmitter 2 is broadcasting on f_2 . A receiver and two band pass filters are provided, e.g., via multiple band pass filter module 204E. Band pass filter 1 is sensitive to f_1 , band pass filter 2 is sensitive to f_2 . Once signals from the transmitters, e.g., two IEMs associated with Pill 1 and Pill 2, respectively, get through their respective band pass filters, the signals go to demodulators. In various aspects, these demodulators can be implemented as separate analog circuits or in the digital domain. In this manner, collisions may be avoided.

FIGURES 11A – 11D illustrate another collision avoidance approach. In various aspects, the specific communications channel(s) may employ duty cycle

modulation, e.g., via a duty cycle modulation module 204B,, wherein a transmitter need not transmit all the time. If two transmitters, e.g., xmtr1 and xmtr2, are not transmitting simultaneously, they will not interfere with each other. For example, If two transmitters are used which have low duty cycles, such as broadcasting
5 10% of the time and off 90% of the time, then probabilistically there is only a 20% chance that the signals will overlap with each other. In this manner, collisions may be avoided.

With reference to **FIGURE 11A**, there a transmitter 1, e.g., xmtr1, that is only on 10% of the time. There is transmitter 2, e.g., xmtr2, that is also only on
10 10% of the time. Of course, there is some probability that they will transmit simultaneously. However, that probability can be controlled by changing the duty cycle and the frequency spread. As a result, if these two transmit periods are slightly different, they will come in and out of interference with each other. The overlap can be controlled, however, by dithering the duty cycle and the frequency
15 spread, e.g., via dither module 204F and spread spectrum module 204D, respectively. In this manner, otherwise occurring collisions may be avoided.

With reference to **FIGURE 11B**, dashed transmitter xmtr2 has a slightly shorter period than the solid transmitter xmtr1. Even though the transmitters begin broadcasting at the same time, after some number of transmissions, the
20 transmitters come out of alignment with each other. As a result, they are now distinct from one another and otherwise occurring collisions may be avoided.

With reference to **FIGURE 11C**, a similar effect can be obtained by having a spread of oscillator frequencies. In practice, the silicon oscillators used for these transmitters have a spread of a few percent in frequency. A 1% difference
25 in frequency means that after a 100 transmissions, two oscillators 1008, 1010 that began in phase with each other are no longer in phase with each other. Various aspects may be based on frequency distribution or the frequencies can also be programmed to be explicitly different, e.g., to have some range of periods. Noise dithering a voltage controlled oscillator frequency can also create
30 this frequency spread.

With respect to **FIGURE 11D**, the retry period is randomized. In this example, xmtr1 broadcasts and then waits some random period of time before broadcasting again. The xmtr1 then waits another random period of time before broadcasting again, and so forth. Xmtr2 begins broadcasting at the same time.

However, in this case it waits a random time before the next transmission, and waits another random time before the next transmission and so forth. In this way, the probability that two transmitters broadcast simultaneously can be controlled by affecting the standard deviation of the retry periods.

5 This approach can be based on a pseudo-random sequence that is preprogrammed into the chip. It can also be based on a real physical random number generator (thermal noise), or on the serial number on the chip. Since every transmitter has a unique serial number, some of the lower bits of the serial number can be used to program this randomization time, either directly or by
10 using a linear shift register.

Additional aspects of the transbody transmission channel use spread spectrum transmission to modulate the transmit message. This approach can be direct spread spectrum or frequency hopping spread spectrum. As an example, any of the code division multiple access (CDMA) techniques developed for cell
15 phones that allow for multitudes of cell phones to broadcast on the same frequency without interference can be employed in this aspect. This aspect can also be based on any of the well known codes in spread spectrum, such as Gold Codes or Kasami codes.

The challenge to be addressed is approached probabilistically. A code is
20 selected such that there are sufficiently many that the probability of two transmitters having the same code broadcasting at the same time is sufficiently small. This approach ties into the idea of using a beacon to find the carrier frequency because spread spectrum transmissions in general do not have a well defined carrier frequency. That information is determined, such as from the
25 beacon.

In certain applications, it is useful to combine the different techniques. By example, when there is a long duty cycle, spread spectrum transmission can be particularly valuable. In this case, the probability of a collision happening is the probability of the long duty cycle times the probability of the spread spectrum.
30 There are no restrictions on combining techniques.

In calculations, it is shown that duty cycle works very well for two or three transmitters operating simultaneously. However, in regards to certain applications, the duty cycle method breaks down when there are more than five transmitters providing data in an overlapping time frame.

The most straightforward method to bolster the duty cycle is to add retransmit randomization, e.g., via retransmit randomization module 204C. By adding a few bits of retransmit randomization, the effect is immediately rendered much less pronounced. In this aspect, the system can easily distinguish five to
5 ten simultaneous transmissions.

To get beyond ten transmissions, spread spectrum is one approach of interest. As systems go to many simultaneous transmitters, even if one has a short duty cycle, the total time that multiple transmitters are transmitting becomes a significant portion of the time and collisions become unavoidable.

10 In systems requiring only a few transmitters, system design can rely on using simpler approaches, such as long duty cycles. Multiple transmit frequencies may be employed in a controlled environment when the frequencies of the transmitters are known. For three to ten transmitters, retransmit randomization works well. Beyond ten transmitters, spread spectrum is one
15 approach that may be employed, and it can combine spread spectrum with other techniques.

Plots on long duty cycle show with three simultaneous transmitters there is about a 1% chance of a transmitter not being detected because of a collision. This is during a one minute transmit interval. One important feature of some
20 transmitters systems is that the transmitters have a finite lifetime. In systems where transmitters have very long lifetimes, these concerns may be absent.

For other kinds of implanted sensors, these are still very important considerations for power consumption. If the system must wait an hour before a window clear enough to transmit a signal is available, then the transmitter is
25 using power all that time.

Another possibility opens up when systems have more sophisticated transmitters. The transmitter can listen for a quiet channel, for example, waiting until it hears nothing transmitting and then transmit.

The spread spectrum approach is quantifiable, depending on how many
30 distinct codes are used. When the Kasami set of codes are used there are 32,000 distinct codes. In this case the probability of having two transmitters transmit on the same code is $1/(32,000)^2$. That probability goes up geometrically with the number of transmitters. Even doing nothing to select transmitters that

have distinct codes, and relying on the randomization of code selection, it supports tens, if not hundreds, of transmitters.

In certain aspects, receivers of the system are configured to selectively receive a signal in a quiet part of a given spectrum. Figure 12A shows an aspect
5 addressing the problem of detecting a low amplitude signal in a noisy environment. One approach to that problem is to find a quiet place in the noise spectrum. The detector of the receiver is programmed to that frequency band. The transmitter periodically broadcasts in that frequency band.

FIGURES 12A and 12B illustrate a technique to detect a low amplitude
10 signal in a noisy environment. With reference to **FIGURE 12A**, in the case where the receiver surveys the noise spectrum, power is a function of frequency. There is a noisy region, quiet region, followed by a noisy region. The broadcast is provided in the quiet region because the least amount of interference is in that region.

15 In **FIGURE 12B**, the transmission occurs at multiple different frequencies, e.g., a ramping scheme. In various aspects, other schemes may be used such as frequency hopping or random scheme. Typically, the chosen scheme will densely covers the frequency band of interest. In practice, the transmitter will eventually jump into the quiet band and eventually transmit in the quiet band. By
20 having the receiver listen only in that quiet band, there is a good chance of receiving / decoding that signal due to the excellent signal to noise ratio (SNR).

The above configuration in which the receiver is employed to receive only a quiet band is not limited to systems having a collision avoidance channel, as described elsewhere in this application. Instead, receivers as described in any of
25 the following applications may be configured to receive only a quiet channel: PCT application serial no. US2007/024225 titled "Active Signal Processing Personal Health Signal Receivers," and filed on November 19, 2007; WO 2006/116718; 60/866,581; 60/945,251; 60/956,694, 60/887,780 and 2006/116718; the disclosures of which applications are herein incorporated by reference.

30 To illustrate some of the foregoing concepts, in one aspect transmissions are broken into two channels. The first channel is used to broadcast the data. A one to two percent duty cycle is performed. Immunity to collisions is enhanced by randomizing the re-broadcast rate. The second channel is used to broadcast

a wakeup beacon. A one to two percent duty cycle is performed. The packet rate is in the 10 mSec range. The beacon transmissions are short, in the range of 100 to 200 uSec, when collisions are not of concern. The beacon and data channel carriers are generated from the same oscillator, so from the beacon the data carrier can be calculated. The receiver will turn on every 10 to 30 seconds for a 10 mSec duration. If a beacon is observed, the receiver will stay on to perform a full demodulation and decode. Otherwise, the receiver will return to sleep.

In certain aspects, the above system is modified to include a frequency dither to the packet interval dither.

In certain aspects, the above system is modified to include a longer duration transmission of 16 carrier cycles at 25 kHz (640 uS) with a 1 to 2 percent duty cycle. This complies with narrow band filter compatibility.

In certain aspects, the above system is modified to so that the modulation as BPSK on OOK on the lower channel.

In certain aspects, the above system is modified so that the modulation as OOK burst on the higher beacon channel.

In certain aspects, the above system is modified so that the use of simple multidimensional parity check codes for FEC (forward error correction).

3.0 Receiver

The signal receiver, sometimes referred to herein as the "receiver", generally includes any device or component capable of receiving the signal, e.g., conductively receiving a signal, via one or more specific communication channels.

One example of such a receiver is the personal receiver, *supra*. Another example of the receiver described in the in: PCT application serial no. PCT/US2006/016370 published as WO 2006/116718; PCT application serial No. PCT/2007/24225 published as WO 2008/063626; PCT application serial no. PCT/US2008/52845 published as US2008/052845; the disclosures of which applications are herein incorporated by reference.

Various aspects include mobile configurations of the receiver that are sized to be stably associated with a living subject in a manner that does not substantially impact movement of said living subject. In certain aspects, the

receiver has a small size. To illustrate, the receiver may occupy a volume of space of about five cm³ or fewer, such as about three cm³ or fewer, including about one cm³ or less. In certain aspects, the receiver has a chip size approximately ranging from ten mm² to two cm².

- 5 The receivers of interest may include both external and implantable receivers.

3.1 External Receivers

In external aspects, the receiver may be *ex vivo*, i.e., present outside of the body during use. External receiver may be configured in any convenient
10 manner. For example, in certain aspects the external receivers may be configured to be associated with a desirable skin location. As such, in aspects the external receivers may be configured to contact a topical skin location of a subject. Configurations of interest include, but are not limited to: patches, wrist bands, belts, etc. For instance, a watch or belt worn externally and equipped with
15 suitable receiving electrodes can be used as receivers in accordance with one aspect of the present invention. The receivers may provide a further communication path via which collected data can be extracted by a patient or health care practitioner. For instance, an implanted collector may include conventional RF circuitry operating, e.g., in the 405-MHz medical device band,
20 with which a practitioner can communicate. The practitioner may communicate, for example, via a data retrieval device, such as a wand, etc.

Where the receiver includes an external component, that component may have output devices for providing data, e.g., audio and/or visual feedback. Examples include audible alarms, LEDs, display screens, or the like. The
25 external component may also include an interface port via which the component can be connected to a computer for reading out data stored therein. By further example, the device may be positioned by a harness that is worn outside the body and has one or more electrodes that attach to the skin at different locations.

In certain external aspects, the receiver may be configured to be in contact
30 with or associated with a patient only temporarily, i.e., transiently. For example, the receiver may be associated / attached / in contact while the pill, ingestible event marker, etc., is actually being ingested.

To illustrate, the receiver may be configured as an external device having two finger electrodes or handgrips. Upon ingestion of a pharma-informatics

enabled pill, the patient touches the electrodes or grabs the handgrips to complete a conductive circuit with the receiver. Upon emission of the signal from the pill, e.g., when the pill dissolves in the stomach, the signal emitted by the identifier of the pill is picked up by the receiver.

5 In certain aspects, the external receiver may include miniaturized electronics which are integrated with the electrodes to form a bandage-style patch with electrodes that, when applied, contact the skin. The bandage-style may be removably attachable, e.g., via an adhesive layer or other construction. A battery and electronics may also be included. The bandage-style patch may be
10 configured to be positioned on a desirable target skin site of the subject, e.g., on the chest, back, side of the torso, etc. In these aspects, the bandage circuitry may be configured to receive signals from devices inside of the subject, e.g., from an identifier of a pharma-informatics enabled pharmaceutical composition, and then relay this information to an external processing device, e.g., a PDA,
15 smartphone, mobile phone, handheld device, computer, etc., as described in greater detail elsewhere. Bandage-style devices that may be readily adapted for use in the present systems include, but are not limited to, those described in U.S. Patent Nos. 6,315,719 and the like, the disclosures of which are herein incorporated by reference.

20

3.2 Implantable Receivers

 In certain aspects, the receiver may be an implantable, i.e., designed and / or configured for implantation into a subject. Implantation may be on a temporary basis or a permanent basis. In these aspects, the receiver is *in vivo* during use.
25 Generally, implantable receivers may maintain functionality when present in a physiological environment, including a high salt, high humidity environment found inside of a body, for various periods of time. Periods of time, for example, include a few minutes to eighty years. More specific time periods include, for example, one or more hours, one or more days, one or more weeks, one or more months,
30 and one or more years.

 For implantable aspects, the receiver may have any convenient shape, including but not limited to: capsule-shaped, disc-shaped, etc. Various receivers may have relatively small sizes. These small sizes may be achieved, for example, by incorporation of a rechargeable battery. In one aspect, the

rechargeable battery has a life span of about two weeks. In another aspect, the rechargeable battery automatically charges from various sources, e.g., coils in the patient's bed. The receiver may be configured to be placed in a number of different locations. Examples of locations include the abdomen, the small of the back, the shoulder, e.g., where implantable pulse generators are placed, etc.

In certain implantable aspects, the receiver is a standalone device, i.e., not physically connected to any other type of implantable device. In yet other aspects, the receiver may be physically coupled to a second implantable device, e.g., a device which serves as a platform for one or more physiological sensors.

Such a device may be a lead, such as a cardiovascular lead. To illustrate, the cardiovascular lead may include one or more distinct physiological sensors, e.g., where the lead is a multi-sensor lead (MSL). Implantable devices of interest further include, but are not limited to: implantable pulse generators, neurostimulator devices, implantable loop recorders, etc.

Receivers may further include a receiver element which serves to receive the signal of interest. The receiver may include a variety of different types of receiver elements, where the nature of the receiver element necessarily varies depending on the nature of the signal produced by the signal generation element. In certain aspects, the receiver may include one or more electrodes for detecting signal emitted by the signal generation element. To illustrate, the receiver device may be provided with two electrodes that are dispersed at a predetermined distance. The predetermined distance may allow the electrodes to detect a differential voltage. The distance may vary, and in certain aspects, ranges from about 0.1 to about five cm, such as from about 0.5 to about 2.5 cm, e.g., about one cm. In certain aspects, the first electrode is in contact with an electrically conductive body element, e.g., blood, and the second electrode is in contact with an electrically insulative body element relative to said conductive body element, e.g., adipose tissue (fat). In an alternative aspect, a receiver that utilizes a single electrode is employed. In certain aspects, the signal detection component may include one or more coils for detecting a signal emitted by the signal generation element. In certain aspects, the signal detection component includes an acoustic detection element for detecting signal emitted by the signal generation element.

A receiver may handle received data in various ways. In some aspects, the receiver simply retransmits the data to an external device, e.g., via

conventional RF communication. In other aspects, the receiver processes the received data to determine whether to take some action such as operating an effector that is under its control, activating a visible or audible alarm, transmitting a control signal to an effector located elsewhere in the body, or the like. In still
5 other aspects, the receiver stores the received data for subsequent retransmission to another device or for use in processing of subsequent data, e.g., detecting a change in some parameter over time. The receivers may perform any combination of these and / or other operations using received data.

In certain aspects, the data that are recorded on the data storage element
10 include at least one of, if not all of, time, date, and an identifier, e.g., global unique serial number, of each composition administered to a patient. The identifier may be the common name of the composition or a coded version thereof. The data recorded on the data storage element of the receiver may further include medical record information of the subject with which the receiver is
15 associated, e.g., identifying information, such as but not limited to name, age, treatment record, etc. In certain aspects, the data of interest include hemodynamic measurements. In certain aspects, the data of interest include cardiac tissue properties. In certain aspects, the data of interest include various physiologic metrics or parameters, e.g., pressure or volume measurements,
20 temperature, activity, respiration rate, pH, etc.

As summarized above, the receivers can be configured to have a very small size. In certain aspects, the desired functionality of the receiver is achieved with one or more integrated circuits and a battery. Aspects of the invention include receivers that have at least a receiver element, e.g., the form of one or
25 more electrodes (such as two spaced apart electrodes) and a power generation element, e.g., a battery, where the battery may be rechargeable, etc., as mentioned above. As such, in certain aspects the power generation element is converted to receive power wirelessly from an external location.

Additional elements that may be present in the receiver include, but are
30 not limited to: a signal demodulator, e.g., for decoding the signal emitted from the pharma-informatics enabled identifier; a signal transmitter, e.g., for sending a signal from the receiver to an external location; a data storage element, e.g., for storing data regarding a received signal, physiological parameter data, medical record data, etc.; a clock element, e.g., for associating a specific time with an

event, such as receipt of a signal; a pre-amplifier; a microprocessor, e.g., for coordinating one or more of the different functionalities of the receiver.

Aspects of implantable versions of the receiver will have a biologically compatible enclosure, two or more sense electrodes, a power source, which
5 could either be a primary cell or rechargeable battery, or one that is powered by broadcast inductively to a coil. The receiver may also have circuitry consisting of: a demodulator to decode the transmitted signal, some storage to record events, a clock, and a way to transmit outside the body. The clock and transmit functionality may, in certain aspects, be omitted. The transmitter could be an RF
10 link or conductive link to move information from local data storage to external data storage.

For the external receivers, aspects include structures that have electrodes opposed to the skin, the demodulator, storage, and power. The communication may be wireless or performed over one or more conductive media, e.g., wires,
15 optical fibers, etc.

In certain aspects, the same electrodes are used for receiving and transmitting signals. One mode may be a wristwatch which is conductively in contact with the body. To move the data from the implant to the wristwatch, currents may be sent out the pads and received by the wristwatch. There are a
20 number of RF techniques for facilitating transmission out of the body that may be employed, such as inductive protocols that use coils. Alternatively, electric fields may be employed, using insulated electrodes, for example.

In certain aspects, the components or functional blocks of the present receivers are present on integrated circuits, where the integrated circuits include
25 a number of distinct functional blocks, i.e., modules. Within a given receiver, at least some of, e.g., two or more, up to an including all of, the functional blocks may be present in a single integrated circuit in the receiver. By single integrated circuit is meant a single circuit structure that includes all of the different functional blocks. As such, the integrated circuit is a monolithic integrated circuit (also
30 known as IC, microcircuit, microchip, silicon chip, computer chip or chip) that is a miniaturized electronic circuit (which may include semiconductor devices, as well as passive components) that has been manufactured in the surface of a thin substrate of semiconductor material. The integrated circuits of certain aspects of the present invention may be hybrid integrated circuits, which are miniaturized

electronic circuits constructed of individual semiconductor devices, as well as passive components, bonded to a substrate or circuit board.

As reviewed above, the receivers exhibit reliable decoding of an encoded signal even in the presence of substantial noise and a low SNR. This functional aspect of the receivers of the invention may be provided via various schemes. Some such schemes include, for example, coherent demodulation, e.g., Costas loop demodulation, accurate low overhead iterative decoding, Forward Error Correction (FEC), and noise cancellation, e.g., as described in PCT application serial no. PCT/US2007/ 024225 titled "Active Signal Processing Personal Health Receivers," and filed on November 19, 2007; the disclosure of which is herein incorporated by reference. Other receivers of interest include, but are not limited to, those described in: WO 2006/116718; 60/866,581; 60/945,251; 60/956,694, 60/887,780 and WO 2006/116718; the disclosures of which are herein incorporated by reference.

Methods

Various aspects include, for example, transmitting, via an in vivo transmitter, an encoded signal; facilitating, via a transbody functionality module, communication of the signal; and receiving, via a receiver, the encoded signal, as heretofore described.

In one aspect, the method provides characteristics of the encoded signal, wherein the characteristics optimize power consumption to facilitate the receiver in at least one of the following: spending maximum time in an inactive mode, waking up quickly, and waking up during a period of high probability that the transmitter is present.

Further, various aspects may alternatively or optionally include such steps related to beacon functionality such as facilitating, via a beacon functionality module, communication of the encoded signal; facilitating, via a frequency hopping functionality module, communication of the encoded signal; and facilitating, via a collision avoidance functionality module, communication of the encoded signal. Some functionality may include, for example, providing beacon wakeup functionality; providing beacon signal functionality; generating a continuous wave, single frequency tone; providing a first frequency that is

different from a data signal which is at a second frequency; and modulating the encoded signal.

Still further, various aspects may alternatively or optionally include steps related to frequency hopping generating random frequency hops on a narrow
5 band transmitted signal.

Further yet, various aspects may alternatively or optionally include steps related to collision avoidance such as transmitting, via a first in vivo transmitter and a second in vivo transmitter, at different frequencies; modulating a duty cycle; retransmitting randomly; and spreading across a frequency spectrum.
10 Modulating a duty cycle may include dithering the duty cycle and spreading among frequencies. Transmitting at different frequencies may comprise providing multiple band pass filtering by different devices wherein respective signals associated with different frequencies are filtered by respective band pass
fillers.

Articles

Various aspects may include an article, comprising, for example, a storage medium having instructions, that when executed by a computing platform, result in execution of a method of providing transbody communications employing
20 communication channels. The method, for example, may comprise various steps/combinations of steps such as transmitting, via an in vivo transmitter, an encoded signal; facilitating, via a transbody functionality module, communication of the signal; and receiving, via a receiver, the encoded signal. Various other steps are illustrated heretofore.

ADDITIONAL SYSTEM ASPECTS

In certain aspects, the receivers are part of a body associated system or network of sensors, receivers, and optionally other devices, both internal and
30 external, which provide a variety of different types of information that is ultimately collected and processed by a processor, such as an external processor, which then can provide contextual data about a patient as output. For example that sensor may be a member of an in-body network of devices which can provide an output that includes data about pill ingestion, one or more physiological sensed

parameters, implantable device operation, etc., to an external collector of the data. The external collector, e.g., in the form of a health care network server, etc., of the data then combines this receiver provided data with additional relevant data about the patient, e.g., weight, weather, medical record data, etc., and may
5 process this disparate data to provide highly specific and contextual patient specific data.

Systems of the subject invention include, in certain aspects, a receiver and one or more pharma-informatics enabled active agent containing compositions. The pharma-informatics enabled pharmaceutical composition is an active agent-
10 containing composition having an identifier stably associated therewith. In certain aspects, the compositions are disrupted upon administration to a subject. As such, in certain aspects, the compositions are physically broken, e.g., dissolved, degraded, eroded, etc., following delivery to a body, e.g., via ingestion, injection, etc. The compositions of these aspects are distinguished from devices that are
15 configured to be ingested and survive transit through the gastrointestinal tract substantially, if not completely, intact. The compositions include an identifier and an active agent/carrier component, where both of these components are present in a pharmaceutically acceptable vehicle.

The identifiers of the compositions may vary depending on the particular
20 aspect and intended application of the composition so long as they are activated (i.e., turned on) upon contact with a target physiological location, e.g., stomach. As such, the identifier may be an identifier that emits a signal when it contacts a target body (i.e., physiological) site. In addition or alternatively, the identifier may be an identifier that emits a signal when interrogated after it has been activated.
25 The identifier may be any component or device that is capable of providing a detectable signal following activation, e.g., upon contact with the target site. In certain aspects, the identifier emits a signal once the composition comes into contact with a physiological target site, e.g., as summarized above. For example, a patient may ingest a pill that, upon contact with the stomach fluids, generates a
30 detectable signal.

The compositions include an active agent/carrier component. By "active agent/carrier component" is meant a composition, which may be a solid or fluid (e.g., liquid), which has an amount of active agent, e.g., a dosage, present in a

pharmaceutically acceptable carrier. The active agent/carrier component may be referred to as a "dosage formulation."

"Active agent" includes any compound or mixture of compounds which produces a physiological result, e.g., a beneficial or useful result, upon contact with a living organism, e.g., a mammal, such as a human. Active agents are distinguishable from such components as vehicles, carriers, diluents, lubricants, binders and other formulating aids, and encapsulating or otherwise protective components. The active agent may be any molecule, as well as binding portion or fragment thereof, that is capable of modulating a biological process in a living subject. In certain aspects, the active agent may be a substance used in the diagnosis, treatment, or prevention of a disease or as a component of a medication. In certain aspects, the active agent may be a chemical substance, such as a narcotic or hallucinogen, which affects the central nervous system and causes changes in behavior.

The active agent (i.e., drug) is capable of interacting with a target in a living subject. The target may be a number of different types of naturally occurring structures, where targets of interest include both intracellular and extracellular targets. Such targets may be proteins, phospholipids, nucleic acids and the like, where proteins are of particular interest. Specific proteinaceous targets of interest include, without limitation, enzymes, e.g. kinases, phosphatases, reductases, cyclooxygenases, proteases and the like, targets comprising domains involved in protein-protein interactions, such as the SH2, SH3, PTB and PDZ domains, structural proteins, e.g. actin, tubulin, etc., membrane receptors, immunoglobulins, e.g. IgE, cell adhesion receptors, such as integrins, etc, ion channels, transmembrane pumps, transcription factors, signaling proteins, and the like.

The active agent (i.e., drug) may include one or more functional groups necessary for structural interaction with the target, e.g., groups necessary for hydrophobic, hydrophilic, electrostatic or even covalent interactions, depending on the particular drug and its intended target. Where the target is a protein, the drug moiety may include functional groups necessary for structural interaction with proteins, such as hydrogen bonding, hydrophobic-hydrophobic interactions, electrostatic interactions, etc., and may include at least an amine, amide,

sulfhydryl, carbonyl, hydroxyl or carboxyl group, such as at least two of the functional chemical groups.

Drugs of interest may include cyclical carbon or heterocyclic structures and/or aromatic or polyaromatic structures substituted with one or more of the
5 above functional groups. Also of interest as drug moieties are structures found among biomolecules, including peptides, saccharides, fatty acids, steroids, purines, pyrimidines, derivatives, structural analogs or combinations thereof. Such compounds may be screened to identify those of interest, where a variety of different screening protocols are known in the art.

10 The drugs may be derived from a naturally occurring or synthetic compound that may be obtained from a wide variety of sources, including libraries of synthetic or natural compounds. For example, numerous means are available for random and directed synthesis of a wide variety of organic compounds and biomolecules, including the preparation of randomized
15 oligonucleotides and oligopeptides. Alternatively, libraries of natural compounds in the form of bacterial, fungal, plant and animal extracts are available or readily produced. Additionally, natural or synthetically produced libraries and compounds are readily modified through conventional chemical, physical and biochemical means, and may be used to produce combinatorial libraries. Known
20 pharmacological agents may be subjected to directed or random chemical modifications, such as acylation, alkylation, esterification, amidification, etc. to produce structural analogs.

As such, the drug may be obtained from a library of naturally occurring or synthetic molecules, including a library of compounds produced through
25 combinatorial means, i.e., a compound diversity combinatorial library. When obtained from such libraries, the drug moiety employed will have demonstrated some desirable activity in an appropriate screening assay for the activity. Combinatorial libraries, as well as methods for producing and screening such libraries, are known in the art and described in: 5,741,713; 5,734,018; 5,731,423;
30 5,721,099; 5,708,153; 5,698,673; 5,688,997; 5,688,696; 5,684,711; 5,641,862; 5,639,603; 5,593,853; 5,574,656; 5,571,698; 5,565,324; 5,549,974; 5,545,568; 5,541,061; 5,525,735; 5,463,564; 5,440,016; 5,438,119; 5,223,409, the disclosures of which are herein incorporated by reference.

Broad categories of active agents of interest include, but are not limited to: cardiovascular agents; pain-relief agents, e.g., analgesics, anesthetics, anti-inflammatory agents, etc.; nerve-acting agents; chemotherapeutic (e.g., anti-neoplastic) agents; etc.

5 As summarized above, the compositions of the invention further include a pharmaceutically acceptable vehicle (i.e., carrier). Common carriers and excipients, such as corn starch or gelatin, lactose, dextrose, sucrose, microcrystalline cellulose, kaolin, mannitol, dicalcium phosphate, sodium chloride, and alginic acid are of interest. Disintegrators commonly used in the formulations
10 of the invention include croscarmellose, microcrystalline cellulose, corn starch, sodium starch glycolate and alginic acid.

 Further details about aspects of pharma-informatics enabled pharmaceutical compositions may be found in pending PCT application PCT/US2006/16370 titled "Pharma-Informatics System" and filed on April 28,
15 2006; as well as United States Provisional Application Serial Nos. 60/807,060 titled "Acoustic Pharma-Informatics System" filed on July 11, 2006; 60/862,925 titled "Controlled Activation Pharma-Informatics System," filed on October 25, 2006; and 60/866,581 titled "In-Vivo Transmission Decoder," filed on November 21, 2006; the disclosures of which are herein incorporated by reference.

20 In certain aspects the systems include an external device which is distinct from the receiver (which may be implanted or topically applied in certain aspects), where this external device provides a number of functionalities. Such an apparatus can include the capacity to provide feedback and appropriate clinical regulation to the patient. Such a device can take any of a number of forms. By
25 example, the device can be configured to sit on the bed next to the patient, e.g., a bedside monitor. Other formats include, but are not limited to, PDAs, smart phones, home computers, etc. The device can read out the information described in more detail in other sections of the subject patent application, both from pharmaceutical ingestion reporting and from physiological sensing devices, such
30 as is produced internally by a pacemaker device or a dedicated implant for detection of the pill. The purpose of the external apparatus is to get the data out of the patient and into an external device. One feature of the external apparatus is its ability to provide pharmacologic and physiologic information in a form that

can be transmitted through a transmission medium, such as a telephone line, to a remote location such as a clinician or to a central monitoring agency.

Systems of the invention enable a dynamic feedback and treatment loop of tracking medication timing and levels, measuring the response to therapy, and
5 recommending altered dosing based on the physiology and molecular profiles of individual patients. For example, a symptomatic heart failure patient takes multiple drugs daily, primarily with the goal of reducing the heart's workload and improving patient quality of life. Mainstays of therapy include angiotensin
10 converting enzyme (ACE) inhibitors, β -blockers and diuretics. For pharmaceutical therapy to be effective, it is vital that patients adhere to their prescribed regimen, taking the required dose at the appropriate time. Multiple studies in the clinical literature demonstrate that more than 50% of Class II and III heart failure patients are not receiving guideline-recommended therapy, and, of those who are titrated appropriately, only 40-60% adhere to the regimen. With the
15 subject systems, heart failure patients can be monitored for patient adherence to therapy, and adherence performance can be linked to key physiologic measurements, to facilitate the optimization of therapy by physicians.

In certain aspects, the systems of the invention may be employed to obtain an aggregate of information that includes sensor data and administration data.
20 For example, one can combine the heart rate, the respiration rate, multi-axis acceleration data, something about the fluid status, and something about temperature, and derive indices that will inform about the total activity of the subject, that can be used to generate a physiological index, such as an activity index. For instance, when there is a rise in temperature, heart rate goes up a bit,
25 and respiration speeds up, which may be employed as an indication that the person is being active. By calibrating this, the amount of calories the person is burning at that instant could be determined. In another example, a particular rhythmic set of pulses or multi-axis acceleration data can indicate that a person is walking up a set of stairs, and from that one can infer how much energy they are
30 using. In another aspect, body fat measurement (e.g. from impedance data) could be combined with an activity index generated from a combination of measured biomarkers to generate a physiological index useful for management of a weight loss or cardiovascular health program. This information can be

combined with cardiac performance indicators to get a good picture of overall health, which can be combined with pharmaceutical therapy administration data. In another aspect, one might find for example that a particular pharmaceutical correlates with a small increase in body temperature, or a change in the electrocardiogram. One can develop a pharmacodynamic model for the metabolism of the drug, and use the information from the receiver to essentially fit the free parameters in that model to give much more accurate estimation of the levels actually present in the serum of the subject. This information could be fed back to dosing regimes. In another aspect, one can combine information from a sensor that measures uterine contractions (e.g. with a strain gauge) and that also monitors fetal heart rate, for use as a high-risk pregnancy monitor.

In certain aspects, the subject specific information that is collected using the systems of the invention may be transmitted to a location where it is combined with data from one or more additional individuals to provide a collection of data which is a composite of data collected from 2 or more, e.g., 5 or more, 10 or more, 25 or more, 50 or more, 100 or more, 1000 or more, etc., individuals. The composite data can then be manipulated, e.g., categorized according to different criteria, and made available to one or more different types of groups, e.g., patient groups, health care practitioner groups, etc., where the manipulation of data may be such as to limit the access of any given group to the type of data that group can access. For example, data can be collected from 100 different individuals that are suffering from the same condition and taking the same medication. The data can be processed and employed to develop easy to follow displays regarding patient compliance with a pharmaceutical dosage regimen and general health. Patient members of the group can access this information and see how their compliance matches with other patient members of the group, and whether they are enjoying the benefits that others are experiencing. In yet another aspect, doctors can also be granted access to a manipulation of the composite data to see how their patients are matching up with patients of other doctors, and obtain useful information on how real patients respond to a given therapeutic treatment regimen. Additional functionalities can be provided to the groups given access to the composite data, where such functionalities may include, but are not limited to: ability to annotate data, chat functionalities, security privileges, etc.

COMPUTER READABLE MEDIA & PROGRAMMING

In certain aspects, the system further includes an element for storing data,
5 i.e., a data storage element, where this element is present on an external device,
such as a bedside monitor, PDA, smart phone, etc. Typically, the data storage
element is a computer readable medium. The term "computer readable medium"
as used herein refers to any storage or transmission medium that participates in
providing instructions and/or data to a computer for execution and/or processing.
10 Examples of storage media include floppy disks, magnetic tape, CD-ROM, a hard
disk drive, a ROM or integrated circuit, a magneto-optical disk, or a computer
readable card such as a PCMCIA card and the like, whether or not such devices
are internal or external to the computer. A file containing information may be
"stored" on computer readable medium, where "storing" means recording
15 information such that it is accessible and retrievable at a later date by a
computer. With respect to computer readable media, "permanent memory" refers
to memory that is permanent. Permanent memory is not erased by termination of
the electrical supply to a computer or processor. Computer hard-drive ROM (i.e.
ROM not used as virtual memory), CD-ROM, floppy disk and DVD are all
20 examples of permanent memory. Random Access Memory (RAM) is an example
of non-permanent memory. A file in permanent memory may be editable and re-
writable.

The invention also provides computer executable instructions (i.e.,
programming) for performing the above methods. The computer executable
25 instructions are present on a computer readable medium. Accordingly, the
invention provides a computer readable medium containing programming for use
in detecting and processing a signal generated by a composition of the invention,
e.g., as reviewed above.

As such, in certain aspects the systems include one or more of: a data
30 storage element, a data processing element, a data display element, data
transmission element, a notification mechanism, and a user interface. These
additional elements may be incorporated into the receiver and/or present on an
external device, e.g., a device configured for processing data and making

decisions, forwarding data to a remote location which provides such activities, etc.

The above described systems are reviewed in terms of communication between an identifier on a pharmaceutical composition and a receiver. However, 5 the systems are not so limited. In a broader sense, the systems are composed of two or more different modules that communicate with each other, e.g., using the transmitter/receiver functionalities as reviewed above, e.g., using the monopole transmitter (e.g., antenna) structures as described above. As such, the above identifier elements may be incorporated into any of a plurality of different devices, 10 e.g., to provide a communications system between two self-powered devices in the body, where the self-powered devices may be sensors, data receivers and storage elements, effectors, etc. In an exemplary system, one of these devices may be a sensor and the other may be a communication hub for communication to the outside world. This inventive aspect may take a number of forms. There 15 can be many sensors, many senders and one receiver. They can be transceivers so both of these can take turns sending and receiving according to known communication protocols. In certain aspects, the means of communication between the two or more individual devices is the mono polar system, e.g., as described above. In these aspects, each of these senders may be configured to 20 take turns sending a high frequency signal into the body using a monopole pulling charge into and out of the body which is a large capacitor and a conductor. The receiver, a monopole receiver is detecting at that frequency the charge going into and out of the body and decoding an encrypted signal such as an amplitude modulated signal or frequency modulated signal. This aspect of the present 25 invention has broad uses. For example, multiple sensors can be placed and implanted on various parts of the body that measure position or acceleration. Without having wires connecting to a central hub, they can communicate that information through a communication medium.

In the methods of the subject invention in which the in vivo transmitter is a 30 pharma-informatics enabled composition, an effective amount of a composition of the invention is administered to a subject in need of the active agent present in the composition, where "effective amount" means a dosage sufficient to produce the desired result, e.g. an improvement in a disease condition or the symptoms associated therewith, the accomplishment of a desired physiological change, etc.

The amount that is administered may also be viewed as a therapeutically effective amount. A "therapeutically effective amount" means the amount that, when administered to a subject for treating a disease, is sufficient to effect treatment for that disease.

5 The composition may be administered to the subject using any convenient means capable of producing the desired result, where the administration route depends, at least in part, on the particular format of the composition, e.g., as reviewed above. As reviewed above, the compositions can be formatted into a variety of formulations for therapeutic administration, including but not limited to
10 solid, semi solid or liquid, such as tablets, capsules, powders, granules, ointments, solutions, suppositories and injections. As such, administration of the compositions can be achieved in various ways, including, but not limited to: oral, buccal, rectal, parenteral, intraperitoneal, intradermal, transdermal, intracheal, etc., administration. In pharmaceutical dosage forms, a given composition may
15 be administered alone or in combination with other pharmaceutically active compounds, e.g., which may also be compositions having signal generation elements stably associated therewith.

 The subject methods find use in the treatment of a variety of different conditions, including disease conditions. The specific disease conditions treatable
20 by with the subject compositions are as varied as the types of active agents that can be present in the subject compositions. Thus, disease conditions include, but are not limited to: cardiovascular diseases, cellular proliferative diseases, such as neoplastic diseases, autoimmune diseases, hormonal abnormality diseases, infectious diseases, pain management, and the like.

25 By treatment is meant at least an amelioration of the symptoms associated with the disease condition afflicting the subject, where amelioration is used in a broad sense to refer to at least a reduction in the magnitude of a parameter, e.g. symptom, associated with the pathological condition being treated. As such, treatment also includes situations where the pathological condition, or at least
30 symptoms associated therewith, are completely inhibited, e.g. prevented from happening, or stopped, e.g. terminated, such that the subject no longer suffers from the pathological condition, or at least the symptoms that characterize the pathological condition. Accordingly, "treating" or "treatment" of a disease includes preventing the disease from occurring in an animal that may be predisposed to

the disease but does not yet experience or exhibit symptoms of the disease (prophylactic treatment), inhibiting the disease (slowing or arresting its development), providing relief from the symptoms or side-effects of the disease (including palliative treatment), and relieving the disease (causing regression of the disease). For the purposes of this invention, a "disease" includes pain.

A variety of subjects are treatable according to the present methods. Generally such subjects are "mammals" or "mammalian," where these terms are used broadly to describe organisms which are within the class mammalia, including the orders carnivore (e.g., dogs and cats), rodentia (e.g., mice, guinea pigs, and rats), and primates (e.g., humans, chimpanzees, and monkeys). In representative aspects, the subjects will be humans.

In certain aspects, the subject methods, as described above, are methods of managing a disease condition, e.g., over an extended period of time, such as 1 week or longer, 1 month or longer, 6 months or longer, 1 year or longer, 2 years or longer, 5 years or longer, etc. The subject methods may be employed in conjunction with one or more additional disease management protocols, e.g., electrostimulation based protocols in cardiovascular disease management, such as pacing protocols, cardiac resynchronization protocols, etc; lifestyle, such a diet and/or exercise regimens for a variety of different disease conditions; etc.

In certain aspects, the methods include modulating a therapeutic regimen based data obtained from the compositions. For example, data may be obtained which includes information about patient compliance with a prescribed therapeutic regimen. This data, with or without additional physiological data, e.g., obtained using one or more sensors, such as the sensor devices described above, may be employed, e.g., with appropriate decision tools as desired, to make determinations of whether a given treatment regimen should be maintained or modified in some way, e.g., by modification of a medication regimen and/or implant activity regimen. As such, methods of invention include methods in which a therapeutic regimen is modified based on signals obtained from the composition(s).

In certain aspects, also provided are methods of determining the history of a composition of the invention, where the composition includes an active agent, an identifier element and a pharmaceutically acceptable carrier. In certain aspects where the identifier emits a signal in response to an interrogation, the

identifier is interrogate, e.g., by a wand or other suitable interrogation device, to obtain a signal. The obtained signal is then employed to determine historical information about the composition, e.g., source, chain of custody, etc.

In yet other aspects where the identifier is one that survives digestion, the methods generally include obtaining the signal generation element of the composition, e.g., by retrieving it from a subject that has ingested the composition, and then determining the history of the composition from obtained signal generation element. For example, where the signal generation element includes an engraved identifier, e.g., barcode or other type of identifier, the engraved identifier may be retrieved from a subject that has ingested the composition and then read to identify at least some aspect of the history of the composition, such as last known purchaser, additional purchasers in the chain of custody of the composition, manufacturer, handling history, etc. In certain aspects, this determining step may include accessing a database or analogous compilation of stored history for the composition.

UTILITY

Medical aspects of the present invention provide the clinician an important new tool in their therapeutic armamentarium: automatic detection and identification of pharmaceutical agents actually delivered into the body. The applications of this new information device and system are multi-fold. Applications include, but are not limited to: (1) monitoring patient compliance with prescribed therapeutic regimens; (2) tailoring therapeutic regimens based on patient compliance; (3) monitoring patient compliance in clinical trials; (4) monitoring usage of controlled substances; and the like. Each of these different illustrative applications is reviewed in greater detail below in copending PCT Application Serial No. PCT/US2006/ 016370; the disclosure of which is herein incorporated by reference. Additional applications in which the subject receivers find use include, but are not limited to: United States provisional Application Serial Nos: 60/887,780 titled "Receivers For Pharma-Informatics Systems," and filed on February 1, 2007; 60/956,694 titled "Personal Health Receivers," and filed on August 18, 2007 and 60/949,223 titled "Ingestible Event Marker," and

filed on July 11, 2007, the disclosures of which applications are incorporated herein by reference.

KITS

5

Also provided are kits for practicing the subject methods. Kits may include one or more receivers of the invention, as described above. In addition, the kits may include one or more dosage compositions, e.g., pharma-informatics enabled dosage compositions. The dosage amount of the one or more pharmacological agents provided in a kit may be sufficient for a single application or for multiple applications. Accordingly, in certain aspects of the subject kits a single dosage amount of a pharmacological agent is present and in certain other aspects multiple dosage amounts of a pharmacological agent may be present in a kit. In those aspects having multiple dosage amounts of pharmacological agent, such may be packaged in a single container, e.g., a single tube, bottle, vial, and the like, or one or more dosage amounts may be individually packaged such that certain kits may have more than one container of a pharmacological agent.

Suitable means for delivering one or more pharmacological agents to a subject may also be provided in a subject kit. The particular delivery means provided in a kit is dictated by the particular pharmacological agent employed, as describe above, e.g., the particular form of the agent such as whether the pharmacological agent is formulated into preparations in solid, semi solid, liquid or gaseous forms, such as tablets, capsules, powders, granules, ointments, solutions, suppositories, injections, inhalants and aerosols, and the like, and the particular mode of administration of the agent, e.g., whether oral, buccal, rectal, parenteral, intraperitoneal, intradermal, transdermal, intracheal, etc. Accordingly, certain systems may include a suppository applicator, syringe, I.V. bag and tubing, electrode, etc.

In certain aspects, the kits may also include an external monitor device, e.g., as described above, which may provide for communication with a remote location, e.g., a doctor's office, a central facility etc., which obtains and processes data obtained about the usage of the composition.

In certain aspects, the kits may include a smart parenteral delivery system that provides specific identification and detection of parenteral beneficial agents

or beneficial agents taken into the body through other methods, for example, through the use of a syringe, inhaler, or other device that administers medicine, such as described in copending application serial no. 60/819,750; the disclosure of which is herein incorporated by reference.

5 The subject kits may also include instructions for how to practice the subject methods using the components of the kit. The instructions may be recorded on a suitable recording medium or substrate. For example, the instructions may be printed on a substrate, such as paper or plastic, etc. As such, the instructions may be present in the kits as a package insert, in the labeling of
10 the container of the kit or components thereof (i.e., associated with the packaging or sub-packaging) etc. In other aspects, the instructions are present as an electronic storage data file present on a suitable computer readable storage medium, e.g. CD-ROM, diskette, etc. In yet other aspects, the actual instructions are not present in the kit, but means for obtaining the instructions from a remote
15 source, e.g. via the internet, are provided. An example of this aspect is a kit that includes a web address where the instructions can be viewed and/or from which the instructions can be downloaded. As with the instructions, this means for obtaining the instructions is recorded on a suitable substrate.

 Some or all components of the subject kits may be packaged in suitable
20 packaging to maintain sterility. In many aspects of the subject kits, the components of the kit are packaged in a kit containment element to make a single, easily handled unit, where the kit containment element, e.g., box or analogous structure, may or may not be an airtight container, e.g., to further preserve the sterility of some or all of the components of the kit.

25

30

It is to be understood that this invention is not limited to particular aspects described, as such may vary. It is also to be understood that the terminology used herein is for the purpose of describing particular aspects only, and is not intended to be limiting, since the scope of the present invention will be limited
5 only by the appended claims.

Where a range of values is provided, it is understood that each intervening value, to the tenth of the unit of the lower limit unless the context clearly dictates otherwise, between the upper and lower limit of that range and any other stated
10 or intervening value in that stated range, is encompassed within the invention. The upper and lower limits of these smaller ranges may independently be included in the smaller ranges and are also encompassed within the invention, subject to any specifically excluded limit in the stated range. Where the stated range includes one or both of the limits, ranges excluding either or both of those
15 included limits are also included in the invention.

Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. Although any methods and materials similar
20 or equivalent to those described herein can also be used in the practice or testing of the present invention, representative illustrative methods and materials are now described.

All publications and patents cited in this specification are herein
25 incorporated by reference as if each individual publication or patent were specifically and individually indicated to be incorporated by reference and are incorporated herein by reference to disclose and describe the methods and/or materials in connection with which the publications are cited. The citation of any publication is for its disclosure prior to the filing date and should not be construed
30 as an admission that the present invention is not entitled to antedate such publication by virtue of prior invention. Further, the dates of publication provided may be different from the actual publication dates which may need to be independently confirmed.

It is noted that, as used herein and in the appended claims, the singular forms "a", "an", and "the" include plural referents unless the context clearly dictates otherwise. It is further noted that the claims may be drafted to exclude any optional element. As such, this statement is intended to serve as antecedent
5 basis for use of such exclusive terminology as "solely," "only" and the like in connection with the recitation of claim elements, or use of a "negative" limitation.

As will be apparent to those of skill in the art upon reading this disclosure,
10 each of the individual aspects described and illustrated herein has discrete components and features which may be readily separated from or combined with the features of any of the other several aspects without departing from the scope or spirit of the present invention. Any recited method can be carried out in the order of events recited or in any other order which is logically possible.

15

Although the foregoing invention has been described in some detail by way of illustration and example for purposes of clarity of understanding, it is
20 readily apparent to those of ordinary skill in the art in light of the teachings of this invention that certain changes and modifications may be made thereto without departing from the spirit or scope of the appended claims.

25 Accordingly, the preceding merely illustrates the principles of the invention. It will be appreciated that those skilled in the art will be able to devise various arrangements which, although not explicitly described or shown herein, embody the principles of the invention and are included within its spirit and scope. Furthermore, all examples and conditional language recited herein are principally
30 intended to aid the reader in understanding the principles of the invention and the concepts contributed by the inventors to furthering the art, and are to be construed as being without limitation to such specifically recited examples and conditions. Moreover, all statements herein reciting principles, aspects, and aspects of the invention as well as specific examples thereof, are intended to

encompass both structural and functional equivalents thereof. Additionally, it is intended that such equivalents include both currently known equivalents and equivalents developed in the future, i.e., any elements developed that perform the same function, regardless of structure. The scope of the present invention, 5 therefore, is not intended to be limited to the exemplary aspects shown and described herein. Rather, the scope and spirit of present invention is embodied by the appended claims.

WHAT IS CLAIMED IS:

1. A system comprising:
 - an in vivo transmitter to transmit an encoded signal;
 - 5 a transbody functionality module to facilitate communication of the encoded signal; and
 - a receiver to receive the encoded signal;
 - wherein the receiver comprises a wake up module to periodically wake up the receiver from a sleep mode to a first energy consumption mode to detect the
 - 10 transmitted encoded signal during a first period, wherein when the receiver detects the transmitted encoded signal during the first period, the receiver transitions to a second energy consumption mode that is greater than the first energy consumption mode, and wherein when the receiver does not detect the transmitted encoded signal during the first period, the receiver transitions back to
 - 15 the sleep mode.
2. The system of claim 1, wherein the transbody functionality module is selected from the group consisting essentially of a beacon functionality module, a frequency hopping functionality module, and a collision avoidance functionality
- 20 module.
3. The system of claim 2, wherein the beacon functionality module comprises at least one element selected from the group consisting essentially of:
 - a beacon wakeup module to provide beacon wakeup functionality;
 - 25 a beacon signal module to provide beacon signal functionality;
 - a wave / frequency module to provide a continuous wave and a single frequency tone;
 - a multiple frequency module to provide multiple frequencies; and
 - a modulated signal module to provide at least one modulated
 - 30 encoded signal.
4. The system of claim 3, wherein a frequency ratio of a beacon and data channel is invariant to frequency error in an ingestible event marker system to provide additional assurance of detection of the encoded signal.

5. The system of claim 3, wherein the frequency hopping functionality module comprises a random module to provide random frequency hops on a narrow band transmitted signal.

6. The system of claim 3, wherein the collision avoidance functionality module comprises at least one element selected from the group consisting essentially of:

5 a transmitter module to provide a first in vivo transmitter transmitting at a first frequency and a second in vivo transmitter transmitting at a second frequency module;

a duty cycle modulation module to provide duty cycle modulation functionality;

10 a retransmit randomization module to provide random retransmittals; and
a spread spectrum module to provide spread spectrum functionality.

7. The system of claim 6, wherein the duty cycle modulation module includes a dithering module to dither a duty cycle and frequency spread module to spread the transmissions among multiple frequencies.

15

8. The system of claim 6, wherein the transmitter modules comprises a multiple band pass filter module to provide multiple band pass filtering by different devices wherein respective encoded signals are filtered by respective band pass filters.

20

9. A method comprising:

transmitting, via an in vivo transmitter, an encoded signal;

facilitating, via a transbody functionality module, communication of the signal; and

25 receiving, via a receiver, the encoded signal;

wherein receiving the encoded signal by the receiver further comprises:

30 periodically waking up the receiver from a sleep mode to a first energy consumption mode to detect the transmitted encoded signal during a first period, wherein when the receiver detects the transmitted encoded signal during the first period, transitioning the receiver to a second energy consumption mode that is greater than the first energy consumption mode, and wherein when the receiver does not detect the transmitted encoded signal during the first period, transitioning the receiver back to the sleep mode.

10. The method of claim 9, further comprising:

providing characteristics of the encoded signal, wherein the characteristics optimize power consumption to facilitate the receiver in at least one of the following: spending maximum time in an inactive mode, waking up quickly, and waking up during a period of high probability that the transmitter is present.

11. The method of claim 9, wherein the facilitating, via a transbody functionality module, communication of the signal comprises at least one of:

facilitating, via a beacon functionality module, communication of the encoded signal;

5 facilitating, via a frequency hopping functionality module, communication of the encoded signal; and

facilitating, via a collision avoidance functionality module, communication of the encoded signal.

10 12. The method of claim 11, wherein the facilitating, via a beacon functionality module communication of the signal comprises at least one of:

providing beacon wakeup functionality;

providing beacon signal functionality;

generating a continuous wave, single frequency tone;

15 providing a first frequency that is different from a data signal which is at a second frequency; and

modulating the encoded signal.

13. The method of claim 11, wherein the facilitating, via a frequency hopping functionality module, communication of the encoded signal comprises generating random frequency hops on a narrow band transmitted signal.

14. The method of claim 11, wherein the facilitating, via a collision avoidance functionality module, communication of the encoded signal comprises at least one of:

transmitting, via a first in vivo transmitter at a first frequency and transmitting, via a second in vivo transmitter, at a second frequency;

modulating a duty cycle;

retransmitting randomly; and

30 spreading across a frequency spectrum.

15. The method of claim 14, wherein the modulating a duty cycle includes dithering the duty cycle and spreading among frequencies.

16. The method of claim 14, wherein the transmitting at different frequencies comprises providing multiple band pass filtering by different devices wherein respective encoded signals are filtered by respective band pass filters.

5 17. The method of claim 9 in a form of a machine-readable medium embodying a set of instructions that, when executed by a machine, causes the machine to perform the method of claim 8.

18. An article, comprising:

10 a storage medium having instructions, that when executed by a computing platform, result in execution of a method of providing transbody communications employing communication channels in a living body, the method comprising:

transmitting, via an in vivo transmitter, an encoded signal;

facilitating, via a transbody functionality module, communication of

15 the signal; and

receiving, via a receiver, the encoded signal

wherein receiving the encoded signal by the receiver further comprises:

periodically waking up the receiver from a sleep mode to a

20 first energy consumption mode to detect the transmitted encoded signal during a first period, wherein when the receiver detects the transmitted encoded signal during the first period, transitioning the receiver to a second energy consumption mode that is greater than the first energy consumption mode, and wherein when the receiver does not detect the
25 transmitted encoded signal during the first period, transitioning the receiver back to the sleep mode.

19. The article of claim 18, further comprising:

providing characteristics of the encoded signal, wherein the characteristics

30 optimize power consumption to facilitate the receiver in at least one of the following: spending maximum time in an inactive mode, waking up quickly, and waking up during a period of high probability that the transmitter is present.

20. The article of claim 18, wherein the facilitating, via a transbody functionality module, communication of the signal comprises at least one of:

facilitating, via a beacon functionality module, communication of the encoded signal;

5 facilitating, via a frequency hopping functionality module, communication of the encoded signal; and

facilitating, via a collision avoidance functionality module, communication of the encoded signal.

10 21. The system of claim 1, wherein the transmitter transmits the encoded signal periodically over a second transmit signal repetition period, wherein the first period is longer than the second transmit signal repetition period such that the receiver detects at least one transmitted encoded signal during the first period.

15 22. The system of claim 1, wherein the transmitter transmits the encoded signal periodically over a second transmit signal repetition period, wherein the first period is shorter than the second transmit signal repetition period.

20 23. The method of claim 9, further comprising transmitting by the transmitter transmits the encoded signal periodically over a second transmit signal repetition period, wherein the first period is longer than the second transmit signal repetition period such that the receiver detects at least one transmitted
25 encoded signal during the first period.

24. The method of claim 9, further comprising transmitting by the transmitter the encoded signal periodically over a second transmit signal repetition period, wherein the first period is shorter than the second transmit
30 signal repetition period.

25. The article of claim 18, wherein the method further comprises transmitting by the transmitter transmits the encoded signal periodically over a second transmit signal repetition period, wherein the first period is longer than the

second transmit signal repetition period such that the receiver detects at least one transmitted encoded signal during the first period.

26. The article of claim 18, wherein the method further comprises
5 transmitting by the transmitter the encoded signal periodically over a second transmit signal repetition period, wherein the first period is shorter than the second transmit signal repetition period.